

User's Guide
to
the PARI library
(version 2.17.3)

The PARI Group

Institut de Mathématiques de Bordeaux, UMR 5251 du CNRS.
Université de Bordeaux, 351 Cours de la Libération
F-33405 TALENCE Cedex, FRANCE
e-mail: `pari@math.u-bordeaux.fr`

Home Page:
<https://pari.math.u-bordeaux.fr/>

Copyright © 2000–2024 The PARI Group

Permission is granted to make and distribute verbatim copies of this manual provided the copyright notice and this permission notice are preserved on all copies.

Permission is granted to copy and distribute modified versions, or translations, of this manual under the conditions for verbatim copying, provided also that the entire resulting derived work is distributed under the terms of a permission notice identical to this one.

PARI/GP is Copyright © 2000–2024 The PARI Group

PARI/GP is free software; you can redistribute it and/or modify it under the terms of the GNU General Public License as published by the Free Software Foundation. It is distributed in the hope that it will be useful, but WITHOUT ANY WARRANTY WHATSOEVER.

Table of Contents

Chapter 4: Programming PARI in Library Mode	13
4.1 Introduction: initializations, universal objects	13
4.2 Important technical notes	14
4.2.1 Backward compatibility	14
4.2.2 Types	14
4.2.3 Type recursivity	15
4.2.4 Variations on basic functions	15
4.2.5 Portability: 32-bit / 64-bit architectures	16
4.2.6 Using <code>malloc</code> / <code>free</code>	16
4.3 Garbage collection	17
4.3.1 Why and how	17
4.3.2 Variants	19
4.3.3 Examples	20
4.3.4 Comments	23
4.4 Creation of PARI objects, assignments, conversions	23
4.4.1 Creation of PARI objects	23
4.4.2 Sizes	25
4.4.3 Assignments	25
4.4.4 Copy	27
4.4.5 Clones	27
4.4.6 Conversions	27
4.5 Implementation of the PARI types	28
4.5.1 Type <code>t_INT</code> (integer)	29
4.5.2 Type <code>t_REAL</code> (real number)	30
4.5.3 Type <code>t_INTMOD</code>	31
4.5.4 Type <code>t_FRAC</code> (rational number)	31
4.5.5 Type <code>t_FFELT</code> (finite field element)	31
4.5.6 Type <code>t_COMPLEX</code> (complex number)	31
4.5.7 Type <code>t_PADIC</code> (p -adic numbers)	31
4.5.8 Type <code>t_QUAD</code> (quadratic number)	31
4.5.9 Type <code>t_POLMOD</code> (polmod)	32
4.5.10 Type <code>t_POL</code> (polynomial)	32
4.5.11 Type <code>t_SER</code> (power series)	33
4.5.12 Type <code>t_RFRAC</code> (rational function)	33
4.5.13 Type <code>t_QFB</code> (binary quadratic form)	33
4.5.14 Type <code>t_VEC</code> and <code>t_COL</code> (vector)	33
4.5.15 Type <code>t_MAT</code> (matrix)	33
4.5.16 Type <code>t_VECSMALL</code> (vector of small integers)	33
4.5.17 Type <code>t_STR</code> (character string)	33
4.5.18 Type <code>t_ERROR</code> (error context)	34
4.5.19 Type <code>t_CLOSURE</code> (closure)	34
4.5.20 Type <code>t_INFINITY</code> (infinity)	34
4.5.21 Type <code>t_LIST</code> (list)	34
4.6 PARI variables	34
4.6.1 Multivariate objects	34
4.6.2 Creating variables	35

4.6.3 Comparing variables	37
4.7 Input and output	37
4.7.1 Input	37
4.7.2 Output to screen or file, output to string	38
4.7.3 Errors	39
4.7.4 Warnings	40
4.7.5 Debugging output	40
4.7.6 Timers and timing output	41
4.8 Iterators, Numerical integration, Sums, Products	42
4.8.1 Iterators	42
4.8.2 Iterating over primes	44
4.8.3 Parallel iterators	45
4.8.4 Numerical analysis	46
4.9 Catching exceptions	47
4.9.1 Basic use	47
4.9.2 Advanced use	47
4.10 A complete program	48
Chapter 5: Technical Reference Guide: the basics	51
5.1 Initializing the library	51
5.1.1 General purpose	51
5.1.2 Technical functions	52
5.1.3 Notions specific to the GP interpreter	54
5.1.4 Public callbacks	55
5.1.5 Configuration variables	56
5.1.6 Utility functions	56
5.1.7 Saving and restoring the GP context	57
5.1.8 GP history	57
5.2 Handling GENs	58
5.2.1 Allocation	58
5.2.2 Length conversions	59
5.2.3 Read type-dependent information	59
5.2.4 Eval type-dependent information	61
5.2.5 Set type-dependent information	62
5.2.6 Type groups	62
5.2.7 Accessors and components	63
5.3 Global numerical constants	64
5.3.1 Constants related to word size	64
5.3.2 Masks used to implement the GEN type	64
5.3.3 $\log 2$, π	65
5.4 Iterating over small primes, low-level interface	65
5.5 Handling the PARI stack	66
5.5.1 Allocating memory on the stack	66
5.5.2 Stack-independent binary objects	67
5.5.3 Garbage collection	67
5.5.4 Garbage collection: advanced use	69
5.5.5 Debugging the PARI stack	70
5.5.6 Copies	71
5.5.7 Simplify	71
5.6 The PARI heap	71

5.6.1 Introduction	71
5.6.2 Public interface	71
5.6.3 Implementation note	72
5.7 Handling user and temp variables	72
5.7.1 Low-level	73
5.7.2 User variables	73
5.7.3 Temporary variables	73
5.8 Adding functions to PARI	74
5.8.1 Nota Bene	74
5.8.2 Coding guidelines	74
5.8.3 GP prototypes, parser codes	75
5.8.4 Integration with gp as a shared module	77
5.8.5 Library interface for install	78
5.8.6 Integration by patching gp	78
5.9 Globals related to PARI configuration	79
5.9.1 PARI version numbers	79
5.9.2 Miscellaneous	79
Chapter 6: Arithmetic kernel: Level 0 and 1	81
6.1 Level 0 kernel (operations on ulongs)	81
6.1.1 Micro-kernel	81
6.1.2 Modular kernel	82
6.1.3 Modular kernel with “precomputed inverse”	83
6.1.4 Switching between FL_XXX and standard operators	85
6.2 Level 1 kernel (operations on longs, integers and reals)	86
6.2.1 Creation	86
6.2.2 Assignment	87
6.2.3 Copy	87
6.2.4 Conversions	88
6.2.5 Integer parts	89
6.2.6 2-adic valuations and shifts	89
6.2.7 From t_INT to bits or digits in base 2^k and back	90
6.2.8 Integer valuation	91
6.2.9 Generic unary operators	92
6.2.10 Comparison operators	93
6.2.11 Generic binary operators	94
6.2.12 Exact division and divisibility	97
6.2.13 Division with integral operands and t_REAL result	97
6.2.14 Division with remainder	98
6.2.15 Modulo to longs	99
6.2.16 Powering, Square root	100
6.2.17 GCD, extended GCD and LCM	101
6.2.18 Continued fractions and convergents	101
6.2.19 Pseudo-random integers	102
6.2.20 Modular operations	102
6.2.21 Extending functions to vector inputs	105
6.2.22 Miscellaneous arithmetic functions	106
Chapter 7: Level 2 kernel	109
7.1 Naming scheme	109
7.2 Coefficient ring	111

7.3 Modular arithmetic	112
7.3.1 FpC / FpV, FpM	112
7.3.2 Flc / Flv, Flm	116
7.3.3 F2c / F2v, F2m	119
7.3.4 F3c / F3v, F3m	121
7.3.5 FlxqV, FlxqC, FlxqM	122
7.3.6 FpX	122
7.3.7 FpXQ, Fq	127
7.3.8 FpXQ	129
7.3.9 Fq	129
7.3.10 FpXn	131
7.3.11 FpXC, FpXM	131
7.3.12 FpXX, FpXY	132
7.3.13 FpXQX, FqX	133
7.3.14 FpXQXn, FqXn	135
7.3.15 FpXQXQ, FqXQ	135
7.3.16 Flx	138
7.3.17 FlxV	144
7.3.18 FlxM	144
7.3.19 FlxT	144
7.3.20 Flxn	145
7.3.21 Flxq	145
7.3.22 FlxX	147
7.3.23 FlxXV, FlxXC, FlxXM	148
7.3.24 FlxqX	149
7.3.25 FlxqXQ	152
7.3.26 FlxqXn	153
7.3.27 F2x	153
7.3.28 F2xq	155
7.3.29 F2xn	156
7.3.30 F2xqV, F2xqM	156
7.3.31 F2xX	156
7.3.32 F2xXV/F2xXC	157
7.3.33 F2xqX	157
7.3.34 F2xqXQ	158
7.3.35 Functions returning objects with t_INTMOD coefficients	159
7.3.36 Slow Chinese remainder theorem over Z	160
7.3.37 Fast remainders	162
7.3.38 Fast Chinese remainder theorem over Z	163
7.3.39 Rational reconstruction	164
7.3.40 Zp	165
7.3.41 ZpM	165
7.3.42 ZpX	165
7.3.43 ZpXQ	167
7.3.44 Zq	167
7.3.45 ZpXQM	167
7.3.46 ZpXQX	167
7.3.47 ZqX	168
7.3.48 Other p -adic functions	168

7.3.49	Conversions involving single precision objects	170
7.4	Higher arithmetic over Z : primes, factorization	173
7.4.1	Pure powers	173
7.4.2	Factorization	174
7.4.3	Coprime factorization	176
7.4.4	Checks attached to arithmetic functions	177
7.4.5	Incremental integer factorization	178
7.4.6	Integer core, squarefree factorization	178
7.4.7	Primes, primality and compositeness tests	179
7.4.8	Iterators over primes	180
7.5	Integral, rational and generic linear algebra	181
7.5.1	ZC / ZV , ZM	181
7.5.2	QM	185
7.5.3	Qevproj	186
7.5.4	zv , zm	186
7.5.5	ZMV / zmV (vectors of ZM/zm)	187
7.5.6	QC / QV , QM	187
7.5.7	RgC / RgV , RgM	187
7.5.8	ZG	192
7.5.9	Sparse and blackbox linear algebra	193
7.5.10	Obsolete functions	195
7.6	Integral, rational and generic polynomial arithmetic	195
7.6.1	ZX	195
7.6.2	Resultants	198
7.6.3	ZXV	198
7.6.4	ZXT	198
7.6.5	ZXQ	199
7.6.6	ZXn	199
7.6.7	ZXQM	199
7.6.8	ZXQX	199
7.6.9	ZXX	200
7.6.10	QX	200
7.6.11	QXQ	201
7.6.12	QXQX	202
7.6.13	QXQM	202
7.6.14	zx	202
7.6.15	RgX	203
7.6.16	RgXn	208
7.6.17	RgXnV	209
7.6.18	RgXQ	209
7.6.19	RgXQV , RgXQC	210
7.6.20	RgXQM	210
7.6.21	RgXQX	211
Chapter 8:	Black box algebraic structures	211
8.1	Black box groups	212
8.1.1	Black box groups with pairing	213
8.1.2	Functions returning black box groups	214
8.2	Black box fields	214
8.2.1	Functions returning black box fields	215

8.3 Black box algebra	215
8.3.1 Functions returning black box algebras	216
8.4 Black box ring	217
8.5 Black box free \mathbf{Z}_p -modules	217
Chapter 9: Operations on general PARI objects	219
9.1 Assignment	219
9.2 Conversions	219
9.2.1 Scalars	219
9.2.2 Modular objects / lifts	221
9.2.3 Between polynomials and coefficient arrays	221
9.3 Constructors	224
9.3.1 Clean constructors	224
9.3.2 Unclean constructors	226
9.3.3 From roots to polynomials	229
9.4 Integer parts	230
9.5 Valuation and shift	230
9.6 Comparison operators	231
9.6.1 Generic	231
9.6.2 Comparison with a small integer	231
9.7 Miscellaneous Boolean functions	232
9.7.1 Obsolete	233
9.8 Sorting	233
9.8.1 Basic sort	233
9.8.2 Indirect sorting	233
9.8.3 Generic sort and search	234
9.8.4 Further useful comparison functions	235
9.9 Division	235
9.10 Divisibility, Euclidean division	236
9.11 GCD, content and primitive part	237
9.11.1 Generic	237
9.11.2 Over the rationals	237
9.12 Generic arithmetic operators	239
9.12.1 Unary operators	239
9.12.2 Binary operators	239
9.13 Generic operators: product, powering, factorback	240
9.14 Matrix and polynomial norms	242
9.15 Substitution and evaluation	243
Chapter 10: Miscellaneous mathematical functions	245
10.1 Fractions	245
10.2 Binomials	245
10.3 Real numbers	245
10.4 Complex numbers	246
10.5 Quadratic numbers and binary quadratic forms	246
10.6 Polynomials	247
10.7 Power series	248
10.8 Functions to handle $\mathbf{t_FFELT}$	248
10.8.1 FFX	251
10.8.2 FFM	252
10.8.3 FFXQ	253

10.9 Transcendental functions	253
10.9.1 Transcendental functions with t_REAL arguments	253
10.9.2 Other complex transcendental functions	254
10.9.3 Modular functions	256
10.9.4 Transcendental functions with t_PADIC arguments	256
10.9.5 Cached constants	257
10.9.6 Obsolete functions	257
10.10 Permutations	258
10.11 Small groups	259
Chapter 11: Standard data structures	263
11.1 Character strings	263
11.1.1 Functions returning a char *	263
11.1.2 Functions returning a t_STR	264
11.1.3 Dynamic strings	264
11.2 Output	265
11.2.1 Output contexts	265
11.2.2 Default output context	265
11.2.3 PARI colors	266
11.2.4 Obsolete output functions	266
11.3 Files	267
11.3.1 pariFILE	267
11.3.2 Temporary files	268
11.4 Errors	268
11.4.1 Internal errors, “system” errors	268
11.4.2 Syntax errors, type errors	269
11.4.3 Overflows	270
11.4.4 Errors triggered intentionally	271
11.4.5 Mathematical errors	272
11.4.6 Miscellaneous functions	273
11.5 Hashtables	273
11.6 Dynamic arrays	276
11.6.1 Initialization	276
11.6.2 Adding elements	276
11.6.3 Accessing elements	276
11.6.4 Stack of stacks	276
11.6.5 Public interface	277
11.7 Vectors and Matrices	277
11.7.1 Access and extract	277
11.7.2 Componentwise operations	279
11.7.3 Low-level vectors and columns functions	279
11.8 Vectors of small integers	280
11.8.1 t_VECSMALL	280
11.8.2 Vectors of t_VECSMALL	282
Chapter 12: Functions related to the GP interpreter	283
12.1 Handling closures	283
12.1.1 Functions to evaluate t_CLOSURE	283
12.1.2 Functions to handle control flow changes	284
12.1.3 Functions to deal with lexical local variables	284
12.1.4 Functions returning new closures	285

12.1.5 Functions used by the gp debugger (break loop)	285
12.1.6 Standard wrappers for iterators	285
12.2 Defaults	286
12.3 Records and Lazy vectors	289
Chapter 13: Algebraic Number Theory	291
13.1 General Number Fields	291
13.1.1 Number field types	291
13.1.2 Extracting info from a nf structure	293
13.1.3 Extracting info from a bnf structure	294
13.1.4 Extracting info from a bnr structure	295
13.1.5 Extracting info from an rnf structure	295
13.1.6 Extracting info from a bid structure	296
13.1.7 Extracting info from a znstar structure	297
13.1.8 Inserting info in a number field structure	297
13.1.9 Increasing accuracy	298
13.1.10 Number field arithmetic	299
13.1.11 Number field arithmetic for linear algebra	301
13.1.12 Cyclotomic field arithmetic for linear algebra	302
13.1.13 Cyclotomic trace	302
13.1.14 Elements in factored form	303
13.1.15 Ideal arithmetic	304
13.1.16 Maximal ideals	307
13.1.17 Decomposition groups	309
13.1.18 Reducing modulo maximal ideals	309
13.1.19 Valuations	310
13.1.20 Signatures	311
13.1.21 Complex embeddings	312
13.1.22 Maximal order and discriminant, conversion to nf structure	313
13.1.23 Computing in the class group	314
13.1.24 Floating point embeddings, the T_2 quadratic form	316
13.1.25 Ideal reduction, low level	316
13.1.26 Ideal reduction, high level	317
13.1.27 Class field theory	318
13.1.28 Abelian maps	320
13.1.29 Grunwald–Wang theorem	320
13.1.30 Relative equations, Galois conjugates	320
13.1.31 Units	322
13.1.32 Obsolete routines	323
13.2 Galois extensions of Q	324
13.2.1 Extracting info from a gal structure	324
13.2.2 Miscellaneous functions	324
13.3 Quadratic number fields and quadratic forms	325
13.3.1 Checks	325
13.3.2 Class number	325
13.3.3 t_QFB	326
13.3.4 Efficient real quadratic forms	328
13.4 Linear algebra over Z	329
13.4.1 Hermite and Smith Normal Forms	329
13.4.2 The LLL algorithm	333

13.4.3 Linear dependencies	335
13.4.4 Reduction modulo matrices	335
13.5 Finite abelian groups and characters	336
13.5.1 Abstract groups	336
13.5.2 Dirichlet characters	337
13.6 Hecke characters	338
13.7 Central simple algebras	338
13.7.1 Initialization	338
13.7.2 Type checks	339
13.7.3 Shallow accessors	339
13.7.4 Other low-level functions	340
Chapter 14: Elliptic curves and arithmetic geometry	341
14.1 Elliptic curves	341
14.1.1 Types of elliptic curves	341
14.1.2 Type checking	341
14.1.3 Extracting info from an <code>ell</code> structure	342
14.1.4 Points	346
14.1.5 Change of variables	346
14.1.6 Generic helper functions	346
14.1.7 Functions to handle elliptic curves over finite fields	347
14.2 Arithmetic on elliptic curve over a finite field in simple form	347
14.2.1 Helper functions	347
14.2.2 Elliptic curves over \mathbf{F}_p , $p > 3$	348
14.2.3 <code>FpE</code>	348
14.2.4 <code>Fle</code>	349
14.2.5 <code>FpJ</code>	350
14.2.6 <code>Flj</code>	350
14.2.7 Elliptic curves over \mathbf{F}_{2^n}	351
14.2.8 <code>F2xqE</code>	351
14.2.9 Elliptic curves over \mathbf{F}_q , small characteristic $p > 2$	352
14.2.10 <code>FlxqE</code>	352
14.2.11 Elliptic curves over \mathbf{F}_q , large characteristic	353
14.2.12 <code>FpXQE</code>	354
14.3 Functions related to modular polynomials	354
14.3.1 Functions related to modular invariants	355
14.4 Other curves	355
Chapter 15: L-functions	357
15.1 Accessors	357
15.2 Conversions and constructors	358
15.3 Variants of GP functions	359
15.4 Inverse Mellin transforms of Gamma products	359
Chapter 16: Modular symbols	361
Chapter 17: Modular forms	363
17.1 Implementation of public data structures	363
17.1.1 Accessors for modular form spaces	363
17.1.2 Accessors for individual modular forms	364
17.1.3 Nebentypus	365
17.1.4 Miscellaneous functions	365
Chapter 18: Plots	367

18.1 Highlevel functions	367
18.2 Function	368
18.2.1 Obsolete functions	368
18.3 Dump rectwindows to a PostScript or SVG file	369
18.4 Technical functions exported for convenience	369
Appendix A: A Sample program and Makefile	371
Appendix B: PARI and threads	373
Index	376

Chapter 4:

Programming PARI in Library Mode

The *User's Guide to Pari/GP* gives in three chapters a general presentation of the system, of the `gp` calculator, and detailed explanation of high level PARI routines available through the calculator. The present manual assumes general familiarity with the contents of these chapters and the basics of ANSI C programming, and focuses on the usage of the PARI library. In this chapter, we introduce the general concepts of PARI programming and describe useful general purpose functions; the following chapters describes all public low or high-level functions, underlying or extending the GP functions seen in Chapter 3 of the User's guide.

4.1 Introduction: initializations, universal objects.

To use PARI in library mode, you must write a C program and link it to the PARI library. See the installation guide or the Appendix to the *User's Guide to Pari/GP* on how to create and install the library and include files. A sample Makefile is presented in Appendix A, and a more elaborate one in `examples/Makefile`. The best way to understand how programming is done is to work through a complete example. We will write such a program in Section 4.10. Before doing this, a few explanations are in order.

First, one must explain to the outside world what kind of objects and routines we are going to use. This is done* with the directive

```
#include <pari/pari.h>
```

In particular, this defines the fundamental type for all PARI objects: the type **GEN**, which is simply a pointer to `long`.

Before any PARI routine is called, one must initialize the system, and in particular the PARI stack which is both a scratchboard and a repository for computed objects. This is done with a call to the function

```
void pari_init(size_t size, ulong maxprime)
```

The first argument is the number of bytes given to PARI to work with, and the second is the upper limit on a precomputed prime number table; `size` should not reasonably be taken below 500000 but you may set `maxprime = 0`, although the system still needs to precompute all primes up to about 2^{16} . For lower-level variants allowing finer control, e.g. preventing PARI from installing its own error or signal handlers, see Section 5.1.2.

We have now at our disposal:

- a PARI *stack* containing nothing. This is a big connected chunk of `size` bytes of memory, where all computations take place. In large computations, intermediate results quickly clutter up memory so some kind of garbage collecting is needed. Most systems do garbage collecting when the memory is getting scarce, and this slows down the performance. PARI takes a different approach,

* This assumes that PARI headers are installed in a directory which belongs to your compiler's search path for header files. You might need to add flags like `-I/usr/local/include` or modify `C_INCLUDE_PATH`.

admittedly more demanding on the programmer: you must do your own cleaning up when the intermediate results are not needed anymore. We will see later how (and when) this is done.

- the following *universal objects* (by definition, objects which do not belong to the stack): the integers 0, 1, -1, 2 and -2 (respectively called `gen_0`, `gen_1`, `gen_m1`, `gen_2` and `gen_m2`), the fraction $\frac{1}{2}$ (`ghalf`). All of these are of type `GEN`.

- a *heap* which is just a linked list of permanent universal objects. For now, it contains exactly the ones listed above. You will probably very rarely use the heap yourself; and if so, only as a collection of copies of objects taken from the stack (called clones in the sequel). Thus you need not bother with its internal structure, which may change as PARI evolves. Some complex PARI functions create clones for special garbage collecting purposes, usually destroying them when returning.

- a table of primes, called `pari_PRIMES`, of type `pari_prime*` (pointer to 32bit unsigned integer). Its use is described in Section 5.4 later. Using it directly is deprecated, high-level iterators provide a cleaner and more flexible interface, see Section 4.8.2 (such iterators use the private prime table, but extend it dynamically).

- access to all the built-in functions of the PARI library. These are declared to the outside world when you include `pari.h`, but need the above things to function properly. So if you forget the call to `pari_init`, you will get a fatal error when running your program.

4.2 Important technical notes.

4.2.1 Backward compatibility. The PARI function names evolved over time, and deprecated functions are eventually deleted. The file `pariold.h` contains macros implementing a weak form of backward compatibility. In particular, whenever the name of a documented function changes, a `#define` is added to this file so that the old name expands to the new one (provided the prototype didn't change also).

This file is included by `pari.h`, but a large section is commented out by default. Define `PARI_OLD_NAMES` before including `pari.h` to pollute your namespace with lots of obsolete names like `un*`: that might enable you to compile old programs without having to modify them. The preferred way to do that is to add `-DPARI_OLD_NAMES` to your compiler `CFLAGS`, so that you don't need to modify the program files themselves.

Of course, it's better to fix the program if you can!

4.2.2 Types.

Although PARI objects all have the C type `GEN`, we will freely use the word **type** to refer to PARI dynamic subtypes: `t_INT`, `t_REAL`, etc. The declaration

```
GEN x;
```

declares a C variable of type `GEN`, but its “value” will be said to have type `t_INT`, `t_REAL`, etc. The meaning should always be clear from the context.

* For (long)`gen_1`. Since 2004 and version 2.2.9, typecasts are completely unnecessary in PARI programs.

4.2.3 Type recursivity.

Conceptually, most PARI types are recursive. But the **GEN** type is a pointer to **long**, not to **GEN**. So special macros must be used to access **GEN**'s components. The simplest one is **gel**(*V*, *i*), where **el** stands for **e**lement, to access component number *i* of the **GEN** *V*. This is a valid **lvalue** (may be put on the left side of an assignment), and the following two constructions are exceedingly frequent

```
gel(V, i) = x;  
x = gel(V, i);
```

where **x** and **V** are **GEN**s. This macro accesses and modifies directly the components of *V* and do not create a copy of the coefficient, contrary to all the library *functions*.

More generally, to retrieve the values of elements of lists of ... of lists of vectors we have the **gmael** macros (for **m**ultidimensional **a**rray **e**lement). The syntax is **gmael***n*(*V*, *a*₁, ..., *a*_{*n*}), where *V* is a **GEN**, the *a*_{*i*} are indexes, and *n* is an integer between 1 and 5. This stands for *x*[*a*₁][*a*₂]...[*a*_{*n*}], and returns a **GEN**. The macros **gel** (resp. **gmael**) are synonyms for **gmael1** (resp. **gmael2**).

Finally, the macro **gcoeff**(*M*, *i*, *j*) has exactly the meaning of *M*[*i*,*j*] in GP when *M* is a matrix. Note that due to the implementation of **t_MATs** as horizontal lists of vertical vectors, **gcoeff**(*x*,*y*) is actually equivalent to **gmael**(*y*,*x*). One should use **gcoeff** in matrix context, and **gmael** otherwise.

4.2.4 Variations on basic functions. In the library syntax descriptions in Chapter 3, we have only given the basic names of the functions. For example **gadd**(*x*, *y*) assumes that *x* and *y* are **GEN**s, and *creates* the result *x*+*y* on the PARI stack. For most of the basic operators and functions, many other variants are available. We give some examples for **gadd**, but the same is true for all the basic operators, as well as for some simple common functions (a complete list is given in Chapter 6):

GEN **gaddgs**(**GEN** *x*, **long** *y*)

GEN **gaddsg**(**long** *x*, **GEN** *y*)

In the following one, *z* is a preexisting **GEN** and the result of the corresponding operation is put into *z*. The size of the PARI stack does not change:

void **gaddz**(**GEN** *x*, **GEN** *y*, **GEN** *z*)

(This last form is inefficient in general and deprecated outside of PARI kernel programming.) Low level kernel functions implement these operators for specialized arguments and are also available: Level 0 deals with operations at the word level (**longs** and **ulongs**), Level 1 with **t_INT** and **t_REAL** and Level 2 with the rest (modular arithmetic, polynomial arithmetic and linear algebra). Here are some examples of Level 1 functions:

GEN **addii**(**GEN** *x*, **GEN** *y*): here *x* and *y* are **GEN**s of type **t_INT** (this is not checked).

GEN **addr**(**GEN** *x*, **GEN** *y*): here *x* and *y* are **GEN**s of type **t_REAL** (this is not checked).

There also exist functions **addir**, **addri**, **mpadd** (whose two arguments can be of type **t_INT** or **t_REAL**), **addis** (to add a **t_INT** and a **long**) and so on.

The Level 1 names are self-explanatory once you know that **i** stands for a **t_INT**, **r** for a **t_REAL**, **mp** for **i** or **r**, **s** for a signed C long integer, **u** for an unsigned C long integer; finally the suffix **z** means that the result is not created on the PARI stack but assigned to a preexisting **GEN** object passed as an extra argument. Chapter 6 gives a description of these low-level functions.

Level 2 names are more complicated, see Section 7.1 for all the gory details, and we content ourselves with a simple example used to implement `t_INTMOD` arithmetic:

`GEN Fp_add(GEN x, GEN y, GEN m)`: returns the sum of x and y modulo m . Here x, y, m are `t_INT`s (this is not checked). The operation is more efficient if the inputs x, y are reduced modulo m , but this is not a necessary condition.

Important Note. These specialized functions are of course more efficient than the generic ones, but note the hidden danger here: the types of the objects involved (which is not checked) must be severely controlled, e.g. using `addii` on a `t_FRAC` argument will cause disasters. Type mismatches may corrupt the PARI stack, though in most cases they will just immediately overflow the stack. Because of this, the PARI philosophy of giving a result which is as exact as possible, enforced for generic functions like `gadd` or `gmul`, is dropped in kernel routines of Level 1, where it is replaced by the much simpler rule: the result is a `t_INT` if and only if all arguments are integer types (`t_INT` but also C `long` and `ulong`) and a `t_REAL` otherwise. For instance, multiplying a `t_REAL` by a `t_INT` always yields a `t_REAL` if you use `mulir`, where `gmul` returns the `t_INT` `gen_0` if the integer is 0.

4.2.5 Portability: 32-bit / 64-bit architectures.

PARI supports both 32-bit and 64-bit based machines, but not simultaneously! The library is compiled assuming a given architecture, and some of the header files you include (through `pari.h`) will have been modified to match the library.

Portable macros are defined to bypass most machine dependencies. If you want your programs to run identically on 32-bit and 64-bit machines, you have to use these, and not the corresponding numeric values, whenever the precise size of your `long` integers might matter. Here are the most important ones:

<code>DEFAULTPREC</code>	64	(\approx 19 decimal digits)
<code>MEDDEFAULTPREC</code>	128	(\approx 38 decimal digits)
<code>BIGDEFAULTPREC</code>	192	(\approx 57 decimal digits)

For instance, suppose you call a transcendental function, such as

```
GEN gexp(GEN x, long prec).
```

The last argument `prec` is an integer multiple of `BITS_IN_LONG`, corresponding to the default floating point precision required. It is *only* used if `x` is an exact object, otherwise the relative precision is determined by the precision of `x`. Note that for parity reasons, half the accuracies available on 32-bit architectures (the odd multiples of 32) have no precise equivalents on 64-bit machines.

4.2.6 Using `malloc` / `free`. You should make use of the PARI stack as much as possible, and avoid allocating objects using the customary functions. If you do, you should use, or at least have a very close look at, the following wrappers:

`void* pari_malloc(size_t size)` calls `malloc` to allocate `size` bytes and returns a pointer to the allocated memory. If the request fails, an error is raised. The `SIGINT` signal is blocked until `malloc` returns, to avoid leaving the system stack in an inconsistent state.

`void* pari_realloc(void* ptr, size_t size)` as `pari_malloc` but calls `realloc` instead of `malloc`.

`void pari_realloc_ip(void** ptr, size_t size)` equivalent to `*ptr= realloc(*ptr, size)`, while blocking `SIGINT`.

`void* pari_calloc(size_t size)` as `pari_malloc`, setting the memory to zero.

`void pari_free(void* ptr)` calls `free` to liberate the memory space pointed to by `ptr`, which must have been allocated by `malloc` (`pari_malloc`) or `realloc` (`pari_realloc`). The `SIGINT` signal is blocked until `free` returns.

If you use the standard `libc` functions instead of our wrappers, then your functions will be subtly incompatible with the `gp` calculator: when the user tries to interrupt a computation, the calculator may crash (if a system call is interrupted at the wrong time).

4.3 Garbage collection.

4.3.1 Why and how.

As we have seen, `pari_init` allocates a big range of addresses, the *stack*, that are going to be used throughout. Recall that all PARI objects are pointers. Except for a few universal objects, they all point at some part of the stack.

The stack starts at the address `bot` and ends just before `top`. This means that the quantity

$$(\text{top} - \text{bot}) / \text{sizeof}(\text{long})$$

is (roughly) equal to the `size` argument of `pari_init`. The PARI stack also has a “current stack pointer” called `avma`, which stands for **a**vaila**b**le **m**emory **a**ddress. These three variables are global (declared by `pari.h`). They are of type `pari_sp`, which means *pari stack pointer*.

The stack is oriented upside-down: the more recent an object, the closer to `bot`. Accordingly, initially `avma = top`, and `avma` gets *decremented* as new objects are created. As its name indicates, `avma` always points just *after* the first free address on the stack, and `(GEN)avma` is always (a pointer to) the latest created object. When `avma` reaches `bot`, the stack overflows, aborting all computations, and an error message is issued. To avoid this *you* need to clean up the stack from time to time, when intermediate objects are not needed anymore. This is called “*garbage collecting*.”

We are now going to describe briefly how this is done. We will see many concrete examples in the next subsection.

- First, PARI routines do their own garbage collecting, which means that whenever a documented function from the library returns, only its result(s) have been added to the stack, possibly up to a very small overhead (undocumented ones may not do this). In particular, a PARI function that does not return a `GEN` does not clutter the stack. Thus, if your computation is small enough (e.g. you call few PARI routines, or most of them return `long` integers), then you do not need to do any garbage collecting. This is probably the case in many of your subroutines. Of course the objects that were on the stack *before* the function call are left alone. Except for the ones listed below, PARI functions only collect their own garbage.

- It may happen that all objects that were created after a certain point can be deleted — for instance, if the final result you need is not a `GEN`, or if some search proved futile. Then, it is enough to record the value of `avma` just *before* the first garbage is created, and restore it upon exit:

```
pari_sp av = avma; /* record initial avma */
garbage ...
set_avma(av); /* restore it */
```

All objects created in the **garbage** zone will eventually be overwritten: they should no longer be accessed after **avma** has been restored. Think of the **set_avma** call as a simple **avma = av** restoring the **avma** value.

- If you want to destroy (i.e. give back the memory occupied by) the *latest* PARI object on the stack (e.g. the latest one obtained from a function call), you can use the function

```
void cgiv(GEN z)
```

where **z** is the object you want to give back. This is equivalent to the above where the initial **av** is computed from **z**.

- Unfortunately life is not so simple, and sometimes you will want to give back accumulated garbage *during* a computation without losing recent data. We shall start with the lowest level function to get a feel for the underlying mechanisms, we shall describe simpler variants later:

GEN gerepile(pari_sp ltop, pari_sp lbot, GEN q). This function cleans up the stack between **ltop** and **lbot**, where **lbot** < **ltop**, and returns the updated object **q**. This means:

- 1) we translate (copy) all the objects in the interval **[avma, lbot]**, so that its right extremity abuts the address **ltop**. Graphically

```

      bot          avma  lbot          ltop  top
End of stack |-----[+++++[---/--/--/--/--|+++++] Start
              free memory          garbage
```

becomes:

```

      bot          avma  ltop  top
End of stack |-----[+++++[+++++] Start
              free memory
```

where **++** denote significant objects, **--** the unused part of the stack, and **---** the garbage we remove.

- 2) The function then inspects all the PARI objects between **avma** and **lbot** (i.e. the ones that we want to keep and that have been translated) and looks at every component of such an object which is not a codeword. Each such component is a pointer to an object whose address is either

- between **avma** and **lbot**, in which case it is suitably updated,
- larger than or equal to **ltop**, in which case it does not change, or
- between **lbot** and **ltop** in which case **gerepile** raises an error (“significant pointers lost in gerepile”).

- 3) **avma** is updated (we add **ltop – lbot** to the old value).

- 4) We return the (possibly updated) object **q**: if **q** initially pointed between **avma** and **lbot**, we return the updated address, as in 2). If not, the original address is still valid, and is returned!

As stated above, no component of the remaining objects (in particular **q**) should belong to the erased segment **[lbot, ltop]**, and this is checked within **gerepile**. But beware as well that the addresses of the objects in the translated zone change after a call to **gerepile**, so you must not access any pointer which previously pointed into the zone below **ltop**. If you need to recover more than one object, use the **gerepileall** function below.

Remark. As a consequence of the preceding explanation, if a PARI object is to be relocated by `gerepile` then, apart from universal objects, the chunks of memory used by its components should be in consecutive memory locations. All GENs created by documented PARI functions are guaranteed to satisfy this. This is because the `gerepile` function knows only about *two connected zones*: the garbage that is erased (between `lbot` and `ltop`) and the significant pointers that are copied and updated. If there is garbage interspersed with your objects, disaster occurs when we try to update them and consider the corresponding “pointers”. In most cases of course the said garbage is in fact a bunch of other GENs, in which case we simply waste time copying and updating them for nothing. But be wary when you allow objects to become disconnected.

In practice this is achieved by the following programming idiom:

```
ltop = avma; garbage(); lbot = avma; q = anything();
return gerepile(ltop, lbot, q); /* returns the updated q */
```

or directly

```
ltop = avma; garbage(); lbot = avma;
return gerepile(ltop, lbot, anything());
```

Beware that

```
ltop = avma; garbage();
return gerepile(ltop, avma, anything())
```

might work, but should be frowned upon. We cannot predict whether `avma` is evaluated after or before the call to `anything()`: it depends on the compiler. If we are out of luck, it is *after* the call, so the result belongs to the garbage zone and the `gerepile` statement becomes equivalent to `set_avma(ltop)`. Thus we return a pointer to random garbage.

4.3.2 Variants.

GEN `gerepileupto(pari_sp ltop, GEN q)`. Cleans the stack between `ltop` and the *connected* object `q` and returns `q` updated. For this to work, `q` must have been created *before* all its components, otherwise they would belong to the garbage zone! Unless mentioned otherwise, documented PARI functions guarantee this.

GEN `gerepilecopy(pari_sp ltop, GEN x)`. Functionally equivalent to, but more efficient than

```
gerepileupto(ltop, gcopy(x))
```

In this case, the **GEN** parameter `x` need not satisfy any property before the garbage collection: it may be disconnected, components created before the root, and so on. Of course, this is about twice slower than either `gerepileupto` or `gerepile`, because `x` has to be copied to a clean stack zone first. This function is a special case of `gerepileall` below, where $n = 1$.

void `gerepileall(pari_sp ltop, int n, ...)`. To cope with complicated cases where many objects have to be preserved. The routine expects n further arguments, which are the *addresses* of the GENs you want to preserve:

```
pari_sp ltop = avma;
...; y = ...; ... x = ...; ...;
gerepileall(ltop, 2, &x, &y);
```

It cleans up the most recent part of the stack (between `ltop` and `avma`), updating all the GENs added to the argument list. A copy is done just before the cleaning to preserve them, so they

do not need to be connected before the call. With `gerepilecopy`, this is the most robust of the `gerepile` functions (the less prone to user error), hence the slowest.

`void gerepileallsp(pari_sp ltop, pari_sp lbot, int n, ...)`. More efficient, but trickier than `gerepileall`. Cleans the stack between `lbot` and `ltop` and updates the GENs pointed at by the elements of `gptr` without any further copying. This is subject to the same restrictions as `gerepile`, the only difference being that more than one address gets updated.

4.3.3 Examples.

4.3.3.1 gerepile.

Let `x` and `y` be two preexisting PARI objects and suppose that we want to compute $x^2 + y^2$. This is done using the following program:

```
GEN x2 = gsqr(x);
GEN y2 = gsqr(y), z = gadd(x2,y2);
```

The GEN `z` indeed points at the desired quantity. However, consider the stack: it contains as unnecessary garbage `x2` and `y2`. More precisely it contains (in this order) `z`, `y2`, `x2`. (Recall that, since the stack grows downward from the top, the most recent object comes first.)

It is not possible to get rid of `x2`, `y2` before `z` is computed, since they are used in the final operation. We cannot record `avma` before `x2` is computed and restore it later, since this would destroy `z` as well. It is not possible either to use the function `cgiv` since `x2` and `y2` are not at the bottom of the stack and we do not want to give back `z`.

But using `gerepile`, we can give back the memory locations corresponding to `x2`, `y2`, and move the object `z` upwards so that no space is lost. Specifically:

```
pari_sp ltop = avma; /* remember the current top of the stack */
GEN x2 = gsqr(x);
GEN y2 = gsqr(y);
pari_sp lbot = avma; /* the bottom of the garbage pile */
GEN z = gadd(x2, y2); /* z is now the last object on the stack */
z = gerepile(ltop, lbot, z);
```

Of course, the last two instructions could also have been written more simply:

```
z = gerepile(ltop, lbot, gadd(x2,y2));
```

In fact `gerepileupto` is even simpler to use, because the result of `gadd` is the last object on the stack and `gadd` is guaranteed to return an object suitable for `gerepileupto`:

```
ltop = avma;
z = gerepileupto(ltop, gadd(gsqr(x), gsqr(y)));
```

Make sure you understand exactly what has happened before you go on!

Remark on assignments and gerepile. When the tree structure and the size of the PARI objects which will appear in a computation are under control, one may allocate sufficiently large objects at the beginning, use assignment statements, then simply restore `avma`. Coming back to the above example, note that *if* we know that `x` and `y` are of type real fitting into `DEFAULTPREC` words, we can program without using `gerepile` at all:

```
z = cgetr(DEFAULTPREC); ltop = avma;
gaffect(gadd(gsqr(x), gsqr(y)), z);
set_avma(ltop);
```

This is often *slower* than a craftily used `gerepile` though, and certainly more cumbersome to use. As a rule, assignment statements should generally be avoided.

Variations on a theme. it is often necessary to do several `gerepiles` during a computation. However, the fewer the better. The only condition for `gerepile` to work is that the garbage be connected. If the computation can be arranged so that there is a minimal number of connected pieces of garbage, then it should be done that way.

For example suppose we want to write a function of two `GEN` variables `x` and `y` which creates the vector $[x^2 + y, y^2 + x]$. Without garbage collecting, one would write:

```
p1 = gsqr(x); p2 = gadd(p1, y);
p3 = gsqr(y); p4 = gadd(p3, x);
z = mkvec2(p2, p4); /* not suitable for gerepileupto! */
```

This leaves a dirty stack containing (in this order) `z`, `p4`, `p3`, `p2`, `p1`. The garbage here consists of `p1` and `p3`, which are separated by `p2`. But if we compute `p3` *before* `p2` then the garbage becomes connected, and we get the following program with garbage collecting:

```
ltop = avma; p1 = gsqr(x); p3 = gsqr(y);
lbot = avma; z = cgetg(3, t_VEC);
gel(z, 1) = gadd(p1,y);
gel(z, 2) = gadd(p3,x); z = gerepile(ltop,lbot,z);
```

Finishing by `z = gerepileupto(ltop, z)` would be ok as well. Beware that

```
ltop = avma; p1 = gadd(gsqr(x), y); p3 = gadd(gsqr(y), x);
z = cgetg(3, t_VEC);
gel(z, 1) = p1;
gel(z, 2) = p3; z = gerepileupto(ltop,z); /* WRONG */
```

is a disaster since `p1` and `p3` are created before `z`, so the call to `gerepileupto` overwrites them, leaving `gel(z, 1)` and `gel(z, 2)` pointing at random data! The following does work:

```
ltop = avma; p1 = gsqr(x); p3 = gsqr(y);
lbot = avma; z = mkvec2(gadd(p1,y), gadd(p3,x));
z = gerepile(ltop,lbot,z);
```

but is very subtly wrong in the sense that `z = gerepileupto(ltop, z)` would *not* work. The reason being that `mkvec2` creates the root `z` of the vector *after* its arguments have been evaluated, creating the components of `z` too early; `gerepile` does not care, but the created `z` is a time bomb which will explode on any later `gerepileupto`. On the other hand

```
ltop = avma; z = cgetg(3, t_VEC);
gel(z, 1) = gadd(gsqr(x), y);
```

```
gel(z, 2) = gadd(gsq(y), x); z = gerepileupto(ltop,z); /* INEFFICIENT */
```

leaves the results of `gsqr(x)` and `gsqr(y)` on the stack (and lets `gerepileupto` update them for naught). Finally, the most elegant and efficient version (with respect to time and memory use) is as follows

```
z = cgetg(3, t_VEC);
ltop = avma; gel(z, 1) = gerepileupto(ltop, gadd(gsq(x), y));
ltop = avma; gel(z, 2) = gerepileupto(ltop, gadd(gsq(y), x));
```

which avoids updating the container `z` and cleans up its components individually, as soon as they are computed.

One last example. Let us compute the product of two complex numbers x and y , using the $3M$ method which requires 3 multiplications instead of the obvious 4. Let $z = x*y$, and set $x = x_r + i*x_i$ and similarly for y and z . We compute $p_1 = x_r * y_r$, $p_2 = x_i * y_i$, $p_3 = (x_r + x_i) * (y_r + y_i)$, and then we have $z_r = p_1 - p_2$, $z_i = p_3 - (p_1 + p_2)$. The program is as follows:

```
ltop = avma;
p1 = gmul(gel(x,1), gel(y,1));
p2 = gmul(gel(x,2), gel(y,2));
p3 = gmul(gadd(gel(x,1), gel(x,2)), gadd(gel(y,1), gel(y,2)));
p4 = gadd(p1,p2);
lbot = avma; z = cgetg(3, t_COMPLEX);
gel(z, 1) = gsub(p1,p2);
gel(z, 2) = gsub(p3,p4); z = gerepile(ltop,lbot,z);
```

Exercise. Write a function which multiplies a matrix by a column vector. Hint: start with a `cgetg` of the result, and use `gerepile` whenever a coefficient of the result vector is computed. You can look at the answer in `src/basemath/RgV.c:RgM_RgC_mul()`.

4.3.3.2 gerepileall.

Let us now see why we may need the `gerepileall` variants. Although it is not an infrequent occurrence, we do not give a specific example but a general one: suppose that we want to do a computation (usually inside a larger function) producing more than one PARI object as a result, say two for instance. Then even if we set up the work properly, before cleaning up we have a stack which has the desired results `z1`, `z2` (say), and then connected garbage from `lbot` to `ltop`. If we write

```
z1 = gerepile(ltop, lbot, z1);
```

then the stack is cleaned, the pointers fixed up, but we have lost the address of `z2`. This is where we need the `gerepileall` function:

```
gerepileall(ltop, 2, &z1, &z2)
```

copies `z1` and `z2` to new locations, cleans the stack from `ltop` to the old `avma`, and updates the pointers `z1` and `z2`. Here we do not assume anything about the stack: the garbage can be disconnected and `z1`, `z2` need not be at the bottom of the stack. If all of these assumptions are in fact satisfied, then we can call `gerepilemanysp` instead, which is usually faster since we do not need the initial copy (on the other hand, it is less cache friendly).

A most important usage is “random” garbage collection during loops whose size requirements we cannot (or do not bother to) control in advance:

```

pari_sp av = avma;
GEN x, y;
while (...)
{
    garbage(); x = anything();
    garbage(); y = anything(); garbage();
    if (gc_needed(av,1)) /* memory is running low (half spent since entry) */
        gerepileall(av, 2, &x, &y);
}

```

Here we assume that only `x` and `y` are needed from one iteration to the next. As it would be costly to call `gerepile` once for each iteration, we only do it when it seems to have become necessary.

More precisely, the macro `stack_lim(av,n)` denotes an address where $2^{n-1}/(2^{n-1}+1)$ of the remaining stack space since reference point `av` is exhausted (1/2 for $n = 1$, 2/3 for $n = 2$). The test `gc_needed(av,n)` becomes true whenever `avma` drops below that address.

4.3.4 Comments.

First, `gerepile` has turned out to be a flexible and fast garbage collector for number-theoretic computations, which compares favorably with more sophisticated methods used in other systems. Our benchmarks indicate that the price paid for using `gerepile` and `gerepile`-related copies, when properly used, is usually less than 1% of the total running time, which is quite acceptable!

Second, it is of course harder on the programmer, and quite error-prone if you do not stick to a consistent PARI programming style. If all seems lost, just use `gerepilecopy` (or `gerepileall`) to fix up the stack for you. You can always optimize later when you have sorted out exactly which routines are crucial and what objects need to be preserved and their usual sizes.

If you followed us this far, congratulations, and rejoice: the rest is much easier.

4.4 Creation of PARI objects, assignments, conversions.

4.4.1 Creation of PARI objects. The basic function which creates a PARI object is

`GEN cgetg(long l, long t)` `l` specifies the number of longwords to be allocated to the object, and `t` is the type of the object, in symbolic form (see Section 4.5 for the list of these). The precise effect of this function is as follows: it first creates on the PARI *stack* a chunk of memory of size `length` longwords, and saves the address of the chunk which it will in the end return. If the stack has been used up, a message to the effect that “the PARI stack overflows” is printed, and an error raised. Otherwise, it sets the type and length of the PARI object. In effect, it fills its first codeword (`z[0]`). Many PARI objects also have a second codeword (types `t_INT`, `t_REAL`, `t_PADIC`, `t_POL`, and `t_SER`). In case you want to produce one of those from scratch, which should be exceedingly rare, *it is your responsibility to fill this second codeword*, either explicitly (using the macros described in Section 4.5), or implicitly using an assignment statement (using `gaffect`).

Note that the length argument `l` is predetermined for a number of types: 3 for types `t_INTMOD`, `t_FRAC`, `t_COMPLEX`, `t_POLMOD`, `t_RFRAC`, 4 for type `t_QUAD`, and 5 for type `t_PADIC` and `t_QFB`. However for the sake of efficiency, `cgetg` does not check this: disasters will occur if you give an incorrect length for those types.

Notes. 1) The main use of this function is create efficiently a constant object, or to prepare for later assignments (see Section 4.4.3). Most of the time you will use GEN objects as they are created and returned by PARI functions. In this case you do not need to use `cgetg` to create space to hold them.

2) For the creation of leaves, i.e. `t_INT` or `t_REAL`,

```
GEN cgeti(long length)
```

```
GEN cgetr(long prec)
```

should be used instead of `cgetg(length, t_INT)` and `cgetg(prec2lg(prec), t_REAL)` respectively. Finally

```
GEN cgetc(long prec)
```

creates a `t_COMPLEX` whose real and imaginary part are `t_REALs` allocated by `cgetr(prec)`.

Examples. 1) Both `z = cgeti(DEFAULTPREC)` and `cgetg(DEFAULTPREC, t_INT)` create a `t_INT` whose “precision” is `bit_accuracy(DEFAULTPREC) = 64`. This means `z` can hold rational integers of absolute value less than 2^{64} . Note that in both cases, the second codeword is *not* filled. Of course we could use numerical values, e.g. `cgeti(4)`, but this would have different meanings on different machines as `bit_accuracy(4)` equals 64 on 32-bit machines, but 128 on 64-bit machines.

2) The following creates a *complex number* whose real and imaginary parts can hold real numbers of precision `bit_accuracy(MEDDEFAULTPREC) = 96` bits:

```
z = cgetg(3, t_COMPLEX);
gel(z, 1) = cgetr(MEDDEFAULTPREC);
gel(z, 2) = cgetr(MEDDEFAULTPREC);
```

or simply `z = cgetc(MEDDEFAULTPREC)`.

3) To create a matrix object for 4×3 matrices:

```
z = cgetg(4, t_MAT);
for(i=1; i<4; i++) gel(z, i) = cgetg(5, t_COL);
```

or simply `z = zeromatcopy(4, 3)`, which further initializes all entries to `gen_0`.

These last two examples illustrate the fact that since PARI types are recursive, all the branches of the tree must be created. The function `cgetg` creates only the “root”, and other calls to `cgetg` must be made to produce the whole tree. For matrices, a common mistake is to think that `z = cgetg(4, t_MAT)` (for example) creates the root of the matrix: one needs also to create the column vectors of the matrix (obviously, since we specified only one dimension in the first `cgetg`!). This is because a matrix is really just a row vector of column vectors (hence a priori not a basic type), but it has been given a special type number so that operations with matrices become possible.

Finally, to facilitate input of constant objects when speed is not paramount, there are four `varargs` functions:

`GEN mkintn(long n, ...)` returns the nonnegative `t_INT` whose expansion in base 2^{32} is given by the following n 32bit-words (unsigned int).

```
mkintn(3, a2, a1, a0);
```

returns $a_2 2^{64} + a_1 2^{32} + a_0$.

GEN `mkpoln(long n, ...)` Returns the `t_POL` whose n coefficients (GEN) follow, in order of decreasing degree.

```
mkpoln(3, gen_1, gen_2, gen_0);
```

returns the polynomial $X^2 + 2X$ (in variable 0, use `setvarn` if you want other variable numbers). Beware that n is the number of coefficients, hence *one more* than the degree.

GEN `mkvecn(long n, ...)` returns the `t_VEC` whose n coefficients (GEN) follow.

GEN `mkcoln(long n, ...)` returns the `t_COL` whose n coefficients (GEN) follow.

Warning. Contrary to the policy of general PARI functions, the latter three functions do *not* copy their arguments, nor do they produce an object a priori suitable for `gerepileupto`. For instance

```
/* gerepile-safe: components are universal objects */
z = mkvecn(3, gen_1, gen_0, gen_2);

/* not OK for gerepileupto: stoi(3) creates component before root */
z = mkvecn(3, stoi(3), gen_0, gen_2);

/* NO! First vector component x is destroyed */
x = gclone(gen_1);
z = mkvecn(3, x, gen_0, gen_2);
gunclone(x);
```

The following function is also available as a special case of `mkintn`:

GEN `uu32toi(ulong a, ulong b)`

Returns the GEN equal to $2^{32}a + b$, *assuming* that $a, b < 2^{32}$. This does not depend on `sizeof(long)`: the behavior is as above on both 32 and 64-bit machines.

4.4.2 Sizes.

`long gsizeword(GEN x)` returns the total number of `BITS_IN_LONG`-bit words occupied by the tree representing x .

`long gsizebyte(GEN x)` returns the total number of bytes occupied by the tree representing x , i.e. `gsizeword(x)` multiplied by `sizeof(long)`. This is normally useless since PARI functions use a number of *words* as input for lengths and precisions.

4.4.3 Assignments. Firstly, if x and y are both declared as GEN (i.e. pointers to something), the ordinary C assignment $y = x$ makes perfect sense: we are just moving a pointer around. However, physically modifying either x or y (for instance, $x[1] = 0$) also changes the other one, which is usually not desirable.

Very important note. Using the functions described in this paragraph is inefficient and often awkward: one of the **gerepile** functions (see Section 4.3) should be preferred. See the paragraph end for one exception to this rule.

The general PARI assignment function is the function **gaffect** with the following syntax:

```
void gaffect(GEN x, GEN y)
```

Its effect is to assign the PARI object **x** into the *preexisting* object **y**. Both **x** and **y** must be *scalar* types. For convenience, vector or matrices of scalar types are also allowed.

This copies the whole structure of **x** into **y** so many conditions must be met for the assignment to be possible. For instance it is allowed to assign a **t_INT** into a **t_REAL**, but the converse is forbidden. For that, you must use the truncation or rounding function of your choice, e.g. **mpfloor**.

It can also happen that **y** is not large enough or does not have the proper tree structure to receive the object **x**. For instance, let **y** the zero integer with length equal to 2; then **y** is too small to accommodate any nonzero **t_INT**. In general common sense tells you what is possible, keeping in mind the PARI philosophy which says that if it makes sense it is valid. For instance, the assignment of an imprecise object into a precise one does *not* make sense. However, a change in precision of imprecise objects is allowed, even if it *increases* its accuracy: we complement the “mantissa” with infinitely many 0 digits in this case. (Mantissa between quotes, because this is not restricted to **t_REALs**, it also applies for *p*-adics for instance.)

All functions ending in “z” such as **gaddz** (see Section 4.2.4) implicitly use this function. In fact what they exactly do is record **avma** (see Section 4.3), perform the required operation, **gaffect** the result to the last operand, then restore the initial **avma**.

You can assign ordinary C long integers into a PARI object (not necessarily of type **t_INT**) using

```
void gaffsg(long s, GEN y)
```

Note. Due to the requirements mentioned above, it is usually a bad idea to use **gaffect** statements. There is one exception: for simple objects (e.g. leaves) whose size is controlled, they can be easier to use than **gerepile**, and about as efficient.

Coercion. It is often useful to coerce an inexact object to a given precision. For instance at the beginning of a routine where precision can be kept to a minimum; otherwise the precision of the input is used in all subsequent computations, which is inefficient if the latter is known to thousands of digits. One may use the **gaffect** function for this, but it is easier and more efficient to call

GEN gtofp(GEN x, long prec) converts the complex number **x** (**t_INT**, **t_REAL**, **t_FRAC**, **t_QUAD** or **t_COMPLEX**) to either a **t_REAL** or **t_COMPLEX** whose components are **t_REAL** of length **prec**.

4.4.4 Copy. It is also very useful to copy a PARI object, not just by moving around a pointer as in the `y = x` example, but by creating a copy of the whole tree structure, without pre-allocating a possibly complicated `y` to use with `gaffect`. The function which does this is called `gcopy`. Its syntax is:

```
GEN gcopy(GEN x)
```

and the effect is to create a new copy of `x` on the PARI stack.

Sometimes, on the contrary, a quick copy of the skeleton of `x` is enough, leaving pointers to the original data in `x` for the sake of speed instead of making a full recursive copy. Use `GEN shallowcopy(GEN x)` for this. Note that the result is not suitable for `gerepileupto` !

Make sure at this point that you understand the difference between `y = x`, `y = gcopy(x)`, `y = shallowcopy(x)` and `gaffect(x,y)`.

4.4.5 Clones. Sometimes, it is more efficient to create a *persistent* copy of a PARI object. This is not created on the stack but on the heap, hence unaffected by `gerepile` and friends. The function which does this is called `gclone`. Its syntax is:

```
GEN gclone(GEN x)
```

A clone can be removed from the heap (thus destroyed) using

```
void guncclone(GEN x)
```

No PARI object should keep references to a clone which has been destroyed!

4.4.6 Conversions. The following functions convert C objects to PARI objects (creating them on the stack as usual):

```
GEN stoi(long s): C long integer ("small") to t_INT.
```

```
GEN dbltor(double s): C double to t_REAL. The accuracy of the result is 19 decimal digits, i.e. a type t_REAL of length DEFAULTPREC, although on 32-bit machines only 16 of them are significant.
```

We also have the converse functions:

```
long itos(GEN x): x must be of type t_INT,
```

```
double rtodbl(GEN x): x must be of type t_REAL,
```

as well as the more general ones:

```
long gtolong(GEN x),
```

```
double gtodouble(GEN x).
```

4.5 Implementation of the PARI types.

We now go through each type and explain its implementation. Let z be a `GEN`, pointing at a PARI object. In the following paragraphs, we will constantly mix two points of view: on the one hand, z is treated as the C pointer it is, on the other, as PARI's handle on some mathematical entity, so we will shamelessly write $z \neq 0$ to indicate that the *value* thus represented is nonzero (in which case the *pointer* z is certainly not NULL). We offer no apologies for this style. In fact, you had better feel comfortable juggling both views simultaneously in your mind if you want to write correct PARI programs.

Common to all the types is the first codeword $z[0]$, which we do not have to worry about since this is taken care of by `cgetg`. Its precise structure depends on the machine you are using, but it always contains the following data: the *internal type number* attached to the symbolic type name, the *length* of the root in longwords, and a technical bit which indicates whether the object is a clone or not (see Section 4.4.5). This last one is used by `gp` for internal garbage collecting, you will not have to worry about it.

Some types have a second codeword, different for each type, which we will soon describe as we will shortly consider each of them in turn.

The first codeword is handled through the following *macros*:

`long typ(GEN z)` returns the type number of z .

`void settyp(GEN z, long n)` sets the type number of z to n (you should not have to use this function if you use `cgetg`).

`long lg(GEN z)` returns the length (in longwords) of the root of z .

`long setlg(GEN z, long l)` sets the length of z to l ; you should not have to use this function if you use `cgetg`.

`void lg_increase(GEN z)` increase the length of z by 1; you should not have to use this function if you use `cgetg`.

`long isclone(GEN z)` is z a clone?

`void setisclone(GEN z)` sets the *clone* bit.

`void unsetisclone(GEN z)` clears the *clone* bit.

Important remark. For the sake of efficiency, none of the codeword-handling macros check the types of their arguments even when there are stringent restrictions on their use. It is trivial to create invalid objects, or corrupt one of the “universal constants” (e.g. setting the sign of `gen_0` to 1), and they usually provide negligible savings. Use higher level functions whenever possible.

Remark. The clone bit is there so that `gunclone` can check it is deleting an object which was allocated by `gclone`. Miscellaneous vector entries are often cloned by `gp` so that a GP statement like $v[1] = x$ does not involve copying the whole of v : the component $v[1]$ is deleted if its clone bit is set, and is replaced by a clone of x . Don't set/unset yourself the clone bit unless you know what you are doing: in particular *never* set the clone bit of a vector component when the said vector is scheduled to be uncloned. Hackish code may abuse the clone bit to tag objects for reasons unrelated to the above instead of using proper data structures. Don't do that.

4.5.1 Type `t_INT (integer)`. this type has a second codeword `z[1]` which contains the following information:

the sign of `z`: coded as 1, 0 or -1 if $z > 0$, $z = 0$, $z < 0$ respectively.

the *effective length* of `z`, i.e. the total number of significant longwords. This means the following: apart from the integer 0, every integer is “normalized”, meaning that the most significant mantissa longword is nonzero. However, the integer may have been created with a longer length. Hence the “length” which is in `z[0]` can be larger than the “effective length” which is in `z[1]`.

This information is handled using the following macros:

`long signe(GEN z)` returns the sign of `z`.

`void setsigne(GEN z, long s)` sets the sign of `z` to `s`.

`long lgefint(GEN z)` returns the effective length of `z`.

`void setlgefint(GEN z, long l)` sets the effective length of `z` to `l`.

The integer 0 can be recognized either by its sign being 0, or by its effective length being equal to 2. Now assume that $z \neq 0$, and let

$$|z| = \sum_{i=0}^n z_i B^i, \quad \text{where } z_n \neq 0 \text{ and } B = 2^{\text{BITS_IN_LONG}}.$$

With these notations, n is `lgefint(z) - 3`, and the mantissa of `z` may be manipulated via the following interface:

`GEN int_MSW(GEN z)` returns a pointer to the most significant word of `z`, z_n .

`GEN int_LSW(GEN z)` returns a pointer to the least significant word of `z`, z_0 .

`GEN int_W(GEN z, long i)` returns the i -th significant word of `z`, z_i . Accessing the i -th significant word for $i > n$ yields unpredictable results.

`GEN int_W_lg(GEN z, long i, long lz)` returns the i -th significant word of `z`, z_i , assuming `lgefint(z)` is `lz` ($= n + 3$). Accessing the i -th significant word for $i > n$ yields unpredictable results.

`GEN int_precW(GEN z)` returns the previous (less significant) word of `z`, z_{i-1} assuming `z` points to z_i .

`GEN int_nextW(GEN z)` returns the next (more significant) word of `z`, z_{i+1} assuming `z` points to z_i .

Unnormalized integers, such that z_n is possibly 0, are explicitly forbidden. To enforce this, one may write an arbitrary mantissa then call

`void int_normalize(GEN z, long known0)`

normalizes in place a nonnegative integer (such that z_n is possibly 0), assuming at least the first `known0` words are zero.

For instance a binary `and` could be implemented in the following way:

```
GEN AND(GEN x, GEN y) {
    long i, lx, ly, lout;
```

```

long *xp, *yp, *outp; /* mantissa pointers */
GEN out;
if (!signe(x) || !signe(y)) return gen_0;
lx = lgefint(x); xp = int_LSW(x);
ly = lgefint(y); yp = int_LSW(y); lout = min(lx,ly); /* > 2 */
out = cgeti(lout); out[1] = evalsigne(1) | evallgefint(lout);
outp = int_LSW(out);
for (i=2; i < lout; i++)
{
    *outp = (*xp) & (*yp);
    outp = int_nextW(outp);
    xp = int_nextW(xp);
    yp = int_nextW(yp);
}
if ( !*int_MSW(out) ) out = int_normalize(out, 1);
return out;
}

```

This low-level interface is mandatory in order to write portable code since PARI can be compiled using various multiprecision kernels, for instance the native one or GNU MP, with incompatible internal structures (for one thing, the mantissa is oriented in different directions).

4.5.2 Type `t_REAL` (real number). this type has a second codeword `z[1]` which also encodes its sign, obtained or set using the same functions as for a `t_INT`, and a binary exponent. This exponent is handled using the following macros:

`long expo(GEN z)` returns the exponent of `z`. This is defined even when `z` is equal to zero.

`void setexpo(GEN z, long e)` sets the exponent of `z` to `e`.

Note the functions:

`long gexpo(GEN z)` which tries to return an exponent for `z`, even if `z` is not a real number.

`long gsigne(GEN z)` which returns a sign for `z`, even when `z` is a real number of type `t_INT`, `t_FRAC` or `t_REAL`, an infinity (`t_INFINITY`) or a `t_QUAD` of positive discriminant.

The real zero is characterized by having its sign equal to 0. If `z` is not equal to 0, then it is represented as $2^e M$, where e is the exponent, and $M \in [1, 2[$ is the mantissa of z , whose digits are stored in `z[2], ..., z[lg(z) - 1]`. But keep in mind that the accuracy of `t_REAL` actually increases by increments of `BITS_IN_LONG`bits.

More precisely, let m be the integer $(z[2], \dots, z[lg(z)-1])$ in base $2^{\text{BITS_IN_LONG}}$; here, `z[2]` is the most significant longword and is normalized, i.e. its most significant bit is 1. Then we have $M := m / 2^{\text{bit_accuracy}(\lg(z)) - 1 - \text{expo}(z)}$.

`GEN mantissa_real(GEN z, long *e)` returns the mantissa m of z , and sets `*e` to the exponent $\text{realprec}(z) - 1 - \text{expo}(z)$, so that $z = m / 2^e$.

Thus, the real number 3.5 to accuracy $\text{realprec}(z)$ is represented as `z[0]` (encoding `type = t_REAL, lg(z)`), `z[1]` (encoding `sign = 1, expo = 1`), `z[2] = 0xe0000000`, `z[3] = ... = z[lg(z) - 1] = 0x0`.

4.5.3 Type $\mathbf{t_INTMOD}$. $\mathbf{z[1]}$ points to the modulus, and $\mathbf{z[2]}$ at the number representing the class \mathbf{z} . Both are separate GEN objects, and both must be $\mathbf{t_INT}$ s, satisfying the inequality $0 \leq \mathbf{z[2]} < \mathbf{z[1]}$.

4.5.4 Type $\mathbf{t_FRAC}$ (rational number). $\mathbf{z[1]}$ points to the numerator n , and $\mathbf{z[2]}$ to the denominator d . Both must be of type $\mathbf{t_INT}$ such that $n \neq 0$, $d > 0$ and $(n, d) = 1$.

4.5.5 Type $\mathbf{t_FFELT}$ (finite field element). (Experimental)

Components of this type should normally not be accessed directly. Instead, finite field elements should be created using `ffgen`.

The second codeword $\mathbf{z[1]}$ determines the storage format of the element, among

- $\mathbf{t_FF_FpXq}$: $\mathbf{A}=\mathbf{z[2]}$ and $\mathbf{T}=\mathbf{z[3]}$ are \mathbf{FpX} , $\mathbf{p}=\mathbf{z[4]}$ is a $\mathbf{t_INT}$, where p is a prime number, T is irreducible modulo p , and $\deg A < \deg T$. This represents the element $A \pmod{T}$ in $\mathbf{F}_p[X]/T$.
- $\mathbf{t_FF_Flxq}$: $\mathbf{A}=\mathbf{z[2]}$ and $\mathbf{T}=\mathbf{z[3]}$ are \mathbf{Flx} , $\mathbf{l}=\mathbf{z[4]}$ is a $\mathbf{t_INT}$, where l is a prime number, T is irreducible modulo l , and $\deg A < \deg T$. This represents the element $A \pmod{T}$ in $\mathbf{F}_l[X]/T$.
- $\mathbf{t_FF_F2xq}$: $\mathbf{A}=\mathbf{z[2]}$ and $\mathbf{T}=\mathbf{z[3]}$ are $\mathbf{F2x}$, $\mathbf{l}=\mathbf{z[4]}$ is the $\mathbf{t_INT}$ 2, T is irreducible modulo 2, and $\deg A < \deg T$. This represents the element $A \pmod{T}$ in $\mathbf{F}_2[X]/T$.

4.5.6 Type $\mathbf{t_COMPLEX}$ (complex number). $\mathbf{z[1]}$ points to the real part, and $\mathbf{z[2]}$ to the imaginary part. The components $\mathbf{z[1]}$ and $\mathbf{z[2]}$ must be of type $\mathbf{t_INT}$, $\mathbf{t_REAL}$ or $\mathbf{t_FRAC}$. For historical reasons $\mathbf{t_INTMOD}$ and $\mathbf{t_PADIC}$ are also allowed (the latter for $p = 2$ or congruent to 3 mod 4 only), but one should rather use the more general $\mathbf{t_POLMOD}$ construction.

4.5.7 Type $\mathbf{t_PADIC}$ (p -adic numbers). this type has a second codeword $\mathbf{z[1]}$ which contains the following information: the p -adic precision (the exponent of p modulo which the p -adic unit corresponding to \mathbf{z} is defined if \mathbf{z} is not 0), i.e. one less than the number of significant p -adic digits, and the exponent of \mathbf{z} . This information can be handled using the following functions:

`long precp(GEN z)` returns the p -adic precision of \mathbf{z} . This is 0 if $\mathbf{z} = 0$.

`void setprecp(GEN z, long l)` sets the p -adic precision of \mathbf{z} to l .

`long valp(GEN z)` returns the p -adic valuation of \mathbf{z} (i.e. the exponent). This is defined even if \mathbf{z} is equal to 0.

`void setvalp(GEN z, long e)` sets the p -adic valuation of \mathbf{z} to e .

In addition to this codeword, $\mathbf{z[2]}$ points to the prime p , $\mathbf{z[3]}$ points to $p^{\text{precp}(\mathbf{z})}$, and $\mathbf{z[4]}$ points to a $\mathbf{t_INT}$ representing the p -adic unit attached to \mathbf{z} modulo $\mathbf{z[3]}$ (and to zero if \mathbf{z} is zero). To summarize, if $z \neq 0$, we have the equality:

$$\mathbf{z} = p^{\text{valp}(\mathbf{z})} * (\mathbf{z[4]} + O(\mathbf{z[3]})), \quad \text{where} \quad \mathbf{z[3]} = p^{\text{precp}(\mathbf{z})}.$$

4.5.8 Type $\mathbf{t_QUAD}$ (quadratic number). $\mathbf{z[1]}$ points to the canonical polynomial P defining the quadratic field (as output by `quadpoly`), $\mathbf{z[2]}$ to the “real part” and $\mathbf{z[3]}$ to the “imaginary part”. The latter are of type $\mathbf{t_INT}$, $\mathbf{t_FRAC}$, $\mathbf{t_INTMOD}$, or $\mathbf{t_PADIC}$ and are to be taken as the coefficients of \mathbf{z} with respect to the canonical basis $(1, X)$ of $\mathbf{Q}[X]/(P(X))$. Exact complex numbers may be implemented as quadratics, but $\mathbf{t_COMPLEX}$ is in general more versatile ($\mathbf{t_REAL}$ components are allowed) and more efficient.

Operations involving a $\mathbf{t_QUAD}$ and $\mathbf{t_COMPLEX}$ are implemented by converting the $\mathbf{t_QUAD}$ to a $\mathbf{t_REAL}$ (or $\mathbf{t_COMPLEX}$ with $\mathbf{t_REAL}$ components) to the accuracy of the $\mathbf{t_COMPLEX}$. As a consequence, operations between $\mathbf{t_QUAD}$ and *exact* $\mathbf{t_COMPLEX}$ s are not allowed.

4.5.9 Type `t_POLMOD` (`polmod`). as for `t_INTMODs`, `z[1]` points to the modulus, and `z[2]` to a polynomial representing the class of `z`. Both must be of type `t_POL` in the same variable, satisfying the inequality $\deg z[2] < \deg z[1]$. However, `z[2]` is allowed to be a simplification of such a polynomial, e.g. a scalar. This is tricky considering the hierarchical structure of the variables; in particular, a polynomial in variable of *lesser* priority (see Section 4.6) than the modulus variable is valid, since it is considered as the constant term of a polynomial of degree 0 in the correct variable. On the other hand a variable of *greater* priority is not acceptable.

4.5.10 Type `t_POL` (`polynomial`). this type has a second codeword. It contains a “*sign*”: 0 if the polynomial is equal to 0, and 1 if not (see however the important remark below) and a *variable number* (e.g. 0 for x , 1 for y , etc. ...).

These data can be handled with the following macros: **`signe`** and **`setsigne`** as for `t_INT` and `t_REAL`,
`long varn(GEN z)` returns the variable number of the object `z`,
`void setvarn(GEN z, long v)` sets the variable number of `z` to `v`.

The variable numbers encode the relative priorities of variables, we will give more details in Section 4.6. Note also the function `long gvar(GEN z)` which tries to return a variable number for `z`, even if `z` is not a polynomial or power series. The variable number of a scalar type is set by definition equal to `NO_VARIABLE`, which has lower priority than any other variable number.

The components `z[2]`, `z[3]`, ... `z[lg(z)-1]` point to the coefficients of the polynomial *in ascending order*, with `z[2]` being the constant term and so on.

For a `t_POL` of nonzero sign, `degpol`, `leading_coeff`, `constant_coeff`, return its degree, and a pointer to the leading, resp. constant, coefficient with respect to the main variable. Note that no copy is made on the PARI stack so the returned value is not safe for a basic `gerepile` call. Applied to any other type than `t_POL`, the result is unspecified. Those three functions are still defined when the sign is 0, see Section 5.2.7 and Section 10.6.

`long degree(GEN x)` returns the degree of `x` with respect to its main variable even when `x` is not a polynomial (a rational function for instance). By convention, the degree of a zero polynomial is -1 .

Important remark. The leading coefficient of a `t_POL` may be equal to zero:

- it is not allowed to be an exact rational 0, such as `gen_0`;
- an exact nonrational 0, like `Mod(0,2)`, is possible for constant polynomials, i.e. of length 3 and no other coefficient: this carries information about the base ring for the polynomial;
- an inexact 0, like `0.E-38` or `0(3^5)`, is always possible. Inexact zeroes do not correspond to an actual 0, but to a very small coefficient according to some metric; we keep them to give information on how much cancellation occurred in previous computations.

A polynomial disobeying any of these rules is an invalid *unnormalized* object. We advise *not* to use low-level constructions to build a `t_POL` coefficient by coefficient, such as

```
GEN T = cgetg(4, t_POL);
T[1] = evalvarn(0);
gel(T, 2) = x;
gel(T, 3) = y;
```

But if you do and it is not clear whether the result will be normalized, call

`GEN normalizepol(GEN x)` applied to an unnormalized `t_POL` `x` (with all coefficients correctly set except that `leading_term(x)` might be zero), normalizes `x` correctly in place and returns `x`. This function sets `signe` (to 0 or 1) properly.

Caveat. A consequence of the remark above is that zero polynomials are characterized by the fact that their sign is 0. It is in general incorrect to check whether `lg(x)` is 2 or `degpol(x) < 0`, although both tests are valid when the coefficient types are under control: for instance, when they are guaranteed to be `t_INTs` or `t_FRACs`. The same remark applies to `t_SERs`.

4.5.11 Type `t_SER` (power series). This type also has a second codeword, which encodes a “*sign*”, i.e. 0 if the power series is 0, and 1 if not, a *variable number* as for polynomials, and an *exponent*. This information can be handled with the following functions: `signe`, `setsigne`, `varn`, `setvarn` as for polynomials. Beware: do *not* use `expo` and `setexpo` on power series.

`long valser(GEN z)` returns the valuation of `z`. This is defined even if `z` is equal to 0.

`void setvalser(GEN z, long e)` sets the valuation of `z` to `e`.

The coefficients `z[2]`, `z[3]`, ..., `z[lg(z)-1]` point to the coefficients of `z` in ascending order. As for polynomials (see remark there), the sign of a `t_SER` is 0 if and only if all its coefficients are equal to 0. (The leading coefficient cannot be an integer 0.) A series whose coefficients are integers equal to zero is represented as $O(x^n)$ (`zeroser(vx, n)`). A series whose coefficients are exact zeroes, but not all of them integers (e.g. an `t_INTMOD` such as `Mod(0, 2)`) is represented as $z * x^{n-1} + O(x^n)$, where `z` is the 0 of the base ring, as per `Rg_get_0`.

Note that the exponent of a power series can be negative, i.e. we are then dealing with a Laurent series (with a finite number of negative terms).

4.5.12 Type `t_RFRAC` (rational function). `z[1]` points to the numerator n , and `z[2]` on the denominator d . The denominator must be of type `t_POL`, with variable of priority at least as high as that of the numerator. The numerator n is not an exact 0 and $(n, d) = 1$ (see `gred_rfac2`).

4.5.13 Type `t_QFB` (binary quadratic form). `z[1]`, `z[2]`, `z[3]` point to the three coefficients of the form, and `z[4]` point to the form discriminant. All four are of type `t_INT`.

4.5.14 Type `t_VEC` and `t_COL` (vector). `z[1]`, `z[2]`, ..., `z[lg(z)-1]` point to the components of the vector.

4.5.15 Type `t_MAT` (matrix). `z[1]`, `z[2]`, ..., `z[lg(z)-1]` point to the column vectors of `z`, i.e. they must be of type `t_COL` and of the same length.

4.5.16 Type `t_VECSMALL` (vector of small integers). `z[1]`, `z[2]`, ..., `z[lg(z)-1]` are ordinary signed long integers. This type is used instead of a `t_VEC` or `t_INTs` for efficiency reasons, for instance to implement efficiently permutations, polynomial arithmetic and linear algebra over small finite fields, etc.

4.5.17 Type `t_STR` (character string).

`char * GSTR(z)` (`= (z+1)`) points to the first character of the (NULL-terminated) string.

4.5.18 Type `t_ERROR` (error context). This type holds error messages, as well as details about the error, as returned by the exception handling system. The second codeword `z[1]` contains the error type (an `int`, as passed to `pari_err`). The subsequent words `z[2], ..., z[lg(z)-1]` are GENs containing additional data, depending on the error type.

4.5.19 Type `t_CLOSURE` (closure). This type holds GP functions and closures, in compiled form. The internal detail of this type is subject to change each time the GP language evolves. Hence we do not describe it here and refer to the Developer’s Guide. However functions to create or to evaluate `t_CLOSURE`s are documented in Section 12.1.

`long closure_arity(GEN C)` returns the arity of the `t_CLOSURE`.

`long closure_is_variadic(GEN C)` returns 1 if the closure `C` is variadic, 0 else.

4.5.20 Type `t_INFINITY` (infinity).

This type has a single `t_INT` component, which is either 1 or -1 , corresponding to $+\infty$ and $-\infty$ respectively.

`GEN mkmoo()` returns $-\infty$

`GEN mkoo()` returns ∞

`long inf_get_sign(GEN x)` returns 1 if x is $+\infty$, and -1 if x is $-\infty$.

4.5.21 Type `t_LIST` (list). this type was introduced for specific `gp` use and is rather inefficient compared to a straightforward linked list implementation (it requires more memory, as well as many unnecessary copies). Hence we do not describe it here and refer to the Developer’s Guide.

Implementation note. For the types including an exponent (or a valuation), we actually store a biased nonnegative exponent (bit-ORing the biased exponent to the codeword), obtained by adding a constant to the true exponent: either `HIGHEXPBIT` (for `t_REAL`) or `HIGHVALPBIT` (for `t_PADIC` and `t_SER`). Of course, this is encapsulated by the exponent/valuation-handling macros and needs not concern the library user.

4.6 PARI variables.

4.6.1 Multivariate objects.

We now consider variables and formal computations. As we have seen in Section 4.5, the codewords for types `t_POL` and `t_SER` encode a “variable number”. This is an integer, ranging from 0 to `MAXVARN`. Relative priorities may be ascertained using

`int varncmp(long v, long w)`

which is > 0 , $= 0$, < 0 whenever v has lower, resp. same, resp. higher priority than w .

The way an object is considered in formal computations depends entirely on its “principal variable number” which is given by the function

`long gvar(GEN z)`

which returns a variable number for z , even if z is not a polynomial or power series. The variable number of a scalar type is set by definition equal to `NO_VARIABLE` which has lower priority than any

valid variable number. The variable number of a recursive type which is not a polynomial or power series is the variable number with highest priority among its components. But for polynomials and power series only the “outermost” number counts (we directly access `varn(x)` in the codewords): the representation is not symmetrical at all.

Under `gp`, one needs not worry too much since the interpreter defines the variables as it sees them* and do the right thing with the polynomials produced.

But in library mode, they are tricky objects if you intend to build polynomials yourself (and not just let PARI functions produce them, which is less efficient). For instance, it does not make sense to have a variable number occur in the components of a polynomial whose main variable has a lower priority, even though PARI cannot prevent you from doing it.

4.6.2 Creating variables. A basic difficulty is to “create” a variable. Some initializations are needed before you can use a given integer v as a variable number.

Initially, this is done for 0 and 1 (the variables `x` and `y` under `gp`), and $2, \dots, 9$ (printed as `t2`, `...t9`), with decreasing priority.

4.6.2.1 User variables. When the program starts, `x` (number 0) and `y` (number 1) are the only available variables, numbers 2 to 9 (decreasing priority) are reserved for building polynomials with predictable priorities.

To define further ones, you may use

```
GEN varhigher(const char *s)
```

```
GEN varlower(const char *s)
```

to recover a monomial of degree 1 in a new variable, which is guaranteed to have higher (resp. lower) priority than all existing ones at the time of the function call. The variable is printed as `s`, but is not part of GP’s interpreter: it is not a symbol bound to a value.

On the other hand

`long fetch_user_var(char *s)`: inspects the user variable whose name is the string pointed to by `s`, creating it if needed, and returns its variable number.

```
long v = fetch_user_var("y");
GEN gy = pol_x(v);
```

The function raises an exception if the name is already in use for an `installed` or built-in function, or an alias. This function is mostly useless since it returns a variable with unpredictable priority. Don’t use it to create new variables.

* The first time a given identifier is read by the GP parser a new variable is created, and it is assigned a strictly lower priority than any variable in use at this point. On startup, before any user input has taken place, `x` is defined in this way and has initially maximal priority (and variable number 0).

Caveat. You can use `gp_read_str` (see Section 4.7.1) to execute a GP command and create GP variables on the fly as needed:

```
GEN gy = gp_read_str("'y"); /* returns pol_x(v), for some v */
long v = varn(gy);
```

But please note the quote 'y in the above. Using `gp_read_str("y")` might work, but is dangerous, especially when programming functions to be used under `gp`. The latter reads the value of `y`, as *currently* known by the `gp` interpreter, possibly creating it in the process. But if `y` has been modified by previous `gp` commands (e.g. `y = 1`), then the value of `gy` is not what you expected it to be and corresponds instead to the current value of the `gp` variable (e.g. `gen_1`).

`GEN fetch_var_value(long v)` returns a shallow copy of the current value of the variable numbered `v`. Returns `NULL` if that variable number is unknown to the interpreter, e.g. it is a user variable. Note that this may not be the same as `pol_x(v)` if assignments have been performed in the interpreter.

4.6.2.2 Temporary variables. You can create temporary variables using

`long fetch_var()` returns a new variable with *lower* priority than any variable currently in use.

`long fetch_var_higher()` returns a new variable with *higher* priority than any variable currently in use.

After the statement `v = fetch_var()`, you can use `pol_1(v)` and `pol_x(v)`. The variables created in this way have no identifier assigned to them though, and are printed as `tnumber`. You can assign a name to a temporary variable, after creating it, by calling the function

```
void name_var(long n, char *s)
```

after which the output machinery will use the name `s` to represent the variable number `n`. The GP parser will *not* recognize it by that name, however, and calling this on a variable known to `gp` raises an error. Temporary variables are meant to be used as free variables to build polynomials and power series, and you should never assign values or functions to them as you would do with variables under `gp`. For that, you need a user variable.

All objects created by `fetch_var` are on the heap and not on the stack, thus they are not subject to standard garbage collecting (they are not destroyed by a `gerepile` or `set_avma(ltop)` statement). When you do not need a variable number anymore, you can delete it using

```
long delete_var()
```

which deletes the *latest* temporary variable created and returns the variable number of the previous one (or simply returns 0 if none remain). Of course you should make sure that the deleted variable does not appear anywhere in the objects you use later on. Here is an example:

```
long first = fetch_var();
long n1 = fetch_var();
long n2 = fetch_var(); /* prepare three variables for internal use */
...
/* delete all variables before leaving */
do { num = delete_var(); } while (num && num <= first);
```

The (dangerous) statement

```
while (delete_var()) /* empty */;
```

removes all temporary variables in use.

4.6.3 Comparing variables.

Let us go back to `varncmp`. There is an interesting corner case, when one of the compared variables (from `gvar`, say) is `NO_VARIABLE`. In this case, `varncmp` declares it has lower priority than any other variable; of course, comparing `NO_VARIABLE` with itself yields 0 (same priority);

In addition to `varncmp` we have

`long varnmax(long v, long w)` given two variable numbers (possibly `NO_VARIABLE`), returns the variable with the highest priority. This function always returns a valid variable number unless it is comparing `NO_VARIABLE` to itself.

`long varnmin(long x, long y)` given two variable numbers (possibly `NO_VARIABLE`), returns the variable with the lowest priority. Note that when comparing a true variable with `NO_VARIABLE`, this function returns `NO_VARIABLE`, which is not a valid variable number.

4.7 Input and output.

Two important aspects have not yet been explained which are specific to library mode: input and output of PARI objects.

4.7.1 Input.

For input, PARI provides several powerful high level functions which enable you to input your objects as if you were under `gp`. In fact, it *is* essentially the GP syntactical parser.

There are two similar functions available to parse a string:

```
GEN gp_read_str(const char *s)
```

```
GEN gp_read_str_multiline(const char *s, char *last)
```

Both functions read the whole string `s`. The function `gp_read_str` ignores newlines: it assumes that the input is one expression and returns the result of this expression.

The function `gp_read_str_multiline` processes the text in the same way as the GP command `read`: newlines are significant and can be used to separate expressions. The return value is that of the last nonempty expression evaluated.

In `gp_read_str_multiline`, if `last` is not NULL, then `*last` receives the last character from the *filtered* input: this can be used to check if the last character was a semi-colon (to hide the output in interactive usage). If (and only if) the input contains no statements, then `*last` is set to 0.

For both functions, `gp`'s metacommands *are* recognized.

Two variants allow to specify a default precision while evaluating the string:

```
GEN gp_read_str_prec(const char *s, long prec) As gp_read_str, but set the precision to prec words while evaluating s.
```

```
GEN gp_read_str_bitprec(const char *s, long bitprec) identical to gp_read_str_prec.  
DEPRECATED.
```

Note. The obsolete form

```
GEN readseq(char *t)
```

still exists for backward compatibility (assumes filtered input, without spaces or comments). Don't use it.

To read a GEN from a file, you can use the simpler interface

```
GEN gp_read_stream(FILE *file)
```

which reads a character string of arbitrary length from the stream `file` (up to the first complete expression sequence), applies `gp_read_str` to it, and returns the resulting GEN. This way, you do not have to worry about allocating buffers to hold the string. To interactively input an expression, use `gp_read_stream(stdin)`. Return NULL when there are no more expressions to read (we reached EOF).

Finally, you can read in a whole file, as in GP's `read` statement

```
GEN gp_read_file(char *name)
```

As usual, the return value is that of the last nonempty expression evaluated. There is one technical exception: if `name` is a *binary* file (from `writebin`) containing more than one object, a `t_VEC` containing them all is returned. This is because binary objects bypass the parser, hence reading them has no useful side effect.

4.7.2 Output to screen or file, output to string.

General output functions return nothing but print a character string as a side effect. Low level routines are available to write on PARI output stream `pari_outfile` (`stdout` by default):

`void pari_putc(char c):` write character `c` to the output stream.

`void pari_puts(char *s):` write `s` to the output stream.

`void pari_flush():` flush output stream; most streams are buffered by default, this command makes sure that all characters output so are actually written.

`void pari_printf(const char *fmt, ...):` the most versatile such function. `fmt` is a character string similar to the one `printf` uses. In there, `%` characters have a special meaning, and describe how to print the remaining operands. In addition to the standard format types (see the GP function `printf`), you can use the *length modifier* `P` (for PARI of course!) to specify that an argument is a GEN. For instance, the following are valid conversions for a GEN argument

<code>%Ps</code>	<i>convert to char* (will print an arbitrary GEN)</i>
<code>%P.10s</code>	<i>convert to char*, truncated to 10 chars</i>
<code>%P.2f</code>	<i>convert to floating point format with 2 decimals</i>
<code>%P4d</code>	<i>convert to integer, field width at least 4</i>

```
pari_printf("x[%d] = %Ps is not invertible!\n", i, gel(x,i));
```

Here `i` is an `int`, `x` a GEN which is not a leaf (presumably a vector, or a polynomial) and this would insert the value of its *i*-th GEN component: `gel(x,i)`.

Simple but useful variants to `pari_printf` are

`void output(GEN x)` prints `x` in raw format, followed by a newline and a buffer flush. This is more or less equivalent to

```

    pari_printf("%Ps\n", x);
    pari_flush();

```

`void outmat(GEN x)` as above except if x is a `t_MAT`, in which case a multi-line display is used to display the matrix. This is prettier for small dimensions, but quickly becomes unreadable and cannot be pasted and reused for input. If all entries of x are small integers, you may use the recursive features of `%Pd` and obtain the same (or better) effect with

```

    pari_printf("%Pd\n", x);
    pari_flush();

```

A variant like `%5Pd` would improve alignment by imposing 5 chars for each coefficient. Similarly if all entries are to be converted to floats, a format like `%5.1Pf` could be useful.

These functions write on (PARI's idea of) standard output, and must be used if you want your functions to interact nicely with `gp`. In most programs, this is not a concern and it is more flexible to write to an explicit `FILE*`, or to recover a character string:

`void pari_fprintf(FILE *file, const char *fmt, ...)` writes the remaining arguments to stream `file` according to the format specification `fmt`.

`char* pari_sprintf(const char *fmt, ...)` produces a string from the remaining arguments, according to the PARI format `fmt` (see `printf`). This is the `libpari` equivalent of `strprintf`, and returns a `malloc`'ed string, which must be freed by the caller. Note that contrary to the analogous `sprintf` in the `libc` you do not provide a buffer (leading to all kinds of buffer overflow concerns); the function provided is actually closer to the GNU extension `asprintf`, although the latter has a different interface.

Simple variants of `pari_sprintf` convert a `GEN` to a `malloc`'ed ASCII string, which you must still `free` after use:

`char* GENTostr(GEN x)`, using the current default output format (`prettymat` by default).

`char* GENToTeXstr(GEN x)`, suitable for inclusion in a `TeX` file.

Note that we have `va_list` analogs of the functions of `printf` type seen so far:

```

void pari_vprintf(const char *fmt, va_list ap)
void pari_vfprintf(FILE *file, const char *fmt, va_list ap)
char* pari_vsprintf(const char *fmt, va_list ap)

```

4.7.3 Errors.

If you want your functions to issue error messages, you can use the general error handling routine `pari_err`. The basic syntax is

```

    pari_err(e_MISC, "error message");

```

This prints the corresponding error message and exits the program (in library mode; go back to the `gp` prompt otherwise). You can also use it in the more versatile guise

```

    pari_err(e_MISC, format, ...);

```

where `format` describes the format to use to write the remaining operands, as in the `pari_printf` function. For instance:

```

    pari_err(e_MISC, "x[%d] = %Ps is not invertible!", i, gel(x,i));

```

The simple syntax seen above is just a special case with a constant format and no remaining arguments. The general syntax is

```
void pari_err(numerr, ...)
```

where `numerr` is a codeword which specifies the error class and what to do with the remaining arguments and what message to print. For instance, if `x` is a `GEN` with internal type `t_STR`, say, `pari_err(e_TYPE, "extgcd", x)` prints the message:

```
***      incorrect type in extgcd (t_STR),
```

See Section 11.4 for details. In the libpari code itself, the general-purpose `e_MISC` is used sparingly: it is so flexible that the corresponding error contexts (`t_ERROR`) become hard to use reliably. Other more rigid error types are generally more useful: for instance the error context attached to the `e_TYPE` exception above is precisely documented and contains `"extgcd"` and `x` (not only its type) as readily available components.

4.7.4 Warnings.

To issue a warning, use

`void pari_warn(warnerr, ...)` In that case, of course, we do *not* abort the computation, just print the requested message and go on. The basic example is

```
pari_warn(warner, "Strategy 1 failed. Trying strategy 2")
```

which is the exact equivalent of `pari_err(e_MISC, ...)` except that you certainly do not want to stop the program at this point, just inform the user that something important has occurred; in particular, this output would be suitably highlighted under `gp`, whereas a simple `printf` would not.

The valid *warning* keywords are `warner` (general), `warnprec` (increasing precision), `warnmem` (garbage collecting) and `warnfile` (error in file operation), used as follows:

```
pari_warn(warnprec, "bnfinit", newprec);
pari_warn(warnmem, "bnfinit");
pari_warn(warnfile, "close", "afile"); /* error when closing "afile" */
```

4.7.5 Debugging output.

For debugging output, you can use the standard output functions, `output` and `pari_printf` mainly. Corresponding to the `gp` metacommand `\x`, you can also output the hexadecimal tree attached to an object:

`void dbgGEN(GEN x, long nb = -1)`, displays the recursive structure of `x`. If `nb = -1`, the full structure is printed, otherwise the leaves (nonrecursive components) are truncated to `nb` words.

The function `output` is vital under debuggers, since none of them knows how to print PARI objects by default. Seasoned PARI developers add the following `gdb` macro to their `.gdbinit`:

```
define oo
  call output((GEN)$arg0)
end
define xx
  call dbgGEN($arg0, -1)
end
```


Typing `i x` at a breakpoint in `gdb` then prints the value of the `GEN x` (provided the optimizer has not put it into a register, but it is rarely a good idea to debug optimized code).

The global variables **DEBUGLEVEL** and **DEBUGMEM** (corresponding to the default **debug** and **debugmem**) are used throughout the PARI code to govern the amount of diagnostic and debugging output, depending on their values. You can use them to debug your own functions, especially if you install the latter under `gp`. Note that **DEBUGLEVEL** is redefined in each code module, attaching it to a particular debug domain (see `setdebug`).

`void setalldebug(long L)` sets all **DEBUGLEVEL** incarnations (all debug domains) to `L`.

`void dbg_pari_heap(void)` print debugging statements about the PARI stack, heap, and number of variables used. Corresponds to `\s` under `gp`.

4.7.6 Timers and timing output.

To handle timings in a reentrant way, PARI defines a dedicated data type, `pari_timer`, together with the following methods:

`void timer_start(pari_timer *T)` start (or reset) a timer.

`long timer_delay(pari_timer *T)` returns the number of milliseconds elapsed since the timer was last reset. Resets the timer as a side effect. Assume `T` was started by `timer_start`.

`long timer_get(pari_timer *T)` returns the number of milliseconds elapsed since the timer was last reset. Does *not* reset the timer. Assume `T` was started by `timer_start`.

`void walltimer_start(pari_timer *T)` start a timer, as if it had been started at the Unix epoch (see `getwalltime`).

`long walltimer_delay(pari_timer *T)` returns the number of milliseconds elapsed since the timer was last checked. Assume `T` was started by `walltimer_start`.

`long walltimer_get(pari_timer *T)` returns the number of milliseconds elapsed since the timer was last reset. Does *not* reset the timer. Assume `T` was started by `walltimer_start`.

`long timer_printf(pari_timer *T, char *format, ...)` This diagnostics function is equivalent to the following code

```
err_printf("Time ")
... prints remaining arguments according to format ...
err_printf(": %ld", timer_delay(T));
```

Resets the timer as a side effect.

They are used as follows:

```
pari_timer T;
timer_start(&T); /* initialize timer */
...
printf("Total time: %ldms\n", timer_delay(&T));
```

or

```
pari_timer T;
timer_start(&T);
for (i = 1; i < 10; i++) {
    ...
}
```

```

    timer_printf(&T, "for i = %ld (L[i] = %Ps)", i, gel(L,i));
}

```

The following functions provided the same functionality, in a nonreentrant way, and are now deprecated.

```

long timer(void)
long timer2(void)
void msgtimer(const char *format, ...)

```

The following function implements `gp`'s timer and should not be used in `libpari` programs: `long gettime(void)` equivalent to `timer_delay(T)` attached to a private timer T .

4.8 Iterators, Numerical integration, Sums, Products.

4.8.1 Iterators. Since it is easier to program directly simple loops in library mode, some GP iterators are mainly useful for GP programming. Here are the others:

- `fordiv` is a trivial iteration over a list produced by `divisors`.
- `forell`, `forqfvec` and `forsubgroup` are currently not implemented as an iterator but as a procedure with callbacks.

`void forell(void *E, long fun(void*, GEN), GEN a, GEN b, long flag)` goes through the same curves as `forell(ell,a,b,,flag)`, calling `fun(E, ell)` for each curve `ell`, stopping if `fun` returns a nonzero value.

`void forqfvec(void *E, long (*fun)(void *, GEN, GEN, double), GEN q, GEN b)`: Evaluate `fun(E,U,v,m)` on all v such that $q(Uv) < b$, where U is a `t_MAT`, v is a `t_VECSMALL` and $m = q(v)$ is a `C double`. The function `fun` must return 0, unless `forqfvec` should stop, in which case, it should return 1.

`void forqfvec1(void *E, long (*fun)(void *, GEN), GEN q, GEN b)`: Evaluate `fun(E,v)` on all v such that $q(v) < b$, where v is a `t_COL`. The function `fun` must return 0, unless `forqfvec` should stop, in which case, it should return 1.

`void forsubgroup(void *E, long fun(void*, GEN), GEN G, GEN B)` goes through the same subgroups as `forsubgroup(H = G, B,)`, calling `fun(E, H)` for each subgroup H , stopping if `fun` returns a nonzero value.

- `forprime` and `forprimestep`, iterators over primes and primes in arithmetic progressions, for which we refer you to the next subsection.

- `forcomposite`, we provide an iterator over composite integers:

`int forcomposite_init(forcomposite_t *T, GEN a, GEN b)` initialize an iterator T over composite integers in $[a, b]$; over composites $\geq a$ if $b = \text{NULL}$. We must have $a \geq 0$. Return 0 if the range is known to be empty from the start (as if $b < a$ or $b < 0$), and return 1 otherwise.

`GEN forcomposite_next(forcomposite_t *T)` returns the next composite in the range, assuming that T was initialized by `forcomposite_init`.

- `forvec`, for which we provide a convenient iterator. To initialize the analog of `forvec(X = v, ..., flag)`, call

`int forvec_init(forvec_t *T, GEN v, long flag)` initialize an iterator T over the vectors generated by `forvec(X = v, ..., flag)`. This returns 0 if this vector list is empty, and 1 otherwise.

`GEN forvec_next(forvec_t *T)` returns the next element in the `forvec` sequence, or NULL if we are done. The return value must be used immediately or copied since the next call to the iterator destroys it: the relevant vector is updated in place. The iterator works hard to not use up PARI stack, and is more efficient when all lower bounds in the initialization vector v are integers. In that case, the cost is linear in the number of tuples enumerated, and you can expect to run over more than 10^9 tuples per minute. If speed is critical and all integers involved would fit in C longs, write a simple direct backtracking algorithm yourself.

- `forpart` is a variant of `forvec` which iterates over partitions. See the documentation of the `forpart` GP function for details. This function is available as a loop with callbacks:

```
void forpart(void *data, long (*call)(void*, GEN), long k, GEN a, GEN n)
```

It is also available as an iterator:

`void forpart_init(forpart_t *T, long k, GEN a, GEN n)` initializes an iterator over the partitions of k , with length restricted by n , and components restricted by a , either of which can be set to NULL to run without restriction.

`GEN forpart_next(forpart_t *T)` returns the next partition, or NULL when all partitions have been exhausted.

`GEN forpart_prev(forpart_t *T)` returns the previous partition, or NULL when all partitions have been exhausted.

In both cases, the partition must be used or copied before the next call since it is returned from a state array which will be modified in place. You may *not* mix calls to `forpart_next` and `forpart_prev`: the first one called determines the ordering used to iterate over the partitions; you can not go back since the `forpart_t` structure is used in incompatible ways.

- `forperm` to loop over permutations of k . See the documentation of the `forperm` GP function for details. This function is available as an iterator:

```
void forperm_init(forperm_t *T, GEN k) initializes an iterator over the permutations of k
(t_INT, t_VEC or t_VECSMALL).
```

`GEN forperm_next(forperm_t *T)` returns the next permutation as a `t_VECSMALL` or NULL when all permutations have been exhausted. The permutation must be used or copied before the next call since it is returned from a state array which will be modified in place.

- `forsubset` to loop over subsets. See the documentation of the `forsubset` GP function for details. This function is available as two iterators:

```
void forallsubset_init(forsubset_t *T, long n)
```

```
void forksubset_init(forsubset_t *T, long n, long k)
```

It is also available in generic form:

`void forsubset_init(forsubset_t *T, GEN nk)` where `nk` is either a `t_INT` n or a `t_VEC` with two integral components $[n, k]$.

In all three cases, `GEN forsubset_next(forsubset_t *T)` returns the next subset as a `t_VECSMALL` or NULL when all subsets have been exhausted.

4.8.2 Iterating over primes.

The library provides a high-level iterator, which stores its (private) data in a `struct forprime_t` and runs over arbitrary ranges of primes, without ever overflowing.

The iterator has two flavors, one providing the successive primes as `ulongs`, the other as `GEN`. They are initialized as follows, where we expect to run over primes $\geq a$ and $\leq b$:

`int u_forprime_init(forprime_t *T, ulong a, ulong b)` for the `ulong` variant, where $b = \text{ULONG_MAX}$ means we will run through all primes representable in a `ulong` type.

`int forprime_init(forprime_t *T, GEN a, GEN b)` for the `GEN` variant, where $b = \text{NULL}$ means $+\infty$.

`int forprimestep_init(forprime_t *T, GEN a, GEN b, GEN q)` initialize an iterator T over primes in an arithmetic progression, $p \geq a$ and $p \leq b$ (where $b = \text{NULL}$ means $+\infty$). The argument q is either a `t_INT` ($p \equiv a \pmod{q}$) or a `t_INTMOD` `Mod(c,N)` and we restrict to that congruence class.

All variants return 1 on success, and 0 if the iterator would run over an empty interval (if $a > b$, for instance). They allocate the `forprime_t` data structure on the PARI stack.

The successive primes are then obtained using

`GEN forprime_next(forprime_t *T)`, returns `NULL` if no more primes are available in the interval and the next suitable prime as a `t_INT` otherwise.

`ulong u_forprime_next(forprime_t *T)`, returns 0 if no more primes are available in the interval and fitting in an `ulong` and the next suitable prime otherwise.

These two functions leave alone the PARI stack, and write their state information in the preallocated `forprime_t` struct. The typical usage is thus:

```
forprime_t T;
GEN p;
pari_sp av = avma, av2;

forprime_init(&T, gen_2, stoi(1000));
av2 = avma;
while ( (p = forprime_next(&T)) )
{
    ...
    if ( prime_is_OK(p) ) break;
    set_avma(av2); /* delete garbage accumulated in this iteration */
}
set_avma(av); /* delete all */
```

Of course, the final `set_avma(av)` could be replaced by a `gerepile` call. Beware that swapping the `av2 = avma` and `forprime_init` call would be incorrect: the first `set_avma(av2)` would delete the `forprime_t` structure!

4.8.3 Parallel iterators.

These iterators loop over the values of a `t_CLOSURE` taken at some data, where the evaluations are done in parallel.

- **parfor.** To initialize the analog of `parfor(i = a, b, ...)`, call

`void parfor_init(parfor_t *T, GEN a, GEN b, GEN code)` initialize an iterator over the evaluation of `code` on the integers between a and b .

`GEN parfor_next(parfor_t *T)` returns a `t_VEC [i,code(i)]` where i is one of the integers and `code(i)` is the evaluation, `NULL` when all data have been exhausted. Once it happens, `parfor_next` must not be called anymore with the same initialization.

`void parfor_stop(parfor_t *T)` needs to be called when leaving the iterator before `parfor_next` returned `NULL`.

The following returns an integer $1 \leq i \leq N$ such that `fun(i)` is not zero, or `NULL`.

```
GEN
parfirst(GEN fun, GEN N)
{
    parfor_t T;
    GEN e;
    parfor_init(&T, gen_1, N, fun);
    while ((e = parfor_next(&T)))
    {
        GEN i = gel(e,1), funi = gel(e,2);
        if (!gequal0(funi))
        { /* found: stop the iterator and return the index */
            parfor_stop(&T);
            return i;
        }
    }
    return NULL; /* not found */
}
```

- **parforeach.** To initialize the analog of `parforeach(V, X, ...)`, call

`void parforeach_init(parforeach_t *T, GEN V, GEN code)` initialize an iterator over the evaluation of `code` on the components of V .

`GEN parforeach_next(parforeach_t *T)` returns a `t_VEC [V[i],code(V[i])]` where $V[i]$ is one of the components of V and `code(V[i])` is the evaluation, `NULL` when all data have been exhausted. Once it happens, `parforprime_next` must not be called anymore with the same initialization.

`void parforeach_stop(parforeach_t *T)` needs to be called when leaving the iterator before `parforeach_next` returned `NULL`.

- **parforstep.** To initialize the analog of `parforstep(i = a, b, s, ...)`, call

`void parforstep_init(parforstep_t *T, GEN a, GEN b, GEN s, GEN code)`

initialize an iterator over the evaluation of `code` between a and b , with steps s (see `forstep` documentation for the possibilities for s).

`GEN parforstep_next(parforstep_t *T)`

returns a `t_VEC [x,code(x)]` where x is one of the evaluation points and `code(x)` is the evaluation, NULL when all data have been exhausted. Once it happens, `parforstep_next` must not be called anymore with the same initialization.

`void parforstep_stop(parforstep_t *T)` needs to be called when leaving the iterator before `parforstep_next` returned NULL.

- `parforprime`. To initialize the analog of `parforprime(p = a, b, ...)`, call

`void parforprime_init(parforprime_t *T, GEN a, GEN b, GEN code)` initialize an iterator over the evaluation of `code` on the prime numbers between a and b .

- `parforprimestep`. To initialize the analog of `parforprimestep(p = a, b, q, ...)`, call

`void parforprimestep_init(parforprime_t *T, GEN a, GEN b, GEN q, GEN code)` initialize an iterator over the evaluation of `code` on the prime numbers between a and b in the congruence class defined by q .

`GEN parforprime_next(parforprime_t *T)` returns a `t_VEC [p,code(p)]` where p is one of the prime numbers and `code(p)` is the evaluation, NULL when all data have been exhausted. Once it happens, `parforprime_next` must not be called anymore with the same initialization.

`void parforprime_stop(parforprime_t *T)` needs to be called when leaving the iterator before `parforprime_next` returned NULL.

- `parforvec`. To initialize the analog of `parforvec(X = V, ..., flag)`, call

`void parforvec_init(parforvec_t *T, GEN V, GEN code, long flag)` initialize an iterator over the evaluation of `code` on the vectors specified by V and `flag`, see `forvec` for detail.

`GEN parforvec_next(parforvec_t *T)` returns a `t_VEC [v,code(v)]` where v is one of the vectors and `code(v)` is the evaluation, NULL when all data have been exhausted. Once it happens, `parforvec_next` must not be called anymore with the same initialization.

`void parforvec_stop(parforvec_t *T)` needs to be called when leaving the iterator before `parforvec_next` returned NULL.

4.8.4 Numerical analysis.

Numerical routines code a function (to be integrated, summed, zeroed, etc.) with two parameters named

```
void *E;
GEN (*eval)(void*, GEN)
```

The second is meant to contain all auxiliary data needed by your function. The first is such that `eval(x, E)` returns your function evaluated at x . For instance, one may code the family of functions $f_t : x \rightarrow (x + t)^2$ via

```
GEN fun(void *t, GEN x) { return gsqr(gadd(x, (GEN)t)); }
```

One can then integrate f_1 between a and b with the call

```
intnum((void*)stoi(1), &fun, a, b, NULL, prec);
```

Since you can set E to a pointer to any `struct` (typecast to `void*`) the above mechanism handles arbitrary functions. For simple functions without extra parameters, you may set $E = \text{NULL}$ and ignore that argument in your function definition.

4.9 Catching exceptions.

4.9.1 Basic use.

PARI provides a mechanism to trap exceptions generated via `pari_err` using the `pari_CATCH` construction. The basic usage is as follows

```
pari_CATCH(err_code) {  
    recovery branch  
}  
pari_TRY {  
    main branch  
}  
pari_ENDCATCH
```

This fragment executes the main branch, then the recovery branch *if* exception `err_code` is thrown, e.g. `e_TYPE`. See Section 11.4 for the description of all error classes. The special error code `CATCH_ALL` is available to catch all errors.

One can replace the `pari_TRY` keyword by `pari_RETRY`, in which case once the recovery branch is run, we run the main branch again, still catching the same exceptions.

Restrictions.

- Such constructs can be nested without adverse effect, the innermost handler catching the exception.
- It is *valid* to leave either branch using `pari_err`.
- It is *invalid* to use C flow control instructions (`break`, `continue`, `return`) to directly leave either branch without seeing the `pari_ENDCATCH` keyword. This would leave an invalid structure in the exception handler stack, and the next exception would crash.
- In order to leave using `break`, `continue` or `return`, one must precede the keyword by a call to

`void pari_CATCH_reset()` disable the current handler, allowing to leave without adverse effect.

4.9.2 Advanced use.

In the recovery branch, the exception context can be examined via the following helper routines:

`GEN pari_err_last()` returns the exception context, as a `t_ERROR`. The exception *E* returned by `pari_err_last` can be rethrown, using

```
pari_err(0, E);
```

`long err_get_num(GEN E)` returns the error symbolic name. E.g `e_TYPE`.

`GEN err_get_compo(GEN E, long i)` error *i*-th component, as documented in Section 11.4.

For instance

```
pari_CATCH(CATCH_ALL) { /* catch everything */  
    GEN x, E = pari_err_last();  
    long code = err_get_num(E);  
    if (code != e_INV) pari_err(0, E); /* unexpected error, rethrow */
```

```

    x = err_get_compo(E, 2);
    /* e_INV has two components, 1: function name 2: noninvertible x */
    if (typ(x) != t_INTMOD) pari_err(0, E); /* unexpected type, rethrow */
    pari_CATCH_reset();
    return x; /* leave ! */
    ...
} pari_TRY {
    main branch
}
pari_ENDCATCH

```

4.10 A complete program.

Now that the preliminaries are out of the way, the best way to learn how to use the library mode is to study a detailed example. We want to write a program which computes the gcd of two integers, together with the Bezout coefficients. We shall use the standard quadratic algorithm which is not optimal but is not too far from the one used in the PARI function **gcdext**.

Let x, y two integers and initially $\begin{pmatrix} s_x & s_y \\ t_x & t_y \end{pmatrix} = \begin{pmatrix} 1 & 0 \\ 0 & 1 \end{pmatrix}$, so that

$$\begin{pmatrix} s_x & s_y \\ t_x & t_y \end{pmatrix} \begin{pmatrix} x \\ y \end{pmatrix} = \begin{pmatrix} x \\ y \end{pmatrix}.$$

To apply the ordinary Euclidean algorithm to the right hand side, multiply the system from the left by $\begin{pmatrix} 0 & 1 \\ 1 & -q \end{pmatrix}$, with $q = \text{floor}(x/y)$. Iterate until $y = 0$ in the right hand side, then the first line of the system reads

$$s_x x + s_y y = \text{gcd}(x, y).$$

In practice, there is no need to update s_y and t_y since $\text{gcd}(x, y)$ and s_x are enough to recover s_y . The following program is now straightforward. A couple of new functions appear in there, whose description can be found in the technical reference manual in Chapter 5, but whose meaning should be clear from their name and the context.

This program can be found in `examples/extgcd.c` together with a proper `Makefile`. You may ignore the first comment

```

/*
GP;install("extgcd", "GG&&", "gcdex", "./libextgcd.so");
*/

```

which instruments the program so that `gp2c-run extgcd.c` can import the `extgcd()` routine into an instance of the `gp` interpreter (under the name `gcdex`). See the `gp2c` manual for details.


```

#include <pari/pari.h>
/*
GP;install("extgcd", "GG&&", "gcdex", "./libextgcd.so");
*/
/* return d = gcd(a,b), sets u, v such that au + bv = gcd(a,b) */
GEN
extgcd(GEN A, GEN B, GEN *U, GEN *V)
{
    pari_sp av = avma;
    GEN ux = gen_1, vx = gen_0, a = A, b = B;
    if (typ(a) != t_INT) pari_err_TYPE("extgcd",a);
    if (typ(b) != t_INT) pari_err_TYPE("extgcd",b);
    if (signe(a) < 0) { a = negi(a); ux = negi(ux); }
    while (!gequal0(b))
    {
        GEN r, q = dvmdii(a, b, &r), v = vx;
        vx = subii(ux, mulii(q, vx));
        ux = v; a = b; b = r;
    }
    *U = ux;
    *V = diviexact( subii(a, mulii(A,ux)), B );
    gerepileall(av, 3, &a, U, V); return a;
}

int
main()
{
    GEN x, y, d, u, v;
    pari_init(1000000,2);
    printf("x = "); x = gp_read_stream(stdin);
    printf("y = "); y = gp_read_stream(stdin);
    d = extgcd(x, y, &u, &v);
    pari_printf("gcd = %Ps\nu = %Ps\nv = %Ps\n", d, u, v);
    pari_close();
    return 0;
}

```

For simplicity, the inner loop does not include any garbage collection, hence memory use is quadratic in the size of the inputs instead of linear. Here is a better version of that loop:

```

    pari_sp av = avma;
    ...
    while (!gequal0(b))
    {
        GEN r, q = dvmdii(a, b, &r), v = vx;
        vx = subii(ux, mulii(q, vx));
        ux = v; a = b; b = r;
        if (gc_needed(av,1))
            gerepileall(av, 4, &a, &b, &ux, &vx);
    }

```

}

Chapter 5:

Technical Reference Guide: the basics

In the following chapters, we describe all public low-level functions of the PARI library. These include specialized functions for handling all the PARI types. Simple higher level functions, such as arithmetic or transcendental functions, are described in Chapter 3 of the GP user's manual; we will eventually see more general or flexible versions in the chapters to come. A general introduction to the major concepts of PARI programming can be found in Chapter 4, which you should really read first.

We shall now study specialized functions, more efficient than the library wrappers, but sloppier on argument checking and damage control; besides speed, their main advantage is to give finer control about the inner workings of generic routines, offering more options to the programmer.

Important advice. Generic routines eventually call lower level functions. Optimize your algorithms first, not overhead and conversion costs between PARI routines. For generic operations, use generic routines first; do not waste time looking for the most specialized one available unless you identify a genuine bottleneck, or you need some special behavior the generic routine does not offer. The PARI source code is part of the documentation; look for inspiration there.

The type `long` denotes a `BITS_IN_LONG`-bit signed long integer (32 or 64 bits). The type `ulong` is defined as `unsigned long`. The word *stack* always refer to the PARI stack, allocated through an initial `pari_init` call. Refer to Chapters 1–2 and 4 for general background.

We shall often refer to the notion of *shallow* function, which means that some components of the result may point to components of the input, which is more efficient than a *deep* copy (full recursive copy of the object tree). Such outputs are not suitable for `gerepileupto` and particular care must be taken when garbage collecting objects which have been input to shallow functions: corresponding outputs also become invalid and should no longer be accessed.

A function is *not stack clean* if it leaves intermediate data on the stack besides its output, for efficiency reasons.

5.1 Initializing the library.

The following functions enable you to start using the PARI functions in a program, and cleanup without exiting the whole program.

5.1.1 General purpose.

`void pari_init(size_t size, ulong maxprime)` initialize the library, with a stack of `size` bytes and a prime table up to the maximum of `maxprime` and 2^{16} . Unless otherwise mentioned, no PARI function will function properly before such an initialization.

`void pari_close(void)` stop using the library (assuming it was initialized with `pari_init`) and frees all allocated objects.

5.1.2 Technical functions.

`void pari_init_opts(size_t size, ulong maxprime, ulong opts)` as `pari_init`, more flexible. `opts` is a mask of flags among the following:

`INIT_JMPm`: install PARI error handler. When an exception is raised, the program is terminated with `exit(1)`.

`INIT_SIGm`: install PARI signal handler.

`INIT_DFTm`: initialize the `GP_DATA` environment structure. This one *must* be enabled once. If you close pari, then restart it, you need not reinitialize `GP_DATA`; if you do not, then old values are restored.

`INIT_noPRIMEm`: do not compute the prime table (ignore the `maxprime` argument). The user *must* call `pari_init_primes` later.

`INIT_noIMTm`: (technical, see `pari_mt_init` in the Developer's Guide for detail). Do not call `pari_mt_init` to initialize the multi-thread engine. If this flag is set, `pari_mt_init()` will need to be called manually. See `examples/pari-mt.c` for an example.

`INIT_noINTGMPm`: do not install PARI-specific GMP memory functions. This option is ignored when the GMP library is not in use. You may install PARI-specific GMP memory functions later by calling

```
void pari_kernel_init(void)
```

and restore the previous values using

```
void pari_kernel_close(void)
```

This option should not be used without a thorough understanding of the problem you are trying to solve. The GMP memory functions are global variables used by the GMP library. If your program is linked with two libraries that require these variables to be set to different values, conflict ensues. To avoid a conflict, the proper solution is to record their values with `mp_get_memory_functions` and to call `mp_set_memory_functions` to restore the expected values each time the code switches from using one library to the other. Here is an example:

```
void *(*pari_alloc_ptr) (size_t);
void *(*pari_realloc_ptr) (void *, size_t, size_t);
void (*pari_free_ptr) (void *, size_t);
void *(*otherlib_alloc_ptr) (size_t);
void *(*otherlib_realloc_ptr) (void *, size_t, size_t);
void (*otherlib_free_ptr) (void *, size_t);

void init(void)
{
    pari_init(8000000, 500000);
    mp_get_memory_functions(&pari_alloc_ptr,&pari_realloc_ptr,
                          &pari_free_ptr);

    otherlib_init();
    mp_get_memory_functions(&otherlib_alloc_ptr,&otherlib_realloc_ptr,
                          &otherlib_free_ptr);
}

void function_that_use_pari(void)
{
```

```

    mp_set_memory_functions(pari_alloc_ptr, pari_realloc_ptr,
                           pari_free_ptr);
    /*use PARI functions*/
}
void function_that_use_otherlib(void)
{
    mp_set_memory_functions(otherlib_alloc_ptr, otherlib_realloc_ptr,
                           otherlib_free_ptr);
    /*use OTHERLIB functions*/
}

```

`void pari_close_opts(ulong init_opts)` as `pari_close`, for a library initialized with a mask of options using `pari_init_opts`. `opts` is a mask of flags among

`INIT_SIGm`: restore `SIG_DFL` default action for signals tampered with by PARI signal handler.

`INIT_DFTm`: frees the `GP_DATA` environment structure.

`INIT_noIMTm`: (technical, see `pari_mt_init` in the Developer's Guide for detail). Do not call `pari_mt_close` to close the multi-thread engine. `INIT_noINTGMPm`: do not restore GMP memory functions.

`void pari_sig_init(void (*f)(int))` install the signal handler `f` (see `signal(2)`): the signals `SIGBUS`, `SIGFPE`, `SIGINT`, `SIGBREAK`, `SIGPIPE` and `SIGSEGV` are concerned.

`void pari_init_primes(ulong maxprime)` Initialize the PARI primes. This function is called by `pari_init(..., maxprime)`. It is provided for users calling `pari_init_opts` with the flag `INIT_noPRIMEm`.

`void pari_sighandler(int signum)` the actual signal handler that PARI uses. This can be used as argument to `pari_sig_init` or `signal(2)`.

`void pari_stackcheck_init(void *stackbase)` controls the system stack exhaustion checking code in the GP interpreter. This should be used when the system stack base address change or when the address seen by `pari_init` is too far from the base address. If `stackbase` is `NULL`, disable the check, else set the base address to `stackbase`. It is normally used this way

```

int thread_start (...)
{
    long first_item_on_the_stack;
    ...
    pari_stackcheck_init(&first_item_on_the_stack);
}

```

`int pari_daemon(void)` forks a PARI daemon, detaching from the main process group. The function returns 1 in the parent, and 0 in the forked son.

`void paristack_setsize(size_t rsize, size_t vsize)` sets the default `parisize` to `rsize` and the default `parisizemax` to `vsize`, and reallocate the stack to match these value, destroying its content. Generally used just after `pari_init`.

`void paristack_resize(ulong newsize)` changes the current stack size to `newsize` (double it if `newsize` is 0). The new size is clipped to be at least the current stack size and at most `parisizemax`. The stack content is not affected by this operation.

`void parivstack_reset(void)` resets the current stack to its default size `parisize`. This is used to recover memory after a computation that enlarged the stack. This function destroys the content of the enlarged stack (between the old and the new bottom of the stack). Before calling this function, you must ensure that `avma` lies within the new smaller stack.

`void paristack_newsize(ulong newsize)` (*does not return*). Library version of
`default(parisize, "newsize")`

Set the default `parisize` to `newsize`, or double `parisize` if `newsize` is equal to 0, then call `cb_pari_err_recover(-1)`.

`void parivstack_resize(ulong newsize)` (*does not return*). Library version of
`default(parisizemax, "newsize")`

Set the default `parisizemax` to `newsize` and call `cb_pari_err_recover(-1)`.

5.1.3 Notions specific to the GP interpreter.

An **entree** is the generic object attached to an identifier (a name) in GP's interpreter, be it a built-in or user function, or a variable. For a function, it has at least the following fields:

`char *name`: the name under which the interpreter knows us.

`void *value`: a pointer to the C function to call.

`long menu`: a small integer ≥ 1 (to which group of function help do we belong, for the `?n` help menu).

`char *code`: the prototype code.

`char *help`: the help text for the function.

A routine in GP is described to the analyzer by an **entree** structure. Built-in PARI routines are grouped in *modules*, which are arrays of **entree** structs, the last of which satisfy `name = NULL` (sentinel). There are currently four modules in PARI/GP:

- general functions (`functions_basic`, known to `libpari`),
- gp-specific functions (`functions_gp`),

and two modules of obsolete functions. The function `pari_init` initializes the interpreter and declares all symbols in `functions_basic`. You may declare further functions on a case by case basis or as a whole module using

`void pari_add_function(entree *ep)` adds a single routine to the table of symbols in the interpreter. It assumes `pari_init` has been called.

`void pari_add_module(entree *mod)` adds all the routines in module `mod` to the table of symbols in the interpreter. It assumes `pari_init` has been called.

For instance, `gp` implements a number of private routines, which it adds to the default set via the calls

```
pari_add_module(functions_gp);
```

A GP `default` is likewise attached to a helper routine, that is run when the value is consulted, or changed by `default0` or `setdefault`. Such routines are grouped in the module `functions_default`.

`void pari_add_defaults_module(entree *mod)` adds all the defaults in module `mod` to the interpreter. It assumes that `pari_init` has been called. From this point on, all defaults in module `mod` are known to `setdefault` and friends.

5.1.4 Public callbacks.

The `gp` calculator associates elaborate functions (for instance the break loop handler) to the following callbacks, and so can you:

`void (*cb_pari_ask_confirm)(const char *s)` initialized to `NULL`. Called with argument `s` whenever PARI wants confirmation for action `s`, for instance in `secure` mode.

`long (*cb_pari_display_hist)(long n)` initialized to `NULL`. If set, called by `gp_embedded` in place of `gp_display_hist`.

`void (*cb_pari_init_histfile)(void)` initialized to `NULL`. Called when the `histfile` default is changed. The intent is for that callback to read the file content, append it to history in memory, then dump the expanded history to the new `histfile`.

`int (*cb_pari_is_interactive)(void)`; initialized to `NULL`.

`void (*cb_pari_quit)(long)` initialized to a no-op. Called when `gp` must evaluate the quit command.

`void (*cb_pari_start_output)(void)` initialized to `NULL`.

`int (*cb_pari_handle_exception)(long)` initialized to `NULL`. If not `NULL`, this routine is called with argument `-1` on `SIGINT`, and argument `err` on error `err`. If it returns a nonzero value, the error or signal handler returns, in effect further ignoring the error or signal, otherwise it raises a fatal error. A possible simple-minded handler, used by the `gp` interpreter, is

`int gp_handle_exception(long err)` if the `breakloop` default is enabled (set to 1) and `cb_pari_break_loop` is not `NULL`, we call this routine with `err` argument and return the result.

`int (*cb_pari_err_handle)(GEN)` If not `NULL`, this routine is called with a `t_ERROR` argument from `pari_err`. If it returns a nonzero value, the error returns, in effect further ignoring the error, otherwise it raises a fatal error.

The default behavior is to print a descriptive error message (display the error), then return 0, thereby raising a fatal error. This differs from `cb_pari_handle_exception` in that the function is not called on `SIGINT` (which do not generate a `t_ERROR`), only from `pari_err`. Use `cb_pari_sigint` if you need to handle `SIGINT` as well.

The following function can be used by `cb_pari_err_handle` to display the error message.

`const char* closure_func_err()` return a statically allocated string holding the name of the function that triggered the error. Return `NULL` if the error was not caused by a function.

`int (*cb_pari_break_loop)(int)` initialized to `NULL`.

`void (*cb_pari_sigint)(void)`. Function called when we receive `SIGINT`. By default, raises

```
pari_err(e_MISC, "user interrupt");
```

A possible simple-minded variant, used by the `gp` interpreter, is

```
void gp_sigint_fun(void)
```

`void (*cb_pari_pre_recover)(long)` initialized to `NULL`. If not `NULL`, this routine is called just before PARI cleans up from an error. It is not required to return. The error number is passed as argument.

`void (*cb_pari_err_recover)(long)` initialized to `pari_exit()`. This callback must not return. It is called after PARI has cleaned-up from an error. The error number is passed as argument, unless the PARI stack has been destroyed, in which case it is called with argument `-1`.

`int (*cb_pari_whatnow)(PariOUT *out, const char *s, int flag)` initialized to `NULL`. If not `NULL`, must check whether `s` existed in older versions of `pari` (the `gp` callback checks against `pari-1.39.15`). All output must be done via `out` methods.

- `flag = 0`: should print verbosely the answer, including help text if available.
- `flag = 1`: must return 0 if the function did not change, and a nonzero result otherwise. May print a help message.

`void (*cb_pari_long_help)(const char *s, long n)` It is called in place of the external help, to handle ??.

5.1.5 Configuration variables.

`pari_library_path`: If set, It should be a path to the `libpari` library. It is used by the function `gpinstall` to locate the PARI library when searching for symbols. This should only be useful on Windows.

5.1.6 Utility functions.

`void pari_ask_confirm(const char *s)` raise an error if the callback `cb_pari_ask_confirm` is `NULL`. Otherwise calls

```
cb_pari_ask_confirm(s);
```

`char* gp_filter(const char *s)` pre-processor for the GP parser: filter out whitespace and GP comments from `s`. The returned string is allocated on the PARI stack and must not be freed.

GEN `pari_compile_str(const char *s)` low-level form of `compile_str`: assumes that `s` does not contain spaces or GP comments and returns the closure attached to the GP expression `s`. Note that GP metacommands are not recognized.

`int gp_meta(const char *s, int ismain)` low-level component of `gp_read_str`: assumes that `s` does not contain spaces or GP comments and try to interpret `s` as a GP metacommand (e.g. starting by `\` or `?`). If successful, execute the metacommand and return 1; otherwise return 0. The `ismain` parameter modifies the way `\r` commands are handled: if nonzero, act as if the file contents were entered via standard input (i.e. call `switchin` and divert `pari_infile`); otherwise, simply call `gp_read_file`.

`void pari_hit_return(void)` wait for the use to enter `\n` via standard input.

`void gp_load_gprc(void)` read and execute the user's GPRC file.

`void pari_center(const char *s)` print `s`, centered.

`void pari_print_version(void)` print verbose version information.

`long pari_community(void)` return the index of the support section `n` the help.

`const char* gp_format_time(long t)` format a delay of t ms suitable for `gp` output, with `timer` set. The string is allocated in the PARI stack via `stack_malloc`.

`const char* gp_format_prompt(const char *p)` format a prompt p suitable for `gp` prompting (includes colors and protecting ANSI escape sequences for readline).

`void pari_alarm(long s)` set an alarm after s seconds (raise an `e_ALARM` exception).

`void gp_help(const char *s, long flag)` print help for s , depending on the value of *flag*:

- `h_REGULAR`, basic help (?);
- `h_LONG`, extended help (??);
- `h_APROPOS`, a propos help (??).

`const char ** gphelp_keyword_list(void)` return a NULL-terminated array of strings, containing keywords known to `gphelp` besides GP functions (e.g. `modulus` or `operator`). Used by the online help system and the contextual completion engine.

`void gp_echo_and_log(const char *p, const char *s)` given a prompt p and attached input command s , update logfile and possibly print on standard output if `echo` is set and we are not in interactive mode. The callback `cb_pari_is_interactive` must be set to a sensible value.

`void gp_alarm_handler(int sig)` the `SIGALRM` handler set by the `gp` interpreter.

`void print_fun_list(char **list, long n)` print all elements of `list` in columns, pausing (hit return) every n lines. `list` is NULL terminated.

5.1.7 Saving and restoring the GP context.

`void gp_context_save(struct gp_context* rec)` save the current GP context.

`void gp_context_restore(struct gp_context* rec)` restore a GP context. The new context must be an ancestor of the current context.

5.1.8 GP history.

These functions allow to control the GP history (the `%` operator).

`void pari_add_hist(GEN x, long t, long r)` adds x as the last history entry; t (resp. r) is the cpu (resp. real) time used to compute it.

`GEN pari_get_hist(long p)`, if $p > 0$ returns entry of index p (i.e. `%p`), else returns entry of index $n + p$ where n is the index of the last entry (used for `%, %', %'', etc.`).

`long pari_get_histtime(long p)` as `pari_get_hist`, returning the cpu time used to compute the history entry, instead of the entry itself.

`long pari_get_histrtime(long p)` as `pari_get_hist`, returning the real time used to compute the history entry, instead of the entry itself.

`GEN pari_histtime(long p)` return the vector `[cpu, real]` where `cpu` and `real` are as above.

`ulong pari_nb_hist(void)` return the index of the last entry.

`void gp_display_hist(long n)` print the history entry n using the usual GP format `"%n = ..."`.

`void str_display_hist(pari_str *S, long n)` as `gp_display_hist`, but output to the string S .

5.2 Handling GENs.

Almost all these functions are either macros or inlined. Unless mentioned otherwise, they do not evaluate their arguments twice. Most of them are specific to a set of types, although no consistency checks are made: e.g. one may access the `sign` of a `t_PADIC`, but the result is meaningless.

5.2.1 Allocation.

GEN `cgetg(long l, long t)` allocates (the root of) a GEN of type `t` and length `l`. Sets `z[0]`.

GEN `cgeti(long l)` allocates a `t_INT` of length `l` (including the 2 codewords). Sets `z[0]` only.

GEN `cgetr(long prec)` allocates a `t_REAL` of precision `prec`. Sets `z[0]` only.

GEN `cgetc(long prec)` allocates a `t_COMPLEX` whose real and imaginary parts are `t_REALs` of precision `prec`.

GEN `cgetg_copy(GEN x, long *lx)` fast version of `cgetg`: allocate a GEN with the same type and length as `x`, setting `*lx` to `lg(x)` as a side-effect. (Only sets the first codeword.) This is a little faster than `cgetg` since we may reuse the bitmask in `x[0]` instead of recomputing it, and we do not need to check that the length does not overflow the possibilities of the implementation (since an object with that length already exists). Note that `cgetg` with arguments known at compile time, as in

```
cgetg(3, t_INTMOD)
```

will be even faster since the compiler will directly perform all computations and checks.

GEN `vec trunc_init(long l)` perform `cgetg(1,t_VEC)`, then set the length to `l` and return the result. This is used to implement vectors whose final length is easily bounded at creation time, that we intend to fill gradually using:

`void vec trunc_append(GEN x, GEN y)` assuming `x` was allocated using `vec trunc_init`, appends `y` as the last element of `x`, which grows in the process. The function is shallow: we append `y`, not a copy; it is equivalent to

```
long lx = lg(x); gel(x, lx) = y; setlg(x, lx+1);
```

Beware that the maximal size of `x` (the `l` argument to `vec trunc_init`) is unknown, hence unchecked, and stack corruption will occur if we append more than `l - 1` elements to `x`. Use the safer (but slower) `shallowconcat` when `l` is not easy to bound in advance.

An other possibility is simply to allocate using `cgetg(1, t)` then fill the components as they become available: this time the downside is that we do not obtain a correct GEN until the vector is complete. Almost no PARI function will be able to operate on it.

`void vec trunc_append_batch(GEN x, GEN y)` successively apply

```
vec trunc_append(x, gel(y, i))
```

for all elements of the vector `y`.

GEN `col trunc_init(long l)` as `vec trunc_init` but perform `cgetg(1,t_COL)`.

GEN `vec small trunc_init(long l)`

`void vec small trunc_append(GEN x, long t)` analog to the above for a `t_VECSMALL` container.

5.2.2 Length conversions.

These routines convert a nonnegative length to different units. Their behavior is undefined at negative integers.

`long ndec2nlong(long x)` converts a number of decimal digits to a number of words. Returns $1 + \text{floor}(x \times \text{BITS_IN_LONG} \log_2 10)$.

`long ndec2prec(long x)` converts a number of decimal digits to a number of bits.

`long ndec2nbits(long x)` converts a number of decimal digits to a number of bits.

`long prec2ndec(long x)` converts a number of bits to a number of decimal digits.

`long nbits2nlong(long x)` converts a number of bits to a number of words. Returns the smallest word count containing x bits, i.e. $\text{ceil}(x/\text{BITS_IN_LONG})$.

`long nbits2ndec(long x)` converts a number of bits to a number of decimal digits.

`long nbits2lg(long x)` converts a number of bits to a length in code words. Currently an alias for `nbits2nlong`.

`long prec2lg(long x)` return the length of a `t_REAL` of precision x .

`long lg2prec(long x)` return the maximal precision of a `t_REAL` of length x .

`long nbits2prec(long x)` convert x to a valid precision.

`long nbits2extraprec(long x)` convert x to a valid precision.

`long nchar2nlong(long x)` converts a number of bytes to number of words. Returns the smallest word count containing x bytes, i.e. $\text{ceil}(x/\text{sizeof}(\text{long}))$.

`long prec2nbits(long x)` return x . For backward compatibility.

`double prec2nbits_mul(long x, double y)` returns $x \times y$. For backward compatibility.

`long bit_accuracy(long x)` converts a length into a number of significant bits;

`double bit_accuracy_mul(long x, double y)` returns $\text{bit_accuracy}(x) \times y$.

`long realprec(GEN x)` precision of a `t_REAL` in bits.

`long bit_prec(GEN x)` precision of a `t_REAL` in bits.

`long precdbl(long x)` return $2 * x$.

5.2.3 Read type-dependent information.

`long typ(GEN x)` returns the type number of x . The header files included through `pari.h` define symbolic constants for the `GEN` types: `t_INT` etc. Never use their actual numerical values. E.g to determine whether x is a `t_INT`, simply check

```
if (typ(x) == t_INT) { }
```

The types are internally ordered and this simplifies the implementation of commutative binary operations (e.g addition, gcd). Avoid using the ordering directly, as it may change in the future; use type grouping functions instead (Section 5.2.6).

`const char* type_name(long t)` given a type number t this routine returns a string containing its symbolic name. E.g `type_name(t_INT)` returns `"t_INT"`. The return value is read-only.

`long lg(GEN x)` returns the length of x in BITS_IN_LONG-bit words.

`long lgefint(GEN x)` returns the effective length of the `t_INT` x in BITS_IN_LONG-bit words.

`long signe(GEN x)` returns the sign (-1 , 0 or 1) of x . Can be used for `t_INT`, `t_REAL`, `t_POL` and `t_SER` (for the last two types, only 0 or 1 are possible).

`long gsigne(GEN x)` returns the sign of a real number x , valid for `t_INT`, `t_REAL` as `signe`, but also for `t_FRAC` and `t_QUAD` of positive discriminants. Raise a type error if `typ(x)` is not among those.

`long expi(GEN x)` returns the binary exponent of the real number equal to the `t_INT` x . This is a special case of `gexpo`.

`long expo(GEN x)` returns the binary exponent of the `t_REAL` x .

`long mpexpo(GEN x)` returns the binary exponent of the `t_INT` or `t_REAL` x .

`long gexpo(GEN x)` same as `expo`, but also valid when x is not a `t_REAL` (returns the largest exponent found among the components of x). When x is an exact 0 , this returns `-HIGHEXPOBIT`, which is lower than any valid exponent.

`long gexpo_safe(GEN x)` same as `gexpo`, but returns a value strictly less than `-HIGHEXPOBIT` when the exponent is not defined (e.g. for a `t_PADIC` or `t_INTMOD` component).

`long valp(GEN x)` returns the p -adic valuation (for a `t_PADIC`).

`long valser(GEN x)` returns the X -adic valuation (for a `t_SER`).

`long precp(GEN x)` returns the precision of the `t_PADIC` x .

`long varn(GEN x)` returns the variable number of the `t_POL` or `t_SER` x (between 0 and `MAXVARN`).

`long gvar(GEN x)` returns the main variable number when any variable at all occurs in the composite object x (the smallest variable number which occurs), and `NO_VARIABLE` otherwise.

`long gvar2(GEN x)` returns the variable number for the ring over which x is defined, e.g. if $x \in \mathbb{Z}[a][b]$ return (the variable number for) a . Return `NO_VARIABLE` if x has no variable or is not defined over a polynomial ring.

`long degpol(GEN x)` is a simple macro returning `lg(x) - 3`. This is the degree of the `t_POL` x with respect to its main variable, *if* its leading coefficient is nonzero (a rational 0 is impossible, but an inexact 0 is allowed, as well as an exact modular 0 , e.g. `Mod(0,2)`). If x has no coefficients (rational 0 polynomial), its length is 2 and we return the expected -1 .

`long lgpol(GEN x)` is equal to `degpol(x) + 1`. Used to loop over the coefficients of a `t_POL` in the following situation:

```
GEN xd = x + 2;
long i, l = lgpol(x);
for (i = 0; i < l; i++) foo( xd[i] ).
```

`long precision(GEN x)` If x is of type `t_REAL`, returns the precision of x , namely

- if x is not zero: the length of x in BITS_IN_LONG-bit words;
- if x is numerically equal to 0 , of exponent e : the absolute accuracy `nbits2prec(e)` if $e < 0$ and `LOWDEFAULTPREC` if $e \geq 0$.

If x is of type `t_COMPLEX`, returns the minimum of the precisions of the real and imaginary part. Otherwise, returns 0 (which stands for infinite precision). In all cases, the precision is either 0 or can be used as a `prec` parameter in transcendental functions.

`long lgcols(GEN x)` is equal to `lg(gel(x,1))`. This is the length of the columns of a `t_MAT` with at least one column.

`long nbrows(GEN x)` is equal to `lg(gel(x,1))-1`. This is the number of rows of a `t_MAT` with at least one column.

`long gprecision(GEN x)` as `precision` for scalars. Returns the lowest precision encountered among the components otherwise.

`long sizedigit(GEN x)` returns 0 if x is exactly 0. Otherwise, returns `gexpo(x)` multiplied by $\log_{10}(2)$. This gives a crude estimate for the maximal number of decimal digits of the components of x .

5.2.4 Eval type-dependent information. These routines convert type-dependent information to bitmask to fill the codewords of `GEN` objects (see Section 4.5). E.g for a `t_REAL` z :

```
z[1] = evalsigne(-1) | evalexpo(2)
```

Compatible components of a codeword for a given type can be OR-ed as above.

`ulong evaltyp(long x)` convert type x to bitmask (first codeword of all `GENs`)

`long evallg(long x)` convert length x to bitmask (first codeword of all `GENs`). Raise overflow error if x is so large that the corresponding length cannot be represented

`long _evallg(long x)` as `evallg` *without* the overflow check.

`ulong evalvarn(long x)` convert variable number x to bitmask (second codeword of `t_POL` and `t_SER`)

`long evalsigne(long x)` convert sign x (in $-1, 0, 1$) to bitmask (second codeword of `t_INT`, `t_REAL`, `t_POL`, `t_SER`)

`long evalprecp(long x)` convert p -adic (X -adic) precision x to bitmask (second codeword of `t_PADIC`, `t_SER`). Raise overflow error if x is so large that the corresponding precision cannot be represented.

`long _evalprecp(long x)` same as `evalprecp` *without* the overflow check.

`long evalvalp(long x)` convert p -adic valuation x to bitmask (second codeword of `t_PADIC`). Raise overflow error if x is so large that the corresponding valuation cannot be represented.

`long _evalvalp(long x)` same as `evalvalp` *without* the overflow check.

`long evalvalser(long x)` convert X -adic valuation x to bitmask (second codeword of `t_SER`). Raise overflow error if x is so large that the corresponding valuation cannot be represented.

`long _evalvalser(long x)` same as `evalvalser` *without* the overflow check.

`long evalexpo(long x)` convert exponent x to bitmask (second codeword of `t_REAL`). Raise overflow error if x is so large that the corresponding exponent cannot be represented

`long _evalexpo(long x)` same as `evalexpo` *without* the overflow check.

`long evallgefint(long x)` convert effective length x to bitmask (second codeword `t_INT`). This should be less or equal than the length of the `t_INT`, hence there is no overflow check for the effective length.

5.2.5 Set type-dependent information. Use these functions and macros with extreme care since usually the corresponding information is set otherwise, and the components and further codeword fields (which are left unchanged) may not be compatible with the new information.

`void settyp(GEN x, long s)` sets the type number of `x` to `s`.

`void setlg(GEN x, long s)` sets the length of `x` to `s`. This is an efficient way of truncating vectors, matrices or polynomials.

`void setlgefint(GEN x, long s)` sets the effective length of the `t_INT` `x` to `s`. The number `s` must be less than or equal to the length of `x`.

`void setsigne(GEN x, long s)` sets the sign of `x` to `s`. If `x` is a `t_INT` or `t_REAL`, `s` must be equal to -1 , 0 or 1 , and if `x` is a `t_POL` or `t_SER`, `s` must be equal to 0 or 1 . No sanity check is made; in particular, setting the sign of a 0 `t_INT` to ± 1 creates an invalid object.

`void togglesign(GEN x)` sets the sign `s` of `x` to $-s$, in place.

`void togglesign_safe(GEN *x)` sets the `s` sign of `*x` to $-s$, in place, unless `*x` is one of the integer universal constants in which case replace `*x` by its negation (e.g. replace `gen_1` by `gen_m1`).

`void setabssign(GEN x)` sets the sign `s` of `x` to $|s|$, in place.

`void affectsign(GEN x, GEN y)` shortcut for `setsigne(y, signe(x))`. No sanity check is made; in particular, setting the sign of a 0 `t_INT` to ± 1 creates an invalid object.

`void affectsign_safe(GEN x, GEN *y)` sets the sign of `*y` to that of `x`, in place, unless `*y` is one of the integer universal constants in which case replace `*y` by its negation if needed (e.g. replace `gen_1` by `gen_m1` if `x` is negative). No other sanity check is made; in particular, setting the sign of a 0 `t_INT` to ± 1 creates an invalid object.

`void normalize_frac(GEN z)` assuming `z` is of the form `mkfrac(a,b)` with $b \neq 0$, make sure that $b > 0$ by changing the sign of `a` in place if needed (use `togglesign`).

`void setexpo(GEN x, long s)` sets the binary exponent of the `t_REAL` `x` to `s`. The value `s` must be a 24-bit signed number.

`void setvalp(GEN x, long s)` sets the p -adic valuation of `x` to `s`, if `x` is a `t_PADIC`.

`void setvalser(GEN x, long s)` sets the X -adic valuation of `x` to `s`, if `x` is a `t_SER`, respectively.

`void setprecp(GEN x, long s)` sets the p -adic precision of the `t_PADIC` `x` to `s`.

`void setvarn(GEN x, long s)` sets the variable number of the `t_POL` or `t_SER` `x` to `s` (where $0 \leq s \leq \text{MAXVARN}$).

5.2.6 Type groups. In the following functions, `t` denotes the type of a `GEN`. They used to be implemented as macros, which could evaluate their argument twice; *no longer*: it is not inefficient to write

```
is_intreal_t(typ(x))
```

`int is_recursive_t(long t)` true iff `t` is a recursive type (the nonrecursive types are `t_INT`, `t_REAL`, `t_STR`, `t_VECSMALL`). Somewhat contrary to intuition, `t_LIST` is also nonrecursive, ; see the Developer's guide for details.

`int is_intreal_t(long t)` true iff `t` is `t_INT` or `t_REAL`.

`int is_rational_t(long t)` true iff `t` is `t_INT` or `t_FRAC`.

`int is_real_t(long t)` true iff `t` is `t_INT` or `t_REAL` or `t_FRAC`.
`int is_qfb_t(long t)` true iff `t` is `t_QFB`.
`int is_vec_t(long t)` true iff `t` is `t_VEC` or `t_COL`.
`int is_matvec_t(long t)` true iff `t` is `t_MAT`, `t_VEC` or `t_COL`.
`int is_scalar_t(long t)` true iff `t` is a scalar, i.e. a `t_INT`, a `t_REAL`, a `t_INTMOD`, a `t_FRAC`, a `t_COMPLEX`, a `t_PADIC`, a `t_QUAD`, or a `t_POLMOD`.
`int is_extscalar_t(long t)` true iff `t` is a scalar (see `is_scalar_t`) or `t` is `t_POL`.
`int is_const_t(long t)` true iff `t` is a scalar which is not `t_POLMOD`.
`int is_noncalc_t(long t)` true if generic operations (`gadd`, `gmul`) do not make sense for `t`: corresponds to types `t_LIST`, `t_STR`, `t_VECSMALL`, `t_CLOSURE`

5.2.7 Accessors and components. The first two functions return GEN components as copies on the stack:

`GEN compo(GEN x, long n)` creates a copy of the `n`-th true component (i.e. not counting the codewords) of the object `x`.

`GEN truecoeff(GEN x, long n)` creates a copy of the coefficient of degree `n` of `x` if `x` is a scalar, `t_POL` or `t_SER`, and otherwise of the `n`-th component of `x`.

On the contrary, the following routines return the address of a GEN component. No copy is made on the stack:

`GEN constant_coeff(GEN x)` returns the address of the constant coefficient of `t_POL` `x`. By convention, a 0 polynomial (whose `sign` is 0) has `gen_0` constant term.

`GEN leading_coeff(GEN x)` returns the address of the leading coefficient of `t_POL` `x`, i.e. the coefficient of largest index stored in the array representing `x`. This may be an inexact 0. By convention, return `gen_0` if the coefficient array is empty.

`GEN gel(GEN x, long i)` returns the address of the `x[i]` entry of `x`. (`el` stands for element.)

`GEN gcoeff(GEN x, long i, long j)` returns the address of the `x[i,j]` entry of `t_MAT` `x`, i.e. the coefficient at row `i` and column `j`.

`GEN gmael(GEN x, long i, long j)` returns the address of the `x[i][j]` entry of `x`. (`mael` stands for multidimensional array element.)

`GEN gmael2(GEN A, long x1, long x2)` is an alias for `gmael`. Similar macros `gmael3`, `gmael4`, `gmael5` are available.

5.3 Global numerical constants.

These are defined in the various public PARI headers.

5.3.1 Constants related to word size.

`long BITS_IN_LONG = 2TWOPOTBITS_IN_LONG`: number of bits in a `long` (32 or 64).

`long BITS_IN_HALFULONG`: `BITS_IN_LONG` divided by 2.

`long LONG_MAX`: the largest positive `long`.

`ulong ULONG_MAX`: the largest `ulong`.

`long DEFAULTPREC`: the length (`lg`) of a `t_REAL` with 64 bits of accuracy

`long MEDDEFAULTPREC`: the length (`lg`) of a `t_REAL` with 128 bits of accuracy

`long BIGDEFAULTPREC`: the length (`lg`) of a `t_REAL` with 192 bits of accuracy

`ulong HIGHBIT`: the largest power of 2 fitting in an `ulong`.

`ulong LOWMASK`: bitmask yielding the least significant bits.

`ulong HIGHMASK`: bitmask yielding the most significant bits.

The last two are used to implement the following convenience macros, returning half the bits of their operand:

`ulong LOWWORD(ulong a)` returns least significant bits.

`ulong HIGHWORD(ulong a)` returns most significant bits.

Finally

`long divsBIL(long n)` returns the Euclidean quotient of n by `BITS_IN_LONG` (with nonnegative remainder).

`long remdBIL(n)` returns the (nonnegative) Euclidean remainder of n by `BITS_IN_LONG`

`long dvmdsBIL(long n, long *r)`

`ulong dvmdubIL(ulong n, ulong *r)` sets r to `remdBIL(n)` and returns `divsBIL(n)`.

5.3.2 Masks used to implement the GEN type.

These constants are used by higher level macros, like `typ` or `lg`:

`EXP0numBITS`, `LGnumBITS`, `SIGNnumBITS`, `TYPnumBITS`, `VALPnumBITS`, `VARNnumBITS`: number of bits used to encode `expo`, `lg`, `signe`, `typ`, `valp`, `varn`.

`PRECPSHIFT`, `SIGNSHIFT`, `TYPSHIFT`, `VARNSHIFT`: shifts used to recover or encode `precp`, `varn`, `typ`, `signe`

`CLONEBIT`, `EXPOBITS`, `LGBITS`, `PRECPBITS`, `SIGNBITS`, `TYPBITS`, `VALPBITS`, `VARNBITS`: bitmasks used to extract `isclone`, `expo`, `lg`, `precp`, `signe`, `typ`, `valp`, `varn` from `GEN` codewords.

`MAXVARN`: the largest possible variable number.

`NO_VARIABLE`: sentinel returned by `gvar(x)` when x does not contain any polynomial; has a lower priority than any valid variable number.

`HIGHEXPBIT`: a power of 2, one more than the largest possible exponent for a `t_REAL`.

`HIGHVALPBIT`: a power of 2, one more than the largest possible valuation for a `t_PADIC` or a `t_SER`.

5.3.3 $\log 2$, π .

These are **double** approximations to useful constants:

M_PI: π .

M_LN2: $\log 2$.

LOG10_2: $\log 2 / \log 10$.

LOG2_10: $\log 10 / \log 2$.

5.4 Iterating over small primes, low-level interface.

One of the methods used by the high-level prime iterator (see Section 4.8.2), is a precomputed table. Its direct use is deprecated, but documented here.

After `pari_init(size, maxprime)`, a prime table `pari PRIMES` is initialized with the successive primes up to (possibly just a little beyond) `maxprime`. The prime table occupies roughly $4\text{maxprime}/\log(\text{maxprime})$ bytes in memory, so be sensible when choosing `maxprime`; it is 2^{20} by default under `gp` and there is no real benefit in choosing a much larger value: the high-level iterator provide *fast* access to primes up to the *square* of `maxprime`. In any case, the implementation requires that `maxprime` $< 2^{\text{BITS_IN_LONG}} - 2048$, whatever memory is available. In fact, `maxprime` is automatically replaced by

`max(maxprime, 65557)` .

In particular, PARI guarantees that the first 6547 primes, up to and including 65557, are present in the table, even if you set `maxprime` to zero in the `pari_init` call.

Some convenience functions:

`ulong maxprime(void)` the largest prime computable using our prime table.

`ulong maxprimeN(void)` the index N of the largest prime computable using the prime table. I.e., $p_N = \text{maxprime}()$.

`GEN prodprimes(void)` a vector T where $T[i]$ is the product of the primes in our prime table that are smaller than 2^{7+i} . Used to quickly detect small prime divisors of large integers, using a few gcd's.

`ulong maxprimelim(void)` the argument used for the last `initprimetable` call. This is at least 65537 and the largest prime less than or equal to this number is `maxprime()`.

`long PRIMES_search(ulong x)` assumes $x \leq \text{maxprimelim}()$. Return $i > 0$ such that $x = \text{pari_PRIMES}[i]$ iff x is prime. Else return $-i < 0$ such that x lies (strictly) between the $(i-1)$ -th and the i -th prime; this is understood as $i = 1$ when $x < 2$: the statement about the non-existing 0-th prime is disregarded.

`void maxprime_check(ulong B)` raise an error if `maxprime()` is $< B$.

`void initprimetable(ulong maxprime)` computes the prime table `pari PRIMES` (of all primes $p < \text{maxprime}$). This caches data allowing fast `prodprimes()`.

5.5 Handling the PARI stack.

5.5.1 Allocating memory on the stack.

`GEN cgetg(long n, long t)` allocates memory on the stack for an object of length `n` and type `t`, and initializes its first codeword.

`GEN cgeti(long n)` allocates memory on the stack for a `t_INT` of length `n`, and initializes its first codeword. Identical to `cgetg(n, t_INT)`.

`GEN cgetr(long n)` allocates memory on the stack for a `t_REAL` of length `n`, and initializes its first codeword. Identical to `cgetg(n, t_REAL)`.

`GEN cgetc(long n)` allocates memory on the stack for a `t_COMPLEX`, whose real and imaginary parts are `t_REALs` of length `n`.

`GEN cgetp(GEN x)` creates space sufficient to hold the `t_PADIC x`, and sets the prime p and the p -adic precision to those of `x`, but does not copy (the p -adic unit or zero representative and the modulus of) `x`.

`GEN new_chunk(size_t n)` allocates a `GEN` with n components, *without* filling the required code words. This is the low-level constructor underlying `cgetg`, which calls `new_chunk` then sets the first code word. It works by simply returning the address `((GEN)avma) - n`, after checking that it is larger than `(GEN)bot`.

`void new_chunk_resize(size_t x)` this function is called by `new_chunk` when the PARI stack overflows. There is no need to call it manually. It will either extend the stack or report an `e_STACK` error.

`char* stack_malloc(size_t n)` allocates memory on the stack for n chars (*not* n `GENs`). This is faster than using `malloc`, and easier to use in most situations when temporary storage is needed. In particular there is no need to `free` individually all variables thus allocated: a simple `set_avma(oldavma)` might be enough. On the other hand, beware that this is not permanent independent storage, but part of the stack. The memory is aligned on `sizeof(long)` bytes boundaries.

`char* stack_malloc_align(size_t n, long k)` as `stack_malloc`, but the memory is aligned on k bytes boundaries. The number k must be a multiple of the `sizeof(long)`.

`char* stack_calloc(size_t n)` as `stack_malloc`, setting the memory to zero.

`char* stack_calloc_align(size_t n, long k)` as `stack_malloc_align`, setting the memory to zero.

Objects allocated through these last three functions cannot be `gerepile`'d, since they are not yet valid `GENs`: their codewords must be filled first.

`GEN cgetalloc(size_t l, long t)`, same as `cgetg(l, t)`, except that the result is allocated using `pari_malloc` instead of the PARI stack. The resulting `GEN` is now impervious to garbage collecting routines, but should be freed using `pari_free`.

5.5.2 Stack-independent binary objects.

`GENbin* copy_bin(GEN x)` copies x into a malloc'ed structure suitable for stack-independent binary transmission or storage. The object obtained is architecture independent provided, `sizeof(long)` remains the same on all PARI instances involved, as well as the multiprecision kernel (either native or GMP).

`GENbin* copy_bin_canon(GEN x)` as `copy_bin`, ensuring furthermore that the binary object is independent of the multiprecision kernel. Slower than `copy_bin`.

`GEN bin_copy(GENbin *p)` assuming p was created by `copy_bin(x)` (not necessarily by the same PARI instance: transmission or external storage may be involved), restores x on the PARI stack.

The routine `bin_copy` transparently encapsulate the following functions:

`GEN GENbinbase(GENbin *p)` the `GEN` data actually stored in p . All addresses are stored as offsets with respect to a common reference point, so the resulting `GEN` is unusable unless it is a nonrecursive type; private low-level routines must be called first to restore absolute addresses.

`void shiftaddress(GEN x, long dec)` converts relative addresses to absolute ones.

`void shiftaddress_canon(GEN x, long dec)` converts relative addresses to absolute ones, and converts leaves from a canonical form to the one specific to the multiprecision kernel in use. The `GENbin` type stores whether leaves are stored in canonical form, so `bin_copy` can call the right variant.

Objects containing closures are harder to e.g. copy and save to disk, since closures contain pointers to libpari functions that will not be valid in another gp instance: there is little chance for them to be loaded at the exact same address in memory. Such objects must be saved along with a linking table.

`GEN copybin_unlink(GEN C)` returns a linking table allowing to safely store and transmit `t_CLOSURE` objects in C . If $C = \text{NULL}$ return a linking table corresponding to the content of all gp variables. C may then be dumped to disk in binary form, for instance.

`void bincopy_relink(GEN C, GEN V)` given a binary object C , as dumped by `writebin` and read back into a session, and a linking table V , restore all closures contained in C (function pointers are translated to their current value).

5.5.3 Garbage collection. See Section 4.3 for a detailed explanation and many examples.

`void set_avma(ulong av)` reset `avma` to `av`. You may think of this as a simple `avma = av` statement, but PARI developers modify this statement in special code branches to detect garbage collecting issues (by invalidating the PARI stack below `av`).

`ulong get_avma(void)` return `avma`. Useful for languages that do not provide access to TLS variables.

`GEN gc_NULL(pari_sp av)` reset `avma` to `av` and return `NULL`.

The following 6 functions reset `avma` to `av` and return x :

`int gc_bool(pari_sp av, int x)`

`double gc_double(pari_sp av, double x)`

`int gc_int(pari_sp av, int x)`

`long gc_long(pari_sp av, long x)`

`ulong gc_ulong(pari_sp av, ulong x)` This allows for instance to return `gc_ulong(av, itou(z))`, whereas

```
    pari_sp av = avma;
    GEN z = ...
    set_avma(av);
    return itou(z);
```

should be frowned upon since `set_avma(av)` conceptually destroys everything from the reference point on, including `z`.

`GEN gc_const(pari_sp av, GEN x)` assumes that x is either not on the stack (clone, universal constant such as `gen_0`) or was defined before `av`.

`GEN gc_stoi(pari_sp av, long x)` reset `avma` to `av` and return `stoi(x)`.

`GEN gc_utoi(pari_sp av, long x)` reset `avma` to `av` and return `utoi(x)`.

`GEN gc_utoipos(pari_sp av, long x)` reset `avma` to `av` and return `utoipos(x)`.

`GEN gc_all(pari_sp av, int n, ...)`. Assumes that $1 \leq n \leq 10$; This is similar to `gerepileall`, expecting n further `GEN*` arguments: the stack is cleaned and the corresponding `GEN` are copied to the stack starting from `av` (in this order: the first argument comes first), and the first such `GEN` is returned. To be used in the following scenario:

```
    GEN f(..., GEN *py)
    {
        pari_sp av = avma;
        GEN x = ..., y = ...
        *py = y; return gc_all(av, 2, &x, py);
    }
```

This function returns x , and the user also recovers y as a side effect. Note that we can later use `cgiv(y)` to recover the memory used by y while still keeping x .

`void cgiv(GEN x)` frees object x , assuming it is the last created on the stack.

`GEN gerepile(pari_sp p, pari_sp q, GEN x)` general garbage collector for the stack.

`void gerepileall(pari_sp av, int n, ...)` cleans up the stack from `av` on (i.e. from `avma` to `av`), preserving the n objects which follow in the argument list (of type `GEN*`). For instance, `gerepileall(av, 2, &x, &y)` preserves x and y .

`void gerepileallsp(pari_sp av, pari_sp ltop, int n, ...)` cleans up the stack between `av` and `ltop`, updating the n elements which follow n in the argument list (of type `GEN*`). Check that the elements of g have no component between `av` and `ltop`, and assumes that no garbage is present between `avma` and `ltop`. Analogous to (but faster than) `gerepileall` otherwise.

`GEN gerepilecopy(pari_sp av, GEN x)` cleans up the stack from `av` on, preserving the object x . Special case of `gerepileall` (case $n = 1$), except that the routine returns the preserved `GEN` instead of updating its address through a pointer.

`void gerepilemany(pari_sp av, GEN* g[], int n)` alternative interface to `gerepileall`. The preserved `GENs` are the elements of the array g of length n : $g[0], g[1], \dots, g[n-1]$. Obsolete: no more efficient than `gerepileall`, error-prone, and clumsy (need to declare an extra `GEN *g`).

`void gerepilemanysp(pari_sp av, pari_sp ltop, GEN* g[], int n)` alternative interface to `gerepileallsp`. Obsolete.

`void gerepilecoeffs(pari_sp av, GEN x, int n)` cleans up the stack from `av` on, preserving `x[0], ..., x[n-1]` (which are GENs).

`void gerepilecoeffssp(pari_sp av, pari_sp ltop, GEN x, int n)` cleans up the stack from `av` to `ltop`, preserving `x[0], ..., x[n-1]` (which are GENs). Same assumptions as in `gerepilemanysp`, of which this is a variant. For instance

```
z = cgetg(3, t_COMPLEX);
av = avma; garbage(); ltop = avma;
z[1] = fun1();
z[2] = fun2();
gerepilecoeffssp(av, ltop, z + 1, 2);
return z;
```

cleans up the garbage between `av` and `ltop`, and connects `z` and its two components. This is marginally more efficient than the standard

```
av = avma; garbage(); ltop = avma;
z = cgetg(3, t_COMPLEX);
z[1] = fun1();
z[2] = fun2(); return gerepile(av, ltop, z);
```

GEN `gerepileupto(pari_sp av, GEN q)` analogous to (but faster than) `gerepilecopy`. Assumes that `q` is connected and that its root was created before any component. If `q` is not on the stack, this is equivalent to `set_avma(av)`; in particular, sentinels which are not even proper GENs such as `q = NULL` are allowed.

GEN `gerepileuptoint(pari_sp av, GEN q)` analogous to (but faster than) `gerepileupto`. Assumes further that `q` is a `t_INT`. The length and effective length of the resulting `t_INT` are equal.

GEN `gerepileuptoleaf(pari_sp av, GEN q)` analogous to (but faster than) `gerepileupto`. Assumes further that `q` is a leaf, i.e a nonrecursive type (`is_recursive_t(typ(q))` is nonzero). Contrary to `gerepileuptoint` and `gerepileupto`, `gerepileuptoleaf` leaves length and effective length of a `t_INT` unchanged.

5.5.4 Garbage collection: advanced use.

`void stackdummy(pari_sp av, pari_sp ltop)` inhibits the memory area between `av` *included* and `ltop` *excluded* with respect to `gerepile`, in order to avoid a call to `gerepile(av, ltop, ...)`. The stack space is not reclaimed though.

More precisely, this routine assumes that `av` is recorded earlier than `ltop`, then marks the specified stack segment as a nonrecursive type of the correct length. Thus `gerepile` will not inspect the zone, at most copy it. To be used in the following situation:

```
av0 = avma; z = cgetg(t_VEC, 3);
gel(z,1) = HUGE(); av = avma; garbage(); ltop = avma;
gel(z,2) = HUGE(); stackdummy(av, ltop);
```

Compared to the orthodox

```
gel(z,2) = gerepile(av, ltop, gel(z,2));
```

or even more wasteful

```
z = gerepilecopy(av0, z);
```

we temporarily lose $(av - ltop)$ words but save a costly `gerepile`. In principle, a garbage collection higher up the call chain should reclaim this later anyway.

Without the `stackdummy`, if the $[av, ltop]$ zone is arbitrary (not even valid GENs as could happen after direct truncation via `setlg`), we would leave dangerous data in the middle of z , which would be a problem for a later

```
gerepile(..., ... , z);
```

And even if it were made of valid GENs, inhibiting the area makes sure `gerepile` will not inspect their components, saving time.

Another natural use in low-level routines is to “shorten” an existing GEN z to its first $n - 1$ components:

```
setlg(z, n);
stackdummy((pari_sp)(z + lg(z)), (pari_sp)(z + n));
```

or to its last n components:

```
long L = lg(z) - n, tz = typ(z);
stackdummy((pari_sp)(z + L), (pari_sp)z);
z += L; z[0] = evaltyp(tz) | evallg(L);
```

The first scenario (safe shortening an existing GEN) is in fact so common, that we provide a function for this:

`void fixlg(GEN z, long ly)` a safe variant of `setlg(z, ly)`. If ly is larger than $lg(z)$ do nothing. Otherwise, shorten z in place, using `stackdummy` to avoid later `gerepile` problems.

`GEN gcopy_avma(GEN x, pari_sp *AVMA)` return a copy of x as from `gcopy`, except that we pretend that initially `avma` is `*AVMA`, and that `*AVMA` is updated accordingly (so that the total size of x is the difference between the two successive values of `*AVMA`). It is not necessary for `*AVMA` to initially point on the stack: `gclone` is implemented using this mechanism.

`GEN icopy_avma(GEN x, pari_sp av)` analogous to `gcopy_avma` but simpler: assume x is a `t_INT` and return a copy allocated as if initially we had `avma` equal to `av`. There is no need to pass a pointer and update the value of the second argument: the new (fictitious) `avma` is just the return value (typecast to `pari_sp`).

5.5.5 Debugging the PARI stack.

`int chk_gerepileupto(GEN x)` returns 1 if x is suitable for `gerepileupto`, and 0 otherwise. In the latter case, print a warning explaining the problem.

`void dbg_gerepile(pari_sp ltop)` outputs the list of all objects on the stack between `avma` and `ltop`, i.e. the ones that would be inspected in a call to `gerepile(..., ltop, ...)`.

`void dbg_gerepileupto(GEN q)` outputs the list of all objects on the stack that would be inspected in a call to `gerepileupto(..., q)`.

`void dbg_fill_stack(void)` marks the unused portion of the stack (between its bottom and `avma`) with repeated magic values: `0xBADC0FFEE0DDF00D` on 64-bit archs, and `0xDEADBEEF` on 32-bit. This allows to quickly detect garbage collection errors, e.g., objets one of whose component

would be overwritten later or uninitialized memory access. The `valgrind` framework more thorough possibilities but requires instrumenting the code.

5.5.6 Copies.

`GEN gcopy(GEN x)` creates a new copy of x on the stack.

`GEN gcopy_lg(GEN x, long l)` creates a new copy of x on the stack, pretending that `lg(x)` is l , which must be less than or equal to `lg(x)`. If equal, the function is equivalent to `gcopy(x)`.

`int isonstack(GEN x)` true iff x belongs to the stack.

`void copyifstack(GEN x, GEN y)` sets $y = gcopy(x)$ if x belongs to the stack, and $y = x$ otherwise. This macro evaluates its arguments once, contrary to

```
y = isonstack(x)? gcopy(x): x;
```

`void icopyifstack(GEN x, GEN y)` as `copyifstack` assuming x is a `t_INT`.

5.5.7 Simplify.

`GEN simplify(GEN x)` you should not need that function in library mode. One rather uses:

`GEN simplify_shallow(GEN x)` shallow, faster, version of `simplify`.

5.6 The PARI heap.

5.6.1 Introduction.

It is implemented as a doubly-linked list of `malloc`'ed blocks of memory, equipped with reference counts. Each block has type `GEN` but need not be a valid `GEN`: it is a chunk of data preceded by a hidden header (meaning that we allocate x and return $x + \text{headersize}$). A *clone*, created by `gclone`, is a block which is a valid `GEN` and whose *clone bit* is set.

5.6.2 Public interface.

`GEN newblock(size_t n)` allocates a block of n words (not bytes).

`void killblock(GEN x)` deletes the block x created by `newblock`. Fatal error if x not a block.

`GEN gclone(GEN x)` creates a new permanent copy of x on the heap (allocated using `newblock`). The *clone bit* of the result is set.

`GEN gcloneref(GEN x)` if x is not a clone, clone it and return the result; otherwise, increase the clone reference count and return x .

`void gunclone(GEN x)` deletes a clone. Deletion at first only decreases the reference count by 1. If the count remains positive, no further action is taken; if the count becomes zero, then the clone is actually deleted. In the current implementation, this is an alias for `killblock`, but it is cleaner to kill clones (valid `GENs`) using this function, and other blocks using `killblock`.

`void guncloneNULL(GEN x)` same as `gunclone`, first checking whether x is `NULL` (and doing nothing in this case).

`void gunclone_deep(GEN x)` is only useful in the context of the GP interpreter which may replace arbitrary components of container types (`t_VEC`, `t_COL`, `t_MAT`, `t_LIST`) by clones. If x is such a

container, the function recursively deletes all clones among the components of x , then unclones x . Useless in library mode: simply use `guncclone`.

`void gunccloneNULL_deep(GEN x)` same as `guncclone_deep`, first checking whether x is NULL (and doing nothing in this case).

`void traverseheap(void(*f)(GEN, void*), void *data)` this applies $f(x, data)$ to each object x on the PARI heap, most recent first. Mostly for debugging purposes.

`GEN getheap()` a simple wrapper around `traverseheap`. Returns a two-component row vector giving the number of objects on the heap and the amount of memory they occupy in long words.

`GEN cgetg_block(long x, long y)` as `cgetg(x,y)`, creating the return value as a block, not on the PARI stack.

`GEN cgetr_block(long prec)` as `cgetr(prec)`, creating the return value as a block, not on the PARI stack.

5.6.3 Implementation note. The hidden block header is manipulated using the following private functions:

`void* bl_base(GEN x)` returns the pointer that was actually allocated by `malloc` (can be freed).

`long bl_refc(GEN x)` the reference count of x : the number of pointers to this block. Decrementing in `killblock`, incremented by the private function `void gclone_refc(GEN x)`; block is freed when the reference count reaches 0.

`long bl_num(GEN x)` the index of this block in the list of all blocks allocated so far (including freed blocks). Uniquely identifies a block until $2^{\text{BITS_IN_LONG}}$ blocks have been allocated and this wraps around.

`GEN bl_next(GEN x)` the block *after* x in the linked list of blocks (NULL if x is the last block allocated not yet killed).

`GEN bl_prev(GEN x)` the block allocated *before* x (never NULL).

We documented the last four routines as functions for clarity (and type checking) but they are actually macros yielding valid lvalues. It is allowed to write `bl_refc(x)++` for instance.

5.7 Handling user and temp variables.

Low-level implementation of user / temporary variables is liable to change. We describe it nevertheless for completeness. Currently variables are implemented by a single array of values divided in 3 zones: `0–nvar` (user variables), `max_avail–MAXVARN` (temporary variables), and `nvar+1–max_avail–1` (pool of free variable numbers).

5.7.1 Low-level.

`void pari_var_init()`: a small part of `pari_init`. Resets variable counters `nvar` and `max_avail`, notwithstanding existing variables! In effect, this even deletes `x`. Don't use it.

`void pari_var_close(void)` attached destructor, called by `pari_close`.

`long pari_var_next()`: returns `nvar`, the number of the next user variable we can create.

`long pari_var_next_temp()` returns `max_avail`, the number of the next temp variable we can create.

`long pari_var_create(entree *ep)` low-level initialization of an `EpVAR`. Return the attached (new) variable number.

`GEN vars_sort_inplace(GEN z)` given a `t_VECSMALL` `z` of variable numbers, sort `z` in place according to variable priorities (highest priority comes first).

`GEN vars_to_RgXV(GEN h)` given a `t_VECSMALL` `z` of variable numbers, return the `t_VEC` of `pol_x(z[i])`.

5.7.2 User variables.

`long fetch_user_var(char *s)` returns a user variable whose name is `s`, creating it is needed (and using an existing variable otherwise). Returns its variable number.

`GEN fetch_var_value(long v)` returns a shallow copy of the current value of the variable numbered `v`. Return `NULL` for a temporary variable.

`entree* is_entry(const char *s)` returns the `entree*` attached to an identifier `s` (variable or function), from the interpreter hashtables. Return `NULL` if the identifier is unknown.

5.7.3 Temporary variables.

`long fetch_var(void)` returns the number of a new temporary variable (decreasing `max_avail`).

`long delete_var(void)` delete latest temp variable created and return the number of previous one.

`void name_var(long n, char *s)` rename temporary variable number `n` to `s`; mostly useful for nicer printout. Error when trying to rename a user variable.

5.8 Adding functions to PARI.

5.8.1 Nota Bene. As mentioned in the `COPYING` file, modified versions of the PARI package can be distributed under the conditions of the GNU General Public License. If you do modify PARI, however, it is certainly for a good reason, and we would like to know about it, so that everyone can benefit from your changes. There is then a good chance that your improvements are incorporated into the next release.

We classify changes to PARI into four rough classes, where changes of the first three types are almost certain to be accepted. The first type includes all improvements to the documentation, in a broad sense. This includes correcting typos or inaccuracies of course, but also items which are not really covered in this document, e.g. if you happen to write a tutorial, or pieces of code exemplifying fine points unduly omitted in the present manual.

The second type is to expand or modify the configuration routines and skeleton files (the `Configure` script and anything in the `config/` subdirectory) so that compilation is possible (or easier, or more efficient) on an operating system previously not catered for. This includes discovering and removing idiosyncrasies in the code that would hinder its portability.

The third type is to modify existing (mathematical) code, either to correct bugs, to add new functionality to existing functions, or to improve their efficiency.

Finally the last type is to add new functions to PARI. We explain here how to do this, so that in particular the new function can be called from `gp`.

5.8.2 Coding guidelines. Code your function in a file of its own, using as a guide other functions in the PARI sources. One important thing to remember is to clean the stack before exiting your main function, since otherwise successive calls to the function clutters the stack with unnecessary garbage, and stack overflow occurs sooner. Also, if it returns a `GEN` and you want it to be accessible to `gp`, you have to make sure this `GEN` is suitable for `gerepileupto` (see Section 4.3).

If error messages or warnings are to be generated in your function, use `pari_err` and `pari_warn` respectively. Recall that `pari_err` does not return but ends with a `longjmp` statement. As well, instead of explicit `printf` / `fprintf` statements, use the following encapsulated variants:

`void pari_putc(char c):` write character `c` to the output stream.

`void pari_puts(char *s):` write `s` to the output stream.

`void pari_printf(const char *fmt, ...):` write following arguments to the output stream, according to the conversion specifications in format `fmt` (see `printf`).

`void err_printf(const char *fmt, ...):` as `pari_printf`, writing to PARI's current error stream.

`void err_flush(void)` flush error stream.

Declare all public functions in an appropriate header file, if you want to access them from C. The other functions should be declared `static` in your file.

Your function is now ready to be used in library mode after compilation and creation of the library. If possible, compile it as a shared library (see the `Makefile` coming with the `extgcd` example in the distribution). It is however still inaccessible from `gp`.

5.8.3 GP prototypes, parser codes. A *GP prototype* is a character string describing all the GP parser needs to know about the function prototype. It contains a sequence of the following atoms:

- Return type: **GEN** by default (must be valid for **gerepileupto**), otherwise the following can appear as the *first* char of the code string:

```

i      return int
l      return long
u      return ulong
v      return void
m      return a GEN which is not gerepile-safe.
```

The **m** code is used for member functions, to avoid unnecessary copies. A copy opcode is generated by the compiler if the result needs to be kept safe for later use.

- Mandatory arguments, appearing in the same order as the input arguments they describe:

```

G      GEN
&      *GEN
L      long (we implicitly typecast int to long)
U      ulong
V      loop variable
n      variable, expects a variable number (a long, not an *entree)
W      a GEN which is a lvalue to be modified in place (for t_LIST)
r      raw input (treated as a string without quotes). Quoted args are copied as strings
        Stops at first unquoted ')' or ',,'. Special chars can be quoted using '\ '
        Example: aa"b\n)"c yields the string "aab\n)c"
s      expanded string. Example: Pi"x"2 yields "3.142x2"
        Unquoted components can be of any PARI type, converted to string following
        current output format
I      closure whose value is ignored, as in for loops,
        to be processed by void closure_evalvoid(GEN C)
E      closure whose value is used, as in sum loops,
        to be processed by void closure_evalgen(GEN C)
J      implicit function of arity 1, as in parsum loops,
        to be processed by void closure_callgen1(GEN C)
```

A *closure* is a GP function in compiled (bytecode) form. It can be efficiently evaluated using the `closure_evalxxx` functions.

- Automatic arguments:

```

f      Fake *long. C function requires a pointer but we do not use the resulting long
b      current real precision in bits
p      current real precision in bits, rounded up to a multiple of BITS_IN_LONG
P      series precision (default seriesprecision, global variable precdl for the library)
C      lexical context (internal, for eval, see localvars_read_str)
```

- Syntax requirements, used by functions like **for**, **sum**, etc.:
 - = separator = required at this point (between two arguments)

- Optional arguments and default values:

```

E*     any number of expressions, possibly 0 (see E)
s*     any number of strings, possibly 0 (see s)
```

Dxxx argument can be omitted and has a default value

The **E*** code reads all remaining arguments in closure context and passes them as a single **t_VEC**. The **s*** code reads all remaining arguments in *string context* and passes the list of strings as a single **t_VEC**. The automatic concatenation rules in string context are implemented so that adjacent strings are read as different arguments, as if they had been comma-separated. For instance, if the remaining argument sequence is: "**xx**" 1, "**yy**", the **s*** atom sends [**a**, **b**, **c**], where *a*, *b*, *c* are GENs of type **t_STR** (content "**xx**"), **t_INT** (equal to 1) and **t_STR** (content "**yy**").

The format to indicate a default value (atom starts with a **D**) is "**Dvalue,type,**", where *type* is the code for any mandatory atom (previous group), *value* is any valid GP expression which is converted according to *type*, and the ending comma is mandatory. For instance **D0,L**, stands for "this optional argument is converted to a **long**, and is 0 by default". So if the user-given argument reads 1 + 3 at this point, **4L** is sent to the function; and **0L** if the argument is omitted. The following special notations are available:

DG	optional GEN , send NULL if argument omitted.
D&	optional *GEN , send NULL if argument omitted. The argument must be prefixed by & .
DI , DE	optional closure, send NULL if argument omitted.
DP	optional long , send precd1 if argument omitted.
DV	optional loop variable.
Dn	optional variable number, -1 if omitted.
Dr	optional raw string, send NULL if argument omitted.
Ds	optional char * , send NULL if argument omitted.

Hardcoded limit. C functions using more than 20 arguments are not supported. Use vectors if you really need that many parameters.

When the function is called under **gp**, the prototype is scanned and each time an atom corresponding to a mandatory argument is met, a user-given argument is read (**gp** outputs an error message if the argument was missing). Each time an optional atom is met, a default value is inserted if the user omits the argument. The "automatic" atoms fill in the argument list transparently, supplying the current value of the corresponding variable (or a dummy pointer).

For instance, here is how you would code the following prototypes, which do not involve default values:

GEN f(GEN x, GEN y, long prec)	----> " GGp "
void f(GEN x, GEN y, long prec)	----> " vGGp "
void f(GEN x, long y, long prec)	----> " vGLp "
long f(GEN x)	----> " lG "
int f(long x)	----> " iL "

If you want more examples, **gp** gives you easy access to the parser codes attached to all GP functions: just type **\h function**. You can then compare with the C prototypes as they stand in **paridecl.h**.

Remark. If you need to implement complicated control statements (probably for some improved summation functions), you need to know how the parser implements closures and lexicals and how the evaluator lets you deal with them, in particular the `push_lex` and `pop_lex` functions. Check their descriptions and adapt the source code in `language/sumiter.c` and `language/intnum.c`.

5.8.4 Integration with `gp` as a shared module.

In this section we assume that your Operating System is supported by `install`. You have written a function in C following the guidelines in Section 5.8.2; in case the function returns a `GEN`, it must satisfy `gerepileupto` assumptions (see Section 4.3).

You then succeeded in building it as part of a shared library and want to finally tell `gp` about your function. First, find a name for it. It does not have to match the one used in library mode, but consistency is nice. It has to be a valid GP identifier, i.e. use only alphabetic characters, digits and the underscore character (`_`), the first character being alphabetic.

Then figure out the correct parser code corresponding to the function prototype (as explained in Section 5.8.3) and write a GP script like the following:

```
install(libname, code, gpname, library)
addhelp(gpname, "some help text")
```

The `addhelp` part is not mandatory, but very useful if you want others to use your module. `libname` is how the function is named in the library, usually the same name as one visible from C.

Read that file from your `gp` session, for instance from your preferences file (or `gprc`), and that's it. You can now use the new function `gpname` under `gp`, and we would very much like to hear about it!

Example. A complete description could look like this:

```
{
  install(bnfinit0, "GD0,L,DGp", ClassGroupInit, "libpari.so");
  addhelp(ClassGroupInit, "ClassGroupInit(P,{flag=0},{data=[]}):
    compute the necessary data for ...");
}
```

which means we have a function `ClassGroupInit` under `gp`, which calls the library function `bnfinit0`. The function has one mandatory argument, and possibly two more (two '`D`' in the code), plus the current real precision. More precisely, the first argument is a `GEN`, the second one is converted to a `long` using `itos` (0 is passed if it is omitted), and the third one is also a `GEN`, but we pass `NULL` if no argument was supplied by the user. This matches the C prototype (from `paridecl.h`):

```
GEN bnfinit0(GEN P, long flag, GEN data, long prec)
```

This function is in fact coded in `basemath/buch2.c`, and is in this case completely identical to the GP function `bnfinit` but `gp` does not need to know about this, only that it can be found somewhere in the shared library `libpari.so`.

Important note. You see in this example that it is the function's responsibility to correctly interpret its operands: `data = NULL` is interpreted *by the function* as an empty vector. Note that since `NULL` is never a valid GEN pointer, this trick always enables you to distinguish between a default value and actual input: the user could explicitly supply an empty vector!

5.8.5 Library interface for `install`.

There is a corresponding library interface for this `install` functionality, letting you expand the GP parser/evaluator available in the library with new functions from your C source code. Functions such as `gp_read_str` may then evaluate a GP expression sequence involving calls to these new function!

```
entree * install(void *f, const char *gpname, const char *code)
```

where `f` is the (address of the) function (cast to `void*`), `gpname` is the name by which you want to access your function from within your GP expressions, and `code` is as above.

5.8.6 Integration by patching `gp`.

If `install` is not available, and installing Linux or a BSD operating system is not an option (why?), you have to hardcode your function in the `gp` binary. Here is what needs to be done:

- Fetch the complete sources of the PARI distribution.
- Drop the function source code module in an appropriate directory (a priori `src/modules`), and declare all public functions in `src/headers/paridecl.h`.
- Choose a help section and add a file `src/functions/section/gpname` containing the following, keeping the notation above:

```
Function:  gpname
Section:   section
C-Name:    libname
Prototype: code
Help:      some help text
```

(If the help text does not fit on a single line, continuation lines must start by a whitespace character.) Two GP2C-related fields (`Description` and `Wrapper`) are also available to improve the code GP2C generates when compiling scripts involving your function. See the GP2C documentation for details.

- Launch `Configure`, which should pick up your C files and build an appropriate `Makefile`. At this point you can recompile `gp`, which will first rebuild the functions database.

Example. We reuse the `ClassGroupInit` / `bnfinit0` from the preceding section. Since the C source code is already part of PARI, we only need to add a file

```
functions/number_fields/ClassGroupInit
```

containing the following:

```
Function: ClassGroupInit
Section: number_fields
C-Name: bnfinit0
Prototype: GD0,L,DGp
Help: ClassGroupInit(P,{flag=0},{tech=[]}): this routine does ...
```

and recompile `gp`.

5.9 Globals related to PARI configuration.

5.9.1 PARI version numbers.

`paricfg_version_code` encodes in a single `long`, the Major and minor version numbers as well as the patchlevel.

`long PARI_VERSION(long M, long m, long p)` produces the version code attached to release $M.m.p$. Each code identifies a unique PARI release, and corresponds to the natural total order on the set of releases (bigger code number means more recent release).

`PARI_VERSION_SHIFT` is the number of bits used to store each of the integers M, m, p in the version code.

`paricfg_vcsversion` is a version string related to the revision control system used to handle your sources, if any. For instance `git-commit hash` if compiled from a git repository.

The two character strings `paricfg_version` and `paricfg_buildinfo`, correspond to the first two lines printed by `gp` just before the Copyright message. The character string `paricfg_compileddate` is the date of compilation which appears on the next line. The character string `paricfg_mt_engine` is the name of the threading engine on the next line.

In the string `paricfg_buildinfo`, the substring `"%s"` needs to be substituted by the output of the function `pari_kernel_version`.

```
const char * pari_kernel_version(void)
```

`GEN pari_version()` returns the version number as a PARI object, a `t_VEC` with three `t_INT` and one `t_STR` components.

5.9.2 Miscellaneous.

`paricfg_datadir`: character string. The location of PARI's `datadir`.

`paricfg_gphelp`: character string. The name of an external help command for ?? (such as the `gphelp` script)

Chapter 6:

Arithmetic kernel: Level 0 and 1

6.1 Level 0 kernel (operations on ulongs).

6.1.1 Micro-kernel. The Level 0 kernel simulates basic operations of the 68020 processor on which PARI was originally implemented. They need “global” `ulong` variables `overflow` (which will contain only 0 or 1) and `hiremainder` to function properly. A routine using one of these lowest-level functions where the description mentions either `hiremainder` or `overflow` must declare the corresponding

```
LOCAL_HIREMAINDER; /* provides 'hiremainder' */
LOCAL_OVERFLOW;    /* provides 'overflow' */
```

in a declaration block. Variables `hiremainder` and `overflow` then become available in the enclosing block. For instance a loop over the powers of an `ulong p` protected from overflows could read

```
while (pk < lim)
{
    LOCAL_HIREMAINDER;
    ...
    pk = mulll(pk, p); if (hiremainder) break;
}
```

For most architectures, the functions mentioned below are really chunks of inlined assembler code, and the above ‘global’ variables are actually local register values.

`ulong addll(ulong x, ulong y)` adds `x` and `y`, returns the lower `BITS_IN_LONG` bits and puts the carry bit into `overflow`.

`ulong addllx(ulong x, ulong y)` adds `overflow` to the sum of the `x` and `y`, returns the lower `BITS_IN_LONG` bits and puts the carry bit into `overflow`.

`ulong subll(ulong x, ulong y)` subtracts `x` and `y`, returns the lower `BITS_IN_LONG` bits and put the carry (borrow) bit into `overflow`.

`ulong subllx(ulong x, ulong y)` subtracts `overflow` from the difference of `x` and `y`, returns the lower `BITS_IN_LONG` bits and puts the carry (borrow) bit into `overflow`.

`int bfffo(ulong x)` returns the number of leading zero bits in `x`. That is, the number of bit positions by which it would have to be shifted left until its leftmost bit first becomes equal to 1, which can be between 0 and `BITS_IN_LONG - 1` for nonzero `x`. When `x` is 0, the result is undefined.

`ulong mulll(ulong x, ulong y)` multiplies `x` by `y`, returns the lower `BITS_IN_LONG` bits and stores the high-order `BITS_IN_LONG` bits into `hiremainder`.

`ulong addmul(ulong x, ulong y)` adds `hiremainder` to the product of `x` and `y`, returns the lower `BITS_IN_LONG` bits and stores the high-order `BITS_IN_LONG` bits into `hiremainder`.

`ulong divll(ulong x, ulong y)` returns the quotient of $(\text{hiremainder} * 2^{\text{BITS_IN_LONG}}) + x$ by y and stores the remainder into `hiremainder`. An error occurs if the quotient cannot be represented by an `ulong`, i.e. if initially $\text{hiremainder} \geq y$.

`long hammingl(ulong x)` returns the Hamming weight of x , i.e. the number of nonzero bits in its binary expansion.

Obsolete routines. Those functions are awkward and no longer used; they are only provided for backward compatibility:

`ulong shiftl(ulong x, ulong y)` returns x shifted left by y bits, i.e. $x \ll y$, where we assume that $0 \leq y \leq \text{BITS_IN_LONG}$. The global variable `hiremainder` receives the bits that were shifted out, i.e. $x \gg (\text{BITS_IN_LONG} - y)$.

`ulong shiftr(ulong x, ulong y)` returns x shifted right by y bits, i.e. $x \gg y$, where we assume that $0 \leq y \leq \text{BITS_IN_LONG}$. The global variable `hiremainder` receives the bits that were shifted out, i.e. $x \ll (\text{BITS_IN_LONG} - y)$.

6.1.2 Modular kernel. The following routines are not part of the level 0 kernel per se, but implement modular operations on words in terms of the above. They are written so that no overflow may occur. Let $m \geq 1$ be the modulus; all operands representing classes modulo m are assumed to belong to $[0, m - 1]$. The result may be wrong for a number of reasons otherwise: it may not be reduced, overflow can occur, etc.

`int odd(ulong x)` returns 1 if x is odd, and 0 otherwise.

`int both_odd(ulong x, ulong y)` returns 1 if x and y are both odd, and 0 otherwise.

`ulong invmod2BIL(ulong x)` returns the smallest positive representative of $x^{-1} \bmod 2^{\text{BITS_IN_LONG}}$, assuming x is odd.

`ulong Fl_add(ulong x, ulong y, ulong m)` returns the smallest nonnegative representative of $x + y$ modulo m .

`ulong Fl_neg(ulong x, ulong m)` returns the smallest nonnegative representative of $-x$ modulo m .

`ulong Fl_sub(ulong x, ulong y, ulong m)` returns the smallest nonnegative representative of $x - y$ modulo m .

`long Fl_center(ulong x, ulong m, ulong mo2)` returns the representative in $] -m/2, m/2]$ of x modulo m . Assume $0 \leq x < m$ and $\text{mo2} = m \gg 1$.

`ulong Fl_mul(ulong x, ulong y, ulong m)` returns the smallest nonnegative representative of xy modulo m .

`ulong Fl_double(ulong x, ulong m)` returns $2x$ modulo m .

`ulong Fl_triple(ulong x, ulong m)` returns $3x$ modulo m .

`ulong Fl_half(ulong x, ulong m)` returns z such that $2z = x$ modulo m assuming such z exists.

`ulong Fl_sqr(ulong x, ulong m)` returns the smallest nonnegative representative of x^2 modulo m .

`ulong Fl_inv(ulong x, ulong m)` returns the smallest positive representative of x^{-1} modulo m . If x is not invertible mod m , raise an exception.

`ulong Fl_invsafe(ulong x, ulong m)` returns the smallest positive representative of x^{-1} modulo m . If x is not invertible mod m , return 0 (which is ambiguous if $m = 1$).

`ulong Fl_invgen(ulong x, ulong m, ulong *pg)` set `*pg` to $g = \gcd(x, m)$ and return u in $(\mathbf{Z}/m\mathbf{Z})^*$ such that $xu = g$ modulo m . We have $g = 1$ if and only if x is invertible, and in this case u is its inverse.

`ulong Fl_div(ulong x, ulong y, ulong m)` returns the smallest nonnegative representative of xy^{-1} modulo m . If y is not invertible mod m , raise an exception.

`ulong Fl_powu(ulong x, ulong n, ulong m)` returns the smallest nonnegative representative of x^n modulo m .

`GEN Fl_powers(ulong x, long n, ulong p)` returns $[x^0, \dots, x^n]$ modulo m , as a `t_VECSMALL`.

`ulong Fl_sqrt(ulong x, ulong p)` returns the square root of x modulo p (smallest nonnegative representative). Assumes p to be prime, and x to be a square modulo p .

`ulong Fl_sqrtl(ulong x, ulong l, ulong p)` returns a l -th root of x modulo p . Assumes p to be prime and $p \equiv 1 \pmod{l}$, and x to be a l -th power modulo p .

`ulong Fl_sqrtn(ulong a, ulong n, ulong p, ulong *zn)` returns `ULONG_MAX` if a is not an n -th power residue mod p . Otherwise, returns an n -th root of a ; if `zn` is not `NULL` set it to a primitive m -th root of 1, $m = \gcd(p-1, n)$ allowing to compute all m solutions in \mathbf{F}_p of the equation $x^n = a$.

`ulong Fl_log(ulong a, ulong g, ulong ord, ulong p)` Let g such that $g^{\text{ord}} \equiv 1 \pmod{p}$. Return an integer e such that $a^e \equiv g \pmod{p}$. If e does not exist, the result is undefined.

`ulong Fl_order(ulong a, ulong o, ulong p)` returns the order of the \mathbf{F}_p a . It is assumed that o is a multiple of the order of a , 0 being allowed (no nontrivial information).

`ulong random_Fl(ulong p)` returns a pseudo-random integer uniformly distributed in $0, 1, \dots, p-1$.

`ulong nonsquare_Fl(ulong p)` return a quadratic nonresidue modulo p , assuming p is an odd prime. If p is 3 mod 4, return $p-1$, else return the smallest (prime) nonresidue.

`ulong pgener_Fl(ulong p)` returns the smallest primitive root modulo p , assuming p is prime.

`ulong pgener_Zl(ulong p)` returns the smallest positive integer which is a primitive root modulo p^k for all $k \geq 1$, assuming p is an odd prime.

`ulong pgener_Fl_local(ulong p, GEN L)`, see `gener_Fp_local`, L is an `Flv`.

`ulong factorial_Fl(long n, ulong p)` return $n! \bmod p$.

6.1.3 Modular kernel with “precomputed inverse”.

This is based on an algorithm by T. Grandlund and N. Möller in “Improved division by invariant integers” <https://gmplib.org/~tege/division-paper.pdf>.

In the following, we set $B = \text{BITS_IN_LONG}$.

`ulong get_Fl_red(ulong p)` returns a pseudoinverse pi for p . Namely an integer $0 < pi < B$ such that, given $0 \leq x < B^2$ (by two long words), we can compute the Euclidean quotient and remainder of x modulo p by performing 2 multiplications and some additions. Precisely, once we set $q = 2^k p$ for the unique k such that $B/2 \leq q < B$, the pseudoinverse pi is equal to the Euclidean quotient of $B^2 - qB + B - 1$ by q . In particular $(pi + B)/B^2$ is very close to $1/q$.

Note that this algorithm is generally less efficient than ordinary quotient and remainders (`divll` or even `/` and `%`) when $0 \leq x < B$ and $p \leq B^{1/2}$ are small. High level functions below allow setting $pi = 0$ to cater for this possibility and avoid calling `get_Fl_red` for arguments where the standard algorithm is preferable.

`ulong divll_pre(ulong x, ulong p, ulong pi)` as `divll`, where pi is the pseudoinverse of p .

`ulong remll_pre(ulong u1, ulong u0, ulong p, ulong pi)` returns the Euclidean remainder of $u_1 2^B + u_0$ modulo p , assuming pi is the pseudoinverse of p . This function is faster if $u_1 < p$.

`ulong remlll_pre(ulong u2, ulong u1, ulong u0, ulong p, ulong pi)` returns the Euclidean remainder of $u_2 2^{2B} + u_1 2^B + u_0$ modulo p , assuming pi is the pseudoinverse of p .

`ulong Fl_sqr_pre(ulong x, ulong p, ulong pi)` returns x^2 modulo p , assuming pi is the pseudoinverse of p .

`ulong Fl_mul_pre(ulong x, ulong y, ulong p, ulong pi)` returns xy modulo p , assuming pi is the pseudoinverse of p .

`ulong Fl_addmul_pre(ulong a, ulong b, ulong c, ulong p, ulong pi)` returns $a + bc$ modulo p , assuming pi is the pseudoinverse of p .

`ulong Fl_addmulmul_pre(ulong a, ulong b, ulong c, ulong d, ulong p, ulong pi)` returns $ab + cd$ modulo p , assuming pi is the pseudoinverse of p .

`ulong Fl_powu_pre(ulong x, ulong n, ulong p, ulong pi)` returns x^n modulo p , assuming pi is the pseudoinverse of p , or 0 in which case we either use ordinary divisions if $p < B^{1/2}$ is small and call `get_Fl_red` ourselves otherwise.

`GEN Fl_powers_pre(ulong x, long n, ulong p, ulong pi)` returns the vector (`t_VECSMALL`) (x^0, \dots, x^n) , assuming pi is the pseudoinverse of p , or 0 in which case we either use ordinary divisions if $p < B^{1/2}$ is small and call `get_Fl_red` ourselves otherwise.

`ulong Fl_log_pre(ulong a, ulong g, ulong ord, ulong p, ulong pi)` as `Fl_log`, assuming pi is the pseudoinverse of p , or 0 in which case we either use ordinary divisions if $p < B^{1/2}$ is small and call `get_Fl_red` ourselves otherwise.

`ulong Fl_sqrt_pre(ulong x, ulong p, ulong pi)` returns a square root of x modulo p , see `Fl_sqrt`. We assume pi is the pseudoinverse of p , or 0 in which case we either use ordinary divisions if $p < B^{1/2}$ is small and call `get_Fl_red` ourselves otherwise.

`ulong Fl_sqrtl_pre(ulong x, ulong l, ulong p, ulong pi)` returns a l -th root of x modulo p , assuming p prime, $p \equiv 1 \pmod{l}$, and x to be a l -th power modulo p . We assume pi is the pseudoinverse of p , or 0 in which case we either use ordinary divisions if $p < B^{1/2}$ is small and call `get_Fl_red` ourselves otherwise.

`ulong Fl_sqrtn_pre(ulong x, ulong n, ulong p, ulong pi, ulong *zn)` See `Fl_sqrtn`, assuming pi is the pseudoinverse of p , or 0 in which case we either use ordinary divisions if $p < B^{1/2}$ is small and call `get_Fl_red` ourselves otherwise.

`ulong Fl_2gener_pre(ulong p, ulong pi)` return a generator of the 2-Sylow subgroup of \mathbf{F}_p^* , to be used in `Fl_sqrt_pre_i`. We assume pi is the pseudoinverse of p , or 0 in which case we either use ordinary divisions if $p < B^{1/2}$ is small and call `get_Fl_red` ourselves otherwise.

`ulong Fl_2gener_pre_i(ulong ns, ulong p, ulong pi)` as `Fl_2gener_pre` where ns is a non-square modulo p .

ulong Fl_sqrt_pre_i(ulong x, ulong s2, ulong p, ulong pi) as Fl_sqrt_pre where s2 is the element returned by Fl_2gener_pre. We assume pi is the pseudoinverse of p , or 0 in which case we either use ordinary divisions if $p < B^{1/2}$ is small and call get_Fl_red ourselves otherwise.

6.1.4 Switching between Fl_xxx and standard operators.

Even though the Fl_xxx routines are efficient, they are slower than ordinary long operations, using the standard +, %, etc. operators. The following macro is used to choose in a portable way the most efficient functions for given operands:

int SMALL_ULONG(ulong p) true if $2p^2 < 2^{\text{BITS_IN_LONG}}$. In that case, it is possible to use ordinary operators efficiently. If $p < 2^{\text{BITS_IN_LONG}}$, one may still use the Fl_xxx routines. Otherwise, one must use generic routines. For instance, the scalar product of the GENs x and y mod p could be computed as follows.

```

long i, l = lg(x);
if (lgefint(p) > 3)
{ /* arbitrary */
    GEN s = gen_0;
    for (i = 1; i < l; i++) s = addii(s, mulii(gel(x,i), gel(y,i)));
    return modii(s, p).
}
else
{
    ulong s = 0, pp =itou(p);
    x = ZV_to_Flv(x, pp);
    y = ZV_to_Flv(y, pp);
    if (SMALL_ULONG(pp))
    { /* very small */
        for (i = 1; i < l; i++)
        {
            s += x[i] * y[i];
            if (s & HIGHBIT) s %= pp;
        }
        s %= pp;
    }
    else
    { /* small */
        for (i = 1; i < l; i++)
            s = Fl_add(s, Fl_mul(x[i], y[i], pp), pp);
    }
    return utoi(s);
}

```

In effect, we have three versions of the same code: very small, small, and arbitrary inputs. The very small and arbitrary variants use lazy reduction and reduce only when it becomes necessary: when overflow might occur (very small), and at the very end (very small, arbitrary).

6.2 Level 1 kernel (operations on longs, integers and reals).

Note. Some functions consist of an elementary operation, immediately followed by an assignment statement. They will be introduced as in the following example:

`GEN gadd[z](GEN x, GEN y[, GEN z])` followed by the explicit description of the function

`GEN gadd(GEN x, GEN y)`

which creates its result on the stack, returning a GEN pointer to it, and the parts in brackets indicate that there exists also a function

`void gaddz(GEN x, GEN y, GEN z)`

which assigns its result to the pre-existing object `z`, leaving the stack unchanged. These assignment variants are kept for backward compatibility but are inefficient: don't use them.

6.2.1 Creation.

`GEN cgeti(long n)` allocates memory on the PARI stack for a `t_INT` of length `n`, and initializes its first codeword. Identical to `cgetg(n,t_INT)`.

`GEN cgetipos(long n)` allocates memory on the PARI stack for a `t_INT` of length `n`, and initializes its two codewords. The sign of `n` is set to 1.

`GEN cgetineg(long n)` allocates memory on the PARI stack for a negative `t_INT` of length `n`, and initializes its two codewords. The sign of `n` is set to -1 .

`GEN cgetr(long n)` allocates memory on the PARI stack for a `t_REAL` of length `n`, and initializes its first codeword. Identical to `cgetg(n,t_REAL)`.

`GEN cgetc(long n)` allocates memory on the PARI stack for a `t_COMPLEX`, whose real and imaginary parts are `t_REALs` of length `n`.

`GEN real_1(long prec)` create a `t_REAL` equal to 1 to `prec` words of accuracy.

`GEN real_1_bit(long bitprec)` create a `t_REAL` equal to 1 to `bitprec` bits of accuracy.

`GEN real_m1(long prec)` create a `t_REAL` equal to -1 to `prec` words of accuracy.

`GEN real_0_bit(long bit)` create a `t_REAL` equal to 0 with exponent `bit`.

`GEN real_0(long prec)` is a shorthand for `real_0_bit(-prec)`.

`GEN int2n(long n)` creates a `t_INT` equal to $1 \ll n$ (i.e 2^n if $n \geq 0$, and 0 otherwise).

`GEN int2u(ulong n)` creates a `t_INT` equal to 2^n .

`GEN int2um1(long n)` creates a `t_INT` equal to $2^n - 1$.

`GEN real2n(long n, long prec)` create a `t_REAL` equal to 2^n to `prec` words of accuracy.

`GEN real_m2n(long n, long prec)` create a `t_REAL` equal to -2^n to `prec` words of accuracy.

`GEN strtol(char *s)` convert the character string `s` to a nonnegative `t_INT`. Decimal numbers, hexadecimal numbers prefixed by `0x` and binary numbers prefixed by `0b` are allowed. The string `s` consists exclusively of digits: no leading sign, no whitespace. Leading zeroes are discarded.

`GEN strtod(char *s, long prec)` convert the character string `s` to a nonnegative `t_REAL` of precision `prec`. The string `s` consists exclusively of digits and optional decimal point and exponent (`e` or `E`): no leading sign, no whitespace. Leading zeroes are discarded.

6.2.2 Assignment. In this section, the z argument in the z -functions must be of type t_INT or t_REAL .

`void mpaff(GEN x, GEN z)` assigns x into z (where x and z are t_INT or t_REAL). Assumes that $lg(z) > 2$.

`void affii(GEN x, GEN z)` assigns the t_INT x into the t_INT z .

`void affir(GEN x, GEN z)` assigns the t_INT x into the t_REAL z . Assumes that $lg(z) > 2$.

`void affiz(GEN x, GEN z)` assigns t_INT x into t_INT or t_REAL z . Assumes that $lg(z) > 2$.

`void affsi(long s, GEN z)` assigns the `long` s into the t_INT z . Assumes that $lg(z) > 2$.

`void affsr(long s, GEN z)` assigns the `long` s into the t_REAL z . Assumes that $lg(z) > 2$.

`void affsz(long s, GEN z)` assigns the `long` s into the t_INT or t_REAL z . Assumes that $lg(z) > 2$.

`void affui(ulong u, GEN z)` assigns the `ulong` u into the t_INT z . Assumes that $lg(z) > 2$.

`void affur(ulong u, GEN z)` assigns the `ulong` u into the t_REAL z . Assumes that $lg(z) > 2$.

`void affrr(GEN x, GEN z)` assigns the t_REAL x into the t_REAL z .

`void affgr(GEN x, GEN z)` assigns the scalar x into the t_REAL z , if possible.

The function `affrs` and `affri` do not exist. So don't use them.

`void affrr_fixlg(GEN y, GEN z)` a variant of `affrr`. First shorten z so that it is no longer than y , then assigns y to z . This is used in the following scenario: room is reserved for the result but, due to cancellation, fewer words of accuracy are available than had been anticipated; instead of appending meaningless 0s to the mantissa, we store what was actually computed.

Note that shortening z is not quite straightforward, since `setlg(z, ly)` would leave garbage on the stack, which `gerepile` might later inspect. It is done using

`void fixlg(GEN z, long ly)` see `stackdummy` and the examples that follow.

6.2.3 Copy.

`GEN icopy(GEN x)` copy relevant words of the t_INT x on the stack: the length and effective length of the copy are equal.

`GEN rcopy(GEN x)` copy the t_REAL x on the stack.

`GEN leafcopy(GEN x)` copy the leaf x on the stack (works in particular for t_INT s and t_REAL s). Contrary to `icopy`, `leafcopy` preserves the original length of a t_INT . The obsolete form `GEN mpcopy(GEN x)` is still provided for backward compatibility.

This function also works on recursive types, copying them as if they were leaves, i.e. making a shallow copy in that case: the components of the copy point to the same data as the component of the source; see also `shallowcopy`.

`GEN leafcopy_avma(GEN x, pari_sp av)` analogous to `gcopy_avma` but simpler: assume x is a leaf and return a copy allocated as if initially we had `avma` equal to `av`. There is no need to pass a pointer and update the value of the second argument: the new (fictitious) `avma` is just the return value (typecast to `pari_sp`).

`GEN icopyspec(GEN x, long nx)` copy the `nx` words $x[2], \dots, x[nx+1]$ to make up a new t_INT . Set the sign to 1.

6.2.4 Conversions.

`GEN itor(GEN x, long prec)` converts the `t_INT` `x` to a `t_REAL` of length `prec` and return the latter. Assumes that `prec > 2`.

`long itos(GEN x)` converts the `t_INT` `x` to a `long` if possible, otherwise raise an exception. We consider the conversion to be possible if and only if $|x| \leq \text{LONG_MAX}$, i.e. $|x| < 2^{63}$ on a 64-bit architecture. Since the range is symmetric, the output of `itos` can safely be negated.

`long itos_or_0(GEN x)` converts the `t_INT` `x` to a `long` if possible, otherwise return 0.

`int is_bigint(GEN n)` true if `itos(n)` would give an error.

`ulong itou(GEN x)` converts the `t_INT` $|x|$ to an `ulong` if possible, otherwise raise an exception. The conversion is possible if and only if $\text{lgfint}(x) \leq 3$.

`long itou_or_0(GEN x)` converts the `t_INT` $|x|$ to an `ulong` if possible, otherwise return 0.

`GEN stoi(long s)` creates the `t_INT` corresponding to the `long s`.

`GEN stor(long s, long prec)` converts the `long s` into a `t_REAL` of length `prec` and return the latter. Assumes that `prec > 2`.

`GEN utoi(ulong s)` converts the `ulong s` into a `t_INT` and return the latter.

`GEN utoipos(ulong s)` converts the *nonzero* `ulong s` into a `t_INT` and return the latter.

`GEN utoineg(ulong s)` converts the *nonzero* `ulong s` into the `t_INT` $-s$ and return the latter.

`GEN utor(ulong s, long prec)` converts the `ulong s` into a `t_REAL` of length `prec` and return the latter. Assumes that `prec > 2`.

`GEN rtor(GEN x, long prec)` converts the `t_REAL` `x` to a `t_REAL` of length `prec` and return the latter. If `prec < lg(x)`, round properly. If `prec > lg(x)`, pad with zeroes. Assumes that `prec > 2`.

The following function is also available as a special case of `mkintn`:

`GEN uu32toi(ulong a, ulong b)` returns the `GEN` equal to $2^{32}a + b$, *assuming* that $a, b < 2^{32}$. This does not depend on `sizeof(long)`: the behavior is as above on both 32 and 64-bit machines.

`GEN uu32toineg(ulong a, ulong b)` returns the `GEN` equal to $-(2^{32}a + b)$, *assuming* that $a, b < 2^{32}$ and that one of a or b is positive. This does not depend on `sizeof(long)`: the behavior is as above on both 32 and 64-bit machines.

`GEN uutoi(ulong a, ulong b)` returns the `GEN` equal to $2^{\text{BITS_IN_LONG}}a + b$.

`GEN uutoineg(ulong a, ulong b)` returns the `GEN` equal to $-(2^{\text{BITS_IN_LONG}}a + b)$.

6.2.5 Integer parts. The following four functions implement the conversion from `t_REAL` to `t_INT` using standard rounding modes. Contrary to usual semantics (complement the mantissa with an infinite number of 0), they will raise an error *precision loss in truncation* if the `t_REAL` represents a range containing more than one integer.

`GEN ceilr(GEN x)` smallest integer larger or equal to the `t_REAL` x (i.e. the `ceil` function).

`GEN floorr(GEN x)` largest integer smaller or equal to the `t_REAL` x (i.e. the `floor` function).

`GEN roundr(GEN x)` rounds the `t_REAL` x to the nearest integer (towards $+\infty$ in case of tie).

`GEN truncr(GEN x)` truncates the `t_REAL` x (not the same as `floorr` if x is negative).

The following four function are analogous, but can also treat the trivial case when the argument is a `t_INT`:

`GEN mpceil(GEN x)` as `ceilr` except that x may be a `t_INT`.

`GEN mpfloor(GEN x)` as `floorr` except that x may be a `t_INT`.

`GEN mpround(GEN x)` as `roundr` except that x may be a `t_INT`.

`GEN mptrunc(GEN x)` as `truncr` except that x may be a `t_INT`.

`GEN diviiround(GEN x, GEN y)` if x and y are `t_INT`s, returns the quotient x/y of x and y , rounded to the nearest integer. If x/y falls exactly halfway between two consecutive integers, then it is rounded towards $+\infty$ (as for `roundr`).

`GEN ceil_safe(GEN x)`, x being a real number (not necessarily a `t_REAL`) returns the smallest integer which is larger than any possible incarnation of x . (Recall that a `t_REAL` represents an interval of possible values.) Note that `gceil` raises an exception if the input accuracy is too low compared to its magnitude.

`GEN floor_safe(GEN x)`, x being a real number (not necessarily a `t_REAL`) returns the largest integer which is smaller than any possible incarnation of x . (Recall that a `t_REAL` represents an interval of possible values.) Note that `gfloor` raises an exception if the input accuracy is too low compared to its magnitude.

`GEN trunc_safe(GEN x)`, x being a real number (not necessarily a `t_REAL`) returns the integer with the largest absolute value, which is closer to 0 than any possible incarnation of x . (Recall that a `t_REAL` represents an interval of possible values.)

`GEN roundr_safe(GEN x)` rounds the `t_REAL` x to the nearest integer (towards $+\infty$). Complement the mantissa with an infinite number of 0 before rounding, hence never raise an exception.

6.2.6 2-adic valuations and shifts.

`long vals(long s)` 2-adic valuation of the `long` s . Returns -1 if s is equal to 0.

`long vali(GEN x)` 2-adic valuation of the `t_INT` x . Returns -1 if x is equal to 0.

`GEN mpshift(GEN x, long n)` shifts the `t_INT` or `t_REAL` x by n . If n is positive, this is a left shift, i.e. multiplication by 2^n . If n is negative, it is a right shift by $-n$, which amounts to the truncation of the quotient of x by 2^{-n} .

`GEN shifti(GEN x, long n)` shifts the `t_INT` x by n .

`GEN shiftr(GEN x, long n)` shifts the `t_REAL` x by n .

`void shiftr_inplace(GEN x, long n)` shifts the `t_REAL` x by n , in place.

`GEN trunc2nr(GEN x, long n)` given a `t_REAL` x , returns `truncr(shiftr(x,n))`, but faster, without leaving garbage on the stack and never raising a *precision loss in truncation* error. Called by `gtrunc2n`.

`GEN mantissa2nr(GEN x, long n)` given a `t_REAL` x , returns the mantissa of $x2^n$ (disregards the exponent of x). Equivalent to

`trunc2nr(x, n-expo(x)+bit_prec(x)-1)`

`GEN mantissa_real(GEN z, long *e)` returns the mantissa m of z , and sets `*e` to the exponent `bit_accuracy(lg(z)) - 1 - expo(z)`, so that $z = m/2^e$.

Low-level. In the following two functions, s (ource) and t (arget) need not be valid GENs (in practice, they usually point to some part of a `t_REAL` mantissa): they are considered as arrays of words representing some mantissa, and we shift globally s by $n > 0$ bits, storing the result in t . We assume that $m \leq M$ and only access $s[m], s[m+1], \dots s[M]$ (read) and likewise for t (write); we may have $s = t$ but more general overlaps are not allowed. The word f is concatenated to s to supply extra bits.

`void shift_left(GEN t, GEN s, long m, long M, ulong f, ulong n)` shifts the mantissa

$s[m], s[m+1], \dots s[M], f$

left by n bits.

`void shift_right(GEN t, GEN s, long m, long M, ulong f, ulong n)` shifts the mantissa

$f, s[m], s[m+1], \dots s[M]$

right by n bits.

6.2.7 From `t_INT` to bits or digits in base 2^k and back.

`GEN binary_zv(GEN x)` given a `t_INT` x , return a `t_VECSMALL` of bits, from most significant to least significant.

`GEN binary_2k(GEN x, long k)` given a `t_INT` x , and $k > 0$, return a `t_VEC` of digits of x in base 2^k , as `t_INT`s, from most significant to least significant.

`GEN binary_2k_nv(GEN x, long k)` given a `t_INT` x , and $0 < k < \text{BITS_IN_LONG}$, return a `t_VECSMALL` of digits of x in base 2^k , as `ulong`s, from most significant to least significant.

`GEN bits_to_int(GEN x, long l)` given a vector x of l bits (as a `t_VECSMALL` or even a pointer to a part of a larger vector, so not a proper GEN), return the integer $\sum_{i=1}^l x[i]2^{l-i}$, as a `t_INT`.

`ulong bits_to_u(GEN v, long l)` same as `bits_to_int`, where $l < \text{BITS_IN_LONG}$, so we can return an `ulong`.

`GEN fromdigitsu(GEN x, GEN B)` given a `t_VECSMALL` x of length l and a `t_INT` B , return the integer $\sum_{i=1}^l x[i]B^{i-1}$, as a `t_INT`, where the $x[i]$ are seen as unsigned integers.

`GEN fromdigits_2k(GEN x, long k)` converse of `binary_2k`; given a `t_VEC` x of length l and a positive `long` k , where each $x[i]$ is a `t_INT` with $0 \leq x[i] < 2^k$, return the integer $\sum_{i=1}^l x[i]2^{k(l-i)}$, as a `t_INT`.

`GEN nv_fromdigits_2k(GEN x, long k)` as `fromdigits_2k`, but with x being a `t_VECSMALL` and each $x[i]$ being a `ulong` with $0 \leq x[i] < 2^{\min\{k, \text{BITS_IN_LONG}\}}$. Here k may be any positive `long`, and the $x[i]$ are regarded as k -bit integers by truncating or extending with zeroes.

6.2.8 Integer valuation. For integers x and p , such that $x \neq 0$ and $|p| > 1$, we define $v_p(x)$ to be the largest integer exponent e such that p^e divides x . If p is prime, this is the ordinary valuation of x at p .

`long Z_pvalrem(GEN x, GEN p, GEN *r)` applied to `t_INTs` $x \neq 0$ and p , $|p| > 1$, returns $e := v_p(x)$. The quotient x/p^e is returned in $*r$. If $|p|$ is a prime, $*r$ is the prime-to- p part of x .

`long Z_pval(GEN x, GEN p)` as `Z_pvalrem` but only returns $v_p(x)$.

`long Z_lvalrem(GEN x, ulong p, GEN *r)` as `Z_pvalrem`, except that p is an `ulong` ($p > 1$).

`long Z_lvalrem_stop(GEN *x, ulong p, int *stop)` assume $x > 0$; returns $e := v_p(x)$ and replaces x by x/p^e . Set `stop` to 1 if the new value of x is $< p^2$ (and 0 otherwise). To be used when trial dividing x by successive primes: the `stop` condition is cheaply tested while testing whether p divides x (is the quotient less than p ?), and allows to decide that n is prime if no prime $< p$ divides n . Not memory-clean.

`long Z_lval(GEN x, ulong p)` as `Z_pval`, except that p is an `ulong` ($p > 1$).

`long u_lvalrem(ulong x, ulong p, ulong *r)` as `Z_pvalrem`, except the inputs/outputs are now `ulongs`.

`long u_lvalrem_stop(ulong *n, ulong p, int *stop)` as `Z_pvalrem_stop`.

`long u_pvalrem(ulong x, GEN p, ulong *r)` as `Z_pvalrem`, except x and r are now `ulongs`.

`long u_lval(ulong x, ulong p)` as `Z_pval`, except the inputs are now `ulongs`.

`long u_pval(ulong x, GEN p)` as `Z_pval`, except x is now an `ulong`.

`long z_lval(long x, ulong p)` as `u_lval`, for signed x .

`long z_lvalrem(long x, ulong p)` as `u_lvalrem`, for signed x .

`long z_pval(long x, GEN p)` as `Z_pval`, except x is now a `long`.

`long z_pvalrem(long x, GEN p)` as `Z_pvalrem`, except x is now a `long`.

`long factorial_lval(ulong n, ulong p)` returns $v_p(n!)$, assuming p is prime.

The following convenience functions generalize `Z_pval` and its variants to “containers” (`ZV` and `ZX`):

`long ZV_pvalrem(GEN x, GEN p, GEN *r)` x being a `ZV` (a vector of `t_INTs`), return the min v of the valuations of its components and set $*r$ to x/p^v . Infinite loop if x is the zero vector. This function is not stack clean.

`long ZV_pval(GEN x, GEN p)` as `ZV_pvalrem` but only returns the “valuation”.

`int ZV_Z_dvd(GEN x, GEN p)` returns 1 if p divides all components of x and 0 otherwise. Faster than testing `ZV_pval(x,p) >= 1`.

`long ZV_lvalrem(GEN x, ulong p, GEN *px)` as `ZV_pvalrem`, except that p is an `ulong` ($p > 1$). This function is not stack-clean.

`long ZV_lval(GEN x, ulong p)` as `ZV_pval`, except that p is an `ulong` ($p > 1$).

`long ZX_pvalrem(GEN x, GEN p, GEN *r)` as `ZV_pvalrem`, for a `ZX` x (a `t_POL` with `t_INT` coefficients). This function is not stack-clean.

`long ZX_pval(GEN x, GEN p)` as `ZV_pval` for a `ZX` x .

`long ZX_lvalrem(GEN x, ulong p, GEN *px)` as `ZV_lvalrem`, a `ZX` x . This function is not stack-clean.

`long ZXX_pvalrem(GEN x, GEN p, GEN *r)` as `ZX_pvalrem`, for a `ZXX` x (a `t_POL` with `ZX` coefficients). This function is not stack-clean.

`long ZXV_pvalrem(GEN x, GEN p, GEN *r)` as `ZV_pvalrem`, for a `ZXV` x (a `t_VEC` with `ZX` coefficients). This function is not stack-clean.

`long ZX_lval(GEN x, ulong p)` as `ZX_pval`, except that p is an `ulong` ($p > 1$).

6.2.9 Generic unary operators. Let “*op*” be a unary operation among

- **neg**: negation ($-x$).
- **abs**: absolute value ($|x|$).
- **sqr**: square (x^2).

The names and prototypes of the low-level functions corresponding to *op* are as follows. The result is of the same type as x .

`GEN opi(GEN x)` creates the result of *op* applied to the `t_INT` x .

`GEN opr(GEN x)` creates the result of *op* applied to the `t_REAL` x .

`GEN mpop(GEN x)` creates the result of *op* applied to the `t_INT` or `t_REAL` x .

Complete list of available functions:

`GEN absi(GEN x), GEN absr(GEN x), GEN mpabs(GEN x)`

`GEN negi(GEN x), GEN negr(GEN x), GEN mpneg(GEN x)`

`GEN sqri(GEN x), GEN sqrr(GEN x), GEN mpsqr(GEN x)`

`GEN absi_shallow(GEN x)` x being a `t_INT`, returns a shallow copy of $|x|$, in particular returns x itself when $x \geq 0$, and `negi(x)` otherwise.

`GEN mpabs_shallow(GEN x)` x being a `t_INT` or a `t_REAL`, returns a shallow copy of $|x|$, in particular returns x itself when $x \geq 0$, and `mpneg(x)` otherwise.

Some miscellaneous routines:

`GEN sqrs(long x)` returns x^2 .

`GEN sqru(ulong x)` returns x^2 .

6.2.10 Comparison operators.

`int cmpss(long s, long t)` compares the `long s` to the `t_long t`.

`int cmpuu(ulong u, ulong v)` compares the `ulong u` to the `t_ulong v`.

`long minss(long x, long y)`

`ulong minuu(ulong x, ulong y)`

`double mindd(double x, double y)` returns the min of x and y .

`long maxss(long x, long y)`

`ulong maxuu(ulong x, ulong y)`

`double maxdd(double x, double y)` returns the max of x and y .

`int mpcmp(GEN x, GEN y)` compares the `t_INT` or `t_REAL x` to the `t_INT` or `t_REAL y`. The result is the sign of $x - y$.

`int cmpii(GEN x, GEN y)` compares the `t_INT x` to the `t_INT y`.

`int cmpir(GEN x, GEN y)` compares the `t_INT x` to the `t_REAL y`.

`int cmpis(GEN x, long s)` compares the `t_INT x` to the `long s`.

`int cmpiu(GEN x, ulong s)` compares the `t_INT x` to the `ulong s`.

`int cmpsi(long s, GEN x)` compares the `long s` to the `t_INT x`.

`int cmpui(ulong s, GEN x)` compares the `ulong s` to the `t_INT x`.

`int cmpsr(long s, GEN x)` compares the `long s` to the `t_REAL x`.

`int cmpri(GEN x, GEN y)` compares the `t_REAL x` to the `t_INT y`.

`int cmprrr(GEN x, GEN y)` compares the `t_REAL x` to the `t_REAL y`.

`int cmprs(GEN x, long s)` compares the `t_REAL x` to the `long s`.

`int equalii(GEN x, GEN y)` compares the `t_INTs x` and `y`. The result is 1 if $x = y$, 0 otherwise.

`int equalrr(GEN x, GEN y)` compares the `t_REALs x` and `y`. The result is 1 if $x = y$, 0 otherwise. Equality is decided according to the following rules: all real zeroes are equal, and different from a nonzero real; two nonzero reals are equal if all their digits coincide up to the length of the shortest of the two, and the remaining words in the mantissa of the longest are all 0.

`int equalis(GEN x, long s)` compare the `t_INT x` and the `long s`. The result is 1 if $x = y$, 0 otherwise.

`int equalsi(long s, GEN x)`

`int equaliu(GEN x, ulong s)` compare the `t_INT x` and the `ulong s`. The result is 1 if $x = y$, 0 otherwise.

`int equalui(ulong s, GEN x)`

The remaining comparison operators disregard the sign of their operands

`int absequaliu(GEN x, ulong u)` compare the absolute value of the `t_INT x` and the `ulong s`. The result is 1 if $|x| = y$, 0 otherwise. This is marginally more efficient than `equalis` even when x is known to be nonnegative.

`int absequalui(ulong u, GEN x)`

`int absncmpiu(GEN x, ulong u)` compare the absolute value of the `t_INT` `x` and the `ulong` `u`.

`int absncmpui(ulong u, GEN x)`

`int absncmpii(GEN x, GEN y)` compares the `t_INT`s `x` and `y`. The result is the sign of $|x| - |y|$.

`int absequalii(GEN x, GEN y)` compares the `t_INT`s `x` and `y`. The result is 1 if $|x| = |y|$, 0 otherwise.

`int absncmprr(GEN x, GEN y)` compares the `t_REAL`s `x` and `y`. The result is the sign of $|x| - |y|$.

`int absrnz_equal2n(GEN x)` tests whether a nonzero `t_REAL` `x` is equal to $\pm 2^e$ for some integer `e`.

`int absrnz_equal1(GEN x)` tests whether a nonzero `t_REAL` `x` is equal to ± 1 .

6.2.11 Generic binary operators. The operators in this section have arguments of C-type `GEN`, `long`, and `ulong`, and only `t_INT` and `t_REAL` `GEN`s are allowed. We say an argument is a real type if it is a `t_REAL` `GEN`, and an integer type otherwise. The result is always a `t_REAL` unless both `x` and `y` are integer types.

Let “*op*” be a binary operation among

- **add**: addition (`x + y`).

- **sub**: subtraction (`x - y`).

- **mul**: multiplication (`x * y`).

- **div**: division (`x / y`). In the case where `x` and `y` are both integer types, the result is the Euclidean quotient, where the remainder has the same sign as the dividend `x`. It is the ordinary division otherwise. A division-by-0 error occurs if `y` is equal to 0.

The last two generic operations are defined only when arguments have integer types; and the result is a `t_INT`:

- **rem**: remainder (“`x % y`”). The result is the Euclidean remainder corresponding to **div**, i.e. its sign is that of the dividend `x`.

- **mod**: true remainder (`x % y`). The result is the true Euclidean remainder, i.e. nonnegative and less than the absolute value of `y`.

Important technical note. The rules given above fixing the output type (to `t_REAL` unless both inputs are integer types) are subtly incompatible with the general rules obeyed by PARI's generic functions, such as `gmul` or `gdiv` for instance: the latter return a result containing as much information as could be deduced from the inputs, so it is not true that if x is a `t_INT` and y a `t_REAL`, then `gmul(x,y)` is always the same as `mulir(x,y)`. The exception is $x = 0$, in that case we can deduce that the result is an exact 0, so `gmul` returns `gen_0`, while `mulir` returns a `t_REAL` 0. Specifically, the one resulting from the conversion of `gen_0` to a `t_REAL` of precision `precision(y)`, multiplied by y ; this determines the exponent of the real 0 we obtain.

The reason for the discrepancy between the two rules is that we use the two sets of functions in different contexts: generic functions allow to write high-level code forgetting about types, letting PARI return results which are sensible and as simple as possible; type specific functions are used in kernel programming, where we do care about types and need to maintain strict consistency: it is much easier to compute the types of results when they are determined from the types of the inputs only (without taking into account further arithmetic properties, like being nonzero).

The names and prototypes of the low-level functions corresponding to *op* are as follows. In this section, the *z* argument in the *z*-functions must be of type `t_INT` when no *r* or *mp* appears in the argument code (no `t_REAL` operand is involved, only integer types), and of type `t_REAL` otherwise.

`GEN mpop[z](GEN x, GEN y[, GEN z])` applies *op* to the `t_INT` or `t_REAL` x and y . The function `mpdivz` does not exist (its semantic would change drastically depending on the type of the *z* argument), and neither do `mprem[z]` nor `mpmod[z]` (specific to integers).

`GEN opsi[z](long s, GEN x[, GEN z])` applies *op* to the `long` s and the `t_INT` x . These functions always return the global constant `gen_0` (not a copy) when the sign of the result is 0.

`GEN opsr[z](long s, GEN x[, GEN z])` applies *op* to the `long` s and the `t_REAL` x .

`GEN opss[z](long s, long t[, GEN z])` applies *op* to the `long`s s and t . These functions always return the global constant `gen_0` (not a copy) when the sign of the result is 0.

`GEN opii[z](GEN x, GEN y[, GEN z])` applies *op* to the `t_INT`s x and y . These functions always return the global constant `gen_0` (not a copy) when the sign of the result is 0.

`GEN opir[z](GEN x, GEN y[, GEN z])` applies *op* to the `t_INT` x and the `t_REAL` y .

`GEN opis[z](GEN x, long s[, GEN z])` applies *op* to the `t_INT` x and the `long` s . These functions always return the global constant `gen_0` (not a copy) when the sign of the result is 0.

`GEN opri[z](GEN x, GEN y[, GEN z])` applies *op* to the `t_REAL` x and the `t_INT` y .

`GEN oprr[z](GEN x, GEN y[, GEN z])` applies *op* to the `t_REAL`s x and y .

`GEN oprs[z](GEN x, long s[, GEN z])` applies *op* to the `t_REAL` x and the `long` s .

Some miscellaneous routines:

`long expu(ulong x)` assuming $x > 0$, returns the binary exponent of the real number equal to x . This is a special case of `gexpo`.

`GEN adduu(ulong x, ulong y)`

`GEN addiu(GEN x, ulong y)`

`GEN addui(ulong x, GEN y)` adds x and y .

`GEN subuu(ulong x, ulong y)`

`GEN subiu(GEN x, ulong y)`
`GEN subui(ulong x, GEN y)` subtracts x by y .
`GEN muluu(ulong x, ulong y)` multiplies x by y .
`ulong umuluu_le(ulong x, ulong y, ulong n)` multiplies x by y . Return xy if $xy \leq n$ and 0 otherwise (in particular if xy does not fit in an `ulong`).
`ulong umuluu_or_0(ulong x, ulong y)` multiplies x by y . Return 0 if xy does not fit in an `ulong`.
`GEN mului(ulong x, GEN y)` multiplies x by y .
`GEN muluui(ulong x, ulong y, GEN z)` return xyz .
`GEN muliu(GEN x, ulong y)` multiplies x by y .
`void addumului(ulong a, ulong b, GEN x)` return $a + b|X|$.
`GEN addmuliu(GEN x, GEN y, ulong u)` returns $x + yu$.
`GEN addmulii(GEN x, GEN y, GEN z)` returns $x + yz$.
`GEN addmulii_inplace(GEN x, GEN y, GEN z)` returns $x + yz$, but returns x itself and not a copy if $yz = 0$. Not suitable for `gerepile` or `gerepileupto`.
`GEN addmuliu_inplace(GEN x, GEN y, ulong u)` returns $x + yu$, but returns x itself and not a copy if $yu = 0$. Not suitable for `gerepile` or `gerepileupto`.
`GEN submuliu_inplace(GEN x, GEN y, ulong u)` returns $x - yu$, but returns x itself and not a copy if $yu = 0$. Not suitable for `gerepile` or `gerepileupto`.
`GEN lincombii(GEN u, GEN v, GEN x, GEN y)` returns $ux + vy$.
`GEN mulsubii(GEN y, GEN z, GEN x)` returns $yz - x$.
`GEN submulii(GEN x, GEN y, GEN z)` returns $x - yz$.
`GEN submuliu(GEN x, GEN y, ulong u)` returns $x - yu$.
`GEN mulu_interval(ulong a, ulong b)` returns $a(a+1) \cdots b$, assuming that $a \leq b$.
`GEN mulu_interval_step(ulong a, ulong b, ulong s)` returns the product of all integers in $[a, b]$ congruent to a modulo s . Assume $a \leq b$ and $s > 0$.
`GEN muls_interval(long a, long b)` returns $a(a+1) \cdots b$, assuming that $a \leq b$.
`GEN invr(GEN x)` returns the inverse of the nonzero `t_REAL` x .
`GEN truedivii(GEN x, GEN y)` returns the true Euclidean quotient (with nonnegative remainder less than $|y|$).
`GEN truedivis(GEN x, long y)` returns the true Euclidean quotient (with nonnegative remainder less than $|y|$).
`GEN truedivsi(long x, GEN y)` returns the true Euclidean quotient (with nonnegative remainder less than $|y|$).
`GEN centermodii(GEN x, GEN y, GEN y2)`, given `t_INTs` x, y , returns z congruent to x modulo y , such that $-y/2 \leq z < y/2$. The function requires an extra argument $y2$, such that $y2 = \text{shifti}(y, -1)$. (In most cases, y is constant for many reductions and $y2$ need only be computed once.)

GEN remi2n(GEN x, long n) returns $x \bmod 2^n$.

GEN addii_sign(GEN x, long sx, GEN y, long sy) add the t_INT s x and y as if their signs were sx and sy .

GEN addir_sign(GEN x, long sx, GEN y, long sy) add the t_INT x and the t_REAL y as if their signs were sx and sy .

GEN addrr_sign(GEN x, long sx, GEN y, long sy) add the t_REAL s x and y as if their signs were sx and sy .

GEN addsi_sign(long x, GEN y, long sy) add x and the t_INT y as if its sign was sy .

GEN addui_sign(ulong x, GEN y, long sy) add x and the t_INT y as if its sign was sy .

6.2.12 Exact division and divisibility.

GEN diviixact(GEN x, GEN y) returns the Euclidean quotient x/y , assuming y divides x . Uses Jebelean algorithm (Jebelean-Krandick bidirectional exact division is not implemented).

GEN diviuexact(GEN x, ulong y) returns the Euclidean quotient x/y , assuming y divides x and y is nonzero.

GEN diviuuexact(GEN x, ulong y, ulong z) returns the Euclidean quotient $x/(yz)$, assuming yz divides x and $yz \neq 0$.

The following routines return 1 (true) if y divides x , and 0 otherwise. All GEN are assumed to be t_INT s:

int dvdi(GEN x, GEN y), int dvdis(GEN x, long y), int dvdiu(GEN x, ulong y),

int dvdsi(long x, GEN y), int dvdui(ulong x, GEN y).

The following routines return 1 (true) if y divides x , and in that case assign the quotient to z ; otherwise they return 0. All GEN are assumed to be t_INT s:

int dvdiiz(GEN x, GEN y, GEN z), int dvdisz(GEN x, long y, GEN z).

int dvdiuz(GEN x, ulong y, GEN z) if y divides x , assigns the quotient $|x|/y$ to z and returns 1 (true), otherwise returns 0 (false).

6.2.13 Division with integral operands and t_REAL result.

GEN rdivii(GEN x, GEN y, long prec), assuming x and y are both of type t_INT , return the quotient x/y as a t_REAL of precision $prec$.

GEN rdiviiz(GEN x, GEN y, GEN z), assuming x and y are both of type t_INT , and z is a t_REAL , assign the quotient x/y to z .

GEN rdivis(GEN x, long y, long prec), assuming x is of type t_INT , return the quotient x/y as a t_REAL of precision $prec$.

GEN rdivsi(long x, GEN y, long prec), assuming y is of type t_INT , return the quotient x/y as a t_REAL of precision $prec$.

GEN rdivss(long x, long y, long prec), return the quotient x/y as a t_REAL of precision $prec$.

6.2.14 Division with remainder. The following functions return two objects, unless specifically asked for only one of them — a quotient and a remainder. The quotient is returned and the remainder is returned through the variable whose address is passed as the `r` argument. The term *true Euclidean remainder* refers to the nonnegative one (`mod`), and *Euclidean remainder* by itself to the one with the same sign as the dividend (`rem`). All GENs, whether returned directly or through a pointer, are created on the stack.

`GEN dvmdii(GEN x, GEN y, GEN *r)` returns the Euclidean quotient of the `t_INT` `x` by a `t_INT` `y` and puts the remainder into `*r`. If `r` is equal to `NULL`, the remainder is not created, and if `r` is equal to `ONLY_REM`, only the remainder is created and returned. In the generic case, the remainder is created after the quotient and can be disposed of individually with a `cgiv(r)`. The remainder is always of the sign of the dividend `x`. If the remainder is 0 set `r = gen_0`.

`void dvmdiiz(GEN x, GEN y, GEN z, GEN t)` assigns the Euclidean quotient of the `t_INT`s `x` and `y` into the `t_INT` `z`, and the Euclidean remainder into the `t_INT` `t`.

Analogous routines `dvmdis[z]`, `dvmdsi[z]`, `dvmdss[z]` are available, where `s` denotes a `long` argument. But the following routines are in general more flexible:

`long sdivss_rem(long s, long t, long *r)` computes the Euclidean quotient and remainder of the `long`s `s` and `t`. Puts the remainder into `*r`, and returns the quotient. The remainder is of the sign of the dividend `s`, and has strictly smaller absolute value than `t`.

`long sdivsi_rem(long s, GEN x, long *r)` computes the Euclidean quotient and remainder of the `long` `s` by the `t_INT` `x`. As `sdivss_rem` otherwise.

`long sdivsi(long s, GEN x)` as `sdivsi_rem`, without remainder.

`GEN divis_rem(GEN x, long s, long *r)` computes the Euclidean quotient and remainder of the `t_INT` `x` by the `long` `s`. As `sdivss_rem` otherwise.

`GEN absdiviu_rem(GEN x, ulong s, ulong *r)` computes the Euclidean quotient and remainder of *absolute value* of the `t_INT` `x` by the `ulong` `s`. As `sdivss_rem` otherwise.

`ulong uabsdiviu_rem(GEN n, ulong d, ulong *r)` as `absdiviu_rem`, assuming that $|n|/d$ fits into an `ulong`.

`ulong uabsdivui_rem(ulong x, GEN y, ulong *rem)` computes the Euclidean quotient and remainder of `x` by $|y|$. As `sdivss_rem` otherwise.

`ulong udivuu_rem(ulong x, ulong y, ulong *rem)` computes the Euclidean quotient and remainder of `x` by `y`. As `sdivss_rem` otherwise.

`ulong ceildivuu(ulong x, ulong y)` return the ceiling of x/y .

`GEN divsi_rem(long s, GEN y, long *r)` computes the Euclidean quotient and remainder of the `long` `s` by the `GEN` `y`. As `sdivss_rem` otherwise.

`GEN divss_rem(long x, long y, long *r)` computes the Euclidean quotient and remainder of the `long` `x` by the `long` `y`. As `sdivss_rem` otherwise.

`GEN truedvmdii(GEN x, GEN y, GEN *r)`, as `dvmdii` but with a nonnegative remainder.

`GEN truedvmdis(GEN x, long y, GEN *z)`, as `dvmdis` but with a nonnegative remainder.

`GEN truedvmdsi(long x, GEN y, GEN *z)`, as `dvmdsi` but with a nonnegative remainder.

6.2.15 Modulo to longs. The following variants of `modii` do not clutter the stack:

`long smodis(GEN x, long y)` computes the true Euclidean remainder of the `t_INT` `x` by the `long` `y`. This is the nonnegative remainder, not the one whose sign is the sign of `x` as in the `div` functions.

`long smodss(long x, long y)` computes the true Euclidean remainder of the `long` `x` by a `long` `y`.

`ulong umodsu(long x, ulong y)` computes the true Euclidean remainder of the `long` `x` by a `ulong` `y`.

`ulong umodiu(GEN x, ulong y)` computes the true Euclidean remainder of the `t_INT` `x` by the `ulong` `y`.

`ulong umodui(ulong x, GEN y)` computes the true Euclidean remainder of the `ulong` `x` by the `t_INT` `|y|`.

The routine `smodsi` does not exist, since it would not always be defined: for a *negative* `x`, if the quotient is ± 1 , the result `x + |y|` would in general not fit into a `long`. Use either `umodui` or `modsi`.

These functions directly access the binary data and are thus much faster than the generic modulo functions:

`int mpodd(GEN x)` which is 1 if `x` is odd, and 0 otherwise.

`ulong Mod2(GEN x)`

`ulong Mod4(GEN x)`

`ulong Mod8(GEN x)`

`ulong Mod16(GEN x)`

`ulong Mod32(GEN x)`

`ulong Mod64(GEN x)` give the residue class of `x` modulo the corresponding power of 2.

`ulong umodi2n(GEN x, long n)` give the residue class of `x` modulo 2^n , $0 \leq n < BITS_IN_LONG$.

The following functions assume that $x \neq 0$ and in fact disregard the sign of `x`. There are about 10% faster than the safer variants above:

`long mod2(GEN x)`

`long mod4(GEN x)`

`long mod8(GEN x)`

`long mod16(GEN x)`

`long mod32(GEN x)`

`long mod64(GEN x)` give the residue class of $|x|$ modulo the corresponding power of 2, for *nonzero* `x`. As well,

`ulong mod2BIL(GEN x)` returns the least significant word of $|x|$, still assuming that $x \neq 0$.

6.2.16 Powering, Square root.

GEN `powii`(GEN `x`, GEN `n`), assumes x and n are `t_INT`s and returns x^n .

GEN `powuu`(ulong `x`, ulong `n`), returns x^n .

GEN `powiu`(GEN `x`, ulong `n`), assumes x is a `t_INT` and returns x^n .

GEN `powis`(GEN `x`, long `n`), assumes x is a `t_INT` and returns x^n (possibly a `t_FRAC` if $n < 0$).

GEN `powrs`(GEN `x`, long `n`), assumes x is a `t_REAL` and returns x^n . This is considered as a sequence of `mulrr`, possibly empty: as such the result has type `t_REAL`, even if $n = 0$. Note that the generic function `gpowgs(x,0)` would return `gen_1`, see the technical note in Section 6.2.11.

GEN `powru`(GEN `x`, ulong `n`), assumes x is a `t_REAL` and returns x^n (always a `t_REAL`, even if $n = 0$).

GEN `powersr`(GEN `e`, long `n`). Given a `t_REAL` e , return the vector v of all e^i , $0 \leq i \leq n$, where $v[i] = e^{i-1}$.

GEN `powrshalf`(GEN `x`, long `n`), assumes x is a `t_REAL` and returns $x^{n/2}$ (always a `t_REAL`, even if $n = 0$).

GEN `powruhalf`(GEN `x`, ulong `n`), assumes x is a `t_REAL` and returns $x^{n/2}$ (always a `t_REAL`, even if $n = 0$).

GEN `powrfrac`(GEN `x`, long `n`, long `d`), assumes x is a `t_REAL` and returns $x^{n/d}$ (always a `t_REAL`, even if $n = 0$).

GEN `powIs`(long `n`) returns $I^n \in \{1, I, -1, -I\}$ (`t_INT` for even n , `t_COMPLEX` otherwise).

ulong `upowuu`(ulong `x`, ulong `n`), returns x^n when $< 2^{\text{BITS_IN_LONG}}$, and 0 otherwise (overflow).

ulong `upowers`(ulong `x`, long `n`), returns $[1, x, \dots, x^n]$ as a `t_VECSMALL`. Assume there is no overflow.

GEN `sqrtremi`(GEN `N`, GEN `*r`), returns the integer square root S of the nonnegative `t_INT` N (rounded towards 0) and puts the remainder R into `*r`. Precisely, $N = S^2 + R$ with $0 \leq R \leq 2S$. If `r` is equal to `NULL`, the remainder is not created. In the generic case, the remainder is created after the quotient and can be disposed of individually with `cgiv(R)`. If the remainder is 0 set `R = gen_0`.

Uses a divide and conquer algorithm (discrete variant of Newton iteration) due to Paul Zimmermann ("Karatsuba Square Root", INRIA Research Report 3805 (1999)).

GEN `sqrtdi`(GEN `N`), returns the integer square root S of the nonnegative `t_INT` N (rounded towards 0). This is identical to `sqrtremi(N, NULL)`.

long `logintall`(GEN `B`, GEN `y`, GEN `*ptq`) returns the floor e of $\log_y B$, where $B > 0$ and $y > 1$ are integers. If `ptq` is not `NULL`, set it to y^e . (Analogous to `logint0`, without sanity checks.)

ulong `ulogintall`(ulong `B`, ulong `y`, ulong `*ptq`) as `logintall` for ulong arguments.

long `logint`(GEN `B`, GEN `y`) returns the floor e of $\log_y B$, where $B > 0$ and $y > 1$ are integers.

ulong `ulogint`(ulong `B`, ulong `y`) as `logint` for ulong arguments.

GEN `vecpowuu`(long `N`, ulong `a`) return the vector of n^a , $n = 1, \dots, N$. Not memory clean.

GEN `vecpowug`(long `N`, GEN `a`, long `prec`) return the vector of n^a , $n = 1, \dots, N$, where the powers are computed at precision `prec`. Not memory clean.

6.2.17 GCD, extended GCD and LCM.

`long cgcd(long x, long y)` returns the GCD of `x` and `y`.

`ulong ugcd(ulong x, ulong y)` returns the GCD of `x` and `y`.

`ulong ugcdiu(GEN x, ulong y)` returns the GCD of `x` and `y`.

`ulong ugcdui(ulong x, GEN y)` returns the GCD of `x` and `y`.

`GEN coprimes_zv(ulong N)` return a `t_VECSMALL` T with N entries such that $T[i] = 1$ iff $(i, N) = 1$ and 0 otherwise.

`long clcm(long x, long y)` returns the LCM of `x` and `y`, provided it fits into a `long`. Silently overflows otherwise.

`ulong ulcm(ulong x, ulong y)` returns the LCM of `x` and `y`, provided it fits into an `ulong`. Silently overflows otherwise.

`GEN gcdii(GEN x, GEN y)`, returns the GCD of the `t_INTs` `x` and `y`.

`GEN lcmii(GEN x, GEN y)`, returns the LCM of the `t_INTs` `x` and `y`.

`GEN bezout(GEN a, GEN b, GEN *u, GEN *v)`, returns the GCD d of `t_INTs` `a` and `b` and sets `u`, `v` to the Bezout coefficients such that $au + bv = d$.

`long cbezout(long a, long b, long *u, long *v)`, returns the GCD d of `a` and `b` and sets `u`, `v` to the Bezout coefficients such that $au + bv = d$.

`GEN halfgcdii(GEN x, GEN y)` assuming `x` and `y` are `t_INTs`, returns a 2-components `t_VEC` $[M, V]$ where M is a 2×2 `t_MAT` and V a 2-component `t_COL`, both with `t_INT` entries, such that $M * [x, y] == V$ and such that if $V = [a, b]$, then $a \geq \left\lceil \sqrt{\max(|x|, |y|)} \right\rceil > b$.

`GEN ZV_extgcd(GEN A)` given a vector of n integers A , returns $[d, U]$, where d is the GCD of the $A[i]$ and U is a matrix in $GL_n(\mathbf{Z})$ such that $AU = [0, \dots, 0, D]$.

`GEN ZV_lcm(GEN v)` given a vector v of integers returns the LCM of its entries.

`GEN ZV_snf_gcd(GEN v, GEN N)` given a vector v of integers and a positive integer N , return the vector whose entries are the gcds $(v[i], N)$. Use case: if v gives the cyclic components for some Abelian group G of finite type, then this returns the structure of the finite groupe G/G^N .

6.2.18 Continued fractions and convergents.

`GEN ZV_allpnqn(GEN x)` given $x = [a_0, \dots, a_n]$ a continued fraction from `gboundcf`, $n \geq 0$, return all convergents as $[P, Q]$, where $P = [p_0, \dots, p_n]$ and $Q = [q_0, \dots, q_n]$.

6.2.19 Pseudo-random integers. These routine return pseudo-random integers uniformly distributed in some interval. The all use the same underlying generator which can be seeded and restarted using `getrand` and `setrand`.

`void setrand(GEN seed)` reseeds the random number generator using the seed n . The seed is either a technical array output by `getrand` or a small positive integer, used to generate deterministically a suitable state array. For instance, running a randomized computation starting by `setrand(1)` twice will generate the exact same output.

`GEN getrand(void)` returns the current value of the seed used by the pseudo-random number generator `random`. Useful mainly for debugging purposes, to reproduce a specific chain of computations. The returned value is technical (reproduces an internal state array of type `t_VECSMALL`), and can only be used as an argument to `setrand`.

`ulong pari_rand(void)` returns a random $0 \leq x < 2^{\text{BITS_IN_LONG}}$.

`long random_bits(long k)` returns a random $0 \leq x < 2^k$. Assumes that $0 \leq k \leq \text{BITS_IN_LONG}$.

`ulong random_Fl(ulong p)` returns a pseudo-random integer in $0, 1, \dots, p-1$.

`GEN randomi(GEN n)` returns a random `t_INT` between 0 and $n-1$.

`GEN randomr(long prec)` returns a random `t_REAL` in $[0, 1[$, with precision `prec`.

6.2.20 Modular operations. In this subsection, all GENs are `t_INT`.

`GEN Fp_red(GEN a, GEN m)` returns a modulo m (smallest nonnegative residue). (This is identical to `modii`).

`GEN Fp_neg(GEN a, GEN m)` returns $-a$ modulo m (smallest nonnegative residue).

`GEN Fp_add(GEN a, GEN b, GEN m)` returns the sum of a and b modulo m (smallest nonnegative residue).

`GEN Fp_sub(GEN a, GEN b, GEN m)` returns the difference of a and b modulo m (smallest nonnegative residue).

`GEN Fp_center(GEN a, GEN p, GEN pov2)` assuming that `pov2` is `shifti(p, -1)` and that $-p/2 < a < p$, returns the representative of a in the symmetric residue system $] -p/2, p/2]$.

`GEN Fp_center_i(GEN a, GEN p, GEN pov2)` internal variant of `Fp_center`, not `gerepile`-safe: when a is already in the proper interval, it is returned as is, without a copy.

`GEN Fp_mul(GEN a, GEN b, GEN m)` returns the product of a by b modulo m (smallest nonnegative residue).

`GEN Fp_addmul(GEN x, GEN y, GEN z, GEN p)` returns $x + yz$.

`GEN Fp_mulu(GEN a, ulong b, GEN m)` returns the product of a by b modulo m (smallest nonnegative residue).

`GEN Fp_muls(GEN a, long b, GEN m)` returns the product of a by b modulo m (smallest nonnegative residue).

`GEN Fp_half(GEN x, GEN m)` returns z such that $2z = x$ modulo m assuming such z exists. Assume that $0 \leq x < m$. Not memory-clean, but suitable for `gerepileupto`.

`GEN Fp_double(GEN x, GEN m)` return $2x$ modulo m . Assume that $0 \leq x < m$. Not memory-clean, but suitable for `gerepileupto`.

GEN Fp_sqr(GEN a, GEN m) returns a^2 modulo m (smallest nonnegative residue).

ulong Fp_powu(GEN x, ulong n, GEN m) raises x to the n -th power modulo m (smallest nonnegative residue). Not memory-clean, but suitable for `gerepileupto`.

ulong Fp_pows(GEN x, long n, GEN m) raises x to the n -th power modulo m (smallest nonnegative residue). A negative n is allowed. Not memory-clean, but suitable for `gerepileupto`.

GEN Fp_pow(GEN x, GEN n, GEN m) returns x^n modulo m (smallest nonnegative residue).

GEN Fp_pow_init(GEN x, GEN n, long k, GEN p) Return a table R that can be used with `Fp_pow_table` to compute the powers of x up to n . The table is of size $2^k \log_2(n)$.

GEN Fp_pow_table(GEN R, GEN n, GEN p) return x^n , where R is given by `Fp_pow_init(x,m,k,p)` for some integer $m \geq n$.

GEN Fp_powers(GEN x, long n, GEN m) returns $[x^0, \dots, x^n]$ modulo m as a `t_VEC` (smallest nonnegative residue).

GEN Fp_inv(GEN a, GEN m) returns an inverse of a modulo m (smallest nonnegative residue). Raise an error if a is not invertible.

GEN Fp_invsafe(GEN a, GEN m) as `Fp_inv`, but return `NULL` if a is not invertible.

GEN Fp_invgen(GEN x, GEN m, GEN *pg) set `*pg` to $g = \gcd(x, m)$ and return u in $(\mathbf{Z}/m\mathbf{Z})^*$ such that $xu = g$ modulo m . We have $g = 1$ if and only if x is invertible, and in this case u is its inverse.

GEN FpV_prod(GEN x, GEN p) returns the product of the components of x .

GEN FpV_inv(GEN x, GEN m) x being a vector of `t_INTs`, return the vector of inverses of the $x[i]$ mod m . The routine uses Montgomery's trick, and involves a single inversion mod m , plus $3(N-1)$ multiplications for N entries. The routine is not stack-clean: $2N$ integers mod m are left on stack, besides the N in the result.

GEN Fp_div(GEN a, GEN b, GEN m) returns the quotient of a by b modulo m (smallest nonnegative residue). Raise an error if b is not invertible.

GEN Fp_divu(GEN a, ulong b, GEN m) returns the quotient of a by b modulo m (smallest nonnegative residue). Raise an error if b is not invertible.

int invmod(GEN a, GEN m, GEN *g), return 1 if a modulo m is invertible, else return 0 and set $g = \gcd(a, m)$.

In the following three functions the integer parameter `ord` can be given either as a positive `t_INT` N , or as its factorization matrix faN , or as a pair $[N, faN]$. The parameter may be omitted by setting it to `NULL` (the value is then $p-1$).

GEN Fp_log(GEN a, GEN g, GEN ord, GEN p) Let g such that $g^{ord} \equiv 1 \pmod{p}$. Return an integer e such that $a^e \equiv g \pmod{p}$. If e does not exist, the result is undefined.

GEN Fp_order(GEN a, GEN ord, GEN p) returns the order of the \mathbf{F}_p a . Assume that `ord` is a multiple of the order of a .

GEN Fp_factored_order(GEN a, GEN ord, GEN p) returns $[o, F]$, where o is the multiplicative order of the \mathbf{F}_p a in \mathbf{F}_p^* , and F is the factorization of o . Assume that `ord` is a multiple of the order of a .

int Fp_issquare(GEN x, GEN p) returns 1 if x is a square modulo p , and 0 otherwise.

`int Fp_ispower(GEN x, GEN n, GEN p)` returns 1 if x is an n -th power modulo p , and 0 otherwise.

`GEN Fp_sqrt(GEN x, GEN p)` returns a square root of x modulo p (the smallest nonnegative residue), where x, p are `t_INTs`, and p is assumed to be prime. Return `NULL` if x is not a quadratic residue modulo p .

`GEN Fp_2gener(GEN p)` return a generator of the 2-Sylow subgroup of \mathbf{F}_p^* . To use with `Fp_sqrt_i`.

`GEN Fp_2gener_i(GEN ns, GEN p)` as `Fp_2gener`, where ns is a non-square modulo p .

`GEN Fp_sqrt_i(GEN x, GEN s2, GEN p)` as `Fp_sqrt` where $s2$ is the element returned by `Fp_2gener`.

`GEN Fp_sqrtn(GEN a, GEN n, GEN p, GEN *zn)` returns `NULL` if a is not an n -th power residue mod p . Otherwise, returns an n -th root of a ; if zn is not `NULL` set it to a primitive m -th root of 1, $m = \gcd(p-1, n)$ allowing to compute all m solutions in \mathbf{F}_p of the equation $x^n = a$.

`GEN Zn_sqrt(GEN x, GEN n)` returns one of the square roots of x modulo n (possibly not prime), where x is a `t_INT` and n is either a `t_INT` or is given by its factorization matrix. Return `NULL` if no such square root exist.

`GEN Zn_quad_roots(GEN N, GEN B, GEN C)` solves the equation $X^2 + BX + C$ modulo N . Return `NULL` if there are no solutions. Else returns $[M, v]$ where $M \mid N$ and the `FpV` v of distinct integers (reduced, implicitly modulo M) is such that x modulo N is a solution to the equation if and only if x modulo M belongs to v . If the discriminant $B^2 - 4C$ is coprime to N , we have $M = N$ but in general M can be a strict divisor of N .

`long kross(long x, long y)` returns the Kronecker symbol $(x|y)$, i.e. $-1, 0$ or 1 . If y is an odd prime, this is the Legendre symbol. (Contrary to `krouu`, `kross` also supports $y = 0$)

`long krouu(ulong x, ulong y)` returns the Kronecker symbol $(x|y)$, i.e. $-1, 0$ or 1 . Assumes y is nonzero. If y is an odd prime, this is the Legendre symbol.

`long krois(GEN x, long y)` returns the Kronecker symbol $(x|y)$ of `t_INT` x and `long` y . As `kross` otherwise.

`long kroiu(GEN x, ulong y)` returns the Kronecker symbol $(x|y)$ of `t_INT` x and nonzero `ulong` y . As `krouu` otherwise.

`long krosi(long x, GEN y)` returns the Kronecker symbol $(x|y)$ of `long` x and `t_INT` y . As `kross` otherwise.

`long kroui(ulong x, GEN y)` returns the Kronecker symbol $(x|y)$ of `long` x and `t_INT` y . As `kross` otherwise.

`long kronecker(GEN x, GEN y)` returns the Kronecker symbol $(x|y)$ of `t_INTs` x and y . As `kross` otherwise.

`GEN factorial_Fp(long n, GEN p)` return $n! \bmod p$.

`GEN pgener_Fp(GEN p)` returns the smallest primitive root modulo p , assuming p is prime.

`GEN pgener_Zp(GEN p)` returns the smallest primitive root modulo p^k , $k > 1$, assuming p is an odd prime.

`long Zp_issquare(GEN x, GEN p)` returns 1 if the `t_INT` x is a p -adic square, 0 otherwise.

`long Zn_issquare(GEN x, GEN n)` returns 1 if `t_INT` x is a square modulo n (possibly not prime), where n is either a `t_INT` or is given by its factorization matrix. Return 0 otherwise.

`long Zn_ispower(GEN x, GEN n, GEN K, GEN *py)` returns 1 if x is a K -th power modulo n (possibly not prime), where n is either a `t_INT` or is given by its factorization matrix. Return 0 otherwise. If `py` is not NULL, set it to y such that $y^K = x$ modulo n .

`GEN pgener_Fp_local(GEN p, GEN L)`, L being a vector of primes dividing $p - 1$, returns the smallest integer $x > 1$ which is a generator of the ℓ -Sylow of \mathbf{F}_p^* for every ℓ in L . In other words, $x^{(p-1)/\ell} \neq 1$ for all such ℓ . In particular, returns `pgener_Fp(p)` if L contains all primes dividing $p - 1$. It is not necessary, and in fact slightly inefficient, to include $\ell = 2$, since 2 is treated separately in any case, i.e. the generator obtained is never a square.

`GEN rootsof1_Fp(GEN n, GEN p)` returns a primitive n -th root modulo the prime p .

`GEN rootsof1u_Fp(ulong n, GEN p)` returns a primitive n -th root modulo the prime p .

`ulong rootsof1_Fl(ulong n, ulong p)` returns a primitive n -th root modulo the prime p .

6.2.21 Extending functions to vector inputs.

The following functions apply f to the given arguments, recursively if they are of vector / matrix type:

`GEN map_proto_G(GEN (*f)(GEN), GEN x)` For instance, if x is a `t_VEC`, return a `t_VEC` whose components are the $f(x[i])$.

`GEN map_proto_lG(long (*f)(GEN), GEN x)` As above, applying the function `stoi(f())`.

`GEN map_proto_GL(GEN (*f)(GEN, long), GEN x, long y)`

`GEN map_proto_lGL(long (*f)(GEN, long), GEN x, long y)`

In the last function, f implements an associative binary operator, which we extend naturally to an n -ary operator f_n for any n : by convention, $f_0() = 1$, $f_1(x) = x$, and

$$f_n(x_1, \dots, x_n) = f(f_{n-1}(x_1, \dots, x_{n-1}), x_n),$$

for $n \geq 2$.

`GEN gassoc_proto(GEN (*f)(GEN, GEN), GEN x, GEN y)` If y is not NULL, return $f(x, y)$. Otherwise, x must be of vector type, and we return the result of f applied to its components, computed using a divide-and-conquer algorithm. More precisely, return

$$f(f(x_1, \text{NULL}), f(x_2, \text{NULL})),$$

where x_1, x_2 are the two halves of x .

6.2.22 Miscellaneous arithmetic functions.

`long bigomegau(ulong n)` returns the number of prime divisors of $n > 0$, counted with multiplicity.

`ulong coreu(ulong n)`, unique squarefree integer d dividing n such that n/d is a square.

`ulong coreu_fact(GEN fa)` same, where `fa` is `factoru(n)`.

`ulong corediscs(long d, ulong *pt_f)`, d (possibly negative) being congruent to 0 or 1 modulo 4, return the fundamental discriminant D such that $d = D * f^2$ and set `*pt_f` to f (if `*pt_f` not NULL).

`GEN coredisc2_fact(GEN fa, long s, GEN *pP, GEN *pE)` let d be an integer congruent to 0 or 1 mod 4. Return $D = \text{coredisc}(d)$ assuming that `fa` is the factorization of $|d|$ and $sd > 0$ (s is the sign of d). Set `*pP` and `*pE` to the factorization of the conductor f such that $d = Df^2$, where P is a `t_VEC` of primes and E a `t_VECSMALL` of exponents.

`ulong coredisc2u_fact(GEN fa, long s, GEN *pP, GEN *pE)` let d be an integer congruent to 0 or 1 mod 4 whose absolute value fits in an `ulong`. Return the absolute value of $D = \text{corediscs}(d)$ assuming that `fa` is the factorization of $|d|$ and $sd > 0$ (s is the sign of d and D). Set `*pP` and `*pE` to the factorization of the conductor f such that $d = Df^2$, where P is a `t_VECSMALL` of primes and E a `t_VECSMALL` of exponents.

`ulong eulerphiu(ulong n)`, Euler's totient function of n .

`ulong eulerphiu_fact(GEN fa)` same, where `fa` is `factoru(n)`.

`long moebiusu(ulong n)`, Moebius μ -function of n .

`long moebiusu_fact(GEN fa)` same, where `fa` is `factoru(n)`.

`ulong radicalu(ulong n)`, product of primes dividing n .

`GEN divisorsu(ulong n)`, returns the divisors of n in a `t_VECSMALL`, sorted by increasing order.

`GEN divisorsu_fact(GEN fa)` same, where `fa` is `factoru(n)`.

`GEN divisorsu_fact_factored(GEN fa)` where `fa` is `factoru(n)`. Return a vector $[D, F]$, where D is a `t_VECSMALL` containing the divisors of u and $F[i]$ contains `factoru(D[i])`.

`GEN divisorsu_moebius(GEN P)` returns the divisors of n of the form $\prod_{p \in S} (-p)$, $S \subset P$ in a `t_VECSMALL`. The vector is not sorted but its first element is guaranteed to be 1. If P is `factoru(n)[1]`, this returns the set of $\mu(d)d$ where d runs through the squarefree divisors of n .

`long numdivu(ulong n)`, returns the number of positive divisors of $n > 0$.

`long numdivu_fact(GEN fa)` same, where `fa` is `factoru(n)`.

`long omegau(ulong n)` returns the number of prime divisors of $n > 0$.

`long maxomegau(ulong x)` return the optimal B such that $\omega(n) \leq B$ for all $n \leq x$.

`long maxomegaoddu(ulong x)` return the optimal B such that $\omega(n) \leq B$ for all odd $n \leq x$.

`long uissquarefree(ulong n)` returns 1 if n is square-free, and 0 otherwise.

`long uissquarefree_fact(GEN fa)` same, where `fa` is `factoru(n)`.

`long uposisfundamental(ulong x)` return 1 if x is a fundamental discriminant, and 0 otherwise.

`long unegisfundamental(ulong x)` return 1 if $-x$ is a fundamental discriminant, and 0 otherwise.
`long sisfundamental(long x)` return 1 if x is a fundamental discriminant, and 0 otherwise.
`int uis_357_power(ulong x, ulong *pt, ulong *mask)` as `is_357_power` for `ulong x`.
`int uis_357_powermod(ulong x, ulong *mask)` as `uis_357_power`, but only check for 3rd, 5th or 7th powers modulo $211 \times 209 \times 61 \times 203 \times 117 \times 31 \times 43 \times 71$.
`long uisprimepower(ulong n, ulong *p)` as `isprimepower`, for `ulong n`.
`int uislucaspsp(ulong n)` returns 1 if the `ulong n` fails Lucas compositeness test (it thus may be prime or composite), and 0 otherwise (proving that n is composite).
`int uis2psp(ulong n)` returns 1 if the odd `ulong n` fails a strong Rabin-Miller test for the base 2 (it thus may be prime or composite), and 0 otherwise (proving that n is composite).
`int uispsp(ulong a, ulong n)` returns 1 if the odd `ulong n` fails a strong Rabin-Miller test for the base $1 < a < n$ (it thus may be prime or composite), and 0 otherwise (proving that n is composite).
`ulong sumdigitsu(ulong n)` returns the sum of decimal digits of u .
`GEN usumdiv_fact(GEN fa)`, sum of divisors of `ulong n`, where `fa` is `factoru(n)`.
`GEN usumdivk_fact(GEN fa, ulong k)`, sum of k -th powers of divisors of `ulong n`, where `fa` is `factoru(n)`.
`GEN hilbertii(GEN x, GEN y, GEN p)`, returns the Hilbert symbol (x, y) at the prime p (NULL for the place at infinity); x and y are `t_INTs`.
`GEN sumdedekind(GEN h, GEN k)` returns the Dedekind sum attached to the `t_INT` h and k , $k > 0$.
`GEN sumdedekind_coprime(GEN h, GEN k)` as `sumdedekind`, except that h and k are assumed to be coprime `t_INTs`.
`GEN u_sumdedekind_coprime(long h, long k)` Let $k > 0$, $0 \leq h < k$, $(h, k) = 1$. Returns $[s_1, s_2]$ in a `t_VECSMALL`, such that $s(h, k) = (s_2 + ks_1)/(12k)$. Requires $\max(h + k/2, k) < \text{LONG_MAX}$ to avoid overflow, in particular $k \leq (2/3)\text{LONG_MAX}$ is fine.

Chapter 7:

Level 2 kernel

These functions deal with modular arithmetic, linear algebra and polynomials where assumptions can be made about the types of the coefficients.

7.1 Naming scheme.

A function name is built in the following way: $A_1 \dots A_n fun$ for an operation fun with n arguments of class A_1, \dots, A_n . A class name is given by a base ring followed by a number of code letters. Base rings are among

F1: $\mathbf{Z}/l\mathbf{Z}$ where $l < 2^{\text{BITS_IN_LONG}}$ is not necessarily prime. Implemented using **ulongs**

Fp: $\mathbf{Z}/p\mathbf{Z}$ where p is a **t_INT**, not necessarily prime. Implemented as **t_INTs** z , preferably satisfying $0 \leq z < p$. More precisely, any **t_INT** can be used as an **Fp**, but reduced inputs are treated more efficiently. Outputs from **Fpxxx** routines are reduced.

Fq: $\mathbf{Z}[X]/(p, T(X))$, p a **t_INT**, T a **t_POL** with **Fp** coefficients or **NULL** (in which case no reduction modulo T is performed). Implemented as **t_POLs** z with **Fp** coefficients, $\deg(z) < \deg T$, although z a **t_INT** is allowed for elements in the prime field.

Z: the integers \mathbf{Z} , implemented as **t_INTs**.

Zp: the p -adic integers \mathbf{Z}_p , implemented as **t_INTs**, for arbitrary p

Z1: the p -adic integers \mathbf{Z}_p , implemented as **t_INTs**, for $p < 2^{\text{BITS_IN_LONG}}$

z: the integers \mathbf{Z} , implemented using (signed) **longs**.

Q: the rational numbers \mathbf{Q} , implemented as **t_INTs** and **t_FRACs**.

Rg: a commutative ring, whose elements can be **gadd**-ed, **gmul**-ed, etc.

Possible letters are:

X: polynomial in X (**t_POL** in a fixed variable), e.g. **FpX** means $\mathbf{Z}/p\mathbf{Z}[X]$

Y: polynomial in $Y \neq X$. This is used to resolve ambiguities. E.g. **FpXY** means $((\mathbf{Z}/p\mathbf{Z}[X])[Y])$.

V: vector (**t_VEC** or **t_COL**), treated as a row vector (independently of the actual type). E.g. **ZV** means \mathbf{Z}^k for some k .

C: vector (**t_VEC** or **t_COL**), treated as a column vector (independently of the actual type). The difference with **V** is purely semantic: if the result is a vector, it will be of type **t_COL** unless mentioned otherwise. For instance the function **ZC_add** receives two integral vectors (**t_COL** or **t_VEC**, possibly different types) of the same length and returns a **t_COL** whose entries are the sums of the input coefficients.

M: matrix (**t_MAT**). E.g. **QM** means a matrix with rational entries

T: Trees. Either a leaf or a **t_VEC** of trees.

E: point over an elliptic curve, represented as two-component vectors $[x, y]$, except for the represented by the one-component vector $[0]$. Not all curve models are supported.

Q: representative (**t_POL**) of a class in a polynomial quotient ring. E.g. an **FpXQ** belongs to $(\mathbf{Z}/p\mathbf{Z})[X]/(T(X))$, **FpXQV** means a vector of such elements, etc.

n: a polynomial representative (**t_POL**) for a truncated power series modulo X^n . E.g. an **FpXn** belongs to $(\mathbf{Z}/p\mathbf{Z})[X]/(X^n)$, **FpXnV** means a vector of such elements, etc.

x, **y**, **m**, **v**, **c**, **q**: as their uppercase counterpart, but coefficient arrays are implemented using **t_VECSMALLs**, which coefficient understood as **ulongs**.

x and **y** (and **q**) are implemented by a **t_VECSMALL** whose first coefficient is used as a code-word and the following are the coefficients, similarly to a **t_POL**. This is known as a 'POLSMALL'.

m are implemented by a **t_MAT** whose components (columns) are **t_VECSMALLs**. This is known as a 'MATSMALL'.

v and **c** are regular **t_VECSMALLs**. Difference between the two is purely semantic.

Omitting the letter means the argument is a scalar in the base ring. Standard functions *fun* are

add: add

sub: subtract

mul: multiply

sqr: square

div: divide (Euclidean quotient)

rem: Euclidean remainder

divrem: return Euclidean quotient, store remainder in a pointer argument. Three special values of that pointer argument modify the default behavior: **NULL** (do not store the remainder, used to implement **div**), **ONLY_REM** (return the remainder, used to implement **rem**), **ONLY_DIVIDES** (return the quotient if the division is exact, and **NULL** otherwise).

gcd: GCD

extgcd: return GCD, store Bezout coefficients in pointer arguments

pow: exponentiate

eval: evaluation / composition

7.2 Coefficient ring.

`long Rg_type(GEN x, GEN *ptp, GEN *ptpol, long *ptprec)` returns the “natural” base ring over which the object x is defined.

Raise an error if it detects consistency problems in modular objects: incompatible rings (e.g. \mathbf{F}_p and \mathbf{F}_q for primes $p \neq q$, $\mathbf{F}_p[X]/(T)$ and $\mathbf{F}_p[X]/(U)$ for $T \neq U$). Minor discrepancies are supported if they make general sense (e.g. \mathbf{F}_p and \mathbf{F}_{p^k} , but not \mathbf{F}_p and \mathbf{Q}_p); `t_FFELT` and `t_POLMOD` of `t_INTMODs` are considered inconsistent, even if they define the same field: if you need to use simultaneously these different finite field implementations, multiply the polynomial by a `t_FFELT` equal to 1 first.

- 0: none of the others (presumably multivariate, possibly inconsistent).
- `t_INT`: defined over \mathbf{Z} .
- `t_FRAC`: defined over \mathbf{Q} .
- `t_INTMOD`: defined over $\mathbf{Z}/p\mathbf{Z}$, where `*ptp` is set to p . It is not checked whether p is prime.
- `t_COMPLEX`: defined over \mathbf{C} (at least one `t_COMPLEX` with at least one inexact floating point `t_REAL` component). Set `*ptprec` to the minimal accuracy (as per `precision`) of inexact components.
- `t_REAL`: defined over \mathbf{R} (at least one inexact floating point `t_REAL` component). Set `*ptprec` to the minimal accuracy (as per `precision`) of inexact components.
- `t_PADIC`: defined over \mathbf{Q}_p , where `*ptp` is set to p and `*ptprec` to the p -adic accuracy.
- `t_FFELT`: defined over a finite field \mathbf{F}_{p^k} , where `*ptp` is set to the field characteristic p and `*ptpol` is set to a `t_FFELT` belonging to the field.
- `t_POL`: defined over a polynomial ring.
- other values are composite corresponding to quotients $R[X]/(T)$, with one primary type `t1`, describing the form of the quotient, and a secondary type `t2`, describing R . If `t` is the `RgX_type`, `t1` and `t2` are recovered using

```
void RgX_type_decode(long t, long *t1, long *t2)
```

`t1` is one of

`t_POLMOD`: at least one `t_POLMOD` component, set `*ppol` to the modulus,

`t_QUAD`: no `t_POLMOD`, at least one `t_QUAD` component, set `*ppol` to the modulus (`-.pol`) of the `t_QUAD`,

`t_COMPLEX`: no `t_POLMOD` or `t_QUAD`, at least one `t_COMPLEX` component, set `*ppol` to $y^2 + 1$.

and the underlying base ring R is given by `t2`, which is one of `t_INT`, `t_INTMOD` (set `*ptp`) or `t_PADIC` (set `*ptp` and `*ptprec`), with the same meaning as above.

`int RgX_type_is_composite(long t)` t as returned by `RgX_type`, return 1 if t is a composite type, and 0 otherwise.

`GEN Rg_get_0(GEN x)` returns 0 in the base ring over which x is defined, to the proper accuracy (e.g. 0, Mod(0,3), 0(5^10)).

`GEN Rg_get_1(GEN x)` returns 1 in the base ring over which x is defined, to the proper accuracy (e.g. 0, Mod(0,3),

`long RgX_type(GEN x, GEN *ptp, GEN *ptpol, long *ptprec)` returns the “natural” base ring over which the polynomial x is defined, otherwise as `Rg_type`.

`long RgX_Rg_type(GEN x, GEN y, GEN *ptp, GEN *ptpol, long *ptprec)` returns the “natural” base ring over which the polynomial x and the element y are defined, otherwise as `Rg_type`.

`long RgX_type2(GEN x, GEN y, GEN *ptp, GEN *ptpol, long *ptprec)` returns the “natural” base ring over which the polynomials x and y are defined, otherwise as `Rg_type`.

`long RgX_type3(GEN x, GEN y, GEN z, GEN *ptp, GEN *ptpol, long *ptprec)` returns the “natural” base ring over which the polynomials x , y and z are defined, otherwise as `Rg_type`.

`long RgM_type(GEN x, GEN *ptp, GEN *ptpol, long *ptprec)` returns the “natural” base ring over which the matrix x is defined, otherwise as `Rg_type`.

`long RgM_type2(GEN x, GEN y, GEN *ptp, GEN *ptpol, long *ptprec)` returns the “natural” base ring over which the matrices x and y are defined, otherwise as `Rg_type`.

`long RgV_type(GEN x, GEN *ptp, GEN *ptpol, long *ptprec)` returns the “natural” base ring over which the vector x is defined, otherwise as `Rg_type`.

`long RgV_type2(GEN x, GEN y, GEN *ptp, GEN *ptpol, long *ptprec)` returns the “natural” base ring over which the vectors x and y are defined, otherwise as `Rg_type`.

`long RgM_RgC_type(GEN x, GEN y, GEN *ptp, GEN *ptpol, long *ptprec)` returns the “natural” base ring over which the matrix x and the vector y are defined, otherwise as `Rg_type`.

7.3 Modular arithmetic.

These routines implement univariate polynomial arithmetic and linear algebra over finite fields, in fact over finite rings of the form $(\mathbf{Z}/p\mathbf{Z})[X]/(T)$, where p is not necessarily prime and $T \in (\mathbf{Z}/p\mathbf{Z})[X]$ is possibly reducible; and finite extensions thereof. All this can be emulated with `t_INTMOD` and `t_POLMOD` coefficients and using generic routines, at a considerable loss of efficiency. Also, specialized routines are available that have no obvious generic equivalent.

7.3.1 FpC / FpV, FpM. A ZV (resp. a ZM) is a `t_VEC` or `t_COL` (resp. `t_MAT`) with `t_INT` coefficients. An FpV or FpM, with respect to a given `t_INT` p , is the same with Fp coordinates; operations are understood over $\mathbf{Z}/p\mathbf{Z}$.

7.3.1.1 Conversions.

`int Rg_is_Fp(GEN z, GEN *p)`, checks if z can be mapped to $\mathbf{Z}/p\mathbf{Z}$: a `t_INT` or a `t_INTMOD` whose modulus is equal to $*p$, (if $*p$ not NULL), in that case return 1, else 0. If a modulus is found it is put in $*p$, else $*p$ is left unchanged.

`int RgV_is_FpV(GEN z, GEN *p)`, z a `t_VEC` (resp. `t_COL`), checks if it can be mapped to a FpV (resp. FpC), by checking `Rg_is_Fp` coefficientwise.

`int RgM_is_FpM(GEN z, GEN *p)`, z a `t_MAT`, checks if it can be mapped to a FpM, by checking `RgV_is_FpV` columnwise.

`GEN Rg_to_Fp(GEN z, GEN p)`, z a scalar which can be mapped to $\mathbf{Z}/p\mathbf{Z}$: a `t_INT`, a `t_INTMOD` whose modulus is divisible by p , a `t_FRAC` whose denominator is coprime to p , or a `t_PADIC` with underlying prime ℓ satisfying $p = \ell^n$ for some n (less than the accuracy of the input). Returns `lift(z * Mod(1,p))`, normalized.

GEN padic_to_Fp(GEN x, GEN p) special case of Rg_to_Fp, for a x a `t_PADIC`.

GEN RgV_to_FpV(GEN z, GEN p), z a `t_VEC` or `t_COL`, returns the `FpV` (as a `t_VEC`) obtained by applying `Rg_to_Fp` coefficientwise.

GEN RgC_to_FpC(GEN z, GEN p), z a `t_VEC` or `t_COL`, returns the `FpC` (as a `t_COL`) obtained by applying `Rg_to_Fp` coefficientwise.

GEN RgM_to_FpM(GEN z, GEN p), z a `t_MAT`, returns the `FpM` obtained by applying `RgC_to_FpC` columnwise.

GEN RgM_Fp_init(GEN z, GEN p, ulong *pp), given an `RgM` z , whose entries can be mapped to \mathbf{F}_p (as per `Rg_to_Fp`), and a prime number p . This routine returns a normal form of z : either an `F2m` ($p = 2$), an `F1m` (p fits into an `ulong`) or an `FpM`. In the first two cases, `pp` is set to `itou(p)`, and to 0 in the last.

The functions above are generally used as follows:

```
GEN add(GEN x, GEN y)
{
    GEN p = NULL;
    if (Rg_is_Fp(x, &p) && Rg_is_Fp(y, &p) && p)
    {
        x = Rg_to_Fp(x, p); y = Rg_to_Fp(y, p);
        z = Fp_add(x, y, p);
        return Fp_to_mod(z);
    }
    else return gadd(x, y);
}
```

GEN FpC_red(GEN z, GEN p), z a `ZC`. Returns `lift(Col(z) * Mod(1,p))`, hence a `t_COL`.

GEN FpV_red(GEN z, GEN p), z a `ZV`. Returns `lift(Vec(z) * Mod(1,p))`, hence a `t_VEC`.

GEN FpM_red(GEN z, GEN p), z a `ZM`. Returns `lift(z * Mod(1,p))`, which is an `FpM`.

7.3.1.2 Basic operations.

GEN random_FpC(long n, GEN p) returns a random `FpC` with n components.

GEN random_FpV(long n, GEN p) returns a random `FpV` with n components.

GEN FpC_center(GEN z, GEN p, GEN pov2) returns a `t_COL` whose entries are the `Fp_center` of the `gel(z,i)`.

GEN FpM_center(GEN z, GEN p, GEN pov2) returns a matrix whose entries are the `Fp_center` of the `gcoeff(z,i,j)`.

void FpC_center_inplace(GEN z, GEN p, GEN pov2) in-place version of `FpC_center`, using `affii`.

void FpM_center_inplace(GEN z, GEN p, GEN pov2) in-place version of `FpM_center`, using `affii`.

GEN FpC_add(GEN x, GEN y, GEN p) adds the `ZC` x and y and reduce modulo p to obtain an `FpC`.

GEN FpV_add(GEN x, GEN y, GEN p) same as `FpC_add`, returning and `FpV`.

GEN FpM_add(GEN x, GEN y, GEN p) adds the two ZMs x and y (assumed to have compatible dimensions), and reduce modulo p to obtain an FpM.

GEN FpC_sub(GEN x, GEN y, GEN p) subtracts the ZC y to the ZC x and reduce modulo p to obtain an FpC.

GEN FpV_sub(GEN x, GEN y, GEN p) same as FpC_sub, returning and FpV.

GEN FpM_sub(GEN x, GEN y, GEN p) subtracts the two ZMs x and y (assumed to have compatible dimensions), and reduce modulo p to obtain an FpM.

GEN FpC_Fp_mul(GEN x, GEN y, GEN p) multiplies the ZC x (seen as a column vector) by the t_INT y and reduce modulo p to obtain an FpC.

GEN FpM_Fp_mul(GEN x, GEN y, GEN p) multiplies the ZM x (seen as a column vector) by the t_INT y and reduce modulo p to obtain an FpM.

GEN FpC_FpV_mul(GEN x, GEN y, GEN p) multiplies the ZC x (seen as a column vector) by the ZV y (seen as a row vector, assumed to have compatible dimensions), and reduce modulo p to obtain an FpM.

GEN FpM_mul(GEN x, GEN y, GEN p) multiplies the two ZMs x and y (assumed to have compatible dimensions), and reduce modulo p to obtain an FpM.

GEN FpM_powu(GEN x, ulong n, GEN p) computes x^n where x is a square FpM.

GEN FpM_FpC_mul(GEN x, GEN y, GEN p) multiplies the ZM x by the ZC y (seen as a column vector, assumed to have compatible dimensions), and reduce modulo p to obtain an FpC.

GEN FpM_FpC_mul_FpX(GEN x, GEN y, GEN p, long v) is a memory-clean version of

```
GEN tmp = FpM_FpC_mul(x,y,p);
return RgV_to_RgX(tmp, v);
```

GEN FpV_FpC_mul(GEN x, GEN y, GEN p) multiplies the ZV x (seen as a row vector) by the ZC y (seen as a column vector, assumed to have compatible dimensions), and reduce modulo p to obtain an Fp.

GEN FpV_dotproduct(GEN x, GEN y, GEN p) scalar product of x and y (assumed to have the same length).

GEN FpV_dotsquare(GEN x, GEN p) scalar product of x with itself. has t_INT entries.

GEN FpV_factorback(GEN L, GEN e, GEN p) given an FpV L and a ZV or zv e of the same length, return $\prod_i L_i^{e_i}$ modulo p.

7.3.1.3 Fp-linear algebra. The implementations are not asymptotically efficient ($O(n^3)$ standard algorithms).

GEN FpM_deplin(GEN x, GEN p) returns a nontrivial kernel vector, or NULL if none exist.

GEN FpM_det(GEN x, GEN p) as det

GEN FpM_gauss(GEN a, GEN b, GEN p) as gauss, where a and b are FpM.

GEN FpM_FpC_gauss(GEN a, GEN b, GEN p) as gauss, where a is a FpM and b a FpC.

GEN FpM_image(GEN x, GEN p) as image

GEN FpM_intersect(GEN x, GEN y, GEN p) as intersect

GEN FpM_intersect_i(GEN x, GEN y, GEN p) internal variant of FpM_intersect but the result is only a generating set, not necessarily an \mathbf{F}_p -basis. It is not gerepile-clean either, but suitable for gerepileupto.

GEN FpM_inv(GEN x, GEN p) returns a left inverse of x (the inverse if x is square), or NULL if x is not invertible.

GEN FpM_FpC_invimage(GEN A, GEN y, GEN p) given an FpM A and an FpC y , returns an x such that $Ax = y$, or NULL if no such vector exist.

GEN FpM_invimage(GEN A, GEN y, GEN p) given two FpM A and y , returns x such that $Ax = y$, or NULL if no such matrix exist.

GEN FpM_ker(GEN x, GEN p) as ker

long FpM_rank(GEN x, GEN p) as rank

GEN FpM_indexrank(GEN x, GEN p) as indexrank

GEN FpM_suppl(GEN x, GEN p) as suppl

GEN FpM_hess(GEN x, GEN p) upper Hessenberg form of x over \mathbf{F}_p .

GEN FpM_charpoly(GEN x, GEN p) characteristic polynomial of x .

7.3.1.4 FqC, FqM and Fq-linear algebra.

An FqM (resp. FqC) is a matrix (resp a t_COL) with Fq coefficients (with respect to given T, p), not necessarily reduced (i.e arbitrary t_INTs and ZXs in the same variable as T).

GEN RgC_to_FqC(GEN z, GEN T, GEN p)

GEN RgM_to_FqM(GEN z, GEN T, GEN p)

GEN FqC_add(GEN a, GEN b, GEN T, GEN p)

GEN FqC_sub(GEN a, GEN b, GEN T, GEN p)

GEN FqC_FqC_mul(GEN a, GEN b, GEN T, GEN p)

GEN FqC_FqV_mul(GEN a, GEN b, GEN T, GEN p)

GEN FqM_FqC_gauss(GEN a, GEN b, GEN T, GEN p) as gauss, where b is a FqC.

GEN FqM_FqC_invimage(GEN a, GEN b, GEN T, GEN p)

GEN FqM_FqC_mul(GEN a, GEN b, GEN T, GEN p)

GEN FqM_deplin(GEN x, GEN T, GEN p) returns a nontrivial kernel vector, or NULL if none exist.

GEN FqM_det(GEN x, GEN T, GEN p) as det

GEN FqM_gauss(GEN a, GEN b, GEN T, GEN p) as gauss, where b is a FqM.

GEN FqM_image(GEN x, GEN T, GEN p) as image

GEN FqM_indexrank(GEN x, GEN T, GEN p) as indexrank

GEN FqM_inv(GEN x, GEN T, GEN p) returns the inverse of x , or NULL if x is not invertible.

GEN FqM_invimage(GEN a, GEN b, GEN T, GEN p) as invimage

GEN FqM_ker(GEN x, GEN T, GEN p) as ker

`GEN FqM_mul(GEN a, GEN b, GEN T, GEN p)`
`long FqM_rank(GEN x, GEN T, GEN p)` as rank
`GEN FqM_suppl(GEN x, GEN T, GEN p)` as suppl
7.3.2 Flc / Flv, Flm. See FpV, FpM operations.
`GEN Flv_copy(GEN x)` returns a copy of x .
`GEN Flv_center(GEN z, ulong p, ulong ps2)`
`GEN random_Flv(long n, ulong p)` returns a random Flv with n components.
`GEN Flm_copy(GEN x)` returns a copy of x .
`GEN matid_Flm(long n)` returns an Flm which is an $n \times n$ identity matrix.
`GEN scalar_Flm(long s, long n)` returns an Flm which is s times the $n \times n$ identity matrix.
`GEN Flm_center(GEN z, ulong p, ulong ps2)`
`GEN Flm_Fl_add(GEN x, ulong y, ulong p)` returns $x + y * \text{Id}$ (x must be square).
`GEN Flm_Fl_sub(GEN x, ulong y, ulong p)` returns $x - y * \text{Id}$ (x must be square).
`GEN Flm_Flc_mul(GEN x, GEN y, ulong p)` multiplies x and y (assumed to have compatible dimensions).
`GEN Flm_Flc_mul_pre(GEN x, GEN y, ulong p, ulong pi)` multiplies x and y (assumed to have compatible dimensions), assuming pi is the pseudoinverse of p , or 0 in which case we assume $\text{SMALL_ULONG}(p)$.
`GEN Flc_Flv_mul(GEN x, GEN y, ulong p)` multiplies the column vector x by the row vector y . The result is a matrix.
`GEN Flm_Flc_mul_pre_Flx(GEN x, GEN y, ulong p, ulong pi, long sv)` return `Flv_to_Flx(Flm_Flc_mul_pre(x, y, p, pi), sv)`.
`GEN Flm_Fl_mul(GEN x, ulong y, ulong p)` multiplies the Flm x by y .
`GEN Flm_Fl_mul_pre(GEN x, ulong y, ulong p, ulong pi)` multiplies the Flm x by y assuming pi is the pseudoinverse of p , or 0 in which case we assume $p < B^{1/2}$ is small.
`GEN Flm_neg(GEN x, ulong p)` negates the Flm x .
`void Flm_Fl_mul_inplace(GEN x, ulong y, ulong p)` replaces the Flm x by $x * y$.
`GEN Flv_Fl_mul(GEN x, ulong y, ulong p)` multiplies the Flv x by y .
`void Flv_Fl_mul_inplace(GEN x, ulong y, ulong p)` replaces the Flc x by $x * y$.
`void Flv_Fl_mul_part_inplace(GEN x, ulong y, ulong p, long l)` multiplies $x[1..l]$ by y modulo p . In place.
`GEN Flv_Fl_div(GEN x, ulong y, ulong p)` divides the Flv x by y .
`void Flv_Fl_div_inplace(GEN x, ulong y, ulong p)` replaces the Flv x by x/y .
`void Flc_lincomb1_inplace(GEN X, GEN Y, ulong v, ulong q)` sets $X \leftarrow X + vY$, where X, Y are Flc. Memory efficient (e.g. no-op if $v = 0$), and gerepile-safe.

`GEN Flv_add(GEN x, GEN y, ulong p)` adds two Flv.
`void Flv_add_inplace(GEN x, GEN y, ulong p)` replaces x by $x + y$.
`GEN Flv_neg(GEN x, ulong p)` returns $-x$.
`void Flv_neg_inplace(GEN x, ulong p)` replaces x by $-x$.
`GEN Flv_sub(GEN x, GEN y, ulong p)` subtracts y to x .
`void Flv_sub_inplace(GEN x, GEN y, ulong p)` replaces x by $x - y$.
`ulong Flv_dotproduct(GEN x, GEN y, ulong p)` returns the scalar product of x and y
`ulong Flv_dotproduct_pre(GEN x, GEN y, ulong p, ulong pi)` returns the scalar product of x and y assuming pi is the pseudoinverse of p , or 0 in which case we assume `SMALL_ULONG(p)`.
`GEN Flv_factorback(GEN L, GEN e, ulong p)` given an Flv L and a zv e of the same length, return $\prod_i L_i^{e_i}$ modulo p .
`ulong Flv_sum(GEN x, ulong p)` returns the sum of the components of x .
`ulong Flv_prod(GEN x, ulong p)` returns the product of the components of x .
`ulong Flv_prod_pre(GEN x, ulong p, ulong pi)` as `Flv_prod` assuming pi is the pseudoinverse of p .
`GEN Flv_inv(GEN x, ulong p)` returns the vector of inverses of the elements of x (as a Flv). Use Montgomery's trick.
`void Flv_inv_inplace(GEN x, ulong p)` in place variant of `Flv_inv`.
`GEN Flv_inv_pre(GEN x, ulong p, ulong pi)` as `Flv_inv` assuming pi is the pseudoinverse of p .
`void Flv_inv_pre_inplace(GEN x, ulong p, ulong pi)` in place variant of `Flv_inv`.
`GEN Flc_FpV_mul(GEN x, GEN y, GEN p)` multiplies x (seen as a column vector) by y (seen as a row vector, assumed to have compatible dimensions) to obtain an Flm.
`GEN zero_Flm(long m, long n)` creates a Flm with $m \times n$ components set to 0. Note that the result allocates a *single* column, so modifying an entry in one column modifies it in all columns.
`GEN zero_Flm_copy(long m, long n)` creates a Flm with $m \times n$ components set to 0.
`GEN zero_Flv(long n)` creates a Flv with n components set to 0.
`GEN Flm_row(GEN A, long x0)` return $A[i,]$, the i -th row of the Flm A .
`GEN Flm_add(GEN x, GEN y, ulong p)` adds x and y (assumed to have compatible dimensions).
`GEN Flm_sub(GEN x, GEN y, ulong p)` subtracts x and y (assumed to have compatible dimensions).
`GEN Flm_mul(GEN x, GEN y, ulong p)` multiplies x and y (assumed to have compatible dimensions).
`GEN Flm_mul_pre(GEN x, GEN y, ulong p, ulong pi)` multiplies x and y (assumed to have compatible dimensions), assuming pi is the pseudoinverse of p , or 0 in which case we assume `SMALL_ULONG(p)`.
`GEN Flm_sqr(GEN x, ulong p)` squares x (assumed to be square).

`GEN Flm_powers(GEN x, ulong n, ulong p)` returns $[x^0, \dots, x^n]$ as a `t_VEC` of `Flms`.

`GEN Flm_powu(GEN x, ulong n, ulong p)` computes x^n where x is a square `Flm`.

`GEN Flm_charpoly(GEN x, ulong p)` return the characteristic polynomial of the square `Flm` x , as a `Flx`.

`GEN Flm_deplin(GEN x, ulong p)`

`ulong Flm_det(GEN x, ulong p)`

`ulong Flm_det_sp(GEN x, ulong p)`, as `Flm_det`, in place (destroys x).

`GEN Flm_gauss(GEN a, GEN b, ulong p)` as `gauss`, where b is a `Flm`.

`GEN Flm_Flc_gauss(GEN a, GEN b, ulong p)` as `gauss`, where b is a `Flc`.

`GEN Flm_indexrank(GEN x, ulong p)`

`GEN Flm_inv(GEN x, ulong p)`

`GEN Flm_adjoint(GEN x, ulong p)` as `matadjoint`.

`GEN Flm_Flc_invimage(GEN A, GEN y, ulong p)` given an `Flm` A and an `Flc` y , returns an x such that $Ax = y$, or `NULL` if no such vector exist.

`GEN Flm_invimage(GEN A, GEN y, ulong p)` given two `Flm` A and y , returns x such that $Ax = y$, or `NULL` if no such matrix exist.

`GEN Flm_ker(GEN x, ulong p)`

`GEN Flm_ker_sp(GEN x, ulong p, long deplin)`, as `Flm_ker` (if `deplin=0`) or `Flm_deplin` (if `deplin=1`), in place (destroys x).

`long Flm_rank(GEN x, ulong p)`

`long Flm_suppl(GEN x, ulong p)`

`GEN Flm_image(GEN x, ulong p)`

`GEN Flm_intersect(GEN x, GEN y, ulong p)`

`GEN Flm_intersect_i(GEN x, GEN y, GEN p)` internal variant of `Flm_intersect` but the result is only a generating set, not necessarily an \mathbf{F}_p -basis. It *is* a basis if both x and y have independent columns. It is not `gerepile-clean` either, but suitable for `gerepileupto`.

`GEN Flm_transpose(GEN x)`

`GEN Flm_hess(GEN x, ulong p)` upper Hessenberg form of x over \mathbf{F}_p .

7.3.3 F2c / F2v, F2m. An F2v v is a `t_VECSMALL` representing a vector over \mathbf{F}_2 . Specifically $z[0]$ is the usual codeword, $z[1]$ is the number of components of v and the coefficients are given by the bits of remaining words by increasing indices.

`ulong F2v_coeff(GEN x, long i)` returns the coefficient $i \geq 1$ of x .

`void F2v_clear(GEN x, long i)` sets the coefficient $i \geq 1$ of x to 0.

`int F2v_equal0(GEN x)` returns 1 if all entries are 0, and return 0 otherwise.

`void F2v_flip(GEN x, long i)` adds 1 to the coefficient $i \geq 1$ of x .

`void F2v_set(GEN x, long i)` sets the coefficient $i \geq 1$ of x to 1.

`void F2v_copy(GEN x)` returns a copy of x .

`GEN F2v_slice(GEN x, long a, long b)` returns the F2v with entries $x[a], \dots, x[b]$. Assumes $a \leq b$.

`ulong F2m_coeff(GEN x, long i, long j)` returns the coefficient (i, j) of x .

`void F2m_clear(GEN x, long i, long j)` sets the coefficient (i, j) of x to 0.

`void F2m_flip(GEN x, long i, long j)` adds 1 to the coefficient (i, j) of x .

`void F2m_set(GEN x, long i, long j)` sets the coefficient (i, j) of x to 1.

`GEN F2m_copy(GEN x)` returns a copy of x .

`GEN F2m_transpose(GEN x)` returns the transpose of x .

`GEN F2m_row(GEN x, long j)` returns the F2v which corresponds to the j -th row of the F2m x .

`GEN F2m_rowslice(GEN x, long a, long b)` returns the F2m built from the a -th to b -th rows of the F2m x . Assumes $a \leq b$.

`GEN F2m_F2c_mul(GEN x, GEN y)` multiplies x and y (assumed to have compatible dimensions).

`GEN F2m_image(GEN x)` gives a subset of the columns of x that generate the image of x .

`GEN F2m_invimage(GEN A, GEN B)`

`GEN F2m_F2c_invimage(GEN A, GEN y)`

`GEN F2m_gauss(GEN a, GEN b)` as `gauss`, where b is a F2m.

`GEN F2m_F2c_gauss(GEN a, GEN b)` as `gauss`, where b is a F2c.

`GEN F2m_indexrank(GEN x)` x being a matrix of rank r , returns a vector with two `t_VECSMALL` components y and z of length r giving a list of rows and columns respectively (starting from 1) such that the extracted matrix obtained from these two vectors using `vecextract(x, y, z)` is invertible.

`GEN F2m_mul(GEN x, GEN y)` multiplies x and y (assumed to have compatible dimensions).

`GEN F2m_powu(GEN x, ulong n)` computes x^n where x is a square F2m.

`long F2m_rank(GEN x)` as `rank`.

`long F2m_suppl(GEN x)` as `suppl`.

`GEN matid_F2m(long n)` returns an F2m which is an $n \times n$ identity matrix.

`GEN zero_F2v(long n)` creates a F2v with n components set to 0.

GEN `const_F2v(long n)` creates a `F2v` with `n` components set to 1.

GEN `F2v_ei(long n, long i)` creates a `F2v` with `n` components set to 0, but for the i -th one, which is set to 1 (i -th vector in the canonical basis).

GEN `zero_F2m(long m, long n)` creates a `F1m` with $m \times n$ components set to 0. Note that the result allocates a *single* column, so modifying an entry in one column modifies it in all columns.

GEN `zero_F2m_copy(long m, long n)` creates a `F2m` with $m \times n$ components set to 0.

GEN `F2v_to_F1v(GEN x)`

GEN `F2c_to_ZC(GEN x)`

GEN `ZV_to_F2v(GEN x)`

GEN `RgV_to_F2v(GEN x)`

GEN `F2m_to_F1m(GEN x)`

GEN `F2m_to_ZM(GEN x)`

GEN `F1v_to_F2v(GEN x)`

GEN `F1m_to_F2m(GEN x)`

GEN `ZM_to_F2m(GEN x)`

GEN `RgM_to_F2m(GEN x)`

`void F2v_add_inplace(GEN x, GEN y)` replaces x by $x + y$. It is allowed for y to be shorter than x .

`void F2v_and_inplace(GEN x, GEN y)` replaces x by the term-by term product of x and y (which is the logical and). It is allowed for y to be shorter than x .

`void F2v_negimply_inplace(GEN x, GEN y)` replaces x by the term-by term logical **and not** of x and y . It is allowed for y to be shorter than x .

`void F2v_or_inplace(GEN x, GEN y)` replaces x by the term-by term logical **or** of x and y . It is allowed for y to be shorter than x .

`int F2v_subset(GEN x, GEN y)` return 1 if the set of indices of non-zero components of y is a subset of the set of indices of non-zero components of x , 0 otherwise.

`ulong F2v_hamming(GEN x)` returns the Hamming weight of x , that is the number of nonzero entries.

`ulong F2m_det(GEN x)`

`ulong F2m_det_sp(GEN x)`, as `F2m_det`, in place (destroys x).

GEN `F2m_deplin(GEN x)`

`ulong F2v_dotproduct(GEN x, GEN y)` returns the scalar product of x and y

GEN `F2m_inv(GEN x)`

GEN `F2m_ker(GEN x)`

GEN `F2m_ker_sp(GEN x, long deplin)`, as `F2m_ker` (if `deplin=0`) or `F2m_deplin` (if `deplin=1`), in place (destroys x).

7.3.4 F3c / F3v, F3m. An F3v v is a `t_VECSMALL` representing a vector over \mathbf{F}_3 . Specifically $z[0]$ is the usual codeword, $z[1]$ is the number of components of v and the coefficients are given by pair of adjacent bits of remaining words by increasing indices, with the coding $00 \mapsto 0, 01 \mapsto 1, 10 \mapsto 2$ and 11 is undefined.

`ulong F3v_coeff(GEN x, long i)` returns the coefficient $i \geq 1$ of x .

`void F3v_clear(GEN x, long i)` sets the coefficient $i \geq 1$ of x to 0.

`void F3v_set(GEN x, long i, ulong n)` sets the coefficient $i \geq 1$ of x to $n < 3$,

`ulong F3m_coeff(GEN x, long i, long j)` returns the coefficient (i, j) of x .

`void F3m_set(GEN x, long i, long j, ulong n)` sets the coefficient (i, j) of x to $n < 3$.

`GEN F3m_copy(GEN x)` returns a copy of x .

`GEN F3m_transpose(GEN x)` returns the transpose of x .

`GEN F3m_row(GEN x, long j)` returns the F3v which corresponds to the j -th row of the F3m x .

`GEN F3m_ker(GEN x)`

`GEN F3m_ker_sp(GEN x, long deplin)`, as `F3m_ker` (if `deplin=0`) or `F2m_deplin` (if `deplin=1`), in place (destroys x).

`GEN F3m_mul(GEN x, GEN y)` multiplies x and y (assumed to have compatible dimensions).

`GEN zero_F3v(long n)` creates a F3v with n components set to 0.

`GEN zero_F3m_copy(long m, long n)` creates a F3m with $m \times n$ components set to 0.

`GEN F3v_to_Flv(GEN x)`

`GEN ZV_to_F3v(GEN x)`

`GEN RgV_to_F3v(GEN x)`

`GEN F3c_to_ZC(GEN x)`

`GEN F3m_to_Flm(GEN x)`

`GEN F3m_to_ZM(GEN x)`

`GEN Flv_to_F3v(GEN x)`

`GEN Flm_to_F3m(GEN x)`

`GEN ZM_to_F3m(GEN x)`

`GEN RgM_to_F3m(GEN x)`

7.3.5 FlxqV, FlxqC, FlxqM. See FqV, FqC, FqM operations.

GEN FlxqV_dotproduct(GEN x, GEN y, GEN T, ulong p) as FpV_dotproduct.

GEN FlxqV_dotproduct_pre(GEN x, GEN y, GEN T, ulong p, ulong pi) where pi is the pseudoinverse of p , or 0 in which case we assume $\text{SMALL_ULONG}(p)$.

GEN FlxM_Flx_add_shallow(GEN x, GEN y, ulong p) as RgM_Rg_add_shallow.

GEN FlxqC_Flxq_mul(GEN x, GEN y, GEN T, ulong p)

GEN FlxqM_Flxq_mul(GEN x, GEN y, GEN T, ulong p)

GEN FlxqM_FlxqC_gauss(GEN a, GEN b, GEN T, ulong p)

GEN FlxqM_FlxqC_invimage(GEN a, GEN b, GEN T, ulong p)

GEN FlxqM_FlxqC_mul(GEN a, GEN b, GEN T, ulong p)

GEN FlxqM_deplin(GEN x, GEN T, ulong p)

GEN FlxqM_det(GEN x, GEN T, ulong p)

GEN FlxqM_gauss(GEN a, GEN b, GEN T, ulong p)

GEN FlxqM_image(GEN x, GEN T, ulong p)

GEN FlxqM_indexrank(GEN x, GEN T, ulong p)

GEN FlxqM_inv(GEN x, GEN T, ulong p)

GEN FlxqM_invimage(GEN a, GEN b, GEN T, ulong p)

GEN FlxqM_ker(GEN x, GEN T, ulong p)

GEN FlxqM_mul(GEN a, GEN b, GEN T, ulong p)

long FlxqM_rank(GEN x, GEN T, ulong p)

GEN FlxqM_suppl(GEN x, GEN T, ulong p)

GEN matid_FlxqM(long n, GEN T, ulong p)

7.3.6 FpX. Let p an understood t_INT , to be given in the function arguments; in practice p is not assumed to be prime, but be wary. Recall than an Fp object is a t_INT , preferably belonging to $[0, p - 1]$; an FpX is a t_POL in a fixed variable whose coefficients are Fp objects. Unless mentioned otherwise, all outputs in this section are FpX s. All operations are understood to take place in $(\mathbf{Z}/p\mathbf{Z})[X]$.

7.3.6.1 Conversions. In what follows p is always a t_INT , not necessarily prime.

int RgX_is_FpX(GEN z, GEN *p), z a t_POL , checks if it can be mapped to a FpX , by checking Rg_is_Fp coefficientwise.

GEN RgX_to_FpX(GEN z, GEN p), z a t_POL , returns the FpX obtained by applying Rg_to_Fp coefficientwise.

GEN FpX_red(GEN z, GEN p), z a ZX , returns $\text{lift}(z * \text{Mod}(1, p))$, normalized.

GEN FpXV_red(GEN z, GEN p), z a t_VEC of ZX . Applies FpX_red componentwise and returns the result (and we obtain a vector of FpX s).

GEN FpXT_red(GEN z, GEN p), z a tree of ZX . Applies FpX_red to each leaf and returns the result (and we obtain a tree of FpX s).

7.3.6.2 Basic operations. In what follows p is always a $\mathbf{t_INT}$, not necessarily prime.

Now, except for p , the operands and outputs are all \mathbf{FpX} objects. Results are undefined on other inputs.

$\mathbf{GEN\ FpX_add}(\mathbf{GEN\ x}, \mathbf{GEN\ y}, \mathbf{GEN\ p})$ adds x and y .

$\mathbf{GEN\ FpX_neg}(\mathbf{GEN\ x}, \mathbf{GEN\ p})$ returns $-x$, the components are between 0 and p if this is the case for the components of x .

$\mathbf{GEN\ FpX_renormalize}(\mathbf{GEN\ x}, \mathbf{long\ l})$, as $\mathbf{normalizepol}$, where $l = \lg(x)$, in place.

$\mathbf{GEN\ FpX_sub}(\mathbf{GEN\ x}, \mathbf{GEN\ y}, \mathbf{GEN\ p})$ returns $x - y$.

$\mathbf{GEN\ FpX_halve}(\mathbf{GEN\ x}, \mathbf{GEN\ p})$ returns z such that $2z = x$ modulo p assuming such z exists.

$\mathbf{GEN\ FpX_mul}(\mathbf{GEN\ x}, \mathbf{GEN\ y}, \mathbf{GEN\ p})$ returns xy .

$\mathbf{GEN\ FpX_mulspec}(\mathbf{GEN\ a}, \mathbf{GEN\ b}, \mathbf{GEN\ p}, \mathbf{long\ na}, \mathbf{long\ nb})$ see $\mathbf{ZX_mulspec}$

$\mathbf{GEN\ FpX_sqr}(\mathbf{GEN\ x}, \mathbf{GEN\ p})$ returns x^2 .

$\mathbf{GEN\ FpX_powu}(\mathbf{GEN\ x}, \mathbf{ulong\ n}, \mathbf{GEN\ p})$ returns x^n .

$\mathbf{GEN\ FpX_convol}(\mathbf{GEN\ x}, \mathbf{GEN\ y}, \mathbf{GEN\ p})$ return the-term by-term product of x and y .

$\mathbf{GEN\ FpX_divrem}(\mathbf{GEN\ x}, \mathbf{GEN\ y}, \mathbf{GEN\ p}, \mathbf{GEN\ *pr})$ returns the quotient of x by y , and sets \mathbf{pr} to the remainder.

$\mathbf{GEN\ FpX_div}(\mathbf{GEN\ x}, \mathbf{GEN\ y}, \mathbf{GEN\ p})$ returns the quotient of x by y .

$\mathbf{GEN\ FpX_div_by_X_x}(\mathbf{GEN\ A}, \mathbf{GEN\ a}, \mathbf{GEN\ p}, \mathbf{GEN\ *r})$ returns the quotient of the \mathbf{FpX} A by $(X - a)$, and sets \mathbf{r} to the remainder $A(a)$.

$\mathbf{GEN\ FpX_rem}(\mathbf{GEN\ x}, \mathbf{GEN\ y}, \mathbf{GEN\ p})$ returns the remainder $x \bmod y$.

$\mathbf{long\ FpX_valrem}(\mathbf{GEN\ x}, \mathbf{GEN\ t}, \mathbf{GEN\ p}, \mathbf{GEN\ *r})$ The arguments x and e being nonzero \mathbf{FpX} returns the highest exponent e such that \mathbf{t}^e divides x . The quotient x/\mathbf{t}^e is returned in $\mathbf{*r}$. In particular, if \mathbf{t} is irreducible, this returns the valuation at \mathbf{t} of x , and $\mathbf{*r}$ is the prime-to- \mathbf{t} part of x .

$\mathbf{GEN\ FpX_deriv}(\mathbf{GEN\ x}, \mathbf{GEN\ p})$ returns the derivative of x . This function is not memory-clean, but nevertheless suitable for $\mathbf{gerepileupto}$.

$\mathbf{GEN\ FpX_integ}(\mathbf{GEN\ x}, \mathbf{GEN\ p})$ returns the primitive of x whose constant term is 0.

$\mathbf{GEN\ FpX_digits}(\mathbf{GEN\ x}, \mathbf{GEN\ B}, \mathbf{GEN\ p})$ returns a vector of \mathbf{FpX} $[c_0, \dots, c_n]$ of degree less than the degree of B and such that $x = \sum_{i=0}^n c_i B^i$.

$\mathbf{GEN\ FpXV_FpX_fromdigits}(\mathbf{GEN\ v}, \mathbf{GEN\ B}, \mathbf{GEN\ p})$ where $v = [c_0, \dots, c_n]$ is a vector of \mathbf{FpX} , returns $\sum_{i=0}^n c_i B^i$.

$\mathbf{GEN\ FpX_translate}(\mathbf{GEN\ P}, \mathbf{GEN\ c}, \mathbf{GEN\ p})$ let c be an \mathbf{Fp} and let P be an \mathbf{FpX} ; returns the translated \mathbf{FpX} of $P(X + c)$.

$\mathbf{GEN\ FpX_gcd}(\mathbf{GEN\ x}, \mathbf{GEN\ y}, \mathbf{GEN\ p})$ returns a (not necessarily monic) greatest common divisor of x and y .

$\mathbf{GEN\ FpX_halfgcd}(\mathbf{GEN\ x}, \mathbf{GEN\ y}, \mathbf{GEN\ p})$ returns a two-by-two \mathbf{FpXM} M with determinant ± 1 such that the image (a, b) of (x, y) by M has the property that $\deg a \geq \frac{\deg x}{2} > \deg b$.

GEN FpX_halfgcd_all(GEN x, GEN y, GEN p, GEN *pt_a, GEN *pt_b) as FpX_halfgcd, in addition, if pt_a (resp. pt_b) is not NULL, *pt_a (resp. *pt_b) is set to a (resp. b).

GEN FpX_extgcd(GEN x, GEN y, GEN p, GEN *u, GEN *v) returns $d = \text{GCD}(x, y)$ (not necessarily monic), and sets *u, *v to the Bezout coefficients such that $*ux + *vy = d$. If u is NULL, *u is not computed which is a bit faster. This is useful when computing the inverse of y modulo x .

GEN FpX_center(GEN z, GEN p, GEN pov2) returns the polynomial whose coefficient belong to the symmetric residue system. Assumes the coefficients already belong to $] -p/2, p[$ and that pov2 is shifti(p, -1).

GEN FpX_center_i(GEN z, GEN p, GEN pov2) internal variant of FpX_center, not gerepile-safe.

GEN FpX_Frobenius(GEN T, GEN p) returns $X^p \pmod{T(X)}$.

GEN FpX_matFrobenius(GEN T, GEN p) returns the matrix of the Frobenius automorphism $x \mapsto x^p$ over the power basis of $\mathbf{F}_p[X]/(T)$.

7.3.6.3 Mixed operations. The following functions implement arithmetic operations between FpX and Fp operands, the result being of type FpX. The integer p need not be prime.

GEN Z_to_FpX(GEN x, GEN p, long v) converts a t_INT to a scalar polynomial in variable v , reduced modulo p .

GEN FpX_Fp_add(GEN y, GEN x, GEN p) add the Fp x to the FpX y.

GEN FpX_Fp_add_shallow(GEN y, GEN x, GEN p) add the Fp x to the FpX y, using a shallow copy (result not suitable for gerepileupto)

GEN FpX_Fp_sub(GEN y, GEN x, GEN p) subtract the Fp x from the FpX y.

GEN FpX_Fp_sub_shallow(GEN y, GEN x, GEN p) subtract the Fp x from the FpX y, using a shallow copy (result not suitable for gerepileupto)

GEN Fp_FpX_sub(GEN x, GEN y, GEN p) returns $x - y$, where x is a t_INT and y an FpX.

GEN FpX_Fp_mul(GEN x, GEN y, GEN p) multiplies the FpX x by the Fp y.

GEN FpX_Fp_mulspec(GEN x, GEN y, GEN p, long lx) see ZX_mulspec

GEN FpX_mulu(GEN x, ulong y, GEN p) multiplies the FpX x by y.

GEN FpX_Fp_mul_to_monic(GEN y, GEN x, GEN p) returns yx assuming the result is monic of the same degree as y (in particular $x \neq 0$).

GEN FpX_Fp_div(GEN x, GEN y, GEN p) divides the FpX x by the Fp y.

GEN FpX_divu(GEN x, ulong y, GEN p) divides the FpX x by y.

7.3.6.4 Miscellaneous operations.

GEN FpX_normalize(GEN z, GEN p) divides the FpX z by its leading coefficient. If the latter is 1, z itself is returned, not a copy. If not, the inverse remains uncollected on the stack.

GEN FpX_invBarrett(GEN T, GEN p), returns the Barrett inverse M of T defined by $M(x)x^n \times T(1/x) \equiv 1 \pmod{x^{n-1}}$ where n is the degree of T .

GEN FpX_rescale(GEN P, GEN h, GEN p) returns $h^{\deg(P)}P(x/h)$. P is an FpX and h is a nonzero Fp (the routine would work with any nonzero t_INT but is not efficient in this case). Neither memory-clean nor suitable for gerepileupto.

GEN FpX_eval(GEN x, GEN y, GEN p) evaluates the FpX x at the Fp y. The result is an Fp.

GEN FpX_FpV_multieval(GEN P, GEN v, GEN p) returns the vector $[P(v[1]), \dots, P(v[n])]$ as a FpV.

GEN FpX_dotproduct(GEN x, GEN y, GEN p) return the scalar product $\sum_{i \geq 0} x_i y_i$ of the coefficients of x and y .

GEN FpXV_FpC_mul(GEN V, GEN W, GEN p) multiplies a nonempty row vector of FpX by a column vector of Fp of compatible dimensions. The result is an FpX.

GEN FpXV_prod(GEN V, GEN p), V being a vector of FpX, returns their product.

GEN FpXV_composedsum(GEN V, GEN p), V being a vector of FpX, returns their composed sum, see FpX_composedsum.

GEN FpXV_factorback(GEN L, GEN e, GEN p, long v) returns $\prod_i L_i^{e_i}$ where L is a vector of FpXs in the variable v and e a vector of non-negative t_INTs or a t_VECSMALL.

GEN FpV_roots_to_pol(GEN V, GEN p, long v), V being a vector of INTs, returns the monic FpX $\prod_i (\text{pol_x}[v] - V[i])$.

GEN FpX_chinese_coprime(GEN x, GEN y, GEN Tx, GEN Ty, GEN Tz, GEN p): returns an FpX, congruent to $x \pmod{Tx}$ and to $y \pmod{Ty}$. Assumes Tx and Ty are coprime, and $Tz = Tx * Ty$ or NULL (in which case it is computed within).

GEN FpV_polint(GEN x, GEN y, GEN p, long v) returns the FpX interpolation polynomial with value $y[i]$ at $x[i]$. Assumes lengths are the same, components are t_INTs, and the $x[i]$ are distinct modulo p .

GEN FpV_FpM_polint(GEN x, GEN V, GEN p, long v) equivalent (but faster) to applying FpV_polint(x,...) to all the elements of the vector V (thus, returns a FpXV).

GEN FpX_FpXV_multirem(GEN A, GEN P, GEN p) given a FpX A and a vector P of pairwise coprime FpX of length $n \geq 1$, return a vector B of the same length such that $B[i] = A \pmod{P[i]}$ and $B[i]$ of minimal degree for all $1 \leq i \leq n$.

GEN FpXV_chinese(GEN A, GEN P, GEN p, GEN *pM) let P be a vector of pairwise coprime FpX, let A be a vector of FpX of the same length $n \geq 1$ and let M be the product of the elements of P . Returns a FpX of minimal degree congruent to $A[i] \pmod{P[i]}$ for all $1 \leq i \leq n$. If pM is not NULL, set $*pM$ to M .

GEN FpV_invVandermonde(GEN L, GEN d, GEN p) L being a FpV of length n , return the inverse M of the Vandermonde matrix attached to the elements of L , eventually multiplied by d if it is not NULL. If A is a FpV and $B = MA$, then the polynomial $P = \sum_{i=1}^n B[i]X^{i-1}$ verifies $P(L[i]) = dA[i]$ for $1 \leq i \leq n$.

`int FpX_is_squarefree(GEN f, GEN p)` returns 1 if the FpX f is squarefree, 0 otherwise.

`int FpX_is_irred(GEN f, GEN p)` returns 1 if the FpX f is irreducible, 0 otherwise. Assumes that p is prime. If f has few factors, `FpX_nbfact(f, p) == 1` is much faster.

`int FpX_is_totally_split(GEN f, GEN p)` returns 1 if the FpX f splits into a product of distinct linear factors, 0 otherwise. Assumes that p is prime. The 0 polynomial is not totally split.

`long FpX_ispower(GEN f, ulong k, GEN p, GEN *pt)` return 1 if the FpX f is a k -th power, 0 otherwise. If pt is not NULL, set it to g such that $g^k = f$.

`GEN FpX_factor(GEN f, GEN p)`, factors the FpX f . Assumes that p is prime. The returned value v is a `t_VEC` with two components: $v[1]$ is a vector of distinct irreducible (FpX) factors, and $v[2]$ is a `t_VECSMALL` of corresponding exponents. The order of the factors is deterministic (the computation is not).

`GEN FpX_factor_squarefree(GEN f, GEN p)` returns the squarefree factorization of f modulo p . This is a vector $[u_1, \dots, u_k]$ of squarefree and pairwise coprime FpX such that $u_k \neq 1$ and $f = \prod u_i^i$. The other u_i may equal 1. Shallow function.

`GEN FpX_ddf(GEN f, GEN p)` assuming that f is squarefree, returns the distinct degree factorization of f modulo p . The returned value v is a `t_VEC` with two components: $F=v[1]$ is a vector of (FpX) factors, and $E=v[2]$ is a `t_VECSMALL`, such that f is equal to the product of the $F[i]$ and each $F[i]$ is a product of irreducible factors of degree $E[i]$.

`long FpX_ddf_degree(GEN f, GEN XP, GEN p)` assuming that f is squarefree and that all its factors have the same degree, return the common degree, where XP is `FpX_Frobenius(f, p)`.

`long FpX_nbfact(GEN f, GEN p)`, assuming the FpX f is squarefree, returns the number of its irreducible factors. Assumes that p is prime.

`long FpX_nbfact_Frobenius(GEN f, GEN XP, GEN p)`, as `FpX_nbfact(f, p)` but faster, where XP is `FpX_Frobenius(f, p)`.

`GEN FpX_degfact(GEN f, GEN p)`, as `FpX_factor`, but the degrees of the irreducible factors are returned instead of the factors themselves (as a `t_VECSMALL`). Assumes that p is prime.

`long FpX_nbroots(GEN f, GEN p)` returns the number of distinct roots in $\mathbf{Z}/p\mathbf{Z}$ of the FpX f . Assumes that p is prime.

`GEN FpX_oneroot(GEN f, GEN p)` returns one root in $\mathbf{Z}/p\mathbf{Z}$ of the FpX f . Return NULL if no root exists. Assumes that p is prime.

`GEN FpX_oneroot_split(GEN f, GEN p)` as `FpX_oneroot`. Faster when f is close to be totally split.

`GEN FpX_roots(GEN f, GEN p)` returns the roots in $\mathbf{Z}/p\mathbf{Z}$ of the FpX f (without multiplicity, as a vector of Fps). Assumes that p is prime.

`GEN FpX_roots_mult(GEN f, long n, GEN p)` returns the roots in $\mathbf{Z}/p\mathbf{Z}$ with multiplicity at least n of the FpX f (without multiplicity, as a vector of Fps). Assumes that p is prime.

`GEN FpX_split_part(GEN f, GEN p)` returns the largest totally split squarefree factor of f .

`GEN FpX_factcyclo(ulong n, GEN p, ulong m)` returns the factors of the n -th cyclotomic polynomial over Fp. if $m = 1$ returns a single factor.

GEN random_FpX(long d, long v, GEN p) returns a random FpX in variable v, of degree less than d.

GEN FpX_resultant(GEN x, GEN y, GEN p) returns the resultant of x and y, both FpX. The result is a t_INT belonging to $[0, p-1]$.

GEN FpX_disc(GEN x, GEN p) returns the discriminant of the FpX x. The result is a t_INT belonging to $[0, p-1]$.

GEN FpX_FpXY_resultant(GEN a, GEN b, GEN p), a a t_POL of t_INTs (say in variable X), b a t_POL (say in variable Y) whose coefficients are either t_POLs in $\mathbf{Z}[Y]$ or t_INTs. Returns $\text{Res}_X(a, b)$ in $\mathbf{F}_p[Y]$ as an FpY. The function assumes that X has lower priority than Y.

ulong FpX_extresultant(GEN a, GEN b, GEN p, GEN *ptU, GEN *ptV) given two FpX a and b, returns their resultant and sets Bezout coefficients (if the resultant is 0, the latter are not set). Assumes that p is prime.

GEN FpX_composedprod(GEN P, GEN Q, GEN p) if $P = a \prod_{i=1}^m (x - p_i)$ and $Q = b \prod_{j=1}^n (x - q_j)$ in some suitable algebraic extension, return $a^n b^m \prod_{i,j} (x - p_i q_j)$.

GEN FpX_composedsum(GEN P, GEN Q, GEN p) if $P = a \prod_{i=1}^m (x - p_i)$ and $Q = b \prod_{j=1}^n (x - q_j)$ in some suitable algebraic extension, return $a^n b^m \prod_{i,j} (x - (p_i + q_j))$.

GEN FpX_Newton(GEN x, long n, GEN p) return $\sum i = 0^{n-1} \pi_i X^i$ where π_i is the sum of the i th-power of the roots of x in an algebraic closure.

GEN FpX_fromNewton(GEN x, GEN p) recover a polynomial from its Newton sums given by the coefficients of x . This function assumes that p and the accuracy of x as a FpXn is larger than the degree of the solution.

GEN FpX_Laplace(GEN x, GEN p) return $\sum_{i=0}^{n-1} x_i i! X^i$.

GEN FpX_invLaplace(GEN x, GEN p) return $\sum_{i=0}^{n-1} x_i / i! X^i$.

7.3.7 FpXQ, Fq. Let p a t_INT and T an FpX for p, both to be given in the function arguments; an FpXQ object is an FpX whose degree is strictly less than the degree of T. An Fq is either an FpXQ or an Fp. Both represent a class in $(\mathbf{Z}/p\mathbf{Z}[X])/(T)$, in which all operations below take place. In addition, Fq routines also allow T = NULL, in which case no reduction mod T is performed on the result.

For efficiency, the routines in this section may leave small unused objects behind on the stack (their output is still suitable for gerepileupto). Besides T and p, arguments are either FpXQ or Fq depending on the function name. (All Fq routines accept FpXQs by definition, not the other way round.)

7.3.7.1 Preconditioned reduction.

For faster reduction, the modulus T can be replaced by an extended modulus in all FpXQ- and Fq-classes functions, and in FpX_rem and FpX_divrem. An extended modulus(FpXT, which is a tree whose leaves are FpX) In current implementation, an extended modulus is either a plain modulus (an FpX) or a pair of polynomials, one being the plain modulus T and the other being FpX_invBarret(T, p).

GEN FpX_get_red(GEN T, GEN p) returns the extended modulus eT.

To write code that works both with plain and extended moduli, the following accessors are defined:

GEN `get_FpX_mod`(GEN `eT`) returns the underlying modulus T .

GEN `get_FpX_var`(GEN `eT`) returns the variable number `varn`(T).

GEN `get_FpX_degree`(GEN `eT`) returns the degree `degpol`(T).

7.3.7.2 Conversions.

int `ff_parse_Tp`(GEN `Tp`, GEN `*T`, GEN `*p`, long `red`) `Tp` is either a prime number p or a `t_VEC` with 2 entries T (an irreducible polynomial mod p) and p (a prime number). Sets `*p` and `*T` to the corresponding GENs (NULL if undefined). If `red` is nonzero, normalize `*T` as an `FpX`; on the other hand, to initialize a p -adic function, set `red` to 0 and `*T` is left as is and must be a `ZX` to start with. Return 1 on success, and 0 on failure. This helper routine is used by GP functions such as `factormod` where a single user argument defines a finite field. `t_FFELT` is not supported.

GEN `Rg_is_FpXQ`(GEN `z`, GEN `*T`, GEN `*p`), checks if `z` is a GEN which can be mapped to $\mathbf{F}_p[X]/(T)$: anything for which `Rg_is_Fp` return 1, a `t_POL` for which `RgX_to_FpX` return 1, a `t_POLMOD` whose modulus is equal to `*T` if `*T` is not NULL (once mapped to a `FpX`), or a `t_FFELT` `z` with the same definition field as `*T` if `*T` is not NULL and is a `t_FFELT`.

If an integer modulus is found it is put in `*p`, else `*p` is left unchanged. If a polynomial modulus is found it is put in `*T`, if a `t_FFELT` `z` is found, `z` is put in `*T`, else `*T` is left unchanged.

int `RgX_is_FpXQX`(GEN `z`, GEN `*T`, GEN `*p`), `z` a `t_POL`, checks if it can be mapped to a `FpXQX`, by checking `Rg_is_FpXQ` coefficientwise.

GEN `Rg_to_FpXQ`(GEN `z`, GEN `T`, GEN `p`), `z` a GEN which can be mapped to $\mathbf{F}_p[X]/(T)$: anything `Rg_to_Fp` can be applied to, a `t_POL` to which `RgX_to_FpX` can be applied to, a `t_POLMOD` whose modulus is divisible by T (once mapped to a `FpX`), a suitable `t_RFRAC`. Returns `z` as an `FpXQ`, normalized.

GEN `Rg_to_Fq`(GEN `z`, GEN `T`, GEN `p`), applies `Rg_to_Fp` if T is NULL and `Rg_to_FpXQ` otherwise.

GEN `RgX_to_FpXQX`(GEN `z`, GEN `T`, GEN `p`), `z` a `t_POL`, returns the `FpXQ` obtained by applying `Rg_to_FpXQ` coefficientwise.

GEN `RgX_to_FqX`(GEN `z`, GEN `T`, GEN `p`): let `z` be a `t_POL`; returns the `FqX` obtained by applying `Rg_to_Fq` coefficientwise.

GEN `Fq_to_FpXQ`(GEN `z`, GEN `T`, GEN `p` /*unused*/) if `z` is a `t_INT`, convert it to a constant polynomial in the variable of T , otherwise return `z` (shallow function).

GEN `Fq_red`(GEN `x`, GEN `T`, GEN `p`), `x` a `ZX` or `t_INT`, reduce it to an `Fq` ($T = \text{NULL}$ is allowed iff `x` is a `t_INT`).

GEN `FqX_red`(GEN `x`, GEN `T`, GEN `p`), `x` a `t_POL` whose coefficients are `ZXs` or `t_INTs`, reduce them to `Fqs`. (If $T = \text{NULL}$, as `FpXX_red`(`x`, `p`).)

GEN `FqV_red`(GEN `x`, GEN `T`, GEN `p`), `x` a vector of `ZXs` or `t_INTs`, reduce them to `Fqs`. (If $T = \text{NULL}$, only reduce components mod `p` to `FpXs` or `Fps`.)

GEN `FpXQ_red`(GEN `x`, GEN `T`, GEN `p`) `x` a `t_POL` whose coefficients are `t_INTs`, reduce them to `FpXQs`.

7.3.8 FpXQ.

GEN FpXQ_add(GEN x, GEN y, GEN T, GEN p)

GEN FpXQ_sub(GEN x, GEN y, GEN T, GEN p)

GEN FpXQ_mul(GEN x, GEN y, GEN T, GEN p)

GEN FpXQ_sqr(GEN x, GEN T, GEN p)

GEN FpXQ_div(GEN x, GEN y, GEN T, GEN p)

GEN FpXQ_inv(GEN x, GEN T, GEN p) computes the inverse of x

GEN FpXQ_invsafe(GEN x, GEN T, GEN p), as FpXQ_inv, returning NULL if x is not invertible.

GEN FpXQ_pow(GEN x, GEN n, GEN T, GEN p) computes x^n .

GEN FpXQ_powu(GEN x, ulong n, GEN T, GEN p) computes x^n for small n .

In the following three functions the integer parameter `ord` can be given either as a positive `t_INT N`, or as its factorization matrix faN , or as a pair $[N, faN]$. The parameter may be omitted by setting it to NULL (the value is then $p^d - 1$, $d = \deg T$).

GEN FpXQ_log(GEN a, GEN g, GEN ord, GEN T, GEN p) Let g be of order dividing `ord` in the finite field $\mathbf{F}_p[X]/(T)$, return e such that $a^e = g$. If e does not exist, the result is undefined. Assumes that T is irreducible mod p .

GEN Fp_FpXQ_log(GEN a, GEN g, GEN ord, GEN T, GEN p) As FpXQ_log, a being a Fp.

GEN FpXQ_order(GEN a, GEN ord, GEN T, GEN p) returns the order of the FpXQ a . Assume that `ord` is a multiple of the order of a . Assume that T is irreducible mod p .

int FpXQ_issquare(GEN x, GEN T, GEN p) returns 1 if x is a square and 0 otherwise. Assumes that T is irreducible mod p .

GEN FpXQ_sqrt(GEN x, GEN T, GEN p) returns a square root of x . Return NULL if x is not a square.

GEN FpXQ_sqrtn(GEN x, GEN n, GEN T, GEN p, GEN *zn) Let T be irreducible mod p and $q = p^{\deg T}$; returns NULL if a is not an n -th power residue mod p . Otherwise, returns an n -th root of a ; if `zn` is not NULL set it to a primitive m -th root of 1 in \mathbf{F}_q , $m = \gcd(q - 1, n)$ allowing to compute all m solutions in \mathbf{F}_q of the equation $x^n = a$.

7.3.9 Fq.

GEN random_Fq(GEN T, GEN p) returns a random Fq

GEN Fq_add(GEN x, GEN y, GEN T/*unused*/, GEN p)

GEN Fq_sub(GEN x, GEN y, GEN T/*unused*/, GEN p)

GEN Fq_mul(GEN x, GEN y, GEN T, GEN p)

GEN Fq_Fp_mul(GEN x, GEN y, GEN T, GEN p) multiplies the Fq x by the `t_INT` y .

GEN Fq_mulu(GEN x, ulong y, GEN T, GEN p) multiplies the Fq x by the scalar y .

GEN Fq_half(GEN x, GEN T, GEN p) returns z such that $2z = x$ assuming such z exists.

GEN Fq_sqr(GEN x, GEN T, GEN p)

`GEN Fq_neg(GEN x, GEN T, GEN p)`
`GEN Fq_neg_inv(GEN x, GEN T, GEN p)` computes $-x^{-1}$
`GEN Fq_inv(GEN x, GEN pol, GEN p)` computes x^{-1} , raising an error if x is not invertible.
`GEN Fq_invsafe(GEN x, GEN pol, GEN p)` as `Fq_inv`, but returns NULL if x is not invertible.
`GEN Fq_div(GEN x, GEN y, GEN T, GEN p)`
`GEN FqV_inv(GEN x, GEN T, GEN p)` x being a vector of Fqs, return the vector of inverses of the $x[i]$. The routine uses Montgomery's trick, and involves a single inversion, plus $3(N - 1)$ multiplications for N entries. The routine is not stack-clean: $2N$ FpXQ are left on stack, besides the N in the result.
`GEN FqV_factorback(GEN L, GEN e, GEN T, GEN p)` given an FqV L and a ZV or zv e of the same length, return $\prod_i L_i^{e_i}$ modulo p .
`GEN Fq_pow(GEN x, GEN n, GEN pol, GEN p)` returns x^n .
`GEN Fq_powu(GEN x, ulong n, GEN pol, GEN p)` returns x^n for small n .
`GEN Fq_log(GEN a, GEN g, GEN ord, GEN T, GEN p)` as `Fp_log` or `FpXQ_log`.
`int Fq_issquare(GEN x, GEN T, GEN p)` returns 1 if x is a square and 0 otherwise. Assumes that T is irreducible mod p and that p is prime; $T = \text{NULL}$ is forbidden unless x is an Fp.
`long Fq_ispower(GEN x, GEN n, GEN T, GEN p)` returns 1 if x is a n -th power and 0 otherwise. Assumes that T is irreducible mod p and that p is prime; $T = \text{NULL}$ is forbidden unless x is an Fp.
`GEN Fq_sqrt(GEN x, GEN T, GEN p)` returns a square root of x . Return NULL if x is not a square.
`GEN Fq_sqrtn(GEN a, GEN n, GEN T, GEN p, GEN *zn)` as `FpXQ_sqrtn`.
`GEN FpXQ_charpoly(GEN x, GEN T, GEN p)` returns the characteristic polynomial of x
`GEN FpXQ_minpoly(GEN x, GEN T, GEN p)` returns the minimal polynomial of x
`GEN FpXQ_norm(GEN x, GEN T, GEN p)` returns the norm of x
`GEN FpXQ_trace(GEN x, GEN T, GEN p)` returns the trace of x
`GEN FpXQ_conjvec(GEN x, GEN T, GEN p)` returns the vector of conjugates $[x, x^p, x^{p^2}, \dots, x^{p^{n-1}}]$ where n is the degree of T .
`GEN gener_FpXQ(GEN T, GEN p, GEN *po)` returns a primitive root modulo (T, p) . T is an FpX assumed to be irreducible modulo the prime p . If po is not NULL it is set to $[o, fa]$, where o is the order of the multiplicative group of the finite field, and fa is its factorization.
`GEN gener_FpXQ_local(GEN T, GEN p, GEN L)`, L being a vector of primes dividing $p^{\deg T} - 1$, returns an element of $G := \mathbf{F}_p[x]/(T)$ which is a generator of the ℓ -Sylow of G for every ℓ in L . It is not necessary, and in fact slightly inefficient, to include $\ell = 2$, since 2 is treated separately in any case, i.e. the generator obtained is never a square if p is odd.
`GEN gener_Fq_local(GEN T, GEN p, GEN L)` as `pgener_Fp_local(p, L)` if T is NULL, or `gener_FpXQ_local` (otherwise).
`GEN FpXQ_powers(GEN x, long n, GEN T, GEN p)` returns $[x^0, \dots, x^n]$ as a `t_VEC` of FpXQs.
`GEN FpXQ_matrix_pow(GEN x, long m, long n, GEN T, GEN p)`, as `FpXQ_powers(x, n - 1, T, p)`, but returns the powers as a $m \times n$ matrix. Usually, we have $m = n = \deg T$.

`GEN FpXQ_autpow(GEN a, ulong n, GEN T, GEN p)` computes $\sigma^n(X)$ assuming $a = \sigma(X)$ where σ is an automorphism of the algebra $\mathbf{F}_p[X]/T(X)$.

`GEN FpXQ_autsum(GEN a, ulong n, GEN T, GEN p)` a being a two-component vector, σ being the automorphism defined by $\sigma(X) = a[1] \pmod{T(X)}$, returns the vector $[\sigma^n(X), b\sigma(b) \dots \sigma^{n-1}(b)]$ where $b = a[2]$.

`GEN FpXQ_auttrace(GEN a, ulong n, GEN T, GEN p)` a being a two-component vector, σ being the automorphism defined by $\sigma(X) = a[1] \pmod{T(X)}$, returns the vector $[\sigma^n(X), b + \sigma(b) + \dots + \sigma^{n-1}(b)]$ where $b = a[2]$.

`GEN FpXQ_outpowers(GEN S, long n, GEN T, GEN p)` returns $[x, S(x), S(S(x)), \dots, S^{(n)}(x)]$ as a `t_VEC` of `FpXQs`.

`GEN FpXQM_autsum(GEN a, long n, GEN T, GEN p)` σ being the automorphism defined by $\sigma(X) = a[1] \pmod{T(X)}$, returns the vector $[\sigma^n(X), b\sigma(b) \dots \sigma^{n-1}(b)]$ where $b = a[2]$ is a square matrix.

`GEN FpX_FpXQ_eval(GEN f, GEN x, GEN T, GEN p)` returns $f(x)$.

`GEN FpX_FpXQV_eval(GEN f, GEN V, GEN T, GEN p)` returns $f(x)$, assuming that V was computed by `FpXQ_powers(x, n, T, p)`.

`GEN FpXC_FpXQ_eval(GEN C, GEN x, GEN T, GEN p)` applies `FpX_FpXQV_eval` to all elements of the vector C and returns a `t_COL`.

`GEN FpXC_FpXQV_eval(GEN C, GEN V, GEN T, GEN p)` applies `FpX_FpXQV_eval` to all elements of the vector C and returns a `t_COL`.

`GEN FpXM_FpXQV_eval(GEN M, GEN V, GEN T, GEN p)` applies `FpX_FpXQV_eval` to all elements of the matrix M .

7.3.10 FpXn. Let p a `t_INT` and T an `FpX` for p , both to be given in the function arguments; an `FpXn` object is an `FpX` whose degree is strictly less than n . They represent a class in $(\mathbf{Z}/p\mathbf{Z})[X]/(X^n)$, in which all operations below take place. They can be seen as truncated power series.

`GEN FpXn_mul(GEN x, GEN y, long n, GEN p)` return $xy \pmod{X^n}$.

`GEN FpXn_sqr(GEN x, long n, GEN p)` return $x^2 \pmod{X^n}$.

`GEN FpXn_div(GEN x, GEN y, long n, GEN p)` return $x/y \pmod{X^n}$.

`GEN FpXn_inv(GEN x, long n, GEN p)` return $1/x \pmod{X^n}$.

`GEN FpXn_exp(GEN f, long n, GEN p)` return $\exp(f)$ as a composition of formal power series. It is required that the valuation of f is positive and that $p > n$.

`GEN FpXn_expint(GEN f, long n, GEN p)` return $\exp(F)$ where F is the primitive of f that vanishes at 0. It is required that $p > n$.

7.3.11 FpXC, FpXM.

`GEN FpXC_center(GEN C, GEN p, GEN pov2)`

`GEN FpXM_center(GEN M, GEN p, GEN pov2)`

7.3.12 FpXX, FpXY. Contrary to what the name implies, an FpXX is a t_POL whose coefficients are either t_INTs or FpXs. This reduces memory overhead at the expense of consistency. The prefix FpXY is an alias for FpXX when variables matters.

GEN FpXX_red(GEN z, GEN p), z a t_POL whose coefficients are either ZXs or t_INTs. Returns the t_POL equal to z with all components reduced modulo p.

GEN FpXX_renormalize(GEN x, long l), as normalizpol, where $l = \lg(x)$, in place.

GEN FpXX_add(GEN x, GEN y, GEN p) adds x and y.

GEN FpXX_sub(GEN x, GEN y, GEN p) returns $x - y$.

GEN FpXX_neg(GEN x, GEN p) returns $-x$.

GEN FpXX_Fp_mul(GEN x, GEN y, GEN p) multiplies the FpXX x by the Fp y.

GEN FpXX_FpX_mul(GEN x, GEN y, GEN p) multiplies the coefficients of the FpXX x by the FpX y.

GEN FpXX_mulu(GEN x, GEN y, GEN p) multiplies the FpXX x by the scalar y.

GEN FpXX_half(GEN x, GEN p) returns z such that $2z = x$ assuming such z exists.

GEN FpXX_deriv(GEN P, GEN p) differentiates P with respect to the main variable.

GEN FpXX_integ(GEN P, GEN p) returns the primitive of P with respect to the main variable whose constant term is 0.

GEN FpXY_eval(GEN Q, GEN y, GEN x, GEN p) Q being an FpXY, i.e. a t_POL with Fp or FpX coefficients representing an element of $\mathbf{F}_p[X][Y]$. Returns the Fp $Q(x, y)$.

GEN FpXY_evalx(GEN Q, GEN x, GEN p) Q being an FpXY, returns the FpX $Q(x, Y)$, where Y is the main variable of Q.

GEN FpXY_evaly(GEN Q, GEN y, GEN p, long vx) Q an FpXY, returns the FpX $Q(X, y)$, where X is the second variable of Q, and vx is the variable number of X.

GEN FpXY_FpXQ_evaly(GEN Q, GEN y, GEN T, GEN p, long vx) Q an FpXY and y being an FpXQ, returns the FpXQX $Q(X, y)$, where X is the second variable of Q, and vx is the variable number of X.

GEN FpXY_Fq_evaly(GEN Q, GEN y, GEN T, GEN p, long vx) Q an FpXY and y being an Fq, returns the FqX $Q(X, y)$, where X is the second variable of Q, and vx is the variable number of X.

GEN FpXY_FpXQ_evalx(GEN Q, GEN x, ulong p) Q an FpXY and x being an FpXQ, returns the FpXQX $Q(x, Y)$, where Y is the first variable of Q.

GEN FpXY_FpXQV_evalx(GEN Q, GEN V, ulong p) Q an FpXY and x being an FpXQ, returns the FpXQX $Q(x, Y)$, where Y is the first variable of Q, assuming that V was computed by FpXQ_powers(x, n, T, p).

GEN FpXYQQ_pow(GEN x, GEN n, GEN S, GEN T, GEN p), x being a FpXY, T being a FpX and S being a FpY, return $x^n \pmod{S, T, p}$.

7.3.13 FpXQX, FqX. Contrary to what the name implies, an FpXQX is a t_POL whose coefficients are Fqs. So the only difference between FqX and FpXQX routines is that $T = \text{NULL}$ is not allowed in the latter. (It was thought more useful to allow t_INT components than to enforce strict consistency, which would not imply any efficiency gain.)

7.3.13.1 Basic operations.

GEN FqX_add(GEN x, GEN y, GEN T, GEN p)

GEN FqX_Fq_add(GEN x, GEN y, GEN T, GEN p) adds the Fq y to the FqX x.

GEN FqX_Fq_sub(GEN x, GEN y, GEN T, GEN p) subtracts the Fq y to the FqX x.

GEN FqX_neg(GEN x, GEN T, GEN p)

GEN FqX_sub(GEN x, GEN y, GEN T, GEN p)

GEN FqX_mul(GEN x, GEN y, GEN T, GEN p)

GEN FqX_Fq_mul(GEN x, GEN y, GEN T, GEN p) multiplies the FqX x by the Fq y.

GEN FqX_mulu(GEN x, ulong y, GEN T, GEN p) multiplies the FqX x by the scalar y.

GEN FqX_half(GEN x, GEN T, GEN p) returns z such that $2z = x$ assuming such z exists.

GEN FqX_Fp_mul(GEN x, GEN y, GEN T, GEN p) multiplies the FqX x by the t_INT y.

GEN FqX_Fq_mul_to_monic(GEN x, GEN y, GEN T, GEN p) returns xy assuming the result is monic of the same degree as x (in particular $y \neq 0$).

GEN FpXQX_normalize(GEN z, GEN T, GEN p)

GEN FqX_normalize(GEN z, GEN T, GEN p) divides the FqX z by its leading term. The leading coefficient becomes 1 as a t_INT .

GEN FqX_sqr(GEN x, GEN T, GEN p)

GEN FqX_powu(GEN x, ulong n, GEN T, GEN p)

GEN FqX_divrem(GEN x, GEN y, GEN T, GEN p, GEN *z)

GEN FqX_div(GEN x, GEN y, GEN T, GEN p)

GEN FqX_div_by_X_x(GEN a, GEN x, GEN T, GEN p, GEN *r)

GEN FqX_rem(GEN x, GEN y, GEN T, GEN p)

GEN FqX_deriv(GEN x, GEN T, GEN p) returns the derivative of x. (This function is suitable for gerepilupto but not memory-clean.)

GEN FqX_integ(GEN x, GEN T, GEN p) returns the primitive of x. whose constant term is 0.

GEN FqX_translate(GEN P, GEN c, GEN T, GEN p) let c be an Fq defined modulo (p, T) , and let P be an FqX; returns the translated FqX of $P(X + c)$.

GEN FqX_gcd(GEN P, GEN Q, GEN T, GEN p) returns a (not necessarily monic) greatest common divisor of x and y .

GEN FqX_extgcd(GEN x, GEN y, GEN T, GEN p, GEN *ptu, GEN *ptv) returns $d = \text{GCD}(x, y)$ (not necessarily monic), and sets $*u, *v$ to the Bezout coefficients such that $*ux + *vy = d$.

GEN FqX_halfgcd(GEN x, GEN y, GEN T, GEN p) returns a two-by-two FqXM M with determinant ± 1 such that the image (a, b) of (x, y) by M has the property that $\deg a \geq \frac{\deg x}{2} > \deg b$.

GEN FqX_eval(GEN x, GEN y, GEN T, GEN p) evaluates the FqX x at the Fq y. The result is an Fq.

GEN FqXY_eval(GEN Q, GEN y, GEN x, GEN T, GEN p) Q an FqXY, i.e. a t_POL with Fq or FqX coefficients representing an element of $\mathbf{F}_q[X][Y]$. Returns the Fq $Q(x, y)$.

GEN FqXY_evalx(GEN Q, GEN x, GEN T, GEN p) Q being an FqXY, returns the FqX $Q(x, Y)$, where Y is the main variable of Q.

GEN random_FpXQX(long d, long v, GEN T, GEN p) returns a random FpXQX in variable v, of degree less than d.

GEN FpXQX_renormalize(GEN x, long lx)

GEN FpXQX_red(GEN z, GEN T, GEN p) z a t_POL whose coefficients are ZXs or t_INTs, reduce them to FpXQs.

GEN FpXQXV_red(GEN z, GEN T, GEN p), z a t_VEC of ZXX. Applies FpX_red componentwise and returns the result (and we obtain a vector of FpXQXs).

GEN FpXQXT_red(GEN z, GEN T, GEN p), z a tree of ZXX. Applies FpX_red to each leaf and returns the result (and we obtain a tree of FpXQXs).

GEN FpXQX_mul(GEN x, GEN y, GEN T, GEN p)

GEN Kronecker_to_FpXQX(GEN z, GEN T, GEN p). Let $n = \deg T$ and let $P(X, Y) \in \mathbf{Z}[X, Y]$ lift a polynomial in $K[Y]$, where $K := \mathbf{F}_p[X]/(T)$ and $\deg_X P < 2n - 1$ — such as would result from multiplying minimal degree lifts of two polynomials in $K[Y]$. Let $z = P(t, t^{2n-1})$ be a Kronecker form of P (see RgXX_to_Kronecker), this function returns $Q \in \mathbf{Z}[X, t]$ such that Q is congruent to $P(X, t) \pmod{(p, T(X))}$, $\deg_X Q < n$, and all coefficients are in $[0, p[$. Not stack-clean. Note that t need not be the same variable as Y!

GEN FpXQX_FpXQ_mul(GEN x, GEN y, GEN T, GEN p)

GEN FpXQX_sqr(GEN x, GEN T, GEN p)

GEN FpXQX_divrem(GEN x, GEN y, GEN T, GEN p, GEN *pr)

GEN FpXQX_div(GEN x, GEN y, GEN T, GEN p)

GEN FpXQX_div_by_X_x(GEN a, GEN x, GEN T, GEN p, GEN *r)

GEN FpXQX_rem(GEN x, GEN y, GEN T, GEN p)

GEN FpXQX_powu(GEN x, ulong n, GEN T, GEN p) returns x^n .

GEN FpXQX_digits(GEN x, GEN B, GEN T, GEN p)

GEN FpXQX_dotproduct(GEN x, GEN y, GEN T, GEN p) returns the scalar product of the coefficients of x and y.

GEN FpXQXV_FpXQX_fromdigits(GEN v, GEN B, GEN T, GEN p)

GEN FpXQX_invBarrett(GEN y, GEN T, GEN p) returns the Barrett inverse of the FpXQX y, namely a lift of $1/\text{polrecip}(y) + O(x^{\deg(y)-1})$.

GEN FpXQXV_prod(GEN V, GEN T, GEN p), V being a vector of FpXQX, returns their product.

GEN FpXQX_gcd(GEN x, GEN y, GEN T, GEN p)

GEN FpXQX_extgcd(GEN x, GEN y, GEN T, GEN p, GEN *ptu, GEN *ptv)

`GEN FpXQX_halfgcd(GEN x, GEN y, GEN T, GEN p)`
`GEN FpXQX_halfgcd_all(GEN x, GEN y, GEN T, GEN p, GEN *ptu, GEN *ptv)`
`GEN FpXQX_resultant(GEN x, GEN y, GEN T, GEN p)` returns the resultant of x and y .
`GEN FpXQX_disc(GEN x, GEN T, GEN p)` returns the discriminant of x .
`GEN FpXQX_FpXQXQ_eval(GEN f, GEN x, GEN S, GEN T, GEN p)` returns $f(x)$.

7.3.14 FpXQXn, FqXn.

A `FpXQXn` is a `t_FpXQX` which represents an element of the ring $(Fp[X]/T(X))[Y]/(Y^n)$, where T is a `FpX`.

`GEN FpXQXn_sqr(GEN x, long n, GEN T, GEN p)`
`GEN FqXn_sqr(GEN x, long n, GEN T, GEN p)`
`GEN FpXQXn_mul(GEN x, GEN y, long n, GEN T, GEN p)`
`GEN FqXn_mul(GEN x, GEN y, long n, GEN T, GEN p)`
`GEN FpXQXn_div(GEN x, GEN y, long n, GEN T, GEN p)`
`GEN FpXQXn_inv(GEN x, long n, GEN T, GEN p)`
`GEN FqXn_inv(GEN x, long n, GEN T, GEN p)`
`GEN FpXQXn_exp(GEN x, long n, GEN T, GEN p)` return $\exp(x)$ as a composition of formal power series. It is required that the valuation of x is positive and that $p > n$.
`GEN FqXn_exp(GEN x, long n, GEN T, GEN p)`
`GEN FpXQXn_expint(GEN f, long n, GEN p)` return $\exp(F)$ where F is the primitive of f that vanishes at 0. It is required that $p > n$.
`GEN FqXn_expint(GEN x, long n, GEN T, GEN p)`

7.3.15 FpXQXQ, FqXQ.

A `FpXQXQ` is a `t_FpXQX` which represents an element of the ring $(Fp[X]/T(X))[Y]/S(X, Y)$, where T is a `FpX` and S a `FpXQX` modulo T . A `FqXQ` is identical except that T is allowed to be `NULL` in which case S must be a `FpX`.

7.3.15.1 Preconditioned reduction.

For faster reduction, the modulus S can be replaced by an extended modulus, which is an `FpXQXT`, in all `FpXQXQ`- and `FqXQ`-classes functions, and in `FpXQX_rem` and `FpXQX_divrem`.

`GEN FpXQX_get_red(GEN S, GEN T, GEN p)` returns the extended modulus `eS`.
`GEN FqX_get_red(GEN S, GEN T, GEN p)` identical, but allow T to be `NULL`, in which case it returns `FpX_get_red(S, p)`.

To write code that works both with plain and extended moduli, the following accessors are defined:

`GEN get_FpXQX_mod(GEN eS)` returns the underlying modulus S .
`GEN get_FpXQX_var(GEN eS)` returns the variable number of the modulus.
`GEN get_FpXQX_degree(GEN eS)` returns the degree of the modulus.

Furthermore, `ZXXT_to_FlxXT` allows to convert an extended modulus for a `FpXQX` to an extended modulus for the corresponding `FlxqX`.

7.3.15.2 basic operations.

GEN FpXQX_FpXQXQV_eval(GEN f, GEN V, GEN S, GEN T, GEN p) returns $f(x)$, assuming that V was computed by FpXQXQ_powers(x, n, S, T, p).

GEN FpXQXQ_div(GEN x, GEN y, GEN S, GEN T, GEN p), x, y and S being FpXQXs, returns $x * y^{-1}$ modulo S.

GEN FpXQXQ_inv(GEN x, GEN S, GEN T, GEN p), x and S being FpXQXs, returns x^{-1} modulo S.

GEN FpXQXQ_invsafe(GEN x, GEN S, GEN T, GEN p), as FpXQXQ_inv, returning NULL if x is not invertible.

GEN FpXQXQ_mul(GEN x, GEN y, GEN S, GEN T, GEN p), x, y and S being FpXQXs, returns xy modulo S.

GEN FpXQXQ_sqr(GEN x, GEN S, GEN T, GEN p), x and S being FpXQXs, returns x^2 modulo S.

GEN FpXQXQ_pow(GEN x, GEN n, GEN S, GEN T, GEN p), x and S being FpXQXs, returns x^n modulo S.

GEN FpXQXQ_powers(GEN x, long n, GEN S, GEN T, GEN p), x and S being FpXQXs, returns $[x^0, \dots, x^n]$ as a t_VEC of FpXQXs.

GEN FpXQXQ_halfFrobenius(GEN A, GEN S, GEN T, GEN p) returns $A(X)^{(q-1)/2} \pmod{S(X)}$ over the finite field \mathbf{F}_q defined by T and p, thus $q = p^n$ where n is the degree of T.

GEN FpXQXQ_minpoly(GEN x, GEN S, GEN T, GEN p), as FpXQ_minpoly

GEN FpXQXQ_matrix_pow(GEN x, long m, long n, GEN S, GEN T, GEN p) returns the same powers of x as FpXQXQ_powers(x, n - 1, S, T, p), but as an $m \times n$ matrix.

GEN FpXQXQ_autpow(GEN a, long n, GEN S, GEN T, GEN p) σ being the automorphism defined by $\sigma(X) = a[1] \pmod{T(X)}$, $\sigma(Y) = a[2] \pmod{S(X, Y), T(X)}$, returns $[\sigma^n(X), \sigma^n(Y)]$.

GEN FpXQXQ_autsum(GEN a, long n, GEN S, GEN T, GEN p) σ being the automorphism defined by $\sigma(X) = a[1] \pmod{T(X)}$, $\sigma(Y) = a[2] \pmod{S(X, Y), T(X)}$, returns the vector $[\sigma^n(X), \sigma^n(Y), b\sigma(b) \dots \sigma^{n-1}(b)]$ where $b = a[3]$.

GEN FpXQXQ_auttrace(GEN a, long n, GEN S, GEN T, GEN p) σ being the automorphism defined by $\sigma(X) = X \pmod{T(X)}$, $\sigma(Y) = a[1] \pmod{S(X, Y), T(X)}$, returns the vector $[\sigma^n(X), \sigma^n(Y), b + \sigma(b) + \dots + \sigma^{n-1}(b)]$ where $b = a[2]$.

GEN FqXQ_add(GEN x, GEN y, GEN S, GEN T, GEN p), x, y and S being FqXs, returns $x + y$ modulo S.

GEN FqXQ_sub(GEN x, GEN y, GEN S, GEN T, GEN p), x, y and S being FqXs, returns $x - y$ modulo S.

GEN FqXQ_mul(GEN x, GEN y, GEN S, GEN T, GEN p), x, y and S being FqXs, returns xy modulo S.

GEN FqXQ_div(GEN x, GEN y, GEN S, GEN T, GEN p), x and S being FqXs, returns x/y modulo S.

GEN FqXQ_inv(GEN x, GEN S, GEN T, GEN p), x and S being FqXs, returns x^{-1} modulo S.

GEN FqXQ_invsafe(GEN x, GEN S, GEN T, GEN p), as FqXQ_inv, returning NULL if x is not invertible.

GEN FqXQ_sqr(GEN x, GEN S, GEN T, GEN p), x and S being FqXs, returns x^2 modulo S.

GEN FqXQ_pow(GEN x, GEN n, GEN S, GEN T, GEN p), x and S being FqXs, returns x^n modulo S.

GEN FqXQ_powers(GEN x, long n, GEN S, GEN T, GEN p), x and S being FqXs, returns $[x^0, \dots, x^n]$ as a t_VEC of FqXs.

GEN FqXQ_matrix_pow(GEN x, long m, long n, GEN S, GEN T, GEN p) returns the same powers of x as FqXQ_powers(x, n-1, S, T, p), but as an $m \times n$ matrix.

GEN FqV_roots_to_pol(GEN V, GEN T, GEN p, long v), V being a vector of Fqs, returns the monic FqX $\prod_i (\text{pol_x}[v] - V[i])$.

7.3.15.3 Miscellaneous operations.

GEN init_Fq(GEN p, long n, long v) returns an irreducible polynomial of degree $n > 0$ over \mathbf{F}_p , in variable v.

int FqX_is_squarefree(GEN P, GEN T, GEN p)

GEN FpXQX_roots(GEN f, GEN T, GEN p) return the roots of f in $\mathbf{F}_p[X]/(T)$. Assumes p is prime and T irreducible in $\mathbf{F}_p[X]$.

GEN FpXQX_roots_mult(GEN f, long n, GEN T, GEN p) returns the roots in $\mathbf{Z}/p\mathbf{Z}$ with multiplicity at least n of the FpXQX f (without multiplicity, as a vector of FpXQs). Assumes p is prime and T irreducible in $\mathbf{F}_p[X]$.

GEN FqX_roots(GEN f, GEN T, GEN p) same but allow T = NULL.

GEN FpXQX_factor(GEN f, GEN T, GEN p) same output convention as FpX_factor. Assumes p is prime and T irreducible in $\mathbf{F}_p[X]$.

GEN FqX_factor(GEN f, GEN T, GEN p) same but allow T = NULL.

GEN FpXQX_factor_squarefree(GEN f, GEN T, GEN p) squarefree factorization of f modulo (T, p) ; same output convention as FpX_factor_squarefree. Assumes p is prime and T irreducible in $\mathbf{F}_p[X]$.

GEN FqX_factor_squarefree(GEN f, GEN T, GEN p) same but allow T = NULL.

GEN FpXQX_ddf(GEN f, GEN T, GEN p) as FpX_ddf.

GEN FqX_ddf(GEN f, GEN T, GEN p) same but allow T = NULL.

long FpXQX_ddf_degree(GEN f, GEN XP, GEN T, GEN p), as FpX_ddf_degree.

GEN FpXQX_degfact(GEN f, GEN T, GEN p), as FpX_degfact.

GEN FqX_degfact(GEN f, GEN T, GEN p) same but allow T = NULL.

GEN FpXQX_split_part(GEN f, GEN T, GEN p) returns the largest totally split squarefree factor of f .

long FpXQX_ispower(GEN f, ulong k, GEN T, GEN p, GEN *pt) return 1 if the FpXQX f is a k -th power, 0 otherwise. If pt is not NULL, set it to g such that $g^k = f$.

long FqX_ispower(GEN f, ulong k, GEN T, GEN p, GEN *pt) same but allow T = NULL.

GEN FpX_factorff(GEN P, GEN T, GEN p). Assumes p prime and T irreducible in $\mathbf{F}_p[X]$. Factor the FpX P over the finite field $\mathbf{F}_p[Y]/(T(Y))$. See FpX_factorff_irred if P is known to be irreducible of \mathbf{F}_p .

`GEN FpX_rootsff(GEN P, GEN T, GEN p)`. Assumes p prime and T irreducible in $\mathbf{F}_p[X]$. Returns the roots of the $\mathbf{F}_p[X]$ P belonging to the finite field $\mathbf{F}_p[Y]/(T(Y))$.

`GEN FpX_factorff_irred(GEN P, GEN T, GEN p)`. Assumes p prime and T irreducible in $\mathbf{F}_p[X]$. Factors the *irreducible* $\mathbf{F}_p[X]$ P over the finite field $\mathbf{F}_p[Y]/(T(Y))$ and returns the vector of irreducible $\mathbf{F}_q[X]$ s factors (the exponents, being all equal to 1, are not included).

`GEN FpX_ffisom(GEN P, GEN Q, GEN p)`. Assumes p prime, P, Q are $\mathbf{Z}[X]$ s, both irreducible mod p , and $\deg(P) \mid \deg(Q)$. Outputs a monomorphism between $\mathbf{F}_p[X]/(P)$ and $\mathbf{F}_p[X]/(Q)$, as a polynomial R such that $Q \mid P(R)$ in $\mathbf{F}_p[X]$. If P and Q have the same degree, it is of course an isomorphism.

`void FpX_ffintersect(GEN P, GEN Q, long n, GEN p, GEN *SP, GEN *SQ, GEN MA, GEN MB)`
Assumes p is prime, P, Q are $\mathbf{Z}[X]$ s, both irreducible mod p , and n divides both the degree of P and Q . Compute SP and SQ such that the subfield of $\mathbf{F}_p[X]/(P)$ generated by SP and the subfield of $\mathbf{F}_p[X]/(Q)$ generated by SQ are isomorphic of degree n . The polynomials P and Q do not need to be of the same variable. If MA (resp. MB) is not `NULL`, it must be the matrix of the Frobenius map in $\mathbf{F}_p[X]/(P)$ (resp. $\mathbf{F}_p[X]/(Q)$).

`GEN FpXQ_ffisom_inv(GEN S, GEN T, GEN p)`. Assumes p is prime, T a $\mathbf{Z}[X]$, which is irreducible modulo p , S a $\mathbf{Z}[X]$ representing an automorphism of $\mathbf{F}_q := \mathbf{F}_p[X]/(T)$. ($S(X)$ is the image of X by the automorphism.) Returns the inverse automorphism of S , in the same format, i.e. an $\mathbf{F}_p[X]$ H such that $H(S) \equiv X$ modulo (T, p) .

`long FpXQX_nbfact(GEN S, GEN T, GEN p)` returns the number of irreducible factors of the polynomial S over the finite field \mathbf{F}_q defined by T and p .

`long FpXQX_nbfact_Frobenius(GEN S, GEN Xq, GEN T, GEN p)` as `FpXQX_nbfact` where Xq is `FpXQX_Frobenius(S, T, p)`.

`long FqX_nbfact(GEN S, GEN T, GEN p)` as above but accept $T=\text{NULL}$.

`long FpXQX_nbroots(GEN S, GEN T, GEN p)` returns the number of roots of the polynomial S over the finite field \mathbf{F}_q defined by T and p .

`long FqX_nbroots(GEN S, GEN T, GEN p)` as above but accept $T=\text{NULL}$.

`GEN FpXQX_Frobenius(GEN S, GEN T, GEN p)` returns $X^q \pmod{S(X)}$ over the finite field \mathbf{F}_q defined by T and p , thus $q = p^n$ where n is the degree of T .

7.3.16 Flx. Let p be an `ulong`, not assumed to be prime unless mentioned otherwise (e.g., all functions involving Euclidean divisions and factorizations), to be given the function arguments; an `Fl` is an `ulong` belonging to $[0, p - 1]$, an `Flx` z is a `t_VECSMALL` representing a polynomial with small integer coefficients. Specifically $z[0]$ is the usual codeword, $z[1] = \text{evalvarn}(v)$ for some variable v , then the coefficients by increasing degree. An `FlxX` is a `t_POL` whose coefficients are `Flxs`.

In the following, an argument called `sv` is of the form `evalvarn(v)` for some variable number v .

7.3.16.1 Preconditioned reduction.

For faster reduction, the modulus T can be replaced by an extended modulus ($\text{Flx}T$) in all Flxq -classes functions, and in Flx_divrem .

$\text{GEN Flx_get_red}(\text{GEN } T, \text{ulong } p)$ returns the extended modulus eT .

$\text{GEN Flx_get_red_pre}(\text{GEN } T, \text{ulong } p, \text{ulong } pi)$ as Flx_get_red . We assume pi is the pseudoinverse of p , or 0 in which case we assume $\text{SMALL_ULONG}(p)$.

To write code that works both with plain and extended moduli, the following accessors are defined:

$\text{GEN get_Flx_mod}(\text{GEN } eT)$ returns the underlying modulus T .

$\text{GEN get_Flx_var}(\text{GEN } eT)$ returns the variable number of the modulus.

$\text{GEN get_Flx_degree}(\text{GEN } eT)$ returns the degree of the modulus.

Furthermore, ZXT_to_FlxT allows to convert an extended modulus for a FpX to an extended modulus for the corresponding Flx .

7.3.16.2 Basic operations.

In this section, pi is the pseudoinverse of p , or 0 in which case we assume $\text{SMALL_ULONG}(p)$.

$\text{ulong Flx_lead}(\text{GEN } x)$ returns the leading coefficient of x as a ulong (return 0 for the zero polynomial).

$\text{ulong Flx_constant}(\text{GEN } x)$ returns the constant coefficient of x as a ulong (return 0 for the zero polynomial).

$\text{GEN Flx_red}(\text{GEN } z, \text{ulong } p)$ converts from zx with nonnegative coefficients to Flx (by reducing them mod p).

$\text{int Flx_equal1}(\text{GEN } x)$ returns 1 (true) if the $\text{Flx } x$ is equal to 1, 0 (false) otherwise.

$\text{int Flx_equal}(\text{GEN } x, \text{GEN } y)$ returns 1 (true) if the $\text{Flx } x$ and y are equal, and 0 (false) otherwise.

$\text{GEN Flx_copy}(\text{GEN } x)$ returns a copy of x .

$\text{GEN Flx_add}(\text{GEN } x, \text{GEN } y, \text{ulong } p)$

$\text{GEN Flx_Fl_add}(\text{GEN } y, \text{ulong } x, \text{ulong } p)$

$\text{GEN Flx_neg}(\text{GEN } x, \text{ulong } p)$

$\text{GEN Flx_neg_inplace}(\text{GEN } x, \text{ulong } p)$, same as Flx_neg , in place (x is destroyed).

$\text{GEN Flx_sub}(\text{GEN } x, \text{GEN } y, \text{ulong } p)$

$\text{GEN Flx_Fl_sub}(\text{GEN } y, \text{ulong } x, \text{ulong } p)$

$\text{GEN Flx_halve}(\text{GEN } x, \text{ulong } p)$ returns z such that $2z = x$ modulo p assuming such z exists.

$\text{GEN Flx_mul}(\text{GEN } x, \text{GEN } y, \text{ulong } p)$

$\text{GEN Flx_mul_pre}(\text{GEN } x, \text{GEN } y, \text{ulong } p, \text{ulong } pi)$

$\text{GEN Flx_Fl_mul}(\text{GEN } y, \text{ulong } x, \text{ulong } p)$

$\text{GEN Flx_Fl_mul_pre}(\text{GEN } y, \text{ulong } x, \text{ulong } p, \text{ulong } pi)$

GEN Flx_double(GEN y, ulong p) returns $2y$.
 GEN Flx_triple(GEN y, ulong p) returns $3y$.
 GEN Flx_mulu(GEN y, ulong x, ulong p) as Flx_Fl_mul but do not assume that $x < p$.
 GEN Flx_Fl_mul_to_monic(GEN y, ulong x, ulong p) returns yx assuming the result is monic of the same degree as y (in particular $x \neq 0$).
 GEN Flx_sqr(GEN x, ulong p)
 GEN Flx_sqr_pre(GEN x, ulong p, ulong pi)
 GEN Flx_powu(GEN x, ulong n, ulong p) return x^n .
 GEN Flx_powu_pre(GEN x, ulong n, ulong p, ulong pi)
 GEN Flx_convolution(GEN x, GEN y, ulong p) return the-term by-term product of x and y .
 GEN Flx_divrem(GEN x, GEN y, ulong p, GEN *pr), here p must be prime.
 GEN Flx_divrem_pre(GEN x, GEN y, ulong p, ulong pi, GEN *pr)
 GEN Flx_div(GEN x, GEN y, ulong p), here p must be prime.
 GEN Flx_div_pre(GEN x, GEN y, ulong p, ulong pi)
 GEN Flx_rem(GEN x, GEN y, ulong p), here p must be prime.
 GEN Flx_rem_pre(GEN x, GEN y, ulong p, ulong pi)
 GEN Flx_deriv(GEN z, ulong p)
 GEN Flx_integ(GEN z, ulong p), here p must be prime.
 GEN Flx_translate1(GEN P, ulong p) return $P(x+1)$, p must be prime. Asymptotically fast (quasi-linear in the degree of P).
 GEN Flx_translate1_basecase(GEN P, ulong p) return $P(x+1)$, p need not be prime. Not asymptotically fast (quadratic in the degree of P).
 GEN zlx_translate1(GEN P, ulong p, long e) return $P(x+1)$ modulo p^e for prime p . Asymptotically fast (quasi-linear in the degree of P).
 GEN Flx_diff1(GEN P, ulong p) return $P(x+1) - P(x)$; p must be prime.
 GEN Flx_digits(GEN x, GEN B, ulong p) returns a vector of Flx $[c_0, \dots, c_n]$ of degree less than the degree of B and such that $x = \sum_{i=0}^n c_i B^i$.
 GEN FlxV_Flx_fromdigits(GEN v, GEN B, ulong p) where $v = [c_0, \dots, c_n]$ is a vector of Flx, returns $\sum_{i=0}^n c_i B^i$.
 GEN Flx_Frobenius(GEN T, ulong p) here p must be prime.
 GEN Flx_Frobenius_pre(GEN T, ulong p, ulong pi)
 GEN Flx_matFrobenius(GEN T, ulong p) here p must be prime.
 GEN Flx_matFrobenius_pre(GEN T, ulong p, ulong pi)
 GEN Flx_gcd(GEN a, GEN b, ulong p) returns a (not necessarily monic) greatest common divisor of x and y . Here p must be prime.

GEN Flx_gcd_pre(GEN a, GEN b, ulong p)

GEN Flx_halfgcd(GEN x, GEN y, ulong p) returns a two-by-two FlxM M with determinant ± 1 such that the image (a, b) of (x, y) by M has the property that $\deg a \geq \frac{\deg x}{2} > \deg b$. Assumes that p is prime.

GEN Flx_halfgcd_pre(GEN a, GEN b, ulong p)

GEN Flx_halfgcd_all(GEN x, GEN y, ulong p, GEN *pt_a, GEN *pt_b)

GEN Flx_halfgcd_all_pre(GEN x, GEN y, ulong p, GEN *pt_a, GEN *pt_b)

GEN Flx_extgcd(GEN a, GEN b, ulong p, GEN *ptu, GEN *ptv), here p must be prime.

GEN Flx_extgcd_pre(GEN a, GEN b, ulong p, ulong pi, GEN *ptu, GEN *ptv)

GEN Flx_roots(GEN f, ulong p) returns the vector of roots of f (without multiplicity, as a t_VECSMALL). Assumes that p is prime.

GEN Flx_roots_pre(GEN f, ulong p, ulong pi)

ulong Flx_oneroot(GEN f, ulong p) returns one root $0 \leq r < p$ of the Flx f in $\mathbf{Z}/p\mathbf{Z}$. Return p if no root exists. Assumes that p is prime.

GEN Flx_oneroot_pre(GEN f, ulong p), as Flx_oneroot

ulong Flx_oneroot_split(GEN f, ulong p) as Flx_oneroot but assume f is totally split. Assumes that p is prime.

ulong Flx_oneroot_split_pre(GEN f, ulong p, ulong pi)

long Flx_ispower(GEN f, ulong k, ulong p, GEN *pt) return 1 if the Flx f is a k -th power, 0 otherwise. If pt is not NULL, set it to g such that $g^k = f$.

GEN Flx_factor(GEN f, ulong p) Assumes that p is prime.

GEN Flx_ddf(GEN f, ulong p) Assumes that p is prime.

GEN Flx_ddf_pre(GEN f, ulong p, ulong pi)

GEN Flx_factor_squarefree(GEN f, ulong p) returns the squarefree factorization of f modulo p . This is a vector $[u_1, \dots, u_k]$ of pairwise coprime Flx such that $u_k \neq 1$ and $f = \prod u_i^i$. Shallow function. Assumes that p is prime.

GEN Flx_factor_squarefree_pre(GEN f, ulong p, ulong pi)

GEN Flx_mod_Xn1(GEN T, ulong n, ulong p) return T modulo $(X^n + 1, p)$. Shallow function.

GEN Flx_mod_Xnm1(GEN T, ulong n, ulong p) return T modulo $(X^n - 1, p)$. Shallow function.

GEN Flx_degfact(GEN f, ulong p) as FpX_degfact. Assumes that p is prime.

GEN Flx_factorff_irred(GEN P, GEN Q, ulong p) as FpX_factorff_irred. Assumes that p is prime.

GEN Flx_rootsff(GEN P, GEN T, ulong p) as FpX_rootsff. Assumes that p is prime.

GEN Flx_factcyclo(ulong n, ulong p, ulong m) returns the factors of the n -th cyclotomic polynomial over \mathbf{F}_p . if $m = 1$ returns a single factor.

GEN Flx_ffisom(GEN P, GEN Q, ulong l) as FpX_ffisom. Assumes that p is prime.

7.3.16.3 Miscellaneous operations.

GEN `pol0_Flx(long sv)` returns a zero Flx in variable v .

GEN `zero_Flx(long sv)` alias for `pol0_Flx`

GEN `pol1_Flx(long sv)` returns the unit Flx in variable v .

GEN `polx_Flx(long sv)` returns the variable v as degree 1 Flx.

GEN `polxn_Flx(long n, long sv)` Returns the monomial of degree n as a Flx in variable v ; assume that $n \geq 0$.

GEN `monomial_Flx(ulong a, long d, long sv)` returns the Flx aX^d in variable v .

GEN `init_Flxq(ulong p, long n, long sv)` returns an irreducible polynomial of degree $n > 0$ over \mathbf{F}_p , in variable v .

GEN `Flx_normalize(GEN z, ulong p)`, as `FpX_normalize`.

GEN `Flx_rescale(GEN P, ulong h, ulong p)` returns $h^{\deg(P)}P(x/h)$, P is a Flx and h is a nonzero integer.

GEN `random_Flx(long d, long sv, ulong p)` returns a random Flx in variable v , of degree less than d .

GEN `Flx_recip(GEN x)`, returns the reciprocal polynomial

`ulong Flx_resultant(GEN a, GEN b, ulong p)`, returns the resultant of a and b . Assumes that p is prime.

`ulong Flx_resultant_pre(GEN a, GEN b, ulong p, ulong pi)`

`ulong Flx_extresultant(GEN a, GEN b, ulong p, GEN *ptU, GEN *ptV)` given two Flx a and b , returns their resultant and sets Bezout coefficients (if the resultant is 0, the latter are not set). Assumes that p is prime.

`ulong Flx_extresultant_pre(GEN a, GEN b, ulong p, ulong pi, GEN *ptU, GEN *ptV)`

GEN `Flx_composedprod(GEN P, GEN Q, ulong p)` if $P = a \prod_{i=1}^m (x - p_i)$ and $Q = b \prod_{j=1}^n (x - q_j)$ in some suitable algebraic extension, return $a^n b^m \prod_{i,j} (x - p_i q_j)$.

GEN `Flx_composedsum(GEN P, GEN Q, ulong p)` if $P = a \prod_{i=1}^m (x - p_i)$ and $Q = b \prod_{j=1}^n (x - q_j)$ in some suitable algebraic extension, return $a^n b^m \prod_{i,j} (x - (p_i + q_j))$.

GEN `Flx_invBarrett(GEN T, ulong p)`, returns the Barrett inverse M of T defined by $M(x) \times x^n T(1/x) \equiv 1 \pmod{x^{n-1}}$ where n is the degree of T . Assumes that p is prime.

GEN `Flx_renormalize(GEN x, long l)`, as `FpX_renormalize`, where $l = \lg(x)$, in place.

GEN `Flx_shift(GEN T, long n)` returns $T * x^n$ if $n \geq 0$, and $T \setminus x^{-n}$ otherwise.

`long Flx_val(GEN x)` returns the valuation of x , i.e. the multiplicity of the 0 root.

`long Flx_valrem(GEN x, GEN *Z)` as `RgX_valrem`, returns the valuation of x . In particular, if the valuation is 0, set $*Z$ to x , not a copy.

GEN `Flx_div_by_X_x(GEN A, ulong a, ulong p, ulong *rem)`, returns the Euclidean quotient of the Flx A by $X - a$, and sets `rem` to the remainder $A(a)$.

`ulong Flx_eval(GEN x, ulong y, ulong p)`, as `FpX_eval`.

`ulong Flx_eval_pre(GEN x, ulong y, ulong p, ulong pi)`
`ulong Flx_eval_powers_pre(GEN P, GEN y, ulong p, ulong pi)`. Let y be the `t_VECSMALL` $(1, a, \dots, a^n)$, where n is the degree of the `Flx` P , return $P(a)$.
`GEN Flx_Flv_multieval(GEN P, GEN v, ulong p)` returns the vector $[P(v[1]), \dots, P(v[n])]$ as a `Flv`.
`ulong Flx_dotproduct(GEN x, GEN y, ulong p)` returns the scalar product of the coefficients of x and y .
`ulong Flx_dotproduct_pre(GEN x, GEN y, ulong p, ulong pi)`.
`GEN Flx_deflate(GEN P, long d)` assuming P is a polynomial of the form $Q(X^d)$, return Q .
`GEN Flx_inflate(GEN P, long d)` returns $P(X^d)$.
`GEN Flx_splitting(GEN P, long k)`, as `RgX_splitting`.
`GEN Flx_blocks(GEN P, long n, long m)`, as `RgX_blocks`.
`int Flx_is_squarefree(GEN z, ulong p)`. Assumes that p is prime.
`int Flx_is_irred(GEN f, ulong p)`, as `FpX_is_irred`. Assumes that p is prime.
`int Flx_is_totally_split(GEN f, ulong p)` returns 1 if the `Flx` f splits into a product of distinct linear factors, 0 otherwise. Assumes that p is prime.
`int Flx_is_smooth(GEN f, long r, ulong p)` return 1 if all irreducible factors of f are of degree at most r , 0 otherwise. Assumes that p is prime.
`int Flx_is_smooth_pre(GEN f, long r, ulong p, ulong pi)`
`long Flx_nbroots(GEN f, ulong p)`, as `FpX_nbroots`. Assumes that p is prime.
`long Flx_nbfact(GEN z, ulong p)`, as `FpX_nbfact`. Assumes that p is prime.
`long Flx_nbfact_pre(GEN z, ulong p, ulong pi)`
`long Flx_nbfact_Frobenius(GEN f, GEN XP, ulong p)`, as `FpX_nbfact_Frobenius`. Assumes that p is prime.
`long Flx_nbfact_Frobenius_pre(GEN f, GEN XP, ulong p, ulong pi)`
`GEN Flx_degfact(GEN f, ulong p)`, as `FpX_degfact`. Assumes that p is prime.
`GEN Flx_nbfact_by_degree(GEN z, long *nb, ulong p)` Assume that the `Flx` z is squarefree mod the prime p . Returns a `t_VECSMALL` D with $\deg z$ entries, such that $D[i]$ is the number of irreducible factors of degree i . Set `nb` to the total number of irreducible factors (the sum of the $D[i]$). Assumes that p is prime.
`void Flx_ffintersect(GEN P, GEN Q, long n, ulong p, GEN*SP, GEN*SQ, GEN MA, GEN MB)`
, as `FpX_ffintersect`. Assumes that p is prime.
`GEN Flx_Laplace(GEN x, ulong p)`
`GEN Flx_invLaplace(GEN x, ulong p)`
`GEN Flx_Newton(GEN x, long n, ulong p)`
`GEN Flx_fromNewton(GEN x, ulong p)`

GEN Flx_Teichmuller(GEN P, ulong p, long n) Return a ZX Q such that $P \equiv Q \pmod{p}$ and $Q(X^p) = 0 \pmod{Q, p^n}$. Assumes that p is prime.

GEN Flv_polint(GEN x, GEN y, ulong p, long sv) as FpV_polint, returning an Flx in variable v . Assumes that p is prime.

GEN Flv_Flm_polint(GEN x, GEN V, ulong p, long sv) equivalent (but faster) to applying Flv_polint(x,...) to all the elements of the vector V (thus, returns a FlxV). Assumes that p is prime.

GEN Flv_invVandermonde(GEN L, ulong d, ulong p) L being a Flv of length n , return the inverse M of the Vandermonde matrix attached to the elements of L , multiplied by d . If A is a Flv and $B = MA$, then the polynomial $P = \sum_{i=1}^n B[i]X^{i-1}$ verifies $P(L[i]) = dA[i]$ for $1 \leq i \leq n$. Assumes that p is prime.

GEN Flv_roots_to_pol(GEN a, ulong p, long sv) as FpV_roots_to_pol returning an Flx in variable v .

7.3.17 FlxV. See FpXV operations.

GEN FlxV_Flc_mul(GEN V, GEN W, ulong p), as FpXV_FpC_mul.

GEN FlxV_red(GEN V, ulong p) reduces each components with Flx_red.

GEN FlxV_prod(GEN V, ulong p), V being a vector of Flx, returns their product.

GEN FlxV_composedsum(GEN V, ulong p), V being a vector of Flx, returns their composed sum, see Flx_composedsum.

ulong FlxC_eval_powers_pre(GEN x, GEN y, ulong p, ulong pi) apply Flx_eval_powers_pre to all elements of x .

GEN FlxV_Flv_multieval(GEN F, GEN v, ulong p) assuming F is a vector of Flx with m entries and v is a Flv with m entries, returns the n -components vector (FlvV) whose j -th entry is $[F_j(v[1]), \dots, F_j(v[n])]$, with $F_j = F[j]$.

GEN FlxC_neg(GEN x, ulong p)

GEN FlxC_sub(GEN x, GEN y, ulong p)

GEN zero_FlxC(long n, long sv)

7.3.18 FlxM. See FpXM operations.

ulong FlxM_eval_powers_pre(GEN M, GEN y, ulong p, ulong pi) this function applies FlxC_eval_powers_pre to all entries of M .

GEN FlxM_neg(GEN x, ulong p)

GEN FlxM_sub(GEN x, GEN y, ulong p)

GEN zero_FlxM(long r, long c, long sv)

7.3.19 FlxT. See FpXT operations.

GEN FlxT_red(GEN V, ulong p) reduces each leaf with Flx_red.

7.3.20 Flxn. See FpXn operations. In this section, pi is the pseudoinverse of p , or 0 in which case we assume $\text{SMALL_ULONG}(p)$.

`GEN Flxn_mul(GEN a, GEN b, long n, ulong p)` returns ab modulo X^n .

`GEN Flxn_mul_pre(GEN a, GEN b, long n, ulong p, ulong pi)`

`GEN Flxn_sqr(GEN a, long n, ulong p)` returns a^2 modulo X^n .

`GEN Flxn_sqr_pre(GEN a, long n, ulong p, ulong pi)`

`GEN Flxn_inv(GEN a, long n, ulong p)` returns $1/a$ modulo X^n .

`GEN Flxn_div(GEN a, GEN b, long n, ulong p)` returns a/b modulo X^n .

`GEN Flxn_div_pre(GEN a, GEN b, long n, ulong p, ulong pi)`

`GEN Flxn_red(GEN a, long n)` returns a modulo X^n .

`GEN Flxn_exp(GEN x, long n, ulong p)` return $\exp(x)$ as a composition of formal power series. It is required that the valuation of x is positive and that $p > n$.

`GEN Flxn_expint(GEN f, long n, ulong p)` return $\exp(F)$ where F is the primitive of f that vanishes at 0. It is required that $p > n$.

7.3.21 Flxq. See FpXQ operations. In this section, pi is the pseudoinverse of p , or 0 in which case we assume $\text{SMALL_ULONG}(p)$.

`GEN Flxq_add(GEN x, GEN y, GEN T, ulong p)`

`GEN Flxq_sub(GEN x, GEN y, GEN T, ulong p)`

`GEN Flxq_mul(GEN x, GEN y, GEN T, ulong p)`

`GEN Flxq_mul_pre(GEN x, GEN y, GEN T, ulong p, ulong pi)`

`GEN Flxq_sqr(GEN y, GEN T, ulong p)`

`GEN Flxq_sqr_pre(GEN y, GEN T, ulong p)`

`GEN Flxq_inv(GEN x, GEN T, ulong p)`

`GEN Flxq_inv_pre(GEN x, GEN T, ulong p, ulong pi)`

`GEN Flxq_invsafe(GEN x, GEN T, ulong p)`

`GEN Flxq_invsafe_pre(GEN x, GEN T, ulong p, ulong pi)`

`GEN Flxq_div(GEN x, GEN y, GEN T, ulong p)`

`GEN Flxq_div_pre(GEN x, GEN y, GEN T, ulong p, ulong pi)`

`GEN Flxq_pow(GEN x, GEN n, GEN T, ulong p)`

`GEN Flxq_pow_pre(GEN x, GEN n, GEN T, ulong p, ulong pi)`

`GEN Flxq_powu(GEN x, ulong n, GEN T, ulong p)`

`GEN Flxq_powu_pre(GEN x, ulong n, GEN T, ulong p)`

`GEN FlxqV_factorback(GEN L, GEN e, GEN Tp, ulong p)`

`GEN Flxq_pow_init(GEN x, GEN n, long k, GEN T, ulong p)`

GEN Flxq_pow_init_pre(GEN x, GEN n, long k, GEN T, ulong p, ulong pi)
 GEN Flxq_pow_table(GEN R, GEN n, GEN T, ulong p)
 GEN Flxq_pow_table_pre(GEN R, GEN n, GEN T, ulong p, ulong pi)
 GEN Flxq_powers(GEN x, long n, GEN T, ulong p)
 GEN Flxq_powers_pre(GEN x, long n, GEN T, ulong p, ulong pi)
 GEN Flxq_matrix_pow(GEN x, long m, long n, GEN T, ulong p), see FpXQ_matrix_pow.
 GEN Flxq_matrix_pow_pre(GEN x, long m, long n, GEN T, ulong p, ulong pi)
 GEN Flxq_autpow(GEN a, long n, GEN T, ulong p) see FpXQ_autpow.
 GEN Flxq_autpow_pre(GEN a, long n, GEN T, ulong p, ulong pi)
 GEN Flxq_autpowers(GEN a, long n, GEN T, ulong p) return $[X, \sigma(X), \dots, \sigma^n(X)]$, assuming $a = \sigma(X)$ where σ is an automorphism of the algebra $\mathbf{F}_p[X]/T(X)$.
 GEN Flxq_autsum(GEN a, long n, GEN T, ulong p) see FpXQ_autsum.
 GEN Flxq_auttrace(GEN a, ulong n, GEN T, ulong p) see FpXQ_auttrace.
 GEN Flxq_auttrace_pre(GEN a, ulong n, GEN T, ulong p, ulong pi)
 GEN Flxq_ffisom_inv(GEN S, GEN T, ulong p), as FpXQ_ffisom_inv.
 GEN Flx_Flxq_eval(GEN f, GEN x, GEN T, ulong p) returns $f(x)$.
 GEN Flx_Flxq_eval_pre(GEN f, GEN x, GEN T, ulong p, ulong pi)
 GEN Flx_FlxqV_eval(GEN f, GEN x, GEN T, ulong p), see FpX_FpXQV_eval.
 GEN Flx_FlxqV_eval_pre(GEN f, GEN x, GEN T, ulong p, ulong pi)
 GEN FlxC_Flxq_eval(GEN C, GEN x, GEN T, ulong p), see FpXC_FpXQ_eval.
 GEN FlxC_Flxq_eval_pre(GEN C, GEN x, GEN T, ulong p, ulong pi)
 GEN FlxC_FlxqV_eval(GEN C, GEN V, GEN T, ulong p) see FpXC_FpXQV_eval.
 GEN FlxC_FlxqV_eval_pre(GEN C, GEN V, GEN T, ulong p, ulong pi)
 GEN FlxqV_roots_to_pol(GEN V, GEN T, ulong p, long v) as FqV_roots_to_pol returning an FlxqX in variable v .
 int Flxq_issquare(GEN x, GEN T, ulong p) returns 1 if x is a square and 0 otherwise. Assume that T is irreducible mod p .
 int Flxq_is2npower(GEN x, long n, GEN T, ulong p) returns 1 if x is a 2^n -th power and 0 otherwise. Assume that T is irreducible mod p .
 GEN Flxq_order(GEN a, GEN ord, GEN T, ulong p) as FpXQ_order.
 GEN Flxq_log(GEN a, GEN g, GEN ord, GEN T, ulong p) as FpXQ_log
 GEN Flxq_sqrtn(GEN x, GEN n, GEN T, ulong p, GEN *zn) as FpXQ_sqrtn.
 GEN Flxq_sqrt(GEN x, GEN T, ulong p) returns a square root of x . Return NULL if x is not a square.
 GEN Flxq_sqrt_pre(GEN x, GEN T, ulong p, ulong pi)

`GEN Flxq_root(GEN a, GEN T, ulong p)` returns x such that $x^p = a$.
`GEN Flxq_root_pre(GEN a, GEN T, ulong p, ulong pi)`
`GEN Flxq_root_fast(GEN a, GEN V, GEN T, ulong p)` assuming that $V = \text{Flxq_powers}(s, p-1, T, p)$ where $s(x)^p \equiv x \pmod{T(x), p}$, returns b such that $b^p = a$. Only useful if p is less than the degree of T .
`GEN Flxq_root_fast_pre(GEN a, GEN V, GEN T, ulong p, ulong pi)`
`GEN Flxq_charpoly(GEN x, GEN T, ulong p)` returns the characteristic polynomial of x
`GEN Flxq_minpoly(GEN x, GEN T, ulong p)` returns the minimal polynomial of x
`GEN Flxq_minpoly_pre(GEN x, GEN T, ulong p, ulong pi)`
`ulong Flxq_norm(GEN x, GEN T, ulong p)` returns the norm of x
`ulong Flxq_trace(GEN x, GEN T, ulong p)` returns the trace of x
`GEN Flxq_conjvec(GEN x, GEN T, ulong p)` returns the conjugates $[x, x^p, x^{p^2}, \dots, x^{p^{n-1}}]$ where n is the degree of T .
`GEN gener_Flxq(GEN T, ulong p, GEN *po)` returns a primitive root modulo (T, p) . T is an `Flx` assumed to be irreducible modulo the prime p . If `po` is not `NULL` it is set to $[o, fa]$, where o is the order of the multiplicative group of the finite field, and fa is its factorization.

7.3.22 FlxX. See `FpXX` operations. In this section, we assume pi is the pseudoinverse of p , or 0 in which case we assume `SMALL_ULONG(p)`.

`GEN pol1_FlxX(long vX, long sx)` returns the unit `FlxX` as a `t_POL` in variable vX which only coefficient is `pol1_Flx(sx)`.
`GEN polx_FlxX(long vX, long sx)` returns the variable X as a degree 1 `t_POL` with `Flx` coefficients in the variable x .
`long FlxY_degreeex(GEN P)` return the degree of P with respect to the secondary variable.
`GEN FlxX_add(GEN P, GEN Q, ulong p)`
`GEN FlxX_sub(GEN P, GEN Q, ulong p)`
`GEN FlxX_Fl_mul(GEN x, ulong y, ulong p)`
`GEN FlxX_double(GEN x, ulong p)`
`GEN FlxX_triple(GEN x, ulong p)`
`GEN FlxX_neg(GEN x, ulong p)`
`GEN FlxX_Flx_add(GEN x, GEN y, ulong p)`
`GEN FlxX_Flx_sub(GEN x, GEN y, ulong p)`
`GEN FlxX_Flx_mul(GEN x, GEN y, ulong p)`
`GEN FlxY_Flx_div(GEN x, GEN y, ulong p)` divides the coefficients of x by y using `Flx_div`.
`GEN FlxX_deriv(GEN P, ulong p)` returns the derivative of P with respect to the main variable.
`GEN FlxX_Laplace(GEN x, ulong p)`

GEN FlxX_invLaplace(GEN x, ulong p)

GEN FlxY_evalx(GEN P, ulong z, ulong p) P being an FlxY, returns the Flx $P(z, Y)$, where Y is the main variable of P .

GEN FlxY_evalx_pre(GEN P, ulong z, ulong p, ulong pi)

GEN FlxX_translate1(GEN P, ulong p, long n) P being an FlxX with all coefficients of degree at most n , return $(P(x, Y + 1))$, where Y is the main variable of P .

GEN zlxX_translate1(GEN P, ulong p, long e, long n) P being an zlxX with all coefficients of degree at most n , return $(P(x, Y + 1))$ modulo p^e for prime p , where Y is the main variable of P .

GEN FlxY_Flx_translate(GEN P, GEN f, ulong p) P being an FlxY and f being an Flx, return $(P(x, Y + f(x)))$, where Y is the main variable of P .

ulong FlxY_evalx_powers_pre(GEN P, GEN xp, ulong p, ulong pi), xp being the vector $[1, x, \dots, x^n]$, where n is larger or equal to the degree of P in X , return $P(x, Y)$, where Y is the main variable of Q .

ulong FlxY_eval_powers_pre(GEN P, GEN xp, GEN yp, ulong p, ulong pi), xp being the vector $[1, x, \dots, x^n]$, where n is larger or equal to the degree of P in X and yp being the vector $[1, y, \dots, y^m]$, where m is larger or equal to the degree of P in Y return $P(x, y)$.

GEN FlxY_Flxq_evalx(GEN x, GEN y, GEN T, ulong p) as FpXY_FpXQ_evalx.

GEN FlxY_Flxq_evalx_pre(GEN x, GEN y, GEN T, ulong p, ulong pi)

GEN FlxY_FlxqV_evalx(GEN x, GEN V, GEN T, ulong p) as FpXY_FpXQV_evalx.

GEN FlxY_FlxqV_evalx_pre(GEN x, GEN V, GEN T, ulong p, ulong pi)

GEN FlxX_renormalize(GEN x, long l), as normalizepol, where $l = \lg(x)$, in place.

GEN FlxX_resultant(GEN u, GEN v, ulong p, long sv) Returns $\text{Res}_X(u, v)$, which is an Flx. The coefficients of u and v are assumed to be in the variable v .

GEN Flx_FlxY_resultant(GEN a, GEN b, ulong p) Returns $\text{Res}_x(a, b)$, which is an Flx in the main variable of b .

GEN FlxX_blocks(GEN P, long n, long m, long sv), as RgX_blocks, where v is the secondary variable.

GEN FlxX_shift(GEN a, long n, long sv), as RgX_shift_shallow, where v is the secondary variable.

GEN FlxX_swap(GEN x, long n, long ws), as RgXY_swap.

GEN FlxYqq_pow(GEN x, GEN n, GEN S, GEN T, ulong p), as FpXYQQ_pow.

7.3.23 FlxXV, FlxXC, FlxXM. See FpXX operations.

GEN FlxXC_sub(GEN x, GEN y, ulong p)

7.3.24 FlxqX. See FpXQX operations.

7.3.24.1 Preconditioned reduction.

For faster reduction, the modulus S can be replaced by an extended modulus, which is an FlxqXT , in all FlxqXQ -classes functions, and in FlxqX_rem and FlxqX_divrem .

$\text{GEN FlxqX_get_red}(\text{GEN } S, \text{GEN } T, \text{ulong } p)$ returns the extended modulus eS .

$\text{GEN FlxqX_get_red_pre}(\text{GEN } S, \text{GEN } T, \text{ulong } p, \text{ulong } pi)$, where pi is a pseudoinverse of p , or 0 in which case we assume $\text{SMALL_ULONG}(p)$.

To write code that works both with plain and extended moduli, the following accessors are defined:

$\text{GEN get_FlxqX_mod}(\text{GEN } eS)$ returns the underlying modulus S .

$\text{GEN get_FlxqX_var}(\text{GEN } eS)$ returns the variable number of the modulus.

$\text{GEN get_FlxqX_degree}(\text{GEN } eS)$ returns the degree of the modulus.

7.3.24.2 basic functions.

In this section, pi is a pseudoinverse of p , or 0 in which case we assume $\text{SMALL_ULONG}(p)$.

$\text{GEN random_FlxqX}(\text{long } d, \text{long } v, \text{GEN } T, \text{ulong } p)$ returns a random FlxqX in variable v , of degree less than d .

$\text{GEN zxX_to_Kronecker}(\text{GEN } P, \text{GEN } Q)$ assuming $P(X, Y)$ is a polynomial of degree in X strictly less than n , returns $P(X, X^{2*n-1})$, the Kronecker form of P .

$\text{GEN Kronecker_to_FlxqX}(\text{GEN } z, \text{GEN } T, \text{ulong } p)$. Let $n = \deg T$ and let $P(X, Y) \in \mathbf{Z}[X, Y]$ lift a polynomial in $K[Y]$, where $K := \mathbf{F}_p[X]/(T)$ and $\deg_X P < 2n-1$ — such as would result from multiplying minimal degree lifts of two polynomials in $K[Y]$. Let $z = P(t, t^{2*n-1})$ be a Kronecker form of P , this function returns $Q \in \mathbf{Z}[X, t]$ such that Q is congruent to $P(X, t) \pmod{(p, T(X))}$, $\deg_X Q < n$, and all coefficients are in $[0, p[$. Not stack-clean. Note that t need not be the same variable as Y !

$\text{GEN Kronecker_to_FlxqX_pre}(\text{GEN } z, \text{GEN } T, \text{ulong } p, \text{ulong } pi)$

$\text{GEN FlxqX_red}(\text{GEN } z, \text{GEN } T, \text{ulong } p)$

$\text{GEN FlxqX_red_pre}(\text{GEN } z, \text{GEN } T, \text{ulong } p, \text{ulong } pi)$

$\text{GEN FlxqX_normalize}(\text{GEN } z, \text{GEN } T, \text{ulong } p)$

$\text{GEN FlxqX_normalize_pre}(\text{GEN } z, \text{GEN } T, \text{ulong } p, \text{ulong } pi)$

$\text{GEN FlxqX_mul}(\text{GEN } x, \text{GEN } y, \text{GEN } T, \text{ulong } p)$

$\text{GEN FlxqX_mul_pre}(\text{GEN } x, \text{GEN } y, \text{GEN } T, \text{ulong } p, \text{ulong } pi)$

$\text{GEN FlxqX_Flxq_mul}(\text{GEN } P, \text{GEN } U, \text{GEN } T, \text{ulong } p)$

$\text{GEN FlxqX_Flxq_mul_pre}(\text{GEN } P, \text{GEN } U, \text{GEN } T, \text{ulong } p, \text{ulong } pi)$

$\text{GEN FlxqX_Flxq_mul_to_monic}(\text{GEN } P, \text{GEN } U, \text{GEN } T, \text{ulong } p)$ returns $P * U$ assuming the result is monic of the same degree as P (in particular $U \neq 0$).

$\text{GEN FlxqX_Flxq_mul_to_monic_pre}(\text{GEN } P, \text{GEN } U, \text{GEN } T, \text{ulong } p, \text{ulong } pi)$

$\text{GEN FlxqX_sqr}(\text{GEN } x, \text{GEN } T, \text{ulong } p)$

GEN FlxqX_sqr_pre(GEN x, GEN T, ulong p, ulong pi)
 GEN FlxqX_powu(GEN x, ulong n, GEN T, ulong p)
 GEN FlxqX_powu_pre(GEN x, ulong n, GEN T, ulong p, ulong pi)
 GEN FlxqX_divrem(GEN x, GEN y, GEN T, ulong p, GEN *pr)
 GEN FlxqX_divrem_pre(GEN x, GEN y, GEN T, ulong p, ulong pi, GEN *pr)
 GEN FlxqX_div(GEN x, GEN y, GEN T, ulong p)
 GEN FlxqX_div_pre(GEN x, GEN y, GEN T, ulong p, ulong pi)
 GEN FlxqX_div_by_X_x(GEN a, GEN x, GEN T, ulong p, GEN *r)
 GEN FlxqX_div_by_X_x_pre(GEN a, GEN x, GEN T, ulong p, ulong pi, GEN *r)
 GEN FlxqX_rem(GEN x, GEN y, GEN T, ulong p)
 GEN FlxqX_rem_pre(GEN x, GEN y, GEN T, ulong p, ulong pi)
 GEN FlxqX_invBarrett(GEN T, GEN Q, ulong p)
 GEN FlxqX_invBarrett_pre(GEN T, GEN Q, ulong p, ulong pi)
 GEN FlxqX_gcd(GEN x, GEN y, ulong p) returns a (not necessarily monic) greatest common divisor of x and y .
 GEN FlxqX_gcd_pre(GEN x, GEN y, ulong p, ulong pi)
 GEN FlxqX_extgcd(GEN x, GEN y, GEN T, ulong p, GEN *ptu, GEN *ptv)
 GEN FlxqX_extgcd_pre(GEN x, GEN y, GEN T, ulong p, ulong pi, GEN *ptu, GEN *ptv)
 GEN FlxqX_halfgcd(GEN x, GEN y, GEN T, ulong p), see FpX_halfgcd.
 GEN FlxqX_halfgcd_pre(GEN x, GEN y, GEN T, ulong p, ulong pi)
 GEN FlxqX_halfgcd_all(GEN x, GEN y, GEN T, ulong p, GEN *a, GEN *b), see FpX_halfgcd_all.
 GEN FlxqX_halfgcd_all_pre(GEN x, GEN y, GEN T, ulong p, ulong pi, GEN *a, GEN *b), see FpX_halfgcd_all_pre.
 GEN FlxqX_resultant(GEN x, GEN y, GEN T, ulong p), see FpX_resultant.
 GEN FlxqX_resultant_pre(GEN x, GEN y, GEN T, ulong p, ulong pi)
 GEN FlxqX_saferes resultant(GEN P, GEN Q, GEN T, ulong p) Returns the resultant of P and Q if Euclid's algorithm succeeds and NULL otherwise. In particular, if p is not prime or T is not irreducible over $\mathbf{F}_p[X]$, the routine may still be used (but will fail if noninvertible leading terms occur).
 GEN FlxqX_composedsum(GEN P, GEN Q, GEN T, ulong p)
 GEN FlxqX_disc(GEN x, GEN T, ulong p)
 GEN FlxqX_eval(GEN x, GEN y, GEN T, ulong p) evaluates the FlxqX x at the Flxq y . The result is an Flxq.
 GEN FlxqXV_prod(GEN V, GEN T, ulong p)

GEN FlxqX_safegcd(GEN P, GEN Q, GEN T, ulong p) Returns the *monic* GCD of P and Q if Euclid's algorithm succeeds and NULL otherwise. In particular, if p is not prime or T is not irreducible over $\mathbf{F}_p[X]$, the routine may still be used (but will fail if noninvertible leading terms occur).

GEN FlxqX_dotproduct(GEN x, GEN y, GEN T, ulong p) returns the scalar product of the coefficients of x and y .

GEN FlxqX_Newton(GEN x, long n, GEN T, ulong p)

GEN FlxqX_Newton_pre(GEN x, long n, GEN T, ulong p, ulong pi)

GEN FlxqX_fromNewton(GEN x, GEN T, ulong p)

GEN FlxqX_fromNewton_pre(GEN x, GEN T, ulong p, ulong pi) We assume pi is a pseudoinverse of p , or 0 in which case we assume SMALL_ULONG(p).

long FlxqX_is_squarefree(GEN S, GEN T, ulong p), as FpX_is_squarefree.

long FlxqX_ispower(GEN f, ulong k, GEN T, ulong p, GEN *pt) return 1 if the FlxqX f is a k -th power, 0 otherwise. If pt is not NULL, set it to g such that $g^k = f$.

GEN FlxqX_Frobenius(GEN S, GEN T, ulong p), as FpXQX_Frobenius

GEN FlxqX_Frobenius_pre(GEN S, GEN T, ulong p, ulong pi)

GEN FlxqX_roots(GEN f, GEN T, ulong p) return the roots of f in $\mathbf{F}_p[X]/(T)$. Assumes p is prime and T irreducible in $\mathbf{F}_p[X]$.

GEN FlxqX_factor(GEN f, GEN T, ulong p) return the factorization of f over $\mathbf{F}_p[X]/(T)$. Assumes p is prime and T irreducible in $\mathbf{F}_p[X]$.

GEN FlxqX_factor_squarefree(GEN f, GEN T, ulong p) returns the squarefree factorization of f , see FpX_factor_squarefree.

GEN FlxqX_factor_squarefree_pre(GEN f, GEN T, ulong p, ulong pi)

GEN FlxqX_ddf(GEN f, GEN T, ulong p) as FpX_ddf.

long FlxqX_ddf_degree(GEN f, GEN XP, GEN T, GEN p), as FpX_ddf_degree.

GEN FlxqX_degfact(GEN f, GEN T, ulong p), as FpX_degfact.

long FlxqX_nbroots(GEN S, GEN T, ulong p), as FpX_nbroots.

long FlxqX_nbfact(GEN S, GEN T, ulong p), as FpX_nbfact.

long FlxqX_nbfact_Frobenius(GEN S, GEN Xq, GEN T, ulong p), as FpX_nbfact_Frobenius.

GEN FlxqX_nbfact_by_degree(GEN z, long *nb, GEN T, ulong p) Assume that the FlxqX z is squarefree mod the prime p . Returns a t_VECSMALL D with $\deg z$ entries, such that $D[i]$ is the number of irreducible factors of degree i . Set nb to the total number of irreducible factors (the sum of the $D[i]$).

GEN FlxqX_FlxqXQ_eval(GEN Q, GEN x, GEN S, GEN T, ulong p) as FpX_FpXQ_eval.

GEN FlxqX_FlxqXQ_eval_pre(GEN Q, GEN x, GEN S, GEN T, ulong p, ulong pi)

GEN FlxqX_FlxqXQV_eval(GEN P, GEN V, GEN S, GEN T, ulong p) as FpX_FpXQV_eval.

GEN FlxqX_FlxqXQV_eval_pre(GEN P, GEN V, GEN S, GEN T, ulong p, ulong pi)

GEN FlxqXC_FlxqXQ_eval(GEN Q, GEN x, GEN S, GEN T, ulong p) as FpXC_FpXQ_eval.
 GEN FlxqXC_FlxqXQ_eval_pre(GEN Q, GEN x, GEN S, GEN T, ulong p, ulong pi)
 GEN FlxqXC_FlxqXQV_eval(GEN P, GEN V, GEN S, GEN T, ulong p) as FpXC_FpXQV_eval.
 GEN FlxqXC_FlxqXQV_eval_pre(GEN P, GEN V, GEN S, GEN T, ulong p, ulong pi)

7.3.25 FlxqXQ. See FpXQXQ operations. In this section, pi is a pseudoinverse of p , or 0 in which case we assume $\text{SMALL_ULONG}(p)$.

GEN FlxqXQ_mul(GEN x, GEN y, GEN S, GEN T, ulong p)
 GEN FlxqXQ_mul_pre(GEN x, GEN y, GEN S, GEN T, ulong p, ulong pi)
 GEN FlxqXQ_sqr(GEN x, GEN S, GEN T, ulong p)
 GEN FlxqXQ_sqr_pre(GEN x, GEN S, GEN T, ulong p, ulong pi)
 GEN FlxqXQ_inv(GEN x, GEN S, GEN T, ulong p)
 GEN FlxqXQ_inv_pre(GEN x, GEN S, GEN T, ulong p, ulong pi)
 GEN FlxqXQ_invsafe(GEN x, GEN S, GEN T, ulong p)
 GEN FlxqXQ_invsafe_pre(GEN x, GEN S, GEN T, ulong p, ulong pi)
 GEN FlxqXQ_div(GEN x, GEN y, GEN S, GEN T, ulong p)
 GEN FlxqXQ_div_pre(GEN x, GEN y, GEN S, GEN T, ulong p, ulong pi)
 GEN FlxqXQ_pow(GEN x, GEN n, GEN S, GEN T, ulong p)
 GEN FlxqXQ_pow_pre(GEN x, GEN n, GEN S, GEN T, ulong p, ulong pi)
 GEN FlxqXQ_powu(GEN x, ulong n, GEN S, GEN T, ulong p)
 GEN FlxqXQ_powu_pre(GEN x, ulong n, GEN S, GEN T, ulong p, ulong pi)
 GEN FlxqXQ_powers(GEN x, long n, GEN S, GEN T, ulong p)
 GEN FlxqXQ_powers_pre(GEN x, long n, GEN S, GEN T, ulong p, ulong pi)
 GEN FlxqXQ_matrix_pow(GEN x, long n, long m, GEN S, GEN T, ulong p)
 GEN FlxqXQ_autpow(GEN a, long n, GEN S, GEN T, ulong p) as FpXQXQ_autpow
 GEN FlxqXQ_autpow_pre(GEN a, long n, GEN S, GEN T, ulong p, ulong pi)
 GEN FlxqXQ_autsum(GEN a, long n, GEN S, GEN T, ulong p) as FpXQXQ_autsum
 GEN FlxqXQ_autsum_pre(GEN a, long n, GEN S, GEN T, ulong p, ulong pi)
 GEN FlxqXQ_auttrace(GEN a, long n, GEN S, GEN T, ulong p) as FpXQXQ_auttrace
 GEN FlxqXQ_auttrace_pre(GEN a, long n, GEN S, GEN T, ulong p, ulong pi)
 GEN FlxqXQ_halfFrobenius(GEN A, GEN S, GEN T, ulong p), as FpXQXQ_halfFrobenius
 GEN FlxqXQ_minpoly(GEN x, GEN S, GEN T, ulong p), as FpXQ_minpoly
 GEN FlxqXQ_minpoly_pre(GEN x, GEN S, GEN T, ulong p, ulong pi)

7.3.26 FlxqXn. See FpXn operations. In this section, we assume pi is the pseudoinverse of p , or 0 in which case we assume `SMALL_ULONG(p)`.

GEN FlxXn_red(GEN a, long n) returns a modulo X^n .
 GEN FlxqXn_mul(GEN a, GEN b, long n, GEN T, ulong p)
 GEN FlxqXn_mul_pre(GEN a, GEN b, long n, GEN T, ulong p, ulong pi)
 GEN FlxqXn_sqr(GEN a, long n, GEN T, ulong p)
 GEN FlxqXn_sqr_pre(GEN a, long n, GEN T, ulong p, ulong pi)
 GEN FlxqXn_inv(GEN a, long n, GEN T, ulong p)
 GEN FlxqXn_inv_pre(GEN a, long n, GEN T, ulong p, ulong pi)
 GEN FlxqXn_expint(GEN a, long n, GEN T, ulong p)
 GEN FlxqXn_expint_pre(GEN a, long n, GEN T, ulong p, ulong pi)

7.3.27 F2x. An F2x z is a `t_VECSMALL` representing a polynomial over $\mathbf{F}_2[X]$. Specifically $z[0]$ is the usual codeword, $z[1] = \text{evalvarn}(v)$ for some variable v and the coefficients are given by the bits of remaining words by increasing degree.

7.3.27.1 Preconditioned reduction.

For faster reduction, the modulus T can be replaced by an extended modulus (`FlxT`) in all `Flxq`-classes functions, and in `Flx_divrem`.

GEN F2x_get_red(GEN T) returns the extended modulus `eT`.

To write code that works both with plain and extended moduli, the following accessors are defined:

GEN get_F2x_mod(GEN eT) returns the underlying modulus T .
 GEN get_F2x_var(GEN eT) returns the variable number of the modulus.
 GEN get_F2x_degree(GEN eT) returns the degree of the modulus.

7.3.27.2 Basic operations.

ulong F2x_coeff(GEN x, long i) returns the coefficient $i \geq 0$ of x .
 void F2x_clear(GEN x, long i) sets the coefficient $i \geq 0$ of x to 0.
 void F2x_flip(GEN x, long i) adds 1 to the coefficient $i \geq 0$ of x .
 void F2x_set(GEN x, long i) sets the coefficient $i \geq 0$ of x to 1.
 GEN F2x_copy(GEN x)
 GEN Flx_to_F2x(GEN x)
 GEN Z_to_F2x(GEN x, long sv)
 GEN ZX_to_F2x(GEN x)
 GEN F2v_to_F2x(GEN x, long sv)
 GEN F2x_to_Flx(GEN x)

GEN F2x_to_F2xX(GEN x, long sv)
 GEN F2x_to_ZX(GEN x)
 GEN pol0_F2x(long sv) returns a zero F2x in variable v .
 GEN zero_F2x(long sv) alias for pol0_F2x.
 GEN pol1_F2x(long sv) returns the F2x in variable v constant to 1.
 GEN polx_F2x(long sv) returns the variable v as degree 1 F2x.
 GEN monomial_F2x(long d, long sv) returns the F2x X^d in variable v .
 GEN random_F2x(long d, long sv) returns a random F2x in variable v , of degree less than d .
 long F2x_degree(GEN x) returns the degree of the F2x x . The degree of 0 is defined as -1 .
 GEN F2x_recip(GEN x)
 int F2x_equal1(GEN x)
 int F2x_equal(GEN x, GEN y)
 GEN F2x_1_add(GEN y) returns $y+1$ where y is a F1x.
 GEN F2x_add(GEN x, GEN y)
 GEN F2x_mul(GEN x, GEN y)
 GEN F2x_sqr(GEN x)
 GEN F2x_divrem(GEN x, GEN y, GEN *pr)
 GEN F2x_rem(GEN x, GEN y)
 GEN F2x_div(GEN x, GEN y)
 GEN F2x_renormalize(GEN x, long lx)
 GEN F2x_deriv(GEN x)
 GEN F2x_deflate(GEN x, long d)
 ulong F2x_eval(GEN P, ulong u) returns $P(u)$.
 void F2x_shift(GEN x, long d) as RgX_shift
 void F2x_even_odd(GEN P, GEN *pe, GEN *po) as RgX_even_odd
 long F2x_valrem(GEN x, GEN *Z)
 GEN F2x_extgcd(GEN a, GEN b, GEN *ptu, GEN *ptv)
 GEN F2x_gcd(GEN a, GEN b)
 GEN F2x_halfgcd(GEN a, GEN b)
 int F2x_issquare(GEN x) returns 1 if x is a square of a F2x and 0 otherwise.
 int F2x_is_irred(GEN f), as FpX_is_irred.
 GEN F2x_degfact(GEN f) as FpX_degfact.
 GEN F2x_sqrt(GEN x) returns the squareroot of x , assuming x is a square of a F2x.

GEN F2x_Frobenius(GEN T)
 GEN F2x_matFrobenius(GEN T)
 GEN F2x_factor(GEN f)
 GEN F2x_factor_squarefree(GEN f)
 GEN F2x_ddf(GEN f)
 GEN F2x_Teichmuller(GEN P, long n) Return a ZX Q such that $P \equiv Q \pmod{2}$ and $Q(X^p) = 0 \pmod{Q, 2^n}$.

7.3.28 F2xq. See FpXQ operations.

GEN F2xq_mul(GEN x, GEN y, GEN T)
 GEN F2xq_sqr(GEN x, GEN T)
 GEN F2xq_div(GEN x, GEN y, GEN T)
 GEN F2xq_inv(GEN x, GEN T)
 GEN F2xq_invsafe(GEN x, GEN T)
 GEN F2xq_pow(GEN x, GEN n, GEN T)
 GEN F2xq_powu(GEN x, ulong n, GEN T)
 GEN F2xq_pow_init(GEN x, GEN n, long k, GEN T)
 GEN F2xq_pow_table(GEN R, GEN n, GEN T)
 ulong F2xq_trace(GEN x, GEN T)
 GEN F2xq_conjvec(GEN x, GEN T) returns the vector of conjugates $[x, x^2, x^{2^2}, \dots, x^{2^{n-1}}]$ where n is the degree of T .
 GEN F2xq_log(GEN a, GEN g, GEN ord, GEN T)
 GEN F2xq_order(GEN a, GEN ord, GEN T)
 GEN F2xq_Artin_Schreier(GEN a, GEN T) returns a solution of $x^2 + x = a$, assuming it exists.
 GEN F2xq_sqrt(GEN a, GEN T)
 GEN F2xq_sqrt_fast(GEN a, GEN s, GEN T) assuming that $s^2 \equiv x \pmod{T(x)}$, computes $b \equiv a(s) \pmod{T}$ so that $b^2 = a$.
 GEN F2xq_sqrtn(GEN a, GEN n, GEN T, GEN *zeta)
 GEN gener_F2xq(GEN T, GEN *po)
 GEN F2xq_powers(GEN x, long n, GEN T)
 GEN F2xq_matrix_pow(GEN x, long m, long n, GEN T)
 GEN F2x_F2xq_eval(GEN f, GEN x, GEN T)
 GEN F2x_F2xqV_eval(GEN f, GEN x, GEN T), see FpX_FpXQV_eval.
 GEN F2xq_outpow(GEN a, long n, GEN T) computes $\sigma^n(X)$ assuming $a = \sigma(X)$ where σ is an automorphism of the algebra $\mathbf{F}_2[X]/T(X)$.
 GEN F2xqV_roots_to_pol(GEN V, GEN T, long v) as FqV_roots_to_pol returning an F2xqX in variable v .

7.3.29 F2xn. See FpXn operations.

GEN F2xn_red(GEN a, long n)
GEN F2xn_div(GEN x, GEN y, long e)
GEN F2xn_inv(GEN x, long e)

7.3.30 F2xqV, F2xqM.. See FqV, FqM operations.

GEN F2xqM_F2xqC_gauss(GEN a, GEN b, GEN T)
GEN F2xqM_F2xqC_invimage(GEN a, GEN b, GEN T)
GEN F2xqM_F2xqC_mul(GEN a, GEN b, GEN T)
GEN F2xqM_deplin(GEN x, GEN T)
GEN F2xqM_det(GEN a, GEN T)
GEN F2xqM_gauss(GEN a, GEN b, GEN T)
GEN F2xqM_image(GEN x, GEN T)
GEN F2xqM_indexrank(GEN x, GEN T)
GEN F2xqM_inv(GEN a, GEN T)
GEN F2xqM_invimage(GEN a, GEN b, GEN T)
GEN F2xqM_ker(GEN x, GEN T)
GEN F2xqM_mul(GEN a, GEN b, GEN T)
long F2xqM_rank(GEN x, GEN T)
GEN F2xqM_suppl(GEN x, GEN T)
GEN matid_F2xqM(long n, GEN T)

7.3.31 F2xX.. See FpXX operations.

GEN ZXX_to_F2xX(GEN x, long v)
GEN FlxX_to_F2xX(GEN x)
GEN F2xX_to_FlxX(GEN B)
GEN F2xX_to_F2xC(GEN B, long N, long sv)
GEN F2xXV_to_F2xM(GEN B, long N, long sv)
GEN F2xX_to_ZXX(GEN B)
GEN F2xX_renormalize(GEN x, long lx)
GEN F2xX_shift(GEN a, long n, long sv), as RgX_shift_shallow, where v is the secondary variable.
long F2xY_degreeex(GEN P) return the degree of P with respect to the secondary variable.
GEN pol1_F2xX(long v, long sv)
GEN polx_F2xX(long v, long sv)

GEN F2xX_add(GEN x, GEN y)
 GEN F2xX_F2x_add(GEN x, GEN y)
 GEN F2xX_F2x_mul(GEN x, GEN y)
 GEN F2xX_deriv(GEN P) returns the derivative of P with respect to the main variable.
 GEN Kronecker_to_F2xqX(GEN z, GEN T)
 GEN F2xX_to_Kronecker(GEN z, GEN T)
 GEN F2xY_F2xq_evalx(GEN x, GEN y, GEN T) as FpXY_FpXQ_evalx.
 GEN F2xY_F2xqV_evalx(GEN x, GEN V, GEN T) as FpXY_FpXQV_evalx.

7.3.32 F2xXV/F2xXC.. See FpXXV operations.

GEN FlxXC_to_F2xXC(GEN B)
 GEN F2xXC_to_ZXXC(GEN B)

7.3.33 F2xqX.. See FlxqX operations.

7.3.33.1 Preconditioned reduction.

For faster reduction, the modulus S can be replaced by an extended modulus, which is an $F2xqXT$, in all $F2xqXQ$ -classes functions, and in $F2xqX_rem$ and $F2xqX_divrem$.

GEN $F2xqX_get_red$ (GEN S , GEN T) returns the extended modulus eS .

To write code that works both with plain and extended moduli, the following accessors are defined:

GEN get_F2xqX_mod (GEN eS) returns the underlying modulus S .
 GEN get_F2xqX_var (GEN eS) returns the variable number of the modulus.
 GEN get_F2xqX_degree (GEN eS) returns the degree of the modulus.

7.3.33.2 basic functions.

GEN $random_F2xqX$ (long d , long v , GEN T , ulong p) returns a random $F2xqX$ in variable v , of degree less than d .
 GEN $F2xqX_red$ (GEN z , GEN T)
 GEN $F2xqX_normalize$ (GEN z , GEN T)
 GEN $F2xqX_F2xq_mul$ (GEN P , GEN U , GEN T)
 GEN $F2xqX_F2xq_mul_to_monic$ (GEN P , GEN U , GEN T)
 GEN $F2xqX_mul$ (GEN x , GEN y , GEN T)
 GEN $F2xqX_sqr$ (GEN x , GEN T)
 GEN $F2xqX_powu$ (GEN x , ulong n , GEN T)
 GEN $F2xqX_rem$ (GEN x , GEN y , GEN T)
 GEN $F2xqX_div$ (GEN x , GEN y , GEN T)

GEN F2xqX_divrem(GEN x, GEN y, GEN T, GEN *pr)
 GEN F2xqXQ_inv(GEN x, GEN S, GEN T)
 GEN F2xqXQ_invsafe(GEN x, GEN S, GEN T)
 GEN F2xqX_invBarrett(GEN T, GEN Q)
 GEN F2xqX_extgcd(GEN x, GEN y, GEN T, GEN *ptu, GEN *ptv)
 GEN F2xqX_gcd(GEN x, GEN y, GEN T)
 GEN F2xqX_halfgcd(GEN x, GEN y, GEN T)
 GEN F2xqX_halfgcd_all(GEN x, GEN y, GEN T, GEN *a, GEN *b)
 GEN F2xqX_resultant(GEN x, GEN y, GEN T)
 GEN F2xqX_disc(GEN x, GEN T)
 GEN F2xqXV_prod(GEN V, GEN T)
 long F2xqX_ispower(GEN f, ulong k, GEN T, GEN *pt)
 GEN F2xqX_F2xqXQ_eval(GEN Q, GEN x, GEN S, GEN T) as FpX_FpXQ_eval.
 GEN F2xqX_F2xqXQV_eval(GEN P, GEN V, GEN S, GEN T) as FpX_FpXQV_eval.
 GEN F2xqX_roots(GEN f, GEN T) return the roots of f in $\mathbf{F}_2[X]/(T)$. Assumes T irreducible in $\mathbf{F}_2[X]$.
 GEN F2xqX_factor(GEN f, GEN T) return the factorization of f over $\mathbf{F}_2[X]/(T)$. Assumes T irreducible in $\mathbf{F}_2[X]$.
 GEN F2xqX_factor_squarefree(GEN f, GEN T) as FlxqX_factor_squarefree.
 GEN F2xqX_ddf(GEN f, GEN T) as FpX_ddf.
 GEN F2xqX_degfact(GEN f, GEN T) as FpX_degfact.

7.3.34 F2xqXQ.. See FlxqXQ operations.

GEN FlxqXQ_inv(GEN x, GEN S, GEN T)
 GEN FlxqXQ_invsafe(GEN x, GEN S, GEN T)
 GEN F2xqXQ_mul(GEN x, GEN y, GEN S, GEN T)
 GEN F2xqXQ_sqr(GEN x, GEN S, GEN T)
 GEN F2xqXQ_pow(GEN x, GEN n, GEN S, GEN T)
 GEN F2xqXQ_powers(GEN x, long n, GEN S, GEN T)
 GEN F2xqXQ_autpow(GEN a, long n, GEN S, GEN T) as FpXQXQ_autpow
 GEN F2xqXQ_auttrace(GEN a, long n, GEN S, GEN T). Let σ be the automorphism defined by $\sigma(X) = a[1] \pmod{T(X)}$ and $\sigma(Y) = a[2] \pmod{S(X, Y), T(X)}$; returns the vector $[\sigma^n(X), \sigma^n(Y), b + \sigma(b) + \dots + \sigma^{n-1}(b)]$ where $b = a[3]$.
 GEN F2xqXQV_red(GEN x, GEN S, GEN T)

7.3.35 Functions returning objects with t_INTMOD coefficients.

Those functions are mostly needed for interface reasons: t_INTMOD s should not be used in library mode since the modular kernel is more flexible and more efficient, but GP users do not have access to the modular kernel. We document them for completeness:

`GEN Fp_to_mod(GEN z, GEN p)`, z a t_INT . Returns $z * \text{Mod}(1,p)$, normalized. Hence the returned value is a t_INTMOD .

`GEN FpX_to_mod(GEN z, GEN p)`, z a ZX . Returns $z * \text{Mod}(1,p)$, normalized. Hence the returned value has t_INTMOD coefficients.

`GEN FpC_to_mod(GEN z, GEN p)`, z a ZC . Returns $\text{Col}(z) * \text{Mod}(1,p)$, a t_COL with t_INTMOD coefficients.

`GEN FpV_to_mod(GEN z, GEN p)`, z a ZV . Returns $\text{Vec}(z) * \text{Mod}(1,p)$, a t_VEC with t_INTMOD coefficients.

`GEN FpVV_to_mod(GEN z, GEN p)`, z a ZVV . Returns $\text{Vec}(z) * \text{Mod}(1,p)$, a t_VEC of t_VEC with t_INTMOD coefficients.

`GEN FpM_to_mod(GEN z, GEN p)`, z a ZM . Returns $z * \text{Mod}(1,p)$, with t_INTMOD coefficients.

`GEN F2c_to_mod(GEN x)`

`GEN F3c_to_mod(GEN x)`

`GEN F2m_to_mod(GEN x)`

`GEN F3m_to_mod(GEN x)`

`GEN Flc_to_mod(GEN z)`

`GEN Flm_to_mod(GEN z)`

`GEN FqC_to_mod(GEN z, GEN T, GEN p)`

`GEN FqM_to_mod(GEN z, GEN T, GEN p)`

`GEN FpXC_to_mod(GEN V, GEN p)`

`GEN FpXM_to_mod(GEN V, GEN p)`

`GEN FpXQC_to_mod(GEN V, GEN T, GEN p)` V being a vector of $FpXQ$, converts each entry to a t_POLMOD with t_INTMOD coefficients, and return a t_COL .

`GEN FpQXQ_to_mod(GEN P, GEN T, GEN p)` P being a $FpQXQ$, converts each coefficient to a t_POLMOD with t_INTMOD coefficients.

`GEN FqX_to_mod(GEN P, GEN T, GEN p)` same but allow $T = \text{NULL}$.

`GEN FqXC_to_mod(GEN P, GEN T, GEN p)`

`GEN FqXM_to_mod(GEN P, GEN T, GEN p)`

`GEN QXQ_to_mod_shallow(GEN x, GEN T)` x a QXQ , which is a lifted representative of elements of $\mathbf{Q}[X]/(T)$ (number field elements in most applications) and T is in $\mathbf{Z}[X]$. Convert it to a t_POLMOD modulo T ; no reduction mod T is attempted: the representatives should be already reduced. Shallow function.

GEN QXQV_to_mod(GEN V, GEN T) V a vector of QXQ, which are lifted representatives of elements of $\mathbf{Q}[X]/(T)$ (number field elements in most applications) and T is in $\mathbf{Z}[X]$. Return a vector where all nonrational entries are converted to `t_POLMOD` modulo T ; no reduction mod T is attempted: the representatives should be already reduced. Used to normalize the output of `nfroots`.

GEN QXQX_to_mod_shallow(GEN P, GEN T) P a polynomial with QXQ coefficients; replace them by `mkpolmod(.,T)`. Shallow function.

GEN QXQC_to_mod_shallow(GEN V, GEN T) V a vector with QXQ coefficients; replace them by `mkpolmod(.,T)`. Shallow function.

GEN QXQM_to_mod_shallow(GEN M, GEN T) M a matrix with QXQ coefficients; replace them by `mkpolmod(.,T)`. Shallow function.

GEN QXQXV_to_mod(GEN V, GEN T) V a vector of polynomials whose coefficients are QXQ. Analogous to `QXQV_to_mod`. Used to normalize the output of `nfactor`.

The following functions are obsolete and should not be used: they receive a polynomial with arbitrary coefficients, apply a conversion function to map them to a finite field, a function from the modular kernel, then `*_to_mod`:

GEN rootmod(GEN f, GEN p), applies `FpX_roots`.

GEN rootmod2(GEN f, GEN p), (now) identical to `rootmod`.

GEN rootmod0(GEN f, GEN p, long flag), (now) identical to `rootmod`; ignores *flag*.

GEN factmod(GEN f, GEN p) applies `*_factor`.

GEN simplefactmod(GEN f, GEN p) applies `*_degfact`.

7.3.36 Slow Chinese remainder theorem over \mathbf{Z} . The routines in this section have quadratic time complexity with respect to the input size; see the routines in the next two sections for quasi-linear time variants.

GEN Z_chinese(GEN a, GEN b, GEN A, GEN B) returns the integer in $[0, \text{lcm}(A, B)[$ congruent to $a \bmod A$ and $b \bmod B$, assuming it exists; in other words, that a and b are congruent mod $\text{gcd}(A, B)$.

GEN Z_chinese_all(GEN a, GEN b, GEN A, GEN B, GEN *pC) as `Z_chinese`, setting `*pC` to the lcm of A and B .

GEN Z_chinese_coprime(GEN a, GEN b, GEN A, GEN B, GEN C), as `Z_chinese`, assuming that $\text{gcd}(A, B) = 1$ and that $C = \text{lcm}(A, B) = AB$.

ulong u_chinese_coprime(ulong a, ulong b, ulong A, ulong B, ulong C), as `Z_chinese_coprime` for ulong inputs and output.

void Z_chinese_pre(GEN A, GEN B, GEN *pC, GEN *pU, GEN *pd) initializes chinese remainder computations modulo A and B . Sets `*pC` to $\text{lcm}(A, B)$, `*pd` to $\text{gcd}(A, B)$, `*pU` to an integer congruent to 0 mod (A/d) and 1 mod (B/d) . It is allowed to set `pd = NULL`, in which case, d is still computed, but not saved.

GEN Z_chinese_post(GEN a, GEN b, GEN C, GEN U, GEN d) returns the solution to the chinese remainder problem x congruent to $a \bmod A$ and $b \bmod B$, where C, U, d were set in `Z_chinese_pre`. If d is NULL, assume the problem has a solution. Otherwise, return NULL if it has no solution.

The following pair of functions is used in homomorphic imaging schemes, when reconstructing an integer from its images modulo pairwise coprime integers. The idea is as follows: we want to discover an integer H which satisfies $|H| < B$ for some known bound B ; we are given pairs (H_p, p) with H congruent to $H_p \bmod p$ and all p pairwise coprime.

Given H congruent to H_p modulo a number of p , whose product is q , and a new pair (H_p, p) , p coprime to q , the following incremental functions use the chinese remainder theorem (CRT) to find a new H , congruent to the preceding one modulo q , but also to H_p modulo p . It is defined uniquely modulo qp , and we choose the centered representative. When P is larger than $2B$, we have $H = H$, but of course, the value of H may stabilize sooner. In many applications it is possible to directly check that such a partial result is correct.

`GEN Z_init_CRT(ulong Hp, ulong p)` given a `Fl Hp` in $[0, p-1]$, returns the centered representative H congruent to H_p modulo p .

`int Z_incremental_CRT(GEN *H, ulong Hp, GEN *q, ulong p)` given a `t_INT *H`, centered modulo $*q$, a new pair (H_p, p) with p coprime to q , this function updates $*H$ so that it also becomes congruent to (H_p, p) , and $*q$ to the product $qp = p \cdot *q$. It returns 1 if the new value is equal to the old one, and 0 otherwise.

`GEN chinese1_coprime_Z(GEN v)` an alternative divide-and-conquer implementation: v is a vector of `t_INTMOD` with pairwise coprime moduli. Return the `t_INTMOD` solving the corresponding chinese remainder problem. This is a streamlined version of

`GEN chinese1(GEN v)`, which solves a general chinese remainder problem (not necessarily over \mathbf{Z} , moduli not assumed coprime).

As above, for H a \mathbf{ZM} : we assume that H and all H_p have dimension > 0 . The original $*H$ is destroyed.

`GEN ZM_init_CRT(GEN Hp, ulong p)`

`int ZM_incremental_CRT(GEN *H, GEN Hp, GEN *q, ulong p)`

As above for H a \mathbf{ZX} : note that the degree may increase or decrease. The original $*H$ is destroyed.

`GEN ZX_init_CRT(GEN Hp, ulong p, long v)`

`int ZX_incremental_CRT(GEN *H, GEN Hp, GEN *q, ulong p)`

As above, for H a matrix whose coefficient are \mathbf{ZX} . The original $*H$ is destroyed. The entries of H are not normalized, use `ZX.renormalize` for this.

`GEN ZXM_init_CRT(GEN Hp, long deg, ulong p)` where `deg` is the maximal degree of all the H_p

`int ZXM_incremental_CRT(GEN *H, GEN Hp, GEN *q, ulong p)`

7.3.37 Fast remainders.

The routines in these section are asymptotically fast (quasi-linear time in the input size).

GEN Z_ZV_mod(GEN A, GEN P) given a **t_INT** A and a vector P of positive pairwise coprime integers of length $n \geq 1$, return a vector B of the same length such that $B[i] = A \pmod{P[i]}$ and $0 \leq B[i] < P[i]$ for all $1 \leq i \leq n$. The vector P may be a **t_VEC** or a **t_VECSMALL** (treated as **ulongs**) and B has the same type as P .

GEN Z_nv_mod(GEN A, GEN P) given a **t_INT** A and a **t_VECSMALL** P of positive pairwise coprime integers of length $n \geq 1$, return a **t_VECSMALL** B of the same length such that $B[i] = A \pmod{P[i]}$ and $0 \leq B[i] < P[i]$ for all $1 \leq i \leq n$. The entries of P and B are treated as **ulongs**.

The following low level functions allow precomputations:

GEN ZV_producttree(GEN P) where P is a vector of integers (or **t_VECSMALL**) of length $n \geq 1$, return the vector of **t_VECS** $[f(P), f^2(P), \dots, f^k(P)]$ where f is the transformation $[p_1, p_2, \dots, p_m] \mapsto [p_1 p_2, p_3 p_4, \dots, p_{m-1} p_m]$ if m is even and $[p_1 p_2, p_3 p_4, \dots, p_{m-2} p_{m-1}, p_m]$ if m is odd, and $k = O(\log m)$ is minimal so that $f^k(P)$ has length 1; in other words, $f^k(P) = [p_1 p_2 \dots p_m]$.

GEN Z_ZV_mod_tree(GEN A, GEN P, GEN T) as **Z_ZV_mod** where T is the tree **ZV_producttree**(P).

GEN ZV_nv_mod_tree(GEN A, GEN P, GEN T) A being a **ZV** and P a **t_VECSMALL** of length $n \geq 1$, the elements of P being pairwise coprime, return the vector of **Flv** $[A \pmod{P[1]}, \dots, A \pmod{P[n]}]$, where T is the tree **ZV_producttree**(P).

GEN ZM_nv_mod_tree(GEN A, GEN P, GEN T) A being a **ZM** and P a **t_VECSMALL** of length $n \geq 1$, the elements of P being pairwise coprime, return the vector of **Flm** $[A \pmod{P[1]}, \dots, A \pmod{P[n]}]$, where T is the tree **ZV_producttree**(P).

GEN ZX_nv_mod_tree(GEN A, GEN P, GEN T) A being a **ZX** and P a **t_VECSMALL** of length $n \geq 1$, the elements of P being pairwise coprime, return the vector of **Flx** polynomials $[A \pmod{P[1]}, \dots, A \pmod{P[n]}]$, where T is the tree **ZV_producttree**(P).

GEN ZXC_nv_mod_tree(GEN A, GEN P, GEN T) A being a **ZXC** and P a **t_VECSMALL** of length $n \geq 1$, the elements of P being pairwise coprime, return the vector of **FlxC** $[A \pmod{P[1]}, \dots, A \pmod{P[n]}]$, where T is the tree **ZV_producttree**(P).

GEN ZXM_nv_mod_tree(GEN A, GEN P, GEN T) A being a **ZXM** and P a **t_VECSMALL** of length $n \geq 1$, the elements of P being pairwise coprime, return the vector of **FlxM** $[A \pmod{P[1]}, \dots, A \pmod{P[n]}]$, where T is the tree **ZV_producttree**(P).

GEN ZXX_nv_mod_tree(GEN A, GEN P, GEN T, long v) A being a **ZXX**, and P a **t_VECSMALL** of length $n \geq 1$, the elements of P being pairwise coprime, return the vector of **FlxX** $[A \pmod{P[1]}, \dots, A \pmod{P[n]}]$, where T is assumed to be the tree created by **ZV_producttree**(P).

7.3.38 Fast Chinese remainder theorem over \mathbb{Z} . The routines in these section are asymptotically fast (quasi-linear time in the input size) and should be used whenever the moduli are known from the start.

The simplest function is

GEN ZV_chinese(GEN A, GEN P, GEN *pM) let P be a vector of positive pairwise coprime integers, let A be a vector of integers of the same length $n \geq 1$ such that $0 \leq A[i] < P[i]$ for all i , and let M be the product of the elements of P . Returns the integer in $[0, M[$ congruent to $A[i] \bmod P[i]$ for all $1 \leq i \leq n$. If pM is not NULL, set *pM to M . We also allow t_VECSMALLs for A and P (seen as vectors of unsigned integers).

GEN ZV_chinese_center(GEN A, GEN P, GEN *pM) As ZV_chinese but return integers in $[-M/2, M/2[$ instead.

The following functions allow to solve many Chinese remainder problems simultaneously, for a given set of moduli:

GEN nxV_chinese_center(GEN A, GEN P, GEN *pt_mod) where A is a vector of nx and P a t_VECSMALL of the same length $n \geq 1$, the elements of P being pairwise coprime, and M being the product of the elements of P , returns the t_POL whose entries are integers in $[-M/2, M/2[$ congruent to $A[i] \bmod P[i]$ for all $1 \leq i \leq n$. If pt_mod is not NULL, set *pt_mod to M .

GEN ncV_chinese_center(GEN A, GEN P, GEN *pM) where A is a vector of VECSMALLs (seen as vectors of unsigned integers) and P a t_VECSMALL of the same length $n \geq 1$, the elements of P being pairwise coprime, and M being the product of the elements of P , returns the t_COL whose entries are integers in $[-M/2, M/2[$ congruent to $A[i] \bmod P[i]$ for all $1 \leq i \leq n$. If pM is not NULL, set *pt_mod to M .

GEN nmV_chinese_center(GEN A, GEN P, GEN *pM) where A is a vector of MATSMALLs (seen as matrices of unsigned integers) and P a t_VECSMALL of the same length $n \geq 1$, the elements of P being pairwise coprime, and M being the product of the elements of P , returns the matrix whose entries are integers in $[-M/2, M/2[$ congruent to $A[i] \bmod P[i]$ for all $1 \leq i \leq n$. If pM is not NULL, set *pM to M . N.B.: this function uses the parallel GP interface.

GEN nxCV_chinese_center(GEN A, GEN P, GEN *pM) where A is a vector of nxCs and P a t_VECSMALL of the same length $n \geq 1$, the elements of P being pairwise coprime, and M being the product of the elements of P , returns the t_COL whose entries are integers in $[-M/2, M/2[$ congruent to $A[i] \bmod P[i]$ for all $1 \leq i \leq n$. If pM is not NULL, set *pt_mod to M .

GEN nxMV_chinese_center(GEN A, GEN P, GEN *pM) where A is a vector of nxMs and P a t_VECSMALL of the same length $n \geq 1$, the elements of P being pairwise coprime, and M being the product of the elements of P , returns the matrix whose entries are integers in $[-M/2, M/2[$ congruent to $A[i] \bmod P[i]$ for all $1 \leq i \leq n$. If pM is not NULL, set *pM to M . N.B.: this function uses the parallel GP interface.

The other routines allow for various precomputations :

GEN ZV_chinesetree(GEN P, GEN T) given P a vector of integers (or t_VECSMALL) and a product tree T from ZV_producttree(P) for the same P , return a “chinese remainder tree” R , preconditionning the solution of Chinese remainder problems modulo the $P[i]$.

GEN ZV_chinese_tree(GEN A, GEN P, GEN T, GEN R) return ZV_chinese(A, P, NULL), where T is created by ZV_producttree(P) and R by ZV_chinesetree(P, T).

GEN `ncV_chinese_center_tree`(GEN A, GEN P, GEN T, GEN R) as `ncV_chinese_center` where T is assumed to be the tree created by `ZV_producttree(P)` and R by `ZV_chinesetree(P, T)`.

GEN `nmV_chinese_center_tree`(GEN A, GEN P, GEN T, GEN R) as `nmV_chinese_center` where T is assumed to be the tree created by `ZV_producttree(P)` and R by `ZV_chinesetree(P, T)`.

GEN `nxV_chinese_center_tree`(GEN A, GEN P, GEN T, GEN R) as `nxV_chinese_center` where T is assumed to be the tree created by `ZV_producttree(P)` and R by `ZV_chinesetree(P, T)`.

GEN `nxCV_chinese_center_tree`(GEN A, GEN P, GEN T, GEN R) as `nxCV_chinese_center` where T is assumed to be the tree created by `ZV_producttree(P)` and R by `ZV_chinesetree(P, T)`.

7.3.39 Rational reconstruction.

`int Fp_ratlift`(GEN x, GEN m, GEN amax, GEN bmax, GEN *a, GEN *b). Assuming that $0 \leq x < m$, $\text{amax} \geq 0$, and $\text{bmax} > 0$ are `t_INTs`, and that $2\text{amaxbmax} < m$, attempts to recognize x as a rational a/b , i.e. to find `t_INTs` a and b such that

- $a \equiv bx \text{ modulo } m$,
- $|a| \leq \text{amax}$, $0 < b \leq \text{bmax}$,
- $\gcd(m, b) = \gcd(a, b)$.

If unsuccessful, the routine returns 0 and leaves a , b unchanged; otherwise it returns 1 and sets a and b .

In almost all applications, we actually know that a solution exists, as well as a nonzero multiple B of b , and $m = p^\ell$ is a prime power, for a prime p chosen coprime to B hence to b . Under the single assumption $\gcd(m, b) = 1$, if a solution a, b exists satisfying the three conditions above, then it is unique.

GEN `FpM_ratlift`(GEN M, GEN m, GEN amax, GEN bmax, GEN denom) given an `FpM` modulo m with reduced or `Fp_center`-ed entries, reconstructs a matrix with rational coefficients by applying `Fp_ratlift` to all entries. Assume that all preconditions for `Fp_ratlift` are satisfied, as well $\gcd(m, b) = 1$ (so that the solution is unique if it exists). Return `NULL` if the reconstruction fails, and the rational matrix otherwise. If `denom` is not `NULL` check further that all denominators divide `denom`.

The function is not stack clean if one of the coefficients of M is negative (centered residues), but still suitable for `gerepileupto`.

GEN `FpX_ratlift`(GEN P, GEN m, GEN amax, GEN bmax, GEN denom) as `FpM_ratlift`, where P is an `FpX`.

GEN `FpC_ratlift`(GEN P, GEN m, GEN amax, GEN bmax, GEN denom) as `FpM_ratlift`, where P is an `FpC`.

7.3.40 Zp.

GEN Zp_invlift(GEN b, GEN a, GEN p, long e) let p be a prime $\mathbf{t_INT}$, a be a $\mathbf{t_INT}$ and b a $\mathbf{t_INT}$ such that $ab \equiv 1 \pmod{p}$. Returns an $\mathbf{t_INT}$ A such that $A \equiv a^{-1} \pmod{p}$ and $Ab \equiv 1 \pmod{p^e}$.

GEN Zp_inv(GEN b, GEN p, long e) let p be a prime $\mathbf{t_INT}$ and b be a $\mathbf{t_INT}$ Returns an $\mathbf{t_INT}$ A such that $Ab \equiv 1 \pmod{p^e}$.

GEN Zp_div(GEN a, GEN b, GEN p, long e) let p be a prime $\mathbf{t_INT}$ and a and b be a $\mathbf{t_INT}$ Returns an $\mathbf{t_INT}$ c such that $cb \equiv a \pmod{p^e}$.

GEN Zp_sqrt(GEN b, GEN p, long e) b and p being $\mathbf{t_INT}$ s, with p a prime (possibly 2), returns a $\mathbf{t_INT}$ a such that $a^2 \equiv b \pmod{p^e}$.

GEN Z2_sqrt(GEN b, long e) b being a $\mathbf{t_INT}$ s returns a $\mathbf{t_INT}$ a such that $a^2 \equiv b \pmod{2^e}$.

GEN Zp_sqrtlift(GEN b, GEN a, GEN p, long e) let a, b, p be $\mathbf{t_INT}$ s, with $p > 2$, such that $a^2 \equiv b \pmod{p}$. Returns a $\mathbf{t_INT}$ A such that $A^2 \equiv b \pmod{p^e}$. Special case of Zp_sqrtnlift.

GEN Zp_sqrtnlift(GEN b, GEN n, GEN a, GEN p, long e) let a, b, n, p be $\mathbf{t_INT}$ s, with $n, p > 1$, and p coprime to n , such that $a^n \equiv b \pmod{p}$. Returns a $\mathbf{t_INT}$ A such that $A^n \equiv b \pmod{p^e}$. Special case of ZpX_liftroot.

GEN Zp_teichmuller(GEN x, GEN p, long e, GEN pe) for p an odd prime, x a $\mathbf{t_INT}$ coprime to p , and $pe = p^e$, returns the $(p-1)$ -th root of 1 congruent to x modulo p , modulo p^e . For convenience, $p = 2$ is also allowed and we return 1 (x is 1 mod 4) or $2^e - 1$ (x is 3 mod 4).

GEN teichmullerinit(long p, long n) returns the values of Zp_teichmuller at all $x = 1, \dots, p-1$.

GEN Zp_exp(GEN z, GEN p, ulong e) given a $\mathbf{t_INT}$ z (preferably reduced mod p^e), return $\exp_p(a) \pmod{p^e}$ ($\mathbf{t_INT}$).

GEN Zp_log(GEN z, GEN p, ulong e) given a $\mathbf{t_INT}$ z (preferably reduced mod p^e), such that $a \equiv 1 \pmod{p}$, return $\log_p(a) \pmod{p^e}$ ($\mathbf{t_INT}$).

7.3.41 ZpM.

GEN ZpM_invlift(GEN M, GEN Np, GEN p, long e) let p be a prime $\mathbf{t_INT}$, Np be a \mathbf{FpM} (modulo p) and M a \mathbf{ZpM} such that $MNp \equiv 1 \pmod{p}$. Returns an \mathbf{ZpM} N such that $N \equiv Np^{-1} \pmod{p}$ and $MN \equiv 1 \pmod{p^e}$.

7.3.42 ZpX.

GEN ZpX_roots(GEN f, GEN p, long e) f a \mathbf{ZX} with leading term prime to p , and without multiple roots mod p . Return a vector of $\mathbf{t_INT}$ s which are the roots of $f \pmod{p^e}$.

GEN ZpX_liftroot(GEN f, GEN a, GEN p, long e) f a \mathbf{ZX} with leading term prime to p , and a a root mod p such that $v_p(f'(a)) = 0$. Return a $\mathbf{t_INT}$ which is the root of $f \pmod{p^e}$ congruent to $a \pmod{p}$.

GEN ZX_Zp_root(GEN f, GEN a, GEN p, long e) same as ZpX_liftroot without the assumption $v_p(f'(a)) = 0$. Return a $\mathbf{t_VEC}$ of $\mathbf{t_INT}$ s, which are the p -adic roots of f congruent to $a \pmod{p}$ (given modulo p^e). Assume that $0 \leq a < p$.

GEN ZpX_liftroots(GEN f, GEN S, GEN p, long e) f a \mathbf{ZX} with leading term prime to p , and S a vector of simple roots mod p . Return a vector of $\mathbf{t_INT}$ s which are the root of $f \pmod{p^e}$ congruent to the $S[i] \pmod{p}$.

`GEN ZpX_liftfact(GEN A, GEN B, GEN pe, GEN p, long e)` is the routine underlying `pol-hensellift`. Here, p is prime defines a finite field \mathbf{F}_p . A is a polynomial in $\mathbf{Z}[X]$, whose leading coefficient is nonzero in \mathbf{F}_p . B is a vector of monic $\mathbf{F}_p[X]$, pairwise coprime in $\mathbf{F}_p[X]$, whose product is congruent to $A/\text{lc}(A)$ in $\mathbf{F}_p[X]$. Lifts the elements of $B \bmod p = p^e$.

`GEN ZpX_Frobenius(GEN T, GEN p, ulong e)` returns the p -adic lift of the Frobenius automorphism of $\mathbf{F}_p[X]/(T)$ to precision e .

`long ZpX_disc_val(GEN f, GEN p)` returns the valuation at p of the discriminant of f . Assume that f is a monic *separable* ZX and that p is a prime number. Proceeds by dynamically increasing the p -adic accuracy; infinite loop if the discriminant of f is 0.

`long ZpX_resultant_val(GEN f, GEN g, GEN p, long M)` returns the valuation at p of $\text{Res}(f, g)$. Assume f, g are both ZX, and that p is a prime number coprime to the leading coefficient of f . Proceeds by dynamically increasing the p -adic accuracy. To avoid an infinite loop when the resultant is 0, we return M if the Sylvester matrix mod p^M still does not have maximal rank.

`GEN ZpX_gcd(GEN f, GEN g, GEN p, GEN pm)` f a monic ZX, g a ZX, $pm = p^m$ a prime power. There is a unique integer $r \geq 0$ and a monic $h \in \mathbf{Q}_p[X]$ such that

$$p^r h \mathbf{Z}_p[X] + p^m \mathbf{Z}_p[X] = f \mathbf{Z}_p[X] + g \mathbf{Z}_p[X] + p^m \mathbf{Z}_p[X].$$

Return the 0 polynomial if $r \geq m$ and a monic $h \in \mathbf{Z}[1/p][X]$ otherwise (whose valuation at p is $> -m$).

`GEN ZpX_reduced_resultant(GEN f, GEN g, GEN p, GEN pm)` f a monic ZX, g a ZX, $pm = p^m$ a prime power. The p -adic *reduced resultant* of f and g is 0 if f, g not coprime in $\mathbf{Z}_p[X]$, and otherwise the generator of the form p^d of

$$(f \mathbf{Z}_p[X] + g \mathbf{Z}_p[X]) \cap \mathbf{Z}_p.$$

Return the reduced resultant modulo p^m .

`GEN ZpX_reduced_resultant_fast(GEN f, GEN g, GEN p, long M)` f a monic ZX, g a ZX, p a prime. Returns the p -adic reduced resultant of f and g modulo p^M . This function computes resultants for a sequence of increasing p -adic accuracies (up to M p -adic digits), returning as soon as it obtains a nonzero result. It is very inefficient when the resultant is 0, but otherwise usually more efficient than computations using a priori bounds.

`GEN ZpX_monice_factor(GEN f, GEN p, long M)` f a monic ZX, p a prime, return the p -adic factorization of f , modulo p^M . This is the underlying low-level recursive function behind `factorpadic` (using a combination of Round 4 factorization and Hensel lifting); the factors are not sorted and the function is not `gerepile-clean`.

`GEN ZpX_primedec(GEN T, GEN p)` T a monic separable ZX, p a prime, return as a factorization matrix the shape of the prime ideal decomposition of (p) in $\mathbf{Q}[X]/(T)$: the first column contains inertia degrees, the second columns contains ramification degrees.

7.3.43 ZpXQ.

`GEN ZpXQ_invlift(GEN b, GEN a, GEN T, GEN p, long e)` let p be a prime `t_INT`, a be a `FpXQ` (modulo (p, T)) and b a `ZpXQ` such that $ab \equiv 1 \pmod{(p, T)}$. Returns an `ZpXQ` A such that $A \equiv a \pmod{p}$ and $Ab \equiv 1 \pmod{(p^e, T)}$.

`GEN ZpXQ_inv(GEN b, GEN T, GEN p, long e)` let p be a prime `t_INT` and b be a `FpXQ` (modulo T, p^e). Returns an `FpXQ` A such that $Ab \equiv 1 \pmod{(p^e, T)}$.

`GEN ZpXQ_div(GEN a, GEN b, GEN T, GEN q, GEN p, long e)` let p be a prime `t_INT` and a and b be a `FpXQ` (modulo T, p^e). Returns an `FpXQ` c such that $cb \equiv a \pmod{(p^e, T)}$. The parameter q must be equal to p^e .

`GEN ZpXQ_sqrtnlift(GEN b, GEN n, GEN a, GEN T, GEN p, long e)` let n, p be `t_INT`s, with $n, p > 1$ and p coprime to n , and a, b be `FpXQ`s (modulo T) such that $a^n \equiv b \pmod{(p, T)}$. Returns an `Fq` A such that $A^n \equiv b \pmod{(p^e, T)}$.

`GEN ZpXQ_sqrt(GEN b, GEN T, GEN p, long e)` let p being a odd prime and b be a `FpXQ` (modulo T, p^e), returns a such that $a^2 \equiv b \pmod{(p^e, T)}$.

`GEN ZpX_ZpXQ_liftroot(GEN f, GEN a, GEN T, GEN p, long e)` as `ZpXQX_liftroot`, but f is a polynomial in $\mathbf{Z}[X]$.

`GEN ZpX_ZpXQ_liftroot_ea(GEN f, GEN a, GEN T, GEN p, long e, void *E, GEN early(void *E, GEN x, GEN q))` as `ZpX_ZpXQ_liftroot` with early abort: the function `early(E, x, q)` will be called with x is a root of f modulo $q = p^n$ for some n . If `early` returns a non-NULL value z , the function returns z immediately.

`GEN ZpXQ_log(GEN a, GEN T, GEN p, long e)` T being a `ZpX` irreducible modulo p , return the logarithm of a in $\mathbf{Z}_p[X]/(T)$ to precision e , assuming that $a \equiv 1 \pmod{p\mathbf{Z}_p[X]}$ if p odd or $a \equiv 1 \pmod{4\mathbf{Z}_2[X]}$ if $p = 2$.

7.3.44 Zq.

`GEN Zq_sqrtnlift(GEN b, GEN n, GEN a, GEN T, GEN p, long e)`

7.3.45 ZpXQM.

`GEN ZpXQM_prodFrobenius(GEN M, GEN T, GEN p, long e)` returns the product of matrices $M\sigma(M)\sigma^2(M)\dots\sigma^{n-1}(M)$ to precision e where σ is the lift of the Frobenius automorphism over $\mathbf{Z}_p[X]/(T)$ and n is the degree of T .

7.3.46 ZpXQX.

`GEN ZpXQX_liftfact(GEN A, GEN B, GEN T, GEN pe, GEN p, long e)` is the routine underlying `polhensellift`. Here, p is prime, $T(Y)$ defines a finite field \mathbf{F}_q . A is a polynomial in $\mathbf{Z}[X, Y]$, whose leading coefficient is nonzero in \mathbf{F}_q . B is a vector of monic or `FqX`, pairwise coprime in $\mathbf{F}_q[X]$, whose product is congruent to $A/\text{lc}(A)$ in $\mathbf{F}_q[X]$. Lifts the elements of $B \pmod{pe = p^e}$, such that the congruence now holds $\pmod{(T, p^e)}$.

`GEN ZpXQX_liftroot(GEN f, GEN a, GEN T, GEN p, long e)` as `ZpX_liftroot`, but f is now a polynomial in $\mathbf{Z}[X, Y]$ and lift the root a in the unramified extension of \mathbf{Q}_p with residue field $\mathbf{F}_p[Y]/(T)$, assuming $v_p(f(a)) > 0$ and $v_p(f'(a)) = 0$.

GEN ZpXQX_liftroot_vald(GEN f, GEN a, long v, GEN T, GEN p, long e) returns the roots of f as ZpXQX_liftroot, where v is the valuation of the content of f' and it is required that $v_p(f(a)) > v$ and $v_p(f'(a)) = v$.

GEN ZpXQX_roots(GEN F, GEN T, GEN p, long e)

GEN ZpXQX_liftroots(GEN F, GEN S, GEN T, GEN p, long e)

GEN ZpXQX_divrem(GEN x, GEN Sp, GEN T, GEN q, GEN p, long e, GEN *pr) as FpXQX_divrem. The parameter q must be equal to p^e .

GEN ZpXQX_digits(GEN x, GEN B, GEN T, GEN q, GEN p, long e) As FpXQX_digits. The parameter q must be equal to p^e .

GEN ZpXQX_ZpXQX_liftroot(GEN f, GEN a, GEN S, GEN T, GEN p, long e) as ZpXQX_liftroot, except that a is an element of $\mathbf{Z}_p[X, Y]/(S(X, Y), T(X))$.

7.3.47 ZqX. ZqX are either ZpX or ZpXQX depending whether T is NULL or not.

GEN ZqX_roots(GEN F, GEN T, GEN p, long e)

GEN ZqX_liftfact(GEN A, GEN B, GEN T, GEN pe, GEN p, long e)

GEN ZqX_liftroot(GEN f, GEN a, GEN T, GEN p, long e)

GEN ZqX_ZqXQX_liftroot(GEN f, GEN a, GEN P, GEN T, GEN p, long e)

7.3.48 Other p -adic functions.

GEN ZpM_echelon(GEN M, long early_abort, GEN p, GEN pm) given a ZM M , a prime p and $pm = p^m$, returns an echelon form E for $M \bmod p^m$. I.e. there exist a square integral matrix U with $\det U$ coprime to p such that $E = MU$ modulo p^m . If $early_abort$ is nonzero, return NULL as soon as one pivot in the echelon form is divisible by p^m . The echelon form is an upper triangular HNF, we do not waste time to reduce it to Gauss-Jordan form.

GEN zlm_echelon(GEN M, long early_abort, ulong p, ulong pm) variant of ZpM_echelon, for a Zlm M .

GEN Zlm_gauss(GEN a, GEN b, ulong p, long e, GEN C) as gauss with the following peculiarities: a and b are ZM, such that a is invertible modulo p . Optional C is an Flm that is an inverse of $a \bmod p$ or NULL. Return the matrix x such that $ax = b \bmod p^e$ and all elements of x are in $[0, p^e - 1]$. For efficiency, it is better to reduce a and $b \bmod p^e$ first.

GEN padic_to_Q(GEN x) truncate the t_PADIC to a t_INT or t_FRAC.

GEN padic_to_Q_shallow(GEN x) shallow version of padic_to_Q

GEN QpV_to_QV(GEN v) apply padic_to_Q_shallow

long padicprec(GEN x, GEN p) returns the absolute p -adic precision of the object x , by definition the minimum precision of the components of x . For a nonzero t_PADIC, this returns $\text{valp}(x) + \text{precp}(x)$.

long padicprec_relative(GEN x) returns the relative p -adic precision of the t_INT, t_FRAC, or t_PADIC x (minimum precision of the components of x for t_POL or vector/matrices). For a t_PADIC, this returns $\text{precp}(x)$ if $x \neq 0$, and 0 for $x = 0$.

7.3.48.1 low-level.

The following technical function returns an optimal sequence of p -adic accuracies, for a given target accuracy:

`ulong quadratic_prec_mask(long n)` we want to reach accuracy $n \geq 1$, starting from accuracy 1, using a quadratically convergent, self-correcting, algorithm; in other words, from inputs correct to accuracy l one iteration outputs a result correct to accuracy $2l$. For instance, to reach $n = 9$, we want to use accuracies $[1, 2, 3, 5, 9]$ instead of $[1, 2, 4, 8, 9]$. The idea is to essentially double the accuracy at each step, and not overshoot in the end.

Let $a_0 = 1, a_1 = 2, \dots, a_k = n$, be the desired sequence of accuracies. To obtain it, we work backwards and set

$$a_k = n, \quad a_{i-1} = (a_i + 1) \setminus 2.$$

This is in essence what the function returns. But we do not want to store the a_i explicitly, even as a `t_VECSMALL`, since this would leave an object on the stack. Instead, we store a_i implicitly in a bitmask `MASK`: let $a_0 = 1$, if the i -th bit of the mask is set, set $a_{i+1} = 2a_i - 1$, and $2a_i$ otherwise; in short the bits indicate the places where we do something special and do not quite double the accuracy (which would be the straightforward thing to do).

In fact, to avoid returning separately the mask and the sequence length $k + 1$, the function returns `MASK + 2k+1`, so the highest bit of the mask indicates the length of the sequence, and the following ones give an algorithm to obtain the accuracies. This is much simpler than it sounds, here is what it looks like in practice:

```
ulong mask = quadratic_prec_mask(n);
long l = 1;
while (mask > 1) {
    /* here, the result is known to accuracy l */
    l = 2*l; if (mask & 1) l--; /* new accuracy l for the iteration */
    mask >>= 1; /* pop low order bit */
    /* ... lift to the new accuracy ... */
}
/* we are done. At this point l = n */
```

We just pop the bits in `mask` starting from the low order bits, stop when `mask` is 1 (that last bit corresponds to the 2^{k+1} that we added to the mask proper). Note that there is nothing specific to Hensel lifts in that function: it would work equally well for an Archimedean Newton iteration.

Note that in practice, we rather use an infinite loop, and insert an

```
if (mask == 1) break;
```

in the middle of the loop: the loop body usually includes preparations for the next iterations (e.g. lifting Bezout coefficients in a quadratic Hensel lift), which are costly and useless in the *last* iteration.

7.3.49 Conversions involving single precision objects.

7.3.49.1 To single precision.

`ulong Rg_to_Fl(GEN z, ulong p)`, z which can be mapped to $\mathbf{Z}/p\mathbf{Z}$: a `t_INT`, a `t_INTMOD` whose modulus is divisible by p , a `t_FRAC` whose denominator is coprime to p , or a `t_PADIC` with underlying prime ℓ satisfying $p = \ell^n$ for some n (less than the accuracy of the input). Returns `lift(z * Mod(1,p))`, normalized, as an `Fl`.

`ulong Rg_to_F2(GEN z)`, as `Rg_to_Fl` for $p = 2$.

`ulong padic_to_Fl(GEN x, ulong p)` special case of `Rg_to_Fl`, for a x a `t_PADIC`.

`GEN RgX_to_F2x(GEN x)`, x a `t_POL`, returns the `F2x` obtained by applying `Rg_to_Fl` coefficientwise.

`GEN RgX_to_Flx(GEN x, ulong p)`, x a `t_POL`, returns the `Flx` obtained by applying `Rg_to_Fl` coefficientwise.

`GEN RgXV_to_FlxV(GEN x, ulong p)`, x a vector, returns the `FlxV` obtained by applying `RgX_to_Flx` coefficientwise.

`GEN Rg_to_F2xq(GEN z, GEN T)`, z a `GEN` which can be mapped to $\mathbf{F}_2[X]/(T)$: anything `Rg_to_Fl` can be applied to, a `t_POL` to which `RgX_to_F2x` can be applied to, a `t_POLMOD` whose modulus is divisible by T (once mapped to a `F2x`), a suitable `t_RFRAC`. Returns z as an `F2xq`, normalized.

`GEN Rg_to_Flxq(GEN z, GEN T, ulong p)`, z a `GEN` which can be mapped to $\mathbf{F}_p[X]/(T)$: anything `Rg_to_Fl` can be applied to, a `t_POL` to which `RgX_to_Flx` can be applied to, a `t_POLMOD` whose modulus is divisible by T (once mapped to a `Flx`), a suitable `t_RFRAC`. Returns z as an `Flxq`, normalized.

`GEN RgX_to_FlxqX(GEN z, GEN T, ulong p)`, z a `GEN` which can be mapped to $\mathbf{F}_p[x]/(T)[X]$: anything `Rg_to_Flxq` can be applied to, a `t_POL` to which `RgX_to_Flx` can be applied to, a `t_POLMOD` whose modulus is divisible by T (once mapped to a `Flx`), a suitable `t_RFRAC`. Returns z as an `FlxqX`, normalized.

`GEN ZX_to_Flx(GEN x, ulong p)` reduce `ZX x` modulo p (yielding an `Flx`). Faster than `RgX_to_Flx`.

`GEN ZV_to_Flv(GEN x, ulong p)` reduce `ZV x` modulo p (yielding an `Flv`).

`GEN ZXV_to_FlxV(GEN v, ulong p)`, as `ZX_to_Flx`, repeatedly called on the vector's coefficients.

`GEN ZXT_to_FlxT(GEN v, ulong p)`, as `ZX_to_Flx`, repeatedly called on the tree leaves.

`GEN ZXX_to_FlxX(GEN B, ulong p, long v)`, as `ZX_to_Flx`, repeatedly called on the polynomial's coefficients.

`GEN zxX_to_FlxX(GEN z, ulong p)` as `zx_to_Flx`, repeatedly called on the polynomial's coefficients.

`GEN ZXXV_to_FlxXV(GEN V, ulong p, long v)`, as `ZXX_to_FlxX`, repeatedly called on the vector's coefficients.

`GEN ZXXT_to_FlxXT(GEN V, ulong p, long v)`, as `ZXX_to_FlxX`, repeatedly called on the tree leaves.

`GEN RgV_to_Flv(GEN x, ulong p)` reduce the `t_VEC/t_COL x` modulo p , yielding a `t_VECSMALL`.

`GEN RgM_to_Flm(GEN x, ulong p)` reduce the `t_MAT x` modulo p .

`GEN ZM_to_Flm(GEN x, ulong p)` reduce `ZM x` modulo p (yielding an `Flm`).

GEN ZXC_to_FlxC(GEN x, ulong p, long sv) reduce ZXC x modulo p (yielding an FlxC). Assume that $sv = \text{evalvarn}(v)$ where v is the variable number of the entries of x . It is allowed for the entries of x to be t_INT.

GEN ZXM_to_FlxM(GEN x, ulong p, long sv) reduce ZXM x modulo p (yielding an FlxM). Assume that $sv = \text{evalvarn}(v)$ where v is the variable number of the entries of x . It is allowed for the entries of x to be t_INT.

GEN ZV_to_zv(GEN z), converts coefficients using itos

GEN ZV_to_nv(GEN z), converts coefficients using itou

GEN ZM_to_zm(GEN z), converts coefficients using itos

7.3.49.2 From single precision.

GEN Flx_to_ZX(GEN z), converts to ZX (t_POL of nonnegative t_INTs in this case)

GEN Flx_to_FlxX(GEN z), converts to FlxX (t_POL of constant Flx in this case).

GEN Flx_to_ZX_inplace(GEN z), same as Flx_to_ZX, in place (z is destroyed).

GEN FlxX_to_ZXX(GEN B), converts an FlxX to a polynomial with ZX or t_INT coefficients (repeated calls to Flx_to_ZX).

GEN FlxXC_to_ZXXC(GEN B), converts an FlxXC to a t_COL with ZXX coefficients (repeated calls to FlxX_to_ZXX).

GEN FlxXM_to_ZXXM(GEN B), converts an FlxXM to a t_MAT with ZXX coefficients (repeated calls to FlxX_to_ZXX).

GEN FlxC_to_ZXC(GEN x), converts a vector of Flx to a column vector of polynomials with t_INT coefficients (repeated calls to Flx_to_ZX).

GEN FlxV_to_ZXV(GEN x), as above but return a t_VEC.

void F2xV_to_FlxV_inplace(GEN v) v is destroyed.

void F2xV_to_ZXV_inplace(GEN v) v is destroyed.

void FlxV_to_ZXV_inplace(GEN v) v is destroyed.

GEN FlxM_to_ZXM(GEN z), converts a matrix of Flx to a matrix of polynomials with t_INT coefficients (repeated calls to Flx_to_ZX).

GEN zx_to_ZX(GEN z), as Flx_to_ZX, without assuming the coefficients to be nonnegative.

GEN zx_to_Flx(GEN z, ulong p) as Flx_red without assuming the coefficients to be nonnegative.

GEN Flc_to_ZC(GEN z), converts to ZC (t_COL of nonnegative t_INTs in this case)

GEN Flc_to_ZC_inplace(GEN z), same as Flc_to_ZC, in place (z is destroyed).

GEN Flv_to_ZV(GEN z), converts to ZV (t_VEC of nonnegative t_INTs in this case)

GEN Flm_to_ZM(GEN z), converts to ZM (t_MAT with nonnegative t_INTs coefficients in this case)

GEN Flm_to_ZM_inplace(GEN z), same as Flm_to_ZM, in place (z is destroyed).

GEN zc_to_ZC(GEN z) as Flc_to_ZC, without assuming coefficients are nonnegative.

GEN zv_to_ZV(GEN z) as Flv_to_ZV, without assuming coefficients are nonnegative.

GEN zm_to_ZM(GEN z) as Flm_to_ZM, without assuming coefficients are nonnegative.

GEN zv_to_Flv(GEN z, ulong p)

GEN zm_to_Flm(GEN z, ulong p)

7.3.49.3 Mixed precision linear algebra. Assumes dimensions are compatible. Multiply a multiprecision object by a single-precision one.

GEN RgM_zc_mul(GEN x, GEN y)

GEN RgMrow_zc_mul(GEN x, GEN y, long i)

GEN RgM_zm_mul(GEN x, GEN y)

GEN RgV_zc_mul(GEN x, GEN y)

GEN RgV_zm_mul(GEN x, GEN y)

GEN ZM_zc_mul(GEN x, GEN y)

GEN zv_ZM_mul(GEN x, GEN y)

GEN ZV_zc_mul(GEN x, GEN y)

GEN ZM_zm_mul(GEN x, GEN y)

GEN ZC_z_mul(GEN x, long y)

GEN ZM_nm_mul(GEN x, GEN y) the entries of y are ulongs.

GEN nm_Z_mul(GEN y, GEN c) the entries of y are ulongs.

7.3.49.4 Miscellaneous involving Fl.

GEN Fl_to_Flx(ulong x, long evx) converts a unsigned long to a scalar Flx. Assume that $evx = evalvarn(vx)$ for some variable number vx .

GEN Z_to_Flx(GEN x, ulong p, long sv) converts a t_INT to a scalar Flx polynomial. Assume that $sv = evalvarn(v)$ for some variable number v .

GEN Flx_to_Flv(GEN x, long n) converts from Flx to Flv with n components (assumed larger than the number of coefficients of x).

GEN zx_to_zv(GEN x, long n) as Flx_to_Flv.

GEN Flv_to_Flx(GEN x, long sv) converts from vector (coefficient array) to (normalized) polynomial in variable v .

GEN zv_to_zx(GEN x, long n) as Flv_to_Flx.

GEN Flm_to_FlxV(GEN x, long sv) converts the columns of Flm x to an array of Flx in the variable v (repeated calls to Flv_to_Flx).

GEN FlxM_to_FlxXV(GEN V, long v) see RgM_to_RgXV

GEN zm_to_zxV(GEN x, long n) as Flm_to_FlxV.

GEN Flm_to_FlxX(GEN x, long sw, long sv) same as Flm_to_FlxV(x, sv) but returns the result as a (normalized) polynomial in variable w .

GEN FlxV_to_Flm(GEN v, long n) reverse Flm_to_FlxV, to obtain an Flm with n rows (repeated calls to Flx_to_Flv).

GEN FlxX_to_Flx(GEN P) Let $P(x, X)$ be a FlxX, return $P(0, X)$ as a Flx.

GEN FlxX_to_Flm(GEN v, long n) reverse Flm_to_FlxX, to obtain an Flm with n rows (repeated calls to Flx_to_Flv).

GEN FlxX_to_FlxC(GEN B, long n, long sv) see RgX_to_RgV. The coefficients of B are assumed to be in the variable v.

GEN FlxV_to_FlxX(GEN x, long v) see RgV_to_RgX.

GEN FlxXV_to_FlxM(GEN V, long n, long sv) see RgXV_to_RgM. The coefficients of $V[i]$ are assumed to be in the variable v.

GEN Fly_to_FlxY(GEN a, long sv) convert coefficients of a to constant Flx in variable v.

7.3.49.5 Miscellaneous involving F2x.

GEN F2x_to_F2v(GEN x, long n) converts from F2x to F2v with n components (assumed larger than the number of coefficients of x).

GEN F2xC_to_ZXC(GEN x), converts a vector of F2x to a column vector of polynomials with t_INT coefficients (repeated calls to F2x_to_ZX).

GEN F2xC_to_FlxC(GEN x)

GEN FlxC_to_F2xC(GEN x)

GEN F2xV_to_F2m(GEN v, long n) F2x_to_F2v to each polynomial to get an F2m with n rows.

7.4 Higher arithmetic over Z: primes, factorization.

7.4.1 Pure powers.

long Z_issquare(GEN n) returns 1 if the t_INT n is a square, and 0 otherwise. This is tested first modulo small prime powers, then sqrtremi is called.

long Z_issquareall(GEN n, GEN *sqrtn) as Z_issquare. If n is indeed a square, set sqrtn to its integer square root. Uses a fast congruence test mod $64 \times 63 \times 65 \times 11$ before computing an integer square root.

long Z_ispow2(GEN x) returns 1 if the t_INT x is a power of 2, and 0 otherwise.

long uissquare(ulong n) as Z_issquare, for an ulong operand n.

long uissquareall(ulong n, ulong *sqrtn) as Z_issquareall, for an ulong operand n.

ulong usqrt(ulong a) returns the floor of the square root of a.

ulong usqrtn(ulong a, ulong n) returns the floor of the n-th root of a.

long Z_ispower(GEN x, ulong k) returns 1 if the t_INT n is a k-th power, and 0 otherwise; assume that $k > 1$.

long Z_ispowerall(GEN x, ulong k, GEN *pt) as Z_ispower. If n is indeed a k-th power, set *pt to its integer k-th root.

long Z_isanypower(GEN x, GEN *ptn) returns the maximal $k \geq 2$ such that the t_INT $x = n^k$ is a perfect power, or 0 if no such k exist; in particular ispower(1), ispower(0), ispower(-1) all return 0. If the return value k is not 0 (so that $x = n^k$) and ptn is not NULL, set *ptn to n.

The following low-level functions are called by `Z_isanypower` but can be directly useful:

`int is_357_power(GEN x, GEN *ptn, ulong *pmask)` tests whether the integer $x > 0$ is a 3-rd, 5-th or 7-th power. The bits of `*mask` initially indicate which test is to be performed; bit 0: 3-rd, bit 1: 5-th, bit 2: 7-th (e.g. `*pmask = 7` performs all tests). They are updated during the call: if the “ i -th power” bit is set to 0 then x is not a k -th power. The function returns 0 (not a 3-rd, 5-th or 7-th power), 3 (3-rd power, not a 5-th or 7-th power), 5 (5-th power, not a 7-th power), or 7 (7-th power); if an i -th power bit is initially set to 0, we take it at face value and assume x is not an i -th power without performing any test. If the return value k is nonzero, set `*ptn` to n such that $x = n^k$.

`int is_pth_power(GEN x, GEN *ptn, forprime_t *T, ulong cutoff)` let $x > 0$ be an integer, `cutoff` > 0 and T be an iterator over primes ≥ 11 , we look for the smallest prime p such that $x = n^p$ (advancing T as we go along). The 11 is due to the fact that `is_357_power` and `issquare` are faster than the generic version for $p < 11$.

Fail and return 0 when the existence of p would imply $2^{\text{cutoff}} > x^{1/p}$, meaning that a possible n is so small that it should have been found by trial division; for maximal speed, you should start by a round of trial division, but the cut-off may also be set to 1 for a rigorous result without any trial division.

Otherwise returns the smallest suitable prime power p^i and set `*ptn` to the p^i -th root of x (which is now not a p -th power). We may immediately recall the function with the same parameters after setting $x = \text{*ptn}$: it will start at the next prime.

7.4.2 Factorization.

`GEN Z_factor(GEN n)` factors the `t_INT` n . The “primes” in the factorization are actually strong pseudoprimes.

`GEN absZ_factor(GEN n)` returns `Z_factor(absi(n))`.

`long Z_issmooth(GEN n, ulong lim)` returns 1 if all the prime factors of the `t_INT` n are less or equal to lim .

`GEN Z_issmooth_fact(GEN n, ulong lim)` returns NULL if a prime factor of the `t_INT` n is $> lim$, and returns the factorization of n otherwise, as a `t_MAT` with `t_VECSMALL` columns (word-size primes and exponents). Neither memory-clean nor suitable for `gerepileupto`.

`GEN Z_factor_until(GEN n, GEN lim)` as `Z_factor`, but stop the factorization process as soon as the unfactored part is smaller than lim . The resulting factorization matrix only contains the factors found. No other assumptions can be made on the remaining factors.

`GEN Z_factor_limit(GEN n, ulong lim)` trial divide n by all primes $p < lim$ in the precomputed list of prime numbers and the `addprimes` prime table. Return the corresponding factorization matrix. The first column of the factorization matrix may contain a single composite, which may or may not be the last entry in presence of a prime table.

If $lim = 0$, the effect is the same as setting $lim = \text{maxprime}() + 1$: use all precomputed primes.

`GEN absZ_factor_limit(GEN n, ulong all)` returns `Z_factor_limit(absi(n))`.

`GEN absZ_factor_limit_strict(GEN n, ulong lim, GEN *pU)`. This function is analogous to `absZ_factor_limit`, with a better interface: trial divide n by all primes $p < lim$ (supposedly in the precomputed list of prime numbers, but lim may be larger) and then the full `addprimes`

prime table (whatever their size). Return the corresponding factorization matrix. In this case, a composite cofactor is *not* included.

If `pU` is not `NULL`, set it to the cofactor, which is either `NULL` (no cofactor) or $[q, k]$, where $q > \text{lim}$ and $k > 0$. The prime divisors of q are greater than `lim` and not in the `addprimes` table, q is not a pure power, and q^k is the largest power of q dividing n . It may happen that q is prime.

`GEN boundfact(GEN x, ulong lim)` as `Z_factor_limit`, applying to `t_INT` or `t_FRAC` inputs.

`GEN Z_smoother(GEN n, GEN L, GEN *pP, GEN *pE)` given a `t_VEC` L containing a list of primes and a `t_INT` n , trial divide n by the elements of L and return the cofactor. Return `NULL` if the cofactor is ± 1 . `*P` and `*E` contain the list of prime divisors found and their exponents, as `t_VECSMALLs`. Neither memory-clean, nor suitable for `gerepileupto`.

`GEN Z_lsmoother(GEN n, GEN L, GEN *pP, GEN *pE)` as `Z_smoother` where L is a `t_VECSMALL` of small primes and both `*P` and `*E` are given as `t_VECSMALL`.

`GEN Z_factor_listP(GEN N, GEN L)` given a `t_INT` N , a vector or primes L containing all prime divisors of N (and possibly others). Return `factor(N)`. Neither memory-clean, nor suitable for `gerepileupto`.

`GEN factor_pn_1(GEN p, ulong n)` returns the factorization of $p^n - 1$, where p is prime and n is a positive integer.

`GEN factor_pn_1_limit(GEN p, ulong n, ulong B)` returns a partial factorization of $p^n - 1$, where p is prime and n is a positive integer. Don't actively search for prime divisors $p > B$, but we may find still find some due to Aurifeuillian factorizations. Any entry $> B^2$ in the output factorization matrix is *a priori* not a prime (but may well be).

`GEN factor_Aurifeuille_prime(GEN p, long n)` an Aurifeuillian factor of $\phi_n(p)$, assuming p prime and an Aurifeuillian factor exists ($p\zeta_n$ is a square in $\mathbf{Q}(\zeta_n)$).

`GEN factor_Aurifeuille(GEN a, long n)` an Aurifeuillian factor of $\phi_n(a)$, assuming a is a nonzero integer and $n > 2$. Returns 1 if no Aurifeuillian factor exists.

`GEN odd_prime_divisors(GEN a)` `t_VEC` of all prime divisors of the `t_INT` a .

`GEN factoru(ulong n)`, returns the factorization of n . The result is a 2-component vector $[P, E]$, where P and E are `t_VECSMALL` containing the prime divisors of n , and the $v_p(n)$.

`GEN factoru_pow(ulong n)`, returns the factorization of n . The result is a 3-component vector $[P, E, C]$, where P , E and C are `t_VECSMALL` containing the prime divisors of n , the $v_p(n)$ and the $p^{v_p(n)}$.

`GEN vecfactoru(ulong a, ulong b)`, returns a `t_VEC` v containing the factorizations (`factoru` format) of a, \dots, b ; assume that $b \geq a > 0$. Uses a sieve with primes up to \sqrt{b} . For all c , $a \leq c \leq b$, the factorization of c is given in $v[c - a + 1]$.

`GEN vecfactoroddu(ulong a, ulong b)`, returns a `t_VEC` v containing the factorizations (`factoru` format) of odd integers in a, \dots, b ; assume that $b \geq a > 0$ are odd. Uses a sieve with primes up to \sqrt{b} . For all odd c , $a \leq c \leq b$, the factorization of c is given in $v[(c - a)/2 + 1]$.

`GEN vecfactoru_i(ulong a, ulong b)`, private version of `vecfactoru`, not memory clean.

`GEN vecfactoroddu_i(ulong a, ulong b)`, private version of `vecfactoroddu`, not memory clean.

`GEN vecfactorsquarefreeu(ulong a, ulong b)` return a `t_VEC` v containing the prime divisors of squarefree integers in a, \dots, b ; assume that $a \leq b$. Uses a sieve with primes up to \sqrt{b} . For all

squarefree c , $a \leq c \leq b$, the prime divisors of c (as a `t_VECSMALL`) are given in $v[c - a + 1]$, and the other entries are `NULL`. Note that because of these `NULL` markers, v is not a valid `GEN`, it is not memory clean and cannot be used in garbage collection routines.

`GEN vecfactorsquarefreeu_coprime(ulong a, ulong b, GEN P)` given a *sorted* `t_VECSMALL` of primes P , return a `t_VEC` v containing the prime divisors of squarefree integers in a, \dots, b coprime to the elements of P ; assume that $a \leq b$. Uses a sieve with primes up to \sqrt{b} . For all squarefree c , $a \leq c \leq b$, the prime divisors of c (as a `t_VECSMALL`) are given in $v[c - a + 1]$, and the other entries are `NULL`. Note that because of these `NULL` markers, v is not a valid `GEN`, it is not memory clean and cannot be used in garbage collection routines.

`GEN vecsquarefreeu(ulong a, ulong b)` return a `t_VECSMALL` v containing the squarefree integers in a, \dots, b . Assume that $a \leq b$. Uses a sieve with primes up to \sqrt{b} .

`ulong tridiv_bound(GEN n)` returns the trial division bound used by `Z_factor(n)`.

`GEN tridiv_boundu(ulong n)` returns the trial division bound used by `factorun`.

`GEN Z_pollardbrent(GEN N, long n, long seed)` try to factor `t_INT` N using $n \geq 1$ rounds of Pollard iterations; *seed* is an integer whose value (mod 8) selects the quadratic polynomial use to generate Pollard's (pseudo)random walk. Returns `NULL` on failure, else a vector of 2 (possibly 3) integers whose product is N .

`GEN Z_ECM(GEN N, long n, long seed, ulong B1)` try to factor `t_INT` N using $n \geq 1$ rounds of ECM iterations (on 8 to 64 curves simultaneously, depending on the size of N); *seed* is an integer whose value selects the curves to be used: increase it by $64n$ to make sure that a subsequent call with a factor of N uses a disjoint set of curves. Finally $B_1 > 7$ determines the computations performed on the curves: we compute $[k]P$ for some point in $E(\mathbf{Z}/N\mathbf{Z})$ and $k = q \prod p^{e_p}$ where $p^{e_p} \leq B_1$ and $q \leq B_2 := 110B_1$; a higher value of B_1 means higher chances of hitting a factor and more time spent. The computation is deterministic for a given set of parameters. Returns `NULL` on failure, else a nontrivial factor or N .

`GEN Q_factor(GEN x)` as `Z_factor`, where x is a `t_INT` or a `t_FRAC`.

`GEN Q_factor_limit(GEN x, ulong lim)` as `Z_factor_limit`, where x is a `t_INT` or a `t_FRAC`.

7.4.3 Coprime factorization.

Given a and b two nonzero integers, let **ppi**(a, b), **ppo**(a, b), **ppg**(a, b), **pple**(a, b) (powers in a of primes inside b , outside b , greater than those in b , less than or equal to those in b) be the integers defined by

- $v_p(\text{ppi}) = v_p(a)[v_p(b) > 0]$,
- $v_p(\text{ppo}) = v_p(a)[v_p(b) = 0]$,
- $v_p(\text{ppg}) = v_p(a)[v_p(a) > v_p(b)]$,
- $v_p(\text{pple}) = v_p(a)[v_p(a) \leq v_p(b)]$.

`GEN Z_ppo(GEN a, GEN b)` returns **ppo**(a, b); shallow function.

`ulong u_ppo(ulong a, ulong b)` returns **ppo**(a, b).

`GEN Z_ppgle(GEN a, GEN b)` returns [**ppg**(a, b), **pple**(a, b)]; shallow function.

`GEN Z_ppio(GEN a, GEN b)` returns [**gcd**(a, b), **ppi**(a, b), **ppo**(a, b)]; shallow function.

GEN Z_cba(GEN *a*, GEN *b*) fast natural coprime base algorithm. Returns a vector of coprime divisors of *a* and *b* such that both *a* and *b* can be multiplicatively generated from this set. Perfect powers are not removed, use **Z_isanypower** if needed; shallow function.

GEN ZV_cba_extend(GEN *P*, GEN *b*) extend a coprime basis *P* by the integer *b*, the result being a coprime basis for $P \cup \{b\}$. Perfect powers are not removed; shallow function.

GEN ZV_cba(GEN *v*) given a vector of nonzero integers *v*, return a coprime basis for *v*. Perfect powers are not removed; shallow function.

7.4.4 Checks attached to arithmetic functions.

Arithmetic functions accept arguments of the following kind: a plain positive integer *N* (**t_INT**), the factorization *fa* of a positive integer (a **t_MAT** with two columns containing respectively primes and exponents), or a vector [*N*, *fa*]. A few functions accept nonzero integers (e.g. **omega**), and some others arbitrary integers (e.g. **factorint**, ...).

int is_Z_factorpos(GEN *f*) returns 1 if *f* looks like the factorization of a positive integer, and 0 otherwise. Useful for sanity checks but not 100% foolproof. Specifically, this routine checks that *f* is a two-column matrix all of whose entries are positive integers. It does *not* check that entries in the first column (“primes”) are prime, or even pairwise coprime, nor that they are strictly increasing.

int is_Z_factornon0(GEN *f*) returns 1 if *f* looks like the factorization of a nonzero integer, and 0 otherwise. Useful for sanity checks but not 100% foolproof, analogous to **is_Z_factorpos**. (Entries in the first column need only be nonzero integers.)

int is_Z_factor(GEN *f*) returns 1 if *f* looks like the factorization of an integer, and 0 otherwise. Useful for sanity checks but not 100% foolproof. Specifically, this routine checks that *f* is a two-column matrix all of whose entries are integers. Entries in the second column (“exponents”) are all positive. Either it encodes the “factorization” 0^e , $e > 0$, or entries in the first column (“primes”) are all nonzero.

GEN clean_Z_factor(GEN *f*) assuming *f* is the factorization of an integer *n*, return the factorization of $|n|$, i.e. remove -1 from the factorization. Shallow function.

GEN fuse_Z_factor(GEN *f*, GEN *B*) assuming *f* is the factorization of an integer *n*, return **boundfact**(*n*, *B*), i.e. return a factorization where all primary factors for $|p| \leq B$ are preserved, and all others are “fused” into a single composite integer; if that remainder is trivial, i.e. equal to 1, it is of course not included. Shallow function.

In the following three routines, *f* is the name of an arithmetic function, and *n* a supplied argument. They all raise exceptions if *n* does not correspond to an integer or an integer factorization of the expected shape.

GEN check_arith_pos(GEN *n*, const char **f*) check whether *n* is attached to the factorization of a positive integer, and return NULL (plain **t_INT**) or a factorization extracted from *n* otherwise. May raise an **e_DOMAIN** ($n \leq 0$) or an **e_TYPE** exception (other failures).

GEN check_arith_non0(GEN *n*, const char **f*) check whether *n* is attached to the factorization of a nonzero integer, and return NULL (plain **t_INT**) or a factorization extracted from *n* otherwise. May raise an **e_TYPE** exception.

GEN check_arith_all(GEN *n*, const char **f*) is attached to the factorization of an integer, and return NULL (plain **t_INT**) or a factorization extracted from *n* otherwise.

7.4.5 Incremental integer factorization.

Routines attached to the dynamic factorization of an integer n , iterating over successive prime divisors. This is useful to implement high-level routines allowed to take shortcuts given enough partial information: e.g. `moebius(n)` can be trivially computed if we hit p such that $p^2 \mid n$. For efficiency, trial division by small primes should have already taken place. In any case, the functions below assume that no prime $< 2^{14}$ divides n .

`GEN ifac_start(GEN n, int moebius)` schedules a new factorization attempt for the integer n . If `moebius` is nonzero, the factorization will be aborted as soon as a repeated factor is detected (Moebius mode). The function assumes that $n > 1$ is a *composite* `t_INT` whose prime divisors satisfy $p > 2^{14}$ and that one can write to n in place.

This function stores data on the stack, no `gerepile` call should delete this data until the factorization is complete. Returns `partial`, a data structure recording the partial factorization state.

`int ifac_next(GEN *partial, GEN *p, long *e)` deletes a primary factor p^e from `partial` and sets `p` (prime) and `e` (exponent), and normally returns 1. Whatever remains in the `partial` structure is now coprime to p .

Returns 0 if all primary factors have been used already, so we are done with the factorization. In this case `p` is set to `NULL`. If we ran in Moebius mode and the factorization was in fact aborted, we have $e = 1$, otherwise $e = 0$.

`int ifac_read(GEN part, GEN *k, long *e)` peeks at the next integer to be factored in the list k^e , where k is not necessarily prime and can be a perfect power as well, but will be factored by the next call to `ifac_next`. You can remove this factorization from the schedule by calling:

`void ifac_skip(GEN part)` removes the next scheduled factorization.

`int ifac_isprime(GEN n)` given n whose prime divisors are $> 2^{14}$, returns the decision the factoring engine would take about the compositeness of n : 0 if n is a proven composite, and 1 if we believe it to be prime; more precisely, n is a proven prime if `factor_proven` is set, and only a BPSW-pseudoprime otherwise.

7.4.6 Integer core, squarefree factorization.

`long Z_issquarefree(GEN n)` returns 1 if the `t_INT` n is square-free, and 0 otherwise.

`long Z_issquarefree_fact(GEN fa)` same, where `fa` is `factor(n)`.

`long Z_isfundamental(GEN x)` returns 1 if the `t_INT` x is a fundamental discriminant, and 0 otherwise.

`GEN core(GEN n)` unique squarefree integer d dividing n such that n/d is a square. The core of 0 is defined to be 0.

`GEN core2(GEN n)` return $[d, f]$ with d squarefree and $n = df^2$.

`GEN corepartial(GEN n, long lim)` as `core`, using `boundfact(n, lim)` to partially factor n . The result is not necessarily squarefree, but $p^2 \mid n$ implies $p > \text{lim}$.

`GEN core2partial(GEN n, long lim)` as `core2`, using `boundfact(n, lim)` to partially factor n . The resulting d is not necessarily squarefree, but $p^2 \mid n$ implies $p > \text{lim}$.

7.4.7 Primes, primality and compositeness tests.

7.4.7.1 Chebyshev's π function, bounds.

`ulong uprimepi(ulong n)`, returns the number of primes $p \leq n$ (Chebyshev's π function).

`double primepi_upper_bound(double x)` return a quick upper bound for $\pi(x)$, using Dusart bounds.

`GEN gprimepi_upper_bound(GEN x)` as `primepi_upper_bound`, returns a `t_REAL`.

`double primepi_lower_bound(double x)` return a quick lower bound for $\pi(x)$, using Dusart bounds.

`GEN gprimepi_lower_bound(GEN x)` as `primepi_lower_bound`, returns a `t_REAL` or `gen_0`.

7.4.7.2 Primes, primes in intervals.

`ulong unextprime(ulong n)`, returns the smallest prime $\geq n$. Return 0 if it cannot be represented as an `ulong` (n bigger than $2^{64} - 59$ or $2^{32} - 5$ depending on the word size).

`ulong uprecprime(ulong n)`, returns the largest prime $\leq n$. Return 0 if $n \leq 1$.

`ulong uprime(long n)` returns the n -th prime, assuming it fits in an `ulong` (overflow error otherwise).

`GEN prime(long n)` same as `utoi(uprime(n))`.

`GEN primes_zv(long m)` returns the first m primes, in a `t_VECSMALL`.

`GEN primes(long m)` return the first m primes, as a `t_VEC` of `t_INTs`.

`GEN primes_interval(GEN a, GEN b)` return the primes in the interval $[a, b]$, as a `t_VEC` of `t_INTs`.

`GEN primes_interval_zv(ulong a, ulong b)` return the primes in the interval $[a, b]$, as a `t_VECSMALL` of `ulongss`.

`GEN primes_upto_zv(ulong b)` return the primes in the interval $[2, b]$, as a `t_VECSMALL` of `ulongss`.

`GEN mpprimorial(long n)` return $n\#$, the product of primes less than or equal to n . The integer n must be non-negative.

7.4.7.3 Tests.

`int uisprime(ulong p)`, returns 1 if p is a prime number and 0 otherwise.

`int uisprime_101(ulong p)`, assuming that p has no divisor ≤ 101 , returns 1 if p is a prime number and 0 otherwise.

`int uisprime_661(ulong p)`, assuming that p has no divisor ≤ 661 , returns 1 if p is a prime number and 0 otherwise.

`int isprime(GEN n)`, returns 1 if the `t_INT` n is a (fully proven) prime number and 0 otherwise.

`long isprimeAPRCL(GEN n)`, returns 1 if the `t_INT` n is a prime number and 0 otherwise, using only the APRCL test — not even trial division or compositeness tests. The workhorse `isprime` should be faster on average, especially if nonprimes are included!

`long isprimeECPP(GEN n)`, returns 1 if the `t_INT` n is a prime number and 0 otherwise, using only the ECPP test. The workhorse `isprime` should be faster on average.

`long BPSW_psp(GEN n)`, returns 1 if the `t_INT` `n` is a Baillie-Pomerance-Selfridge-Wagstaff pseudoprime, and 0 otherwise (proven composite).

`int BPSW_isprime(GEN x)` assuming x is a BPSW-pseudoprime, rigorously prove its primality. The function `isprime` is currently implemented as

`BPSW_psp(x) && BPSW_isprime(x)`

`long millerrabin(GEN n, long k)` performs k strong Rabin-Miller compositeness tests on the `t_INT` n , using k random bases. This function also caches square roots of -1 that are encountered during the successive tests and stops as soon as three distinct square roots have been produced; we have in principle factored n at this point, but unfortunately, there is currently no way for the factoring machinery to become aware of it. (It is highly implausible that hard to find factors would be exhibited in this way, though.) This should be slower than `BPSW_psp` for $k \geq 4$ and we expect it to be less reliable.

`GEN ecpp(GEN N)` returns an ECPP certificate for `t_INT` N ; underlies `primecert`.

`GEN ecpp0(GEN N, long t)` returns a (potentially) partial ECPP certificate for `t_INT` N where strong pseudo-primes $< 2^t$ are included as primes in the certificate. Underlies `primecert` with t set to the `partial` argument.

`GEN ecppexport(GEN cert, long flag)` export a PARI ECPP certificate to MAGMA or Primo format; underlies `primecertexport`.

`long ecppisvalid(GEN cert)` checks whether a PARI ECPP certificate is valid; underlies `primecertisvalid`.

`long check_ecppcert(GEN cert)` checks whether `cert` looks like a PARI ECPP certificate, (valid or invalid) without doing any computation.

7.4.8 Iterators over primes.

`int forprime_init(forprime_t *T, GEN a, GEN b)` initialize an iterator T over primes in $[a, b]$; over primes $\geq a$ if $b = \text{NULL}$. Return 0 if the range is known to be empty from the start (as if $b < a$ or $b < 0$), and return 1 otherwise. Use `forprime_next` to iterate over the prime collection.

`int forprimestep_init(forprime_t *T, GEN a, GEN b, GEN q)` initialize an iterator T over primes in an arithmetic progression in $[a, b]$; over primes $\geq a$ if $b = \text{NULL}$. The argument q is either a `t_INT` ($p \equiv a \pmod{q}$) or a `t_INTMOD` `Mod(c, N)` and we restrict to that congruence class. Return 0 if the range is known to be empty from the start (as if $b < a$ or $b < 0$), and return 1 otherwise. Use `forprime_next` to iterate over the prime collection.

`GEN forprime_next(forprime_t *T)` returns the next prime in the range, assuming that T was initialized by `forprime_init`.

`int u_forprime_init(forprime_t *T, ulong a, ulong b)`

`ulong u_forprime_next(forprime_t *T)`

`void u_forprime_restrict(forprime_t *T, ulong c)` let T an iterator over primes initialized via `u_forprime_init(&T, a, b)`, possibly followed by a number of calls to `u_forprime_next`, and $a \leq c \leq b$. Restrict the range of primes considered to $[a, c]$.

`int u_forprime_arith_init(forprime_t *T, ulong a, ulong b, ulong c, ulong q)` initialize an iterator over primes in $[a, b]$, congruent to c modulo q . Subsequent calls to `u_forprime_next` will only return primes congruent to c modulo q . Note that unless $(c, q) = 1$ there will be at most one such prime.

7.5 Integral, rational and generic linear algebra.

7.5.1 ZC / ZV, ZM. A ZV (resp. a ZM, resp. a ZX) is a `t_VEC` or `t_COL` (resp. `t_MAT`, resp. `t_POL`) with `t_INT` coefficients.

7.5.1.1 ZC / ZV.

`void RgV_check_ZV(GEN x, const char *s)` Assuming `x` is a `t_VEC` or `t_COL` raise an error if it is not a ZV (`s` should point to the name of the caller).

`int RgV_is_ZV(GEN x)` Assuming `x` is a `t_VEC` or `t_COL` return 1 if it is a ZV, and 0 otherwise.

`int RgV_is_ZVpos(GEN x)` Assuming `x` is a `t_VEC` or `t_COL` return 1 if it is a ZV with positive entries, and 0 otherwise.

`int RgV_is_ZVnon0(GEN x)` Assuming `x` is a `t_VEC` or `t_COL` return 1 if it is a ZV with nonzero entries, and 0 otherwise.

`int RgV_is_QV(GEN P)` return 1 if the RgV `P` has only `t_INT` and `t_FRAC` coefficients, and 0 otherwise.

`int RgV_is_arithprog(GEN v, GEN *a, GEN *b)` assuming `x` is a `t_VEC` or `t_COL` return 1 if its entries follow an arithmetic progression of the form $a + b * n$, $n = 0, 1, \dots$ and set `a` and `b`. Else return 0.

`int ZV_equal0(GEN x)` returns 1 if all entries of the ZV `x` are zero, and 0 otherwise.

`int ZV_cmp(GEN x, GEN y)` compare two ZV, which we assume have the same length (lexicographic order).

`int ZV_abscmp(GEN x, GEN y)` compare two ZV, which we assume have the same length (lexicographic order, comparing absolute values).

`int ZV_equal(GEN x, GEN y)` returns 1 if the two ZV are equal and 0 otherwise. A `t_COL` and a `t_VEC` with the same entries are declared equal.

`GEN identity_ZV(long n)` return the `t_VEC` $[1, 2, \dots, n]$.

`GEN ZC_add(GEN x, GEN y)` adds `x` and `y`.

`GEN ZC_sub(GEN x, GEN y)` subtracts `x` and `y`.

`GEN ZC_Z_add(GEN x, GEN y)` adds `y` to `x[1]`.

`GEN ZC_Z_sub(GEN x, GEN y)` subtracts `y` to `x[1]`.

`GEN Z_ZC_sub(GEN a, GEN x)` returns the vector $[a - x_1, -x_2, \dots, -x_n]$.

`GEN ZC_copy(GEN x)` returns a (`t_COL`) copy of `x`.

`GEN ZC_neg(GEN x)` returns $-x$ as a `t_COL`.

`void ZV_neg_inplace(GEN x)` negates the ZV `x` in place, by replacing each component by its opposite (the type of `x` remains the same, `t_COL` or `t_COL`). If you want to save even more memory by avoiding the implicit component copies, use `ZV_togglesign`.

`void ZV_togglesign(GEN x)` negates `x` in place, by toggling the sign of its integer components. Universal constants `gen_1`, `gen_m1`, `gen_2` and `gen_m2` are handled specially and will not be corrupted. (We use `togglesign_safe`.)

GEN `ZC_Z_mul`(GEN `x`, GEN `y`) multiplies the ZC or ZV `x` (which can be a column or row vector) by the `t_INT` `y`, returning a ZC.

GEN `ZC_Z_divexact`(GEN `x`, GEN `y`) returns x/y assuming all divisions are exact.

GEN `ZC_divexactu`(GEN `x`, `ulong` `y`) returns x/y assuming all divisions are exact.

GEN `ZC_Z_div`(GEN `x`, GEN `y`) returns x/y , where the resulting vector has rational entries.

GEN `ZV_ZV_mod`(GEN `a`, GEN `b`). Assuming a and b are two ZV of the same length, returns the vector whose i -th component is `modii(a[i], b[i])`.

GEN `ZV_dotproduct`(GEN `x`, GEN `y`) as `RgV_dotproduct` assuming x and y have `t_INT` entries.

GEN `ZV_dotsquare`(GEN `x`) as `RgV_dotsquare` assuming x has `t_INT` entries.

GEN `ZC_lincomb`(GEN `u`, GEN `v`, GEN `x`, GEN `y`) returns $ux + vy$, where u, v are `t_INT` and x, y are ZC or ZV. Return a ZC

void `ZC_lincomb1_inplace`(GEN `X`, GEN `Y`, GEN `v`) sets $X \leftarrow X + vY$, where v is a `t_INT` and X, Y are ZC or ZV. (The result has the type of X .) Memory efficient (e.g. no-op if $v = 0$), but not gerpil-safe.

void `ZC_lincomb1_inplace_i`(GEN `X`, GEN `Y`, GEN `v`, `long` `n`) variant of `ZC_lincomb1_inplace`: only update $X[1], \dots, X[n]$, assuming that $n < \lg(X)$.

GEN `ZC_ZV_mul`(GEN `x`, GEN `y`, GEN `p`) multiplies the ZC `x` (seen as a column vector) by the ZV `y` (seen as a row vector, assumed to have compatible dimensions).

GEN `ZV_content`(GEN `x`) returns the GCD of all the components of `x`.

GEN `ZV_extgcd`(GEN `A`) given a vector of n integers A , returns $[d, U]$, where d is the content of A and U is a matrix in $GL_n(\mathbf{Z})$ such that $AU = [D, 0, \dots, 0]$.

GEN `ZV_prod`(GEN `x`) returns the product of all the components of `x` (1 for the empty vector).

GEN `ZV_sum`(GEN `x`) returns the sum of all the components of `x` (0 for the empty vector).

`long` `ZV_max_lg`(GEN `x`) returns the effective length of the longest entry in x .

`long` `ZV_max_expi`(GEN `x`) returns the number of bits of the largest entry in x .

`int` `ZV_dvd`(GEN `x`, GEN `y`) assuming x, y are two ZVs of the same length, return 1 if $y[i]$ divides $x[i]$ for all i and 0 otherwise. Error if one of the $y[i]$ is 0.

GEN `ZV_sort`(GEN `L`) sort the ZV L . Returns a vector with the same type as L .

GEN `ZV_sort_shallow`(GEN `L`) shallow version of `ZV_sort`.

void `ZV_sort_inplace`(GEN `L`) sort the ZV L , in place.

GEN `ZV_sort_uniq`(GEN `L`) sort the ZV L , removing duplicate entries. Returns a vector with the same type as L .

GEN `ZV_sort_uniq_shallow`(GEN `L`) shallow version of `ZV_sort_uniq`.

`long` `ZV_search`(GEN `L`, GEN `y`) look for the `t_INT` y in the sorted ZV L . Return an index i such that $L[i] = y$, and 0 otherwise.

GEN `ZV_indexsort`(GEN `L`) returns the permutation which, applied to the ZV L , would sort the vector. The result is a `t_VECSMALL`.

GEN ZV_union_shallow(GEN x, GEN y) given two *sorted* ZV (as per ZV_sort, returns the union of x and y . Shallow function. In case two entries are equal in x and y , include the one from x .

GEN ZC_union_shallow(GEN x, GEN y) as ZV_union_shallow but return a t_COL.

7.5.1.2 ZM.

void RgM_check_ZM(GEN A, const char *s) Assuming x is a t_MAT raise an error if it is not a ZM (s should point to the name of the caller).

GEN RgM_rescale_to_int(GEN x) given a matrix x with real entries (t_INT, t_FRAC or t_REAL), return a ZM which is very close to Dx for some well-chosen integer D . More precisely, if the input is exact, D is the denominator of x ; else it is a power of 2 chosen so that all inexact entries are correctly rounded to 1 ulp.

GEN ZM_copy(GEN x) returns a copy of x .

int ZM_equal(GEN A, GEN B) returns 1 if the two ZM are equal and 0 otherwise.

int ZM_equal0(GEN A) returns 1 if the ZM A is identically equal to 0.

GEN ZM_add(GEN x, GEN y) returns $x + y$ (assumed to have compatible dimensions).

GEN ZM_sub(GEN x, GEN y) returns $x - y$ (assumed to have compatible dimensions).

GEN ZM_neg(GEN x) returns $-x$.

void ZM_togglesign(GEN x) negates x in place, by toggling the sign of its integer components. Universal constants gen_1, gen_m1, gen_2 and gen_m2 are handled specially and will not be corrupted. (We use togglesign_safe.)

GEN ZM_mul(GEN x, GEN y) multiplies x and y (assumed to have compatible dimensions).

GEN ZM2_mul(GEN x, GEN y) multiplies the two-by-two ZM x and y .

GEN ZM_sqr(GEN x) returns x^2 , where x is a square ZM.

GEN ZM2_sqr(GEN x) returns x^2 , where x is a two-by-two ZM.

GEN ZM_Z_mul(GEN x, GEN y) multiplies the ZM x by the t_INT y .

GEN ZM_ZC_mul(GEN x, GEN y) multiplies the ZM x by the ZC y (seen as a column vector, assumed to have compatible dimensions).

GEN ZM_ZX_mul(GEN x, GEN T) returns $x \times y$, where y is RgX_to_RgC($T, \lg(x) - 1$).

GEN ZM_diag_mul(GEN d, GEN m) given a vector d with integer entries and a ZM m of compatible dimensions, return $\text{diagonal}(d) * m$.

GEN ZM_mul_diag(GEN m, GEN d) given a vector d with integer entries and a ZM m of compatible dimensions, return $m * \text{diagonal}(d)$.

GEN ZM_multosym(GEN x, GEN y)

GEN ZM_transmultosym(GEN x, GEN y)

GEN ZM_transmul(GEN x, GEN y)

GEN ZMrow_ZC_mul(GEN x, GEN y, long i) multiplies the i -th row of ZM x by the ZC y (seen as a column vector, assumed to have compatible dimensions). Assumes that x is nonempty and $0 < i < \lg(x[1])$.

`int ZMrow_equal0(GEN V, long i)` returns 1 if the i -th row of the ZM V is zero, and 0 otherwise.

`GEN ZV_ZM_mul(GEN x, GEN y)` multiplies the ZV x by the ZM y . Returns a `t_VEC`.

`GEN ZM_Z_divexact(GEN x, GEN y)` returns x/y assuming all divisions are exact.

`GEN ZM_divexactu(GEN x, ulong y)` returns x/y assuming all divisions are exact.

`GEN ZM_Z_div(GEN x, GEN y)` returns x/y , where the resulting matrix has rational entries.

`GEN ZM_ZV_mod(GEN a, GEN b)`. Assuming a is a ZM whose columns have the same length as the ZV b , apply `ZV_ZV_mod(a[i], b)` to all columns.

`GEN ZC_Q_mul(GEN x, GEN y)` returns $x*y$, where y is a rational number and the resulting `t_COL` has rational entries.

`GEN ZM_Q_mul(GEN x, GEN y)` returns $x*y$, where y is a rational number and the resulting matrix has rational entries.

`GEN ZM_pow(GEN x, GEN n)` returns x^n , assuming x is a square ZM and $n \geq 0$.

`GEN ZM_powu(GEN x, ulong n)` returns x^n , assuming x is a square ZM and $n \geq 0$.

`GEN ZM_det(GEN M)` if M is a ZM, returns the determinant of M . This is the function underlying `matdet` whenever M is a ZM.

`GEN ZM_permanent(GEN M)` if M is a ZM, returns its permanent. This is the function underlying `matpermanent` whenever M is a ZM. It assumes that the matrix is square of dimension $< \text{BITS_IN_LONG}$.

`GEN ZM_detmult(GEN M)` if M is a ZM, returns a multiple of the determinant of the lattice generated by its columns. This is the function underlying `detint`.

`GEN ZM_supnorm(GEN x)` return the sup norm of the ZM x .

`GEN ZM_charpoly(GEN M)` returns the characteristic polynomial (in variable 0) of the ZM M .

`GEN ZM_imagecompl(GEN x)` returns `matimagecompl(x)`.

`long ZM_rank(GEN x)` returns `matrank(x)`.

`GEN ZM_ker(GEN x)` returns the primitive part of `matker(x)`; in other words the \mathbf{Q} -basis vectors are made integral and primitive.

`GEN ZM_indexrank(GEN x)` returns `matindexrank(x)`.

`GEN ZM_indeximage(GEN x)` returns `gel(ZM_indexrank(x), 2)`.

`long ZM_max_lg(GEN x)` returns the effective length of the longest entry in x .

`long ZM_max_expi(GEN x)` returns the number of bits of the largest entry in x .

`GEN ZM_inv(GEN M, GEN *pd)` if M is a ZM, return a primitive matrix H such that MH is d times the identity and set `*pd` to d . Uses a multimodular algorithm up to Hadamard's bound. If you suspect that the denominator is much smaller than $\det M$, you may use `ZM_inv_ratlift`.

`GEN ZM_inv_ratlift(GEN M, GEN *pd)` if M is a ZM, return a primitive matrix H such that MH is d times the identity and set `*pd` to d . Uses a multimodular algorithm, attempting rational reconstruction along the way. To be used when you expect that the denominator of M^{-1} is much smaller than $\det M$ else use `ZM_inv`.

`GEN SL2_inv_shallow(GEN M)` return the inverse of $M \in \text{SL}_2(\mathbf{Z})$. Not gerepile-safe.

`GEN ZM_pseudoinv(GEN M, GEN *pv, GEN *pd)` if M is a nonempty ZM, let $v = [y, z]$ returned by `indexrank` and let M_1 be the corresponding square invertible matrix. Return a primitive left-inverse H such that HM_1 is d times the identity and set `*pd` to d . If `pv` is not NULL, set `*pv` to v . Not gerepile-safe.

`GEN ZM_gauss(GEN a, GEN b)` as `gauss`, where a and b coefficients are `t_INTs`.

`GEN ZM_det_triangular(GEN x)` returns the product of the diagonal entries of x (its determinant if it is indeed triangular).

`int ZM_isidentity(GEN x)` return 1 if the ZM x is the identity matrix, and 0 otherwise.

`int ZM_isdiagonal(GEN x)` return 1 if the ZM x is diagonal, and 0 otherwise.

`int ZM_isscalar(GEN x, GEN s)` given a ZM x and a `t_INT` s , return 1 if x is equal to s times the identity, and 0 otherwise. If s is NULL, test whether x is an arbitrary scalar matrix.

`long ZC_is_ei(GEN x)` return i if the ZC x has 0 entries, but for a 1 at position i .

`int ZM_ishnf(GEN x)` return 1 if x is in HNF form, i.e. is upper triangular with positive diagonal coefficients, and for $j > i$, $x_{i,i} > x_{i,j} \geq 0$.

7.5.2 QM.

`GEN QM_charpoly_ZX(GEN M)` returns the characteristic polynomial (in variable 0) of the QM M , assuming that the result has integer coefficients.

`GEN QM_charpoly_ZX_bound(GEN M, long b)` as `QM_charpoly_ZX` assuming that the sup norm of the (integral) result is $\leq 2^b$.

`GEN QM_gauss(GEN a, GEN b)` as `gauss`, where a and b coefficients are `t_FRACs`.

`GEN QM_gauss_i(GEN a, GEN b, long flag)` as `QM_gauss` if `flag` is 0. Else, no longer assume that a is left-invertible and return a solution of $Pax = Pb$ where P is a row-selection matrix such that $A = PaQ$ is square invertible of maximal rank, for some column-selection matrix Q ; in particular, x is a solution of the original equation $ax = b$ if and only if a solution exists.

`GEN QM_indexrank(GEN x)` returns `matindexrank(x)`.

`GEN QM_inv(GEN M)` return the inverse of the QM M .

`long QM_rank(GEN x)` returns `matrank(x)`.

`GEN QM_image(GEN x)` returns an integral matrix with primitive columns generating the image of x .

`GEN QM_image_shallow(GEN A)` shallow version of the previous function, not suitable for `gerepile`.

7.5.3 Qevproj.

GEN Qevproj_init(GEN M) let M be a $n \times d$ ZM of maximal rank $d \leq n$, representing the basis of a \mathbf{Q} -subspace V of \mathbf{Q}^n . Return a projector on V , to be used by Qevproj_apply. The interface details may change in the future, but this function currently returns $[M, B, D, p]$, where p is a `t_VECSMALL` with d entries such that the submatrix $A = \text{rowpermute}(M, p)$ is invertible, B is a ZM and d a `t_INT` such that $AB = DId_d$.

GEN Qevproj_apply(GEN T, GEN pro) let T be an $n \times n$ QM, stabilizing a \mathbf{Q} -subspace $V \subset \mathbf{Q}^n$ of dimension d , and let pro be a projector on that subspace initialized by Qevproj_init(M). Return the $d \times d$ matrix representing $T|_V$ on the basis given by the columns of M .

GEN Qevproj_apply_vecei(GEN T, GEN pro, long k) as Qevproj_apply, return only the image of the k -th basis vector $M[k]$ (still on the basis given by the columns of M).

GEN Qevproj_down(GEN T, GEN pro) given a ZC (resp. a ZM) T representing an element (resp. a vector of elements) in the subspace V return a QC (resp. a QM) U such that $T = MU$.

7.5.4 zv, zm.

GEN identity_zv(long n) return the `t_VECSMALL` $[1, 2, \dots, n]$.

GEN random_zv(long n) returns a random zv with n components.

GEN zv_abs(GEN x) return $[|x[1]|, \dots, |x[n]|]$ as a zv.

GEN zv_neg(GEN x) return $-x$. No check for overflow is done, which occurs in the fringe case where an entry is equal to $2^{\text{BITS_IN_LONG}-1}$.

GEN zv_neg_inplace(GEN x) negates x in place and return it. No check for overflow is done, which occurs in the fringe case where an entry is equal to $2^{\text{BITS_IN_LONG}-1}$.

GEN zm_zc_mul(GEN x, GEN y)

GEN zm_mul(GEN x, GEN y)

GEN zv_z_mul(GEN x, long n) return nx . No check for overflow is done.

long zv_content(GEN x) returns the gcd of the entries of x .

long zv_dotproduct(GEN x, GEN y)

long zv_prod(GEN x) returns the product of all the components of \mathbf{x} (assumes no overflow occurs).

GEN zv_prod_Z(GEN x) returns the product of all the components of \mathbf{x} ; consider all $x[i]$ as `ulongs`.

long zv_sum(GEN x) returns the sum of all the components of \mathbf{x} (assumes no overflow occurs).

long zv_sumpart(GEN v, long n) returns the sum $v[1] + \dots + v[n]$ (assumes no overflow occurs and $\lg(v) > n$).

int zv_cmp0(GEN x) returns 1 if all entries of the zv x are 0, and 0 otherwise.

int zv_equal(GEN x, GEN y) returns 1 if the two zv are equal and 0 otherwise.

int zv_equal0(GEN x) returns 1 if all entries are 0, and return 0 otherwise.

long zv_search(GEN L, long y) look for y in the sorted zv L . Return an index i such that $L[i] = y$, and 0 otherwise.

GEN zv_copy(GEN x) as `Flv_copy`.

`GEN zm_transpose(GEN x) as Flm_transpose.`
`GEN zm_copy(GEN x) as Flm_copy.`
`GEN zero_zm(long m, long n) as zero_Flm.`
`GEN zero_zv(long n) as zero_Flv.`
`GEN zm_row(GEN A, long x0) as Flm_row.`
`GEN zv_diagonal(GEN v)` return the square `zm` whose diagonal is given by the entries of `v`.
`GEN zm_permanent(GEN M)` return the permanent of M . The function assumes that the matrix is square of dimension $< \text{BITS_IN_LONG}$.
`int zvV_equal(GEN x, GEN y)` returns 1 if the two `zvV` (vectors of `zv`) are equal and 0 otherwise.

7.5.5 ZMV / zmV (vectors of ZM/zm).

`int RgV_is_ZMV(GEN x)` Assuming `x` is a `t_VEC` or `t_COL` return 1 if its components are ZM, and 0 otherwise.
`GEN ZMV_to_zmV(GEN z)`
`GEN zmV_to_ZMV(GEN z)`
`GEN ZMV_to_FlmV(GEN z, ulong m)`

7.5.6 QC / QV, QM.

`GEN QM_mul(GEN x, GEN y)` multiplies `x` and `y` (assumed to have compatible dimensions).
`GEN QM_sqr(GEN x)` returns the square of `x` (assumed to be square).
`GEN QM_QC_mul(GEN x, GEN y)` multiplies `x` and `y` (assumed to have compatible dimensions).
`GEN QM_det(GEN M)` returns the determinant of M .
`GEN QM_ker(GEN x)` returns `matker(x)`.

7.5.7 RgC / RgV, RgM.

`RgC` and `RgV` routines assume the inputs are `VEC` or `COL` of the same dimension. `RgM` assume the inputs are `MAT` of compatible dimensions.

7.5.7.1 Matrix arithmetic.

`void RgM_dimensions(GEN x, long *m, long *n)` sets m , resp. n , to the number of rows, resp. columns of the `t_MAT` `x`.
`GEN RgC_add(GEN x, GEN y)` returns $x + y$ as a `t_COL`.
`GEN RgC_neg(GEN x)` returns $-x$ as a `t_COL`.
`GEN RgC_sub(GEN x, GEN y)` returns $x - y$ as a `t_COL`.
`GEN RgV_add(GEN x, GEN y)` returns $x + y$ as a `t_VEC`.
`GEN RgV_neg(GEN x)` returns $-x$ as a `t_VEC`.
`GEN RgV_sub(GEN x, GEN y)` returns $x - y$ as a `t_VEC`.

`GEN RgM_add(GEN x, GEN y)` return $x + y$.
`GEN RgM_neg(GEN x)` returns $-x$.
`GEN RgM_sub(GEN x, GEN y)` returns $x - y$.
`GEN RgM_Rg_add(GEN x, GEN y)` assuming x is a square matrix and y a scalar, returns the square matrix $x + y * \text{Id}$.
`GEN RgM_Rg_add_shallow(GEN x, GEN y)` as `RgM_Rg_add` with much fewer copies. Not suitable for `gerepileupto`.
`GEN RgM_Rg_sub(GEN x, GEN y)` assuming x is a square matrix and y a scalar, returns the square matrix $x - y * \text{Id}$.
`GEN RgM_Rg_sub_shallow(GEN x, GEN y)` as `RgM_Rg_sub` with much fewer copies. Not suitable for `gerepileupto`.
`GEN RgC_Rg_add(GEN x, GEN y)` assuming x is a nonempty column vector and y a scalar, returns the vector $[x_1 + y, x_2, \dots, x_n]$.
`GEN RgC_Rg_sub(GEN x, GEN y)` assuming x is a nonempty column vector and y a scalar, returns the vector $[x_1 - y, x_2, \dots, x_n]$.
`GEN Rg_RgC_sub(GEN a, GEN x)` assuming x is a nonempty column vector and a a scalar, returns the vector $[a - x_1, -x_2, \dots, -x_n]$.
`GEN RgC_Rg_div(GEN x, GEN y)`
`GEN RgM_Rg_div(GEN x, GEN y)` returns x/y (y treated as a scalar).
`GEN RgC_Rg_mul(GEN x, GEN y)`
`GEN RgV_Rg_mul(GEN x, GEN y)`
`GEN RgM_Rg_mul(GEN x, GEN y)` returns $x \times y$ (y treated as a scalar).
`GEN RgV_RgC_mul(GEN x, GEN y)` returns $x \times y$.
`GEN RgV_RgM_mul(GEN x, GEN y)` returns $x \times y$.
`GEN RgM_RgC_mul(GEN x, GEN y)` returns $x \times y$.
`GEN RgM_RgX_mul(GEN x, GEN T)` returns $x \times y$, where y is `RgX_to_RgC(T, lg(x) - 1)`.
`GEN RgM_mul(GEN x, GEN y)` returns $x \times y$.
`GEN RgM_div(GEN a, GEN b)` returns ab^{-1} or NULL if this turns out to be impossible.
`GEN RgM_ZM_mul(GEN x, GEN y)` returns $x \times y$ assuming that y is a ZM.
`GEN RgM_transmul(GEN x, GEN y)` returns $x^{\sim} \times y$.
`GEN RgM_multosym(GEN x, GEN y)` returns $x \times y$, assuming the result is a symmetric matrix (about twice faster than a generic matrix multiplication).
`GEN RgM_transmultosym(GEN x, GEN y)` returns $x^{\sim} \times y$, assuming the result is a symmetric matrix (about twice faster than a generic matrix multiplication).
`GEN RgMrow_RgC_mul(GEN x, GEN y, long i)` multiplies the i -th row of `RgM x` by the `RgC y` (seen as a column vector, assumed to have compatible dimensions). Assumes that x is nonempty and $0 < i < \text{lg}(x[1])$.

GEN RgM_mulreal(GEN x, GEN y) returns the real part of $x \times y$ (whose entries are t_INT, t_FRAC, t_REAL or t_COMPLEX).

GEN RgM_sqr(GEN x) returns x^2 .

GEN RgC_RgV_mul(GEN x, GEN y) returns $x \times y$ (the matrix $(x_i y_j)$).

GEN RgC_RgV_mulrealsym(GEN x, GEN y) returns the real part of $x \times y$ (whose entries are t_INT, t_FRAC, t_REAL or t_COMPLEX), assuming the result is symmetric.

The following two functions are not well defined in general and only provided for convenience in specific cases:

GEN RgC_RgM_mul(GEN x, GEN y) returns $x \times y[1,]$ if y is a row matrix $1 \times n$, error otherwise.

GEN RgM_RgV_mul(GEN x, GEN y) returns $x \times y[, 1]$ if y is a column matrix $n \times 1$, error otherwise.

GEN RgM_powers(GEN x, long n) returns $[x^0, \dots, x^n]$ as a t_VEC of RgMs.

GEN RgV_sum(GEN v) sum of the entries of v

GEN RgV_prod(GEN v) product of the entries of v , using a divide and conquer strategy

GEN RgV_sumpart(GEN v, long n) returns the sum $v[1] + \dots + v[n]$ (assumes that $\lg(v) > n$).

GEN RgV_sumpart2(GEN v, long m, long n) returns the sum $v[m] + \dots + v[n]$ (assumes that $\lg(v) > n$ and $m > 0$). Returns gen_0 when $m > n$.

GEN RgM_sumcol(GEN v) returns a t_COL, sum of the columns of the t_MAT v .

GEN RgV_dotproduct(GEN x, GEN y) returns the scalar product of x and y

GEN RgV_dotsquare(GEN x) returns the scalar product of x with itself.

GEN RgV_kill0(GEN v) returns a shallow copy of v where entries matched by `gequal0` are replaced by NULL. The return value is not a valid GEN and must be handled specially. The idea is to pre-treat a vector of coefficients to speed up later linear combinations or scalar products.

GEN gram_matrix(GEN v) returns the Gram matrix $(v_i \cdot v_j)$ attached to the entries of v (matrix, or vector of vectors).

GEN RgV_polint(GEN X, GEN Y, long v) X and Y being two vectors of the same length, returns the polynomial T in variable v such that $T(X[i]) = Y[i]$ for all i . The special case $X = \text{NULL}$ corresponds to $X = [1, 2, \dots, n]$, where n is the length of Y . This is the function underlying `polint` for formal interpolation.

GEN polintspec(GEN X, GEN Y, GEN t, long n, long *pe) return $P(t)$ where P is the Lagrange interpolation polynomial attached to the n points $(X[0], Y[0]), \dots, (X[n-1], Y[n-1])$. If `pe` is not NULL and t is a complex numeric value, `*pe` contains an error estimate for the returned value (Neville's algorithm, see `polinterpolate`). In extrapolation algorithms, e.g., Romberg integration, this function is usually called on actual GEN vectors with offsets: $x+k$ and $y+k$ so as to interpolate on $x[k..k+n-1]$ without having to use `vecslice`. This is the function underlying `polint` for numerical interpolation.

GEN polint_i(GEN X, GEN Y, GEN t, long *pe) as `polintspec`, where X and Y are actual GEN vectors.

GEN vandermondeinverse(GEN r, GEN T, GEN d, GEN V) Given a vector r of n scalars and the t_POL $T = \prod_{i=1}^n (X - r_i)$, return dM^{-1} , where $M = (r_i^{j-1})_{1 \leq i, j \leq n}$ is the van der Monde matrix; V is

NULL or a vector containing the $T'(r_i)$, as returned by `vandermondeinverseinit`. The demonimator d may be set to NULL (handled as 1). If c is the k -column of the result, it is essentially d times the k -th Lagrange interpolation polynomial: we have $\sum_j c_j r_i^{j-1} = d\delta_{i=k}$. This is the function underlying `RgV_polint` when the base field is not $\mathbf{Z}/p\mathbf{Z}$: it uses $O(n^2)$ scalar operations and is asymptotically slower than variants using multi-evaluation such as `FpV_polint`; it is also accurate over inexact fields.

GEN vandermondeinverseinit(GEN r) Given a vector r of n scalars, let T be the `t_POL` $T = \prod_{j=1}^n (X - r_j)$. This function returns the $T'(r_i)$ computed stably via products of difference: the i -th entry is $T'(r_i) = \prod_{j \neq i} (r_i - r_j)$. It is asymptotically slow (uses $O(n^2)$ scalar operations, where multi-evaluation achieves quasi-linear running time) but allows accurate computation at low accuracies when T has large complex coefficients.

7.5.7.2 Special shapes.

The following routines check whether matrices or vectors have a special shape, using `gequal1` and `gequal0` to test components. (This makes a difference when components are inexact.)

int RgV_isscalar(GEN x) return 1 if all the entries of x are 0 (as per `gequal0`), except possibly the first one. The name comes from vectors expressing polynomials on the standard basis $1, T, \dots, T^{n-1}$, or on `nf.zk` (whose first element is 1).

int QV_isscalar(GEN x) as `RgV_isscalar`, assuming x is a QV (`t_INT` and `t_FRAC` entries only).

int ZV_isscalar(GEN x) as `RgV_isscalar`, assuming x is a ZV (`t_INT` entries only).

int RgM_isscalar(GEN x, GEN s) return 1 if x is the scalar matrix equal to s times the identity, and 0 otherwise. If s is NULL, test whether x is an arbitrary scalar matrix.

int RgM_isidentity(GEN x) return 1 if the `t_MAT` x is the identity matrix, and 0 otherwise.

int RgM_isdiagonal(GEN x) return 1 if the `t_MAT` x is a diagonal matrix, and 0 otherwise.

long RgC_is_ei(GEN x) return i if the `t_COL` x has 0 entries, but for a 1 at position i .

int RgM_is_ZM(GEN x) return 1 if the `t_MAT` x has only `t_INT` coefficients, and 0 otherwise.

long qfiseven(GEN M) return 1 if the square symmetric `typZM` x is an even quadratic form (all diagonal coefficients are even), and 0 otherwise.

int RgM_is_QM(GEN x) return 1 if the `t_MAT` x has only `t_INT` or `t_FRAC` coefficients, and 0 otherwise.

long RgV_isin(GEN v, GEN x) return the first index i such that $v[i] = x$ if it exists, and 0 otherwise. Naive search in linear time, does not assume that v is sorted.

long RgV_isin_i(GEN v, GEN x, long n) return the first index $i \leq n$ such that $v[i] = x$ if it exists, and 0 otherwise. Naive search in linear time, does not assume that v is sorted. Assume that $n < \lg(v)$.

GEN RgM_diagonal(GEN m) returns the diagonal of m as a `t_VEC`.

GEN RgM_diagonal_shallow(GEN m) shallow version of `RgM_diagonal`

7.5.7.3 Conversion to floating point entries.

GEN RgC_gtofp(GEN x, GEN prec) returns the `t_COL` obtained by applying `gtofp(gel(x,i), prec)` to all coefficients of x .

GEN RgV_gtofp(GEN x, GEN prec) returns the `t_VEC` obtained by applying `gtofp(gel(x,i), prec)` to all coefficients of x .

GEN RgC_gtomp(GEN x, long prec) returns the `t_COL` obtained by applying `gtomp(gel(x,i), prec)` to all coefficients of x .

GEN RgC_fpnorml2(GEN x, long prec) returns (a stack-clean variant of)

`gnorml2(RgC_gtofp(x, prec))`

GEN RgM_gtofp(GEN x, GEN prec) returns the `t_MAT` obtained by applying `gtofp(gel(x,i), prec)` to all coefficients of x .

GEN RgM_gtomp(GEN x, long prec) returns the `t_MAT` obtained by applying `gtomp(gel(x,i), prec)` to all coefficients of x .

GEN RgM_fpnorml2(GEN x, long prec) returns (a stack-clean variant of)

`gnorml2(RgM_gtofp(x, prec))`

7.5.7.4 Linear algebra, linear systems.

GEN RgM_inv(GEN a) returns a left inverse of a (which needs not be square), or `NULL` if this turns out to be impossible. The latter happens when the matrix does not have maximal rank (or when rounding errors make it appear so).

GEN RgM_inv_upper(GEN a) as `RgM_inv`, assuming that a is a nonempty invertible upper triangular matrix, hence a little faster.

GEN RgM_RgC_invimage(GEN A, GEN B) returns a `t_COL` X such that $AX = B$ if one such exists, and `NULL` otherwise.

GEN RgM_invimage(GEN A, GEN B) returns a `t_MAT` X such that $AX = B$ if one such exists, and `NULL` otherwise.

GEN RgM_Hadamard(GEN a) returns an upper bound for the absolute value of $\det(a)$. The bound is a `t_INT`.

GEN RgM_solve(GEN a, GEN b) returns $a^{-1}b$ where a is a square `t_MAT` and b is a `t_COL` or `t_MAT`. Returns `NULL` if a^{-1} cannot be computed, see `RgM_inv`.

If $b = \text{NULL}$, the matrix a need no longer be square, and we strive to return a left inverse for a (`NULL` if it does not exist).

GEN RgM_solve_realimag(GEN M, GEN b) M being a `t_MAT` with $r_1 + r_2$ rows and $r_1 + 2r_2$ columns, y a `t_COL` or `t_MAT` such that the equation $Mx = y$ makes sense, returns x under the following simplifying assumptions: the first r_1 rows of M and y are real (the r_2 others are complex), and x is real. This is stabler and faster than calling `RgM_solve(M, b)` over \mathbf{C} . In most applications, M approximates the complex embeddings of an integer basis in a number field, and x is actually rational.

GEN split_realimag(GEN x, long r1, long r2) x is a `t_COL` or `t_MAT` with $r_1 + r_2$ rows, whose first r_1 rows have real entries (the r_2 others are complex). Return an object of the same type as x

and $r_1 + 2r_2$ rows, such that the first $r_1 + r_2$ rows contain the real part of x , and the r_2 following ones contain the imaginary part of the last r_2 rows of x . Called by `RgM_solve_realimag`.

`GEN RgM_det_triangular(GEN x)` returns the product of the diagonal entries of x (its determinant if it is indeed triangular).

`GEN Frobeniusform(GEN V, long n)` given the vector V of elementary divisors for $M - x\text{Id}$, where M is an $n \times n$ square matrix. Returns the Frobenius form of M .

`int RgM_QR_init(GEN x, GEN *pB, GEN *pQ, GEN *pL, long prec)` QR-decomposition of a square invertible `t_MAT` x with real coefficients. Sets `*pB` to the vector of squared lengths of the $x[i]$, `*pL` to the Gram-Schmidt coefficients and `*pQ` to a vector of successive Householder transforms. If R denotes the transpose of L and Q is the result of applying `*pQ` to the identity matrix, then $x = QR$ is the QR decomposition of x . Returns 0 if x is not invertible or we hit a precision problem, and 1 otherwise.

`int QR_init(GEN x, GEN *pB, GEN *pQ, GEN *pL, long prec)` as `RgM_QR_init`, assuming further that x has `t_INT` or `t_REAL` coefficients.

`GEN R_from_QR(GEN x, long prec)` assuming that x is a square invertible `t_MAT` with `t_INT` or `t_REAL` coefficients, return the upper triangular R from the QR decomposition of x . Not memory clean. If the matrix is not known to have `t_INT` or `t_REAL` coefficients, apply `RgM_gtomp` first.

`GEN gaussred_from_QR(GEN x, long prec)` assuming that x is a square invertible `t_MAT` with `t_INT` or `t_REAL` coefficients, returns `qfgaussred(x~* x)`; this is essentially the upper triangular R matrix from the QR decomposition of x , renormalized to accomodate `qfgaussred` conventions. Not memory clean.

`GEN RgM_gram_schmidt(GEN e, GEN *ptB)` naive (unstable) Gram-Schmidt orthogonalization of the basis (e_i) given by the columns of `t_MAT` e . Return the e_i^* (as columns of a `t_MAT`) and set `*ptB` to the vector of squared lengths $|e_i^*|^2$.

`GEN RgM_Babai(GEN M, GEN y)` given a `t_MAT` M of maximal rank n and a `t_COL` y of the same dimension, apply Babai's nearest plane algorithm to return an *integral* x such that $y - Mx$ has small L_2 norm. This yields an approximate solution to the closest vector problem: if M is LLL-reduced, then

$$\|y - Mx\|_2 \leq 2(2/\sqrt{3})^n \|y - MX\|_2$$

for all $X \in \mathbf{Z}^n$.

`GEN RgM_Cholesky(GEN M)` given a square symmetric `t_MAT` M , return R such that ${}^tRR = M$, or NULL is no solution is found (M is not positive or was given with insufficient accuracy).

7.5.8 ZG.

Let G be a multiplicative group with neutral element 1_G whose multiplication is supported by `gmul` and where equality test is performed using `gidentical`, e.g. a matrix group. The following routines implement basic computations in the group algebra $\mathbf{Z}[G]$. All of them are shallow for efficiency reasons. A `ZG` is either

- a `t_INT` n , representing $n[1_G]$
- or a “factorization matrix” with two columns $[g, e]$: the first one contains group elements, sorted according to `cmp_universal`, and the second one contains integer “exponents”, representing $\sum e_i[g_i]$.

Note that `to_famat` and `to_famat_shallow(g, e)` allow to build the **ZG** $e[g]$ from $e \in \mathbf{Z}$ and $g \in G$.

GEN `ZG_normalize(GEN x)` given a `t_INT` x or a factorization matrix *without* assuming that the first column is properly sorted. Return a valid (sorted) **ZG**. Shallow function.

GEN `ZG_add(GEN x, GEN y)` return $x + y$; shallow function.

GEN `ZG_neg(GEN x)` return $-x$; shallow function.

GEN `ZG_sub(GEN x, GEN y)` return $x - y$; shallow function.

GEN `ZG_mul(GEN x, GEN y)` return xy ; shallow function.

GEN `ZG_G_mul(GEN x, GEN y)` given a **ZG** x and $y \in G$, return xy ; shallow function.

GEN `G_ZG_mul(GEN x, GEN y)` given a **ZG** y and $x \in G$, return xy ; shallow function.

GEN `ZG_Z_mul(GEN x, GEN n)` given a **ZG** x and $y \in \mathbf{Z}$, return xy ; shallow function.

GEN `ZGC_G_mul(GEN v, GEN x)` given v a vector of **ZG** and $x \in G$ return the vector (with the same type as v with entries $v[i] \cdot x$. Shallow function.

void `ZGC_G_mul_inplace(GEN v, GEN x)` as `ZGC_G_mul`, modifying v in place.

GEN `ZGC_Z_mul(GEN v, GEN n)` given v a vector of **ZG** and $n \in \mathbf{Z}$ return the vector (with the same type as v with entries $n \cdot v[i]$. Shallow function.

GEN `G_ZGC_mul(GEN x, GEN v)` given v a vector of **ZG** and $x \in G$ return the vector of $x \cdot v[i]$. Shallow function.

GEN `ZGCs_add(GEN x, GEN y)` add two sparse vectors of **ZG** elements (see Sparse linear algebra below).

7.5.9 Sparse and blackbox linear algebra.

A sparse column **zCs** v is a `t_COL` with two components C and E which are `t_VECSMALL` of the same length, representing $\sum_i E[i] * e_{C[i]}$, where (e_j) is the canonical basis. A sparse matrix (**zMs**) is a `t_VEC` of **zCs**.

FpCs and **FpMs** are identical to the above, but $E[i]$ is now interpreted as a *signed* C long integer representing an element of \mathbf{F}_p . This is important since p can be so large that $p + E[i]$ would not fit in a C long.

RgCs and **RgMs** are similar, except that the type of the components of E is now unspecified. Functions handling those later objects must not depend on the type of those components.

F2Ms are `t_VEC` of **F2Cs**. **F2Cs** are `t_VECSMALL` whoses entries are the nonzero coefficients (1).

It is not possible to derive the space dimension (number of rows) from the above data. Thus most functions take an argument **nbrow** which is the number of rows of the corresponding column/matrix in dense representation.

GEN `F2Ms_to_F2m(GEN M, long nbrow)` convert a **F2m** to a **F2Ms**.

GEN `F2m_to_F2Ms(GEN M)` convert a **F2m** to a **F2Ms**.

GEN `zCs_to_ZC(GEN C, long nbrow)` convert the sparse vector C to a dense **ZC** of dimension **nbrow**.

GEN zMs_to_ZM(GEN M, long nbrow) convert the sparse matrix M to a dense ZM whose columns have dimension nbrow.

GEN FpMs_FpC_mul(GEN M, GEN B, GEN p) multiply the sparse matrix M (over \mathbf{F}_p) by the FpC B . The result is an FpC, i.e. a dense vector.

GEN zMs_ZC_mul(GEN M, GEN B, GEN p) multiply the sparse matrix M by the ZC B (over \mathbf{Z}). The result is an ZC, i.e. a dense vector.

GEN FpV_FpMs_mul(GEN B, GEN M, GEN p) multiply the FpV B by the sparse matrix M (over \mathbf{F}_p). The result is an FpV, i.e. a dense vector.

GEN ZV_zMs_mul(GEN B, GEN M, GEN p) multiply the FpV B (over \mathbf{Z}) by the sparse matrix M . The result is an ZV, i.e. a dense vector.

void RgMs_structelim(GEN M, long nbrow, GEN A, GEN *p_col, GEN *p_row) M being a RgMs with nbrow rows, A being a list of row indices, perform structured elimination on M by removing some rows and columns until the number of effectively present rows is equal to the number of columns. The result is stored in two t_VECSMALLs, *p_col and *p_row: *p_col is a map from the new columns indices to the old one. *p_row is a map from the old rows indices to the new one (0 if removed).

GEN F2Ms_colelim(GEN M, long nbrow) returns some subset of the columns of M as a t_VECSMALL of indices, selected such that the dimension of the kernel of the matrix is preserved. The subset is not guaranteed to be minimal.

GEN F2Ms_ker(GEN M, long nbrow) returns some kernel vectors of M using block Lanczos algorithm.

GEN FpMs_leftkernel_elt(GEN M, long nbrow, GEN p) M being a sparse matrix over \mathbf{F}_p , return a nonzero FpV X such that XM components are almost all 0.

GEN FpMs_FpCs_solve(GEN M, GEN B, long nbrow, GEN p) solve the equation $MX = B$, where M is a sparse matrix and B is a sparse vector, both over \mathbf{F}_p . Return either a solution as a t_COL (dense vector), the index of a column which is linearly dependent from the others as a t_VECSMALL with a single component, or NULL (can happen if B is not in the image of M).

GEN FpMs_FpCs_solve_safe(GEN M, GEN B, long nbrow, GEN p) as above, but in the event that p is not a prime and an impossible division occurs, return NULL.

GEN ZpMs_ZpCs_solve(GEN M, GEN B, long nbrow, GEN p, long e) solve the equation $MX = B$, where M is a sparse matrix and B is a sparse vector, both over $\mathbf{Z}/p^e\mathbf{Z}$. Return either a solution as a t_COL (dense vector), or the index of a column which is linearly dependent from the others as a t_VECSMALL with a single component.

GEN gen_FpM_Wiedemann(void *E, GEN (*f)(void*, GEN), GEN B, GEN p) solve the equation $f(X) = B$ over \mathbf{F}_p , where B is a FpV, and f is a blackbox endomorphism, where $f(E, X)$ computes the value of f at the (dense) column vector X . Returns either a solution t_COL, or a kernel vector as a t_VEC.

GEN gen_ZpM_Dixon_Wiedemann(void *E, GEN (*f)(void*, GEN), GEN B, GEN p, long e) solve equation $f(X) = B$ over $\mathbf{Z}/p^e\mathbf{Z}$, where B is a ZV, and f is a blackbox endomorphism, where $f(E, X)$ computes the value of f at the (dense) column vector X . Returns either a solution t_COL, or a kernel vector as a t_VEC.

7.5.10 Obsolete functions.

The functions in this section are kept for backward compatibility only and will eventually disappear.

GEN `image2`(GEN `x`) compute the image of x using a very slow algorithm. Use `image` instead.

7.6 Integral, rational and generic polynomial arithmetic.

7.6.1 ZX.

void `RgX_check_ZX`(GEN `x`, const char `*s`) Assuming `x` is a `t_POL` raise an error if it is not a ZX (`s` should point to the name of the caller).

GEN `ZX_copy`(GEN `x`, GEN `p`) returns a copy of `x`.

long `ZX_max_lg`(GEN `x`) returns the effective length of the longest component in x .

GEN `scalar_ZX`(GEN `x`, long `v`) returns the constant ZX in variable v equal to the `t_INT` x .

GEN `scalar_ZX_shallow`(GEN `x`, long `v`) returns the constant ZX in variable v equal to the `t_INT` x . Shallow function not suitable for `gerepile` and friends.

GEN `ZX_renormalize`(GEN `x`, long `l`), as `normalizpol`, where $l = \lg(x)$, in place.

int `ZX_equal`(GEN `x`, GEN `y`) returns 1 if the two ZX have the same `degpol` and their coefficients are equal. Variable numbers are not checked.

int `ZX_equal1`(GEN `x`) returns 1 if the ZX x is equal to 1 and 0 otherwise.

int `ZX_is_monic`(GEN `x`) returns 1 if the ZX x is monic and 0 otherwise. The zero polynomial considered not monic.

GEN `ZX_add`(GEN `x`, GEN `y`) adds x and y .

GEN `ZX_sub`(GEN `x`, GEN `y`) subtracts x and y .

GEN `ZX_neg`(GEN `x`) returns $-x$.

GEN `ZX_Z_add`(GEN `x`, GEN `y`) adds the integer y to the ZX x .

GEN `ZX_Z_add_shallow`(GEN `x`, GEN `y`) shallow version of `ZX_Z_add`.

GEN `ZX_Z_sub`(GEN `x`, GEN `y`) subtracts the integer y to the ZX x .

GEN `Z_ZX_sub`(GEN `x`, GEN `y`) subtracts the ZX y to the integer x .

GEN `ZX_Z_mul`(GEN `x`, GEN `y`) multiplies the ZX x by the integer y .

GEN `ZX_mulu`(GEN `x`, ulong `y`) multiplies x by the integer y .

GEN `ZX_shifti`(GEN `x`, long `n`) shifts all coefficients of x by n bits, which can be negative.

GEN `ZX_Z_divexact`(GEN `x`, GEN `y`) returns x/y assuming all divisions are exact.

GEN `ZX_divuexact`(GEN `x`, ulong `y`) returns x/y assuming all divisions are exact.

GEN `ZX_remi2n`(GEN `x`, long `n`) reduces all coefficients of x to n bits, using `remi2n`.

GEN `ZX_mul`(GEN `x`, GEN `y`) multiplies x and y .

GEN ZX_sqr(GEN x, GEN p) returns x^2 .

GEN ZX_mulspec(GEN a, GEN b, long na, long nb). Internal routine: a and b are arrays of coefficients representing polynomials $\sum_{i=0}^{na-1} a[i]X^i$ and $\sum_{i=0}^{nb-1} b[i]X^i$. Returns their product (as a true GEN) in variable 0.

GEN ZX_sqrspec(GEN a, long na). Internal routine: a is an array of coefficients representing polynomial $\sum_{i=0}^{na-1} a[i]X^i$. Return its square (as a true GEN) in variable 0.

GEN ZX_rem(GEN x, GEN y) returns the remainder of the Euclidean division of $x \bmod y$. Assume that x, y are two ZX and that y is monic.

GEN ZX_mod_Xnm1(GEN T, ulong n) return T modulo $X^n - 1$. Shallow function.

GEN ZX_div_by_X_1(GEN T, GEN *r) return the quotient of T by $X - 1$. If r is not NULL set it to $T(1)$.

GEN ZX_digits(GEN x, GEN B) returns a vector of ZX $[c_0, \dots, c_n]$ of degree less than the degree of B and such that $x = \sum_{i=0}^n c_i B^i$. Assume that B is monic.

GEN ZXV_ZX_fromdigits(GEN v, GEN B) where $v = [c_0, \dots, c_n]$ is a vector of ZX, returns $\sum_{i=0}^n c_i B^i$.

GEN ZX_gcd(GEN x, GEN y) returns a gcd of the ZX x and y . Not memory-clean, but suitable for gerepileupto.

GEN ZX_gcd_all(GEN x, GEN y, GEN *pX) returns a gcd d of x and y . If pX is not NULL, set $*pX$ to a (nonzero) integer multiple of x/d . If x and y are both monic, then d is monic and $*pX$ is exactly x/d . Not memory clean.

GEN ZX_radical(GEN x) returns the largest squarefree divisor of the ZX x . Not memory clean.

GEN ZX_content(GEN x) returns the content of the ZX x .

long ZX_val(GEN P) as RgX_val, but assumes P has t_INT coefficients.

long ZX_valrem(GEN P, GEN *z) as RgX_valrem, but assumes P has t_INT coefficients.

GEN ZX_to_monic(GEN q GEN *L) given q a nonzero ZX, returns a monic integral polynomial Q such that $Q(x) = Cq(x/L)$, for some rational C and positive integer $L > 0$. If L is not NULL, set *L to L ; if $L = 1$, *L is set to gen_1. Shallow function.

GEN ZX_primitive_to_monic(GEN q, GEN *L) as ZX_to_monic except q is assumed to have trivial content, which avoids recomputing it. The result is suboptimal if q is not primitive (L larger than necessary), but remains correct. Shallow function.

GEN ZX_Z_normalize(GEN q, GEN *L) a restricted version of ZX_primitive_to_monic, where q is a *monic* ZX of degree > 0 . Finds the largest integer $L > 0$ such that $Q(X) := L^{-\deg q} q(Lx)$ is integral and return Q ; this is not well-defined if q is a monomial, in that case, set $L = 1$ and $Q = q$. If L is not NULL, set *L to L . Shallow function.

GEN ZX_Q_normalize(GEN q, GEN *L) a variant of ZX_Z_normalize where $L > 0$ is allowed to be rational, the monic $Q \in \mathbf{Z}[X]$ has possibly smaller coefficients. Shallow function.

GEN ZX_Q_mul(GEN x, GEN y) returns $x * y$, where y is a rational number and the resulting t_POL has rational entries.

long ZX_deflate_order(GEN P) given a nonconstant ZX P , returns the largest exponent d such that P is of the form $P(x^d)$.

`long ZX_deflate_max(GEN P, long *d)`. Given a nonconstant polynomial with integer coefficients P , sets d to `ZX_deflate_order(P)` and returns `RgX_deflate(P,d)`. Shallow function.

`GEN ZX_rescale(GEN P, GEN h)` returns $h^{\deg(P)}P(x/h)$. P is a ZX and h is a nonzero integer. Neither memory-clean nor suitable for `gerepileupto`.

`GEN ZX_rescale2n(GEN P, long n)` returns $2^n \deg(P)P(x \gg n)$ where P is a ZX.

`GEN ZX_rescale_lt(GEN P)` returns the monic integral polynomial $h^{\deg(P)-1}P(x/h)$, where P is a nonzero ZX and h is its leading coefficient. Neither memory-clean nor suitable for `gerepileupto`.

`GEN ZX_translate(GEN P, GEN c)` assume P is a ZX and c an integer. Returns $P(X+c)$ (optimized for $c = \pm 1$).

`GEN ZX_affine(GEN P, GEN a, GEN b)` P is a ZX, a and b are `t_INT`. Return $P(aX+b)$ (optimized for $b = \pm 1$). Not memory clean.

`GEN ZX_Z_eval(GEN P, GEN x)` evaluate the ZX P at the integer x .

`GEN ZX_unscale(GEN P, GEN h)` given a ZX P and a `t_INT` h , returns $P(hx)$. Not memory clean.

`GEN ZX_z_unscale(GEN P, long h)` given a ZX P , returns $P(hx)$. Not memory clean.

`GEN ZX_unscale2n(GEN P, long n)` given a ZX P , returns $P(x \ll n)$. Not memory clean.

`GEN ZX_unscale_div(GEN P, GEN h)` given a ZX P and a `t_INT` h such that $h \mid P(0)$, returns $P(hx)/h$. Not memory clean.

`GEN ZX_unscale_divpow(GEN P, GEN h, long k)` given a ZX P , a `t_INT` h and $k > 0$, returns $P(hx)/h^k$ assuming the result has integral coefficients. Not memory clean.

`GEN ZX_eval1(GEN P)` returns the integer $P(1)$.

`GEN ZX_graeffe(GEN p)` returns the Graeffe transform of p , i.e. the ZX q such that $p(x)p(-x) = q(x^2)$.

`GEN ZX_deriv(GEN x)` returns the derivative of x .

`GEN ZX_resultant(GEN A, GEN B)` returns the resultant of the ZX A and B .

`GEN ZX_disc(GEN T)` returns the discriminant of the ZX T .

`GEN ZX_factor(GEN T)` returns the factorization of the primitive part of T over $\mathbf{Q}[X]$ (the content is lost).

`int ZX_is_squarefree(GEN T)` returns 1 if the ZX T is squarefree, 0 otherwise.

`long ZX_is_irred(GEN T)` returns 1 if T is irreducible, and 0 otherwise.

`GEN ZX_squff(GEN T, GEN *E)` write the nonzero ZX T as a product $\prod T_i^{e_i}$ with the $e_1 < e_2 < \dots$ all distinct and the T_i pairwise coprime. Return the vector of the T_i , and set $*E$ to the vector of the e_i , as a `t_VECSMALL`. For efficiency, powers of x should have been removed from T using `ZX_valrem`, but the result is also correct if not. Not memory clean.

`GEN ZX_Uspensky(GEN P, GEN ab, long flag, long bitprec)` let P be a ZX polynomial whose real roots are simple and `bitprec` is the relative precision in bits. For efficiency reasons, P should not only have simple real roots but actually be primitive and squarefree, but the routine neither checks nor enforces this, and it returns correct results in this case as well.

- If `flag` is 0 returns a list of intervals that isolate the real roots of P . The return value is a column of elements which are either vectors $[a,b]$ of rational numbers meaning that there is a

single nonrational root in the open interval (a, b) or elements $x0$ such that $x0$ is a rational root of P . Beware that the limits of the open intervals can be roots of the polynomial.

- If `flag` is 1 returns an approximation of the real roots of P .
- If `flag` is 2 returns the number of roots.

The argument `ab` specify the interval in which the roots are searched. The default interval is $(-\infty, \infty)$. If `ab` is an integer or fraction a then the interval is $[a, \infty)$. If `ab` is a vector $[a, b]$, where `t_INT`, `t_FRAC` or `t_INFINITY` are allowed for a and b , the interval is $[a, b]$.

`long ZX_sturm(GEN P)` number of real roots of the nonconstant squarefree ZX P . For efficiency, it is advised to make P primitive first.

`long ZX_sturmpart(GEN P, GEN ab)` number of real roots of the nonconstant squarefree ZX P in the interval specified by `ab`: either `NULL` (no restriction) or a `t_VEC` $[a, b]$ with two real components (of type `t_INT`, `t_FRAC` or `t_INFINITY`). For efficiency, it is advised to make P primitive first.

`long ZX_sturm_irred(GEN P)` number of real roots of the ZX P , assumed irreducible over $\mathbf{Q}[X]$. For efficiency, it is advised to make P primitive first.

`long ZX_realroots_irred(GEN P, long prec)` real roots of the ZX P , assumed irreducible over $\mathbf{Q}[X]$ to precision `prec`. For efficiency, it is advised to make P primitive first.

7.6.2 Resultants.

`GEN ZX_ZXY_resultant(GEN A, GEN B)` under the assumption that A in $\mathbf{Z}[Y]$, B in $\mathbf{Q}[Y][X]$, and $R = \text{Res}_Y(A, B) \in \mathbf{Z}[X]$, returns the resultant R .

`GEN ZX_composedsum(GEN P, GEN Q)` if $P = a \prod_i (x - p_i)$ and $Q = b \prod_j (x - q_j)$ in some suitable algebraic extension, return $ab \prod_{i,j} (x - (p_i + q_j))$.

`GEN ZX_compositum(GEN A, GEN B, long *lambda)` given two irreducible ZX , returns an irreducible ZX C defining their compositum and set `lambda` to a small integer k such that if α is a root of A and β is a root of B , then $k\alpha + \beta$ is a root of C .

`GEN ZX_ZXY_rnfequation(GEN A, GEN B, long *lambda)`, assume A in $\mathbf{Z}[Y]$, B in $\mathbf{Q}[Y][X]$, and $R = \text{Res}_Y(A, B) \in \mathbf{Z}[X]$. If `lambda` = `NULL`, returns R as in `ZY_ZXY_resultant`. Otherwise, `lambda` must point to some integer, e.g. 0 which is used as a seed. The function then finds a small $\lambda \in \mathbf{Z}$ (starting from `*lambda`) such that $R_\lambda(X) := \text{Res}_Y(A, B(X + \lambda Y))$ is squarefree, resets `*lambda` to the chosen value and returns R_λ .

7.6.3 ZXV.

`GEN ZXV_equal(GEN x, GEN y)` returns 1 if the two vectors of ZX are equal, as per `ZX_equal` (variables are not checked to be equal) and 0 otherwise.

`GEN ZXV_Z_mul(GEN x, GEN y)` multiplies the vector of ZX x by the integer y .

`GEN ZXV_remi2n(GEN x, long n)` applies `ZX_remi2n` to all coefficients of x .

`GEN ZXV_dotproduct(GEN x, GEN y)` as `RgV_dotproduct` assuming x and y have ZX entries.

7.6.4 ZXT.

`GEN ZXT_remi2n(GEN x, long n)` applies `ZX_remi2n` to all leaves of the tree x .

7.6.5 ZXQ.

GEN ZXQ_mul(GEN x, GEN y, GEN T) returns $x * y \bmod T$, assuming that all inputs are ZXs and that T is monic.

GEN ZXQ_sqr(GEN x, GEN T) returns $x^2 \bmod T$, assuming that all inputs are ZXs and that T is monic.

GEN ZXQ_powu(GEN x, ulong n, GEN T) returns $x^n \bmod T$, assuming that all inputs are ZXs and that T is monic.

GEN ZXQ_powers(GEN x, long n, GEN T) returns $[x^0, \dots, x^n] \bmod T$ as a t_VEC, assuming that all inputs are ZXs and that T is monic.

GEN ZXQ_charpoly(GEN A, GEN T, long v): let T and A be ZXs, returns the characteristic polynomial of $\text{Mod}(A, T)$. More generally, A is allowed to be a QX, hence possibly has rational coefficients, *assuming* the result is a ZX, i.e. the algebraic number $\text{Mod}(A, T)$ is integral over \mathbb{Z} .

GEN ZXQ_minpoly(GEN A, GEN B, long d, ulong bound) let T and A be ZXs, returns the minimal polynomial of $\text{Mod}(A, T)$ assuming it has degree d and its coefficients are less than 2^{bound} . More generally, A is allowed to be a QX, hence possibly has rational coefficients, *assuming* the result is a ZX, i.e. the algebraic number $\text{Mod}(A, T)$ is integral over \mathbb{Z} .

7.6.6 ZXn.

GEN ZXn_mul(GEN x, GEN y, long n) return $xy \pmod{X^n}$.

GEN ZXn_sqr(GEN x, long n) return $x^2 \pmod{X^n}$.

GEN eta_ZXn(long r, long n) return $\eta(X^r) = \prod_{i>0} (1 - X^{ri}) \pmod{X^n}$, $r > 0$.

GEN eta_product_ZXn(GEN DR, long n): $DR = [D, R]$ being a vector with two t_VECSMALL components, return $\prod_i \eta(X^{d_i})^{r_i}$. Shallow function.

7.6.7 ZXQM.

ZXQM are matrices of ZXQ. All entries must be integers or polynomials of degree strictly less than the degree of T .

GEN ZXQM_mul(GEN x, GEN y, GEN T) returns $x * y \bmod T$, assuming that all inputs are ZXs and that T is monic.

GEN ZXQM_sqr(GEN x, GEN T) returns $x^2 \bmod T$, assuming that all inputs are ZXs and that T is monic.

7.6.8 ZXQX.

GEN ZXQX_mul(GEN x, GEN y, GEN T) returns $x * y$, assuming that all inputs are ZXQXs and that T is monic.

GEN ZXQX_ZXQ_mul(GEN x, GEN y, GEN T) returns $x * y$, assuming that x is a ZXQX, y is a ZXQ and T is monic.

GEN ZXQX_sqr(GEN x, GEN T) returns x^2 , assuming that all inputs are ZXQXs and that T is monic.

GEN ZXQX_gcd(GEN x, GEN y, GEN T) returns the gcd of x and y , assuming that all inputs are ZXQXs and that T is monic.

7.6.9 ZXX.

`void RgX_check_ZXX(GEN x, const char *s)` Assuming x is a `t_POL` raise an error if it one of its coefficients is not an integer or a `ZX` (s should point to the name of the caller).

`GEN ZXX_renormalize(GEN x, long l)`, as `normalizpol`, where $l = \lg(x)$, in place.

`long ZXX_max_lg(GEN x)` returns the effective length of the longest component in x ; assume all coefficients are `t_INT` or `ZXs`.

`GEN ZXX_evalx0(GEN P)` returns $P(X, 0)$.

`GEN ZXX_Z_mul(GEN x, GEN y)` returns xy .

`GEN ZXX_Q_mul(GEN x, GEN y)` returns $x*y$, where y is a rational number and the resulting `t_POL` has rational entries.

`GEN ZXX_Z_add_shallow(GEN x, GEN y)` returns $x + y$. Shallow function.

`GEN ZXX_Z_divexact(GEN x, GEN y)` returns x/y assuming all integer divisions are exact.

`GEN Kronecker_to_ZXX(GEN z, long n, long v)` recover $P(X, Y)$ from its Kronecker form $P(X, X^{2n-1})$ (see `RgXX_to_Kronecker`), v is the variable number corresponding to Y . Shallow function.

`GEN Kronecker_to_ZXQX(GEN z, GEN T)`. Let $n = \deg T$ and let $P(X, Y) \in \mathbf{Z}[X, Y]$ lift a polynomial in $K[Y]$, where $K := \mathbf{Z}[X]/(T)$ and $\deg_X P < 2n - 1$ — such as would result from multiplying minimal degree lifts of two polynomials in $K[Y]$. Let $z = P(t, t^{2n-1})$ be a Kronecker form of P (see `RgXX_to_Kronecker`), this function returns $Q \in \mathbf{Z}[X, t]$ such that Q is congruent to $P(X, t)$ mod $(T(X))$, $\deg_X Q < n$. Not stack-clean. Note that t need not be the same variable as Y !

`GEN ZXX_mul_Kronecker(GEN P, GEN Q, long n)` return `ZX_mul` applied to the Kronecker forms $P(X, X^{2n-1})$ and $Q(X, X^{2n-1})$ of P and Q . Not memory clean.

`GEN ZXX_sqr_Kronecker(GEN P, long n)` return `ZX_sqr` applied to the Kronecker forms $P(X, X^{2n-1})$ of P . Not memory clean.

7.6.10 QX.

`void RgX_check_QX(GEN x, const char *s)` Assuming x is a `t_POL` raise an error if it is not a `QX` (s should point to the name of the caller).

`GEN QX_mul(GEN x, GEN y)`

`GEN QX_sqr(GEN x)`

`GEN QX_ZX_rem(GEN x, GEN y)` y is assumed to be monic.

`GEN QX_gcd(GEN x, GEN y)` returns a gcd of the `QX` x and y .

`GEN QX_disc(GEN T)` returns the discriminant of the `QX` T .

`GEN QX_factor(GEN T)` as `ZX_factor`.

`GEN QX_resultant(GEN A, GEN B)` returns the resultant of the `QX` A and B .

`GEN QX_complex_roots(GEN p, long l)` returns the complex roots of the `QX` p at accuracy l , where real roots are returned as `t_REALs`. More efficient when p is irreducible and primitive. Special case of `cleanroots`.

7.6.11 QXQ.

GEN QXQ_norm(GEN A, GEN B) A being a QX and B being a ZX, returns the norm of the algebraic number $A \bmod B$, using a modular algorithm. To ensure that B is a ZX, one may replace it by **Q_primpart**(B), which of course does not change the norm.

If A is not a ZX — it has a denominator —, but the result is nevertheless known to be an integer, it is much more efficient to call **QXQ_intnorm** instead.

GEN QXQ_intnorm(GEN A, GEN B) A being a QX and B being a ZX, returns the norm of the algebraic number $A \bmod B$, *assuming* that the result is an integer, which is for instance the case is $A \bmod B$ is an algebraic integer, in particular if A is a ZX. To ensure that B is a ZX, one may replace it by **Q_primpart**(B) (which of course does not change the norm).

If the result is not known to be an integer, you must use **QXQ_norm** instead, which is slower.

GEN QXQ_mul(GEN A, GEN B, GEN T) returns the product of A and B modulo T where both A and B are a QX and T is a monic ZX.

GEN QXQ_sqr(GEN A, GEN T) returns the square of A modulo T where A is a QX and T is a monic ZX.

GEN QXQ_inv(GEN A, GEN B) returns the inverse of A modulo B where A is a QX and B is a ZX. Should you need this for a QX B , just use

```
QXQ_inv(A, Q_primpart(B));
```

But in all cases where modular arithmetic modulo B is desired, it is much more efficient to replace B by **Q_primpart**(B) once and for all.

GEN QXQ_div(GEN A, GEN B, GEN T) returns A/B modulo T where A and B are QX and T is a ZX. Use this function when the result is expected to be of the same size as $B^{-1} \bmod T$ or smaller. Otherwise, it will be faster to use **QXQ_mul**(**A**, **QXQ_inv**(**B**, **T**), **T**).

GEN QXQ_charpoly(GEN A, GEN T, long v) where A is a QX and T is a ZX, returns the characteristic polynomial of $\text{Mod}(A, T)$. If the result is known to be a ZX, then calling **ZXQ_charpoly** will be faster.

GEN QXQ_powers(GEN x, long n, GEN T) returns $[x^0, \dots, x^n]$ as **RgXQ_powers** would, but in a more efficient way when x has a huge integer denominator (we start by removing that denominator). Assume that x is a QX and T is a ZX. Meant to precompute powers of algebraic integers in $\mathbf{Q}[t]/(T)$.

GEN QXQ_reverse(GEN f, GEN T) as **RgXQ_reverse**, assuming f is a QX.

GEN QX_ZXQV_eval(GEN f, GEN nV, GEN dV) as **RgX_RgXQV_eval**, except that f is assumed to be a QX, V is given implicitly by a numerator **nV** (ZV) and denominator **dV** (a positive **t_INT** or **NULL** for trivial denominator). Not memory clean, but suitable for **gerepileupto**.

GEN QXV_QXQ_eval(GEN v, GEN a, GEN T) v is a vector of QXs (possibly scalars, i.e. rational numbers, for convenience), a and T both QX. Return the vector of evaluations at a modulo T . Not memory clean, nor suitable for **gerepileupto**.

GEN QXY_QXQ_evalx(GEN P, GEN a, GEN T) $P(X, Y)$ is a **t_POL** with QX coefficients (possibly scalars, i.e. rational numbers, for convenience), a and T both QX. Return the QX $P(a \bmod T, Y)$. Not memory clean, nor suitable for **gerepileupto**.

7.6.12 QXQX.

GEN QXQX_mul(GEN x, GEN y, GEN T) where T is a monic ZX.

GEN QXQX_QXQ_mul(GEN x, GEN y, GEN T) where T is a monic ZX.

GEN QXQX_sqr(GEN x, GEN T) where T is a monic ZX

GEN QXQX_powers(GEN x, long n, GEN T) where T is a monic ZX

GEN nfgcd(GEN P, GEN Q, GEN T, GEN den) given P and Q in $\mathbf{Z}[X, Y]$, T monic irreducible in $\mathbf{Z}[Y]$, returns the primitive d in $\mathbf{Z}[X, Y]$ which is a gcd of P, Q in $K[X]$, where K is the number field $\mathbf{Q}[Y]/(T)$. If not NULL, den is a multiple of the integral denominator of the (monic) gcd of P, Q in $K[X]$.

GEN nfgcd_all(GEN P, GEN Q, GEN T, GEN den, GEN *Pnew) as nfgcd. If Pnew is not NULL, set *Pnew to a nonzero integer multiple of P/d . If P and Q are both monic, then d is monic and *Pnew is exactly P/d . Not memory clean if the gcd is 1 (in that case *Pnew is set to P).

GEN QXQX_gcd(GEN x, GEN y, GEN T) returns the gcd of x and y , assuming that x and y are QXQXs and that T is a monic ZX.

GEN QXQX_homogenous_evalpow(GEN P, GEN a, GEN B, GEN T) Evaluate the homogenous polynomial associated to the univariate polynomial P on (a, b) where B is the vector of powers of b with exponents 0 to the degree of P (QXQ_powers(b, degpol(P), T)).

7.6.13 QXQM.

QXQM are matrices of QXQ. All entries must be t_INT, t_FRAC or polynomials of degree strictly less than the degree of T , which must be a monic ZX.

GEN QXQM_mul(GEN x, GEN y, GEN T) returns $x * y \bmod T$.

GEN QXQM_sqr(GEN x, GEN T) returns $x^2 \bmod T$.

7.6.14 zx.

GEN zero_zx(long sv) returns a zero zx in variable v .

GEN polx_zx(long sv) returns the variable v as degree 1 Flx.

GEN zx_renormalize(GEN x, long l), as Flx_renormalize, where $l = \lg(x)$, in place.

GEN zx_shift(GEN T, long n) return T multiplied by x^n , assuming $n \geq 0$.

long zx_lval(GEN f, long p) return the valuation of f at p .

GEN zx_z_divexact(GEN x, long y) return x/y assuming all divisions are exact.

7.6.15 RgX.

7.6.15.1 Tests.

`long RgX_degree(GEN x, long v)` x being a `t_POL` and $v \geq 0$, returns the degree in v of x . Error if x is not a polynomial in v .

`int RgX_isscalar(GEN x)` return 1 if all the coefficients of x of degree > 0 are 0 (as per `gequal0`).

`int RgX_is_rational(GEN P)` return 1 if the `RgX` P has only rational coefficients (`t_INT` and `t_FRAC`), and 0 otherwise.

`int RgX_is_QX(GEN P)` return 1 if the `RgX` P has only `t_INT` and `t_FRAC` coefficients, and 0 otherwise.

`int RgX_is_ZX(GEN P)` return 1 if the `RgX` P has only `t_INT` coefficients, and 0 otherwise.

`int RgX_is_monomial(GEN x)` returns 1 (true) if x is a nonzero monomial in its main variable, 0 otherwise.

`long RgX_equal(GEN x, GEN y)` returns 1 if the `t_POLs` x and y have the same `degpol` and their coefficients are equal (as per `gequal`). Variable numbers are not checked. Note that this is more stringent than `gequal(x,y)`, which only checks whether $x - y$ satisfies `gequal0`; in particular, they may have different apparent degrees provided the extra leading terms are 0.

`long RgX_equal_var(GEN x, GEN y)` returns 1 if x and y have the same variable number and `RgX_equal(x,y)` is 1.

7.6.15.2 Coefficients, blocks.

`GEN RgX_coeff(GEN P, long n)` return the coefficient of x^n in P , defined as `gen_0` if $n < 0$ or $n > \text{degpol}(P)$. Shallow function.

`int RgX_blocks(GEN P, long n, long m)` writes $P(X) = a_0(X) + X^n * a_1(X) * X^n + \dots + X^{n*(m-1)} a_{m-1}(X)$, where the a_i are polynomial of degree at most $n - 1$ (except possibly for the last one) and returns $[a_0(X), a_1(X), \dots, a_{m-1}(X)]$. Shallow function.

`void RgX_even_odd(GEN p, GEN *pe, GEN *po)` write $p(X) = E(X^2) + XO(X^2)$ and set `*pe = E`, `*po = O`. Shallow function.

`GEN RgX_splitting(GEN P, long k)` write $P(X) = a_0(X^k) + X a_1(X^k) + \dots + X^{k-1} a_{k-1}(X^k)$ and return $[a_0(X), a_1(X), \dots, a_{k-1}(X)]$. Shallow function.

`GEN RgX_copy(GEN x)` returns (a deep copy of) x .

`GEN RgX_renormalize(GEN x)` remove leading terms in x which are equal to (necessarily inexact) zeros.

`GEN RgX_renormalize_lg(GEN x, long lx)` as `setlg(x, lx)` followed by `RgX_renormalize(x)`. Assumes that $lx \leq \lg(x)$.

`GEN RgX_recip(GEN P)` returns the reverse of the polynomial P , i.e. $X^{\deg P} P(1/X)$.

`GEN RgX_recip_shallow(GEN P)` shallow function of `RgX_recip`.

`GEN RgX_recip_i(GEN P)` shallow function of `RgX_recip`, where we further assume that $P(0) \neq 0$, so that the degree of the output is the degree of P .

`long rfracrecip(GEN *a, GEN *b)` let `*a` and `*b` be such that their quotient F is a `t_RFRAC` in variable X . Write $F(1/X) = X^v A/B$ where A and B are coprime to X and v in \mathbf{Z} . Set `*a` to A , `*b` to B and return v .

`GEN RgX_deflate(GEN P, long d)` assuming P is a polynomial of the form $Q(X^d)$, return Q . Shallow function, not suitable for `gerepileupto`.

`long RgX_deflate_order(GEN P)` given a nonconstant polynomial P , returns the largest exponent d such that P is of the form $P(x^d)$ (use `gequal0` to check whether coefficients are 0).

`long RgX_deflate_max(GEN P, long *d)` given a nonconstant polynomial P , sets `d` to `RgX_deflate_order(P)` and returns `RgX_deflate(P,d)`. Shallow function.

`long rfrac_deflate_order(GEN F)` as `RgX_deflate_order` where F is a nonconstant `t_RFRAC`.

`long rfrac_deflate_max(GEN F, long *d)` as `RgX_deflate_max` where F is a nonconstant `t_RFRAC`.

`GEN rfrac_deflate(GEN F, long m)` as `RgX_deflate` where F is a `t_RFRAC`.

`GEN RgX_inflate(GEN P, long d)` return $P(X^d)$. Shallow function, not suitable for `gerepileupto`.

`GEN RgX_rescale_to_int(GEN x)` given a polynomial x with real entries (`t_INT`, `t_FRAC` or `t_REAL`), return a `ZX` which is very close to Dx for some well-chosen integer D . More precisely, if the input is exact, D is the denominator of x ; else it is a power of 2 chosen so that all inexact entries are correctly rounded to 1 ulp.

`GEN RgX_homogenize(GEN P, long v)` Return the homogenous polynomial associated to P in the secondary variable v , that is $y^d * P(x/y)$ where d is the degree of P , x is the variable of P , and y is the variable with number v .

`GEN RgX_homogenous_evalpow(GEN P, GEN a, GEN B)` Evaluate the homogenous polynomial associated to the univariate polynomial P on (a,b) where B is the vector of powers of b with exponents 0 to the degree of P (`gpowers(b,degpol(P))`).

`GEN RgXX_to_Kronecker(GEN P, long n)` Assuming $P(X,Y)$ is a polynomial of degree in X strictly less than n , returns $P(X, X^{2*n-1})$, the Kronecker form of P . Shallow function.

`GEN RgXX_to_Kronecker_spec(GEN Q, long lQ, long n)` return `RgXX_to_Kronecker(P,n)`, where P is the polynomial $\sum_{i=0}^{lQ-1} Q[i]x^i$. To be used when splitting the coefficients of genuine polynomials into blocks. Shallow function.

7.6.15.3 Shifts, valuations.

`GEN RgX_shift(GEN x, long n)` returns $x * t^n$ if $n \geq 0$, and $x \backslash t^{-n}$ otherwise.

`GEN RgX_shift_shallow(GEN x, long n)` as `RgX_shift`, but shallow (coefficients are not copied).

`GEN RgX_rotate_shallow(GEN P, long k, long p)` returns $P * X^k \pmod{X^p - 1}$, assuming the degree of P is strictly less than p , and $k \geq 0$.

`void RgX_shift_inplace_init(long v)` $v \geq 0$, prepare for a later call to `RgX_shift_inplace`. Reserves v words on the stack.

`GEN RgX_shift_inplace(GEN x, long v)` $v \geq 0$, assume that `RgX_shift_inplace_init(v)` has been called (reserving v words on the stack), immediately followed by a `t_POL` x . Return `RgX_shift(x,v)` by shifting x in place. To be used as follows

```

RgX_shift_inplace_init(v);
av = avma;
...
x = gerepileupto(av, ...); /* a t_POL */
return RgX_shift_inplace(x, v);

```

`long RgX_valrem(GEN P, GEN *pz)` returns the valuation v of the `t_POL` P with respect to its main variable X . Check whether coefficients are 0 using `isexactzero`. Set `*pz` to `RgX_shift_shallow(P, -v)`.

`long RgX_val(GEN P)` returns the valuation v of the `t_POL` P with respect to its main variable X . Check whether coefficients are 0 using `isexactzero`.

`long RgX_valrem_inexact(GEN P, GEN *z)` as `RgX_valrem`, using `gequal0` instead of `isexactzero`.

`long RgXV_maxdegree(GEN V)` returns the maximum of the degrees of the components of the vector of `t_POLs` V .

7.6.15.4 Basic arithmetic.

`GEN RgX_add(GEN x, GEN y)` adds x and y .

`GEN RgX_sub(GEN x, GEN y)` subtracts x and y .

`GEN RgX_neg(GEN x)` returns $-x$.

`GEN RgX_Rg_add(GEN y, GEN x)` returns $x + y$.

`GEN RgX_Rg_add_shallow(GEN y, GEN x)` returns $x + y$; shallow function.

`GEN Rg_RgX_sub(GEN x, GEN y)`

`GEN RgX_Rg_sub(GEN y, GEN x)` returns $x - y$

`GEN RgX_Rg_mul(GEN y, GEN x)` multiplies the `RgX` y by the scalar x .

`GEN RgX_muls(GEN y, long s)` multiplies the `RgX` y by the `long` s .

`GEN RgX_mul2n(GEN y, long n)` multiplies the `RgX` y by 2^n .

`GEN RgX_Rg_div(GEN y, GEN x)` divides the `RgX` y by the scalar x .

`GEN RgX_divs(GEN y, long s)` divides the `RgX` y by the `long` s .

`GEN RgX_Rg_divexact(GEN x, GEN y)` exact division of the `RgX` y by the scalar x .

`GEN RgX_Rg_eval_bk(GEN f, GEN x)` returns $f(x)$ using Brent and Kung algorithm. (Use `poleval` for Horner algorithm.)

`GEN RgX_RgV_eval(GEN f, GEN V)` as `RgX_Rg_eval_bk(f, x)`, assuming V was output by `gpowers(x, n)` for some $n \geq 1$.

`GEN RgXV_RgV_eval(GEN f, GEN V)` apply `RgX_RgV_eval_bk(, V)` to all the components of the vector f .

`GEN RgX_normalize(GEN x)` divides x by its leading coefficient. If the latter is 1, x itself is returned, not a copy. Leading coefficients equal to 0 are stripped, e.g.

```
0.*t^3 + Mod(0,3)*t^2 + 2*t
```

is normalized to t .

GEN RgX_mul(GEN x, GEN y) multiplies the two t_POL (in the same variable) x and y. Detect the coefficient ring and use an appropriate algorithm.

GEN RgX_mul_i(GEN x, GEN y) multiplies the two t_POL (in the same variable) x and y. Do not detect the coefficient ring. Use a generic Karatsuba algorithm.

GEN RgX_mul_normalized(GEN A, long a, GEN B, long b) returns $(X^a + A)(X^b + B) - X^{(a+b)}$, where we assume that $\deg A < a$ and $\deg B < b$ are polynomials in the same variable X .

GEN RgX_sqr(GEN x) squares the t_POL x. Detect the coefficient ring and use an appropriate algorithm.

GEN RgX_sqr_i(GEN x) squares the t_POL x. Do not detect the coefficient ring. Use a generic Karatsuba algorithm.

GEN RgXV_prod(GEN V), V being a vector of RgX, returns their product.

GEN RgX_divrem(GEN x, GEN y, GEN *r) by default, returns the Euclidean quotient and store the remainder in r . Three special values of r change that behavior • NULL: do not store the remainder, used to implement RgX_div,

- ONLY_REM: return the remainder, used to implement RgX_rem,
- ONLY_DIVIDES: return the quotient if the division is exact, and NULL otherwise.

In the generic case, the remainder is created after the quotient and can be disposed of individually with a cgiv(r).

GEN RgX_div(GEN x, GEN y)

GEN RgX_div_by_X_x(GEN A, GEN a, GEN *r) returns the quotient of the RgX A by $(X - a)$, and sets r to the remainder A(a).

GEN RgX_rem(GEN x, GEN y)

GEN RgX_pseudodivrem(GEN x, GEN y, GEN *ptr) compute a pseudo-quotient q and pseudo-remainder r such that $\text{lc}(y)^{\deg(x)-\deg(y)+1}x = qy + r$. Return q and set *ptr to r .

GEN RgX_pseudorem(GEN x, GEN y) return the remainder in the pseudo-division of x by y .

GEN RgXQX_pseudorem(GEN x, GEN y, GEN T) return the remainder in the pseudo-division of x by y over $R[X]/(T)$.

int ZXQX_dvd(GEN x, GEN y, GEN T) let T be a monic irreducible ZX, let x, y be t_POL whose coefficients are either t_INTs or ZX in the same variable as T . Assume further that the leading coefficient of y is an integer. Return 1 if $y|x$ in $(\mathbb{Z}[Y]/(T))[X]$, and 0 otherwise.

GEN RgXQX_pseudodivrem(GEN x, GEN y, GEN T, GEN *ptr) compute a pseudo-quotient q and pseudo-remainder r such that $\text{lc}(y)^{\deg(x)-\deg(y)+1}x = qy + r$ in $R[X]/(T)$. Return q and set *ptr to r .

GEN RgX_mulXn(GEN a, long n) returns $a * X^n$. This may be a t_FRAC if $n < 0$ and the valuation of a is not large enough.

GEN RgX_addmulXn(GEN a, GEN b, long n) returns $a + b * X^n$, assuming that $n > 0$.

GEN RgX_addmulXn_shallow(GEN a, GEN b, long n) shallow variant of RgX_addmulXn.

GEN RgX_digits(GEN x, GEN B) returns a vector of RgX $[c_0, \dots, c_n]$ of degree less than the degree of B and such that $x = \sum_{i=0}^n c_i B^i$.

7.6.15.5 Internal routines working on coefficient arrays.

These routines operate on coefficient blocks which are invalid GENs. A GEN argument a or b in routines below is actually a coefficient arrays representing the polynomials $\sum_{i=0}^{na-1} a[i]X^i$ and $\sum_{i=0}^{nb-1} b[i]X^i$. Note that $a[0]$ and $b[0]$ contain coefficients and not the mandatory GEN codeword. This allows to implement divide-and-conquer methods directly, without needing to allocate wrappers around coefficient blocks.

GEN RgX_mulspec(GEN a, GEN b, long na, long nb). Internal routine: given two coefficient arrays representing polynomials, return their product (as a true GEN) in variable 0.

GEN RgX_sqrspec(GEN a, long na). Internal routine: given a coefficient array representing a polynomial r return its square (as a true GEN) in variable 0.

GEN RgX_addspec(GEN x, GEN y, long nx, long ny) given two coefficient arrays representing polynomials, return their sum (as a true GEN) in variable 0.

GEN RgX_addspec_shallow(GEN x, GEN y, long nx, long ny) shallow variant of RgX_addspec.

7.6.15.6 GCD, Resultant.

GEN RgX_gcd(GEN x, GEN y) returns the GCD of x and y , assumed to be t_POL s in the same variable.

GEN RgX_gcd_simple(GEN x, GEN y) as RgX_gcd using a standard extended Euclidean algorithm. Usually slower than RgX_gcd.

GEN RgX_extgcd(GEN x, GEN y, GEN *u, GEN *v) returns $d = \text{GCD}(x, y)$, and sets $*u, *v$ to the Bezout coefficients such that $*ux + *vy = d$. Uses a generic subresultant algorithm.

GEN RgX_extgcd_simple(GEN x, GEN y, GEN *u, GEN *v) as RgX_extgcd using a standard extended Euclidean algorithm. Usually slower than RgX_extgcd.

GEN RgX_halfgcd(GEN x, GEN y) assuming x and y are t_POL s in the same variable, returns a 2×2 t_MAT M with t_POL entries, such that $M * [x, y] == [a, b]$ such that $\deg a \geq \lceil \max(\deg x, \deg y) / 2 \rceil > \deg b$.

GEN RgX_halfgcd_all(GEN x, GEN y, GEN *pt_a, GEN *pt_b) as RgX_halfgcd, in addition, if pt_a (resp. pt_b) is not NULL, $*pt_a$ (resp. $*pt_b$) is set to a (resp. b).

GEN RgX_chinese_coprime(GEN x, GEN y, GEN Tx, GEN Ty, GEN Tz) returns an RgX, congruent to $x \bmod Tx$ and to $y \bmod Ty$. Assumes Tx and Ty are coprime, and $Tz = Tx * Ty$ or NULL (in which case it is computed within).

GEN RgX_disc(GEN x) returns the discriminant of the t_POL x with respect to its main variable.

GEN RgX_resultant_all(GEN x, GEN y, GEN *sol) returns $\text{resultant}(x, y)$. If sol is not NULL, sets it to the last nonconstant remainder in the polynomial remainder sequence if it exists and to gen_0 otherwise (e.g. one polynomial has degree 0).

7.6.15.7 Other operations.

GEN RgX_gtofp(GEN x, GEN prec) returns the polynomial obtained by applying

gtofp(gel(x,i), prec)

to all coefficients of x .

GEN RgX_fpnorml2(GEN x, long prec) returns (a stack-clean variant of)

gnorml2(RgX_gtofp(x, prec))

GEN RgX_deriv(GEN x) returns the derivative of x with respect to its main variable.

GEN RgX_integ(GEN x) returns the primitive of x vanishing at 0, with respect to its main variable.

GEN RgX_rescale(GEN P, GEN h) returns $h^{\deg(P)}P(x/h)$. P is an RgX and h is nonzero. (Leaves small objects on the stack. Suitable but inefficient for gerepileupto.)

GEN RgXV_rescale(GEN v, GEN h) apply RgX_unscale to a vector of RgX.

GEN RgX_unscale(GEN P, GEN h) returns $P(hx)$. (Leaves small objects on the stack. Suitable but inefficient for gerepileupto.)

GEN RgXV_unscale(GEN v, GEN h) apply RgX_unscale to a vector of RgX.

GEN RgX_translate(GEN P, GEN c) assume c is a scalar or a polynomials whose main variable has lower priority than the main variable X of P . Returns $P(X + c)$ (optimized for $c = \pm 1$).

GEN RgX_affine(GEN P, GEN a, GEN b) Return $P(aX + b)$ (optimized for $b = \pm 1$). Not memory clean.

7.6.15.8 Function related to modular forms.

GEN RgX_act_GL2Q(GEN g, long k) let R be a commutative ring and $g = [a, b; c, d]$ be in $\text{GL}_2(\mathbf{Q})$, g acts (on the left) on homogeneous polynomials of degree $k - 2$ in $V := R[X, Y]_{k-2}$ via

$$g \cdot P := P(dX - cY, -bX + aY) = (\det g)^{k-2} P((X, Y) \cdot g^{-1}).$$

This function returns the matrix in $M_{k-1}(R)$ of $P \mapsto g \cdot P$ in the basis $(X^{k-2}, \dots, Y^{k-2})$ of V .

GEN RgX_act_ZGL2Q(GEN z, long k) let $G := \text{GL}_2(\mathbf{Q})$, acting on $R[X, Y]_{k-2}$ and $z \in \mathbf{Z}[G]$. Return the matrix giving $P \mapsto z \cdot P$ in the basis $(X^{k-2}, \dots, Y^{k-2})$.

7.6.16 RgXn.

GEN RgXn_red_shallow(GEN x, long n) return $x \% t^n$, where $n \geq 0$. Shallow function.

GEN RgXn_recip_shallow(GEN P) returns $X^n P(1/X)$. Shallow function.

GEN RgXn_mul(GEN a, GEN b, long n) returns ab modulo X^n , where a, b are two t_POL in the same variable X and $n \geq 0$. Uses Karatsuba algorithm (Mulders, Hanrot-Zimmermann variant).

GEN RgXn_sqr(GEN a, long n) returns a^2 modulo X^n , where a is a t_POL in the variable X and $n \geq 0$. Uses Karatsuba algorithm (Mulders, Hanrot-Zimmermann variant).

GEN RgX_mulhigh_i(GEN f, GEN g, long n) return the Euclidean quotient of $f(x) * g(x)$ by x^n (high product). Uses RgXn_mul applied to the reciprocal polynomials of f and g . Not suitable for gerepile.

GEN RgX_sqrhigh_i(GEN f, long n) return the Euclidean quotient of $f(x)^2$ by x^n (high product). Uses RgXn_sqr applied to the reciprocal polynomial of f . Not suitable for gerepile.

GEN RgXn_inv(GEN a, long n) returns a^{-1} modulo X^n , where a is a t_POL in the variable X and $n \geq 0$. Uses Newton-Raphson algorithm.

GEN RgXn_inv_i(GEN a, long n) as RgXn_inv without final garbage collection (suitable for gerepileupto).

GEN RgXn_div(GEN a, GEN b, long n) returns a/b modulo X^n , where a and b are t_POLs in the variable X and $n \geq 0$. Uses Newton-Raphson/Karp-Markstein algorithm.

GEN RgXn_div_i(GEN a, GEN b, long n) as RgXn_div without final garbage collection (suitable for gerepileupto).

GEN RgXn_powers(GEN x, long m, long n) returns $[x^0, \dots, x^m]$ modulo X^n as a t_VEC of RgXns.

GEN RgXn_powu(GEN x, ulong m, long n) returns x^m modulo X^n .

GEN RgXn_powu_i(GEN x, ulong m, long n) as RgXn_powu, not memory clean.

GEN RgXn_sqrt(GEN a, long n) returns $a^{1/2}$ modulo X^n , where a is a t_POL in the variable X and $n \geq 0$. Assume that $a = 1 \bmod X$. Uses Newton algorithm.

GEN RgXn_exp(GEN a, long n) returns $\exp(a)$ modulo X^n , assuming $a = 0 \bmod X$.

GEN RgXn_expint(GEN f, long n) return $\exp(F)$ where F is the primitive of f that vanishes at 0.

GEN RgXn_eval(GEN Q, GEN x, long n) special case of RgX_RgXQ_eval, when the modulus is a monomial: returns $Q(x)$ modulo t^n , where $x \in R[t]$.

GEN RgX_RgXn_eval(GEN f, GEN x, long n) returns $f(x)$ modulo X^n .

GEN RgX_RgXnV_eval(GEN f, GEN V, long n) as RgX_RgXn_eval(f, x, n), assuming V was output by RgXn_powers(x, m, n) for some $m \geq 1$.

GEN RgXn_reverse(GEN f, long n) assuming that $f = ax \bmod x^2$ with a invertible, returns a t_POL g of degree $< n$ such that $(g \circ f)(x) = x \bmod x^n$.

7.6.17 RgXnV.

GEN RgXnV_red_shallow(GEN x, long n) apply RgXn_red_shallow to all the components of the vector x .

7.6.18 RgXQ.

GEN RgXQ_mul(GEN y, GEN x, GEN T) computes $xy \bmod T$

GEN RgXQ_sqr(GEN x, GEN T) computes $x^2 \bmod T$

GEN RgXQ_inv(GEN x, GEN T) return the inverse of $x \bmod T$.

GEN RgXQ_pow(GEN x, GEN n, GEN T) computes $x^n \bmod T$

GEN RgXQ_powu(GEN x, ulong n, GEN T) computes $x^n \bmod T$, n being an ulong.

GEN RgXQ_powers(GEN x, long n, GEN T) returns $[x^0, \dots, x^n]$ as a t_VEC of RgXQs.

GEN RgXQ_matrix_pow(GEN y, long n, long m, GEN P) returns RgXQ_powers(y, m-1, P), as a matrix of dimension $n \geq \deg P$.

GEN RgXQ_norm(GEN x, GEN T) returns the norm of $\text{Mod}(x, T)$.

GEN RgXQ_trace(GEN x, GEN T) returns the trace of $\text{Mod}(x, T)$.

GEN RgXQ_charpoly(GEN x, GEN T, long v) returns the characteristic polynomial of $\text{Mod}(x, T)$, in variable v .

GEN RgXQ_minpoly(GEN x, GEN T, long v) returns the minimal polynomial of $\text{Mod}(x, T)$, in variable v .

GEN RgX_RgXQ_eval(GEN f, GEN x, GEN T) returns $f(x)$ modulo T .

GEN RgX_RgXQV_eval(GEN f, GEN V, GEN T) as RgX_RgXQ_eval(f, x, T), assuming V was output by RgXQ_powers(x, n, T) for some $n \geq 1$.

int RgXQ_ratlift(GEN x, GEN T, long amax, long bmax, GEN *P, GEN *Q) Assuming that $\text{amax} + \text{bmax} < \deg T$, attempts to recognize x as a rational function a/b , i.e. to find $\mathbf{t_POLs}$ P and Q such that

- $P \equiv Qx$ modulo T ,
- $\deg P \leq \text{amax}, \deg Q \leq \text{bmax}$,
- $\gcd(T, P) = \gcd(P, Q)$.

If unsuccessful, the routine returns 0 and leaves P, Q unchanged; otherwise it returns 1 and sets P and Q .

GEN RgXQ_reverse(GEN f, GEN T) returns a $\mathbf{t_POL}$ g of degree $< n = \deg T$ such that $T(x)$ divides $(g \circ f)(x) - x$, by solving a linear system. Low-level function underlying `modreverse`: it returns a lift of $[\text{modreverse}(f, T)]$; faster than the high-level function since it needs not compute the characteristic polynomial of $f \bmod T$ (often already known in applications). In the trivial case where $n \leq 1$, returns a scalar, not a constant $\mathbf{t_POL}$.

7.6.19 RgXQV, RgXQC.

GEN RgXQC_red(GEN z, GEN T) z a vector whose coefficients are RgXs (arbitrary GENs in fact), reduce them to RgXQs (applying `grem` coefficientwise) in a $\mathbf{t_COL}$.

GEN RgXQV_red(GEN z, GEN T) z a vector whose coefficients are RgXs (arbitrary GENs in fact), reduce them to RgXQs (applying `grem` coefficientwise) in a $\mathbf{t_VEC}$.

GEN RgXQV_RgXQ_mul(GEN z, GEN x, GEN T) z multiplies the RgXQV z by the scalar (RgXQ) x .

GEN RgXQV_factorback(GEN L, GEN e, GEN T) returns $\prod_i L_i^{e_i} \bmod T$ where L is a vector of RgXQs and e a vector of $\mathbf{t_INTs}$.

7.6.20 RgXQM.

GEN RgXQM_red(GEN z, GEN T) z a matrix whose coefficients are RgXs (arbitrary GENs in fact), reduce them to RgXQs (applying `grem` coefficientwise).

GEN RgXQM_mul(GEN x, GEN y, GEN T)

7.6.21 RgXQX.

GEN RgXQX_red(GEN z, GEN T) z a `t_POL` whose coefficients are RgXs (arbitrary GENs in fact), reduce them to RgXQs (applying `grem` coefficientwise).

GEN RgXQX_mul(GEN x, GEN y, GEN T)

GEN RgXQX_RgXQ_mul(GEN x, GEN y, GEN T) multiplies the RgXQX y by the scalar (RgXQ) x.

GEN RgXQX_sqr(GEN x, GEN T)

GEN RgXQX_powers(GEN x, long n, GEN T)

GEN RgXQX_divrem(GEN x, GEN y, GEN T, GEN *pr)

GEN RgXQX_div(GEN x, GEN y, GEN T)

GEN RgXQX_rem(GEN x, GEN y, GEN T)

GEN RgXQX_translate(GEN P, GEN c, GEN T) assume the main variable X of P has higher priority than the main variable Y of T and c . Return a lift of $P(X + \text{Mod}(c(Y), T(Y)))$.

GEN Kronecker_to_mod(GEN z, GEN T) $z \in R[X]$ represents an element $P(X, Y)$ in $R[X, Y] \bmod T(Y)$ in Kronecker form, i.e. $z = P(X, X^{2*n-1})$

Let R be some commutative ring, $n = \deg T$ and let $P(X, Y) \in R[X, Y]$ lift a polynomial in $K[Y]$, where $K := R[X]/(T)$ and $\deg_X P < 2n - 1$ — such as would result from multiplying minimal degree lifts of two polynomials in $K[Y]$. Let $z = P(t, t^{2*n-1})$ be a Kronecker form of P , this function returns the image of $P(X, t)$ in $K[t]$, with `t_POLMOD` coefficients. Not stack-clean. Note that t need not be the same variable as Y !

Chapter 8:

Black box algebraic structures

The generic routines like `gmul` or `gadd` allow handling objects belonging to a fixed list of basic types, with some natural polymorphism (you can mix rational numbers and polynomials, etc.), at the expense of efficiency and sometimes of clarity when the recursive structure becomes complicated, e.g. a few levels of `t_POLMOD`s attached to different polynomials and variable numbers for quotient structures. This is the only possibility in GP.

On the other hand, the Level 2 Kernel allows dedicated routines to handle efficiently objects of a very specific type, e.g. polynomials with coefficients in the same finite field. This is more efficient, but involves a lot of code duplication since polymorphism is no longer possible.

A third and final option, still restricted to library programming, is to define an arbitrary algebraic structure (currently groups, fields, rings, algebras and \mathbf{Z}_p -modules) by providing suitable methods, then using generic algorithms. For instance naive Gaussian pivoting applies over all base fields and need only be implemented once. The difference with the first solution is that we no longer depend on the way functions like `gmul` or `gadd` will guess what the user is trying to do. We can then implement independently various groups / fields / algebras in a clean way.

8.1 Black box groups.

A black box group is defined by a `bb_group` struct, describing methods available to handle group elements:

```
struct bb_group
{
    GEN (*mul)(void*, GEN, GEN);
    GEN (*pow)(void*, GEN, GEN);
    GEN (*rand)(void*);
    ulong (*hash)(GEN);
    int (*equal)(GEN, GEN);
    int (*equal1)(GEN);
    GEN (*easylog)(void *E, GEN, GEN, GEN);
};
```

`mul(E,x,y)` returns the product xy .

`pow(E,x,n)` returns x^n (n integer, possibly negative or zero).

`rand(E)` returns a random element in the group.

`hash(x)` returns a hash value for x (`hash_GEN` is suitable for this field).

`equal(x,y)` returns one if $x = y$ and zero otherwise.

`equal1(x)` returns one if x is the neutral element in the group, and zero otherwise.

`easylog(E,a,g,o)` (optional) returns either NULL or the discrete logarithm n such that $g^n = a$, the element g being of order o . This provides a short-cut in situation where a better algorithm than the generic one is known.

A group is thus described by a `struct bb_group` as above and auxiliary data typecast to `void*`. The following functions operate on black box groups:

`GEN gen_Shanks_log(GEN x, GEN g, GEN N, void *E, const struct bb_group *grp)`
 Generic baby-step/giant-step algorithm (Shanks's method). Assuming that g has order N , compute an integer k such that $g^k = x$. Return `cgetg(1, t_VEC)` if there are no solutions. This requires $O(\sqrt{N})$ group operations and uses an auxiliary table containing $O(\sqrt{N})$ group elements.

The above is useful for a one-shot computation. If many discrete logs are desired: `GEN gen_Shanks_init(GEN g, long n, void *E, const struct bb_group *grp)` return an auxiliary data structure T required to compute a discrete log in base g . Compute and store all powers g^i , $i < n$.

`GEN gen_Shanks(GEN T, GEN x, ulong N, void *E, const struct bb_group *grp)` Let T be computed by `gen_Shanks_init(g,n,...)`. Return $k < nN$ such that $g^k = x$ or NULL if no such index exist. It uses $O(N)$ operation in the group and fast table lookups (in time $O(\log n)$). The interface is such that the function may be used when the order of the base g is unknown, and hence compute it given only an upper bound B for it: e.g. choose n, N such that $nN \geq B$ and compute the discrete log l of g^{-1} in base g , then use `gen_order` with multiple $N = l + 1$.

`GEN gen_Pollard_log(GEN x, GEN g, GEN N, void *E, const struct bb_group *grp)`
 Generic Pollard rho algorithm. Assuming that g has order N , compute an integer k such that $g^k = x$. This requires $O(\sqrt{N})$ group operations in average and $O(1)$ storage. Will enter an infinite loop if there are no solutions.

GEN `gen_plog`(GEN `x`, GEN `g`, GEN `N`, void `*E`, const struct `bb_group`) Assuming that g has prime order N , compute an integer k such that $g^k = x$, using either `gen_Shanks_log` or `gen_Pollard_log`. Return `cgetg(1, t_VEC)` if there are no solutions.

GEN `gen_Shanks_sqrtm`(GEN `a`, GEN `n`, GEN `N`, GEN `*zetan`, void `*E`, const struct `bb_group` `*grp`) returns one solution of $x^n = a$ in a black box cyclic group of order N . Return NULL if no solution exists. If `zetan` is not NULL it is set to an element of exact order n . This function uses `gen_plog` for all prime divisors of $\gcd(n, N)$.

GEN `gen_PH_log`(GEN `a`, GEN `g`, GEN `N`, void `*E`, const struct `bb_group` `*grp`) returns an integer k such that $g^k = x$, assuming that the order of g divides N , using Pohlig-Hellman algorithm. Return `cgetg(1, t_VEC)` if there are no solutions. This calls `gen_plog` repeatedly for all prime divisors p of N .

In the following functions the integer parameter `ord` can be given in all the formats recognized for the argument of arithmetic functions, i.e. either as a positive `t_INT` N , or as its factorization matrix faN , or (preferred) as a pair $[N, faN]$.

GEN `gen_order`(GEN `x`, GEN `ord`, void `*E`, const struct `bb_group` `*grp`) computes the order of x ; `ord` is a multiple of the order, for instance the group order.

GEN `gen_factored_order`(GEN `x`, GEN `ord`, void `*E`, const struct `bb_group` `*grp`) returns a pair $[o, F]$, where o is the order of x and F is the factorization of o ; `ord` is as in `gen_order`.

GEN `gen_gener`(GEN `ord`, void `*E`, const struct `bb_group` `*grp`) returns a random generator of the group, assuming it is of order exactly `ord`.

GEN `get_arith_Z`(GEN `ord`) given `ord` as above in one of the formats recognized for arithmetic functions, i.e. a positive `t_INT` N , its factorization faN , or the pair $[N, faN]$, return N .

GEN `get_arith_ZZM`(GEN `ord`) given `ord` as above, return the pair $[N, faN]$. This may require factoring N .

GEN `gen_select_order`(GEN `v`, void `*E`, const struct `bb_group` `*grp`) Let v be a vector of possible orders for the group; try to find the true order by checking orders of random points. This will not terminate if there is an ambiguity.

8.1.1 Black box groups with pairing.

These functions handle groups of rank at most 2 equipped with a family of bilinear pairings which behave like the Weil pairing on elliptic curves over finite field. In the descriptions below, the function `pairorder`(`E`, `P`, `Q`, `m`, `F`) must return the order of the m -pairing of P and Q , both of order dividing m , where F is the factorization matrix of a multiple of m .

GEN `gen_ellgroup`(GEN `o`, GEN `d`, GEN `*pt_m`, void `*E`, const struct `bb_group` `*grp`, GEN `pairorder`(void `*E`, GEN `P`, GEN `Q`, GEN `m`, GEN `F`)) returns the elementary divisors $[d_1, d_2]$ of the group, assuming it is of order exactly $o > 1$, and that d_2 divides d . If $d_2 = 1$ then $[o]$ is returned, otherwise `m=*pt_m` is set to the order of the pairing required to verify a generating set which is to be used with `gen_ellgens`. For the parameter o , all formats recognized by arithmetic functions are allowed, preferably a factorization matrix or a pair $[n, factor(n)]$.

GEN `gen_ellgens`(GEN `d1`, GEN `d2`, GEN `m`, void `*E`, const struct `bb_group` `*grp`, GEN `pairorder`(void `*E`, GEN `P`, GEN `Q`, GEN `m`, GEN `F`)) the parameters d_1 , d_2 , m being as returned by `gen_ellgroup`, returns a pair of generators $[P, Q]$ such that P is of order d_1 and the m -pairing of P and Q is of order m . (Note: Q needs not be of order d_2). For the parameter d_1 , all

formats recognized by arithmetic functions are allowed, preferably a factorization matrix or a pair $[n, \text{factor}(n)]$.

8.1.2 Functions returning black box groups.

`const struct bb_group * get_Flxq_star(void **E, GEN T, ulong p)`

`const struct bb_group * get_FpXQ_star(void **E, GEN T, GEN p)` returns a pointer to the black box group $(\mathbf{F}_p[x]/(T))^*$.

`const struct bb_group * get_FpE_group(void **pE, GEN a4, GEN a6, GEN p)` returns a pointer to a black box group and set `*pE` to the necessary data for computing in the group $E(\mathbf{F}_p)$ where E is the elliptic curve $E : y^2 = x^3 + a_4x + a_6$, with a_4 and a_6 in \mathbf{F}_p .

`const struct bb_group * get_FpXQE_group(void **pE, GEN a4, GEN a6, GEN T, GEN p)` returns a pointer to a black box group and set `*pE` to the necessary data for computing in the group $E(\mathbf{F}_p[X]/(T))$ where E is the elliptic curve $E : y^2 = x^3 + a_4x + a_6$, with a_4 and a_6 in $\mathbf{F}_p[X]/(T)$.

`const struct bb_group * get_FlxqE_group(void **pE, GEN a4, GEN a6, GEN T, ulong p)` idem for small p .

`const struct bb_group * get_F2xqE_group(void **pE, GEN a2, GEN a6, GEN T)` idem for $p = 2$.

8.2 Black box fields.

A black box field is defined by a `bb_field` struct, describing methods available to handle field elements:

```
struct bb_field
{
    GEN (*red)(void *E ,GEN);
    GEN (*add)(void *E ,GEN, GEN);
    GEN (*mul)(void *E ,GEN, GEN);
    GEN (*neg)(void *E ,GEN);
    GEN (*inv)(void *E ,GEN);
    int (*equal0)(GEN);
    GEN (*s)(void *E, long);
};
```

In contrast of black box group, elements can have non canonical forms, and only `red` is required to return a canonical form. For instance a black box implementation of finite fields, all methods except `red` may return arbitrary representatives in $\mathbf{Z}[X]$ of the correct congruence class modulo $(p, T(X))$.

`red(E,x)` returns the canonical form of x .

`add(E,x,y)` returns the sum $x + y$.

`mul(E,x,y)` returns the product xy .

`neg(E,x)` returns $-x$.

`inv(E,x)` returns the inverse of x .

`equal0(x)` x being in canonical form, returns one if $x = 0$ and zero otherwise.

`s(n)` n being a small signed integer, returns n times the unit element.

A field is thus described by a `struct bb_field` as above and auxiliary data typecast to `void*`. The following functions operate on black box fields:

```
GEN gen_Gauss(GEN a, GEN b, void *E, const struct bb_field *ff)
GEN gen_Gauss_pivot(GEN x, long *rr, void *E, const struct bb_field *ff)
GEN gen_det(GEN a, void *E, const struct bb_field *ff)
GEN gen_ker(GEN x, long deplin, void *E, const struct bb_field *ff)
GEN gen_matcolinvimage(GEN a, GEN b, void *E, const struct bb_field *ff)
GEN gen_matcolmul(GEN a, GEN b, void *E, const struct bb_field *ff)
GEN gen_matid(long n, void *E, const struct bb_field *ff)
GEN gen_matinvimage(GEN a, GEN b, void *E, const struct bb_field *ff)
GEN gen_matmul(GEN a, GEN b, void *E, const struct bb_field *ff)
```

8.2.1 Functions returning black box fields.

```
const struct bb_field * get_Fp_field(void **pE, GEN p)
const struct bb_field * get_Fq_field(void **pE, GEN T, GEN p)
const struct bb_field * get_Flxq_field(void **pE, GEN T, ulong p)
const struct bb_field * get_F2xq_field(void **pE, GEN T)
const struct bb_field * get_nf_field(void **pE, GEN nf)
```

8.3 Black box algebra.

A black box algebra is defined by a `bb_algebra` struct, describing methods available to handle algebra elements:

```
struct bb_algebra
{
    GEN (*red)(void *E, GEN x);
    GEN (*add)(void *E, GEN x, GEN y);
    GEN (*sub)(void *E, GEN x, GEN y);
    GEN (*mul)(void *E, GEN x, GEN y);
    GEN (*sqr)(void *E, GEN x);
    GEN (*one)(void *E);
    GEN (*zero)(void *E);
};
```

In contrast with black box groups, elements can have non canonical forms, but only `add` is allowed to return a non canonical form.

`red(E,x)` returns the canonical form of x .

`add(E,x,y)` returns the sum $x + y$.

`sub(E,x,y)` returns the difference $x - y$.

`mul(E,x,y)` returns the product xy .

`sqr(E,x)` returns the square x^2 .

`one(E)` returns the unit element.

`zero(E)` returns the zero element.

An algebra is thus described by a `struct bb_algebra` as above and auxiliary data typecast to `void*`. The following functions operate on black box algebra:

`GEN gen_bkeval(GEN P, long d, GEN x, int use_sqr, void *E, const struct bb_algebra *ff, GEN cmul(void *E, GEN P, long a, GEN x))` x being an element of the black box algebra, and P some black box polynomial of degree d over the base field, returns $P(x)$. The function `cmul(E,P,a,y)` must return the coefficient of degree a of P multiplied by y . `cmul` is allowed to return a non canonical form; it is also allowed to return `NULL` instead of an exact 0.

The flag `use_sqr` has the same meaning as for `gen_powers`. This implements an algorithm of Brent and Kung (1978).

`GEN gen_bkeval_powers(GEN P, long d, GEN V, void *E, const struct bb_algebra *ff, GEN cmul(void *E, GEN P, long a, GEN x))` as `gen_RgX_bkeval` assuming V was output by `gen_powers(x,l,E,ff)` for some $l \geq 1$. For optimal performance, l should be computed by `brent_kung_optpow`.

`long brent_kung_optpow(long d, long n, long m)` returns the optimal parameter l for the evaluation of n/m polynomials of degree d . Fractional values can be used if the evaluations are done with different accuracies, and thus have different weights.

8.3.1 Functions returning black box algebras.

`const struct bb_algebra * get_FpX_algebra(void **E, GEN p, long v)` return the algebra of polynomials over \mathbf{F}_p in variable v .

`const struct bb_algebra * get_FpXQ_algebra(void **E, GEN T, GEN p)` return the algebra $\mathbf{F}_p[X]/(T(X))$.

`const struct bb_algebra * get_FpXQX_algebra(void **E, GEN T, GEN p, long v)` return the algebra of polynomials over $\mathbf{F}_p[X]/(T(X))$ in variable v .

`const struct bb_algebra * get_FlxqXQ_algebra(void **E, GEN S, GEN T, ulong p)` return the algebra $\mathbf{F}_p[X,Y]/(S(X,Y),T(X))$ (for `ulong p`).

`const struct bb_algebra * get_FpXQXQ_algebra(void **E, GEN S, GEN T, GEN p)` return the algebra $\mathbf{F}_p[X,Y]/(S(X,Y),T(X))$.

`const struct bb_algebra * get_Rg_algebra(void)` return the generic algebra.

8.4 Black box ring.

A black box ring is defined by a `bb_ring` struct, describing methods available to handle ring elements:

```
struct bb_ring
{
    GEN (*add)(void *E, GEN x, GEN y);
    GEN (*mul)(void *E, GEN x, GEN y);
    GEN (*sqr)(void *E, GEN x);
};
```

`add(E,x,y)` returns the sum $x + y$.

`mul(E,x,y)` returns the product xy .

`sqr(E,x)` returns the square x^2 .

`GEN gen_fromdigits(GEN v, GEN B, void *E, struct bb_ring *r)` where B is a ring element and $v = [c_0, \dots, c_{n-1}]$ a vector of ring elements, return $\sum_{i=0}^n c_i B^i$ using binary splitting.

`GEN gen_digits(GEN x, GEN B, long n, void *E, struct bb_ring *r, GEN (*div)(void *E, GEN x, GEN y, GEN *r))`

(Require the ring to be Euclidean)

`div(E,x,y,&r)` performs the Euclidean division of x by y in the ring R , returning the quotient q and setting r to the residue so that $x = qy + r$ holds. The residue must belong to a fixed set of representatives of $R/(y)$.

The argument x being a ring element, `gen_digits` returns a vector of ring elements $[c_0, \dots, c_{n-1}]$ such that $x = \sum_{i=0}^n c_i B^i$. Furthermore for all $i \neq n - 1$, the elements c_i belonging to the fixed set of representatives of $R/(B)$.

8.5 Black box free \mathbf{Z}_p -modules.

(Very experimental)

`GEN gen_ZpX_Dixon(GEN F, GEN V, GEN q, GEN p, long N, void *E, GEN lin(void *E, GEN F, GEN z, GEN q), GEN invl(void *E, GEN z))`

Let F be a `ZpXT` representing the coefficients of some abstract linear mapping f over $\mathbf{Z}_p[X]$ seen as a free \mathbf{Z}_p -module, let V be an element of $\mathbf{Z}_p[X]$ and let $q = p^N$. Return $y \in \mathbf{Z}_p[X]$ such that $f(y) = V \pmod{p^N}$ assuming the following holds for $n \leq N$:

- $\text{lin}(E, \text{FpX_red}(F, p^n), z, p^n) \equiv f(z) \pmod{p^n}$
- $f(\text{invl}(E, z)) \equiv z \pmod{p}$

The rationale for the argument F being that it allows `gen_ZpX_Dixon` to reduce it to the required p -adic precision.

`GEN gen_ZpX_Newton(GEN x, GEN p, long n, void *E, GEN eval(void *E, GEN a, GEN q), GEN invd(void *E, GEN b, GEN v, GEN q, long N))`

Let x be an element of $\mathbf{Z}_p[X]$ seen as a free \mathbf{Z}_p -module, and f some differentiable function over $\mathbf{Z}_p[X]$ such that $f(x) \equiv 0 \pmod{p}$. Return y such that $f(y) \equiv 0 \pmod{p^n}$, assuming the following holds for all $a, b \in \mathbf{Z}_p[X]$ and $M \leq N$:

- $v = \text{eval}(E, a, p^N)$ is a vector of elements of $\mathbf{Z}_p[X]$,
- $w = \text{invd}(E, b, v, p^M, M)$ is an element in $\mathbf{Z}_p[X]$,
- $v[1] \equiv f(a) \pmod{p^N \mathbf{Z}_p[X]}$,
- $df_a(w) \equiv b \pmod{p^M \mathbf{Z}_p[X]}$

and df_a denotes the differential of f at a . Motivation: `eval` allows to evaluate f and `invd` allows to invert its differential. Frequently, data useful to compute the differential appear as a subproduct of computing the function. The vector v allows `eval` to provide these to `invd`. The implementation of `invd` will generally involves the use of the function `gen_ZpX_Dixon`.

`GEN gen_ZpM_Newton(GEN x, GEN p, long n, void *E, GEN eval(void *E, GEN a, GEN q), GEN invd(void *E, GEN b, GEN v, GEN q, long N))` as above, with polynomials replaced by matrices.

Chapter 9:

Operations on general PARI objects

9.1 Assignment.

It is in general easier to use a direct conversion, e.g. `y = stoi(s)`, than to allocate a target of correct type and sufficient size, then assign to it:

```
GEN y = cgeti(3); affsi(s, y);
```

These functions can still be moderately useful in complicated garbage collecting scenarios but you will be better off not using them.

`void gaffsg(long s, GEN x)` assigns the `long s` into the object `x`.

`void gaffect(GEN x, GEN y)` assigns the object `x` into the object `y`. Both `x` and `y` must be scalar types. Type conversions (e.g. from `t_INT` to `t_REAL` or `t_INTMOD`) occur if legitimate.

`int is_universal_constant(GEN x)` returns 1 if `x` is a global PARI constant you should never assign to (such as `gen_1`), and 0 otherwise.

9.2 Conversions.

9.2.1 Scalars.

`double rtodbl(GEN x)` applied to a `t_REAL x`, converts `x` into a `double` if possible.

`GEN dbltor(double x)` converts the `double x` into a `t_REAL`.

`long dblexpo(double x)` returns `expo(dbltor(x))`, but faster and without cluttering the stack.

`ulong dblmantissa(double x)` returns the most significant word in the mantissa of `dbltor(x)`.

`int gisdouble(GEN x)` if `x` is a real number (not necessarily a `t_REAL`), return 1 if `x` can be converted to a `double`, 0 otherwise.

`double gtodouble(GEN x)` if `x` is a real number (not necessarily a `t_REAL`), converts `x` into a `double` if possible.

`long gtos(GEN x)` converts the `t_INT x` to a small integer if possible, otherwise raise an exception. This function is similar to `itos`, slightly slower since it checks the type of `x`.

`ulong gtou(GEN x)` converts the non-negative `t_INT x` to an unsigned small integer if possible, otherwise raise an exception. This function is similar to `itou`, slightly slower since it checks the type of `x`.

`double dbllog2r(GEN x)` assuming that `x` is a nonzero `t_REAL`, returns an approximation to `log2(|x|)`.

`double dblmodulus(GEN x)` return an approximation to `|x|`.

`long gtolong(GEN x)` if x is an integer (not necessarily a `t_INT`), converts x into a `long` if possible.

`GEN fractor(GEN x, long l)` applied to a `t_FRAC` x , converts x into a `t_REAL` of length `prec`.

`GEN quadtofp(GEN x, long l)` applied to a `t_QUAD` x , converts x into a `t_REAL` or `t_COMPLEX` depending on the sign of the discriminant of x , to precision `l BITS_IN_LONG`-bit words.

`GEN upper_to_cx(GEN x, long *prec)` valid for a `t_COMPLEX` or `t_QUAD` belonging to the upper half-plane. If a `t_QUAD`, convert it to `t_COMPLEX` using accuracy `*prec`. If x is inexact, sets `*prec` to the precision of x .

`GEN cxtofp(GEN x, long prec)` converts the `t_COMPLEX` x to a complex whose real and imaginary parts are `t_REAL` of length `prec` (special case of `gtofp`).

`GEN cxcompotor(GEN x, long prec)` converts the `t_INT`, `t_REAL` or `t_FRAC` x to a `t_REAL` of length `prec`. These are all the real types which may occur as components of a `t_COMPLEX`; special case of `gtofp` (introduced so that the latter is not recursive and can thus be inlined).

`GEN cxtoreal(GEN x)` converts the complex (`t_INT`, `t_REAL`, `t_FRAC` or `t_COMPLEX`) x to a real number if its imaginary part is 0. Shallow function.

converts the `t_COMPLEX` x to a complex whose real and imaginary parts are `t_REAL` of length `prec` (special case of `gtofp`).

`GEN gtofp(GEN x, long prec)` converts the complex number x (`t_INT`, `t_REAL`, `t_FRAC`, `t_QUAD` or `t_COMPLEX`) to either a `t_REAL` or `t_COMPLEX` whose components are `t_REAL` of precision `prec`; not necessarily of *length* `prec`: a real 0 may be given as `real_0(...)`. If the result is a `t_COMPLEX` extra care is taken so that its modulus really has accuracy `prec`: there is a problem if the real part of the input is an exact 0; indeed, converting it to `real_0(prec)` would be wrong if the imaginary part is tiny, since the modulus would then become equal to 0, as in $1.E-100 + 0.E-38 = 0.E-38$.

`GEN gtomp(GEN z, long prec)` converts the real number x (`t_INT`, `t_REAL`, `t_FRAC`, real `t_QUAD`) to either a `t_INT` or a `t_REAL` of precision `prec`. Not memory clean if x is a `t_INT`: we return x itself and not a copy.

`GEN gcvttop(GEN x, GEN p, long l)` converts x into a `t_PADIC` of precision l . Works componentwise on recursive objects, e.g. `t_POL` or `t_VEC`. Converting 0 yields $O(p^l)$; converting a nonzero number yield a result well defined modulo $p^{v_p(x)+l}$.

`GEN cvttop(GEN x, GEN p, long l)` as `gcvttop`, assuming that x is a scalar.

`GEN cvtop2(GEN x, GEN y)` y being a p -adic, converts the scalar x to a p -adic of the same accuracy. Shallow function.

`GEN cvstop2(long s, GEN y)` y being a p -adic, converts the scalar s to a p -adic of the same accuracy. Shallow function.

`GEN gprec(GEN x, long l)` returns a copy of x whose precision is changed to l digits. The precision change is done recursively on all components of x . Digits means *decimal*, p -adic and X -adic digits for `t_REAL`, `t_SER`, `t_PADIC` components, respectively.

`GEN gprec_w(GEN x, long prec)` returns a shallow copy of x whose `t_REAL` components have their precision changed to `prec` bits. This is often more useful than `gprec`.

`GEN gprec_wtrunc(GEN x, long prec)` returns a shallow copy of x whose `t_REAL` components have their precision *truncated* to `prec` bits. Contrary to `gprec_w`, this function may never increase the precision of x .

GEN `gprec_wensure(GEN x, long prec)` returns a shallow copy of x whose `t_REAL` components have their precision *increased* to at least $prec$ bits. Contrary to `gprec_w`, this function may never decrease the precision of x .

The following functions are obsolete and kept for backward compatibility only:

GEN `precision0(GEN x, long n)`

GEN `bitprecision0(GEN x, long n)`

9.2.2 Modular objects / lifts.

GEN `gmodulo(GEN x, GEN y)` creates the object **Mod**(x, y) on the PARI stack, where x and y are either both `t_INT`s, and the result is a `t_INTMOD`, or x is a scalar or a `t_POL` and y a `t_POL`, and the result is a `t_POLMOD`.

GEN `gmodulgs(GEN x, long y)` same as **gmodulo** except y is a `long`.

GEN `gmodulsg(long x, GEN y)` same as **gmodulo** except x is a `long`.

GEN `gmodulss(long x, long y)` same as **gmodulo** except both x and y are `long`s.

GEN `lift_shallow(GEN x)` shallow version of `lift`

GEN `liftall_shallow(GEN x)` shallow version of `liftall`

GEN `liftint_shallow(GEN x)` shallow version of `liftint`

GEN `liftpol_shallow(GEN x)` shallow version of `liftpol`

GEN `centerlift0(GEN x, long v)` DEPRECATED, kept for backward compatibility only: use either `lift0(x, v)` or `centerlift(x)`.

9.2.3 Between polynomials and coefficient arrays.

GEN `gtopoly(GEN x, long v)` converts or truncates the object x into a `t_POL` with main variable number v . A common application would be the conversion of coefficient vectors (coefficients are given by decreasing degree). E.g. `[2,3]` goes to $2*v + 3$

GEN `gtopolyrev(GEN x, long v)` converts or truncates the object x into a `t_POL` with main variable number v , but vectors are converted in reverse order compared to `gtopoly` (coefficients are given by increasing degree). E.g. `[2,3]` goes to $3*v + 2$. In other words the vector represents a polynomial in the basis $(1, v, v^2, v^3, \dots)$.

GEN `normalizpol(GEN x)` applied to an unnormalized `t_POL` x (with all coefficients correctly set except that `leading_term(x)` might be zero), normalizes x correctly in place and returns x . For internal use. Normalizing means deleting all leading *exact* zeroes (as per `isexactzero`), except if the polynomial turns out to be 0, in which case we try to find a coefficient c which is a nonrational zero, and return the constant polynomial c . (We do this so that information about the base ring is not lost.)

GEN `normalizpol_lg(GEN x, long l)` applies `normalizpol` to x , pretending that `lg(x)` is l , which must be less than or equal to `lg(x)`. If equal, the function is equivalent to `normalizpol(x)`.

GEN `normalizpol_approx(GEN x, long lx)` as `normalizpol_lg`, with the difference that we just delete all leading zeroes (as per `gequal0`). This rougher normalization is used when we have no other choice, for instance before attempting a Euclidean division by x .

The following routines do *not* copy coefficients on the stack (they only move pointers around), hence are very fast but not suitable for `gerepile` calls. Recall that an `RgV` (resp. an `RgX`, resp. an `RgM`) is a `t_VEC` or `t_COL` (resp. a `t_POL`, resp. a `t_MAT`) with arbitrary components. Similarly, an `RgXV` is a `t_VEC` or `t_COL` with `RgX` components, etc.

`GEN RgV_to_RgX(GEN x, long v)` converts the `RgV` `x` to a (normalized) polynomial in variable `v` (as `gtopolyrev`, without copy).

`GEN RgV_to_RgX_reverse(GEN x, long v)` converts the `RgV` `x` to a (normalized) polynomial in variable `v` (as `gtopoly`, without copy).

`GEN RgX_to_RgC(GEN x, long N)` converts the `t_POL` `x` to a `t_COL` `v` with `N` components. Coefficients of `x` are listed by increasing degree, so that `y[i]` is the coefficient of the term of degree $i - 1$ in `x`.

`GEN Rg_to_RgC(GEN x, long N)` as `RgX_to_RgV`, except that other types than `t_POL` are allowed for `x`, which is then considered as a constant polynomial.

`GEN RgM_to_RgXV(GEN x, long v)` converts the `RgM` `x` to a `t_VEC` of `RgX`, by repeated calls to `RgV_to_RgX`.

`GEN RgM_to_RgXV_reverse(GEN x, long v)` converts the `RgM` `x` to a `t_VEC` of `RgX`, by repeated calls to `RgV_to_RgX_reverse`.

`GEN RgV_to_RgM(GEN v, long N)` converts the vector `v` to a `t_MAT` with `N` rows, by repeated calls to `Rg_to_RgV`.

`GEN RgXV_to_RgM(GEN v, long N)` converts the vector of `RgX` `v` to a `t_MAT` with `N` rows, by repeated calls to `RgX_to_RgV`.

`GEN RgM_to_RgXX(GEN x, long v, long w)` converts the `RgM` `x` into a `t_POL` in variable `v`, whose coefficients are `t_POLs` in variable `w`. This is a shortcut for

`RgV_to_RgX(RgM_to_RgXV(x, w), v);`

There are no consistency checks with respect to variable priorities: the above is an invalid object if `varncmp(v, w) ≥ 0`.

`GEN RgXX_to_RgM(GEN x, long N)` converts the `t_POL` `x` with `RgX` (or constant) coefficients to a matrix with `N` rows.

`long RgXY_degreeex(GEN P)` return the degree of `P` with respect to the secondary variable.

`GEN RgXY_derivx(GEN P)` return the derivative of `P` with respect to the secondary variable.

`GEN RgXY_swap(GEN P, long n, long w)` converts the bivariate polynomial $P(u, v)$ (a `t_POL` with `t_POL` or scalar coefficients) to $P(\text{pol_x}[w], u)$, assuming `n` is an upper bound for $\deg_v(P)$.

`GEN RgXY_swapspec(GEN C, long n, long w, long lP)` as `RgXY_swap` where the coefficients of `P` are given by `gel(C, 0), ..., gel(C, lP-1)`.

`GEN RgX_to_ser(GEN x, long l)` convert the `t_POL` `x` to a *shallow* `t_SER` of length $l \geq 2$. Unless the polynomial is an exact zero, the coefficient of lowest degree T^d of the result is not an exact zero (as per `isexactzero`). The remainder is $O(T^{d+l-2})$.

`GEN RgX_to_ser_inexact(GEN x, long l)` convert the `t_POL` `x` to a *shallow* `t_SER` of length $l \geq 2$. Unless the polynomial is zero, the coefficient of lowest degree T^d of the result is not zero (as per `equal0`). The remainder is $O(T^{d+l-2})$.

GEN `RgV_to_ser`(GEN `x`, long `v`, long `l`) convert the `t_VEC` `x`, to a *shallow* `t_SER` of length $l \geq 2$.

GEN `rfrac_to_ser`(GEN `F`, long `l`) applied to a `t_RFRAC` `F`, creates a `t_SER` of length $l \geq 2$ congruent to `F`. Not memory-clean but suitable for `gerepileupto`.

GEN `rfrac_to_ser_i`(GEN `F`, long `l`) internal variant of `rfrac_to_ser`, neither memory-clean nor suitable for `gerepileupto`.

GEN `rfracrecip_to_ser_absolute`(GEN `F`, long `d`) applied to a `t_RFRAC` `F`, creates the `t_SER` $F(1/t) + O(t^d)$. Note that we use absolute and not relative precision here.

GEN `gtoser`(GEN `s`, long `v`, long `d`). This function is deprecated, kept for backward compatibility: it follows the semantic of `Ser(s,v)`, with `d = seriesprecision` implied and is hard to use as a general conversion function. Use `gtoser_prec` instead.

It converts the object `s` into a `t_SER` with main variable number `v` and $d > 0$ significant terms, but the argument `d` is sometimes ignored. More precisely

- if `s` is a scalar (with respect to variable `v`), we return a constant power series with d significant terms;
- if `s` is a `t_POL` in variable `v`, it is truncated to d terms if needed;
- if `s` is a vector, the coefficients of the vector are understood to be the coefficients of the power series starting from the constant term (as in `Polrev`), and the precision d is *ignored*;
- if `s` is already a power series in `v`, we return a copy, and the precision d is again *ignored*.

GEN `gtoser_prec`(GEN `s`, long `v`, long `d`) this function is a variant of `gtoser` following the semantic of `Ser(s,v,d)`: the precision d is always taken into account.

GEN `gtocol`(GEN `x`) converts the object `x` into a `t_COL`

GEN `gtomat`(GEN `x`) converts the object `x` into a `t_MAT`.

GEN `gtovec`(GEN `x`) converts the object `x` into a `t_VEC`.

GEN `gtovecsmall`(GEN `x`) converts the object `x` into a `t_VECSMALL`.

GEN `normalizeser`(GEN `x`) applied to an unnormalized `t_SER` `x` (i.e. type `t_SER` with all coefficients correctly set except that `x[2]` might be zero), normalizes `x` correctly in place. Returns `x`. For internal use.

GEN `serchop0`(GEN `s`) given a `t_SER` of the form $x^v s(x)$, with $s(0) \neq 0$, return $x^v (s - s(0))$. Shallow function.

GEN `serchop_i`(GEN `x`, long `n`) returns a shallow copy of `t_SER` `x` with all terms of degree strictly less than n removed. Shallow version of `serchop`.

9.3 Constructors.

9.3.1 Clean constructors.

GEN `zeropadic`(GEN `p`, long `n`) creates a 0 `t_PADIC` equal to $O(p^n)$.

GEN `zeroser`(long `v`, long `n`) creates a 0 `t_SER` in variable `v` equal to $O(X^n)$.

GEN `scalarser`(GEN `x`, long `v`, long `prec`) creates a constant `t_SER` in variable `v` and precision `prec`, whose constant coefficient is (a copy of) `x`, in other words $x + O(v^{\text{prec}})$. Assumes that `prec` ≥ 0 .

GEN `pol_0`(long `v`) Returns the constant polynomial 0 in variable `v`.

GEN `pol_1`(long `v`) Returns the constant polynomial 1 in variable `v`.

GEN `pol_x`(long `v`) Returns the monomial of degree 1 in variable `v`.

GEN `pol_xn`(long `n`, long `v`) Returns the monomial of degree `n` in variable `v`; assume that `n` ≥ 0 .

GEN `pol_xnall`(long `n`, long `v`) Returns the Laurent monomial of degree `n` in variable `v`; `n` < 0 is allowed.

GEN `pol_x_powers`(long `N`, long `v`) returns the powers of `pol_x(v)`, of degree 0 to `N` $- 1$, in a vector with `N` components.

GEN `scalarpol`(GEN `x`, long `v`) creates a constant `t_POL` in variable `v`, whose constant coefficient is (a copy of) `x`.

GEN `deg1pol`(GEN `a`, GEN `b`, long `v`) creates the degree 1 `t_POL` $a\text{pol_x}(v) + b$

GEN `zeropol`(long `v`) is identical `pol_0`.

GEN `zerocol`(long `n`) creates a `t_COL` with `n` components set to `gen_0`.

GEN `zerovec`(long `n`) creates a `t_VEC` with `n` components set to `gen_0`.

GEN `zerovec_block`(long `n`) as `zerovec` but return a clone.

GEN `col_ei`(long `n`, long `i`) creates a `t_COL` with `n` components set to `gen_0`, but for the `i`-th one which is set to `gen_1` (`i`-th vector in the canonical basis).

GEN `vec_ei`(long `n`, long `i`) creates a `t_VEC` with `n` components set to `gen_0`, but for the `i`-th one which is set to `gen_1` (`i`-th vector in the canonical basis).

GEN `trivial_fact`(void) returns the trivial (empty) factorization `Mat([]~, []~)`

GEN `prime_fact`(GEN `x`) returns the factorization `Mat([x]~, [1]~)`

GEN `Rg_col_ei`(GEN `x`, long `n`, long `i`) creates a `t_COL` with `n` components set to `gen_0`, but for the `i`-th one which is set to `x`.

GEN `vecsmall_ei`(long `n`, long `i`) creates a `t_VECSMALL` with `n` components set to 0, but for the `i`-th one which is set to 1 (`i`-th vector in the canonical basis).

GEN `scalarcol`(GEN `x`, long `n`) creates a `t_COL` with `n` components set to `gen_0`, but the first one which is set to a copy of `x`. (The name comes from `RgV_isscalar`.)

GEN `mkintmodu`(ulong `x`, ulong `y`) creates the `t_INTMOD` `Mod(x, y)`. The inputs must satisfy $x < y$.

GEN `zeromat(long m, long n)` creates a `t_MAT` with $m \times n$ components set to `gen_0`. Note that the result allocates a *single* column, so modifying an entry in one column modifies it in all columns. To fully allocate a matrix initialized with zero entries, use `zeromacopy`.

GEN `zeromacopy(long m, long n)` creates a `t_MAT` with $m \times n$ components set to `gen_0`.

GEN `matid(long n)` identity matrix in dimension n (with components `gen_1` and `gen_0`).

GEN `scalarmat(GEN x, long n)` scalar matrix, x times the identity.

GEN `scalarmat_s(long x, long n)` scalar matrix, `stoi(x)` times the identity.

GEN `vecrange(GEN a, GEN b)` returns the `t_VEC` $[a..b]$.

GEN `vecrangess(long a, long b)` returns the `t_VEC` $[a..b]$.

See also next section for analogs of the following functions:

GEN `mkfracss(long x, long y)` creates the `t_FRAC` x/y . Assumes that $y > 1$ and $(x, y) = 1$.

GEN `sstoQ(long x, long y)` returns the `t_INT` or `t_FRAC` x/y ; no assumptions.

GEN `uutoQ(ulong x, ulong y)` returns the `t_INT` or `t_FRAC` x/y ; no assumptions.

void `Qtoss(GEN q, long *n, long *d)` given a `t_INT` or `t_FRAC` q , set n and d such that $q = n/d$ with $d \geq 1$ and $(n, d) = 1$. Overflow error if numerator or denominator do not fit into a long integer.

GEN `mkfraccopy(GEN x, GEN y)` creates the `t_FRAC` x/y . Assumes that $y > 1$ and $(x, y) = 1$.

GEN `mkrfraccopy(GEN x, GEN y)` creates the `t_RFRAC` x/y . Assumes that y is a `t_POL`, x a compatible type whose variable has lower or same priority, with $(x, y) = 1$.

GEN `mkcolcopy(GEN x)` creates a 1-dimensional `t_COL` containing x .

GEN `mkmatcopy(GEN x)` creates a 1-by-1 `t_MAT` wrapping the `t_COL` x .

GEN `mkveccopy(GEN x)` creates a 1-dimensional `t_VEC` containing x .

GEN `mkvec2copy(GEN x, GEN y)` creates a 2-dimensional `t_VEC` equal to $[x, y]$.

GEN `mkcols(long x)` creates a 1-dimensional `t_COL` containing `stoi(x)`.

GEN `mkcol2s(long x, long y)` creates a 2-dimensional `t_COL` containing $[\text{stoi}(x), \text{stoi}(y)]$.

GEN `mkcol3s(long x, long y, long z)` creates a 3-dimensional `t_COL` containing $[\text{stoi}(x), \text{stoi}(y), \text{stoi}(z)]$.

GEN `mkcol4s(long x, long y, long z, long t)` creates a 4-dimensional `t_COL` containing $[\text{stoi}(x), \text{stoi}(y), \text{stoi}(z), \text{stoi}(t)]$.

GEN `mkvecs(long x)` creates a 1-dimensional `t_VEC` containing `stoi(x)`.

GEN `mkvec2s(long x, long y)` creates a 2-dimensional `t_VEC` containing $[\text{stoi}(x), \text{stoi}(y)]$.

GEN `mkmat22s(long a, long b, long c, long d)` creates the 2 by 2 `t_MAT` with successive rows $[\text{stoi}(a), \text{stoi}(b)]$ and $[\text{stoi}(c), \text{stoi}(d)]$.

GEN `mkvec3s(long x, long y, long z)` creates a 3-dimensional `t_VEC` containing $[\text{stoi}(x), \text{stoi}(y), \text{stoi}(z)]$.

GEN `mkvec4s(long x, long y, long z, long t)` creates a 4-dimensional `t_VEC` containing $[\text{stoi}(x), \text{stoi}(y), \text{stoi}(z), \text{stoi}(t)]$.

GEN `mkvecsmall(long x)` creates a 1-dimensional `t_VECSMALL` containing `x`.

GEN `mkvecsmall2(long x, long y)` creates a 2-dimensional `t_VECSMALL` containing `[x, y]`.

GEN `mkvecsmall3(long x, long y, long z)` creates a 3-dimensional `t_VECSMALL` containing `[x, y, z]`.

GEN `mkvecsmall4(long x, long y, long z, long t)` creates a 4-dimensional `t_VECSMALL` containing `[x, y, z, t]`.

GEN `mkvecsmall5(long x, long y, long z, long t, long u)` creates a 5-dimensional `t_VECSMALL` containing `[x, y, z, t, u]`.

GEN `mkvecsmalln(long n, ...)` returns the `t_VECSMALL` whose n coefficients (`long`) follow.
Warning: since this is a variadic function, C type promotion is not performed on the arguments by the compiler, thus you have to make sure that all the arguments are of type `long`, in particular integer constants need to be written with the L suffix: `mkvecsmalln(2, 1L, 2L)` is correct, but `mkvecsmalln(2, 1, 2)` is not.

9.3.2 Unclean constructors.

Contrary to the policy of general PARI functions, the functions in this subsection do *not* copy their arguments, nor do they produce an object a priori suitable for `gerepileupto`. In particular, they are faster than their clean equivalent (which may not exist). *If* you restrict their arguments to universal objects (e.g `gen_0`), then the above warning does not apply.

GEN `mkcomplex(GEN x, GEN y)` creates the `t_COMPLEX` $x + iy$.

GEN `mulcxI(GEN x)` creates the `t_COMPLEX` ix . The result in general contains data pointing back to the original x . Use `gcop` if this is a problem. But in most cases, the result is to be used immediately, before x is subject to garbage collection.

GEN `mulcxmI(GEN x)`, as `mulcxI`, but returns $-ix$.

GEN `mulcxpowIs(GEN x, long k)`, as `mulcxI`, but returns $x \cdot i^k$.

GEN `mkquad(GEN n, GEN x, GEN y)` creates the `t_QUAD` $x + yw$, where w is a root of n , which is of the form `quadpoly(D)`.

GEN `quadpoly_i(GEN D)` creates the canonical quadratic polynomial of discriminant D . Assume that the `t_INT` D is congruent to 0, 1 mod 4 and not a square.

GEN `mkfrac(GEN x, GEN y)` creates the `t_FRAC` x/y . Assumes that $y > 1$ and $(x, y) = 1$.

GEN `mkrfrac(GEN x, GEN y)` creates the `t_RFRAC` x/y . Assumes that y is a `t_POL`, x a compatible type whose variable has lower or same priority, with $(x, y) = 1$.

GEN `mkcol(GEN x)` creates a 1-dimensional `t_COL` containing `x`.

GEN `mkcol2(GEN x, GEN y)` creates a 2-dimensional `t_COL` equal to `[x, y]`.

GEN `mkcol3(GEN x, GEN y, GEN z)` creates a 3-dimensional `t_COL` equal to `[x, y, z]`.

GEN `mkcol4(GEN x, GEN y, GEN z, GEN t)` creates a 4-dimensional `t_COL` equal to `[x, y, z, t]`.

GEN `mkcol5(GEN a1, GEN a2, GEN a3, GEN a4, GEN a5)` creates the 5-dimensional `t_COL` equal to `[a1, a2, a3, a4, a5]`.

GEN `mkcol6(GEN x, GEN y, GEN z, GEN t, GEN u, GEN v)` creates the 6-dimensional column vector `[x, y, z, t, u, v]`.

GEN mkintmod(GEN x, GEN y) creates the $t_INTMOD \text{Mod}(x, y)$. The inputs must be t_INTs satisfying $0 \leq x < y$.

GEN mkpolmod(GEN x, GEN y) creates the $t_POLMOD \text{Mod}(x, y)$. The input must satisfy $\deg x < \deg y$ with respect to the main variable of the $t_POL y$. x may be a scalar.

GEN mkmat(GEN x) creates a 1-column t_MAT with column x (a t_COL).

GEN mkmat2(GEN x, GEN y) creates a 2-column t_MAT with columns x, y (t_COLs of the same length).

GEN mkmat22(GEN a, GEN b, GEN c, GEN d) creates the 2 by 2 t_MAT with successive rows $[a, b]$ and $[c, d]$.

GEN mkmat3(GEN x, GEN y, GEN z) creates a 3-column t_MAT with columns x, y, z (t_COLs of the same length).

GEN mkmat4(GEN x, GEN y, GEN z, GEN t) creates a 4-column t_MAT with columns x, y, z, t (t_COLs of the same length).

GEN mkmat5(GEN x, GEN y, GEN z, GEN t, GEN u) creates a 5-column t_MAT with columns x, y, z, t, u (t_COLs of the same length).

GEN mkvec(GEN x) creates a 1-dimensional t_VEC containing x .

GEN mkvec2(GEN x, GEN y) creates a 2-dimensional t_VEC equal to $[x, y]$.

GEN mkvec3(GEN x, GEN y, GEN z) creates a 3-dimensional t_VEC equal to $[x, y, z]$.

GEN mkvec4(GEN x, GEN y, GEN z, GEN t) creates a 4-dimensional t_VEC equal to $[x, y, z, t]$.

GEN mkvec5(GEN a1, GEN a2, GEN a3, GEN a4, GEN a5) creates the 5-dimensional t_VEC equal to $[a_1, a_2, a_3, a_4, a_5]$.

GEN mkqfb(GEN a, GEN b, GEN c, GEN D) creates t_QFB equal to $Qfb(a, b, c)$, assuming that $D = b^2 - 4ac$.

GEN mkerr(long n) returns a t_ERROR with error code n (enum `err_list`).

It is sometimes useful to return such a container whose entries are not universal objects, but nonetheless suitable for `gerepileupto`. If the entries can be computed at the time the result is returned, the following macros achieve this effect:

GEN retmkvec(GEN x) returns a vector containing the single entry x , where the vector root is created just before the function argument x is evaluated. Expands to

```
{
  GEN res = cgetg(2, t_VEC);
  gel(res, 1) = x; /* or rather, the expansion of  $x$  */
  return res;
}
```

For instance, the `retmkvec(gcopy(x))` returns a clean object, just like `return mkveccopy(x)` would.

GEN retmkvec2(GEN x, GEN y) returns the 2-dimensional t_VEC $[x, y]$.

GEN retmkvec3(GEN x, GEN y, GEN z) returns the 3-dimensional t_VEC $[x, y, z]$.

`GEN retmkvec4(GEN x, GEN y, GEN z, GEN t)` returns the 4-dimensional `t_VEC` `[x,y,z,t]`.
`GEN retmkvec5(GEN x, GEN y, GEN z, GEN t, GEN u)` returns the 5-dimensional row vector `[x,y,z,t,u]`.
`GEN retconst_vec(long n, GEN x)` returns the n -dimensional `t_VEC` whose entries are constant and all equal to x .
`GEN retmkcol(GEN x)` returns the 1-dimensional `t_COL` `[x]`.
`GEN retmkcol2(GEN x, GEN y)` returns the 2-dimensional `t_COL` `[x,y]`.
`GEN retmkcol3(GEN x, GEN y, GEN z)` returns the 3-dimensional `t_COL` `[x,y,z]`.
`GEN retmkcol4(GEN x, GEN y, GEN z, GEN t)` returns the 4-dimensional `t_COL` `[x,y,z,t]`.
`GEN retmkcol5(GEN x, GEN y, GEN z, GEN t, GEN u)` returns the 5-dimensional column vector `[x,y,z,t,u]`.
`GEN retmkcol6(GEN x, GEN y, GEN z, GEN t, GEN u, GEN v)` returns the 6-dimensional column vector `[x,y,z,t,u,v]`.
`GEN retconst_col(long n, GEN x)` returns the n -dimensional `t_COL` whose entries are constant and all equal to x .
`GEN retmkmat(GEN x)` returns the 1-column `t_MAT` with column x .
`GEN retmkmat2(GEN x, GEN y)` returns the 2-column `t_MAT` with columns x, y .
`GEN retmkmat3(GEN x, GEN y, GEN z)` returns the 3-dimensional `t_MAT` with columns x, y, z .
`GEN retmkmat4(GEN x, GEN y, GEN z, GEN t)` returns the 4-dimensional `t_MAT` with columns x, y, z, t .
`GEN retmkmat5(GEN x, GEN y, GEN z, GEN t, GEN u)` returns the 5-dimensional `t_MAT` with columns x, y, z, t, u .
`GEN retmkmat22(GEN a, GEN b, GEN c, GEN d)` return the 2 by 2 `t_MAT` with successive rows `[a, b]` and `[c, d]`.
`GEN retmkcomplex(GEN x, GEN y)` returns the `t_COMPLEX` $x + I*y$.
`GEN retmkfrac(GEN x, GEN y)` returns the `t_FRAC` x / y . Assume x and y are coprime and $y > 1$.
`GEN retmkrffrac(GEN x, GEN y)` returns the `t_RFRAC` x / y . Assume x and y are coprime and more generally that the rational function cannot be simplified.
`GEN retmkintmod(GEN x, GEN y)` returns the `t_INTMOD` $\text{Mod}(x, y)$.
`GEN retmkquad(GEN n, GEN a, GEN b)`.
`GEN retmkpolmod(GEN x, GEN y)` returns the `t_POLMOD` $\text{Mod}(x, y)$.
`GEN mkintn(long n, ...)` returns the nonnegative `t_INT` whose expansion in base 2^{32} is given by the following n 32bit-words (`unsigned int`).

$$\text{mkintn}(3, a_2, a_1, a_0);$$
returns $a_2 2^{64} + a_1 2^{32} + a_0$.
`GEN mkpoln(long n, ...)` Returns the `t_POL` whose n coefficients (`GEN`) follow, in order of decreasing degree.

`mkpoln(3, gen_1, gen_2, gen_0);`

returns the polynomial $X^2 + 2X$ (in variable 0, use `setvarn` if you want other variable numbers). Beware that n is the number of coefficients, hence *one more* than the degree.

GEN `mkvecn(long n, ...)` returns the `t_VEC` whose n coefficients (GEN) follow.

GEN `mkcoln(long n, ...)` returns the `t_COL` whose n coefficients (GEN) follow.

GEN `scalarcoll_shallow(GEN x, long n)` creates a `t_COL` with n components set to `gen_0`, but the first one which is set to a shallow copy of `x`. (The name comes from `RgV_isscalar`.)

GEN `scalarmat_shallow(GEN x, long n)` creates an $n \times n$ scalar matrix whose diagonal is set to shallow copies of the scalar `x`.

GEN `RgX_sylvestermatrix(GEN f, GEN g)` return the Sylvester matrix attached to the two `t_POL` in the same variable f and g .

GEN `diagonal_shallow(GEN x)` returns a diagonal matrix whose diagonal is given by the vector x . Shallow function.

GEN `scalarpol_shallow(GEN a, long v)` returns the degree 0 `t_POL` $\text{apol}_x(v)^0$.

GEN `deg1pol_shallow(GEN a, GEN b, long v)` returns the degree 1 `t_POL` $\text{apol}_x(v) + b$

GEN `deg2pol_shallow(GEN a, GEN b, GEN c, long v)` returns the degree 2 `t_POL` $ax^2 + bx + c$ where $x = \text{pol}_x(v)$.

GEN `zeropadic_shallow(GEN p, long n)` returns a (shallow) 0 `t_PADIC` equal to $O(\mathfrak{p}^n)$.

9.3.3 From roots to polynomials.

GEN `deg1_from_roots(GEN L, long v)` given a vector L of scalars, returns the vector of monic linear polynomials in variable v whose roots are the $L[i]$, i.e. the $x - L[i]$.

GEN `roots_from_deg1(GEN L)` given a vector L of monic linear polynomials, return their roots, i.e. the $-L[i](0)$.

GEN `roots_to_pol(GEN L, long v)` given a vector of scalars L , returns the monic polynomial in variable v whose roots are the $L[i]$. Leaves some garbage on stack, but suitable for `gerepileupto`.

GEN `roots_to_pol_r1(GEN L, long v, long r1)` as `roots_to_pol` assuming the first r_1 roots are “real”, and the following ones are representatives of conjugate pairs of “complex” roots. So if L has $r_1 + r_2$ elements, we obtain a polynomial of degree $r_1 + 2r_2$. In most applications, the roots are indeed real and complex, but the implementation assumes only that each “complex” root z introduces a quadratic factor $X^2 - \text{trace}(z)X + \text{norm}(z)$. Leaves some garbage on stack, but suitable for `gerepileupto`.

9.4 Integer parts.

GEN `gfloor`(GEN `x`) creates the floor of `x`, i.e. the (true) integral part.

GEN `gfrac`(GEN `x`) creates the fractional part of `x`, i.e. `x` minus the floor of `x`.

GEN `gceil`(GEN `x`) creates the ceiling of `x`.

GEN `ground`(GEN `x`) rounds towards $+\infty$ the components of `x` to the nearest integers.

GEN `grndtoi`(GEN `x`, long `*e`) same as `ground`, but in addition sets `*e` to the binary exponent of $x - \text{ground}(x)$. If this is positive, then significant bits are lost in the rounded result. This kind of situation raises an error message in `ground` but not in `grndtoi`. The parameter `e` can be set to NULL if an error estimate is not needed, for a minor speed up.

GEN `gtrunc`(GEN `x`) truncates `x`. This is the false integer part if `x` is a real number (i.e. the unique integer closest to `x` among those between 0 and `x`). If `x` is a `t_SER`, it is truncated to a `t_POL`; if `x` is a `t_RFRAC`, this takes the polynomial part.

GEN `gtrunc2n`(GEN `x`, long `n`) creates the floor of $2^n x$, this is only implemented for `t_INT`, `t_REAL`, `t_FRAC` and `t_COMPLEX` of those.

GEN `gcvttoi`(GEN `x`, long `*e`) analogous to `grndtoi` for `t_REAL` inputs except that rounding is replaced by truncation. Also applies componentwise for vector or matrix inputs; otherwise, sets `*e` to `-HIGHEXPOBIT` (infinite real accuracy) and return `gtrunc(x)`.

9.5 Valuation and shift.

GEN `gshift`[`z`](GEN `x`, long `n`[, GEN `z`]) yields the result of shifting (the components of) `x` left by `n` (if `n` is nonnegative) or right by $-\text{n}$ (if `n` is negative). Applies only to `t_INT` and vectors/matrices of such. For other types, it is simply multiplication by 2^n .

GEN `gmul2n`[`z`](GEN `x`, long `n`[, GEN `z`]) yields the product of `x` and 2^n . This is different from `gshift` when `n` is negative and `x` is a `t_INT`: `gshift` truncates, while `gmul2n` creates a fraction if necessary.

long `gvaluation`(GEN `x`, GEN `p`) returns the greatest exponent e such that p^e divides `x`, when this makes sense.

long `gval`(GEN `x`, long `v`) returns the highest power of the variable number `v` dividing the `t_POL` `x`.

9.6 Comparison operators.

9.6.1 Generic.

`long gcmp(GEN x, GEN y)` comparison of x with y : returns 1 ($x > y$), 0 ($x = y$) or -1 ($x < y$). Two `t_STR` are compared using the standard lexicographic ordering; a `t_STR` cannot be compared to any non-string type. If neither x nor y is a `t_STR`, their allowed types are `t_INT`, `t_REAL`, `t_FRAC`, `t_QUAD` with positive discriminant (use the canonical embedding $w \rightarrow \sqrt{D}/2$ or $w \rightarrow (1 + \sqrt{D})/2$) or `t_INFINITY`. Use `cmp_universal` to compare arbitrary GENs.

`long lexcmp(GEN x, GEN y)` comparison of x with y for the lexicographic ordering; when comparing objects of different lengths whose components are all equal up to the smallest of their length, consider that the longest is largest. Consider scalars as 1-component vectors. Return `gcmp(x, y)` if both arguments are scalars.

`int gequalX(GEN x)` return 1 (true) if x is a variable (monomial of degree 1 with `t_INT` coefficients equal to 1 and 0), and 0 otherwise

`long gequal(GEN x, GEN y)` returns 1 (true) if x is equal to y , 0 otherwise. A priori, this makes sense only if x and y have the same type, in which case they are recursively compared componentwise. When the types are different, a `true` result means that $x - y$ was successfully computed and that `gequal0` found it equal to 0. In particular

`gequal(cgetg(1, t_VEC), gen_0)`

is true, and the relation is not transitive. E.g. an empty `t_COL` and an empty `t_VEC` are not equal but are both equal to `gen_0`.

`long gidentical(GEN x, GEN y)` returns 1 (true) if x is identical to y , 0 otherwise. In particular, the types and length of x and y must be equal. This test is much stricter than `gequal`, in particular, `t_REAL` with different accuracies are tested different. This relation is transitive.

`GEN gmax(GEN x, GEN y)` returns a copy of the maximum of x and y , compared using `gcmp`.

`GEN gmin(GEN x, GEN y)` returns a copy of the minimum of x and y , compared using `gcmp`.

`GEN gmax_shallow(GEN x, GEN y)` shallow version of `gmax`.

`GEN gmin_shallow(GEN x, GEN y)` shallow version of `gmin`.

9.6.2 Comparison with a small integer.

`int isexactzero(GEN x)` returns 1 (true) if x is exactly equal to 0 (including `t_INTMODs` like `Mod(0,2)`), and 0 (false) otherwise. This includes recursive objects, for instance vectors, whose components are 0.

`GEN gisexactzero(GEN x)` returns `NULL` unless x is exactly equal to 0 (as per `isexactzero`). When x is an exact zero return the attached scalar zero as a `t_INT` (`gen_0`), a `t_INTMOD` (`Mod(0,N)` for the largest possible N) or a `t_FFELT`.

`int isrationalzero(GEN x)` returns 1 (true) if x is equal to an integer 0 (excluding `t_INTMODs` like `Mod(0,2)`), and 0 (false) otherwise. Contrary to `isintzero`, this includes recursive objects, for instance vectors, whose components are 0.

`int ismpzzero(GEN x)` returns 1 (true) if x is a `t_INT` or a `t_REAL` equal to 0.

`int isintzero(GEN x)` returns 1 (true) if x is a `t_INT` equal to 0.

`int isint1(GEN x)` returns 1 (true) if `x` is a `t_INT` equal to 1.

`int isintm1(GEN x)` returns 1 (true) if `x` is a `t_INT` equal to -1 .

`int equali1(GEN n)` Assuming that `x` is a `t_INT`, return 1 (true) if `x` is equal to 1, and return 0 (false) otherwise.

`int equalim1(GEN n)` Assuming that `x` is a `t_INT`, return 1 (true) if `x` is equal to -1 , and return 0 (false) otherwise.

`int is_pm1(GEN x)`. Assuming that `x` is a *nonzero* `t_INT`, return 1 (true) if `x` is equal to -1 or 1, and return 0 (false) otherwise.

`int gequal0(GEN x)` returns 1 (true) if `x` is equal to 0, 0 (false) otherwise.

`int gequal1(GEN x)` returns 1 (true) if `x` is equal to 1, 0 (false) otherwise.

`int gequalm1(GEN x)` returns 1 (true) if `x` is equal to -1 , 0 (false) otherwise.

`long gcmpsg(long s, GEN x)`

`long gcmpgs(GEN x, long s)` comparison of `x` with the `long s`.

`GEN gmaxsg(long s, GEN x)`

`GEN gmaxgs(GEN x, long s)` returns the largest of `x` and the `long s` (converted to `GEN`)

`GEN gminsg(long s, GEN x)`

`GEN gmings(GEN x, long s)` returns the smallest of `x` and the `long s` (converted to `GEN`)

`long gequalsg(long s, GEN x)`

`long gequalgs(GEN x, long s)` returns 1 (true) if `x` is equal to the `long s`, 0 otherwise.

9.7 Miscellaneous Boolean functions.

`int isrationalzeroscalar(GEN x)` equivalent to, but faster than,

`is_scalar_t(typ(x)) && isrationalzero(x)`

`int isinexact(GEN x)` returns 1 (true) if `x` has an inexact component, and 0 (false) otherwise.

`int isinexactreal(GEN x)` return 1 if `x` has an inexact `t_REAL` component, and 0 otherwise.

`int isrealappr(GEN x, long e)` applies (recursively) to complex inputs; returns 1 if `x` is approximately real to the bit accuracy `e`, and 0 otherwise. This means that any `t_COMPLEX` component must have imaginary part `t` satisfying `gexpo(t) < e`.

`int isint(GEN x, GEN *n)` returns 0 (false) if `x` does not round to an integer. Otherwise, returns 1 (true) and set `n` to the rounded value.

`int issmall(GEN x, long *n)` returns 0 (false) if `x` does not round to a small integer (suitable for `itos`). Otherwise, returns 1 (true) and set `n` to the rounded value.

`long iscomplex(GEN x)` returns 1 (true) if `x` is a complex number (of component types embeddable into the reals) but is not itself real, 0 if `x` is a real (not necessarily of type `t_REAL`), or raises an error if `x` is not embeddable into the complex numbers.

9.7.1 Obsolete.

The following less convenient comparison functions and Boolean operators were used by the historical GP interpreter. They are provided for backward compatibility only and should not be used:

```
GEN gle(GEN x, GEN y)
GEN glt(GEN x, GEN y)
GEN gge(GEN x, GEN y)
GEN ggt(GEN x, GEN y)
GEN geq(GEN x, GEN y)
GEN gne(GEN x, GEN y)
GEN gor(GEN x, GEN y)
GEN gand(GEN x, GEN y)
GEN gnot(GEN x, GEN y)
```

9.8 Sorting.

9.8.1 Basic sort.

`GEN sort(GEN x)` sorts the vector `x` in ascending order using a mergesort algorithm, and `gcmp` as the underlying comparison routine (returns the sorted vector). This routine copies all components of `x`, use `gen_sort_inplace` for a more memory-efficient function.

`GEN lexsort(GEN x)`, as `sort`, using `lexcmp` instead of `gcmp` as the underlying comparison routine.

`GEN vecsort(GEN x, GEN k)`, as `sort`, but sorts the vector `x` in ascending *lexicographic* order, according to the entries of the `t_VECSMALL` `k`. For example, if `k = [2, 1, 3]`, sorting will be done with respect to the second component, and when these are equal, with respect to the first, and when these are equal, with respect to the third.

9.8.2 Indirect sorting.

`GEN indexsort(GEN x)` as `sort`, but only returns the permutation which, applied to `x`, would sort the vector. The result is a `t_VECSMALL`.

`GEN indexlexsort(GEN x)`, as `indexsort`, using `lexcmp` instead of `gcmp` as the underlying comparison routine.

`GEN indexvecsort(GEN x, GEN k)`, as `vecsort`, but only returns the permutation that would sort the vector `x`.

`long vecindexmin(GEN x)` returns the index for a minimal element of `x` (`t_VEC`, `t_COL` or `t_VECSMALL`).

`long vecindexmax(GEN x)` returns the index for a maximal element of `x` (`t_VEC`, `t_COL` or `t_VECSMALL`).

9.8.3 Generic sort and search. The following routines allow to use an arbitrary comparison function `int (*cmp)(void* data, GEN x, GEN y)`, such that `cmp(data,x,y)` returns a negative result if $x < y$, a positive one if $x > y$ and 0 if $x = y$. The `data` argument is there in case your `cmp` requires additional context.

`GEN gen_sort(GEN x, void *data, int (*cmp)(void *, GEN, GEN))`, as `sort`, with an explicit comparison routine.

`GEN gen_sort_shallow(GEN x, void *data, int (*cmp)(void *, GEN, GEN))`, shallow variant of `gen_sort`.

`GEN gen_sort_uniq(GEN x, void *data, int (*cmp)(void *, GEN, GEN))`, as `gen_sort`, removing duplicate entries.

`GEN gen_indexsort(GEN x, void *data, int (*cmp)(void*, GEN, GEN))`, as `indexsort`.

`GEN gen_indexsort_uniq(GEN x, void *data, int (*cmp)(void*, GEN, GEN))`, as `indexsort`, removing duplicate entries.

`void gen_sort_inplace(GEN x, void *data, int (*cmp)(void*, GEN, GEN), GEN *perm)` sort `x` in place, without copying its components. If `perm` is not `NULL`, it is set to the permutation that would sort the original `x`.

`GEN gen_setminus(GEN A, GEN B, int (*cmp)(GEN, GEN))` given two sorted vectors A and B , returns the vector of elements of A not belonging to B .

`GEN sort_factor(GEN y, void *data, int (*cmp)(void *, GEN, GEN))`: assuming `y` is a factorization matrix, sorts its rows in place (no copy is made) according to the comparison function `cmp` applied to its first column.

`GEN merge_sort_uniq(GEN x, GEN y, void *data, int (*cmp)(void *, GEN, GEN))` assuming `x` and `y` are sorted vectors, with respect to the `cmp` comparison function, return a sorted concatenation, with duplicates removed. Shallow function.

`GEN setunion_i(GEN x, GEN y)` shallow version of `setunion`, a simple alias for

`merge_sort_uniq(x,y, (void*)cmp_universal, cmp_nodata)`

`GEN merge_factor(GEN fx, GEN fy, void *data, int (*cmp)(void *, GEN, GEN))` let `fx` and `fy` be factorization matrices for X and Y sorted with respect to the comparison function `cmp` (see `sort_factor`), returns the factorization of $X * Y$.

`GEN ZM_merge_factor(GEN fx, GEN fy)` as `merge_factor`, where `fx` and `fy` are factorization matrices of integers.

`long gen_search(GEN v, GEN y, void *data, int (*cmp)(void*, GEN, GEN))`.

Let v be a vector sorted according to `cmp(data,a,b)`; look for an index i such that $v[i]$ is equal to y . If y is found, return i (not necessarily the first occurrence in case of multisets), else return $-i$ where i is the index where y should be inserted.

`long tablesearch(GEN T, GEN x, int (*cmp)(GEN, GEN))` is a faster implementation for the common case `gen_search(T,x,cmp,cmp_nodata)` when we have no need to insert missing elements; return 0 in case x is not found.

9.8.4 Further useful comparison functions.

`int cmp_universal(GEN x, GEN y)` a somewhat arbitrary universal comparison function, devoid of sensible mathematical meaning. It is transitive, and returns 0 if and only if `gidentical(x,y)` is true. Useful to sort and search vectors of arbitrary data.

`int cmp_nodata(void *data, GEN x, GEN y)`. This function is a hack used to pass an existing basic comparison function lacking the `data` argument, i.e. with prototype `int (*cmp)(GEN x, GEN y)`. Instead of `gen_sort(x, NULL, cmp)` which may or may not work depending on how your compiler handles typecasts between incompatible function pointers, one should use `gen_sort(x, (void*)cmp, cmp_nodata)`.

Here are a few basic comparison functions, to be used with `cmp_nodata`:

`int ZV_cmp(GEN x, GEN y)` compare two ZV, which we assume have the same length (lexicographic order).

`int cmp_Flx(GEN x, GEN y)` compare two Flx, which we assume have the same main variable (lexicographic order).

`int cmp_RgX(GEN x, GEN y)` compare two polynomials, which we assume have the same main variable (lexicographic order). The coefficients are compared using `gcmp`.

`int cmp_prime_over_p(GEN x, GEN y)` compare two prime ideals, which we assume divide the same prime number. The comparison is ad hoc but orders according to increasing residue degrees.

`int cmp_prime_ideal(GEN x, GEN y)` compare two prime ideals in the same nf . Orders by increasing primes, breaking ties using `cmp_prime_over_p`.

`int cmp_padic(GEN x, GEN y)` compare two `t_PADIC` (for the same prime p).

Finally a more elaborate comparison function:

`int gen_cmp_RgX(void *data, GEN x, GEN y)` compare two polynomials, ordering first by increasing degree, then according to the coefficient comparison function:

```
int (*cmp_coeff)(GEN,GEN) = (int (*)(GEN,GEN)) data;
```

9.9 Division.

`GEN gdivgu(GEN x, ulong u)` return x/u .

`GEN gdivgunextu(GEN x, ulong u)` return $x/(u(u+1))$. If $u(u+1)$ does not fit into an `ulong`, it is created and left on the stack for efficiency.

`GEN divrunextu(GEN x, ulong i)` as `gdivgunextu` for a `t_REAL` x .

9.10 Divisibility, Euclidean division.

GEN gdivexact(GEN *x*, GEN *y*) returns the quotient x/y , assuming *y* divides *x*. Not stack clean if $y = 1$ (we return *x*, not a copy).

int gdvd(GEN *x*, GEN *y*) returns 1 (true) if *y* divides *x*, 0 otherwise.

GEN gdiventres(GEN *x*, GEN *y*) creates a 2-component vertical vector whose components are the true Euclidean quotient and remainder of *x* and *y*.

GEN gdivent[*z*](GEN *x*, GEN *y*[, GEN *z*]) yields the true Euclidean quotient of *x* and the **t_INT** or **t_POL** *y*, as per the \backslash GP operator.

GEN gdiventsg(long *s*, GEN *y*[, GEN *z*]), as **gdivent** except that *x* is a long.

GEN gdiventgs[*z*](GEN *x*, long *s*[, GEN *z*]), as **gdivent** except that *y* is a long.

GEN gmod[*z*](GEN *x*, GEN *y*[, GEN *z*]) yields the remainder of *x* modulo the **t_INT** or **t_POL** *y*, as per the % GP operator. A **t_REAL** or **t_FRAC** *y* is also allowed, in which case the remainder is the unique real r such that $0 \leq r < |y|$ and $y = qx + r$ for some (in fact unique) integer q .

GEN gmodsg(long *s*, GEN *y*[, GEN *z*]) as **gmod**, except *x* is a long.

GEN gmodgs(GEN *x*, long *s*[, GEN *z*]) as **gmod**, except *y* is a long.

GEN gdivmod(GEN *x*, GEN *y*, GEN **r*) If *r* is not equal to **NULL** or **ONLY_REM**, creates the (false) Euclidean quotient of *x* and *y*, and puts (the address of) the remainder into **r*. If *r* is equal to **NULL**, do not create the remainder, and if *r* is equal to **ONLY_REM**, create and output only the remainder. The remainder is created after the quotient and can be disposed of individually with a **cgiv**(*r*).

GEN poldivrem(GEN *x*, GEN *y*, GEN **r*) same as **gdivmod** but specifically for **t_POLs** *x* and *y*, not necessarily in the same variable. Either of *x* and *y* may also be scalars, treated as polynomials of degree 0.

GEN gdeuc(GEN *x*, GEN *y*) creates the Euclidean quotient of the **t_POLs** *x* and *y*. Either of *x* and *y* may also be scalars, treated as polynomials of degree 0.

GEN grem(GEN *x*, GEN *y*) creates the Euclidean remainder of the **t_POL** *x* divided by the **t_POL** *y*. Either of *x* and *y* may also be scalars, treated as polynomials of degree 0.

GEN gdivround(GEN *x*, GEN *y*) if *x* and *y* are real (**t_INT**, **t_REAL**, **t_FRAC**), return the rounded Euclidean quotient of *x* and *y* as per the $\backslash/$ GP operator. Operate componentwise if *x* is a **t_COL**, **t_VEC** or **t_MAT**. Otherwise as **gdivent**.

GEN centermod_i(GEN *x*, GEN *y*, GEN *y2*), as **centermodii**, componentwise.

GEN centermod(GEN *x*, GEN *y*), as **centermod_i**, except that *y2* is computed (and left on the stack for efficiency).

GEN ginvmod(GEN *x*, GEN *y*) creates the inverse of *x* modulo *y* when it exists. *y* must be of type **t_INT** (in which case *x* is of type **t_INT**) or **t_POL** (in which case *x* is either a scalar type or a **t_POL**).

9.11 GCD, content and primitive part.

9.11.1 Generic.

`GEN resultant(GEN x, GEN y)` creates the resultant of the `t_POLs` `x` and `y` computed using Sylvester's matrix (inexact inputs), a modular algorithm (inputs in $\mathbf{Q}[X]$) or the subresultant algorithm, as optimized by Lazard and Ducos. Either of `x` and `y` may also be scalars (treated as polynomials of degree 0)

`GEN ggcd(GEN x, GEN y)` creates the GCD of `x` and `y`.

`GEN glcm(GEN x, GEN y)` creates the LCM of `x` and `y`.

`GEN gbezout(GEN x, GEN y, GEN *u, GEN *v)` returns the GCD of `x` and `y`, and puts (the addresses of) objects `u` and `v` such that $ux + vy = \text{gcd}(x, y)$ into `*u` and `*v`.

`GEN subresext(GEN x, GEN y, GEN *U, GEN *V)` returns the resultant of `x` and `y`, and puts (the addresses of) polynomials `u` and `v` such that $ux + vy = \text{Res}(x, y)$ into `*U` and `*V`.

`GEN content(GEN x)` returns the GCD of all the components of `x`.

`GEN primitive_part(GEN x, GEN *c)` sets `c` to `content(x)` and returns the primitive part x / c . A trivial content is set to `NULL`.

`GEN primpart(GEN x)` as above but the content is lost. (For efficiency, the content remains on the stack.)

`GEN denom_i(GEN x)` shallow version of `denom`.

`GEN numer_i(GEN x)` shallow version of `numer`.

9.11.2 Over the rationals.

`long Q_pval(GEN x, GEN p)` valuation at the `t_INT` `p` of the `t_INT` or `t_FRAC` `x`.

`long Q_lval(GEN x, ulong p)` same for `ulong` `p`.

`long Q_pvalrem(GEN x, GEN p, GEN *r)` returns the valuation e at the `t_INT` `p` of the `t_INT` or `t_FRAC` `x`. The quotient x/p^e is returned in `*r`.

`long Q_lvalrem(GEN x, ulong p, GEN *r)` same for `ulong` `p`.

`GEN Q_abs(GEN x)` absolute value of the `t_INT` or `t_FRAC` `x`.

`GEN Qdivii(GEN x, GEN y)`, assuming x and y are both of type `t_INT`, return the quotient x/y as a `t_INT` or `t_FRAC`; marginally faster than `gdiv`.

`GEN Qdivis(GEN x, long y)`, assuming x is an `t_INT`, return the quotient x/y as a `t_INT` or `t_FRAC`; marginally faster than `gdiv`.

`GEN Qdiviu(GEN x, ulong y)`, assuming x is an `t_INT`, return the quotient x/y as a `t_INT` or `t_FRAC`; marginally faster than `gdiv`.

`GEN Q_abs_shallow(GEN x)` x being a `t_INT` or a `t_FRAC`, returns a shallow copy of $|x|$, in particular returns x itself when $x \geq 0$, and `gneg(x)` otherwise.

`GEN Q_gcd(GEN x, GEN y)` gcd of the `t_INT` or `t_FRAC` `x` and `y`.

In the following functions, arguments belong to a $M \otimes_{\mathbf{Z}} \mathbf{Q}$ for some natural \mathbf{Z} -module M , e.g. multivariate polynomials with integer coefficients (or vectors/matrices recursively built from such

objects), and an element of M is said to be *integral*. We are interested in contents, denominators, etc. with respect to this canonical integral structure; in particular, contents belong to \mathbf{Q} , denominators to \mathbf{Z} . For instance the \mathbf{Q} -content of $(1/2)xy$ is $(1/2)$, and its \mathbf{Q} -denominator is 2, whereas `content` would return $y/2$ and `denom` 1.

`GEN Q_content(GEN x)` the \mathbf{Q} -content of x .

`GEN Z_content(GEN x)` as `Q_content` but assume that all rationals are in fact `t_INTs` and return `NULL` when the content is 1. This function returns as soon as the content is found to equal 1.

`GEN Q_content_safe(GEN x)` as `Q_content`, returning `NULL` when the \mathbf{Q} -content is not defined (e.g. for a `t_REAL` or `t_INTMOD` component).

`GEN Q_denom(GEN x)` the \mathbf{Q} -denominator of x . Shallow function. Raises an `e_TYPE` error out when the notion is meaningless, e.g. for a `t_REAL` or `t_INTMOD` component.

`GEN Q_denom_safe(GEN x)` the \mathbf{Q} -denominator of x . Shallow function. Return `NULL` when the notion is meaningless.

`GEN Q_primitive_part(GEN x, GEN *c)` sets c to the \mathbf{Q} -content of x and returns x / c , which is integral.

`GEN Q_primpart(GEN x)` as above but the content is lost. (For efficiency, the content remains on the stack.)

`GEN vec_Q_primpart(GEN x)` as above component-wise. Applied to a `t_MAT`, the result has primitive columns.

`GEN row_Q_primpart(GEN x)` as above, applied to the rows of a `t_MAT`, so that the result has primitive rows. Not `gerepile`-safe.

`GEN Q_remove_denom(GEN x, GEN *ptd)` sets d to the \mathbf{Q} -denominator of x and returns $x * d$, which is integral. Shallow function.

`GEN Q_div_to_int(GEN x, GEN c)` returns x / c , assuming c is a rational number (`t_INT` or `t_FRAC`) and the result is integral.

`GEN Q_mul_to_int(GEN x, GEN c)` returns $x * c$, assuming c is a rational number (`t_INT` or `t_FRAC`) and the result is integral.

`GEN Q_muli_to_int(GEN x, GEN d)` returns $x * c$, assuming c is a `t_INT` and the result is integral.

`GEN mul_content(GEN cx, GEN cy)` cx and cy are as set by `primitive_part`: either a `GEN` or `NULL` representing the trivial content 1. Returns their product (either a `GEN` or `NULL`).

`GEN div_content(GEN cx, GEN cy)` cx and cy are as set by `primitive_part`: either a `GEN` or `NULL` representing the trivial content 1. Returns their quotient (either a `GEN` or `NULL`).

`GEN inv_content(GEN c)` c is as set by `primitive_part`: either a `GEN` or `NULL` representing the trivial content 1. Returns its inverse (either a `GEN` or `NULL`).

`GEN mul_denom(GEN dx, GEN dy)` dx and dy are as set by `Q_remove_denom`: either a `t_INT` or `NULL` representing the trivial denominator 1. Returns their product (either a `t_INT` or `NULL`).

9.12 Generic arithmetic operators.

9.12.1 Unary operators.

GEN `gneg[z](GEN x[, GEN z])` yields $-x$.

GEN `gneg_i(GEN x)` shallow function yielding $-x$.

GEN `gabs[z](GEN x[, GEN z])` yields $|x|$.

GEN `gsqr(GEN x)` creates the square of x .

GEN `ginv(GEN x)` creates the inverse of x .

9.12.2 Binary operators.

Let “*op*” be a binary operation among

op=**add**: addition ($x + y$).

op=**sub**: subtraction ($x - y$).

op=**mul**: multiplication ($x * y$).

op=**div**: division (x / y).

The names and prototypes of the functions corresponding to *op* are as follows:

GEN `gop(GEN x, GEN y)`

GEN `gopgs(GEN x, long s)`

GEN `gopgu(GEN x, ulong u)`

GEN `gopsg(long s, GEN y)`

GEN `gopug(ulong u, GEN y)`

Explicitly

GEN `gadd(GEN x, GEN y)`, GEN `gaddgs(GEN x, long s)`, GEN `gaddsg(long s, GEN x)`

GEN `gmul(GEN x, GEN y)`, GEN `gmulgs(GEN x, long s)`, GEN `gmulsg(long s, GEN x)`, GEN `gmulgu(GEN x, ulong u)`, GEN `gmulug(GEN x, ulong u)`,

GEN `gsub(GEN x, GEN y)`, GEN `gsubgs(GEN x, long s)`, GEN `gsubsg(long s, GEN x)`

GEN `gdiv(GEN x, GEN y)`, GEN `gdivgs(GEN x, long s)`, GEN `gdivsg(long s, GEN x)`, GEN `gdivgu(GEN x, ulong u)`,

GEN `gpow(GEN x, GEN y, long l)` creates x^y . If y is a `t_INT`, return `powgi(x,y)` (the precision l is not taken into account). Otherwise, the result is $\exp(y * \log(x))$ where exact arguments are converted to floats of precision l in case of need; if there is no need, for instance if x is a `t_REAL`, l is ignored. Indeed, if x is a `t_REAL`, the accuracy of $\log x$ is determined from the accuracy of x , it is no problem to multiply by y , even if it is an exact type, and the accuracy of the exponential is determined, exactly as in the case of the initial $\log x$.

GEN `gpowgs(GEN x, long n)` creates x^n using binary powering. To treat the special case $n = 0$, we consider `gpowgs` as a series of `gmul`, so we follow the rule of returning result which is as exact as possible given the input. More precisely, we return

- `gen_1` if x has type `t_INT`, `t_REAL`, `t_FRAC`, or `t_PADIC`
- `Mod(1,N)` if x is a `t_INTMOD` modulo N .
- `gen_1` for `t_COMPLEX`, `t_QUAD` unless one component is a `t_INTMOD`, in which case we return `Mod(1, N)` for a suitable N (the gcd of the moduli that appear).
- `FF_1(x)` for a `t_FFELT`.
- `qfb_1(x)` for `t_QFB`.
- the identity permutation for `t_VECSMALL`.
- `Rg_get_1(x)` otherwise

Of course, the only practical use of this routine for $n = 0$ is to obtain the multiplicative neutral element in the base ring (or to treat marginal cases that should be special cased anyway if there is the slightest doubt about what the result should be).

`GEN powgi(GEN x, GEN y)` creates x^y , where y is a `t_INT`, using left-shift binary powering. The case where $y = 0$ (as all cases where y is small) is handled by `gpowgs(x, 0)`.

`GEN gpowers(GEN x, long n)` returns the vector $[1, x, \dots, x^n]$.

`GEN grootsof1(long n, long prec)` returns the vector $[1, x, \dots, x^{n-1}]$, where x is the n -th root of unity $\exp(2i\pi/n)$.

`GEN gsqrpowers(GEN x, long n)` returns the vector $[x, x^4, \dots, x^{n^2}]$.

In addition we also have the obsolete forms:

`void gaddz(GEN x, GEN y, GEN z)`

`void gsubz(GEN x, GEN y, GEN z)`

`void gmulz(GEN x, GEN y, GEN z)`

`void gdivz(GEN x, GEN y, GEN z)`

9.13 Generic operators: product, powering, factorback.

To describe the following functions, we use the following private typedefs to simplify the description:

```
typedef (*F0)(void *);
typedef (*F1)(void *, GEN);
typedef (*F2)(void *, GEN, GEN);
```

They correspond to generic functions with one and two arguments respectively (the `void*` argument provides some arbitrary evaluation context).

`GEN gen_product(GEN v, void *D, F2 op)` Given two objects x, y , assume that `op(D, x, y)` implements an associative binary operator. If v has k entries, return

$$v[1] \text{ op } v[2] \text{ op } \dots \text{ op } v[k];$$

returns `gen_1` if $k = 0$ and a copy of $v[1]$ if $k = 1$. Use divide and conquer strategy. Leave some garbage on stack, but suitable for `gerepileupto` if `mul` is.

GEN `gen_pow`(GEN `x`, GEN `n`, void `*D`, F1 `sqr`, F2 `mul`) $n > 0$ a `t_INT`, returns x^n ; `mul`(`D`, `x`, `y`) implements the multiplication in the underlying monoid; `sqr` is a (presumably optimized) shortcut for `mul`(`D`, `x`, `x`).

GEN `gen_powu`(GEN `x`, ulong `n`, void `*D`, F1 `sqr`, F2 `mul`) $n > 0$, returns x^n . See `gen_pow`.

GEN `gen_pow_i`(GEN `x`, GEN `n`, void `*E`, F1 `sqr`, F2 `mul`) internal variant of `gen_pow`, not memory-clean.

GEN `gen_powu_i`(GEN `x`, ulong `n`, void `*E`, F1 `sqr`, F2 `mul`) internal variant of `gen_powu`, not memory-clean.

GEN `gen_pow_fold`(GEN `x`, GEN `n`, void `*D`, F1 `sqr`, F1 `msqr`) variant of `gen_pow`, where `mul` is replaced by `msqr`, with `msqr`(`D`, `y`) returning xy^2 . In particular `D` must implicitly contain `x`.

GEN `gen_pow_fold_i`(GEN `x`, GEN `n`, void `*E`, F1 `sqr`, F1 `msqr`) internal variant of the function `gen_pow_fold`, not memory-clean.

GEN `gen_powu_fold`(GEN `x`, ulong `n`, void `*D`, F1 `sqr`, F1 `msqr`), see `gen_pow_fold`.

GEN `gen_powu_fold_i`(GEN `x`, ulong `n`, void `*E`, F1 `sqr`, F1 `msqr`) see `gen_pow_fold_i`.

GEN `gen_pow_init`(GEN `x`, GEN `n`, long `k`, void `*E`, GEN (`*sqr`)(void*, GEN), GEN (`*mul`)(void*, GEN, GEN)) Return a table `R` that can be used with `gen_pow_table` to compute the powers of `x` up to `n`. The table is of size $2^k \log_2(n)$.

GEN `gen_pow_table`(GEN `R`, GEN `n`, void `*E`, GEN (`*one`)(void*), GEN (`*mul`)(void*, GEN, GEN))

Return x^n , where `R` is as given by `gen_pow_init`(`x`,`m`,`k`,`E`,`sqr`,`mul`) for some integer $m \geq n$.

GEN `gen_powers`(GEN `x`, long `n`, long `usesqr`, void `*D`, F1 `sqr`, F2 `mul`, F0 `one`) returns $[x^0, \dots, x^n]$ as a `t_VEC`; `mul`(`D`, `x`, `y`) implements the multiplication in the underlying monoid; `sqr` is a (presumably optimized) shortcut for `mul`(`D`, `x`, `x`); `one` returns the monoid unit. The flag `usesqr` should be set to 1 if squaring are faster than multiplication by `x`.

GEN `gen_factorback`(GEN `L`, GEN `e`, void `*D`, F2 `mul`, F2 `pow`, GEN (`*one`)(void *)`D`) generic form of `factorback`. The pair $[L, e]$ is of the form

- `[fa, NULL]`, `fa` a two-column factorization matrix: expand it.
- `[v, NULL]`, `v` a vector of objects: return their product.
- or `[v, e]`, `v` a vector of objects, `e` a vector of integral exponents (a `ZV` or `zV`): return the product of the $v[i]^{e[i]}$.

`mul`(`D`, `x`, `y`) and `pow`(`D`, `x`, `n`) return xy and x^n respectively.

`one`(`D`) returns the neutral element. If `one` is `NULL`, `gen_1` is used instead.

9.14 Matrix and polynomial norms.

This section concerns only standard norms of **R** and **C** vector spaces, not algebraic norms given by the determinant of some multiplication operator. We have already seen type-specific functions like `ZM_supnorm` or `RgM_fpnorml2` and limit ourselves to generic functions assuming nothing about their `GEN` argument; these functions allow the following scalar types: `t_INT`, `t_FRAC`, `t_REAL`, `t_COMPLEX`, `t_QUAD` and are defined recursively (in terms of norms of their components) for the following “container” types: `t_POL`, `t_VEC`, `t_COL` and `t_MAT`. They raise an error if some other type appears in the argument.

GEN gnorml2(GEN x) The norm of a scalar is the square of its complex modulus, the norm of a recursive type is the sum of the norms of its components. For polynomials, vectors or matrices of complex numbers one recovers the *square* of the usual L^2 norm. In most applications, the missing square root computation can be skipped.

GEN gnorml1(GEN x, long prec) The norm of a scalar is its complex modulus, the norm of a recursive type is the sum of the norms of its components. For polynomials, vectors or matrices of complex numbers one recovers the usual L^1 norm. One must include a real precision `prec` in case the inputs include `t_COMPLEX` or `t_QUAD` with exact rational components: a square root must be computed and we must choose an accuracy.

GEN gnorml1_fake(GEN x) as `gnorml1`, except that the norm of a `t_QUAD` $x + wy$ or `t_COMPLEX` $x + Iy$ is defined as $|x| + |y|$, where we use the ordinary real absolute value. This is still a norm of **R** vector spaces, which is easier to compute than `gnorml1` and can often be used in its place.

GEN gsupnorm(GEN x, long prec) The norm of a scalar is its complex modulus, the norm of a recursive type is the max of the norms of its components. A precision `prec` must be included for the same reason as in `gnorml1`.

void gsupnorm_aux(GEN x, GEN *m, GEN *m2, long prec) is the low-level function underlying `gsupnorm`, used as follows:

```
GEN m = NULL, m2 = NULL;
gsupnorm_aux(x, &m, &m2);
```

After the call, the sup norm of x is the min of `m` and the square root of `m2`; one or both of `m`, `m2` may be `NULL`, in which case it must be omitted. You may initially set `m` and `m2` to non-`NULL` values, in which case, the above procedure yields the max of (the initial) `m`, the square root of (the initial) `m2`, and the sup norm of x .

The strange interface is due to the fact that $|z|^2$ is easier to compute than $|z|$ for a `t_QUAD` or `t_COMPLEX` z : `m2` is the max of those $|z|^2$, and `m` is the max of the other $|z|$.

9.15 Substitution and evaluation.

GEN gsubst(GEN x, long v, GEN y) substitutes the object y into x for the variable number v.

GEN poleval(GEN q, GEN x) evaluates the t_POL or t_RFRAC q at x . For convenience, a t_VEC or t_COL is also recognized as the t_POL gtovectrev(q).

GEN RgX_cxeval(GEN T, GEN x, GEN xi) evaluate the t_POL T at x via Horner's scheme. If xi is not NULL it must be equal to $1/x$ and we evaluate $x^{\deg T}T(1/x)$ instead. This is useful when $|x| > 1$ is a t_REAL or an inexact t_COMPLEX and T has “balanced” coefficients, since the evaluation becomes numerically stable.

GEN RgXY_cxevalx(GEN T, GEN x, GEN xi) Apply RgX_cxeval to all the polynomials coefficients of T .

GEN RgX_RgM_eval(GEN q, GEN x) evaluates the t_POL q at the square matrix x .

GEN RgX_RgMV_eval(GEN f, GEN V) returns the evaluation $f(x)$, assuming that V was computed by FpXQ_powers(x, n) for some $n > 1$.

GEN qfeval(GEN q, GEN x) evaluates the quadratic form q (symmetric matrix) at x (column vector of compatible dimensions).

GEN qfevalb(GEN q, GEN x, GEN y) evaluates the polar bilinear form attached to the quadratic form q (symmetric matrix) at x, y (column vectors of compatible dimensions).

GEN hqfeval(GEN q, GEN x) evaluates the Hermitian form q (a Hermitian complex matrix) at x .

GEN qf_RgM_apply(GEN q, GEN M) q is a symmetric $n \times n$ matrix, M an $n \times k$ matrix, return $M'qM$.

GEN qf_ZM_apply(GEN q, GEN M) as above assuming that both q and M have integer entries.

Chapter 10: Miscellaneous mathematical functions

10.1 Fractions.

GEN `absfrac`(GEN `x`) returns the absolute value of the `t_FRAC` `x`.

GEN `absfrac_shallow`(GEN `x`) `x` being a `t_FRAC`, returns a shallow copy of $|x|$, in particular returns `x` itself when $x \geq 0$, and `gneg(x)` otherwise.

GEN `sqrfrac`(GEN `x`) returns the square of the `t_FRAC` `x`.

10.2 Binomials.

GEN `binomial`(GEN `x`, long `k`)

GEN `binomialuu`(ulong `n`, ulong `k`)

GEN `vecbinomial`(long `n`), which returns a vector `v` with $n + 1$ `t_INT` components such that $v[k + 1] = \text{binomial}(n, k)$ for `k` from 0 up to `n`.

10.3 Real numbers.

GEN `R_abs`(GEN `x`) `x` being a `t_INT`, a `t_REAL` or a `t_FRAC`, returns $|x|$.

GEN `R_abs_shallow`(GEN `x`) `x` being a `t_INT`, a `t_REAL` or a `t_FRAC`, returns a shallow copy of $|x|$, in particular returns `x` itself when $x \geq 0$, and `gneg(x)` otherwise.

GEN `modRr_safe`(GEN `x`, GEN `y`) let `x` be a `t_INT`, a `t_REAL` or `t_FRAC` and let `y` be a `t_REAL`. Return $x \% y$ unless the input accuracy is insufficient to compute the floor or x/y in which case we return `NULL`.

GEN `modRr_i`(GEN `x`, GEN `y`, GEN `iy`) let `x` be a `t_INT`, a `t_REAL` or `t_FRAC` and let `y` be a `t_REAL` and `iy = invr(y)`. Return $x \% y$ unless the input accuracy is insufficient to compute the floor or x/y in which case we return `NULL`.

10.4 Complex numbers.

GEN `gimag`(GEN `x`) returns a copy of the imaginary part of `x`.

GEN `greal`(GEN `x`) returns a copy of the real part of `x`. If `x` is a `t_QUAD`, returns the coefficient of 1 in the “canonical” integral basis $(1, \omega)$.

GEN `gconj`(GEN `x`) returns `greal(x) - 2gimag(x)`, which is the ordinary complex conjugate except for a real `t_QUAD`.

GEN `imag_i`(GEN `x`), shallow variant of `gimag`.

GEN `real_i`(GEN `x`), shallow variant of `greal`.

GEN `conj_i`(GEN `x`), shallow variant of `gconj`.

GEN `mulreal`(GEN `x`, GEN `y`) returns the real part of xy ; x, y have type `t_INT`, `t_FRAC`, `t_REAL` or `t_COMPLEX`. See also `RgM_mulreal`.

GEN `cxnorm`(GEN `x`) norm of the `t_COMPLEX` x (modulus squared).

GEN `cxexpm1`(GEN `x`) returns $\exp(x) - 1$, for a `t_COMPLEX` x .

int `cx_approx_equal`(GEN `a`, GEN `b`) test whether (`t_INT`, `t_FRAC`, `t_REAL`, or `t_COMPLEX` of those) a and b are approximately equal. This returns 1 if and only if the division by $a - b$ would produce a division by 0 (which is a less stringent test than testing whether $a - b$ evaluates to 0).

int `cx_approx0`(GEN `a`, GEN `b`) test whether (`t_INT`, `t_FRAC`, `t_REAL`, or `t_COMPLEX` of those) a is approximately 0, where b is a reference point. A non-0 `t_REAL` component x is approximately 0 if

$$\text{exponent}(b) - \text{exponent}(x) > \text{bit_prec}(x).$$

10.5 Quadratic numbers and binary quadratic forms.

GEN `quad_disc`(GEN `x`) returns the discriminant of the `t_QUAD` x . Not stack-clean but suitable for `gerepileupto`.

GEN `quadnorm`(GEN `x`) norm of the `t_QUAD` x .

GEN `qfb_disc`(GEN `x`) returns the discriminant of the `t_QFB` x .

GEN `qfb_disc3`(GEN `x`, GEN `y`, GEN `z`) returns $y^2 - 4xz$ assuming all inputs are `t_INT`s. Not stack-clean.

GEN `qfb_ZM_apply`(GEN `q`, GEN `g`) returns $q \circ g$.

GEN `qfbforms`(GEN `D`) given a discriminant $D < 0$, return the list of reduced forms of discriminant D as `t_VECSMALL` with 3 components. The primitive forms in the list enumerate the class group of the quadratic order of discriminant D ; if D is fundamental, all returned forms are automatically primitive.

10.6 Polynomials.

GEN truecoef(GEN x , long n) returns **polcoef**($x, n, -1$), i.e. the coefficient of the term of degree n in the main variable. This is a safe but expensive function that must *copy* its return value so that it be *gerepile*-safe. Use **polcoef_i** for a fast internal variant.

GEN polcoef_i(GEN x , long n , long v) internal shallow function. Rewrite x as a Laurent polynomial in the variable v and returns its coefficient of degree n (**gen_0** if this falls outside the coefficient array). Allow **t_POL**, **t_SER**, **t_RFRAC** and scalars.

long degree(GEN x) returns **poldegree**($x, -1$), the degree of x with respect to its main variable, with the usual meaning if the leading coefficient of x is nonzero. If the sign of x is 0, this function always returns -1 . Otherwise, we return the index of the leading coefficient of x , i.e. the coefficient of largest index stored in x . For instance the “degrees” of

```
0. E-38 * x^4 + 0.E-19 * x + 1
Mod(0,2) * x^0    \\ sign is 0 !
```

are 4 and -1 respectively.

long degpol(GEN x) is a simple macro returning **lg**(x) $- 3$. This is the degree of the **t_POL** x with respect to its main variable, *if* its leading coefficient is nonzero (a rational 0 is impossible, but an inexact 0 is allowed, as well as an exact modular 0, e.g. **Mod**(0,2)). If x has no coefficients (rational 0 polynomial), its length is 2 and we return the expected -1 .

GEN characteristic(GEN x) returns the characteristic of the base ring over which the polynomial is defined (as defined by **t_INTMOD** and **t_FFELT** components). The function raises an exception if incompatible primes arise from **t_FFELT** and **t_PADIC** components. Shallow function.

GEN residual_characteristic(GEN x) returns a kind of “residual characteristic” of the base ring over which the polynomial is defined. This is defined as the gcd of all moduli **t_INTMOD**s occurring in the structure, as well as primes p arising from **t_PADIC**s or **t_FFELT**s. The function raises an exception if incompatible primes arise from **t_FFELT** and **t_PADIC** components. Shallow function.

GEN resultant(GEN x , GEN y) resultant of x and y , with respect to the main variable of highest priority. Uses either the subresultant algorithm (generic case), a modular algorithm (inputs in $\mathbf{Q}[X]$) or Sylvester’s matrix (inexact inputs).

GEN resultant2(GEN x , GEN y) resultant of x and y , with respect to the main variable of highest priority. Computes the determinant of Sylvester’s matrix.

GEN cleanroots(GEN x , long $prec$) returns the complex roots of the complex polynomial x (with coefficients **t_INT**, **t_FRAC**, **t_REAL** or **t_COMPLEX** of the above). The roots are returned as **t_REAL** or **t_COMPLEX** of **t_REALS** of precision $prec$ (guaranteeing a nonzero imaginary part). See **QX_complex_roots**.

double fujiwara_bound(GEN x) return a quick upper bound for the logarithm in base 2 of the modulus of the largest complex roots of the polynomial x (complex coefficients).

double fujiwara_bound_real(GEN x , long $sign$) return a quick upper bound for the logarithm in base 2 of the absolute value of the largest real root of sign $sign$ (1 or -1), for the polynomial x (real coefficients).

GEN polmod_to_embed(GEN x , long $prec$) return the vector of complex embeddings of the **t_POLMOD** x (with complex coefficients). Shallow function, simple complex variant of **conjvec**.

GEN pollegendre_reduced(long n , long v) let $P_n(t) \in \mathbf{Q}[t]$ be the n -th Legendre polynomial in variable v . Return $p \in \mathbf{Z}[t]$ such that $2^n P_n(t) = p(t^2)$ (n even) or $tp(t^2)$ (n odd).

10.7 Power series.

`GEN sertoser(GEN x, long prec)` return the `t_SER` x truncated or extended (with zeros) to `prec` terms. Shallow function, assume that `prec` ≥ 0 .

`GEN derivser(GEN x)` returns the derivative of the `t_SER` x with respect to its main variable.

`GEN integser(GEN x)` returns the primitive of the `t_SER` x with respect to its main variable.

`GEN truecoef(GEN x, long n)` returns `polcoef(x,n, -1)`, i.e. the coefficient of the term of degree `n` in the main variable. This is a safe but expensive function that must *copy* its return value so that it be *gerepile*-safe. Use `polcoef_i` for a fast internal variant.

`GEN ser_unscale(GEN P, GEN h)` return $P(hx)$, not memory clean.

`GEN ser_normalize(GEN x)` divide x by its “leading term” so that the series is either 0 or equal to $t^v(1 + O(t))$. Shallow function if the “leading term” is 1.

`int ser_isexactzero(GEN x)` return 1 if x is a zero series, all of whose known coefficients are exact zeroes; this implies that $\text{sign}(x) = 0$ and $\text{lg}(x) \leq 3$.

`GEN ser_inv(GEN x)` return the inverse of the `t_SER` x using Newton iteration.

`GEN psi1series(long n, long v, long prec)` creates the `t_SER` $\psi(1 + x + O(x^n))$ in variable v .

10.8 Functions to handle `t_FFELT`.

These functions define the public interface of the `t_FFELT` type to use in generic functions. However, in specific functions, it is better to use the functions class `FpXQ` and/or `F1xq` as appropriate.

`GEN FF_p(GEN a)` returns the characteristic of the definition field of the `t_FFELT` element a .

`long FF_f(GEN a)` returns the dimension of the definition field over its prime field; the cardinality of the dimension field is thus p^f .

`GEN FF_p_i(GEN a)` shallow version of `FF_p`.

`GEN FF_q(GEN a)` returns the cardinality of the definition field of the `t_FFELT` element a .

`GEN FF_mod(GEN a)` returns the polynomial (with reduced `t_INT` coefficients) defining the finite field, in the variable used to display a .

`long FF_var(GEN a)` returns the variable used to display a .

`GEN FF_gen(GEN a)` returns the standard generator of the definition field of the `t_FFELT` element a , see `ffgen`, that is $x \pmod{T}$ where T is the polynomial over the prime field that define the finite field.

`GEN FF_to_FpXQ(GEN a)` converts the `t_FFELT` a to a polynomial P with reduced `t_INT` coefficients such that $a = P(g)$ where g is the generator of the finite field returned by `ffgen`, in the variable used to display g .

`GEN FF_to_FpXQ_i(GEN a)` shallow version of `FF_to_FpXQ`.

`GEN FF_to_F2xq(GEN a)` converts the `t_FFELT` a to a `F2x` P such that $a = P(g)$ where g is the generator of the finite field returned by `ffgen`, in the variable used to display g . This only work if the characteristic is 2.

GEN FF_to_F2xq_i(GEN a) shallow version of FF_to_F2xq.

GEN FF_to_Flxq(GEN a) converts the t_FFELT a to a Flx P such that $a = P(g)$ where g is the generator of the finite field returned by `ffgen`, in the variable used to display g . This only work if the characteristic is small enough.

GEN FF_to_Flxq_i(GEN a) shallow version of FF_to_Flxq.

GEN p_to_FF(GEN p, long v) returns a t_FFELT equal to 1 in the finite field $\mathbf{Z}/p\mathbf{Z}$. Useful for generic code that wants to handle (inefficiently) $\mathbf{Z}/p\mathbf{Z}$ as if it were not a prime field.

GEN Tp_to_FF(GEN T, GEN p) returns a t_FFELT equal to 1 in the finite field $\mathbf{F}_p/(T)$, where T is a ZX , assumed to be irreducible modulo p , or NULL in which case the routine acts as `p_to_FF(p,0)`. No checks.

GEN Fq_to_FF(GEN x, GEN ff) returns a t_FFELT equal to x in the finite field defined by the t_FFELT ff , where x is an Fq (either a t_INT or a ZX : a t_POL with t_INT coefficients). No checks.

GEN FqX_to_FFX(GEN x, GEN ff) given an FqX x , return the polynomial with t_FFELT coefficients obtained by applying `Fq_to_FF` coefficientwise. No checks, and no normalization if the leading coefficient maps to 0.

GEN FF_1(GEN a) returns the unity in the definition field of the t_FFELT element a .

GEN FF_zero(GEN a) returns the zero element of the definition field of the t_FFELT element a .

int FF_equal0(GEN a) returns 1 if the t_FFELT a is equal to 0 else returns 0.

int FF_equal1(GEN a) returns 1 if the t_FFELT a is equal to 1 else returns 0.

int FF_equalm1(GEN a) returns -1 if the t_FFELT a is equal to 1 else returns 0.

int FF_equal(GEN a, GEN b) return 1 if the t_FFELT a and b have the same definition field and are equal, else 0.

int FF_samefield(GEN a, GEN b) return 1 if the t_FFELT a and b have the same definition field, else 0.

int Rg_is_FF(GEN c, GEN *ff) to be called successively on many objects, setting $*ff = \text{NULL}$ (unset) initially. Returns 1 as long as c is a t_FFELT defined over the same field as $*ff$ (setting $*ff = c$ if unset), and 0 otherwise.

int RgC_is_FFC(GEN x, GEN *ff) apply `Rg_is_FF` successively to all components of the t_VEC or t_COL x . Return 0 if one call fails, and 1 otherwise.

int RgM_is_FFM(GEN x, GEN *ff) apply `Rg_is_FF` to all components of the t_MAT . Return 0 if one call fails, and 1 otherwise.

GEN FF_add(GEN a, GEN b) returns $a + b$ where a and b are t_FFELT having the same definition field.

GEN FF_Z_add(GEN a, GEN x) returns $a + x$, where a is a t_FFELT , and x is a t_INT , the computation being performed in the definition field of a .

GEN FF_Q_add(GEN a, GEN x) returns $a + x$, where a is a t_FFELT , and x is a t_RFRAC , the computation being performed in the definition field of a .

GEN FF_sub(GEN a, GEN b) returns $a - b$ where a and b are t_FFELT having the same definition field.

GEN `FF_mul`(GEN `a`, GEN `b`) returns ab where `a` and `b` are `t_FFELT` having the same definition field.

GEN `FF_Z_mul`(GEN `a`, GEN `b`) returns ab , where `a` is a `t_FFELT`, and `b` is a `t_INT`, the computation being performed in the definition field of `a`.

GEN `FF_div`(GEN `a`, GEN `b`) returns a/b where `a` and `b` are `t_FFELT` having the same definition field.

GEN `FF_neg`(GEN `a`) returns $-a$ where `a` is a `t_FFELT`.

GEN `FF_neg_i`(GEN `a`) shallow function returning $-a$ where `a` is a `t_FFELT`.

GEN `FF_inv`(GEN `a`) returns a^{-1} where `a` is a `t_FFELT`.

GEN `FF_sqr`(GEN `a`) returns a^2 where `a` is a `t_FFELT`.

GEN `FF_mul2n`(GEN `a`, long `n`) returns $a2^n$ where `a` is a `t_FFELT`.

GEN `FF_pow`(GEN `a`, GEN `n`) returns a^n where `a` is a `t_FFELT` and `n` is a `t_INT`.

GEN `FF_Frobenius`(GEN `a`, GEN `n`) returns x^{p^n} where `x` is the standard generator of the definition field of the `t_FFELT` element `a`, `t_FFELT`, `n` is a `t_INT`, and p is the characteristic of the definition field of `a`.

GEN `FF_Z_Z_muldiv`(GEN `a`, GEN `x`, GEN `y`) returns ay/z , where `a` is a `t_FFELT`, and `x` and `y` are `t_INT`, the computation being performed in the definition field of `a`.

GEN `Z_FF_div`(GEN `x`, GEN `a`) return x/a where `a` is a `t_FFELT`, and `x` is a `t_INT`, the computation being performed in the definition field of `a`.

GEN `FF_norm`(GEN `a`) returns the norm of the `t_FFELT` `a` with respect to its definition field.

GEN `FF_trace`(GEN `a`) returns the trace of the `t_FFELT` `a` with respect to its definition field.

GEN `FF_conjvec`(GEN `a`) returns the vector of conjugates $[a, a^p, a^{p^2}, \dots, a^{p^{n-1}}]$ where the `t_FFELT` `a` belong to a field with p^n elements.

GEN `FF_charpoly`(GEN `a`) returns the characteristic polynomial) of the `t_FFELT` `a` with respect to its definition field.

GEN `FF_minpoly`(GEN `a`) returns the minimal polynomial of the `t_FFELT` `a`.

GEN `FF_sqrt`(GEN `a`) returns an `t_FFELT` `b` such that $a = b^2$ if it exist, where `a` is a `t_FFELT`.

long `FF_issquareall`(GEN `x`, GEN `*pt`) returns 1 if `x` is a square, and 0 otherwise. If `x` is indeed a square, set `pt` to its square root.

long `FF_issquare`(GEN `x`) returns 1 if `x` is a square and 0 otherwise.

long `FF_ispower`(GEN `x`, GEN `K`, GEN `*pt`) Given K a positive integer, returns 1 if `x` is a K -th power, and 0 otherwise. If `x` is indeed a K -th power, set `pt` to its K -th root.

GEN `FF_sqrtn`(GEN `a`, GEN `n`, GEN `*zn`) returns an n -th root of `a` if it exist. If `zn` is non-NULL set it to a primitive n -th root of the unity.

GEN `FF_log`(GEN `a`, GEN `g`, GEN `o`) the `t_FFELT` `g` being a generator for the definition field of the `t_FFELT` `a`, returns a `t_INT` `e` such that $a^e = g$. If `e` does not exists, the result is currently undefined. If `o` is not NULL it is assumed to be a factorization of the multiplicative order of `g` (as set by `FF_primroot`)

GEN FF_order(GEN a, GEN o) returns the order of the t_FFELT a. If o is non-NULL, it is assumed that o is a multiple of the order of a.

GEN FF_primroot(GEN a, GEN *o) returns a generator of the multiplicative group of the definition field of the t_FFELT a. If o is not NULL, set it to the factorization of the order of the primitive root (to speed up FF_log).

GEN FF_map(GEN m, GEN a) returns $A(m)$ where $A=a.pol$ assuming a and m belongs to fields having the same characteristic.

10.8.1 FFX.

The functions in this sections take polynomial arguments and a t_FFELT a. The coefficients of the polynomials must be of type t_INT , t_INTMOD or t_FFELT and compatible with a.

GEN FFX_add(GEN P, GEN Q, GEN a) returns the sum of the polynomials P and Q defined over the definition field of the t_FFELT a.

GEN FFX_mul(GEN P, GEN Q, GEN a) returns the product of the polynomials P and Q defined over the definition field of the t_FFELT a.

GEN FFX_sqr(GEN P, GEN a) returns the square of the polynomial P defined over the definition field of the t_FFELT a.

GEN FFX_rem(GEN P, GEN Q, GEN a) returns the remainder of the polynomial P modulo the polynomial Q, where P and Q are defined over the definition field of the t_FFELT a.

GEN FFX_gcd(GEN P, GEN Q, GEN a) returns the GCD of the polynomials P and Q defined over the definition field of the t_FFELT a.

GEN FFX_extgcd(GEN P, GEN Q, GEN a, GEN *U, GEN *V) returns the GCD of the polynomials P and Q defined over the definition field of the t_FFELT a and sets *U, *V to the Bezout coefficients such that $*UP + *VQ = d$. If *U is set to NULL, it is not computed which is a bit faster.

GEN FFX_halfgcd(GEN x, GEN y, GEN a) returns a two-by-two matrix M with determinant ± 1 such that the image (A, B) of (x, y) by M has the property that $\deg A \geq \frac{\deg x}{2} > \deg B$.

GEN FFX_halfgcd_all(GEN x, GEN y, GEN a, GEN *ptA, GEN *ptB) as FFX_halfgcd, in addition, if ptA (resp. ptB) is not NULL, *ptA (resp. *ptB) is set to A (resp. B).

GEN FFX_resultant(GEN P, GEN Q, GEN a) returns the resultant of the polynomials P and Q where P and Q are defined over the definition field of the t_FFELT a.

GEN FFX_disc(GEN P, GEN a) returns the discriminant of the polynomial P where P is defined over the definition field of the t_FFELT a.

GEN FFX_isplayer(GEN P, ulong k, GEN a, GEN *py) return 1 if the FFX P is a k -th power, 0 otherwise, where P is defined over the definition field of the t_FFELT a. If py is not NULL, set it to g such that $g^k = f$.

GEN FFX_factor(GEN f, GEN a) returns the factorization of the univariate polynomial f over the definition field of the t_FFELT a. The coefficients of f must be of type t_INT , t_INTMOD or t_FFELT and compatible with a.

GEN FFX_factor_squarefree(GEN f, GEN a) returns the squarefree factorization of the univariate polynomial f over the definition field of the t_FFELT a. This is a vector $[u_1, \dots, u_k]$ of pairwise coprime FFX such that $u_k \neq 1$ and $f = \prod u_i$.

GEN FFX_ddf(GEN f, GEN a) assuming that f is squarefree, returns the distinct degree factorization of f modulo p . The returned value v is a `t_VEC` with two components: $F=v[1]$ is a vector of (FFX) factors, and $E=v[2]$ is a `t_VECSMALL`, such that f is equal to the product of the $F[i]$ and each $F[i]$ is a product of irreducible factors of degree $E[i]$.

GEN FFX_degfact(GEN f, GEN a), as FFX_factor, but the degrees of the irreducible factors are returned instead of the factors themselves (as a `t_VECSMALL`).

GEN FFX_roots(GEN f, GEN a) returns the roots (`t_FFELT`) of the univariate polynomial f over the definition field of the `t_FFELT` a . The coefficients of f must be of type `t_INT`, `t_INTMOD` or `t_FFELT` and compatible with a .

GEN FFX_preimagerel(GEN F, GEN x, GEN a) returns $P\%F$ where $P=x.pol$ assuming a and x belongs to fields having the same characteristic, and that the coefficients of F belong to the definition field of a .

GEN FFX_preimage(GEN F, GEN x, GEN a) as FFX_preimagerel but return NULL if the remainder is of degree greater or equal to 1, the constant coefficient otherwise.

GEN FFX_roots_to_pol(GEN V, GEN ff, long v) V being a vector over the finite field given by ff (`t_FFELT`), returns the monic `t_POL` $\prod_i (pol_x[v] - V[i])$.

10.8.2 FFM.

GEN FFM_FFC_gauss(GEN M, GEN C, GEN ff) given a matrix M (`t_MAT`) and a column vector C (`t_COL`) over the finite field given by ff (`t_FFELT`) such that M is invertible, return the unique column vector X such that $MX = C$.

GEN FFM_FFC_invimage(GEN M, GEN C, GEN ff) given a matrix M (`t_MAT`) and a column vector C (`t_COL`) over the finite field given by ff (`t_FFELT`), return a column vector X such that $MX = C$, or NULL if no such vector exists.

GEN FFM_FFC_mul(GEN M, GEN C, GEN ff) returns the product of the matrix M (`t_MAT`) and the column vector C (`t_COL`) over the finite field given by ff (`t_FFELT`).

GEN FFM_deplin(GEN M, GEN ff) returns a nonzero vector (`t_COL`) in the kernel of the matrix M over the finite field given by ff , or NULL if no such vector exists.

GEN FFM_det(GEN M, GEN ff) returns the determinant of the matrix M over the finite field given by ff .

GEN FFM_gauss(GEN M, GEN N, GEN ff) given two matrices M and N (`t_MAT`) over the finite field given by ff (`t_FFELT`) such that M is invertible, return the unique matrix X such that $MX = N$.

GEN FFM_image(GEN M, GEN ff) returns a matrix whose columns span the image of the matrix M over the finite field given by ff .

GEN FFM_indexrank(GEN M, GEN ff) given a matrix M of rank r over the finite field given by ff , returns a vector with two `t_VECSMALL` components y and z containing r row and column indices, respectively, such that the $r \times r$ -matrix formed by the $M[i, j]$ for i in y and j in z is invertible.

GEN FFM_inv(GEN M, GEN ff) returns the inverse of the square matrix M over the finite field given by ff , or NULL if M is not invertible.

GEN FFM_invimage(GEN M, GEN N, GEN ff) given two matrices M and N (`t_MAT`) over the finite field given by ff (`t_FFELT`), return a matrix X such that $MX = N$, or NULL if no such matrix exists.

`GEN FFM_ker(GEN M, GEN ff)` returns the kernel of the `t_MAT` `M` over the finite field given by the `t_FFELT` `ff`.

`GEN FFM_mul(GEN M, GEN N, GEN ff)` returns the product of the matrices `M` and `N` (`t_MAT`) over the finite field given by `ff` (`t_FFELT`).

`long FFM_rank(GEN M, GEN ff)` returns the rank of the matrix `M` over the finite field given by `ff`.

`GEN FFM_suppl(GEN M, GEN ff)` given a matrix `M` over the finite field given by `ff` whose columns are linearly independent, returns a square invertible matrix whose first columns are those of `M`.

10.8.3 FFXQ.

`GEN FFXQ_mul(GEN P, GEN Q, GEN T, GEN a)` returns the product of the polynomials `P` and `Q` modulo the polynomial `T`, where `P`, `Q` and `T` are defined over the definition field of the `t_FFELT` `a`.

`GEN FFXQ_sqr(GEN P, GEN T, GEN a)` returns the square of the polynomial `P` modulo the polynomial `T`, where `P` and `T` are defined over the definition field of the `t_FFELT` `a`.

`GEN FFXQ_inv(GEN P, GEN Q, GEN a)` returns the inverse of the polynomial `P` modulo the polynomial `Q`, where `P` and `Q` are defined over the definition field of the `t_FFELT` `a`.

`GEN FFXQ_minpoly(GEN Pf, GEN Qf, GEN a)` returns the minimal polynomial of the polynomial `P` modulo the polynomial `Q`, where `P` and `Q` are defined over the definition field of the `t_FFELT` `a`.

10.9 Transcendental functions.

The following two functions are only useful when interacting with `gp`, to manipulate its internal default precision (expressed as a number of decimal digits, not in words as used everywhere else):

`long getrealprecision(void)` returns `realprecision`.

`long setrealprecision(long n, long *prec)` sets the new `realprecision` to `n`, which is returned. As a side effect, set `prec` to the corresponding number of words `ndec2prec(n)`.

10.9.1 Transcendental functions with `t_REAL` arguments.

In the following routines, x is assumed to be a `t_REAL` and the result is a `t_REAL` (sometimes a `t_COMPLEX` with `t_REAL` components), with the largest accuracy which can be deduced from the input. The naming scheme is inconsistent here, since we sometimes use the prefix `mp` even though `t_INT` inputs are forbidden:

`GEN sqrtr(GEN x)` returns the square root of x .

`GEN cbrtr(GEN x)` returns the real cube root of x .

`GEN sqrtnr(GEN x, long n)` returns the n -th root of x , assuming $n \geq 1$ and $x \geq 0$.

`GEN sqrtnr_abs(GEN x, long n)` returns the n -th root of $|x|$, assuming $n \geq 1$ and $x \neq 0$.

`GEN mpcos[z](GEN x[, GEN z])` returns $\cos(x)$.

`GEN mpsin[z](GEN x[, GEN z])` returns $\sin(x)$.

`GEN mplog[z](GEN x[, GEN z])` returns $\log(x)$. We must have $x > 0$ since the result must be a `t_REAL`. Use `glog` for the general case, where you want such computations as $\log(-1) = I$.

`GEN mpexp[z](GEN x[, GEN z])` returns $\exp(x)$.

GEN `mpexpm1`(GEN `x`) returns $\exp(x) - 1$, but is more accurate than `subrs(mpexp(x), 1)`, which suffers from catastrophic cancellation if $|x|$ is very small.

void `mpsincosm1`(GEN `x`, GEN `*s`, GEN `*c`) sets `s` and `c` to $\sin(x)$ and $\cos(x) - 1$ respectively, where `x` is a `t_REAL`; the latter is more accurate than `subrs(mpcos(y), 1)`, which suffers from catastrophic cancellation if $|x|$ is very small.

GEN `mpveceint1`(GEN `C`, GEN `eC`, long `n`) as `veceint1`; assumes that $C > 0$ is a `t_REAL` and that `eC` is NULL or `mpexp(C)`.

GEN `mpeint1`(GEN `x`, GEN `expx`) returns `eint1(x)`, for a `t_REAL` $x \neq 0$, assuming that `expx` is `mpexp(x)`.

A few variants on the Lambert function: they actually work when `gtofp` can map all GEN arguments to a `t_REAL`.

GEN `mplambertW`(GEN `y`) solution $x = W_0(y)$ of the implicit equation $x \exp(x) = y$, for $y > -1/e$ a `t_REAL`.

GEN `mplambertx_logx`(GEN `a`, GEN `b`, long `bit`) solve $x - a \log(x) = b$ with $a > 0$ and $b \geq a(1 - \log(a))$.

GEN `mplambertX`(GEN `y`, long `bit`) as `mplambertx_logx` in the special case $a = 1, b = \log(y)$. In other words, solve $e^x/x = y$ with $y \geq e$.

GEN `mplambertxlogx_x`(GEN `a`, GEN `b`, long `bit`) solve $x \log(x) - ax = b$; if $b < 0$, assume $a \geq 1 + \log|b|$.

Useful low-level functions which *disregard* the sign of x :

GEN `sqrtr_abs`(GEN `x`) returns $\sqrt{|x|}$ assuming $x \neq 0$.

GEN `cbrtr_abs`(GEN `x`) returns $|x|^{1/3}$ assuming $x \neq 0$.

GEN `exp1r_abs`(GEN `x`) returns $\exp(|x|) - 1$, assuming $x \neq 0$.

GEN `logr_abs`(GEN `x`) returns $\log(|x|)$, assuming $x \neq 0$.

10.9.2 Other complex transcendental functions.

GEN `atanhuu`(ulong `u`, ulong `v`, long `prec`) computes $\operatorname{atanh}(u/v)$ using binary splitting, assuming $0 < u < v$. Not memory clean but suitable for `gerepileupto`. The complexity is $O(b/\log(v/u))$, where b is `prec2nbits(prec)`, so becomes impractical when v/u is too close to 1.

GEN `atanhui`(ulong `u`, GEN `v`, long `prec`) computes $\operatorname{atanh}(u/v)$ using binary splitting, assuming $0 < u < v$. Not memory clean but suitable for `gerepileupto`.

GEN `szeta`(long `s`, long `prec`) returns the value of Riemann's zeta function at the (possibly negative) integer $s \neq 1$, in relative accuracy `prec`.

GEN `veczeta`(GEN `a`, GEN `b`, long `N`, long `prec`) returns in a vector all the $\zeta(aj + b)$, where $j = 0, 1, \dots, N - 1$, where a and b are real numbers (of arbitrary type, although `t_INT` is treated more efficiently). Assumes that $N \geq 1, b > 1$ and $a(N - 1) + b > 1$ (in case $a < 0$); the silly case $a = 0$ is wasteful but allowed.

GEN `ggamma1m1`(GEN `x`, long `prec`) return $\Gamma(1 + x) - 1$ assuming $|x| < 1$. Guard against cancellation when x is small.

A few variants on sin and cos:

`void mpsincos(GEN x, GEN *s, GEN *c)` sets s and c to $\sin(x)$ and $\cos(x)$ respectively, where x is a `t_REAL`

`void mpsinhcosh(GEN x, GEN *s, GEN *c)` sets s and c to $\sinh(x)$ and $\cosh(x)$ respectively, where x is a `t_REAL`

`GEN expIrr(GEN x)` returns $\exp(ix)$, where x is a `t_REAL`. The return type is `t_COMPLEX` unless the imaginary part is equal to 0 to the current accuracy (its sign is 0).

`GEN expIPiR(GEN x, long prec)` return $\exp(i\pi x)$, where x is a real number (`t_INT`, `t_FRAC` or `t_REAL`).

`GEN expIPiC(GEN z, long prec)` return $\exp(i\pi x)$, where x is a complex number (`t_INT`, `t_FRAC`, `t_REAL` or `t_COMPLEX`).

`GEN expIxy(GEN x, GEN y, long prec)` returns $\exp(ixy)$. Efficient when x is real and y pure imaginary.

`GEN pow2Pis(GEN s, long prec)` returns $(2\pi)^s$. The intent of this function and the next ones is to be accurate even if s has a huge imaginary part: π is computed at an accuracy taking into account the cancellation induced by argument reduction when computing the sine or cosine of $\Im s \log 2\pi$.

`GEN powPis(GEN s, long prec)` returns π^s , as `pow2Pis`.

`long powcx_prec(long e, GEN s, long prec)` if $e \approx \log_2 |x|$ return the precision at which $\log(x)$ must be computed to evaluate x^s reliably (taking into account argument reduction).

`GEN powcx(GEN x, GEN logx, GEN s, long prec)` assuming s is a `t_COMPLEX` and `logx` is $\log(x)$ computed to accuracy `powcx_prec`, return x^s .

`void gsincos(GEN x, GEN *s, GEN *c, long prec)` general case.

`GEN rootsof1_cx(GEN d, long prec)` return $e(1/d)$ at precision `prec`, $e(x) = \exp(2i\pi x)$.

`GEN rootsof1u_cx(ulong d, long prec)` return $e(1/d)$ at precision `prec`.

`GEN rootsof1q_cx(long a, long b, long prec)` return $e(a/b)$ at precision `prec`.

`GEN rootsof1powinit(long a, long b, long prec)` precompute b -th roots of 1 for `rootsof1pow`, i.e. to later compute $e(ac/b)$ for varying c .

`GEN rootsof1pow(GEN T, long c)` given $T = \text{rootsof1powinit}(a, b, \text{prec})$, return $e(ac/b)$.

A generalization of `affrr_fixlg`

`GEN affc_fixlg(GEN x, GEN res)` assume `res` was allocated using `cgetc`, and that x is either a `t_REAL` or a `t_COMPLEX` with `t_REAL` components. Assign x to `res`, first shortening the components of `res` if needed (in a gerepile-safe way). Further convert `res` to a `t_REAL` if x is a `t_REAL`.

`GEN trans_eval(const char *fun, GEN (*f)(GEN, long), GEN x, long prec)` evaluate the transcendental function f (named "fun" at the argument x and precision `prec`). This is a quick way to implement a transcendental function to be made available under GP, starting from a C function handling only `t_REAL` and `t_COMPLEX` arguments. This routine first converts x to a suitable type:

- `t_INT/t_FRAC` to `t_REAL` of precision `prec`, `t_QUAD` to `t_REAL` or `t_COMPLEX` of precision `prec`.

- `t_POLMOD` to a `t_COL` of complex embeddings (as in `conjvec`)

Then evaluates the function at `t_VEC`, `t_COL`, `t_MAT` arguments coefficientwise.

GEN `trans_evalgen(const char *fun, void *E, GEN (*f)(void*, GEN, long), GEN x, long prec)`, general variant evaluating $f(E, x, prec)$, where the function prototype allows to wrap an arbitrary context given by the argument E .

10.9.3 Modular functions.

GEN `cxredsl2(GEN z, GEN *g)` given t a `t_COMPLEX` belonging to the upper half-plane, find $\gamma \in \mathrm{SL}_2(\mathbf{Z})$ such that $\gamma \cdot z$ belongs to the standard fundamental domain and set $*g$ to γ .

GEN `cxredsl2_i(GEN z, GEN *g, GEN *czd)` as `cxredsl2`; also sets $*czd$ to $cz+d$, if $\gamma = [a, b; c, d]$.

GEN `cxEk(GEN tau, long k, long prec)` returns $E_k(\tau)$ by direct evaluation of $1 + 2/\zeta(1-k) \sum_n n^{k-1} q^n / (1 - q^n)$, $q = e(\tau)$. Assume that $\Im \tau > 0$ and k even. Very slow unless τ is already reduced modulo $\mathrm{SL}_2(\mathbf{Z})$. Not `gerepile`-clean but suitable for `gerepileupto`.

10.9.4 Transcendental functions with `t_PADIC` arguments.

The argument x is assumed to be a `t_PADIC`.

GEN `Qp_exp(GEN x)` shortcut for `gexp(x, /*ignored*/prec)`

long `Qp_exp_prec(GEN x)` number of terms to sum in the $\exp(x)$ series to reach the same p -adic accuracy as $x \neq 0$. If $n = p - 1$, $e = v_p(x)$ and $b = \text{prec}(x)$, this is the ceiling of $nb/(ne - 1)$. Return -1 if the series does not converge ($ne \leq 1$).

GEN `Qp_gamma(GEN x)` shortcut for `ggamma(x, /*ignored*/prec)`

GEN `Qp_zeta(GEN x)` shortcut for `gzeta(x, /*ignored*/prec)`; assume that $x \neq 1$.

GEN `Qp_zetahurwitz(GEN x, GEN y, long k)` shortcut for `zetahurwitz(x, y, k, /*ignored*/prec)`.

GEN `Qp_psi(GEN x)` shortcut for `gpsi(x, /*ignored*/prec)`.

GEN `Qp_log(GEN x)` shortcut for `glog(x, /*ignored*/prec)`.

GEN `Qp_sqrt(GEN x)` shortcut for `gsqrt(x, /*ignored*/prec)` Return NULL if x is not a square.

GEN `Qp_sqrtn(GEN x, GEN n, GEN *z)` shortcut for `gsqrtn(x, n, z, /*ignored*/prec)`. Return NULL if x is not an n -th power.

GEN `Qp_agm2_sequence(GEN a1, GEN b1)` assume $a_1/b_1 = 1 \bmod p$ if p odd and $\bmod 2^4$ if $p = 2$. Let $A_1 = a_1/p^v$ and $B_1 = b_1/p^v$ with $v = v_p(a_1) = v_p(b_1)$; let further $A_{n+1} = (A_n + B_n + 2B_{n+1})/4$, $B_{n+1} = B_n \sqrt{A_n/B_n}$ (the square root of $A_n B_n$ congruent to $B_n \bmod p$) and $R_n = p^v(A_n - B_n)$. We stop when R_n is 0 at the given p -adic accuracy. This function returns in a triplet `t_VEC` the three sequences (A_n) , (B_n) and (R_n) , corresponding to a sequence of 2-isogenies on the Tate curve $y^2 = x(x - a_1)(x + a_1 - b_1)$. The common limit of A_n and B_n is the $M_2(a_1, b_1)$, the square of the p -adic AGM of $\sqrt{a_1}$ and $\sqrt{b_1}$. This is given by `ellQp_Ei` and is used by corresponding ascending and descending p -adic Landen transforms:

void `Qp_ascending_Landen(GEN ABR, GEN *ptx, GEN *pty)`

void `Qp_descending_Landen(GEN ABR, GEN *ptx, GEN *pty)`

10.9.5 Cached constants.

The cached constant is returned at its current precision, which may be larger than `prec`. One should always use the `mpxxx` variant: `mppi`, `mpeuler`, or `mplog2`.

GEN `consteuler(long prec)` precomputes Euler-Mascheroni's constant at precision `prec`.

GEN `constcatalan(long prec)` precomputes Catalan's constant at precision `prec`.

GEN `constpi(long prec)` precomputes π at precision `prec`.

GEN `constlog2(long prec)` precomputes $\log(2)$ at precision `prec`.

void `constbern(long n)` precomputes the n even Bernoulli numbers B_2, \dots, B_{2n} as `t_FRAC`. No more than n Bernoulli numbers will ever be stored (by `bernfrac` or `bernreal`), unless a subsequent call to `constbern` increases the cache.

GEN `constzeta(long n, long prec)` ensures that the n values $\gamma, \zeta(2), \dots, \zeta(n)$ are cached at accuracy bigger than or equal to `prec` and return a vector containing at least those value. Note that $\gamma = \lim_1 \zeta(s) - 1/(s-1)$. If the accuracy of cached data is too low or n is greater than the cache length, the cache is recomputed at the given parameters.

The following functions use cached data if `prec` is smaller than the precision of the cached value; otherwise the newly computed data replaces the old cache.

GEN `mppi(long prec)` returns π at precision `prec`.

GEN `Pi2n(long n, long prec)` returns $2^n \pi$ at precision `prec`.

GEN `PiI2(long n, long prec)` returns the complex number $2\pi i$ at precision `prec`.

GEN `PiI2n(long n, long prec)` returns the complex number $2^n \pi i$ at precision `prec`.

GEN `mpeuler(long prec)` returns Euler-Mascheroni's constant at precision `prec`.

GEN `mpeuler(long prec)` returns Catalan's number at precision `prec`.

GEN `mplog2(long prec)` returns $\log 2$ at precision `prec`.

The following functions use the Bernoulli numbers cache initialized by `constbern`:

GEN `bernreal(long i, long prec)` returns the Bernoulli number B_i as a `t_REAL` at precision `prec`. If `constbern(n)` was called previously with $n \geq i$, then the cached value is (converted to a `t_REAL` of accuracy `prec` then) returned. Otherwise, the missing value is computed; the cache is not updated.

GEN `bernfrac(long i)` returns the Bernoulli number B_i as a rational number (`t_FRAC` or `t_INT`). If the `constbern` cache includes B_i , the latter is returned. Otherwise, the missing value is computed; the cache is not updated.

10.9.6 Obsolete functions.

void `mpbern(long n, long prec)`

10.10 Permutations .

Permutations are represented in two different ways

- (perm) a `t_VECSMALL` p representing the bijection $i \mapsto p[i]$; unless mentioned otherwise, this is the form used in the functions below for both input and output,

- (cyc) a `t_VEC` of `t_VECSMALL`s representing a product of disjoint cycles.

`GEN identity_perm(long n)` return the identity permutation on n symbols.

`GEN cyclic_perm(long n, long d)` return the cyclic permutation mapping i to $i + d \pmod{n}$ in S_n . Assume that $d \leq n$.

`GEN perm_mul(GEN s, GEN t)` multiply s and t (composition $s \circ t$)

`GEN perm_sqr(GEN s)` multiply s by itself (composition $s \circ s$)

`GEN perm_conj(GEN s, GEN t)` return sts^{-1} .

`int perm_commute(GEN p, GEN q)` return 1 if p and q commute, 0 otherwise.

`GEN perm_inv(GEN p)` returns the inverse of p .

`GEN perm_pow(GEN p, GEN n)` returns p^n

`GEN perm_powu(GEN p, ulong n)` returns p^n

`GEN cyc_pow_perm(GEN p, long n)` the permutation p is given as a product of disjoint cycles (cyc); return p^n (as a perm).

`GEN cyc_pow(GEN p, long n)` the permutation p is given as a product of disjoint cycles (cyc); return p^n (as a cyc).

`GEN perm_cycles(GEN p)` return the cyclic decomposition of p .

`GEN perm_order(GEN p)` returns the order of the permutation p (as the lcm of its cycle lengths).

`ulong perm_orderu(GEN p)` returns the order of the permutation p (as the lcm of its cycle lengths) assuming it fits in a `ulong`.

`long perm_sign(GEN p)` returns the sign of the permutation p .

`GEN vecperm_orbits(GEN gen, long n)` return the orbits of $\{1, 2, \dots, n\}$ under the action of the subgroup of S_n generated by gen .

`GEN Z_to_perm(long n, GEN x)` as `numtoperm`, returning a `t_VECSMALL`.

`GEN perm_to_Z(GEN v)` as `permtonum` for a `t_VECSMALL` input.

`GEN perm_to_GAP(GEN p)` return a `t_STR` which is a representation of p compatible with the GAP computer algebra system.

10.11 Small groups.

The small (finite) groups facility is meant to deal with subgroups of Galois groups obtained by `galoisinit` and thus is currently limited to weakly super-solvable groups.

A group *grp* of order *n* is represented by its regular representation (for an arbitrary ordering of its element) in S_n . A subgroup of such group is represented by the restriction of the representation to the subgroup. A *small group* can be either a group or a subgroup. Thus it is embedded in some S_n , where *n* is the multiple of the order. Such an *n* is called the *domain* of the small group. The domain of a trivial subgroup cannot be derived from the subgroup data, so some functions require the subgroup domain as argument.

The small group *grp* is represented by a `t_VEC` with two components:

grp[1] is a generating subset $[s_1, \dots, s_g]$ of *grp* expressed as a vector of permutations of length *n*.

grp[2] contains the relative orders $[o_1, \dots, o_g]$ of the generators *grp*[1].

See `galoisinit` for the technical details.

`GEN checkgroup(GEN gal, GEN *elts)` check whether *gal* is a small group or a Galois group. Returns the underlying small group and set *elts* to the list of elements or to NULL if it is not known.

`GEN checkgroupelts(GEN gal)` check whether *gal* is a small group or a Galois group, or a vector of permutations listing the group elements. Returns the list of group elements as permutations.

`GEN galois_group(GEN gal)` return the underlying small group of the Galois group *gal*.

`GEN cyclicgroup(GEN g, long s)` return the cyclic group with generator *g* of order *s*.

`GEN trivialgroup(void)` return the trivial group.

`GEN dicyclicgroup(GEN g1, GEN g2, long s1, long s2)` returns the group with generators *g1*, *g2* with respecting relative orders *s1*, *s2*.

`GEN abelian_group(GEN v)` let *v* be a `t_VECSMALL` seen as the SNF of a small abelian group, return its regular representation.

`long group_domain(GEN grp)` returns the domain of the *nontrivial* small group *grp*. Return an error if *grp* is trivial.

`GEN group_elts(GEN grp, long n)` returns the list of elements of the small group *grp* of domain *n* as permutations.

`GEN groupeelts_to_group(GEN elts)`, where *elts* is the list of elements of a group, returns the corresponding small group, if it exists, otherwise return NULL.

`GEN group_set(GEN grp, long n)` returns a $F2v$ *b* such that *b*[*i*] is set if and only if the small group *grp* of domain *n* contains a permutation sending 1 to *i*.

`GEN groupeelts_set(GEN elts, long n)`, where *elts* is the list of elements of a small group of domain *n*, returns a $F2v$ *b* such that *b*[*i*] is set if and only if the small group contains a permutation sending 1 to *i*.

`GEN groupeelts_conj_set(GEN elts, GEN p)`, where *elts* is the list of elements of a small group of domain *n*, returns a $F2v$ *b* such that *b*[*i*] is set if and only if the small group contains a permutation sending $p^{-1}[1]$ to $p^{-1}[i]$.

`int group_subgroup_is_faithful(GEN G, GEN H)` return 1 if the action of G on G/H by translation is faithful, 0 otherwise.

`GEN groupelts_conjclasses(GEN elts, long *pn)`, where $elts$ is the list of elements of a small group (sorted with respect to `vecsmall_lexcmp`), return a `t_VECSMALL conj` of the same length such that `conj[i]` is the index in $\{1, \dots, n\}$ of the conjugacy class of `elts[i]` for some unspecified but deterministic ordering of the classes, where n is the number of conjugacy classes. If `pn` is non NULL, `*pn` is set to n .

`GEN conjclasses_repr(GEN conj, long nb)`, where `conj` and `nb` are as returned by the call `groupelts_conjclasses(elts)`, return `t_VECSMALL` of length `nb` which gives the indices in `elts` of a representative of each conjugacy class.

`GEN group_to_cc(GEN G)`, where G is a small group or a Galois group, returns a `cc` (conjugacy classes) structure `[elts,conj,rep,flag]`, as obtained by `alggroupcenter`, where `conj` is `groupelts_conjclasses(elts)` and `rep` is the attached `conjclasses_repr`. `flag` is 1 if the permutation representation is transitive (in which case an element g of G is characterized by $g[1]$), and 0 otherwise. Shallow function.

`long group_order(GEN grp)` returns the order of the small group grp (which is the product of the relative orders).

`long group_isabelian(GEN grp)` returns 1 if the small group grp is Abelian, else 0.

`GEN group_abelianHNF(GEN grp, GEN elts)` if grp is not Abelian, returns NULL, else returns the HNF matrix of grp with respect to the generating family $grp[1]$. If $elts$ is no NULL, it must be the list of elements of grp .

`GEN group_abelianSNF(GEN grp, GEN elts)` if grp is not Abelian, returns NULL, else returns its cyclic decomposition. If $elts$ is no NULL, it must be the list of elements of grp .

`long group_subgroup_isnormal(GEN G, GEN H)`, H being a subgroup of the small group G , returns 1 if H is normal in G , else 0.

`long group_isA4S4(GEN grp)` returns 1 if the small group grp is isomorphic to A_4 , 2 if it is isomorphic to S_4 , 3 if it is isomorphic to $(3 \times 3) : 4$ and 0 else. This is mainly to deal with the idiosyncrasy of the format.

`GEN group_leftcoset(GEN G, GEN g)` where G is a small group and g a permutation of the same domain, the left coset gG as a vector of permutations.

`GEN group_rightcoset(GEN G, GEN g)` where G is a small group and g a permutation of the same domain, the right coset Gg as a vector of permutations.

`long group_perm_normalize(GEN G, GEN g)` where G is a small group and g a permutation of the same domain, return 1 if $gGg^{-1} = G$, else 0.

`GEN group_quotient(GEN G, GEN H)`, where G is a small group and H is a subgroup of G , returns the quotient map $G \rightarrow G/H$ as an abstract data structure.

`GEN groupelts_quotient(GEN elts, GEN H)`, where $elts$ is the list of elements of a small group G , H is a subgroup of G , returns the quotient map $G \rightarrow G/H$ as an abstract data structure.

`GEN quotient_perm(GEN C, GEN g)` where C is the quotient map $G \rightarrow G/H$ for some subgroup H of G and g an element of G , return the image of g by C (i.e. the coset gH).

GEN `quotient_group`(GEN `C`, GEN `G`) where C is the quotient map $G \rightarrow G/H$ for some *normal* subgroup H of G , return the quotient group G/H as a small group.

GEN `quotient_grouplets`(GEN `C`) where C is the quotient map $G \rightarrow G/H$ for some group G and some *normal* subgroup H of G , return the list of elements of the quotient group G/H (as permutations over corresponding to the regular representation).

GEN `quotient_subgroup_lift`(GEN `C`, GEN `H`, GEN `S`) where C is the quotient map $G \rightarrow G/H$ for some group G normalizing H and S is a subgroup of G/H , return the inverse image of S by C .

GEN `group_subgroups`(GEN `grp`) returns the list of subgroups of the small group `grp` as a `t_VEC`.

GEN `grouplets_solvable_subgroups`(GEN `elts`) where `elts` is the list of elements of a finite group, returns the list of its solvable subgroups, each as a list of its elements.

GEN `subgroups_tableset`(GEN `S`, long `n`) where S is a vector of subgroups of domain n , returns a table which matches the set of elements of the subgroups against the index of the subgroups.

long `tableset_find_index`(GEN `tbl`, GEN `set`) searches the set `set` in the table `tbl` and returns its attached index, or 0 if not found.

GEN `grouplets_abelian_group`(GEN `elts`) where `elts` is the list of elements of an *Abelian* small group, returns the corresponding small group.

long `grouplets_exponent`(GEN `elts`) where `elts` is the list of elements of a small group, returns the exponent the group (the LCM of the order of the elements of the group).

GEN `grouplets_center`(GEN `elts`) where `elts` is the list of elements of a small group, returns the list of elements of the center of the group.

GEN `group_export`(GEN `grp`, long `format`) convert a small group to another format, as a `t_STR` describing the group for the given syntax, see `galoisexport`.

GEN `group_export_GAP`(GEN `G`) export a small group to GAP format.

GEN `group_export_MAGMA`(GEN `G`) export a small group to MAGMA format.

long `group_ident`(GEN `grp`, GEN `elts`) returns the index of the small group `grp` in the GAP4 Small Group library, see `galoisidentify`. If `elts` is not NULL, it must be the list of elements of `grp`.

long `group_ident_trans`(GEN `grp`, GEN `elts`) returns the index of the regular representation of the small group `grp` in the GAP4 Transitive Group library, see `polgalois`. If `elts` is no NULL, it must be the list of elements of `grp`.

Chapter 11:

Standard data structures

11.1 Character strings.

11.1.1 Functions returning a char *.

`char* pari_strdup(const char *s)` returns a malloc'ed copy of *s* (uses `pari_malloc`).

`char* pari_strndup(const char *s, long n)` returns a malloc'ed copy of at most *n* chars from *s* (uses `pari_malloc`). If *s* is longer than *n*, only *n* characters are copied and a terminal null byte is added.

`char* stack_strdup(const char *s)` returns a copy of *s*, allocated on the PARI stack (uses `stack_malloc`).

`char* stack_strcat(const char *s, const char *t)` returns the concatenation of *s* and *t*, allocated on the PARI stack (uses `stack_malloc`).

`char* stack_sprintf(const char *fmt, ...)` runs `pari_sprintf` on the given arguments, returning a string allocated on the PARI stack.

`char* uordinal(ulong x)` return the ordinal number attached to *x* (i.e. 1st, 2nd, etc.) as a `stack_malloc`'ed string.

`char* itostr(GEN x)` writes the `t_INT` *x* to a `stack_malloc`'ed string.

`char* GENTostr(GEN x)`, using the current default output format (`GP_DATA->fmt`, which contains the output style and the number of significant digits to print), converts *x* to a malloc'ed string. Simple variant of `pari_sprintf`.

`char* GENTostr_raw(GEN x)` as `GENTostr` with the following differences: 1) the output format is `f_RAW`; 2) the result is allocated on the stack and *must not* be freed.

`char* GENTostr_unquoted(GEN x)` as `GENTostr_raw` with the following additional difference: a `t_STR` *x* is printed without enclosing quotes (to be used by `print`).

`char* GENToTeXstr(GEN x)`, as `GENTostr`, except that `f_TEX` overrides the output format from `GP_DATA->fmt`.

`char* RgV_to_str(GEN g, long flag)` *g* being a vector of GENs, returns a malloc'ed string, the concatenation of the `GENTostr` applied to its elements, except that `t_STR` are printed without enclosing quotes. `flag` determines the output format: `f_RAW`, `f_PRETTYMAT` or `f_TEX`.

11.1.2 Functions returning a `t_STR`.

`GEN strtogenstr(const char *s)` returns a `t_STR` with content `s`.

`GEN strntogenstr(const char *s, long n)` returns a `t_STR` containing the first `n` characters of `s`.

`GEN chartogenstr(char c)` returns a `t_STR` containing the character `c`.

`GEN GENTogenstr(GEN x)` returns a `t_STR` containing the printed form of `x` (in `raw` format). This is often easier to use than `GENTostr` (which returns a malloc'ed `char*`) since there is no need to free the string after use.

`GEN GENTogenstr_nospace(GEN x)` as `GENTogenstr`, removing all spaces from the output.

`GEN Str(GEN g)` as `RgV_to_str` with output format `f_RAW`, but returns a `t_STR`, not a malloc'ed string.

`GEN strtex(GEN g)` as `RgV_to_str` with output format `f_TEX`, but returns a `t_STR`, not a malloc'ed string.

`GEN strexpend(GEN g)` as `RgV_to_str` with output format `f_RAW`, performing tilde and environment expansion on the result. Returns a `t_STR`, not a malloc'ed string.

`GEN gsprintf(const char *fmt, ...)` equivalent to `pari_sprintf(fmt, ...)`, followed by `strtogenstr`. Returns a `t_STR`, not a malloc'ed string.

`GEN gvsprintf(const char *fmt, va_list ap)` variadic version of `gsprintf`

`GEN pari_base64(const char *s)` convert the string to base64 (RFC4648 "+" "/" with padding).

11.1.3 Dynamic strings.

A `pari_str` is a dynamic string which grows dynamically as needed. This structure contains private data and two public members `char *string`, which is the string itself and `use_stack` which tells whether the string lives

- on the PARI stack (value 1), meaning that it will be destroyed by any manipulation of the stack, e.g. a `gerepile` call or resetting `avma`;
- in malloc'ed memory (value 0), in which case it is impervious to stack manipulation but will need to be explicitly freed by the user after use, via `pari_free(s.string)`.

`void str_init(pari_str *S, int use_stack)` initializes a dynamic string; if `use_stack` is 0, then the string is malloc'ed, else it lives on the PARI stack.

`void str_printf(pari_str *S, const char *fmt, ...)` write to the end of `S` the remaining arguments according to PARI format `fmt`.

`void str_putc(pari_str *S, char c)` write the character `c` to the end of `S`.

`void str_puts(pari_str *S, const char *s)` write the string `s` to the end of `S`.

11.2 Output.

11.2.1 Output contexts.

An output context, of type `PariOUT`, is a `struct` that models a stream and contains the following function pointers:

```
void (*putch)(char);          /* fputc()-alike */
void (*puts)(const char*);    /* fputs()-alike */
void (*flush)(void);          /* fflush()-alike */
```

The methods `putch` and `puts` are used to print a character or a string respectively. The method `flush` is called to finalize a messages.

The generic functions `pari_putc`, `pari_puts`, `pari_flush` and `pari_printf` print according to a *default output context*, which should be sufficient for most purposes. Lower level functions are available, which take an explicit output context as first argument:

`void out_putc(PariOUT *out, char c)` essentially equivalent to `out->putc(c)`. In addition, registers whether the last character printed was a `\n`.

`void out_puts(PariOUT *out, const char *s)` essentially equivalent to `out->puts(s)`. In addition, registers whether the last character printed was a `\n`.

`void out_printf(PariOUT *out, const char *fmt, ...)`

`void out_vprintf(PariOUT *out, const char *fmt, va_list ap)`

N.B. The function `out_flush` does not exist since it would be identical to `out->flush()`

`int pari_last_was_newline(void)` returns a nonzero value if the last character printed via `out_putc` or `out_puts` was `\n`, and 0 otherwise.

`void pari_set_last_newline(int last)` sets the boolean value to be returned by the function `pari_last_was_newline` to *last*.

11.2.2 Default output context. They are defined by the global variables `pariOut` and `pariErr` for normal outputs and warnings/errors, and you probably do not want to change them. If you *do* change them, diverting output in nontrivial ways, this probably means that you are rewriting `gp`. For completeness, we document in this section what the default output contexts do.

pariOut. writes output to the `FILE*` `pari_outfile`, initialized to `stdout`. The low-level methods are actually the standard `putc` / `fputs`, plus some magic to handle a log file if one is open.

pariErr. prints to the `FILE*` `pari_errfile`, initialized to `stderr`. The low-level methods are as above.

You can stick with the default `pariOut` output context and change PARI's standard output, redirecting `pari_outfile` to another file, using

`void switchout(const char *name)` where `name` is a character string giving the name of the file you want to write to; the output is *appended* at the end of the file. To close the file and revert to outputting to `stdout`, call `switchout(NULL)`.

11.2.3 PARI colors. In this section we describe the low-level functions used to implement GP's color scheme, attached to the `colors` default. The following symbolic names are attached to gp's output strings:

- `c_ERR` an error message
- `c_HIST` a history number (as in `%1 = ...`)
- `c_PROMPT` a prompt
- `c_INPUT` an input line (minus the prompt part)
- `c_OUTPUT` an output
- `c_HELP` a help message
- `c_TIME` a timer
- `c_NONE` everything else

If the `colors` default is set to a nonempty value, before gp outputs a string, it first outputs an ANSI colors escape sequence — understood by most terminals —, according to the `colors` specifications. As long as this is in effect, the following strings are rendered in color, possibly in bold or underlined.

`void term_color(long c)` prints (as if using `pari_puts`) the ANSI color escape sequence attached to output object `c`. If `c` is `c_NONE`, revert to default printing style.

`void out_term_color(PariOUT *out, long c)` as `term_color`, using output context `out`.

`char* term_get_color(char *s, long c)` returns as a character string the ANSI color escape sequence attached to output object `c`. If `c` is `c_NONE`, the value used to revert to default printing style is returned. The argument `s` is either `NULL` (string allocated on the PARI stack), or preallocated storage (in which case, it must be able to hold at least 16 chars, including the final `\0`).

11.2.4 Obsolete output functions.

These variants of `void output(GEN x)`, which prints `x`, followed by a newline and a buffer flush are complicated to use and less flexible than what we saw above, or than the `pari_printf` variants. They are provided for backward compatibility and are scheduled to disappear.

`void brute(GEN x, char format, long dec)`

`void matbrute(GEN x, char format, long dec)`

`void texe(GEN x, char format, long dec)`

11.3 Files.

The following routines are trivial wrappers around system functions (possibly around one of several functions depending on availability). They are usually integrated within PARI's diagnostics system, printing messages if the debug level for "files" is high enough.

`int pari_is_dir(const char *name)` returns 1 if `name` points to a directory, 0 otherwise.

`int pari_is_file(const char *name)` returns 1 if `name` points to a file, 0 otherwise.

`int file_is_binary(FILE *f)` returns 1 if the file `f` is a binary file (in the `writebin` sense), 0 otherwise.

`void pari_unlink(const char *s)` deletes the file named `s`. Warn if the operation fails.

`void pari_fread_chars(void *b, size_t n, FILE *f)` read `n` chars from stream `f`, storing the result in pre-allocated buffer `b` (assumed to be large enough).

`char* path_expand(const char *s)` perform tilde and environment expansion on `s`. Returns a malloc'ed buffer.

`void strftime_expand(const char *s, char *buf, long max)` perform time expansion on `s`, storing the result (at most `max` chars) in buffer `buf`. Trivial wrapper around

```
time_t t = time(NULL);
strftime(buf, max, s, localtime(&t));
```

`char* pari_get_homedir(const char *user)` expands `~user` constructs, returning the home directory of user `user`, or NULL if it could not be determined (in particular if the operating system has no such concept). The return value may point to static area and may be overwritten by subsequent system calls: use immediately or `strdup` it.

`int pari_stdin_isatty(void)` returns 1 if our standard input `stdin` is attached to a terminal. Trivial wrapper around `isatty`.

11.3.1 pariFILE.

PARI maintains a linked list of open files, to reclaim resources (file descriptors) on error or interrupts. The corresponding data structure is a `pariFILE`, which is a wrapper around a standard `FILE*`, containing further the file name, its type (regular file, pipe, input or output file, etc.). The following functions create and manipulate this structure; they are integrated within PARI's diagnostics system, printing messages if the debug level for "files" is high enough.

`pariFILE* pari_fopen(const char *s, const char *mode)` wrapper around `fopen(s, mode)`, return NULL on failure.

`pariFILE* pari_fopen_or_fail(const char *s, const char *mode)` simple wrapper around `fopen(s, mode)`; error on failure.

`pariFILE* pari_fopengz(const char *s)` opens the file whose name is `s`, and associates a (read-only) `pariFILE` with it. If `s` is a compressed file (`.gz` suffix), it is uncompressed on the fly. If `s` cannot be opened, also try to open `s.gz`. Returns NULL on failure.

`void pari_fclose(pariFILE *f)` closes the underlying file descriptor and deletes the `pariFILE` struct.

`pariFILE* pari_safeopen(const char *s, const char *mode)` creates a *new* file `s` (a priori for writing) with 600 permissions. Error if the file already exists. To avoid symlink attacks, a symbolic link exists, regardless of where it points to.

11.3.2 Temporary files.

PARI has its own idea of the system temp directory derived from an environment variable (\$GPTMPDIR, else \$TMPDIR), or the first writable directory among /tmp, /var/tmp and ..

`char* pari_unique_dir(const char *s)` creates a “unique directory” and return its name built from the string *s*, the user id and process pid (on Unix systems). This directory is itself located in the temp directory mentioned above. The name returned is malloc’ed.

`char* pari_unique_filename(const char *s)` creates a *new* empty file in the temp directory, whose name contains the id-string *s* (truncated to its first 8 chars), followed by a system-dependent suffix (incorporating the ids of both the user and the running process, for instance). The function returns the tempfile name and creates an empty file with that name. The name returned is malloc’ed.

`char* pari_unique_filename_suffix(const char *s, const char *suf)` analogous to above `pari_unique_filename`, creating a (previously nonexistent) tempfile whose name ends with suffix *suf*.

11.4 Errors.

This section documents the various error classes, and the corresponding arguments to `pari_err`. The general syntax is

```
void pari_err(numerr, ...)
```

In the sequel, we mostly use sequences of arguments of the form

```
const char *s
const char *fmt, ...
```

where *fmt* is a PARI format, producing a string *s* from the remaining arguments. Since providing the correct arguments to `pari_err` is quite error-prone, we also provide specialized routines `pari_err_ERRORCLASS(...)` instead of `pari_err(e_ERRORCLASS, ...)` so that the C compiler can check their arguments.

We now inspect the list of valid keywords (error classes) for `numerr`, and the corresponding required arguments.

11.4.1 Internal errors, “system” errors.

11.4.1.1 e_ARCH. A requested feature *s* is not available on this architecture or operating system.

```
pari_err(e_ARCH)
```

prints the error message: `sorry, 's' not available on this system.`

11.4.1.2 e_BUG. A bug in the PARI library, in function *s*.

```
pari_err(e_BUG, const char *s)
pari_err_BUG(const char *s)
```

prints the error message: `Bug in s, please report.`

11.4.1.3 e_FILE. Error while trying to open a file.

```
pari_err(e_FILE, const char *what, const char *name)
pari_err_FILE(const char *what, const char *name)
```

prints the error message: error opening *what*: '*name*'.

11.4.1.4 e_FILEDESC. Error while handling a file descriptor.

```
pari_err(e_FILEDESC, const char *where, long n)
pari_err_FILEDESC(const char *where, long n)
```

prints the error message: invalid file descriptor in *where*: '*name*'.

11.4.1.5 e_IMPL. A requested feature *s* is not implemented.

```
pari_err(e_IMPL, const char *s)
pari_err_IMPL(const char *s)
```

prints the error message: sorry, *s* is not yet implemented.

11.4.1.6 e_PACKAGE. Missing optional package *s*.

```
pari_err(e_PACKAGE, const char *s)
pari_err_PACKAGE(const char *s)
```

prints the error message: package *s* is required, please install it

11.4.2 Syntax errors, type errors.

11.4.2.1 e_DIM. arguments submitted to function *s* have inconsistent dimensions. E.g., when solving a linear system, or trying to compute the determinant of a nonsquare matrix.

```
pari_err(e_DIM, const char *s)
pari_err_DIM(const char *s)
```

prints the error message: inconsistent dimensions in *s*.

11.4.2.2 e_FLAG. A flag argument is out of bounds in function *s*.

```
pari_err(e_FLAG, const char *s)
pari_err_FLAG(const char *s)
```

prints the error message: invalid flag in *s*.

11.4.2.3 e_NOTFUNC. Generated by the PARI evaluator; tried to use a GEN which is not a `t_CLOSURE` in a function call syntax (as in `f = 1; f(2);`).

```
pari_err(e_NOTFUNC, GEN fun)
```

prints the error message: not a function in a function call.

11.4.2.4 e_OP. Impossible operation between two objects than cannot be typecast to a sensible common domain for deeper reasons than a type mismatch, usually for arithmetic reasons. As in $0(2) + 0(3)$: it is valid to add two `t_PADICs`, provided the underlying prime is the same; so the addition is not forbidden a priori for type reasons, it only becomes so when inspecting the objects and trying to perform the operation.

```
pari_err(e_OP, const char *op, GEN x, GEN y)
pari_err_OP(const char *op, GEN x, GEN y)
```

As `e_TYPE2`, replacing forbidden by inconsistent.

11.4.2.5 e_PRIORITY. object o in function s contains variables whose priority is incompatible with the expected operation. E.g. `Pol([x,1], 'y')`: this raises an error because it's not possible to create a polynomial whose coefficients involve variables with higher priority than the main variable.

```
pari_err(e_PRIORITY, const char *s, GEN o, const char *op, long v)
pari_err_PRIORITY(const char *s, GEN o, const char *op, long v)
```

prints the error message: `incorrect priority in s, variable v_o op v , where v_o is gvar(o).`

11.4.2.6 e_SYNTAX. Syntax error, generated by the PARI parser.

```
pari_err(e_SYNTAX, const char *msg, const char *e, const char *entry)
```

where `msg` is a complete error message, and `e` and `entry` point into the *same* character string, which is the input that was incorrectly parsed: `e` points to the character where the parser failed, and `entry` \leq `e` points somewhat before.

Prints the error message: `msg`, followed by a colon, then a part of the input character string (in general `entry` itself, but an initial segment may be truncated if `e - entry` is large); a caret points at `e`, indicating where the error took place.

11.4.2.7 e_TYPE. An argument x of function s had an unexpected type. (As in `factor("blah").`)

```
pari_err(e_TYPE, const char *s, GEN x)
pari_err_TYPE(const char *s, GEN x)
```

prints the error message: `incorrect type in s (t_x)`, where t_x is the type of x .

11.4.2.8 e_TYPE2. Forbidden operation between two objects than cannot be typecast to a sensible common domain, because their types do not match up. (As in `Mod(1,2) + Pi.`)

```
pari_err(e_TYPE2, const char *op, GEN x, GEN y)
pari_err_TYPE2(const char *op, GEN x, GEN y)
```

prints the error message: `forbidden $s\ t_x\ op\ t_y$` , where t_z denotes the type of z . Here, s denotes the spelled out name of the operator $op \in \{+, *, /, \%, =\}$, e.g. *addition* for "+" or *assignment* for "=". If op is not in the above operator, list, it is taken to be the already spelled out name of a function, e.g. "gcd", and the error message becomes `forbidden $op\ t_x, t_y$` .

11.4.2.9 e_VAR. polynomials x and y submitted to function s have inconsistent variables. E.g., considering the algebraic number `Mod(t,t^2+1)` in `nfinite(x^2+1)`.

```
pari_err(e_VAR, const char *s, GEN x, GEN y)
pari_err_VAR(const char *s, GEN x, GEN y)
```

prints the error message: `inconsistent variables in s $X \neq Y$` , where X and Y are the names of the variables of x and y , respectively.

11.4.3 Overflows.

11.4.3.1 e_COMPONENT. Trying to access an inexistent component of a vector/matrix/list: the index is less than 1 or greater than the allowed length.

```
pari_err(e_COMPONENT, const char *f, const char *op, GEN lim, GEN x)
pari_err_COMPONENT(const char *f, const char *op, GEN lim, GEN x)
```

prints the error message: `nonexistent component in f: index op lim`. Special case: if f is the empty string (no meaningful public function name can be used), we ignore it and print the message: `nonexistent component: index op lim`.

11.4.3.2 e_DOMAIN. An argument x is not in the function's domain (as in `moebius(0)` or `zeta(1)`).

```
pari_err(e_DOMAIN, char *f, char *v, char *op, GEN lim, GEN x)
pari_err_DOMAIN(char *f, char *v, char *op, GEN lim, GEN x)
```

prints the error message: `domain error in f: v op lim`. Special case: if `op` is the empty string, we ignore `lim` and print the error message: `domain error in f: v out of range`.

11.4.3.3 e_MAXPRIME. A function using the precomputed list of prime numbers ran out of primes.

```
pari_err(e_MAXPRIME, ulong c)
pari_err_MAXPRIME(ulong c)
```

prints the error message: `not enough precomputed primes, need primelimit ~c if c is nonzero`. And simply `not enough precomputed primes` otherwise.

11.4.3.4 e_MEM. A call to `pari_malloc` or `pari_realloc` failed.

```
pari_err(e_MEM)
```

prints the error message: `not enough memory`.

11.4.3.5 e_OVERFLOW. An object in function s becomes too large to be represented within PARI's hardcoded limits. (As in `2^2^2^10` or `exp(1e100)`, which overflow in `lg` and `expo`.)

```
pari_err(e_OVERFLOW, const char *s)
pari_err_OVERFLOW(const char *s)
```

prints the error message: `overflow in s`.

11.4.3.6 e_PREC. Function s fails because input accuracy is too low. (As in `floor(1e100)` at default accuracy.)

```
pari_err(e_PREC, const char *s)
pari_err_PREC(const char *s)
```

prints the error message: `precision too low in s`.

11.4.3.7 e_STACK. The PARI stack overflows.

```
pari_err(e_STACK)
```

prints the error message: `the PARI stack overflows !` as well as some statistics concerning stack usage.

11.4.4 Errors triggered intentionally.

11.4.4.1 e_ALARM. A timeout, generated by the `alarm` function.

```
pari_err(e_ALARM, const char *fmt, ...)
```

prints the error message: `s`.

11.4.4.2 e_USER. A user error, as triggered by `error(g_1, \dots, g_n)` in GP.

```
pari_err(e_USER, GEN g)
```

prints the error message: `user error:`, then the entries of the vector g .

11.4.5 Mathematical errors.

11.4.5.1 e_CONSTPOL. An argument of function s is a constant polynomial, which does not make sense. (As in `galoisinit(Pol(1))`.)

```
pari_err(e_CONSTPOL, const char *s)
pari_err_CONSTPOL(const char *s)
```

prints the error message: `constant polynomial in s`.

11.4.5.2 e_COPRIME. Function s expected two coprime arguments, and did receive x, y which were not.

```
pari_err(e_COPRIME, const char *s, GEN x, GEN y)
pari_err_COPRIME(const char *s, GEN x, GEN y)
```

prints the error message: `elements not coprime in s: x,y`.

11.4.5.3 e_INV. Tried to invert a noninvertible object x .

```
pari_err(e_INV, const char *s, GEN x)
pari_err_INV(const char *s, GEN x)
```

prints the error message: `impossible inverse in s: x`. If $x = \text{Mod}(a, b)$ is a `t_INTMOD` and a is not 0 mod b , this allows to factor the modulus, as $\text{gcd}(a, b)$ is a nontrivial divisor of b .

11.4.5.4 e_IRREDPOL. Function s expected an irreducible polynomial, and did not receive one. (As in `nfinit(x^2-1)`.)

```
pari_err(e_IRREDPOL, const char *s, GEN x)
pari_err_IRREDPOL(const char *s, GEN x)
```

prints the error message: `not an irreducible polynomial in s: x`.

11.4.5.5 e_MISC. Generic uncategorized error.

```
pari_err(e_MISC, const char *fmt, ...)
```

prints the error message: `s`.

11.4.5.6 e_MODULUS. moduli x and y submitted to function s are inconsistent. E.g., considering the algebraic number $\text{Mod}(t, t^2+1)$ in `nfinit(t^3-2)`.

```
pari_err(e_MODULUS, const char *s, GEN x, GEN y)
pari_err_MODULUS(const char *s, GEN x, GEN y)
```

prints the error message: `inconsistent moduli in s, then the moduli`.

11.4.5.7 e_PRIME. Function s expected a prime number, and did receive p , which was not. (As in `idealprimedec(nf, 4)`.)

```
pari_err(e_PRIME, const char *s, GEN x)
pari_err_PRIME(const char *s, GEN x)
```

prints the error message: `not a prime in s: x`.

11.4.5.8 e_ROOTS0. An argument of function *s* is a zero polynomial, and we need to consider its roots. (As in `polroots(0)`.)

```
pari_err(e_ROOTS0, const char *s)
pari_err_ROOTS0(const char *s)
```

prints the error message: zero polynomial in *s*.

11.4.5.9 e_SQRTN. Tried to compute an *n*-th root of *x*, which does not exist, in function *s*. (As in `sqrt(Mod(-1,3))`.)

```
pari_err(e_SQRTN, GEN x)
pari_err_SQRTN(GEN x)
```

prints the error message: not an *n*-th power residue in *s*: *x*.

11.4.6 Miscellaneous functions.

`long name_numerr(const char *s)` return the error number corresponding to an error name. E.g. `name_numerr("e_DIM")` returns `e_DIM`.

`const char* numerr_name(long errnum)` returns the error name corresponding to an error number. E.g. `name_numerr(e_DIM)` returns `"e_DIM"`.

`char* pari_err2str(GEN err)` returns the error message that would be printed on `t_ERROR err`. The name is allocated on the PARI stack and must not be freed.

`int pari_err_display(GEN err)` displays the error message corresponding to `err`. Always return 0. Default value of the callback `cb_pari_err_handle`.

11.5 Hashtables.

A **hashtable**, or associative array, is a set of pairs (k, v) of keys and values. PARI implements general extensible hashtables for fast data retrieval: when creating a table, we may either choose to use the PARI stack, or `malloc` so as to be stack-independent. A hashtable is implemented as a table of linked lists, each list containing all entries sharing the same hash value. The table length is a prime number, which roughly doubles as the table overflows by gaining new entries; both the current number of entries and the threshold before the table grows are stored in the table. Finally the table remembers the functions used to hash the entries's keys and to test for equality two entries hashed to the same value.

An entry, or **hashentry**, contains

- a key/value pair (k, v) , both of type `void*` for maximal flexibility,
- the hash value of the key, for the table hash function. This hash is mapped to a table index (by reduction modulo the table length), but it contains more information, and is used to bypass costly general equality tests if possible,
- a link pointer to the next entry sharing the same table cell.

```
typedef struct {
    void *key, *val;
    ulong hash; /* hash(key) */
    struct hashentry *next;
```

```

} hashentry;

typedef struct {
    ulong len; /* table length */
    hashentry **table; /* the table */
    ulong nb, maxnb; /* number of entries stored and max nb before enlarging */
    ulong pindex; /* prime index */
    ulong (*hash) (void *k); /* hash function */
    int (*eq) (void *k1, void *k2); /* equality test */
    int use_stack; /* use the PARI stack, resp. malloc */
} hashtable;

```

```
hashtable* hash_create(size, hash, eq, use_stack)
```

```

    ulong size;
    ulong (*hash)(void*);
    int (*eq)(void*,void*);
    int use_stack;

```

creates a hashtable with enough room to contain `size` entries. The functions `hash` and `eq` compute the hash value of keys and test keys for equality, respectively. If `use_stack` is non zero, the resulting table will use the PARI stack; otherwise, we use `malloc`.

`hashtable* hash_create_ulong(ulong size, long stack)` special case when the keys are `ulong`s with ordinary equality test.

`hashtable* hash_create_str(ulong size, long stack)` special case when the keys are character strings with string equality test (and `hash_str` hash function).

`void hash_init(hashtable *h, ulong size, ulong (*hash)(void*), int (*eq)(void*, void*), use_stack)` Initialize `h` for an hashtable with enough room to contain `size` entries of type `void*`. The functions `eq` test keys for equality. If `use_stack` is non zero, the resulting table will use the PARI stack; otherwise, we use `malloc`.

`void hash_init_GEN(hashtable *h, ulong size, int (*eq)(GEN, GEN), use_stack)` Initialize `h` for an hashtable with enough room to contain `size` entries of type `GEN`. The functions `eq` test keys for equality. If `use_stack` is non zero, the resulting table will use the PARI stack; otherwise, we use `malloc`. The hash used is `hash_GEN`.

`void hash_init_ulong(hashtable *h, ulong size, use_stack)` Initialize `h` for an hashtable with enough room to contain `size` entries of type `ulong`. If `use_stack` is non zero, the resulting table will use the PARI stack; otherwise, we use `malloc`.

`void hash_insert(hashtable *h, void *k, void *v)` inserts (k, v) in hashtable `h`. No copy is made: `k` and `v` themselves are stored. The implementation does not prevent one to insert two entries with equal keys `k`, but which of the two is affected by later commands is undefined.

`void hash_insert2(hashtable *h, void *k, void *v, ulong hash)` as `hash_insert`, assuming `h->hash(k)` is `hash`.

`void hash_insert_long(hashtable *h, void *k, long v)` as `hash_insert` but `v` is a `long`.

`hashentry* hash_search(hashtable *h, void *k)` look for an entry with key `k` in `h`. Return it if it one exists, and `NULL` if not.

hashentry* hash_search2(hashtable *h, void *k, ulong hash) as hash_search assuming $h \rightarrow \text{hash}(k)$ is hash.

GEN hash_haskey_GEN(hashtable *h, void *k) returns the associate value if the key k belongs to the hash, otherwise returns NULL.

int hash_haskey_long(hashtable *h, void *k, long *v) returns 1 if the key k belongs to the hash and set v to its value, otherwise returns 0.

hashentry * hash_select(hashtable *h, void *k, void *E, int (*select)(void *, hashentry *)) variant of hash_search, useful when entries with identical keys are inserted: among the entries attached to key k , return one satisfying the selection criterion (such that $\text{select}(E, e)$ is nonzero), or NULL if none exist.

hashentry* hash_remove(hashtable *h, void *k) deletes an entry (k, v) with key k from h and return it. (Return NULL if none was found.) Only the linking structures are freed, memory attached to k and v is not reclaimed.

hashentry* hash_remove_select(hashtable *h, void *k, void *E, int(*select)(void *, hashentry *)) a variant of hash_remove, useful when entries with identical keys are inserted: among the entries attached to key k , return one satisfying the selection criterion (such that $\text{select}(E, e)$ is nonzero) and delete it, or NULL if none exist. Only the linking structures are freed, memory attached to k and v is not reclaimed.

GEN hash_keys(hashtable *h) return in a t_VECSMALL the keys stored in hashtable h .

GEN hash_keys_GEN(hashtable *h) return in a t_VEC the keys stored in hashtable h (which are assumed to be GENs).

GEN hash_values(hashtable *h) return in a t_VECSMALL the values stored in hashtable h .

void hash_destroy(hashtable *h) deletes the hashtable, by removing all entries.

void hash_dbg(hashtable *h) print statistics for hashtable h , allows to evaluate the attached hash function performance on actual data.

Some interesting hash functions are available:

ulong hash_str(const char *s)

ulong hash_str_len(const char *s, long len) hash the prefix string containing the first len characters (assume $\text{strlen}(s) \geq \text{len}$).

ulong hash_GEN(GEN x) generic hash function.

ulong hash_zv(GEN x) hash a t_VECSMALL.

11.6 Dynamic arrays.

A **dynamic array** is a generic way to manage stacks of data that need to grow dynamically. It allocates memory using `pari_malloc`, and is independent of the PARI stack; it even works before the `pari_init` call.

11.6.1 Initialization.

To create a stack of objects of type `foo`, we proceed as follows:

```
foo *t_foo;
pari_stack s_foo;
pari_stack_init(&s_foo, sizeof(*t_foo), (void**)&t_foo);
```

Think of `s_foo` as the controlling interface, and `t_foo` as the (dynamic) array tied to it. The value of `t_foo` may be changed as you add more elements.

11.6.2 Adding elements. The following function pushes an element on the stack.

```
/* access globals t_foo and s_foo */
void push_foo(foo x)
{
    long n = pari_stack_new(&s_foo);
    t_foo[n] = x;
}
```

11.6.3 Accessing elements.

Elements are accessed naturally through the `t_foo` pointer. For example this function swaps two elements:

```
void swapfoo(long a, long b)
{
    foo x;
    if (a > s_foo.n || b > s_foo.n) pari_err_BUG("swapfoo");
    x = t_foo[a];
    t_foo[a] = t_foo[b];
    t_foo[b] = x;
}
```

11.6.4 Stack of stacks. Changing the address of `t_foo` is not supported in general. In particular `realloc()`'ed array of stacks and stack of stacks are not supported.

11.6.5 Public interface. Let `s` be a `pari_stack` and `data` the data linked to it. The following public fields are defined:

- `s.alloc` is the number of elements allocated for `data`.
- `s.n` is the number of elements in the stack and `data[s.n-1]` is the topmost element of the stack. `s.n` can be changed as long as $0 \leq s.n \leq s.alloc$ holds.

`void pari_stack_init(pari_stack *s, size_t size, void **data)` links `*s` to the data pointer `*data`, where `size` is the size of data element. The pointer `*data` is set to `NULL`, `s->n` and `s->alloc` are set to 0: the array is empty.

`void pari_stack_alloc(pari_stack *s, long nb)` makes room for `nb` more elements, i.e. makes sure that $s.alloc \geq s.n + nb$, possibly reallocating `data`.

`long pari_stack_new(pari_stack *s)` increases `s.n` by one unit, possibly reallocating `data`, and returns `s.n - 1`.

Caveat. The following construction is incorrect because `stack_new` can change the value of `t_foo`:

```
t_foo[ pari_stack_new(&s_foo) ] = x;
```

`void pari_stack_delete(pari_stack *s)` frees `data` and resets the stack to the state immediately following `stack_init` (`s->n` and `s->alloc` are set to 0).

`void * pari_stack_pushp(pari_stack *s, void *u)` This function assumes that `*data` is of pointer type. Pushes the element `u` on the stack `s`.

`void ** pari_stack_base(pari_stack *s)` returns the address of `data`, typecast to a `void **`.

11.7 Vectors and Matrices.

11.7.1 Access and extract. See Section 9.3.1 and Section 9.3.2 for various useful constructors. Coefficients are accessed and set using `gel`, `gcoeff`, see Section 5.2.7. There are many internal functions to extract or manipulate subvectors or submatrices but, like the accessors above, none of them are suitable for `gerepileupto`. Worse, there are no type verification, nor bound checking, so use at your own risk.

`GEN shallowcopy(GEN x)` returns a `GEN` whose components are the components of `x` (no copy is made). The result may now be used to compute in place without destroying `x`. This is essentially equivalent to

```
GEN y = cgetg(lg(x), typ(x));
for (i = 1; i < lg(x); i++) y[i] = x[i];
return y;
```

except that `t_MAT` is treated specially since shallow copies of all columns are made. The function also works for nonrecursive types, but is useless in that case since it makes a deep copy. If `x` is known to be a `t_MAT`, you may call `RgM_shallowcopy` directly; if `x` is known not to be a `t_MAT`, you may call `leafcopy` directly.

`GEN RgM_shallowcopy(GEN x)` returns `shallowcopy(x)`, where `x` is a `t_MAT`.

`GEN shallowtrans(GEN x)` returns the transpose of `x`, *without* copying its components, i. e., it returns a `GEN` whose components are (physically) the components of `x`. This is the internal function underlying `gtrans`.

GEN `shallowconcat`(GEN x , GEN y) concatenate x and y , *without* copying components, i. e., it returns a GEN whose components are (physically) the components of x and y .

GEN `shallowconcat1`(GEN x) x must be `t_VEC`, `t_COL` or `t_LIST`, concatenate its elements from left to right. Shallow version of `gconcat1`.

GEN `shallowmatconcat`(GEN v) shallow version of `matconcat`.

GEN `shallowextract`(GEN x , GEN y) extract components of the vector or matrix x according to the selection parameter y . This is the shallow analog of `extract0(x, y, NULL)`, see `vecextract`.

GEN `RgV_F2v_extract_shallow`(GEN V , GEN x) extract components of the vector V whose indices corresponds to non-zero components of x . Shallow function.

GEN `shallowmatextract`(GEN M , GEN $l1$, GEN $l2$) extract components of the matrix M according to the `t_VECSMALL` $l1$ (list of lines indices) and $l2$ (list of columns indices). This is the shallow analog of `extract0(x, l1, l2)`, see `vecextract`.

GEN `RgM_minor`(GEN A , long i , long j) given a square `t_MAT` A , return the matrix with i -th row and j -th column removed.

GEN `vconcat`(GEN A , GEN B) concatenate vertically the two `t_MAT` A and B of compatible dimensions. A NULL pointer is accepted for an empty matrix. See `shallowconcat`.

GEN `matslice`(GEN A , long a , long b , long c , long d) returns the submatrix $A[a..b, c..d]$. Assume $a \leq b$ and $c \leq d$.

GEN `row`(GEN A , long i) return $A[i,]$, the i -th row of the `t_MAT` A .

GEN `row_i`(GEN A , long i , long $j1$, long $j2$) return part of the i -th row of `t_MAT` A : $A[i, j1], A[i, j1 + 1] \dots, A[i, j2]$. Assume $j1 \leq j2$.

GEN `rowcopy`(GEN A , long i) return the row $A[i,]$ of the `t_MAT` A . This function is memory clean and suitable for `gerepileupto`. See `row` for the shallow equivalent.

GEN `rowslice`(GEN A , long $i1$, long $i2$) return the `t_MAT` formed by the $i1$ -th through $i2$ -th rows of `t_MAT` A . Assume $i1 \leq i2$.

GEN `rowsplice`(GEN A , long i) return the `t_MAT` formed from the coefficients of `t_MAT` A with i -th row removed.

GEN `rowpermute`(GEN A , GEN p), p being a `t_VECSMALL` representing a list $[p_1, \dots, p_n]$ of rows of `t_MAT` A , returns the matrix whose rows are $A[p_1,], \dots, A[p_n,]$.

GEN `rowslicepermute`(GEN A , GEN p , long $x1$, long $x2$), short for

`rowslice(rowpermute(A, p), x1, x2)`

(more efficient).

GEN `vecslice`(GEN A , long $j1$, long $j2$), return $A[j1], \dots, A[j2]$. If A is a `t_MAT`, these correspond to *columns* of A . The object returned has the same type as A (`t_VECSMALL`, `t_VEC`, `t_COL` or `t_MAT`). Assume $j1 \leq j2$ or $j2 = j1 - 1$ (return empty vector/matrix).

GEN `vecsplice`(GEN A , long j) return A with j -th entry removed (`t_VEC`, `t_COL`) or j -th column removed (`t_MAT`).

GEN `veclast`(GEN A) return the last entry of A (`t_VEC`, `t_COL`) or last column of A (`t_MAT`). Shallow, undefined if `lg(A)` is 1.

GEN `vecreverse`(GEN `A`). Returns a GEN which has the same type as `A` (`t_VEC`, `t_COL` or `t_MAT`), and whose components are the $A[n], \dots, A[1]$. If `A` is a `t_MAT`, these are the *columns* of `A`.

void `vecreverse_inplace`(GEN `A`) as `vecreverse`, but reverse `A` in place.

GEN `vecpermute`(GEN `A`, GEN `p`) `p` is a `t_VECSMALL` representing a list $[p_1, \dots, p_n]$ of indices. Returns a GEN which has the same type as `A` (`t_VEC`, `t_COL` or `t_MAT`), and whose components are $A[p_1], \dots, A[p_n]$. If `A` is a `t_MAT`, these are the *columns* of `A`.

GEN `vecsmallpermute`(GEN `A`, GEN `p`) as `vecpermute` when `A` is a `t_VECSMALL`.

GEN `vecslicepermute`(GEN `A`, GEN `p`, long `y1`, long `y2`) short for

`vecslice(vecpermute(A,p), y1, y2)`

(more efficient).

11.7.2 Componentwise operations.

The following convenience routines automate trivial loops of the form

for (`i` = 1; `i` < `lg(a)`; `i`++) `gel(v,i)` = `f(gel(a,i), gel(b,i))`

for suitable `f`:

GEN `vecinv`(GEN `a`). Given a vector `a`, returns the vector whose i -th component is `ginv(a[i])`.

GEN `vecmul`(GEN `a`, GEN `b`). Given `a` and `b` two vectors of the same length, returns the vector whose i -th component is `gmul(a[i], b[i])`.

GEN `vecdiv`(GEN `a`, GEN `b`). Given `a` and `b` two vectors of the same length, returns the vector whose i -th component is `gdiv(a[i], b[i])`.

GEN `vecsqr`(GEN `a`) returns the vector whose i -th component is `gsqr(a[i])`.

GEN `vecpow`(GEN `a`, GEN `n`). Given `n` a `t_INT`, returns the vector whose i -th component is $a[i]^n$.

GEN `vecmodii`(GEN `a`, GEN `b`). Assuming `a` and `b` are two ZV of the same length, returns the vector whose i -th component is `modii(a[i], b[i])`.

GEN `vecmoduu`(GEN `a`, GEN `b`). Assuming `a` and `b` are two `t_VECSMALL` of the same length, returns the vector whose i -th component is $a[i] \% b[i]$.

Note that `vecadd` or `vecsub` do not exist since `gadd` and `gsub` have the expected behavior. On the other hand, `ginv` does not accept vector types, hence `vecinv`.

11.7.3 Low-level vectors and columns functions.

These functions handle `t_VEC` as an abstract container type of GENs. No specific meaning is attached to the content. They accept both `t_VEC` and `t_COL` as input, but `col` functions always return `t_COL` and `vec` functions always return `t_VEC`.

Note. All the functions below are shallow.

GEN `const_col(long n, GEN x)` returns a `t_COL` of `n` components equal to `x`.

GEN `const_vec(long n, GEN x)` returns a `t_VEC` of `n` components equal to `x`.

int `vec_isconst(GEN v)` Returns 1 if all the components of `v` are equal, else returns 0.

void `vec_setconst(GEN v, GEN x)` `v` a pre-existing vector. Set all its components to `x`.

int `vec_is1to1(GEN v)` Returns 1 if the components of `v` are pair-wise distinct, i.e. if $i \mapsto v[i]$ is a 1-to-1 mapping, else returns 0.

GEN `vec_append(GEN V, GEN s)` append `s` to the vector `V`.

GEN `vec_prepend(GEN V, GEN s)` prepend `s` to the vector `V`.

GEN `vec_shorten(GEN v, long n)` shortens the vector `v` to `n` components.

GEN `vec_lengthen(GEN v, long n)` lengthens the vector `v` to `n` components. The extra components are not initialized.

GEN `vec_insert(GEN v, long n, GEN x)` inserts `x` at position `n` in the vector `v`.

GEN `vec_equiv(GEN O)` given a vector of objects `O`, return a vector with `n` components where `n` is the number of distinct objects in `O`. The i -th component is a `t_VECSMALL` containing the indices of the elements in `O` having the same value. Applied to the image of a function evaluated on some finite set, it computes the fibers of the function.

GEN `vec_reduce(GEN O, GEN *pE)` given a vector of objects `O`, return the vector `v` (of the same type as `O`) of *distinct* elements of `O` and set a `t_VECSMALL` `E` with the same length as `v`, such that `E[i]` is the multiplicity of object `v[i]` in the original `O`. Shallow function.

11.8 Vectors of small integers.

11.8.1 t_VECSMALL.

These functions handle `t_VECSMALL` as an abstract container type of small signed integers. No specific meaning is attached to the content.

GEN `const_vecsmall(long n, long c)` returns a `t_VECSMALL` of `n` components equal to `c`.

GEN `vec_to_vecsmall(GEN z)` identical to `ZV_to_zv(z)`.

GEN `vecsmall_to_vec(GEN z)` identical to `zv_to_ZV(z)`.

GEN `vecsmall_to_col(GEN z)` identical to `zv_to_ZC(z)`.

GEN `vecsmall_to_vec_inplace(GEN z)` apply `stoi` to all entries of `z` and set its type to `t_VEC`.

GEN `vecsmall_copy(GEN x)` makes a copy of `x` on the stack.

GEN `vecsmall_shorten(GEN v, long n)` shortens the `t_VECSMALL` `v` to `n` components.

GEN `vecsmall_lengthen(GEN v, long n)` lengthens the `t_VECSMALL` `v` to `n` components. The extra components are not initialized.

GEN `vecsmall_indexsort(GEN x)` performs an indirect sort of the components of the `t_VECSMALL` `x` and return a permutation stored in a `t_VECSMALL` (merge sort).

`void vecsmall_sort(GEN v)` sorts the `t_VECSMALL v` in place (merge sort).

`GEN vecsmall_reverse(GEN v)` as `vecreverse` for a `t_VECSMALL v`.

`long vecsmall_max(GEN v)` returns the maximum of the elements of `t_VECSMALL v`, assumed nonempty.

`long vecsmall_indexmax(GEN v)` returns the index of the largest element of `t_VECSMALL v`, assumed nonempty.

`long vecsmall_min(GEN v)` returns the minimum of the elements of `t_VECSMALL v`, assumed nonempty.

`long vecsmall_indexmin(GEN v)` returns the index of the smallest element of `t_VECSMALL v`, assumed nonempty.

`int vecsmall_isconst(GEN v)` Returns 1 if all the components of `v` are equal, else returns 0.

`int vecsmall_is1to1(GEN v)` Returns 1 if the components of `v` are pair-wise distinct, i.e. if $i \mapsto v[i]$ is a 1-to-1 mapping, else returns 0.

`long vecsmall_isin(GEN v, long x)` returns the first index i such that $v[i]$ is equal to x . Naive search in linear time, does not assume that `v` is sorted.

`GEN vecsmall_uniq(GEN v)` given a `t_VECSMALL v`, return the vector of unique occurrences.

`GEN vecsmall_uniq_sorted(GEN v)` same as `vecsmall_uniq`, but assumes `v` sorted.

`long vecsmall_duplicate(GEN v)` given a `t_VECSMALL v`, return 0 if there is no duplicates, or the index of the first duplicate (`vecsmall_duplicate([1,1])` returns 2).

`long vecsmall_duplicate_sorted(GEN v)` same as `vecsmall_duplicate`, but assume `v` sorted.

`int vecsmall_lexcmp(GEN x, GEN y)` compares two `t_VECSMALL` lexically.

`int vecsmall_prefixcmp(GEN x, GEN y)` truncate the longest `t_VECSMALL` to the length of the shortest and compares them lexicographically.

`GEN vecsmall_prepend(GEN V, long s)` prepend `s` to the `t_VECSMALL V`.

`GEN vecsmall_append(GEN V, long s)` append `s` to the `t_VECSMALL V`.

`GEN vecsmall_concat(GEN u, GEN v)` concat the `t_VECSMALL u` and `v`.

`long vecsmall_coincidence(GEN u, GEN v)` returns the numbers of indices where `u` and `v` agree.

`long vecsmall_pack(GEN v, long base, long mod)` handles the `t_VECSMALL v` as the digit of a number in base `base` and return this number modulo `mod`. This can be used as an hash function.

`GEN vecsmall_prod(GEN v)` given a `t_VECSMALL v`, return the product of its entries.

The following sorting functions assume all entries of the `t_VECSMALL v` satisfy $0 \leq v[i] \leq M$ and use a counting sort, in linear time $O(\#v + M)$:

`void vecsmall_counting_sort(GEN v, long M)` sorts the `t_VECSMALL v` in place.

`GEN vecsmall_counting_indexsort(GEN v, long M)` as `vecsmall_indexsort` using a counting sort.

`GEN vecsmall_counting_uniq(GEN v, long M)` as `vecsmall_uniq` using a counting sort.

11.8.2 Vectors of `t_VECSMALL`. These functions manipulate vectors of `t_VECSMALL` (`vecvecsmall`).

`GEN vecvecsmall_sort(GEN x)` sorts lexicographically the components of the vector `x`.

`GEN vecvecsmall_sort_shallow(GEN x)`, shallow variant of `vecvecsmall_sort`.

`void vecvecsmall_sort_inplace(GEN x, GEN *perm)` sort lexicographically `x` in place, without copying its components. If `perm` is not `NULL`, it is set to the permutation that would sort the original `x`.

`GEN vecvecsmall_sort_uniq(GEN x)` sorts lexicographically the components of the vector `x`, removing duplicates entries.

`GEN vecvecsmall_indexsort(GEN x)` performs an indirect lexicographic sorting of the components of the vector `x` and return a permutation stored in a `t_VECSMALL`.

`long vecvecsmall_search(GEN x, GEN y)` `x` being a sorted `vecvecsmall` and `y` a `t_VECSMALL`, search `y` inside `x`.

`GEN vecvecsmall_max(GEN x)` returns the largest entry in all $x[i]$, assumed nonempty. Shallow function.

Chapter 12:

Functions related to the GP interpreter

12.1 Handling closures.

12.1.1 Functions to evaluate `t_CLOSURE`.

`void closure_disassemble(GEN C)` print the `t_CLOSURE` `C` in GP assembly format.

`GEN closure_callgenall(GEN C, long n, ...)` evaluate the `t_CLOSURE` `C` with the `n` arguments (of type `GEN`) following `n` in the function call. Assumes `C` has arity $\geq n$.

`GEN closure_callgenvec(GEN C, GEN args)` evaluate the `t_CLOSURE` `C` with the arguments supplied in the vector `args`. Assumes `C` has arity $\geq \lg(\text{args}) - 1$.

`GEN closure_callgenvecprec(GEN C, GEN args, long prec)` as `closure_callgenvec` but set the precision locally to `prec`.

`GEN closure_callgenvecdef(GEN C, GEN args, GEN def)` evaluate the `t_CLOSURE` `C` with the arguments supplied in the vector `args`, where the `t_VECSMALL` `def` indicates which arguments are actually present. Assumes `C` has arity $\geq \lg(\text{args}) - 1$.

`GEN closure_callgenvecdefprec(GEN C, GEN args, GEN def, long prec)` as `closure_callgenvecdef` but set the precision locally to `prec`.

`GEN closure_callgen0(GEN C, long prec)` evaluate the `t_CLOSURE` `C` without arguments.

`GEN closure_callgen0prec(GEN C, long prec)` evaluate the `t_CLOSURE` `C` without arguments, but set the precision locally to `prec`.

`GEN closure_callgen1(GEN C, GEN x)` evaluate the `t_CLOSURE` `C` with argument `x`. Assumes `C` has arity ≥ 1 .

`GEN closure_callgen1prec(GEN C, GEN x, long prec)` as `closure_callgen1`, but set the precision locally to `prec`.

`GEN closure_callgen2(GEN C, GEN x, GEN y)` evaluate the `t_CLOSURE` `C` with argument `x`, `y`. Assumes `C` has arity ≥ 2 .

`void closure_callvoid1(GEN C, GEN x)` evaluate the `t_CLOSURE` `C` with argument `x` and discard the result. Assumes `C` has arity ≥ 1 .

The following technical functions are used to evaluate *inline* closures and closures of arity 0.

The control flow statements (`break`, `next` and `return`) will cause the evaluation of the closure to be interrupted; this is called below a *flow change*. When that occurs, the functions below generally return `NULL`. The caller can then adopt three positions:

- raises an exception (`closure_evalnobrk`).
- passes through (by returning `NULL` itself).

- handles the flow change.

`GEN closure_evalgen(GEN code)` evaluates a closure and returns the result, or `NULL` if a flow change occurred.

`GEN closure_evalnobrk(GEN code)` as `closure_evalgen` but raise an exception if a flow change occurs. Meant for iterators where interrupting the closure is meaningless, e.g. `intnum` or `sumnum`.

`void closure_evalvoid(GEN code)` evaluates a closure whose return value is ignored. The caller has to deal with eventual flow changes by calling `loop_break`.

The remaining functions below are for exceptional situations:

`GEN closure_evalres(GEN code)` evaluates a closure and returns the result. The difference with `closure_evalgen` being that, if the flow end by a `return` statement, the result will be the returned value instead of `NULL`. Used by the main GP loop.

`GEN closure_evalbrk(GEN code, long *status)` as `closure_evalres` but set `status` to a nonzero value if a flow change occurred. This variant is not stack clean. Used by the break loop.

`GEN closure_trapgen(long numerr, GEN code)` evaluates closure, while trapping error `numerr`. Return `(GEN)1L` if error trapped, and the result otherwise, or `NULL` if a flow change occurred. Used by trap.

12.1.2 Functions to handle control flow changes.

`long loop_break(void)` processes an eventual flow changes inside an iterator. If this function return 1, the iterator should stop.

12.1.3 Functions to deal with lexical local variables.

Function using the prototype code ‘V’ need to manually create and delete a lexical variable for each code ‘V’, which will be given a number $-1, -2, \dots$

`void push_lex(GEN a, GEN code)` creates a new lexical variable whose initial value is a on the top of the stack. This variable get the number -1 , and the number of the other variables is decreased by one unit. When the first variable of a closure is created, the argument `code` must be the closure that references this lexical variable. The argument `code` must be `NULL` for all subsequent variables (if any). (The closure contains the debugging data for the variable).

`void pop_lex(long n)` deletes the n topmost lexical variables, increasing the number of other variables by n . The argument n must match the number of variables allocated through `push_lex`.

`GEN get_lex(long vn)` get the value of the variable with number `vn`.

`void set_lex(long vn, GEN x)` set the value of the variable with number `vn`.

12.1.4 Functions returning new closures.

GEN `compile_str(const char *s)` returns the closure corresponding to the GP expression `s`.

GEN `closure_deriv(GEN code)` returns a closure corresponding to the numerical derivative of the closure `code`.

GEN `closure_derivn(GEN code, long n)` returns a closure corresponding to the numerical derivative of order $n > 0$ of the closure `code`.

GEN `snm_closure(entree *ep, GEN data)` Let `data` be a vector of length m , `ep` be an `entree` pointing to a C function f of arity $n + m$, returns a `t_CLOSURE` object g of arity n such that $g(x_1, \dots, x_n) = f(x_1, \dots, x_n, \text{gel}(\text{data}, 1), \dots, \text{gel}(\text{data}, m))$. If `data` is `NULL`, then $m = 0$ is assumed. Shallow function.

GEN `strtofunction(char *str)` returns a closure corresponding to the built-in or install'ed function named `str`.

GEN `strtoclosure(char *str, long n, ...)` returns a closure corresponding to the built-in or install'ed function named `str` with the n last parameters set to the n GENs following `n`. This is analogous to `snm_closure(isentry(str), mkvecn(...))` but the latter has lower overhead since it does not copy arguments, nor does it validate inputs.

In the example code below, `agm1` is set to the function `x->agm(x,1)` and `res` is set to `agm(2,1)`.

```
GEN agm1 = strtoclosure("agm",1, gen_1);
GEN res = closure_callgen1(agm1, gen_2);
```

12.1.5 Functions used by the gp debugger (break loop). long `closure_context(long s)` restores the compilation context starting at frame `s+1`, and returns the index of the topmost frame. This allow to compile expressions in the topmost lexical scope.

void `closure_err(long level)` prints a backtrace of the last 20 stack frames, starting at frame `level`, the numbering starting at 0.

12.1.6 Standard wrappers for iterators. Two families of standard wrappers are provided to interface iterators like `intnum` or `sumnum` with GP.

12.1.6.1 Standard wrappers for inline closures. These wrappers are used to implement GP functions taking inline closures as input. The object (GEN)E must be an inline closure which is evaluated with the lexical variable number -1 set to x .

GEN `gp_eval(void *E, GEN x)` is used for the prototype code 'E'.

GEN `gp_evalprec(void *E, GEN x, long prec)` as `gp_eval`, but set the precision locally to `prec`.

long `gp_evalvoid(void *E, GEN x)` is used for the prototype code 'I'. The resulting value is discarded. Return a nonzero value if a control-flow instruction request the iterator to terminate immediately.

long `gp_evalbool(void *E, GEN x)` returns the boolean `gp_eval(E, x)` evaluates to (i.e. true iff the value is nonzero).

GEN `gp_evalupto(void *E, GEN x)` memory-safe version of `gp_eval`, `gcopy`-ing the result, when the evaluator returns components of previously allocated objects (e.g. member functions).

12.1.6.2 Standard wrappers for true closures. These wrappers are used to implement GP functions taking true closures as input.

`GEN gp_call(void *E, GEN x)` evaluates the closure (GEN)E on x .

`GEN gp_callprec(void *E, GEN x, long prec)` as `gp_call`, but set the precision locally to `prec`.

`GEN gp_call2(void *E, GEN x, GEN y)` evaluates the closure (GEN)E on (x, y) .

`long gp_callbool(void *E, GEN x)` evaluates the closure (GEN)E on x , returns 1 if its result is nonzero, and 0 otherwise.

`long gp_callvoid(void *E, GEN x)` evaluates the closure (GEN)E on x , discarding the result. Return a nonzero value if a control-flow instruction request the iterator to terminate immediately.

12.2 Defaults.

`entree* pari_is_default(const char *s)` return the `entree` structure attached to s if it is the name of a default, NULL otherwise.

`GEN setdefault(const char *s, const char *v, long flag)` is the low-level function underlying `default0`. If s is NULL, call all default setting functions with string argument NULL and flag `d_ACKNOWLEDGE`. Otherwise, check whether s corresponds to a default and call the corresponding default setting function with arguments v and `flag`.

We shall describe these functions below: if v is NULL, we only look at the default value (and possibly print or return it, depending on `flag`); otherwise the value of the default to v , possibly after some translation work. The flag is one of

- `d_INITRC` called while reading the `gprc`: print and return `gnil`, possibly defer until `gp` actually starts.
- `d_RETURN` return the current value, as a `t_INT` if possible, as a `t_STR` otherwise.
- `d_ACKNOWLEDGE` print the current value, return `gnil`.
- `d_SILENT` print nothing, return `gnil`.

Low-level functions called by `setdefault`:

`GEN sd_Texstyle(const char *v, long flag)`

`GEN sd_breakloop(const char *v, long flag)`

`GEN sd_colors(const char *v, long flag)`

`GEN sd_compatible(const char *v, long flag)`

`GEN sd_datadir(const char *v, long flag)`

`GEN sd_debug(const char *v, long flag)`

`GEN sd_debugfiles(const char *v, long flag)`

`GEN sd_debugmem(const char *v, long flag)`

`GEN sd_echo(const char *v, long flag)`

`GEN sd_factor_add_primes(const char *v, long flag)`

```

GEN sd_factor_proven(const char *v, long flag)
GEN sd_factorlimit(const char *v, long flag)
GEN sd_format(const char *v, long flag)
GEN sd_graphcolormap(const char *v, long flag)
GEN sd_graphcolors(const char *v, long flag)
GEN sd_help(const char *v, long flag)
GEN sd_histfile(const char *v, long flag)
GEN sd_histsize(const char *v, long flag)
GEN sd_lines(const char *v, long flag)
GEN sd_linewrap(const char *v, long flag)
GEN sd_log(const char *v, long flag)
GEN sd_logfile(const char *v, long flag)
GEN sd_nbthreads(const char *v, long flag)
GEN sd_new_galois_format(const char *v, long flag)
GEN sd_output(const char *v, long flag)
GEN sd_parisize(const char *v, long flag)
GEN sd_parisizemax(const char *v, long flag)
GEN sd_path(const char *v, long flag)
GEN sd_plothsizes(const char *v, long flag)
GEN sd_prettyprinter(const char *v, long flag)
GEN sd_primelimit(const char *v, long flag)
GEN sd_prompt(const char *v, long flag)
GEN sd_prompt_cont(const char *v, long flag)
GEN sd_psfile(const char *v, long flag) The psfile default is obsolete, don't use this func-
tion.
GEN sd_readline(const char *v, long flag)
GEN sd_realbitprecision(const char *v, long flag)
GEN sd_realprecision(const char *v, long flag)
GEN sd_recover(const char *v, long flag)
GEN sd_secure(const char *v, long flag)
GEN sd_seriesprecision(const char *v, long flag)
GEN sd_simplify(const char *v, long flag)
GEN sd_sopath(const char *v, int flag)

```

```

GEN sd_strictargs(const char *v, long flag)
GEN sd_strictmatch(const char *v, long flag)
GEN sd_timer(const char *v, long flag)
GEN sd_threadsize(const char *v, long flag)
GEN sd_threadsizemax(const char *v, long flag)

```

Generic functions used to implement defaults: most of the above routines are implemented in terms of the following generic ones. In all routines below

- **v** and **flag** are the arguments passed to **default**: **v** is a new value (or the empty string: no change), and **flag** is one of **d_INITRC**, **d_RETURN**, etc.

- **s** is the name of the default being changed, used to display error messages or acknowledgements.

```

GEN sd_toggle(const char *v, long flag, const char *s, int *ptn)

```

- if **v** is neither "0" nor "1", an error is raised using **pari_err**.
- **ptn** points to the current numerical value of the toggle (1 or 0), and is set to the new value (when **v** is nonempty).

For instance, here is how the timer default is implemented internally:

```

GEN
sd_timer(const char *v, long flag)
{ return sd_toggle(v,flag,"timer", &(GP_DATA->chrono)); }

```

The exact behavior and return value depends on **flag**:

- **d_RETURN**: returns the new toggle value, as a **GEN**.
- **d_ACKNOWLEDGE**: prints a message indicating the new toggle value and return **gnil**.
- other cases: print nothing and return **gnil**.

```

GEN sd_ulong(const char *v, long flag, const char *s, ulong *ptn, ulong Min, ulong Max, const char **msg)

```

- **ptn** points to the current numerical value of the toggle, and is set to the new value (when **v** is nonempty).

- **Min** and **Max** point to the minimum and maximum values allowed for the default.

- **v** must translate to an integer in the allowed ranger, a suffix among **k/K** ($\times 10^3$), **m/M** ($\times 10^6$), or **g/G** ($\times 10^9$) is allowed, but no arithmetic expression.

- **msg** is a [NULL]-terminated array of messages or NULL (ignored). If **msg** is not NULL, **msg[i]** contains a message attached to the value *i* of the default. The last entry in the **msg** array is used as a message attached to all subsequent ones.

The exact behavior and return value depends on **flag**:

- **d_RETURN**: returns the new value, as a **GEN**.
- **d_ACKNOWLEDGE**: prints a message indicating the new value, possibly a message attached to it via the **msg** argument, and return **gnil**.

- other cases: print nothing and return `gnil`.

GEN `sd_intarray(const char *v, long flag, const char *s, GEN *pz)`

- records a `t_VECSMALL` array of nonnegative integers.
- `pz` points to the current `t_VECSMALL` value, and is set to the new value (when `v` is nonempty).

The exact return value depends on `flag`:

- `d_RETURN`: returns the new value, as a `t_VEC` (converted via `zv_to_ZV`)
- `d_ACKNOWLEDGE`: prints a message indicating the new value, (as a `t_VEC`) and return `gnil`.
- other cases: print nothing and return `gnil`.

GEN `sd_string(const char *v, long flag, const char *s, char **pstr)` • `v` is subject to environment expansion, then time expansion.

- `pstr` points to the current string value, and is set to the new value (when `v` is nonempty).

12.3 Records and Lazy vectors.

The functions in this section are used to implement `ell` structures and analogous objects, which are vectors some of whose components are initialized to dummy values, later computed on demand. We start by initializing the structure:

GEN `obj_init(long d, long n)` returns an *obj* `S`, a `t_VEC` with `d` regular components, accessed as `gel(S,1), ..., gel(S,d)`; together with a record of `n` members, all initialized to 0. The arguments `d` and `n` must be nonnegative.

After `S = obj_init(d, n)`, the prototype of our other functions are of the form

GEN `obj_do(GEN S, long tag, ...)`

The first argument `S` holds the structure to be managed. The second argument `tag` is the index of the struct member (from 1 to `n`) we operate on. We recommend to define an `enum` and use descriptive names instead of hardcoded numbers. For instance, if `n = 3`, after defining

```
enum { TAG_p = 1, TAG_list, TAG_data };
```

one may use `TAG_list` or 2 indifferently as a tag. The former being preferred, of course.

Technical note. In the current implementation, S is a `t_VEC` with $d + 1$ entries. The first d components are ordinary `t_GEN` entries, which you can read or assign to in the customary way. But the last component `gel(S, d + 1)`, a `t_VEC` of length n initialized to `zerovec(n)`, must be handled in a special way: you should never access or modify its components directly, only through the API we are about to describe. Indeed, its entries are meant to contain dynamic data, which will be stored, retrieved and replaced (for instance by a value computed to a higher accuracy), while interacting safely with intermediate `gerepile` calls. This mechanism allows to simulate C `structs`, in a simpler way than with general hashtables, while remaining compatible with the GP language, which knows neither `structs` nor hashtables. It also serialize the structure in an ordinary `GEN`, which facilitates copies and garbage collection (use `gcopy` or `gerepile`), rather than having to deal with individual components of actual C `structs`.

`GEN obj_reinit(GEN S)` make a shallow copy of S , re-initializing all dynamic components. This allows “forking” a lazy vector while avoiding both a memory leak, and storing pointers to the same data in different objects (with risks of a double free later).

`GEN obj_check(GEN S, long tag)` if the *tag*-component in S is non empty, return it. Otherwise return `NULL`. The `t_INT 0` (initial value) is used as a sentinel to indicated an empty component.

`GEN obj_insert(GEN S, long tag, GEN O)` insert (a clone of) O as *tag*-component of S . Any previous value is deleted, and data pointing to it become invalid.

`GEN obj_insert_shallow(GEN S, long K, GEN O)` as `obj_insert`, inserting O as-is, not via a clone.

`GEN obj_checkbuild(GEN S, long tag, GEN (*build)(GEN))` if the *tag*-component of S is non empty, return it. Otherwise insert (a clone of) `build(S)` as *tag*-component in S , and return it.

`GEN obj_checkbuild_padicprec(GEN S, long tag, GEN (*build)(GEN, long), long prec)` if the *tag*-component of S is non empty *and* has relative p -adic precision \geq `prec`, return it. Otherwise insert (a clone of) `build(S, prec)` as *tag*-component in S , and return it.

`GEN obj_checkbuild_realprec(GEN S, long tag, GEN (*build)(GEN, long), long prec)` if the *tag*-component of S is non empty *and* satisfies `gprecision` \geq `prec`, return it. Otherwise insert (a clone of) `build(S, prec)` as *tag*-component in S , and return it.

`GEN obj_checkbuild_prec(GEN S, long tag, GEN (*build)(GEN, long), GEN (*gpr)(GEN), long prec)` if the *tag*-component of S is non empty *and* has precision `gpr(x)` \geq `prec`, return it. Otherwise insert (a clone of) `build(S, prec)` as *tag*-component in S , and return it.

`void obj_free(GEN S)` destroys all clones stored in the n tagged components, and replace them by the initial value 0. The regular entries of S are unaffected, and S remains a valid object. This is used to avoid memory leaks.

Chapter 13:

Algebraic Number Theory

13.1 General Number Fields.

13.1.1 Number field types.

None of the following routines thoroughly check their input: they distinguish between *bona fide* structures as output by PARI routines, but designing perverse data will easily fool them. To give an example, a square matrix will be interpreted as an ideal even though the \mathbf{Z} -module generated by its columns may not be an \mathbf{Z}_K -module (i.e. the expensive `nfisideal` routine will *not* be called).

`long nftyp(GEN x)`. Returns the type of number field structure stored in `x`, `typ_NF`, `typ_BNF`, or `typ_BNR`. Other answers are possible, meaning `x` is not a number field structure.

`GEN get_nf(GEN x, long *t)`. Extract an *nf* structure from `x` if possible and return it, otherwise return `NULL`. Sets `t` to the `nftyp` of `x` in any case.

`GEN get_bnf(GEN x, long *t)`. Extract a *bnf* structure from `x` if possible and return it, otherwise return `NULL`. Sets `t` to the `nftyp` of `x` in any case.

`GEN get_nfpol(GEN x, GEN *nf)` try to extract an *nf* structure from `x`, and sets `*nf` to `NULL` (failure) or to the *nf*. Returns the (monic, integral) polynomial defining the field.

`GEN get_bnfpol(GEN x, GEN *bnf, GEN *nf)` try to extract a *bnf* and an *nf* structure from `x`, and sets `*bnf` and `*nf` to `NULL` (failure) or to the corresponding structure. Returns the (monic, integral) polynomial defining the field.

`GEN checknf(GEN x)` if an *nf* structure can be extracted from `x`, return it; otherwise raise an exception. The more general `get_nf` is often more flexible.

`GEN checkbnf(GEN x)` if an *bnf* structure can be extracted from `x`, return it; otherwise raise an exception. The more general `get_bnf` is often more flexible.

`GEN checkbnf_i(GEN bnf)` same as `checkbnf` but return `NULL` instead of raising an exception.

`void checkbnr(GEN bnr)` Raise an exception if the argument is not a *bnr* structure.

`GEN checkbnr_i(GEN bnr)` same as `checkbnr` but returns the *bnr* or `NULL` instead of raising an exception.

`GEN checknf_i(GEN nf)` same as `checknf` but return `NULL` instead of raising an exception.

`void checkrnf(GEN rnf)` Raise an exception if the argument is not an *rnf* structure.

`int checkrnf_i(GEN rnf)` same as `checkrnf` but return 0 on failure and 1 on success.

`void checkbid(GEN bid)` Raise an exception if the argument is not a *bid* structure.

`GEN checkbid_i(GEN bid)` same as `checkbid` but return `NULL` instead of raising an exception and return `bid` on success.

`GEN checkznstar_i(GEN G)` return G if it is a *znstar*; else return NULL on failure.

`GEN checkgal(GEN x)` if a *galoisinit* structure can be extracted from x , return it; otherwise raise an exception.

`void checksqmat(GEN x, long N)` check whether x is a square matrix of dimension N . May be used to check for ideals if N is the field degree.

`void checkprid(GEN pr)` Raise an exception if the argument is not a prime ideal structure.

`int checkprid_i(GEN pr)` same as `checkprid` but return 0 instead of raising an exception and return 1 on success.

`int is_nf_factor(GEN F)` return 1 if F is an ideal factorization and 0 otherwise.

`int is_nf_extfactor(GEN F)` return 1 if F is an extended ideal factorization (allowing 0 or negative exponents) and 0 otherwise.

`int RgV_is_prV(GEN v)` returns 1 if the vector v contains only prime ideals and 0 otherwise.

`GEN get_prid(GEN ideal)` return the underlying prime ideal structure if one can be extracted from *ideal* (ideal or extended ideal), and return NULL otherwise.

`void checkabgrp(GEN v)` Raise an exception if the argument is not an abelian group structure, i.e. a `t_VEC` with either 2 or 3 entries: $[N, cyc]$ or $[N, cyc, gen]$.

`GEN abgrp_get_no(GEN x)` extract the cardinality N from an abelian group structure.

`GEN abgrp_get_cyc(GEN x)` extract the elementary divisors *cyc* from an abelian group structure.

`GEN abgrp_get_gen(GEN x)` extract the generators *gen* from an abelian group structure.

`GEN cyc_get_expo(GEN cyc)` return the exponent of the group with structure *cyc*; 0 for an infinite group.

`void checkmodpr(GEN modpr)` Raise an exception if the argument is not a `modpr` structure (from `nfmodprinit`).

`GEN get_modpr(GEN x)` return x if it is a `modpr` structure and NULL otherwise.

`GEN checknfelt_mod(GEN nf, GEN x, const char *s)` given an *nf* structure *nf* and a `t_POLMOD` x , return the attached polynomial representative (shallow) if x and *nf* are compatible. Raise an exception otherwise. Set *s* to the name of the caller for a meaningful error message.

`int check_ZKmodule_i(GEN x)` return 1 if x looks like a projective \mathbf{Z}_K -module, i.e., a pair $[A, I]$ where A is a matrix and I is a list of ideals and A has as many columns as I has elements. Or possibly a longer list $[A, I, \dots]$ such as the output of `rnfpsudobasis`. Otherwise return 0.

`void check_ZKmodule(GEN x, const char *s)` raise an exception unless x is recognized as a projective \mathbf{Z}_K -module. Set *s* to the name of the caller for a meaningful error message.

`long idealtyp(GEN *ideal, GEN *fa)` The input is *ideal*, a pointer to an ideal or extended ideal; returns the type of the underlying ideal among `id_PRINCIPAL` (a number field element), `id_PRIME` (a prime ideal) `id_MAT` (an ideal in matrix form).

As a first side effect, **ideal* is set to the underlying ideal, possibly simplified (for instance the zero ideal represented by an empty matrix is replaced by `gen_0`).

If *fa* is not NULL, then **fa* is set to the extended part in the input: either NULL (regular ideal) or the extended part of an extended ideal.

13.1.2 Extracting info from a nf structure.

These functions expect a true *nf* argument attached to a number field $K = \mathbf{Q}[x]/(T)$, e.g. a *bnf* will not work. Let $n = [K : \mathbf{Q}]$ be the field degree.

`GEN nf_get_pol(GEN nf)` returns the polynomial T (monic, in $\mathbf{Z}[x]$).

`long nf_get_varn(GEN nf)` returns the variable number of the number field defining polynomial.

`long nf_get_r1(GEN nf)` returns the number of real places r_1 .

`long nf_get_r2(GEN nf)` returns the number of complex places r_2 .

`void nf_get_sign(GEN nf, long *r1, long *r2)` sets r_1 and r_2 to the number of real and complex places respectively. Note that $r_1 + 2r_2$ is the field degree.

`long nf_get_degree(GEN nf)` returns the number field degree, $n = r_1 + 2r_2$.

`GEN nf_get_disc(GEN nf)` returns the field discriminant.

`GEN nf_get_index(GEN nf)` returns the index of T , i.e. the index of the order generated by the power basis $(1, x, \dots, x^{n-1})$ in the maximal order of K .

`GEN nf_get_zk(GEN nf)` returns a basis (w_1, w_2, \dots, w_n) for the maximal order of K . Those are polynomials in $\mathbf{Q}[x]$ of degree $< n$; it is guaranteed that $w_1 = 1$.

`GEN nf_get_zkden(GEN nf)` returns the denominator of `nf_get_zk`, as a positive `t_INT`.

`GEN nf_get_zkprimpart(GEN nf)` returns `nf_get_zk` times its denominator.

`GEN nf_get_invzk(GEN nf)` returns the matrix $(m_{i,j}) \in M_n(\mathbf{Z})$ giving the power basis (x^i) in terms of the (w_j) , i.e. such that $x^{j-1} = \sum_{i=1}^n m_{i,j} w_i$ for all $1 \leq j \leq n$; since $w_1 = 1 = x^0$, we have $m_{i,1} = \delta_{i,1}$ for all i . The conversion functions in the `algtobasis` family essentially amount to a left multiplication by this matrix.

`GEN nf_get_roots(GEN nf)` returns the r_1 real roots of the polynomial defining the number fields: first the r_1 real roots (as `t_REALs`), then the r_2 representatives of the pairs of complex conjugates.

`GEN nf_get_allroots(GEN nf)` returns all the complex roots of T : first the r_1 real roots (as `t_REALs`), then the r_2 pairs of complex conjugates.

`GEN nf_get_M(GEN nf)` returns the $(r_1 + r_2) \times n$ matrix M giving the embeddings of K : $M[i, j]$ contains $w_j(\alpha_i)$, where α_i is the i -th element of `nf_get_roots(nf)`. In particular, if v is an n -th dimensional `t_COL` representing the element $\sum_{i=1}^n v[i] w_i$ of K , then `RgM_RgC_mul(M, v)` represents the embeddings of v .

`GEN nf_get_G(GEN nf)` returns a $n \times n$ real matrix G such that $Gv \cdot Gv = T_2(v)$, where v is an n -th dimensional `t_COL` representing the element $\sum_{i=1}^n v[i] w_i$ of K and T_2 is the standard Euclidean form on $K \otimes \mathbf{R}$, i.e. $T_2(v) = \sum_{\sigma} |\sigma(v)|^2$, where σ runs through all n complex embeddings of K .

`GEN nf_get_roundG(GEN nf)` returns a rescaled version of G , rounded to nearest integers, specifically `RM_round_maxrank(G)`.

`GEN nf_get_ramified_primes(GEN nf)` returns the vector of ramified primes.

`GEN nf_get_Tr(GEN nf)` returns the matrix of the Trace quadratic form on the basis (w_1, \dots, w_n) : its (i, j) entry is $\text{Tr} w_i w_j$.

`GEN nf_get_diff(GEN nf)` returns the primitive part of the inverse of the above Trace matrix.

`long nf_get_prec(GEN nf)` returns the precision (in words) to which the *nf* was computed.

13.1.3 Extracting info from a bnf structure.

These functions expect a true *bnf* argument, e.g. a *bnr* will not work.

`GEN bnf_get_nf(GEN bnf)` returns the underlying *nf*.

`GEN bnf_get_clgp(GEN bnf)` returns the class group in *bnf*, which is a 3-component vector $[h, cyc, gen]$.

`GEN bnf_get_cyc(GEN bnf)` returns the elementary divisors of the class group (cyclic components) $[d_1, \dots, d_k]$, where $d_k \mid \dots \mid d_1$.

`GEN bnf_get_gen(GEN bnf)` returns the generators $[g_1, \dots, g_k]$ of the class group. Each g_i has order d_i , and the full module of relations between the g_i is generated by the $d_i g_i = 0$.

`GEN bnf_get_no(GEN bnf)` returns the class number.

`GEN bnf_get_reg(GEN bnf)` returns the regulator.

`GEN bnf_get_logfu(GEN bnf)` returns (complex floating point approximations to) the logarithms of the complex embeddings of our system of fundamental units.

`GEN bnf_get_fu(GEN bnf)` returns the fundamental units. Raise an error if the *bnf* does not contain units in algebraic form.

`GEN bnf_get_fu_nocheck(GEN bnf)` as `bnf_get_fu` without checking whether units are present. Do not use this unless you initialize the *bnf* yourself!

`GEN bnf_get_tuU(GEN bnf)` returns a generator of the torsion part of \mathbf{Z}_K^* .

`long bnf_get_tuN(GEN bnf)` returns the order of the torsion part of \mathbf{Z}_K^* , i.e. the number of roots of unity in K .

`GEN bnf_get_sunits(GEN bnf)` allows access to the algebraic data stored by `bnfinit(,1)`. The function returns NULL unless the *bnf* was initialized by `bnfinit(,1)`, else a vector $[X, U, E, \text{lim}]$ where

- X is a vector of rational primes and algebraic integers all of whose prime divisors have norm less than `lim`,
- U is a matrix of exponents whose columns yield the fundamental units `bnf.fu`. More precisely,

$$\text{bnf.fu}[j] = \prod_i X[i]^{U[i,j]}.$$

- E is a matrix of exponents whose columns yield the generators of principal ideals attached to the HNF of the *bnf* relation matrix between the maximal ideals of norm less `lim` (that generate the class group under GRH). More precisely, `bnf[5]` contains the prime factor base P (its first r elements being independant class group generators), `bnf[1]` contains a matrix W in HNF in $M_r(\mathbf{Z})$ and `bnf[2]`, contains a matrix B in $M_{r \times c}(\mathbf{Z})$. We define algebraic numbers e_j for $j \leq r + c$ such that

$$\prod_{i \leq r} p_i^{w[i,j]} = (e_j), \quad j \leq r$$

$$P_j \prod_{i \leq r} p_i^{b[i,j]} = (e_j), \quad j > r$$

Then $e_j = \prod_i X[i]^{E[i,j]}$.

`GEN bnf_has_fu(GEN bnf)` return fundamental units in expanded form if `bnf` contains them. Else return `NULL`.

`GEN bnf_compactfu(GEN bnf)` return fundamental units as a vector of algebraic numbers in compact form if `bnf` contains them. Else return `NULL`.

`GEN bnf_compactfu_mat(GEN bnf)` as a pair (X, U) , where X is a vector of S -units and U is a matrix with integer entries (without 0 rows), see `bnf_get_sunits`, if `bnf` contains them. Else return `NULL`.

13.1.4 Extracting info from a `bnr` structure.

These functions expect a true *bnr* argument.

`GEN bnr_get_bnf(GEN bnr)` returns the underlying *bnf*.

`GEN bnr_get_nf(GEN bnr)` returns the underlying *nf*.

`GEN bnr_get_clgp(GEN bnr)` returns the ray class group.

`GEN bnr_get_no(GEN bnr)` returns the ray class number.

`GEN bnr_get_cyc(GEN bnr)` returns the elementary divisors of the ray class group (cyclic components) $[d_1, \dots, d_k]$, where $d_k \mid \dots \mid d_1$.

`GEN bnr_get_gen(GEN bnr)` returns the generators $[g_1, \dots, g_k]$ of the ray class group. Each g_i has order d_i , and the full module of relations between the g_i is generated by the $d_i g_i = 0$. Raise a generic error if the *bnr* does not contain the ray class group generators.

`GEN bnr_get_gen_nocheck(GEN bnr)` as `bnr_get_gen` without checking whether generators are present. Do not use this unless you initialize the *bnr* yourself!

`GEN bnr_get_bid(GEN bnr)` returns the *bid* attached to the *bnr* modulus.

`GEN bnr_get_mod(GEN bnr)` returns the modulus attached to the *bnr*.

13.1.5 Extracting info from an *rnf* structure.

These functions expect a true *rnf* argument, attached to an extension L/K , $K = \mathbf{Q}[y]/(T)$, $L = K[x]/(P)$.

`long rnf_get_degree(GEN rnf)` returns the *relative* degree $[L : K]$.

`long rnf_get_absdegree(GEN rnf)` returns the absolute degree $[L : \mathbf{Q}]$.

`long rnf_get_nfdegree(GEN rnf)` returns the degree of the base field $[K : \mathbf{Q}]$.

`GEN rnf_get_nf(GEN rnf)` returns the base field K , an *nf* structure.

`GEN rnf_get_nfpol(GEN rnf)` returns the polynomial T defining the base field K .

`long rnf_get_nfvarn(GEN rnf)` returns the variable y attached to the base field K .

`GEN rnf_get_nfzk(GEN rnf)` returns the integer basis of the base field K .

`GEN rnf_get_pol(GEN rnf)` returns the relative polynomial defining L/K .

`long rnf_get_varn(GEN rnf)` returns the variable x attached to L .

`GEN rnf_get_zk(GEN nf)` returns the relative integer basis generating \mathbf{Z}_L as a \mathbf{Z}_K -module, as a pseudo-matrix (A, I) in HNF.

`GEN rnf_get_disc(GEN rnf)` is the output $[\mathfrak{d}, s]$ of `rnfdisc`.

`GEN rnf_get_ramified_primes(GEN rnf)` returns the vector of rational primes below ramified primes in the relative extension, i.e. all prime numbers appearing in the factorization of

`ideallnorm(rnf_get_nf(rnf), rnf_get_disc(rnf));`

`GEN rnf_get_idealdisc(GEN rnf)` is the ideal discriminant \mathfrak{d} from `rnfdisc`.

`GEN rnf_get_index(GEN rnf)` is the index ideal \mathfrak{f}

`GEN rnf_get_polabs(GEN rnf)` returns an absolute polynomial defining L/\mathbf{Q} .

`GEN rnf_get_alpha(GEN rnf)` a root α of the polynomial defining the base field, modulo `polabs` (cf. `rnfequation`)

`GEN rnf_get_k(GEN rnf)` a small integer k such that $\theta = \beta + k\alpha$ is a root of `polabs`, where β is a root of `pol` and α a root of the polynomial defining the base field, as in `rnf_get_alpha` (cf. also `rnfequation`).

`GEN rnf_get_invzk(GEN rnf)` contains A^{-1} , where (A, I) is the chosen pseudo-basis for \mathbf{Z}_L over \mathbf{Z}_K .

`GEN rnf_get_map(GEN rnf)` returns technical data attached to the map $K \rightarrow L$. Currently, this contains data from `rnfequation`, as well as the polynomials T and P .

13.1.6 Extracting info from a bid structure.

These functions expect a true *bid* argument, attached to a modulus $I = I_0 I_\infty$ in a number field K . The underlying abelian group is $G = (\mathbf{Z}_K/I)^*$. Not that if the *bid* was initialized by `Idealstarmod` with a non-NULL `cycmod` argument, computations take place in G/G^{cycmod} instead.

`GEN bid_get_mod(GEN bid)` returns the modulus attached to the *bid*.

`GEN bid_get_MOD(GEN bid)` returns the integer `cycmod` given as argument to `Idealstarmod`, or NULL if we used `Idealstar` to initialize *bid*.

`GEN bid_get_grp(GEN bid)` returns the abelian group attached to $(\mathbf{Z}_K/I)^*$.

`GEN bid_get_ideal(GEN bid)` return the finite part I_0 of the *bid* modulus (an integer ideal).

`GEN bid_get_arch(GEN bid)` return the Archimedean part I_∞ of the *bid* modulus as a vector of real places in `vec01` format, see Section 13.1.20.

`GEN bid_get_archp(GEN bid)` return the Archimedean part I_∞ of the *bid* modulus, as a vector of real places in indices format see Section 13.1.20.

`GEN bid_get_fact(GEN bid)` returns the ideal factorization $I_0 = \prod_i \mathfrak{p}_i^{e_i}$.

`GEN bid_get_fact2(GEN bid)` as `bid_get_fact` with all factors \mathfrak{p}^1 with \mathfrak{p} of norm 2 removed from the factorization. (They play no role in the structure of $(\mathbf{Z}_K/I)^*$, except that the generators must be made coprime to them.)

`bid_get_ideal(bid)`, via `idealfactor`.

`GEN bid_get_no(GEN bid)` returns the cardinality of the group $(\mathbf{Z}_K/I)^*$.

GEN `bid_get_cyc`(GEN `bid`) returns the elementary divisors of the group $(\mathbf{Z}_K/I)^*$ (cyclic components) $[d_1, \dots, d_k]$, where $d_k \mid \dots \mid d_1$.

GEN `bid_get_gen`(GEN `bid`) returns the generators of $(\mathbf{Z}_K/I)^*$ contained in `bid`. Raise a generic error if `bid` does not contain generators.

GEN `bid_get_gen_nocheck`(GEN `bid`) as `bid_get_gen` without checking whether generators are present. Do not use this unless you initialize the `bid` yourself!

GEN `bid_get_sprk`(GEN `bid`) return a list of structures attached to the $(\mathbf{Z}_K/\mathfrak{p}^e)^*$ where \mathfrak{p}^e divides I_0 exactly.

GEN `bid_get_sarch`(GEN `bid`) return the structure attached to $(\mathbf{Z}_K/I_\infty)^*$, by `nfarchstar`.

GEN `bid_get_U`(GEN `bid`) return the matrix with integral coefficients relating the local generators (from chinese remainders) to the global SNF generators (`bid.gen`).

13.1.7 Extracting info from a znstar structure.

These functions expect an argument G as returned by `znstar0(N, 1)`, attached to a positive N and the abelian group $(\mathbf{Z}/N\mathbf{Z})^*$. Let (g_i) be the SNF generators, where g_i has order d_i ; we call (g'_i) the (canonical) Conrey generators, where g'_i has order d'_i . Both sets of generators have the same cardinality.

GEN `znstar_get_N`(GEN `bid`) return N .

GEN `znstar_get_faN`(GEN G) return the factorization `factor(N)`, $N = \prod_j p_j^{e_j}$.

GEN `znstar_get_pe`(GEN G) return the vector of primary factors $(p_j^{e_j})$.

GEN `znstar_get_no`(GEN G) the cardinality $\phi(N)$ of G .

GEN `znstar_get_cyc`(GEN G) elementary divisors (d_i) of $(\mathbf{Z}/N\mathbf{Z})^*$.

GEN `znstar_get_gen`(GEN G) SNF generators divisors (g_i) of $(\mathbf{Z}/N\mathbf{Z})^*$.

GEN `znstar_get_conreycyc`(GEN G) orders (d'_i) of Conrey generators.

GEN `znstar_get_conreygen`(GEN G) Conrey generators (g'_i) .

GEN `znstar_get_U`(GEN G) a square matrix U such that $(g_i) = U(g'_i)$.

GEN `znstar_get_Ui`(GEN G) a square matrix U' such that $U'(g_i) = (g'_i)$. In general, UU' will not be the identity.

13.1.8 Inserting info in a number field structure.

If the required data is not part of the structure, it is computed then inserted, and the new value is returned.

These functions expect a `bnf` argument:

GEN `bnf_build_cycgen`(GEN `bnf`) the `bnf` contains generators $[g_1, \dots, g_k]$ of the class group, each with order d_i . Then $g_i^{d_i} = (x_i)$ is a principal ideal. This function returns the x_i as a factorization matrix (`famat`) giving the element in factored form as a product of S -units.

GEN `bnf_build_matalpha`(GEN `bnf`) the class group was computed using a factorbase S of prime ideals \mathfrak{p}_i , $i \leq r$. They satisfy relations of the form $\prod_j \mathfrak{p}_i^{e_{i,j}} = (\alpha_j)$, where the $e_{i,j}$ are given by the matrices `bnf[1]` (W , singling out a minimal set of generators in S) and `bnf[2]` (B , expressing the

rest of S in terms of the singled out generators). This function returns the α_j in factored form as a product of S -units.

`GEN bnf_build_units(GEN bnf)` returns a minimal set of generators for the unit group in expanded form. The first element is a torsion unit, the others have infinite order. This expands units in compact form contained in a `bnf` from `bnfinit`(, 1) and may be *very* expensive if the units are huge.

`GEN bnf_build_cheapfu(GEN bnf)` as `bnf_build_units` but only expand units in compact form if the computation is inexpensive (a few seconds). Return `NULL` otherwise.

These functions expect a `rnf` argument:

`GEN rnf_build_nfabs(GEN rnf, long prec)` given a `rnf` structure attached to L/K , (compute and) return an `nf` structure attached to L at precision `prec`.

`void rnfcomplete(GEN rnf)` as `rnf_build_nfabs` using the precision of K for `prec`.

`GEN rnf_zkabs(GEN rnf)` returns a \mathbf{Z} -basis in HNF for \mathbf{Z}_L as a pair $[T, v]$, where T is `rnf_get_polabs(rnf)` and v a vector of elements lifted from $\mathbf{Q}[X]/(T)$. Note that the function `rnf_build_nfabs` essentially applies `nfinit` to the output of this function.

13.1.9 Increasing accuracy.

`GEN nfnewprec(GEN x, long prec)`. Raise an exception if x is not a number field structure (`nf`, `bnf` or `bnr`). Otherwise, sets its accuracy to `prec` and return the new structure. This is mostly useful with `prec` larger than the accuracy to which x was computed, but it is also possible to decrease the accuracy of x (truncating relevant components, which may speed up later computations). This routine may modify the original x (see below).

This routine is straightforward for `nf` structures, but for the other ones, it requires all principal ideals corresponding to the `bnf` relations in algebraic form (they are originally only available via floating point approximations). This in turn requires many calls to `bnfisprincipal0`, which is often slow, and may fail if the initial accuracy was too low. In this case, the routine will not actually fail but recomputes a `bnf` from scratch!

Since this process may be very expensive, the corresponding data is cached (as a *clone*) in the *original* x so that later precision increases become very fast. In particular, the copy returned by `nfnewprec` also contains this additional data.

`GEN bnfnewprec(GEN x, long prec)`. As `nfnewprec`, but extracts a `bnf` structure from x before increasing its accuracy, and returns only the latter.

`GEN bnrnewprec(GEN x, long prec)`. As `nfnewprec`, but extracts a `bnr` structure from x before increasing its accuracy, and returns only the latter.

`GEN rnfnewprec(GEN x, long prec)`. As `nfnewprec`, but extracts a `rnf` structure from x before increasing its accuracy, and returns only the latter.

`GEN nfnewprec_shallow(GEN nf, long prec)`

`GEN bnfnewprec_shallow(GEN bnf, long prec)`

`GEN rnfnewprec_shallow(GEN rnf, long prec)`

`GEN bnrnewprec_shallow(GEN bnr, long prec)` Shallow functions underlying the above, except that the first argument must now have the corresponding number field type. I.e. one cannot call `nfnewprec_shallow(nf, prec)` if `nf` is actually a `bnf`.

13.1.10 Number field arithmetic. The number field $K = \mathbf{Q}[X]/(T)$ is represented by an `nf` (or `bnf` or `bnr` structure). An algebraic number belonging to K is given as

- a `t_INT`, `t_FRAC` or `t_POL` (implicitly modulo T), or
- a `t_POLMOD` (modulo T), or
- a `t_COL` v of dimension $N = [K : \mathbf{Q}]$, representing the element in terms of the computed integral basis (e_i) , as

```
sum(i = 1, N, v[i] * nf.zk[i])
```

The preferred forms are `t_INT` and `t_COL` of `t_INT`. Routines can handle denominators but it is much more efficient to remove denominators first (`Q_remove_denom`) and take them into account at the end.

Safe routines. The following routines do not assume that their `nf` argument is a true *nf* (it can be any number field type, e.g. a *bnf*), and accept number field elements in all the above forms. They return their result in `t_COL` form.

`GEN nfadd(GEN nf, GEN x, GEN y)` returns $x + y$.

`GEN nfsub(GEN nf, GEN x, GEN y)` returns $x - y$.

`GEN nfdiv(GEN nf, GEN x, GEN y)` returns x/y .

`GEN nfinv(GEN nf, GEN x)` returns x^{-1} .

`GEN nfmul(GEN nf, GEN x, GEN y)` returns xy .

`GEN nfpow(GEN nf, GEN x, GEN k)` returns x^k , k is in \mathbf{Z} .

`GEN nfpow_u(GEN nf, GEN x, ulong k)` returns x^k , $k \geq 0$; the argument `nf` is a true *nf* structure.

`GEN nfsqr(GEN nf, GEN x)` returns x^2 .

`long nfval(GEN nf, GEN x, GEN pr)` returns the valuation of x at the maximal ideal \mathfrak{p} attached to the *prid* `pr`. Returns `LONG_MAX` if x is 0.

`GEN nfnorm(GEN nf, GEN x)` absolute norm of x .

`GEN nftrace(GEN nf, GEN x)` absolute trace of x .

`GEN nfpoleval(GEN nf, GEN pol, GEN a)` evaluate the `t_POL` `pol` (with coefficients in `nf`) on the algebraic number a (also in *nf*).

`GEN FpX_FpC_nfpoleval(GEN nf, GEN pol, GEN a, GEN p)` evaluate the `FpX` `pol` on the algebraic number a (also in *nf*).

The following three functions implement trivial functionality akin to Euclidean division for which we currently have no real use. Of course, even if the number field is actually Euclidean, these do not in general implement a true Euclidean division.

`GEN nfdiveuc(GEN nf, GEN a, GEN b)` returns the algebraic integer closest to x/y . Functionally identical to `ground(nfdiv(nf,x,y))`.

`GEN nfdivrem(GEN nf, GEN a, GEN b)` returns the vector $[q, r]$, where

```
q = nfdiveuc(nf, a, b);
r = nfsub(nf, a, nfmul(nf,q,b));    \\ or r = nfmod(nf,a,b);
```

GEN `nfmod`(GEN `nf`, GEN `a`, GEN `b`) returns r such that

```
q = nfdiveuc(nf, a, b);
r = nfsub(nf, a, nfmul(nf,q,b));
```

GEN `nf_to_scalar_or_basis`(GEN `nf`, GEN `x`) let x be a number field element. If it is a rational scalar, i.e. can be represented by a `t_INT` or `t_FRAC`, return the latter. Otherwise returns its basis representation (`nfaltobasis`). Shallow function.

GEN `nf_to_scalar_or_alg`(GEN `nf`, GEN `x`) let x be a number field element. If it is a rational scalar, i.e. can be represented by a `t_INT` or `t_FRAC`, return the latter. Otherwise returns its lifted `t_POLMOD` representation (lifted `nfbasistoalg`). Shallow function.

GEN `nfV_to_scalar_or_alg`(GEN `nf`, GEN `v`) apply `nf_to_scalar_or_alg` to all components of vector v .

GEN `RgX_to_nfX`(GEN `nf`, GEN `x`) let x be a `t_POL` whose coefficients are number field elements; apply `nf_to_scalar_or_basis` to each coefficient and return the resulting new polynomial. Shallow function.

GEN `RgM_to_nfM`(GEN `nf`, GEN `x`) let x be a `t_MAT` whose coefficients are number field elements; apply `nf_to_scalar_or_basis` to each coefficient and return the resulting new matrix. Shallow function.

GEN `RgC_to_nfC`(GEN `nf`, GEN `x`) let x be a `t_COL` or `t_VEC` whose coefficients are number field elements; apply `nf_to_scalar_or_basis` to each coefficient and return the resulting new `t_COL`. Shallow function.

GEN `nfX_to_monico`(GEN `nf`, GEN `T`, GEN `*pL`) given a nonzero `t_POL` T with coefficients in nf , return a monic polynomial f with integral coefficients such that $f(x) = CT(x/L)$ for some integral L and some C in nf . The function allows coefficients in basis form; if $L \neq 1$, it will return them in algebraic form. If `pL` is not NULL, `*pL` is set to L . Shallow function.

Unsafe routines. The following routines assume that their `nf` argument is a true nf (e.g. a *bnf* is not allowed) and their argument are restricted in various ways, see the precise description below.

GEN `nfX_disc`(GEN `nf`, GEN `A`) given an nf structure attached to a number field K with main variable Y (`nf_get_varn(nf)`), a `t_POL` $A \in K[X]$ given as a lift in $\mathbf{Q}[X, Y]$ (implicitly modulo `nf_get_pol(nf)`), return the discriminant of A as a `t_POL` in $\mathbf{Q}[Y]$ (representing an element of K).

GEN `nfX_resultant`(GEN `nf`, GEN `A`, GEN `B`) analogous to `nfX_disc`, $A, B \in \mathbf{Q}[X, Y]$; return the resultant of A and B with respect to X as a `t_POL` in $\mathbf{Q}[Y]$ (representing an element of K).

GEN `nfinvmideal`(GEN `nf`, GEN `x`, GEN `A`) given an algebraic integer x and a nonzero integral ideal A in HNF, returns a y such that $xy \equiv 1$ modulo A .

GEN `nfpowmodideal`(GEN `nf`, GEN `x`, GEN `n`, GEN `ideal`) given an algebraic integer x , an integer n , and a nonzero integral ideal A in HNF, returns an algebraic integer congruent to x^n modulo A .

GEN `nfmuli`(GEN `nf`, GEN `x`, GEN `y`) returns $x \times y$ assuming that both x and y are either `t_INTs` or ZVs of the correct dimension. The argument `nf` is a true nf structure.

GEN `nfsqri`(GEN `nf`, GEN `x`) returns x^2 assuming that x is a `t_INT` or a ZV of the correct dimension. The argument `nf` is a true nf structure.

GEN `nfC_nf_mul`(GEN `nf`, GEN `v`, GEN `x`) given a `t_VEC` or `t_COL` v of elements of K in `t_INT`, `t_FRAC` or `t_COL` form, multiply it by the element x (arbitrary form). This is faster than multiplying

coordinatewise since pre-computations related to x (computing the multiplication table) are done only once. The components of the result are in most cases `t_COLs` but are allowed to be `t_INTs` or `t_FRACs`. Shallow function.

`GEN nfC_multable_mul(GEN v, GEN mx)` same as `nfC_nf_mul`, where the argument x is replaced by its multiplication table `mx`.

`GEN zkC_multable_mul(GEN v, GEN x)` same as `nfC_nf_mul`, where v is a vector of algebraic integers, x is an algebraic integer, and x is replaced by `zk_multable(x)`.

`GEN zk_multable(GEN nf, GEN x)` given a `ZC` x (implicitly representing an algebraic integer), returns the `ZM` giving the multiplication table by x . Shallow function (the first column of the result points to the same data as x).

`GEN zk_inv(GEN nf, GEN x)` given a `ZC` x (implicitly representing an algebraic integer), returns the `QC` giving the inverse x^{-1} . Return `NULL` if x is 0. Not memory clean but safe for `gerepileupto`.

`GEN zkmultable_inv(GEN mx)` as `zk_inv`, where the argument given is `zk_multable(x)`.

`GEN zkmultable_capZ(GEN mx)` given a nonzero *zkmultable* mx attached to $x \in \mathbf{Z}_K$, return the positive generator of $(x) \cap \mathbf{Z}$.

`GEN zk_scalar_or_multable(GEN nf, GEN x)` given a `t_INT` or `ZC` x , returns a `t_INT` equal to x if the latter is a scalar (`t_INT` or `ZV_isscalar(x)` is 1) and `zk_multable(nf, x)` otherwise. Shallow function.

13.1.11 Number field arithmetic for linear algebra.

The following routines implement multiplication in a commutative R -algebra, generated by $(e_1 = 1, \dots, e_n)$, and given by a multiplication table M : elements in the algebra are n -dimensional `t_COLs`, and the matrix M is such that for all $1 \leq i, j \leq n$, its column with index $(i-1)n + j$, say (c_k) , gives $e_i \cdot e_j = \sum c_k e_k$. It is assumed that e_1 is the neutral element for the multiplication (a convenient optimization, true in practice for all multiplications we needed to implement). If x has any other type than `t_COL` where an algebra element is expected, it is understood as $x e_1$.

`GEN multable(GEN M, GEN x)` given a column vector x , representing the quantity $\sum_{i=1}^N x_i e_i$, returns the multiplication table by x . Shallow function.

`GEN ei_multable(GEN M, long i)` returns the multiplication table by the i -th basis element e_i . Shallow function.

`GEN tablemul(GEN M, GEN x, GEN y)` returns $x \cdot y$.

`GEN tablesqr(GEN M, GEN x)` returns x^2 .

`GEN tablemul_ei(GEN M, GEN x, long i)` returns $x \cdot e_i$.

`GEN tablemul_ei_ej(GEN M, long i, long j)` returns $e_i \cdot e_j$.

`GEN tablemulvec(GEN M, GEN x, GEN v)` given a vector v of elements in the algebra, returns the $x \cdot v[i]$.

The following routines implement naive linear algebra using the *black box field* mechanism:

`GEN nfM_det(GEN nf, GEN M)`

`GEN nfM_inv(GEN nf, GEN M)`

`GEN nfM_ker(GEN nf, GEN M)`

GEN nfM_mul(GEN nf, GEN A, GEN B)

GEN nfM_nfC_mul(GEN nf, GEN A, GEN B)

13.1.12 Cyclotomic field arithmetic for linear algebra.

The following routines implement modular algorithms in cyclotomic fields. In the prototypes, P is the n -th cyclotomic polynomial Φ_n and M is a `t_MAT` with `t_INT` or `ZX` coefficients, understood modulo P .

GEN ZabM_ker(GEN M, GEN P, long n) returns an integral (primitive) basis of the kernel of M .

GEN ZabM_indexrank(GEN M, GEN P, long n) return a vector with two `t_VECSMALL` components giving the rank profile of M . Inefficient (but correct) when M does not have almost full column rank.

GEN ZabM_inv(GEN M, GEN P, long n, GEN *pden) assume that M is invertible; return N and sets the algebraic integer `*pden` (an integer or a `ZX`, implicitly modulo P) such that $MN = \text{den} \cdot \text{Id}$.

GEN ZabM_pseudoinv(GEN M, GEN P, long n, GEN *pv, GEN *pden) analog of `ZM_pseudoinv`. Not gerepile-safe.

GEN ZabM_inv_ratlift(GEN M, GEN P, long n, GEN *pden) return a primitive matrix H such that MH is d times the identity and set `*pden` to d . Uses a multimodular algorithm, attempting rational reconstruction along the way. To be used when you expect that the denominator of M^{-1} is much smaller than $\det M$ else use `ZabM_inv`.

13.1.13 Cyclotomic trace.

Given two positive integers m and n such that $K_m = \mathbf{Q}(\zeta_m) \subset K_n = \mathbf{Q}(\zeta_n)$, these functions implement relative trace computation from K_n to K_m . This is in particular useful for character values.

GEN Qab_trace_init(long n, long m, GEN Pn, GEN Pm) assume that `Pn` is `polcyclo(n)`, `Pm` is `polcyclo(m)` (both in the same variable), initialize a structure T used in the following routines. Shallow function.

GEN Qab_tracerel(GEN T, long t, GEN z) assume T was created by `Qab_trace_init`, t is an integer such that $0 \leq t < [K_n : K_m]$ and z belongs to the cyclotomic field $\mathbf{Q}(\zeta_n) = \mathbf{Q}[X]/(\text{Pn})$. Return the normalized relative trace $[K_n : K_m]^{-1} \text{Tr}_{K_n/K_m}(\zeta_n^t z)$. Shallow function.

GEN QabV_tracerel(GEN T, long t, GEN v) v being a vector of entries belonging to K_n , apply `Qab_tracerel` to all entries. Shallow function.

GEN QabM_tracerel(GEN T, long t, GEN m) m being a matrix of entries belonging to K_n , apply `Qab_tracerel` to all entries. Shallow function.

13.1.14 Elements in factored form.

Computational algebraic theory performs extensively linear algebra on \mathbf{Z} -modules with a natural multiplicative structure (K^* , fractional ideals in K , \mathbf{Z}_K^* , ideal class group), thereby raising elements to horrendously large powers. A seemingly innocuous elementary linear algebra operation like $C_i \leftarrow C_i - 10000C_1$ involves raising entries in C_1 to the 10000-th power. Understandably, it is often more efficient to keep elements in factored form rather than expand every such expression. A *factorization matrix* (or *famat*) is a two column matrix, the first column containing *elements* (arbitrary objects which may be repeated in the column), and the second one contains *exponents* (`t_INTs`, allowed to be 0). By abuse of notation, the empty matrix `cgetg(1, t_MAT)` is recognized as the trivial factorization (no element, no exponent).

Even though we think of a *famat* with columns g and e as one meaningful object when fully expanded as $\prod g[i]^{e[i]}$, *famats* are basically about concatenating information to keep track of linear algebra: the objects stored in a *famat* need not be operation-compatible, they will not even be compared to each other (with one exception: `famat_reduce`). Multiplying two *famats* just concatenates their elements and exponents columns. In a context where a *famat* is expected, an object x which is not of type `t_MAT` will be treated as the factorization x^1 . The following functions all return *famats*:

`GEN famat_mul(GEN f, GEN g)` f, g are *famat*, or objects whose type is *not* `t_MAT` (understood as f^1 or g^1). Returns fg . The empty factorization is the neutral element for *famat* multiplication.

`GEN famat_mul_shallow(GEN f, GEN g)` shallow version of `famat_mul`.

`GEN famat_pow(GEN f, GEN n)` n is a `t_INT`. If f is a `t_MAT`, assume it is a *famat* and return f^n (multiplies the exponent column by n). Otherwise, understand it as an element and returns the 1-line *famat* f^n .

`GEN famat_pow_shallow(GEN f, GEN n)` shallow version of `famat_pow`.

`GEN famat_pows_shallow(GEN f, long n)` shallow version of `famat_pow` where n is a small integer.

`GEN famat_mulpow_shallow(GEN f, GEN g, GEN e)` *famat* corresponding to $f \cdot g^e$. Shallow function.

`GEN famat_mulpows_shallow(GEN f, GEN g, long e)` *famat* shallow version of `famat_mulpow` where e is a small integer.

`GEN famat_sqr(GEN f)` returns f^2 .

`GEN famat_inv(GEN f)` returns f^{-1} .

`GEN famat_div(GEN f, GEN g)` return f/g .

`GEN famat_inv_shallow(GEN f)` shallow version of `famat_inv`.

`GEN famat_div_shallow(GEN f, GEN g)` return f/g ; shallow.

`GEN famat_Z_gcd(GEN M, GEN n)` restrict the *famat* M to the prime powers dividing n .

`GEN to_famat(GEN x, GEN k)` given an element x and an exponent k , returns the *famat* x^k .

`GEN to_famat_shallow(GEN x, GEN k)` same, as a shallow function.

`GEN Z_to_famat(GEN x)` converts the `t_INT` x to a *famat*. This does not factor x but will replace it by y^k with y integral and k maximal. Note that 0 gets converted to 0^1 . Shallow function.

GEN `Q_to_famat`(GEN `x`) converts the `t_INT` or `t_FRAC` `x` to a *famat*. If `x` is a `t_INT`, as `Z_to_famat`. Else, this does not factor `x` but will replace it by $y^a z^{-b}$ with integral `y` and `z` and maximal (positive) `a` and `b`. Shallow function.

GEN `famatV_factorback`(GEN `v`, GEN `e`) given a vector of *famats* `v` and a ZV `e` return the *famat* $\prod_i v[i]^{e[i]}$. Shallow function.

GEN `famatV_zv_factorback`(GEN `v`, GEN `e`) given a vector of *famats* `v` and a zv `e` return the *famat* $\prod_i v[i]^{e[i]}$. Shallow function.

GEN `ZM_famat_limit`(GEN `f`, GEN `limit`) given a *famat* `f` with `t_INT` entries, returns a *famat* `g` with all factors larger than `limit` multiplied out as the last entry (with exponent 1). Shallow function.

Note that it is trivial to break up a *famat* into its two constituent columns: `gel(f,1)` and `gel(f,2)` are the elements and exponents respectively. Conversely, `mkmat2` builds a (shallow) *famat* from two `t_COLs` of the same length.

GEN `famat_reduce`(GEN `f`) given a *famat* `f`, returns a *famat* `g` without repeated elements or 0 exponents, such that the expanded forms of `f` and `g` would be equal. Shallow function.

GEN `famat_remove_trivial`(GEN `f`) given a *famat* `f`, returns a *famat* `g` without 0 exponents. Shallow function.

GEN `famatsmall_reduce`(GEN `f`) as `famat_reduce`, but for exponents given by a `t_VECSMALL`.

GEN `famat_to_nf`(GEN `nf`, GEN `f`) You normally never want to do this! This is a simplified form of `nfactorback`, where we do not check the user input for consistency. The elements must be regular algebraic numbers (not *famats*) over the given number field.

Why should you *not* want to use this function ? You should not need to: most of the functions useful in this context accept *famats* as inputs, for instance `nfsign`, `nfsign_arch`, `ideallog` and `bnfisunit`. Otherwise, we can hopefully make good use of a quotient operation (modulo a fixed conductor, modulo ℓ -th powers); see the end of Section 13.1.26. If nothing else works, this function is available but is expected to be slow or even overflow the possibilities of the implementation.

GEN `famat_idealfactor`(GEN `nf`, GEN `x`) This is a good alternative for `famat_to_nf`, returning the factorization of the ideal generated by `x`. Since the answer is still given in factorized form, there is no risk of coefficient explosion when the exponents are large. Of course, all components of `x` must be factored individually.

GEN `famat_nfvalrem`(GEN `nf`, GEN `x`, GEN `pr`, GEN `*py`) return the valuation `v` at `pr` of `famat_to_nf(x)`, without performing the expansion of course. Notice that the output is a GEN since it cannot be assumed to fit into a `long`. If `py` is not NULL it contains the *famat* obtained by applying `nfvalrem` to each entry of the first column and copying the second column, with 0 exponents removed. The expanded algebraic number is coprime to `pr` (in fact, all its components are coprime to `pr`) and equal to $x\tau^v$ where τ is the fixed anti-uniformizer for `pr` (`pr_get_tau`).

Caveat. Receiving a *famat* input, `bnfisunit` assumes that it is an actual unit, since this is expensive to check, and normally easy to ensure from the user's side.

13.1.15 Ideal arithmetic.

Conversion to HNF.

`GEN idealhnf(GEN nf, GEN x)` where the argument `nf` is a true *nf* structure. Returns the HNF of the ideal defined by x : x may be an algebraic number (defining a principal ideal), a maximal ideal (as given by `idealprimedec` or `idealfactor`), or a matrix whose columns give generators for the ideal. This last format is complicated, but useful to reduce general modules to the canonical form once in a while:

- if strictly less than $N = [K : Q]$ generators are given, x is the \mathbf{Z}_K -module they generate,
- if N or more are given, it is assumed that they form a \mathbf{Z} -basis (that the matrix has maximal rank N). This acts as `mathnf` since the \mathbf{Z}_K -module structure is (taken for granted hence) not taken into account in this case.

Extended ideals are also accepted, their principal part being discarded.

`GEN idealhnf0(GEN nf, GEN x, GEN y)` returns the HNF of the ideal generated by the two algebraic numbers x and y .

The following low-level functions underlie the above two: they all assume that `nf` is a true *nf* and perform no type checks:

`GEN idealhnf_principal(GEN nf, GEN x)` returns the ideal generated by the algebraic number x .

`GEN idealhnf_shallow(GEN nf, GEN x)` is `idealhnf` except that the result may not be suitable for `gerepile`: if x is already in HNF, we return x , not a copy!

`GEN idealhnf_two(GEN nf, GEN v)` assuming $a = v[1]$ is a nonzero `t_INT` and $b = v[2]$ is an algebraic integer, possibly given in regular representation by a `t_MAT` (the multiplication table by b , see `zk_multable`), returns the HNF of $a\mathbf{Z}_K + b\mathbf{Z}_K$.

Operations.

The basic ideal routines accept all *nfs* (*nf*, *bnf*, *bnr*) and ideals in any form, including extended ideals, and return ideals in HNF, or an extended ideal when that makes sense:

`GEN idealadd(GEN nf, GEN x, GEN y)` returns $x + y$.

`GEN idealdiv(GEN nf, GEN x, GEN y)` returns x/y . Returns an extended ideal if x or y is an extended ideal.

`GEN idealmul(GEN nf, GEN x, GEN y)` returns xy . Returns an extended ideal if x or y is an extended ideal.

`GEN idealsqr(GEN nf, GEN x)` returns x^2 . Returns an extended ideal if x is an extended ideal.

`GEN idealinv(GEN nf, GEN x)` returns x^{-1} . Returns an extended ideal if x is an extended ideal.

`GEN idealpow(GEN nf, GEN x, GEN n)` returns x^n . Returns an extended ideal if x is an extended ideal.

`GEN idealpows(GEN nf, GEN ideal, long n)` returns x^n . Returns an extended ideal if x is an extended ideal.

`GEN idealmulred(GEN nf, GEN x, GEN y)` returns an extended ideal equal to xy .

`GEN idealpowred(GEN nf, GEN x, GEN n)` returns an extended ideal equal to x^n .

More specialized routines suffer from various restrictions:

`GEN idealdivexact(GEN nf, GEN x, GEN y)` returns x/y , assuming that the quotient is an integral ideal. Much faster than `idealdiv` when the norm of the quotient is small compared to Nx . Strips the principal parts if either x or y is an extended ideal.

`GEN idealdivpowprime(GEN nf, GEN x, GEN pr, GEN n)` returns $x\mathfrak{p}^{-n}$, assuming x is an ideal in HNF or a rational number, and `pr` a *prid* attached to `p`. Not suitable for `gerepileupto` since it returns x when $n = 0$. The `nf` argument must be a true *nf* structure.

`GEN idealmulpowprime(GEN nf, GEN x, GEN pr, GEN n)` returns $x\mathfrak{p}^n$, assuming x is an ideal in HNF or a rational number, and `pr` a *prid* attached to `p`. Not suitable for `gerepileupto` since it returns x when $n = 0$. The `nf` argument must be a true *nf* structure.

`GEN idealprodprime(GEN nf, GEN v)` given a list v of prime ideals in *prid* form, return their product. Assume that `nf` is a true *nf* structure.

`GEN idealprod(GEN nf, GEN v)` given a list v of ideals, return their product.

`GEN idealprodval(GEN nf, GEN v, GEN pr)` given a list v of ideals return the valuation of their product at the prime ideal `pr`.

`GEN idealHNF_mul(GEN nf, GEN x, GEN y)` returns xy , assuming that `nf` is a true *nf*, x is an integral ideal in HNF and y is an integral ideal in HNF or precompiled form (see below). For maximal speed, the second ideal y may be given in precompiled form $y = [a, b]$, where a is a nonzero `t_INT` and b is an algebraic integer in regular representation (a `t_MAT` giving the multiplication table by the fixed element): very useful when many ideals x are going to be multiplied by the same ideal y . This essentially reduces each ideal multiplication to an $N \times N$ matrix multiplication followed by a $N \times 2N$ modular HNF reduction (modulo $xy \cap \mathbf{Z}$).

`GEN idealHNF_inv(GEN nf, GEN I)` returns I^{-1} , assuming that `nf` is a true *nf* and x is a fractional ideal in HNF.

`GEN idealHNF_inv_Z(GEN nf, GEN I)` returns $(I \cap \mathbf{Z}) \cdot I^{-1}$, assuming that `nf` is a true *nf* and x is an integral fractional ideal in HNF. The result is an integral ideal in HNF.

`GEN ideals_by_norm(GEN nf, GEN N)` given a true *nf* structure and a integer N , which can also be given by a factorization matrix or (preferably) by a pair $[N, \text{factor}(N)]$, return all ideals of norm N in factored form. Not `gerepile` clean.

Approximation.

`GEN idealaddtoone(GEN nf, GEN A, GEN B)` given to coprime integer ideals A, B , returns $[a, b]$ with $a \in A, b \in B$, such that $a + b = 1$. The result is reduced mod AB , so a, b will be small.

`GEN idealaddtoone_i(GEN nf, GEN A, GEN B)` as `idealaddtoone` except that `nf` must be a true *nf*, and only a is returned.

`GEN idealaddtoone_raw(GEN nf, GEN A, GEN B)` as `idealaddtoone_i` except that the reduction mod AB is only performed modulo the lcm of $A \cap \mathbf{Z}$ and $B \cap \mathbf{Z}$, which will increase the size of a .

`GEN zkchineseinit(GEN nf, GEN A, GEN B, GEN AB)` given two coprime integral ideals A and B (in any form, preferably HNF) and their product AB (in HNF form), initialize a solution to the Chinese remainder problem modulo AB . The `nf` argument must be a true *nf* structure.

`GEN zkchinese(GEN zkc, GEN x, GEN y)` given `zkc` from `zkchineseinit`, and x, y two integral elements given as `t_INT` or `ZC`, return a z modulo AB such that $z = x \bmod A$ and $z = y \bmod B$.

GEN `zkchinese1`(GEN `zkc`, GEN `x`) as `zkchinese` for $y = 1$; useful to lift elements in a nice way from $(\mathbf{Z}_K/A_i)^*$ to $(\mathbf{Z}_K/\prod_i A_i)^*$.

GEN `hnfmerge_get_1`(GEN `A`, GEN `B`) given two square upper HNF integral matrices A, B of the same dimension $n > 0$, return a in the image of A such that $1 - a$ is in the image of B . (By abuse of notation we denote 1 the column vector $[1, 0, \dots, 0]$.) If such an a does not exist, return `NULL`. This is the function underlying `idealaddtoone`.

GEN `idealaddmultoone`(GEN `nf`, GEN `v`) given a list of n (globally) coprime integer ideals $(v[i])$ returns an n -dimensional vector a such that $a[i] \in v[i]$ and $\sum a[i] = 1$. If $[K : \mathbf{Q}] = N$, this routine computes the HNF reduction (with $Gl_{nN}(\mathbf{Z})$ base change) of an $N \times nN$ matrix; so it is well worth pruning "useless" ideals from the list (as long as the ideals remain globally coprime).

GEN `idealapprfact`(GEN `nf`, GEN `fx`) as `idealappr`, except that x *must* be given in factored form. (This is unchecked.)

GEN `idealcoprime`(GEN `nf`, GEN `x`, GEN `y`). Given 2 integral ideals x and y , returns an algebraic number α such that αx is an integral ideal coprime to y .

GEN `idealcoprimefact`(GEN `nf`, GEN `x`, GEN `fy`) same as `idealcoprime`, except that y is given in factored form, as from `idealfactor`.

GEN `idealchinese`(GEN `nf`, GEN `x`, GEN `y`)

GEN `idealchineseinit`(GEN `nf`, GEN `x`)

13.1.16 Maximal ideals.

The PARI structure attached to maximal ideals is a *prid* (for *prime ideal*), usually produced by `idealprimedec` and `idealfactor`. In this section, we describe the format; other sections will deal with their daily use.

A *prid* attached to a maximal ideal \mathfrak{p} stores the following data: the underlying rational prime p , the ramification degree $e \geq 1$, the residue field degree $f \geq 1$, a p -uniformizer π with valuation 1 at \mathfrak{p} and valuation 0 at all other primes dividing p and a rescaled "anti-uniformizer" τ used to compute valuations. This τ is an algebraic integer such that τ/p has valuation -1 at \mathfrak{p} and is integral at all other primes; in particular, the valuation of $x \in \mathbf{Z}_K$ is positive if and only if the algebraic integer $x\tau$ is divisible by p (easy to check for elements in `t_COL` form).

GEN `pr_get_p`(GEN `pr`) returns p . Shallow function.

GEN `pr_get_gen`(GEN `pr`) returns π . Shallow function.

long `pr_get_e`(GEN `pr`) returns e .

long `pr_get_f`(GEN `pr`) returns f .

GEN `pr_get_tau`(GEN `pr`) returns `zk_scalar_or_multable(nf, τ)`, which is the `t_INT` 1 iff p is inert, and a ZM otherwise. Shallow function.

int `pr_is_inert`(GEN `pr`) returns 1 if p is inert, 0 otherwise.

GEN `pr_norm`(GEN `pr`) returns the norm p^f of the maximal ideal.

ulong `upr_norm`(GEN `pr`) returns the norm p^f of the maximal ideal, as an `ulong`. Assume that the result does not overflow.

GEN `pr_hnf`(GEN `pr`) return the HNF of \mathfrak{p} .

GEN `pr_inv`(GEN `pr`) return the fractional ideal \mathfrak{p}^{-1} , in HNF.

GEN `pr_inv_p`(GEN `pr`) return the integral ideal $p\mathfrak{p}^{-1}$, in HNF.

GEN `idealprimedec`(GEN `nf`, GEN `p`) list of maximal ideals dividing the prime p .

GEN `idealprimedec_limit_f`(GEN `nf`, GEN `p`, long `f`) as `idealprimedec`, limiting the list to primes of residual degree $\leq f$ if f is nonzero.

GEN `idealprimedec_limit_norm`(GEN `nf`, GEN `p`, GEN `B`) as `idealprimedec`, limiting the list to primes of norm $\leq B$, which must be a positive `t_INT`.

GEN `idealprimedec_galois`(GEN `nf`, GEN `p`) return a single prime ideal above p . The `nf` argument is a true `nf` structure.

GEN `idealprimedec_degrees`(GEN `nf`, GEN `p`) return a (sorted) `t_VECSMALL` containing the residue degrees $f(\mathfrak{p}/p)$. The `nf` argument is a true `nf` structure.

GEN `idealprimedec_kummer`(GEN `nf`, GEN `Ti`, long `ei`, GEN `p`) let `nf` (true `nf`) correspond to $K = \mathbf{Q}[X]/(T)$ (T monic $\mathbf{Z}[X]$). Let $T \equiv \prod_i T_i^{e_i} \pmod{p}$ be the factorization of T and let (f, g, h) be as in Dedekind criterion for prime p : $f \equiv \prod T_i$, $g \equiv \prod T_i^{e_i-1}$, $h = (T - fg)/p$, and let D be the gcd of (f, g, h) in $\mathbf{F}_p[X]$. Let `Ti` (`FpX`) be one irreducible factor T_i not dividing D , with `ei` = e_i . This function returns the prime ideal attached to T_i by Kummer / Dedekind criterion, namely $p\mathbf{Z}_K + T_i(\bar{X})\mathbf{Z}_K$, which has ramification index e_i over p . The `nf` argument is a true `nf` structure. Shallow function.

GEN `idealfactor`(GEN `nf`, GEN `x`) factors the fractional (hence nonzero) ideal x into prime ideal powers; return the factorization matrix.

GEN `idealfactor_limit`(GEN `nf`, GEN `x`, ulong `lim`) as `idealfactor`, including only prime ideals above rational primes $< \text{lim}$.

GEN `idealfactor_partial`(GEN `nf`, GEN `x`, GEN `L`) return partial factorization of fractional ideal x as limited by argument L :

- $L = \text{NULL}$: as `idealfactor`;
- L a `t_INT`: as `idealfactor_limit`;

- L a vector of prime ideals of `nf` and/or rational primes (standing for “all prime ideal divisors of given rational prime”) limit factorization to trial division by elements of L ; do not include the cofactor. For efficiency, the list should not contain the same element twice, nor both a rational prime and one of its prime ideal divisors, but the function will work in that case as well.

GEN `idealHNF_Z_factor`(GEN `x`, GEN `*pvN`, GEN `*pvZ`) given an integral (nonzero) ideal x in HNF, compute both the factorization of Nx and of $x \cap \mathbf{Z}$. This returns the vector of prime divisors of both and sets `*pvN` and `*pvZ` to the corresponding `t_VECSMALL` vector of exponents for the factorization for the Norm and intersection with \mathbf{Z} respectively.

GEN `idealHNF_Z_factor_i`(GEN `x`, GEN `fa`, GEN `*pvN`, GEN `*pvZ`) internal variant of `idealHNF_Z_factor` where `fa` is either a partial factorization of $x \cap \mathbf{Z}$ ($= x[1, 1]$) or `NULL`. Returns the prime divisors of x above the rational primes in `fa` and attached `vn` and `vZ`. If `fa` is `NULL`, use the full factorization, i.e. identical to `idealHNF_Z_factor`.

GEN `nf_pV_to_prV`(GEN `nf`, GEN `P`) given a vector of rational primes P , return the vector of all prime ideals above the $P[i]$.

GEN nf_deg1_prime(GEN nf) let *nf* be a true *nf*. This function returns a degree 1 (unramified) prime ideal not dividing *nf.index*. In fact it returns an ideal above the smallest prime $p \geq [K : \mathbf{Q}]$ satisfying those conditions.

GEN prV_lcm_capZ(GEN L) given a vector *L* of *prid* (maximal ideals) return the squarefree positive integer generating their lcm intersected with \mathbf{Z} . Not **gerepile-safe**.

GEN prV_primes(GEN) GEN L given a vector of *prid*, return the (sorted) list of rational primes *P* they divide. Not **gerepile-clean** but suitable for **gerepileupto**.

GEN pr_uniformizer(GEN pr, GEN F) given a *prid* attached to \mathfrak{p}/p and *F* in \mathbf{Z} divisible exactly by *p*, return an *F*-uniformizer for *pr*, i.e. a *t* in \mathbf{Z}_K such that $v_{\mathfrak{p}}(t) = 1$ and $(t, F/\mathfrak{p}) = 1$. Not **gerepile-safe**.

13.1.17 Decomposition groups.

GEN idealramfrobenius(GEN nf, GEN gal, GEN pr, GEN ram) Let *K* be the number field defined by *nf* and assume K/\mathbf{Q} be a Galois extension with Galois group given **gal=galoisinit(nf)**, and that *pr* is the prime ideal \mathfrak{P} in *prid* format, and that \mathfrak{P} is ramified, and *ram* is its list of ramification groups as output by **idealramgroups**. This function returns a permutation of **gal.group** which defines an automorphism σ in the decomposition group of \mathfrak{P} such that if *p* is the unique prime number in \mathfrak{P} , then $\sigma(x) \equiv x^p \pmod{\mathbf{P}}$ for all $x \in \mathbf{Z}_K$.

GEN idealramfrobenius_aut(GEN nf, GEN gal, GEN pr, GEN ram, GEN aut) as **idealramfrobenius(nf, gal, pr, ram)**.

GEN idealramgroups_aut(GEN nf, GEN gal, GEN pr, GEN aut) as **idealramgroups(nf, gal, pr)**.

GEN idealfrobenius_aut(GEN nf, GEN gal, GEN pr, GEN aut) faster version of **idealfrobenius(nf, gal, pr)** where *aut* must be equal to **nfgaloispermtobasis(nf, gal)**.

13.1.18 Reducing modulo maximal ideals.

GEN nfmodprinit(GEN nf, GEN pr) returns an abstract **modpr** structure, attached to reduction modulo the maximal ideal *pr*, in **idealprimedec** format. From this data we can quickly project any *pr*-integral number field element to the residue field.

GEN modpr_get_pr(GEN x) return the *pr* component from a **modpr** structure.

GEN modpr_get_p(GEN x) return the *p* component from a **modpr** structure (underlying rational prime).

GEN modpr_get_T(GEN x) return the *T* component from a **modpr** structure: either NULL (prime of degree 1) or an irreducible **FpX** defining the residue field over \mathbf{F}_p .

In library mode, it is often easier to use directly

GEN nf_to_Fq_init(GEN nf, GEN *ppr, GEN *pT, GEN *pp) concrete version of **nfmodprinit**: *nf* and **ppr* are the inputs, the return value is a **modpr** and **ppr*, **pT* and **pp* are set as side effects.

The input **ppr* is either a maximal ideal or already a **modpr** (in which case it is replaced by the underlying maximal ideal). The residue field is realized as $\mathbf{F}_p[X]/(T)$ for some monic $T \in \mathbf{F}_p[X]$, and we set **pT* to *T* and **pp* to *p*. Set *T* = NULL if the prime has degree 1 and the residue field is \mathbf{F}_p .

In short, this receives (or initializes) a `modpr` structure, and extracts from it T , p and \mathfrak{p} .

`GEN nf_to_Fq(GEN nf, GEN x, GEN modpr)` returns an `Fq` congruent to x modulo the maximal ideal attached to `modpr`. The output is canonical: all elements in a given residue class are represented by the same `Fq`.

`GEN Fq_to_nf(GEN x, GEN modpr)` returns an `nf` element lifting the residue field element x , either a `t_INT` or an algebraic integer in `algtobasis` format.

`GEN modpr_genFq(GEN modpr)` Returns an `nf` element whose image by `nf_to_Fq` is $X \pmod{T}$, if $\deg T > 1$, else 1.

`GEN zkmodprinit(GEN nf, GEN pr)` as `nfmodprinit`, but we assume we will only reduce algebraic integers, hence do not initialize data allowing to remove denominators. More precisely, we can in fact still handle an x whose rational denominator is not 0 in the residue field (i.e. if the valuation of x is nonnegative at all primes dividing p).

`GEN zk_to_Fq_init(GEN nf, GEN *pr, GEN *T, GEN *p)` as `nf_to_Fq_init`, able to reduce only p -integral elements.

`GEN zk_to_Fq(GEN x, GEN modpr)` as `nf_to_Fq`, for a p -integral x .

`GEN nfM_to_FqM(GEN M, GEN nf, GEN modpr)` reduces a matrix of `nf` elements to the residue field; returns an `FqM`.

`GEN FqM_to_nfM(GEN M, GEN modpr)` lifts an `FqM` to a matrix of `nf` elements.

`GEN nfV_to_FqV(GEN A, GEN nf, GEN modpr)` reduces a vector of `nf` elements to the residue field; returns an `FqV` with the same type as A (`t_VEC` or `t_COL`).

`GEN FqV_to_nfV(GEN A, GEN modpr)` lifts an `FqV` to a vector of `nf` elements (same type as A).

`GEN nfX_to_FqX(GEN Q, GEN nf, GEN modpr)` reduces a polynomial with `nf` coefficients to the residue field; returns an `FqX`.

`GEN FqX_to_nfX(GEN Q, GEN modpr)` lifts an `FqX` to a polynomial with coefficients in `nf`.

The following functions are technical and avoid computing a true `nfmodpr`:

`GEN pr_basis_perm(GEN nf, GEN pr)` given a true `nf` structure and a prime ideal `pr` above p , return as a `t_VEC` the $f(\mathfrak{p}/p)$ indices i such that the `nf.zk[i]` mod \mathfrak{p} form an \mathbf{F}_p -basis of the residue field.

`GEN QXQV_to_FpM(GEN v, GEN T, GEN p)` let p be a positive integer, v be a vector of n polynomials with rational coefficients whose denominators are coprime to p , and T be a `ZX` (preferably monic) of degree d whose leading coefficient is coprime to p . Return the $d \times n$ `FpM` whose columns are the $v[i] \pmod{T, p}$ in the canonical basis $1, X, \dots, X^{d-1}$, see `RgX_to_RgC`. This is for instance useful when v contains a \mathbf{Z} -basis of the maximal order of a number field $\mathbf{Q}[X]/(P)$, p is a prime not dividing the index of P and T is an irreducible factor of $P \pmod{p}$, attached to a maximal ideal \mathfrak{p} : left-multiplication by the matrix maps number field elements (in basis form) to the residue field of \mathfrak{p} .

13.1.19 Valuations.

`long nfval(GEN nf, GEN x, GEN P)` return $v_P(x)$

Unsafe functions. assume that P, Q are `prid`.

`long ZC_nfval(GEN x, GEN P)` returns $v_P(x)$, assuming x is a `ZC`, representing a nonzero algebraic integer.

`long ZC_nfvalrem(GEN x, GEN P, GEN *newx)` returns $v = v_P(x)$, assuming x is a `ZC`, representing a nonzero algebraic integer, and sets `*newx` to $x\tau^v$ which is an algebraic integer coprime to p .

`int ZC_prdvd(GEN x, GEN P)` returns 1 if P divides x and 0 otherwise. Assumes that x is a `ZC`, representing an algebraic integer. Faster than computing $v_P(x)$.

`int pr_equal(GEN P, GEN Q)` returns 1 if P and Q represent the same maximal ideal: they must lie above the same p and share the same e, f invariants, but the p -uniformizer and τ element may differ. Returns 0 otherwise.

13.1.20 Signatures.

“Signs” of the real embeddings of number field element are represented in additive notation, using the standard identification $(\mathbf{Z}/2\mathbf{Z}, +) \rightarrow (\{-1, 1\}, \times)$, $s \mapsto (-1)^s$.

With respect to a fixed `nf` structure, a selection of real places (a divisor at infinity) is normally given as a `t_VECSMALL` of indices of the roots `nf.roots` of the defining polynomial for the number field. For compatibility reasons, in particular under `GP`, the (obsolete) `vec01` form is also accepted: a `t_VEC` with `gen_0` or `gen_1` entries.

The following internal functions go back and forth between the two representations for the Archimedean part of divisors (`GP`: 0/1 vectors, library: list of indices):

`GEN vec01_to_indices(GEN v)` given a `t_VEC` v with `t_INT` entries return as a `t_VECSMALL` the list of indices i such that $v[i] \neq 0$. (Typically used with 0, 1-vectors but not necessarily so.) If v is already a `t_VECSMALL`, return it: not suitable for `gerepile` in this case.

`GEN vecsmall01_to_indices(GEN v)` as

`vec01_to_indices(zv_to_ZV(v));`

`GEN indices_to_vec01(GEN p, long n)` return the 0/1 vector of length n with ones exactly at the positions $p[1], p[2], \dots$

`GEN nfsign(GEN nf, GEN x)` x being a number field element and `nf` any form of number field, return the 0 – 1-vector giving the signs of the r_1 real embeddings of x , as a `t_VECSMALL`. Linear algebra functions like `Flv_add_inplace` then allow keeping track of signs in series of multiplications. The argument `nf` is a true `nf` structure.

If x is a `t_VEC` of number field elements, return the matrix whose columns are the signs of the $x[i]$.

`GEN nfsign_arch(GEN nf, GEN x, GEN arch)` `arch` being a list of distinct real places, either in `vec01` (`t_VEC` with `gen_0` or `gen_1` entries) or `indices` (`t_VECSMALL`) form (see `vec01_to_indices`), returns the signs of x at the corresponding places. This is the low-level function underlying `nfsign`. The argument `nf` is a true `nf` structure.

`int nfchecksigns(GEN nf, GEN x, GEN pl)` pl is a `t_VECSMALL` with r_1 components, all of which are in $\{-1, 0, 1\}$. Return 1 if $\sigma_i(x)pl[i] \geq 0$ for all i , and 0 otherwise.

`GEN nfsign_units(GEN bnf, GEN archp, int add_tu)` `archp` being a divisor at infinity in `indices` form (or `NULL` for the divisor including all real places), return the signs at `archp` of a

bnf.tu and of system of fundamental units for the field **bnf.fu**, in that order if **add_tu** is set; and in the same order as **bnf.fu** otherwise.

GEN **nfsign_fu**(GEN **bnf**, GEN **archp**) returns the signs at **archp** of the fundamental units **bnf.fu**. This is an alias for **nfsign_units** with **add_tu** unset.

GEN **nfsign_tu**(GEN **bnf**, GEN **archp**) returns the signs at **archp** of the torsion unit generator **bnf.tu**.

GEN **nfsign_from_logarch**(GEN **L**, GEN **invpi**, GEN **archp**) given **L** the vector of the $\log \sigma(x)$, where σ runs through the (real or complex) embeddings of some number field, **invpi** being a floating point approximation to $1/\pi$, and **archp** being a divisor at infinity in **indices** form, return the signs of x at the corresponding places. This is the low-level function underlying **nfsign_units**; the latter is actually a trivial wrapper **bnf** structures include the $\log \sigma(x)$ for a system of fundamental units of the field.

GEN **set_sign_mod_divisor**(GEN **nf**, GEN **x**, GEN **y**, GEN **sarch**) let $f = f_0 f_\infty$ be a divisor, let **sarch** be the output of **nfarchstar**(**nf**, **f0**, **finf**), let x encode a vector of signs at the places of f_∞ (see below), and let y be a nonzero number field element. Returns z congruent to $y \bmod f_0$ (integral if y is) such that z and x have the same signs at f_∞ . The argument **nf** is a true *nf* structure.

The following formats are supported for x : a $\{0,1\}$ -vector of signs as a **t_VECSMALL** (0 for positive, 1 for negative); **NULL** for a totally positive element (only 0s); a number field element which is replaced by its signature at f_∞ .

GEN **nfarchstar**(GEN **nf**, GEN **f0**, GEN **finf**) for a divisor $f = f_0 f_\infty$ represented by the integral ideal **f0** in HNF and the **finf** in **indices** form, returns $(\mathbf{Z}_K/f_\infty)^*$ in a form suitable for computations mod f . See **set_sign_mod_divisor**.

GEN **idealprincipalunits**(GEN **nf**, GEN **pr**, long **e**) returns the multiplicative group $(1 + pr)/(1 + pr^e)$ as an abelian group. Faster than **idealstar** when the norm of pr is large, since it avoids (useless) work in the multiplicative group of the residue field.

13.1.21 Complex embeddings.

GEN **nfembed**(GEN **nf**, GEN **x**, long **k**) returns a floating point approximation of the k -th embedding of x (attached to the k -th complex root in **nf.roots**). Note that the semantic is different from **nfeltembed** (which increases the precision of *nf* until the embeddings have the requested precision): **nfembed** provides the embedding with the precision that is achievable given *nf*.

GEN **nfeltembed_i**(GEN ***pnf**, GEN **x**, GEN **ind**, long **prec**) as **nfeltembed**, except that no garbage collecting is performed and ***pnf** must be initially set to a (true) *nf* structure and, if the routine needs to increase the accuracy of *nf* to achieve the requested accuracy **prec**, then the functions sets it to the new more precise *nf*.

GEN **nf_cxlog**(GEN **nf**, GEN **x**, long **prec**) return the vector of complex logarithmic embeddings $(e_i \log(\sigma_i X))$ where $e_i = 1$ if $i \leq r_1$ and $e_i = 2$ if $r_1 < i \leq r_2$ of $X = \mathbf{Q_primpart}(x)$. Returns **NULL** if loss of accuracy. Not **gerepile**-clean but suitable for **gerepileupto**. Allows x in compact representation, in which case **Q_primpart** is taken componentwise.

GEN **nf_cxlog_normalize**(GEN **nf**, GEN **x**, long **prec**) an *nf* structure attached to a number field K and x from **nf_cxlog**(*nf*, X) (a column vector of complex logarithmic embeddings with

$r_1 + r_2$ components) and let $e = (e_1, \dots, e_{r_1+r_2})$. Return

$$x - \frac{\log(N_{K/\mathbf{Q}}X)}{[K:\mathbf{Q}]}e$$

where the imaginary parts are further normalized modulo $2\pi i \cdot e$.

The composition `nf_cxlog` followed by `nf_cxlog_normalize` is a morphism from $(K^*/\mathbf{Q}_+^*, \times)$ to $((\mathbf{C}/2\pi i\mathbf{Z})^{r_1} \times (\mathbf{C}/4\pi i\mathbf{Z})^{r_2}, +)$. Its real part maps the units \mathbf{Z}_K^* to a lattice in the hyperplane $\sum_i x_i = 0$ in $\mathbf{R}^{r_1+r_2}$.

`GEN nfV_cxlog(GEN nf, GEN x, long prec)` applies `nf_cxlog` to each component of the vector x . Returns NULL if loss of accuracy for even one component. Not `gerepile-clean`.

`GEN nflogembed(GEN nf, GEN x, GEN *emb, long prec)` return the vector of real logarithmic embeddings $(e_i \text{Log}|\sigma_i x|)$ where $e_i = 1$ if $i \leq r_1$ and $e_i = 2$ if $r_1 < i \leq r_2$. Returns NULL if loss of accuracy. Not `gerepile-clean`. If `emb` is non-NULL set it to $(e_i \sigma_i x)$. Allows x in compact representation, in which case `emb` is returned in compact representation as well, as a factorization matrix (expanding the factorization may overflow exponents).

13.1.22 Maximal order and discriminant, conversion to `nf` structure.

A number field $K = \mathbf{Q}[X]/(T)$ is defined by a monic $T \in \mathbf{Z}[X]$. The low-level function computing a maximal order is

`void nfmaxord(nfmaxord_t *S, GEN T0, long flag)`, where the polynomial T_0 is squarefree with integer coefficients. Let K be the étale algebra $\mathbf{Q}[X]/(T_0)$ and let $T = \text{ZX_Q_normalize}(T_0)$, i.e. $T = CT_0(X/L)$ is monic and integral for some $C, Q \in \mathbf{Q}$.

The structure `nfmaxord_t` is initialized by the call; it has the following fields:

```
GEN T0, T, dT, dK; /* T0, T, discriminants of T and K */
GEN unscale; /* the integer L */
GEN index; /* index of power basis in maximal order */
GEN dTP, dTE; /* factorization of |dT|, primes / exponents */
GEN dKP, dKE; /* factorization of |dK|, primes / exponents */
GEN basis; /* Z-basis for maximal order of Q[X]/(T) */
```

The exponent vectors are `t_VECSMALL`. The primes in `dTP` and `dKP` are pseudoprimes, not proven primes. We recommend restricting to $T = T_0$, i.e. either to pass the input polynomial through `ZX_Q_normalize` *before* the call, or to forget about T_0 and go on with the polynomial T ; otherwise `unscale` $\neq 1$, all data is expressed in terms of $T \neq T_0$, and needs to be converted to T_0 . For instance to convert the basis to $\mathbf{Q}[X]/(T_0)$:

```
RgXV_unscale(S.basis, S.unscale)
```

Instead of passing T (monic `ZX`), one can use the format $[T, \text{list}P]$ as in `nfbasis` or `nfinit`, which computes an order which is maximal at a set of primes, but need not be the maximal order.

The `flag` is an or-ed combination of the binary flags, both of them deprecated:

`nf_PARTIALFACT`: do not try to fully factor `dT` and only look for primes less than `factorlimit`. In that case, the elements in `dTP` and `dKP` need not all be primes. But the resulting `dK`, `index` and `basis` are correct provided there exists no prime $p > \text{factorlimit}$ such that p^2 divides the field discriminant `dK`. This flag is *deprecated*: the $[T, \text{list}P]$ format is safer and more flexible.

`nf_ROUND2`: this flag is *deprecated* and now ignored.

`void nfinit_basic(nfmaxord_t *S, GEN T0)` a wrapper around `nfmaxord` (without the deprecated flag) that also accepts number field structures (*nf*, *bnf*, ...) for *T0*.

`GEN nfmaxord_to_nf(nfmaxord_t *S, GEN ro, long prec)` convert an `nfmaxord_t` to an *nf* structure at precision `prec`, where `ro` is `NULL`. The argument `ro` may also be set to a vector with $r_1 + r_2$ components containing the roots of $S \rightarrow T$ suitably ordered, i.e. first r_1 `t_REAL` roots, then r_2 `t_COMPLEX` representing the conjugate pairs, but this is *strongly discouraged*: the format is error-prone, and it is hard to compute the roots to the right accuracy in order to achieve `prec` accuracy for the *nf*. This function uses the integer basis $S \rightarrow \text{basis}$ as is, *without* performing LLL-reduction. Unless the basis is already known to be reduced, use rather the following higher-level function:

`GEN nfinit_complete(nfmaxord_t *S, long flag, long prec)` convert an `nfmaxord_t` to an *nf* structure at precision `prec`. The `flag` has the same meaning as in `nfinit0`. If $S \rightarrow \text{basis}$ is known to be reduced, it will be faster to use `nfmaxord_to_nf`.

`GEN indexpartial(GEN T, GEN dT)` T a monic separable $\mathbf{Z}[X]$, dT is either `NULL` (no information) or a multiple of the discriminant of T . Let $K = \mathbf{Q}[X]/(T)$ and \mathbf{Z}_K its maximal order. Returns a multiple of the exponent of the quotient group $\mathbf{Z}_K/(\mathbf{Z}[X]/(T))$. In other word, a *denominator* d such that $dx \in \mathbf{Z}[X]/(T)$ for all $x \in \mathbf{Z}_K$.

`GEN FpX_gcd_check(GEN x, GEN y, GEN D)` let x and y be two coprime polynomials with integer coefficients and let D be a factor of the resultant of x and y ; try to factor D by running the Euclidean algorithm on x and y modulo D . This returns `NULL` or a non trivial factor of D . This is the low-level function underlying `poldiscfactors` (applied to x , `ZX_deriv(x)` and the discriminant of x). It succeeds when D has at least two prime divisors p and q such that one sub-resultant of x and y is divisible by p but not by q .

13.1.23 Computing in the class group.

We compute with arbitrary ideal representatives (in any of the various formats seen above), and call

`GEN bnfisprincipal0(GEN bnf, GEN x, long flag)`. The `bnf` structure already contains information about the class group in the form $\oplus_{i=1}^n (\mathbf{Z}/d_i\mathbf{Z})g_i$ for canonical integers d_i (with $d_n \mid \dots \mid d_1$ all > 1) and essentially random generators g_i , which are ideals in HNF. We normally do not need the value of the g_i , only that they are fixed once and for all and that any (nonzero) fractional ideal x can be expressed uniquely as $x = (t) \prod_{i=1}^n g_i^{e_i}$, where $0 \leq e_i < d_i$, and (t) is some principal ideal. Computing e is straightforward, but t may be very expensive to obtain explicitly. The routine returns (possibly partial) information about the pair $[e, t]$, depending on `flag`, which is an or-ed combination of the following symbolic flags:

- `nf_GEN` tries to compute t . Returns $[e, t]$, with t an empty vector if the computation failed. This flag is normally useless in nontrivial situations since the next two serve analogous purposes in more efficient ways.

- `nf_GENMAT` tries to compute t in factored form, which is much more efficient than `nf_GEN` if the class group is moderately large; imagine a small ideal $x = (t)g^{10000}$: the norm of t has 10000 as many digits as the norm of g ; do we want to see it as a vector of huge meaningless integers? The idea is to compute e first, which is easy, then compute (t) as $x \prod g_i^{-e_i}$ using successive `idealmulred`, where the ideal reduction extracts small principal ideals along the way, eventually raised to large powers because of the binary exponentiation technique; the point is to keep this principal part in

factored *unexpanded* form. Returns $[e, t]$, with t an empty vector if the computation failed; this should be exceedingly rare, unless the initial accuracy to which **bnf** was computed was ridiculously low (and then **bnfinit** should not have succeeded either). Setting/unsetting **nf_GEN** has no effect when this flag is set.

- **nf_GEN_IF_PRINCIPAL** tries to compute t *only* if the ideal is principal ($e = 0$). Returns **gen_0** if the ideal is not principal. Setting/unsetting **nf_GEN** has no effect when this flag is set, but setting/unsetting **nf_GENMAT** is possible.

- **nf_FORCE** in the above, insist on computing t , even if it requires recomputing a **bnf** from scratch. This is a last resort, and normally the accuracy of a **bnf** can be increased without trouble, but it may be that some algebraic information simply cannot be recovered from what we have: see **bnfnewprec**. It should be very rare, though.

In simple cases where you do not care about t , you may use

GEN isprincipal(GEN bnf, GEN x), which is a shortcut for **bnfisprincipal0(bnf, x, 0)**.

The following low-level functions are often more useful:

GEN isprincipalfact(GEN bnf, GEN C, GEN L, GEN f, long flag) is about the same as **bnfisprincipal0** applied to $C \prod L[i]^{f[i]}$, where the $L[i]$ are ideals, the $f[i]$ integers and C is either an ideal or NULL (omitted). Make sure to include **nf_GENMAT** in **flag**!

GEN isprincipalfact_or_fail(GEN bnf, GEN C, GEN L, GEN f) is for delicate cases, where we must be more clever than **nf_FORCE** (it is used when trying to increase the accuracy of a *bnf*, for instance). It performs

```
isprincipalfact(bnf,C, L, f, nf_GENMAT);
```

but if it fails to compute t , it just returns a **t_INT**, which is the estimated precision (in words, as usual) that would have been sufficient to complete the computation. The point is that **nf_FORCE** does exactly this internally, but goes on increasing the accuracy of the **bnf**, then discarding it, which is a major inefficiency if you intend to compute lots of discrete logs and have selected a precision which is just too low. (It is sometimes not so bad since most of the really expensive data is cached in **bnf** anyway, if all goes well.) With this function, the *caller* may decide to increase the accuracy using **bnfnewprec** (and keep the resulting **bnf**!), or avoid the computation altogether. In any case the decision can be taken at the place where it is most likely to be correct.

void bnftestprimes(GEN bnf, GEN B) is an ingredient to certify unconditionnally a **bnf** computed assuming GRH, cf. **bnfcertify**. Running this function successfully proves that the classes of all prime ideals of norm $\leq B$ belong to the subgroup of the class group generated by the factorbase used to compute the **bnf** (equal to the class group under GRH). If the condition is not true, then (GRH is false and) the function will run forever.

If it is known that primes of norm less than B generate the class group (through variants of Minkowski's convex body or Zimmert's twin classes theorems), then the true class group is proven to be a quotient of **bnf.clgp**.

13.1.24 Floating point embeddings, the T_2 quadratic form.

We assume the nf is a true **nf** structure, attached to a number field K of degree n and signature (r_1, r_2) . We saw that

`GEN nf_get_M(GEN nf)` returns the $(r_1 + r_2) \times n$ matrix M giving the embeddings of K , so that if v is an n -th dimensional **t_COL** representing the element $\sum_{i=1}^n v[i]w_i$ of K , then `RgM_RgC_mul(M, v)` represents the embeddings of v . Its first r_1 components are real numbers (**t_INT**, **t_FRAC** or **t_REAL**, usually the latter), and the last r_2 are complex numbers (usually of **t_COMPLEX**, but not necessarily for embeddings of rational numbers).

`GEN embed_T2(GEN x, long r1)` assuming x is the vector of floating point embeddings of some algebraic number v , i.e.

```
x = RgM_RgC_mul(nf_get_M(nf), algtobasis(nf, v));
```

returns $T_2(v)$. If the floating point embeddings themselves are not needed, but only the values of T_2 , it is more efficient to restrict to real arithmetic and use

```
gnorml2( RgM_RgC_mul(nf_get_G(nf), algtobasis(nf, v)));
```

`GEN embednorm_T2(GEN x, long r1)` analogous to `embed_T2`, applied to the **gnorm** of the floating point embeddings. Assuming that

```
x = gnorm( RgM_RgC_mul(nf_get_M(nf), algtobasis(nf, v)) );
```

returns $T_2(v)$.

`GEN embed_roots(GEN z, long r1)` given a vector z of $r_1 + r_2$ complex embeddings of the algebraic number v , return the $r_1 + 2r_2$ roots of its characteristic polynomial. Shallow function.

`GEN embed_disc(GEN z, long r1, long prec)` given a vector z of $r_1 + r_2$ complex embeddings of the algebraic number v , return a floating point approximation of the discriminant of its characteristic polynomial as a **t_REAL** of precision **prec**.

`GEN embed_norm(GEN x, long r1)` given a vector z of $r_1 + r_2$ complex embeddings of the algebraic number v , return (a floating point approximation of) the norm of v .

13.1.25 Ideal reduction, low level.

In the following routines nf is a true **nf**, attached to a number field K of degree n :

`GEN nf_get_Gtwist(GEN nf, GEN v)` assuming v is a **t_VECSMALL** with $r_1 + r_2$ entries, let

$$||x||_v^2 = \sum_{i=1}^{r_1+r_2} 2^{v_i \varepsilon_i} |\sigma_i(x)|^2,$$

where as usual the σ_i are the (real and) complex embeddings and $\varepsilon_i = 1$, resp. 2, for a real, resp. complex place. This is a twisted variant of the T_2 quadratic form, the standard Euclidean form on $K \otimes \mathbf{R}$. In applications, only the relative size of the v_i will matter.

Let $G_v \in M_n(\mathbf{R})$ be a square matrix such that if $x \in K$ is represented by the column vector X in terms of the fixed **Z**-basis of \mathbf{Z}_K in nf , then

$$||x||_v^2 = {}^t(G_v X) \cdot G_v X.$$

(This is a kind of Cholesky decomposition.) This function returns a rescaled copy of G_v , rounded to nearest integers, specifically `RM_round_maxrank(G_v)`. Suitable for `gerepileupto`, but does not collect garbage. For convenience, also allow $v = \text{NULL}$ (`nf_get_roundG`) and v a `t_MAT` as output from the function itself: in both these cases, shallow function.

`GEN nf_get_Gtwist1(GEN nf, long i)`. Simple special case. Returns the twisted G matrix attached to the vector v whose entries are all 0 except the i -th one, which is equal to 10.

`GEN idealpseudomin(GEN x, GEN G)`. Let x, G be two ZMs, such that the product Gx is well-defined. This returns a “small” integral linear combinations of the columns of x , given by the LLL-algorithm applied to the lattice Gx . Suitable for `gerepileupto`, but does not collect garbage.

In applications, x is an integral ideal, G approximates a Cholesky form for the T_2 quadratic form as returned by `nf_get_Gtwist`, and we return a small element a in the lattice (x, T_2) . This is used to implement `idealred`.

`GEN idealpseudomin_nonscalar(GEN x, GEN G)`. As `idealpseudomin`, but we insist of returning a nonscalar a (`ZV_isscalar` is false), if the dimension of x is > 1 .

In the interpretation where x defines an integral ideal on a fixed \mathbf{Z}_K basis whose first element is 1, this means that a is not rational.

`GEN idealpseudominvec(GEN x, GEN G)`. As `idealpseudomin_nonscalar`, but we return about $n^2/2$ nonscalar elements in x with small T_2 -norm, where the dimension of x is n .

`GEN idealpseudored(GEN x, GEN G)`. As `idealpseudomin` but we return the full reduced \mathbf{Z} -basis of x as a `t_MAT` instead of a single vector.

`GEN idealred_elt(GEN nf, GEN x)` shortcut for

`idealpseudomin(x, nf_get_roundG(nf))`

13.1.26 Ideal reduction, high level.

Given an ideal x this means finding a “simpler” ideal in the same ideal class. The public GP function is of course available

`GEN idealred0(GEN nf, GEN x, GEN v)` finds an $a \in K^*$ such that $(a)x$ is integral of small norm and returns it, as an ideal in HNF. What “small” means depends on the parameter v , see the GP description. More precisely, a is returned by `idealpseudomin(($x_{\mathbf{Z}}$) $x^v - 1$), G)` divided by $x_{\mathbf{Z}}$, where $x_{\mathbf{Z}} = (x \cap \mathbf{Z})$ and where G is `nf_get_Gtwist(nf, v)` for $v \neq \text{NULL}$ and `nf_get_roundG(nf)` otherwise.

Usually one sets $v = \text{NULL}$ to obtain an element of small T_2 norm in x :

`GEN idealred(GEN nf, GEN x)` is a shortcut for `idealred0(nf, x, NULL)`.

The function `idealred` remains complicated to use: in order not to lose information x must be an extended ideal, otherwise the value of a is lost. There is a subtlety here: the principal ideal (a) is easy to recover, but a itself is an instance of the principal ideal problem which is very difficult given only an nf (once a bnf structure is available, `bnfisprincipal0` will recover it).

`GEN idealmoddivisor(GEN bnr, GEN x)` A proof-of-concept implementation, useless in practice. If `bnr` is attached to some modulus f , returns a “small” ideal in the same class as x in the ray class group modulo f . The reason why this is useless is that using extended ideals with principal part in a computation, there is a simple way to reduce them: simply reduce the generator of the principal part in $(\mathbf{Z}_K/f)^*$.

`GEN famat_to_nf_moddivisor(GEN nf, GEN g, GEN e, GEN bid)` given a true nf attached to a number field K , a bid structure attached to a modulus f , and an algebraic number in factored form $\prod g[i]^{e[i]}$, such that $(g[i], f) = 1$ for all i , returns a small element in \mathbf{Z}_K congruent to it mod f . Note that if f contains places at infinity, this includes sign conditions at the specified places.

A simpler case when the conductor has no place at infinity:

`GEN famat_to_nf_modideal_coprime(GEN nf, GEN g, GEN e, GEN f, GEN expo)` as above except that the ideal f is now integral in HNF (no need for a full bid), and we pass the exponent of the group $(\mathbf{Z}_K/f)^*$ as `expo`; any multiple will also do, at the expense of efficiency. Of course if a bid for f is available, it is easy to extract f and the exact value of `expo` from it (the latter is the first elementary divisor in the group structure). A useful trick: if you set `expo` to *any* positive integer, the result is correct up to `expo`-th powers, hence exact if `expo` is a multiple of the exponent; this is useful when trying to decide whether an element is a square in a residue field for instance! (take `expo=2`).

`GEN nf_to_Fp_coprime(GEN nf, GEN x, GEN modpr)` this low-level function is variant of `famat_to_nf_modideal_coprime`: nf is a true nf structure, `modpr` is from `zkmodprinit` attached to a prime of degree 1 above the prime number p , and x is either a number field element or a `famat` factorization matrix. We finally assume that no component of x has a denominator p .

What to do when the $g[i]$ are not coprime to f , but only $\prod g[i]^{e[i]}$ is? Then the situation is more complicated, and we advise to solve it one prime divisor of f at a time. Let v be the valuation attached to a maximal ideal `pr`:

`GEN famat_makecoprime(GEN nf, GEN g, GEN e, GEN pr, GEN prk, GEN expo)` returns an element in $(\mathbf{Z}_K/\mathfrak{pr}^k)^*$ congruent to the product $\prod g[i]^{e[i]}$, assumed to be globally coprime to `pr`. As above, `expo` is any positive multiple of the exponent of $(\mathbf{Z}_K/\mathfrak{pr}^k)^*$, for instance $(Nv-1)p^{k-1}$, if p is the underlying rational prime. You may use other values of `expo` (see the useful trick in `famat_to_nf_modideal_coprime`).

`GEN sunits_makecoprime(GEN g, GEN pr, GEN prk)` is a specialized variant that allows to precondition a vector of $g[i]$ assumed to be integral primes or algebraic integers so that it becomes suitable for `famat_to_nf_modideal_coprime` modulo `pr`. This is in particular useful for the output of `bnf_get_sunits`.

`GEN Idealstarprk(GEN nf, GEN pr, long k, long flag)` same as `Idealstar` for $I = \mathfrak{pr}^k$. The `nf` argument is a true nf structure.

13.1.27 Class field theory.

Under GP, a class-field theoretic description of a number field is given by a triple A, B, C , where the defining set $[A, B, C]$ can have any of the following forms: $[bnr]$, $[bnr, subgroup]$, $[bnf, modulus]$, $[bnf, modulus, subgroup]$. You can still use directly all of (`libpari`'s routines implementing) GP's functions as described in Chapter 3, but they are often awkward in the context of `libpari` programming. In particular, it does not make much sense to always input a triple A, B, C because of the fringe $[bnf, modulus, subgroup]$. The first routine to call, is thus

`GEN Buchray(GEN bnf, GEN mod, long flag)` initializes a bnr structure from `bnf` and modulus `mod`. `flag` is an or-ed combination of `nf_GEN` (include generators) and `nf_INIT` (if omitted, do not return a bnr , only the ray class group as an abelian group). In fact, the single most useful value of `flag` is `nf_INIT` to initialize a proper bnr : omitting `nf_GEN` saves a lot of time and will not adversely affect any class field theoretic function; adding `nf_GEN` makes debugging easier. The flag

0 allows to compute only the ray class group structure but will gain little time; if we only need the *order* of the ray class group, then `bnrclassno` is fastest.

Now we have a proper *bnr* encoding a *bnf* and a modulus, we no longer need the `[bnf, modulus]` and `[bnf, modulus, subgroup]` forms, which would internally call `Buchray` anyway. Recall that a subgroup H is given by a matrix in HNF, whose column express generators of H on the fixed generators of the ray class group that stored in our *bnr*. You may also code the trivial subgroup by `NULL`. It is also allowed to replace H by a character χ of the ray class group modulo *mod*: it represents the subgroup $\text{Ker}\chi$.

`GEN bnr_subgroup_check(GEN bnr, GEN H, GEN *pdeg)` given a *bnr* attached to a modulus *mod*, check whether H represents a congruence subgroup (of the ray class group modulo *mod*) and returns a normalized representation: `NULL` for the trivial subgroup, or in HNF, reduced modulo the elementary divisors of the ray class group. In particular, if H is a character of the ray class group, the returned value is the character kernel. If *pdeg* is not `NULL`, **pdeg* is set to the degree of the attached class field: the index of H in the ray class group.

`void bnr_subgroup_sanitize(GEN *pbnr, GEN *pH)` given a *bnr* and a congruence subgroup, make sanity checks and compute the subgroup conductor. Then replace the pair to match the conductor: the *bnr* has the right conductor as modulus, and the subgroup is normalized. Instead of a *bnr*, this function also accepts a *bnf* (gets replaced by the *bnr* with trivial conductor). Instead of a subgroup, the function also accepts an integer N (replaced by $\text{Cl}_f(K)^N$) or a character (replaced by its kernel).

`void bnr_char_sanitize(GEN *pbnr, GEN *pchi)` same idea as `bnr_subgroup_sanitize`: we are given a *bnr* and a ray class character, make sanity checks and update the data to use the conductor as modulus.

`GEN bnrconductor(GEN bnr, GEN H, long flag)` see the documentation of the `GP` function.

`GEN bnrconductor_factored(GEN bnr, GEN H)` return a pair $[F, fa]$ where F is the conductor and fa is the factorization of the finite part of the conductor. Shallow function.

`GEN bnrconductor_raw(GEN bnr, GEN H)` return the conductor of H . Shallow function.

`long bnrconductor(GEN bnr, GEN H)` returns 1 if the class field defined by the subgroup H (of the ray class group mod f coded in *bnr*) has conductor f . Returns 0 otherwise.

`GEN ideallog_units(GEN bnf, GEN bid)` return the images of the units generators *bnf.tu* and *bnf.tu* in the finite abelian group $(\mathbf{Z}_K/f)^*$ attached to *bid*.

`GEN ideallog_units0(GEN bnf, GEN bid, GEN N)` let $G = (\mathbf{Z}_K/f)^*$ be the finite abelian group attached to *bid*. Return the images of the units generators *bnf.tu* and *bnf.tu* in G/G^N . If N is `NULL`, same as `ideallog_units`.

`GEN bnrchar_primitive(GEN bnr, GEN chi, GEN bnrc)` Given a normalized character $\chi = [d, c]$ on *bnr.clgp* (see `char_normalize`) of conductor *bnrc.mod*, compute the primitive character χ_{ic} on *bnrc.clgp* equivalent to χ , given as a normalized character $[D, C]$: $\chi_{\text{ic}}(\text{bnrc.gen}[i])$ is $\zeta_D^{C[i]}$, where D is minimal. It is easier to use `bnrconductor_i(bnr, chi, 2)`, but the latter recomputes *bnrc* for each new character.

`GEN bnrchar_primitive_raw(GEN bnr, GEN chi, GEN bnrc)` as `bnrchar_primitive`, with χ a regular (unnormalized) character on *bnr.clgp* of conductor *bnrc.mod*. Return a regular (unnormalized) primitive character on *bnrc*.

`GEN bnrdisc(GEN bnr, GEN H, long flag)` returns the discriminant and signature of the class field defined by `bnr` and `H`. See the description of the GP function for details. `flag` is an or-ed combination of the flags `rnf_REL` (output relative data) and `rnf_COND` (return 0 unless the modulus is the conductor).

`GEN ABC_to_bnr(GEN A, GEN B, GEN C, GEN *H, int addgen)` This is a quick conversion function designed to go from the too general (inefficient) A, B, C form to the preferred bnr, H form for class fields. Given A, B, C as explained above (omitted entries coded by `NULL`), return the attached bnr , and set H to the attached subgroup. If `addgen` is 1, make sure that if the bnr needed to be computed, then it contains generators.

13.1.28 Abelian maps. A map $f : A \rightarrow B$ between two abelian groups of finite type is given by a triple: $[M, cyc_A, cyc_B]$, where $cyc_A = [a_1, \dots, a_m]$ and $cyc_B = [b_1, \dots, b_n]$ are the elementary divisors for A and B (see `ZM_snf`) so that $A = \oplus_{i \leq m} (\mathbf{Z}/a_i \mathbf{Z}) g_i$ and $B = \oplus_{j \leq n} (\mathbf{Z}/b_j \mathbf{Z}) G_j$. The matrix M gives the image of the generators g_i in terms of the G_j : $(f(g_i))_{i \leq m} = (G_j)_{j \leq n} \cdot M$. The function `bnrmap` returns such a structure.

`GEN bnrsurjection(GEN BNR, GEN bnr)` `BNR` and `bnr` defined over the same field K , for moduli F and f with $f \mid F$, returns the canonical surjection $\text{Cl}_K(F) \rightarrow \text{Cl}_K(f)$ as an abelian map. I.e., a triple $[M, cyc_F, cyc_f]$. M gives the image of the fixed ray class group generators of `BNR` in terms of the ones in `bnr`, cyc_F and cyc_f are the cyclic structures of `BNR` and `bnr` respectively (as per `bnr_get_cyc`). Shallow function.

`GEN abmap_kernel(GEN S)` returns the kernel of the abelian map S , as a matrix H in HNF: the subgroup is $(g_i) \cdot H$.

`GEN abmap_subgroup_image(GEN S, GEN H)` given a subgroup H of A (its generators are the $(g_i)H$); for efficiency, H should be given in canonical form, i.e., as an HNF left divisor of $\text{diag}(a_1, \dots, a_m)$. Returns the subgroup $f(H)$ of B , as an HNF left divisor of $\text{diag}(b_1, \dots, b_n)$.

13.1.29 Grunwald–Wang theorem.

`GEN nfgwkummer(GEN nf, GEN Lpr, GEN Ld, GEN pl, long var)` low-level version of `nfgrunwaldwang`, assuming that `nf` contains suitable roots of unity, and directly using Kummer theory to construct the extension.

`GEN bnfgwgeneric(GEN bnf, GEN Lpr, GEN Ld, GEN pl, long var)` low-level version of `nfgrunwaldwang`, assuming that `bnf` is a `bnfinit` structure, and calling `rnfkummer` to construct the extension.

13.1.30 Relative equations, Galois conjugates.

`GEN nfissquarefree(GEN nf, GEN P)` given P a polynomial with coefficients in nf , return 1 if P is squarefree, and 0 otherwise. If is allowed (though less efficient) to replace nf by a monic `ZX` defining the field.

`GEN rnfequationall(GEN A, GEN B, long *pk, GEN *pLPRS)` A is either an nf type (corresponding to a number field K) or an irreducible `ZX` defining a number field K . B is an irreducible polynomial in $K[X]$. Returns an absolute equation C (over \mathbf{Q}) for the number field $K[X]/(B)$. C is the characteristic polynomial of $b + ka$ for some roots a of A and b of B , and k is a small rational integer. Set `*pk` to k .

If `pLPRS` is not `NULL` set it to $[h_0, h_1]$, $h_i \in \mathbf{Q}[X]$, where $h_0 + h_1 Y$ is the last nonconstant polynomial in the pseudo-Euclidean remainder sequence attached to $A(Y)$ and $B(X - kY)$, leading

to $C = \text{Res}_Y(A(Y), B(X - kY))$. In particular $a := -h_0/h_1$ is a root of A in $\mathbf{Q}[X]/(C)$, and $X - ka$ is a root of B .

`GEN nf_rnfeq(GEN A, GEN B)` wrapper around `rnfequationall` to allow mapping $K \rightarrow L$ (`eltup`) and converting elements of L between absolute and relative form (`reltoabs`, `abstorel`), *without* computing a full *rnf* structure, which is useful if the relative integral basis is not required. In fact, since A may be a `t_POL` or an *nf*, the integral basis of the base field is not needed either. The return value is the same as `rnf_get_map`. Shallow function.

`GEN nf_rnfeqsimple(GEN A, GEN B)` as `nf_rnfeq` except some fields are omitted, so that only the `abstorel` operation is supported. Shallow function.

`GEN eltabstorel(GEN rnfeq, GEN x)` `rnfeq` is as given by `rnf_get_map` (but in this case `rnfeltabstorel` is more robust), `nf_rnfeq` or `nf_rnfeqsimple`, return x as an element of L/K , i.e. as a `t_POLMOD` with `t_POLMOD` coefficients. Shallow function.

`GEN eltabstorel_lift(GEN rnfeq, GEN x)` same as `eltabstorel`, except that x is returned in partially lifted form, i.e. as a `t_POL` with `t_POLMOD` coefficients.

`GEN eltretoabs(GEN rnfeq, GEN x)` `rnfeq` is as given by `rnf_get_map` (but in this case `rnfeltreloabs` is more robust) or `nf_rnfeq`, return x in absolute form.

`GEN nf_nfzk(GEN nf, GEN rnfeq)` `rnfeq` as given by `nf_rnfeq`, `nf` a true *nf* structure, return a suitable representation of `nf.zk` allowing quick computation of the map $K \rightarrow L$ by the function `nfeltup`, *without* computing a full *rnf* structure, which is useful if the relative integral basis is not required. The computed value is the same as in `rnf_get_nfzk`. Shallow function.

`GEN nfeltup(GEN nf, GEN x, GEN zknf)` `zknf` and is initialized by `nf_nfzk` or `rnf_get_nfzk` (but in this case `nfeltup` is more robust); `nf` is a true *nf* structure for K , returns $x \in K$ as a (lifted) element of L , in absolute form.

`GEN rnfdisc_factored(GEN nf, GEN pol, GEN *pd)` variant of `rnfdisc` returning the relative discriminant ideal *factorization*, and setting `*pd` to the discriminant as an element in $K^*/(K^*)^2$. Shallow function. The argument `nf` is a true *nf* structure.

`GEN Rg_nffix(const char *f, GEN T, GEN c, int lift)` given a ZX T and a “coefficient” c supposedly belonging to $\mathbf{Q}[y]/(T)$, check whether this is the case and return a cleaned up version of c . The string f is the calling function name, used to report errors.

This means that c must be one of `t_INT`, `t_FRAC`, `t_POL` in the variable y with rational coefficients, or `t_POLMOD` modulo T which lift to a rational `t_POL` as above. The cleanup consists in the following improvements:

- `t_POL` coefficients are reduced modulo T .
- `t_POL` and `t_POLMOD` belonging to \mathbf{Q} are converted to rationals, `t_INT` or `t_FRAC`.
- if `lift` is nonzero, convert `t_POLMOD` to `t_POL`, and otherwise convert `t_POL` to `t_POLMODs` modulo T .

`GEN RgX_nffix(const char *f, GEN T, GEN P, int lift)` check whether P is a polynomial with coefficients in the number field defined by the absolute equation $T(y) = 0$, where T is a ZX and returns a cleaned up version of P . This checks whether P is indeed a `t_POL` with variable compatible with coefficients in $\mathbf{Q}[y]/(T)$, i.e.

$$\text{varncmp}(\text{varn}(P), \text{varn}(T)) < 0$$

and applies `Rg_nffix` to each coefficient.

`GEN RgV_nffix(const char *f, GEN T, GEN P, int lift)` as `RgX_nffix` for a vector of coefficients.

`GEN polmod_nffix(const char *f, GEN rnf, GEN x, int lift)` given a `t_POLMOD` x supposedly defining an element of rnf , check this and perform `Rg_nffix` cleanups.

`GEN polmod_nffix2(const char *f, GEN T, GEN P, GEN x, int lift)` as in `polmod_nffix`, where the relative extension is explicitly defined as $L = (\mathbf{Q}[y]/(T))[x]/(P)$, instead of by an `rnf` structure.

`long numberofconjugates(GEN T, long pinit)` returns a quick multiple for the number of \mathbf{Q} -automorphism of the (integral, monic) `t_POL` T , from modular factorizations, starting from prime `pinit` (you can set it to 2). This upper bounds often coincides with the actual number of conjugates. Of course, you should use `nfgaloisconj` to be sure.

`GEN nfroots_if_split(GEN *pt, GEN T)` let `*pt` point either to a number field structure or an irreducible `ZX`, defining a number field K . Given T a monic squarefree polynomial with coefficients in \mathbf{Z}_K , return the list of roots of `pol` in K if the polynomial splits completely, and `NULL` otherwise. In other words, this checks whether $K[X]/(T)$ is normal over K (hence Galois since T is separable by assumption).

In the case where `*pT` is a `ZX`, the function has to compute internally a conditional `nf` attached to K , whose `nf.zk` may not define the maximal order \mathbf{Z}_K (see `nfroots`); `*pT` is then replaced by the conditional `nf` to avoid losing that information.

`GEN rnfabelianconjgen(GEN nf, GEN P)` nf being a number field structure attached to K and P being an irreducible polynomial in $K[X]$. This function returns `gen_0` if $L = K[X]/(P)$ is not abelian over K , else it returns a pair (g, o) where g is a vector of K -automorphisms of L generating the abelian group $G = \text{Gal}(L/K)$ and o is a `t_VEC` of the same length giving the relative orders of the g_i : $o[1]$ is the order of g_1 and for $i \geq 2$, $o[i]$ is the order of g_i in $G/(g_1, \dots, g_{i-1})$. The length need not be minimal: the $o[i]$ need not be the elementary divisors of G .

13.1.31 Units.

`GEN nfrootsof1(GEN nf)` returns a two-component vector $[w, z]$ where w is the number of roots of unity in the number field nf , and z is a primitive w -th root of unity.

`GEN nfcyclotomicunits(GEN nf, GEN zu)` where `zu` is as output by `nfrootsof1(nf)`, return the vector of the cyclotomic units in nf expressed over the integral basis. If $\zeta = \zeta_n$ belongs to the base field (n maximal), this function returns

- (when n is not a prime power) the $\zeta^a - 1$, for all $1 \leq a < n/2$ such that $n/(a, n)$ is not a prime power and a is a strict divisor of n .
- (all n) for p prime, $v_p(n) = k > 0$, the $(z^a - 1)/(z - 1)$, where $z = \zeta^{n/p^k}$, for all $1 < a \leq (p^k - 1)/2$, $(p, a) = 1$.

These are independent modulo torsion if n is a prime power, but not necessarily so otherwise.

`GEN sunits_mod_units(GEN bnf, GEN S)` return independent generators for $U_S(K)/U(K)$.

13.1.32 Obsolete routines.

Still provided for backward compatibility, but should not be used in new programs. They will eventually disappear.

GEN zidealstar(GEN nf, GEN x) short for Idealstar(nf,x,nf_GEN)

GEN zidealstarinit(GEN nf, GEN x) short for Idealstar(nf,x,nf_INIT)

GEN zidealstarinitgen(GEN nf, GEN x) short for Idealstar(nf,x,nf_GEN|nf_INIT)

GEN idealstar0(GEN nf, GEN x, long flag) short for idealstarmod(nf, ideal, flag, NULL). Use Idealstarmod or Idealstar.

GEN bnrinit0(GEN bnf, GEN ideal, long flag) short for bnrinitmod(bnf,ideal,flag,NULL). Use Buchray or Buchraymod.

GEN buchimag(GEN D, GEN c1, GEN c2, GEN gCO) short for

Buchquad(D,gtodouble(c1),gtodouble(c2), /*ignored*/0)

GEN buchreal(GEN D, GEN gsens, GEN c1, GEN c2, GEN RELSUP, long prec) short for

Buchquad(D,gtodouble(c1),gtodouble(c2), prec)

The following use a naming scheme which is error-prone and not easily extensible; besides, they compute generators as per nf_GEN and not nf_GENMAT. Don't use them:

GEN isprincipalforce(GEN bnf, GEN x)

GEN isprincipalgen(GEN bnf, GEN x)

GEN isprincipalgenforce(GEN bnf, GEN x)

GEN isprincipalraygen(GEN bnr, GEN x), use bnrprincipal.

Variants on polred: use polredbest.

GEN factoredpolred(GEN x, GEN fa)

GEN factoredpolred2(GEN x, GEN fa)

GEN smallpolred(GEN x)

GEN smallpolred2(GEN x), use Polred.

GEN polred0(GEN x, long flag, GEN p)

GEN polredabs(GEN x)

GEN polredabs2(GEN x)

GEN polredabsall(GEN x, long flun)

Superseded by bnrdisclist0:

GEN discrayabslist(GEN bnf, GEN L)

GEN discrayabslistarch(GEN bnf, GEN arch, long bound)

Superseded by idealappr (*flag* is ignored)

GEN idealappr0(GEN nf, GEN x, long flag)

Superseded by bnrconductor_raw or bnrconductormod:

GEN bnrconductor_i(GEN bnr, GEN H, long flag) shallow variant of bnrconductor.

GEN bnrconductorofchar(GEN bnr, GEN chi)

13.2 Galois extensions of \mathbb{Q} .

This section describes the data structure output by the function `galoisinit`. This will be called a `gal` structure in the following.

13.2.1 Extracting info from a `gal` structure.

The functions below expect a `gal` structure and are shallow. See the documentation of `galoisinit` for the meaning of the member functions.

`GEN gal_get_pol(GEN gal)` returns `gal.pol`

`GEN gal_get_p(GEN gal)` returns `gal.p`

`GEN gal_get_e(GEN gal)` returns the integer e such that `gal.mod==gal.pe`.

`GEN gal_get_mod(GEN gal)` returns `gal.mod`.

`GEN gal_get_roots(GEN gal)` returns `gal.roots`.

`GEN gal_get_invvdm(GEN gal)` `gal[4]`.

`GEN gal_get_den(GEN gal)` return `gal[5]`.

`GEN gal_get_group(GEN gal)` returns `gal.group`.

`GEN gal_get_gen(GEN gal)` returns `gal.gen`.

`GEN gal_get_orders(GEN gal)` returns `gal.orders`.

13.2.2 Miscellaneous functions.

`GEN nfgaloispermtobasis(GEN nf, GEN gal)` return the images of the field generator by the automorphisms `gal.orders` expressed on the integral basis `nf.zk`.

`GEN nfgaloismatrix(GEN nf, GEN s)` returns the ZM attached to the automorphism s , seen as a linear operator expressed on the number field integer basis. This allows to use

```
M = nfgaloismatrix(nf, s);
sx = ZM_ZC_mul(M, x);    /* or RgM_RgC_mul(M, x) if x is not integral */
```

instead of

```
sx = nfgaloisapply(nf, s, x);
```

for an algebraic integer x .

`GEN nfgaloismatrixapply(GEN nf, GEN M, GEN x)` given an automorphism M in `nfgaloismatrix` form, return the image of x under the automorphism. Variant of `galoisapply`.

13.3 Quadratic number fields and quadratic forms.

13.3.1 Checks.

`void check_quaddisc(GEN x, long *s, long *mod4, const char *f)` checks whether the GEN x is a quadratic discriminant (`t_INT`, not a square, congruent to 0, 1 modulo 4), and raise an exception otherwise. Set $*s$ to the sign of x and $*mod4$ to x modulo 4 (0 or 1), unless `mod4` is NULL.

`void check_quaddisc_real(GEN x, long *mod4, const char *f)` as `check_quaddisc`; check that `signe(x)` is positive.

`void check_quaddisc_imag(GEN x, long *mod4, const char *f)` as `check_quaddisc`; check that `signe(x)` is negative.

13.3.2 Class number.

Given a D congruent to 0 or 1 modulo 4, let $h(D)$ denote the class number of the order of discriminant D . The function `quadclassunit` uses index calculus and computes $h(D)$ in subexponential time in $\log |D|$ but it assumes the truth of the GRH. For imaginary quadratic orders, it is also comparatively slow for *small* values, say $|D| \leq 10^{18}$. Here are some alternatives:

`GEN classno(GEN D)` corresponds to `qfbclassno(D,0)` and is only useful for $D < 0$, uses a baby-step giant-step technique and runs in time $O(D^{1/4})$. The result is guaranteed correct for $|D| < 2 \cdot 10^{10}$ and fastest in that range. For larger values of $|D|$, the algorithm is no longer rigorous and may give incorrect results (we know no concrete example); it also becomes relatively less interesting compared to `quadclassunit`.

`GEN classno2(GEN D)` corresponds to `qfbclassno(D,1)` and runs in time $O(D^{1/2})$; the function is provided for testing purposes only since it is never competitive.

`GEN quadclassnoF(GEN D, GEN *pd)` returns the positive integer $h(D)/h(d)$ where d is the fundamental discriminant attached to D . If `pd` is not NULL, set $*pd$ to d .

`GEN quadclassno(GEN D)` returns $h(D)$ using Buchmann's algorithm on the order of discriminant D . If D is not fundamental, it will usually be faster to call `coredisc2_fact` and `quadclassnoF_fact` to reduce to this case first.

`long quadclassnos(long D)` returns $h(D)$ using Buchmann's algorithm on the order of discriminant D .

`ulong unegquadclassnoF(ulong x, long *pd)` returns $h(-x)/h(d)$. Set $*pd$ to d .

`ulong uposquadclassnoF(ulong x, long *pd)` returns $h(x)/h(d)$. Set $*pd$ to d .

`GEN quadclassnoF_fact(GEN D, GEN P, GEN E)` let D be a fundamental discriminant, and $f = \prod_i P[i]^{E[i]}$ be a positive conductor for the order of discriminant Df^2 (P is a ZV and E is a ZV or zv). Returns the positive integer

$$h(Df^2)/h(D) = \frac{f}{[O_D^\times : O_{Df^2}^\times]} \prod_{p|f} (1 - (D/p)p^{-1}).$$

`ulong uquadclassnoF_fact(ulong d, long s, GEN P, GEN E)` let $s = 1$ or -1 be a sign, $D = sd$ be a fundamental discriminant, and $f = \prod_i P[i]^{E[i]}$ be a positive conductor for the order of discriminant Df^2 (P and E are `t_VECSMALL`). Returns the integer

$$h(Df^2)/h(d) = \frac{f}{[O_D^\times : O_{Df^2}^\times]} \prod_{p|f} (1 - (D/p)p^{-1}).$$

`GEN hclassno(GEN d)` returns the Hurwitz-Kronecker class number $H(d)$. These play a central role in trace formulas and are usually needed for many consecutive values of d . Thus, the function uses a cache so that later calls for *small* consecutive values of d are instantaneous, see `getcache`. Large values of d ($d > 500000$) call `quadclassunit` individually and are not memoized.

`GEN hclassnoF_fact(GEN P, GEN E, GEN D)` return $H(Df^2)/H(D)$ assuming D is a negative fundamental discriminant, where the conductor f is given in factored form: P (ZV) is the list of prime divisors of f and E (`t_VECSMALL`) their multiplicities.

`long uhclassnoF_fact(GEN faf, long D)` return $H(Df^2)/H(D)$ assuming D is a negative fundamental discriminant and $d = Df^2$ is an `ulong` and faf is `factoru(d)`.

`GEN hclassno6(GEN d)` assuming $d > 0$, returns the integer $6H(d)$. This is a low-level function behind `hclassno`.

`ulong hclassno6u(ulong d)` assuming $d > 0$, returns the integer $6H(d)$. Using this function creates (or extends) caches of Hurwitz class numbers and CoreDiscs of negative integers to speed up consecutive or repeated calls (see `getcache`). If this is a problem, use:

`ulong hclassno6u_no_cache(ulong d)` as `hclassno6u` without creating caches. Existing caches will be used.

13.3.3 `t_QFB`.

The functions in this section operate on binary quadratic forms of type `t_QFB`. When specified, a `t_QFB` argument q attached to an indefinite form can be replaced by the pair $[q, d]$ where the `t_REAL` d is Shanks's distance.

`GEN qfb_1(GEN q)` given a `t_QFB` q , return the unit form q^0 .

`int qfb_equal1(GEN q)` returns 1 if the `t_QFB` q is the unit form.

13.3.3.1 Reduction.

`GEN qfbred(GEN x)` reduction of a `t_QFB` x . Also allow extended indefinite forms.

`GEN qfbred_i(GEN x)` internal version of `qfbred`: assume x is a `t_QFB`.

13.3.3.2 Composition.

`GEN qfbcomp(GEN x, GEN y)` compose the two `t_QFB` x and y (with same discriminant), then reduce the result. This is the same as `gmul(x, y)`. Also allow extended indefinite forms.

`GEN qfbcomp_i(GEN x, GEN y)` internal version of `qfbcomp`: assume x and y are `t_QFB` of the same discriminant.

`GEN qfbsqr(GEN x)` as `qfbcomp(x, x)`.

`GEN qfbsqr_i(GEN x)` as `qfbcomp_i(x, x)`.

Same as above, *without* reducing the result:

GEN `qfbcomprow`(GEN `x`, GEN `y`) compose two `t_QFB`s, without reducing the result. Also allow extended indefinite forms.

GEN `qfbcomprow_i`(GEN `x`, GEN `y`) internal version of `qfbcomprow`: assume x and y are `t_QFB` of the same discriminant.

13.3.3.3 Powering.

GEN `qfbpow`(GEN `x`, GEN `n`) computes x^n and reduce the result. Also allow extended indefinite forms.

GEN `qfbpows`(GEN `x`, long `n`) computes x^n and reduce the result. Also allow extended indefinite forms.

GEN `qfbpow_i`(GEN `x`, GEN `n`) internal version of `qfbcomp`. Assume x is a `QFB`.

GEN `qfbpowraw`(GEN `x`, long `n`) compute x^n (pure composition, no reduction), for a `t_QFB` x . Also allow indefinite forms.

13.3.3.4 Order, discrete log.

GEN `qfi_order`(GEN `q`, GEN `o`) assuming that the imaginary `t_QFB` q has order dividing o , compute its order in the class group. The order can be given in all formats allowed by generic discrete log functions, the preferred format being [`ord`, `fa`] (`t_INT` and its factorization).

GEN `qfi_log`(GEN `a`, GEN `g`, GEN `o`) given an imaginary `t_QFB` a and assuming that the `t_QFB` g has order o , compute an integer k such that $a^k = g$. Return `cgetg(1, t_VEC)` if there are no solutions. Uses a generic Pollig-Hellman algorithm, then either Shanks (small o) or Pollard rho (large o) method. The order can be given in all formats allowed by generic discrete log functions, the preferred format being [`ord`, `fa`] (`t_INT` and its factorization).

GEN `qfi_Shanks`(GEN `a`, GEN `g`, long `n`) given an imaginary `t_QFB` a and assuming that the `t_QFB` g has (small) order n , compute an integer k such that $a^k = g$. Return `cgetg(1, t_VEC)` if there are no solutions. Directly uses Shanks algorithm, which is inefficient when n is composite.

13.3.3.5 Solve, Cornacchia.

The following functions underly `qfbsolve`; p denotes a prime number.

GEN `qfisolvep`(GEN `Q`, GEN `p`) solves $Q(x, y) = p$ over the integers, for an imaginary `t_QFB` Q . Return `gen_0` if there are no solutions.

GEN `qfrsolvep`(GEN `Q`, GEN `p`) solves $Q(x, y) = p$ over the integers, for a real `t_QFB` Q . Return `gen_0` if there are no solutions.

long `cornacchia`(GEN `d`, GEN `p`, GEN `*px`, GEN `*py`) solves $x^2 + dy^2 = p$ over the integers, where $d > 0$ is congruent to 0 or 3 modulo 4. Return 1 if there is a solution (and store it in `*x` and `*y`), 0 otherwise.

long `cornacchia2`(GEN `d`, GEN `p`, GEN `*px`, GEN `*py`) as `cornacchia`, for the equation $x^2 + dy^2 = 4p$.

long `cornacchia2_sqrt`(GEN `d`, GEN `p`, GEN `b`, GEN `*px`, GEN `*py`) as `cornacchia2`, where $p > 2$ and b is the smallest squareroot of d modulo p .

13.3.3.6 Prime forms.

GEN primeform_u(GEN D, ulong p) t_QFB of discriminant D whose first coefficient is the prime p , assuming $(D/p) \geq 0$.

GEN primeform(GEN D, GEN p)

13.3.4 Efficient real quadratic forms. Unfortunately, real t_QFBs are very inefficient, and are only provided for backward compatibility.

- they do not contain needed quantities, which are thus constantly recomputed (the discriminant square root \sqrt{D} and its integer part),
- the distance component is stored in logarithmic form, which involves computing one extra logarithm per operation. It is much more efficient to store its exponential, computed from ordinary multiplications and divisions (taking exponent overflow into account), and compute its logarithm at the very end.

Internally, we have two representations for real quadratic forms:

- **qfr3**, a container $[a, b, c]$ with at least 3 entries: the three coefficients; the idea is to ignore the distance component.
- **qfr5**, a container with at least 5 entries $[a, b, c, e, d]$: the three coefficients a t_REAL d and a t_INT e coding the distance component $2^{Ne}d$, in exponential form, for some large fixed N .

It is a feature that **qfr3** and **qfr5** have no specified length or type. It implies that a **qfr5** or t_QFB will do whenever a **qfr3** is expected. Routines using these objects require a global context, provided by a struct qfr_data *:

```
struct qfr_data {
    GEN D;          /* discriminant, t_INT */
    GEN sqrtD;      /* sqrt(D), t_REAL */
    GEN isqrtD;     /* floor(sqrt(D)), t_INT */
};
```

void qfr_data_init(GEN D, long prec, struct qfr_data *S) given a discriminant $D > 0$, initialize S for computations at precision prec (\sqrt{D} is computed to that initial accuracy).

All functions below are shallow, and not stack clean.

GEN qfr3_comp(GEN x, GEN y, struct qfr_data *S) compose two **qfr3**, reducing the result.

GEN qfr3_compraw(GEN x, GEN y) as **qfr3_comp**, without reducing the result.

GEN qfr3_pow(GEN x, GEN n, struct qfr_data *S) compute x^n , reducing along the way.

GEN qfr3_red(GEN x, struct qfr_data *S) reduce x .

GEN qfr3_rho(GEN x, struct qfr_data *S) perform one reduction step; **qfr3_red** just performs reduction steps until we hit a reduced form.

GEN qfr3_to_qfr(GEN x, GEN d) recover an ordinary t_QFB from the **qfr3** x , adding discriminant component d .

Before we explain **qfr5**, recall that it corresponds to an ideal, that reduction corresponds to multiplying by a principal ideal, and that the distance component is a clever way to keep track of these principal ideals. More precisely, reduction consists in a number of reduction steps, going

from the form (a, b, c) to $\rho(a, b, c) = (c, -b \bmod 2c, *)$; the distance component is multiplied by (a floating point approximation to) $(b + \sqrt{D})/(b - \sqrt{D})$.

GEN `qfr5_comp`(GEN `x`, GEN `y`, struct `qfr_data *S`) compose two `qfr5`, reducing the result, and updating the distance component.

GEN `qfr5_compraw`(GEN `x`, GEN `y`) as `qfr5_comp`, without reducing the result.

GEN `qfr5_pow`(GEN `x`, GEN `n`, struct `qfr_data *S`) compute x^n , reducing along the way.

GEN `qfr5_red`(GEN `x`, struct `qfr_data *S`) reduce x .

GEN `qfr5_rho`(GEN `x`, struct `qfr_data *S`) perform one reduction step.

GEN `qfr5_dist`(GEN `e`, GEN `d`, long `prec`) decode the distance component from exponential (`qfr5`-specific) to logarithmic form (true Shanks's distance).

GEN `qfr_to_qfr5`(GEN `x`, long `prec`) convert a real `t_QFB` to a `qfr5` with initial trivial distance component ($= 1$).

GEN `qfr5_to_qfr`(GEN `x`, GEN `d`), assume x is a `qfr5` and d is NULL or the original distance component of some real `t_QFB`. Convert x to a `t_QFB`, with the correct (logarithmic) distance component if d is not NULL.

13.4 Linear algebra over \mathbb{Z} .

13.4.1 Hermite and Smith Normal Forms.

GEN `ZM_hnf`(GEN `x`) returns the upper triangular Hermite Normal Form of the ZM x (removing 0 columns), using the `ZM_hnfall` algorithm. If you want the true HNF, use `ZM_hnfall(x, NULL, 0)`.

GEN `ZM_hnfmod`(GEN `x`, GEN `d`) returns the HNF of the ZM x (removing 0 columns), assuming the `t_INT` d is a multiple of the determinant of x . This is usually faster than `ZM_hnf` (and uses less memory) if the dimension is large, > 50 say.

GEN `ZM_hnfmodid`(GEN `x`, GEN `d`) returns the HNF of the ZM x concatenated with the diagonal matrix with diagonal d , where d is a vector of integers of compatible dimension. Variant: if d is a `t_INT`, then concatenate dId .

GEN `ZM_hnfmodprime`(GEN `x`, GEN `p`) returns the HNF of the matrix $(x \mid pId)$ (removing 0 columns), for a ZM x and a prime number p . The algorithm involves only \mathbf{F}_p -linear algebra and is faster than `ZM_hnfmodid` (which will call it when d is prime).

GEN `ZM_hnfmodall`(GEN `x`, GEN `d`, long `flag`) low-level function underlying the `ZM_hnfmod` variants. If `flag` is 0, calls `ZM_hnfmod(x, d)`; `flag` is an or-ed combination of:

- `hnf_MODID` call `ZM_hnfmodid` instead of `ZM_hnfmod`,
- `hnf_PART` return as soon as we obtain an upper triangular matrix, saving time. The pivots are nonnegative and give the diagonal of the true HNF, but the entries to the right of the pivots need not be reduced, i.e. they may be large or negative.
- `hnf_CENTER` returns the centered HNF, where the entries to the right of a pivot p are centered residues in $[-p/2, p/2[$, hence smallest possible in absolute value, but possibly negative.

GEN `ZM_hnfmodall_i`(GEN `x`, GEN `d`, long `flag`) as `ZM_hnfmodall` without final garbage collection. Not `gerepile`-safe.

GEN `ZM_hnfall`(GEN `x`, GEN `*U`, long `remove`) returns the upper triangular HNF H of the ZM x ; if U is not NULL, set it to the matrix U such that $xU = H$. If `remove` = 0, H is the true HNF, including 0 columns; if `remove` = 1, delete the 0 columns from H but do not update U accordingly (so that the integer kernel may still be recovered): we no longer have $xU = H$; if `remove` = 2, remove 0 columns from H and update U so that $xU = H$. The matrix U is square and invertible unless `remove` = 2.

This routine uses a naive algorithm which is potentially exponential in the dimension (due to coefficient explosion) but is fast in practice, although it may require lots of memory. The base change matrix U may be very large, when the kernel is large.

GEN `ZM_hnfall_i`(GEN `x`, GEN `*U`, long `remove`) as `ZM_hnfall` without final garbage collection. Not `gerepile`-safe.

GEN `ZM_hnfperm`(GEN `A`, GEN `*ptU`, GEN `*ptperm`) returns the hnf $H = PAU$ of the matrix PA , where P is a suitable permutation matrix, and $U \in \text{Gl}_n(\mathbf{Z})$. P is chosen so as to (heuristically) minimize the size of U ; in this respect it is less efficient than `ZM_hnfall1` but usually faster. Set `*ptU` to U and `*ptperm` to a `t_VECSMALL` representing the row permutation attached to $P = (\delta_{i, \text{perm}[i]})$. If `ptU` is set to NULL, U is not computed, saving some time; although useless, setting `ptperm` to NULL is also allowed.

GEN `ZM_hnf_knapsack`(GEN `x`) given a ZM x , compute its HNF h . Return h if it has the knapsack property: every column contains only zeroes and ones and each row contains a single 1; return NULL otherwise. Not suitable for `gerepile`.

GEN `ZM_hnfall1`(GEN `x`, GEN `*U`, int `remove`) returns the HNF H of the ZM x ; if U is not NULL, set it to the matrix U such that $xU = H$. The meaning of `remove` is the same as in `ZM_hnfall`.

This routine uses the LLL variant of Havas, Majewski and Mathews, which is polynomial time, but rather slow in practice because it uses an exact LLL over the integers instead of a floating point variant; it uses polynomial space but lots of memory is needed for large dimensions, say larger than 300. On the other hand, the base change matrix U is essentially optimally small with respect to the L_2 norm.

GEN `ZM_hnfcenter`(GEN `M`). Given a ZM in HNF M , update it in place so that nondiagonal entries belong to a system of *centered* residues. Not suitable for `gerepile`.

Some direct applications: the following routines apply to upper triangular integral matrices; in practice, these come from HNF algorithms.

GEN `hnf_divscale`(GEN `A`, GEN `B`, GEN `t`) A an upper triangular ZM, B a ZM, t an integer, such that $C := tA^{-1}B$ is integral. Return C .

GEN `hnf_invscale`(GEN `A`, GEN `t`) A an upper triangular ZM, t an integer such that $C := tA^{-1}$ is integral. Return C . Special case of `hnf_divscale` when B is the identity matrix.

GEN `hnf_solve`(GEN `A`, GEN `B`) A a ZM in upper HNF (not necessarily square), B a ZM or ZC. Return $A^{-1}B$ if it is integral, and NULL if it is not.

GEN `hnf_invimage`(GEN `A`, GEN `b`) A a ZM in upper HNF (not necessarily square), b a ZC. Return $A^{-1}B$ if it is integral, and NULL if it is not.

int `hnfdivide`(GEN `A`, GEN `B`) A and B are two upper triangular ZM. Return 1 if $A^{-1}B$ is integral, and 0 otherwise.

Smith Normal Form.

GEN ZM_snf(GEN x) returns the Smith Normal Form (vector of elementary divisors) of the ZM x .

GEN ZM_snfall(GEN x, GEN *U, GEN *V) returns ZM_snf(x) and sets U and V to unimodular matrices such that $UxV = D$ (diagonal matrix of elementary divisors). Either (or both) U or V may be NULL in which case the corresponding matrix is not computed.

GEN ZV_snfall(GEN d, GEN *U, GEN *V) here d is a ZV; same as ZM_snfall applied to diagonal(d), but faster.

GEN ZM_snfall_i(GEN x, GEN *U, GEN *V, long flag) low level version of ZM_snfall:

- if the first bit of *flag* is 0, return a diagonal matrix (as in ZM_snfall), else a vector of elementary divisors (as in ZM_snf).

- if the second bit of *flag* is 1, assume that x is invertible and allow U and V to have determinant congruent to 1 modulo d , where d is the largest elementary divisor of x . Rationale: the finite group $G = \mathbf{Z}^n / \mathfrak{S}x$ has exponent d and we are only interested in the action of U, V as they act on G not in genuine unimodular matrices. (See ZM_snf_group.)

void ZM_snfclean(GEN d, GEN U, GEN V) assuming d, U, V come from $d = \text{ZM_snfall}(x, \&U, \&V)$, where U or V may be NULL, cleans up the output in place. This means that elementary divisors equal to 1 are deleted and U, V are updated. This also works when d is a t_VEC of elementary divisors. The output is not suitable for gerepileupto.

void ZV_snfclean(GEN d) assuming d is a t_VEC of elementary divisors, return a shortened version where divisors equal to 1 are deleted. The output is not suitable for gerepileupto; we return d itself if no divisor is 1.

void ZV_snf_trunc(GEN D) given a vector D of elementary divisors (i.e. a ZV such that $d_i \mid d_{i+1}$), truncate it *in place* to leave out the trivial divisors (equal to 1).

GEN ZM_snf_group(GEN H, GEN *U, GEN *Uinv) this function computes data to go back and forth between an abelian group (of finite type) given by generators and relations, and its canonical SNF form. Given an abstract abelian group with generators $g = (g_1, \dots, g_n)$ and a vector $X = (x_i) \in \mathbf{Z}^n$, we write gX for the group element $\sum_i x_i g_i$; analogously if M is an $n \times r$ integer matrix gM is a vector containing r group elements. The group neutral element is 0; by abuse of notation, we still write 0 for a vector of group elements all equal to the neutral element. The input is a full relation matrix H among the generators, i.e. a ZM (not necessarily square) such that $gX = 0$ for some $X \in \mathbf{Z}^n$ if and only if X is in the integer image of H , so that the abelian group is isomorphic to $\mathbf{Z}^n / \text{Im}H$. The routine assumes that H is in HNF; replace it by its HNF if it is not the case. (Of course this defines the same group.)

Let G a minimal system of generators in SNF for our abstract group: if the d_i are the elementary divisors ($\dots \mid d_2 \mid d_1$), each G_i has either infinite order ($d_i = 0$) or order $d_i > 1$. Let D the matrix with diagonal (d_i) , then

$$GD = 0, \quad G = gU_{\text{inv}}, \quad g = GU,$$

for some integer matrices U and U_{inv} . Note that these are not even square in general; even if square, there is no guarantee that these are unimodular: they are chosen to have minimal entries given the known relations in the group and only satisfy $D \mid (UU_{\text{inv}} - \text{Id})$ and $H \mid (U_{\text{inv}}U - \text{Id})$.

The function returns the vector of elementary divisors (d_i) ; if U is not NULL, it is set to U ; if U_{inv} is not NULL it is set to U_{inv} . The function is not memory clean.

GEN ZV_snf_group(GEN d, GEN *newU, GEN *newUi), here d is a ZV; same as ZM_snf_group applied to diagonal(d), but faster.

GEN ZV_snf_gcd(GEN v, GEN N) given a vector v of integers and a positive integer N , return the vector whose entries are the gcds $(v[i], N)$. Use case: if v gives the cyclic components for some abelian group G of finite type, then this returns the structure of the finite groupe G/G^N .

The following functions compute the p^n -rank of abelian groups given a vector of elementary divisors and underly snfrank:

long ZV_snf_rank(GEN D, GEN p) assume D is a ZV and p is a t_INT.

long ZV_snf_rank_u(GEN D, ulong p) assume D is a ZV.

long zv_snf_rank(GEN D, ulong p) assume D is a zv.

The following routines underly the various matrixqz variants. In all case the $m \times n$ t_MAT x is assumed to have rational (t_INT and t_FRAC) coefficients

GEN QM_ImQ(GEN x) returns a basis for $\text{Im}_{\mathbf{Q}}x \cap \mathbf{Z}^n$.

GEN QM_ImZ(GEN x) returns a basis for $\text{Im}_{\mathbf{Z}}x \cap \mathbf{Z}^n$.

GEN QM_ImQ_hnf(GEN x) returns an HNF basis for $\text{Im}_{\mathbf{Q}}x \cap \mathbf{Z}^n$.

GEN QM_ImZ_hnf(GEN x) returns an HNF basis for $\text{Im}_{\mathbf{Z}}x \cap \mathbf{Z}^n$.

GEN QM_ImQ_hnfall(GEN A, GEN *pB, long remove) as QM_ImQ_hnf, further returning the transformation matrix as in ZM_hnfall.

GEN QM_ImZ_hnfall(GEN A, GEN *pB, long remove) as QM_ImZ_hnf, further returning the transformation matrix as in ZM_hnfall.

GEN QM_ImQ_all(GEN A, GEN *pB, long remove, long hnf) as QM_ImQ, further returning the transformation matrix as in ZM_hnfall, and returning an HNF basis if hnf is nonzero.

GEN QM_ImZ_all(GEN A, GEN *pB, long remove, long hnf) as QM_ImZ, further returning the transformation matrix as in ZM_hnfall, and returning an HNF basis if hnf is nonzero.

GEN QM_minors_coprime(GEN x, GEN D), assumes $m \geq n$, and returns a matrix in $M_{m,n}(\mathbf{Z})$ with the same \mathbf{Q} -image as x , such that the GCD of all $n \times n$ minors is coprime to D ; if D is NULL, we want the GCD to be 1.

The following routines are simple wrappers around the above ones and are normally useless in library mode:

GEN hnf(GEN x) checks whether x is a ZM, then calls ZM_hnf. Normally useless in library mode.

GEN hnfmmod(GEN x, GEN d) checks whether x is a ZM, then calls ZM_hnfmmod. Normally useless in library mode.

GEN hnfmmodid(GEN x, GEN d) checks whether x is a ZM, then calls ZM_hnfmmodid. Normally useless in library mode.

GEN hnfall(GEN x) calls ZM_hnfall(x, &U, 1) and returns $[H, U]$. Normally useless in library mode.

GEN hnfl1l(GEN x) calls ZM_hnfl1l(x, &U, 1) and returns $[H, U]$. Normally useless in library mode.

GEN `hnfperm`(GEN `x`) calls `ZM_hnfperm(x, &U, &P)` and returns $[H, U, P]$. Normally useless in library mode.

GEN `smith`(GEN `x`) checks whether x is a ZM, then calls `ZM_snf`. Normally useless in library mode.

GEN `smithall`(GEN `x`) checks whether x is a ZM, then calls `ZM_snfall(x, &U, &V)` and returns $[U, V, D]$. Normally useless in library mode.

Some related functions over $K[X]$, K a field:

GEN `gsmith`(GEN `A`) the input matrix must be square, returns the elementary divisors.

GEN `gsmithall`(GEN `A`) the input matrix must be square, returns the $[U, V, D]$, D diagonal, such that $UAV = D$.

GEN `RgM_hnfall`(GEN `A`, GEN `*pB`, long `remove`) analogous to `ZM_hnfall`.

GEN `smithclean`(GEN `z`) cleanup the output of `smithall` or `gsmithall` (delete elementary divisors equal to 1, updating base change matrices).

13.4.2 The LLL algorithm.

The basic GP functions and their immediate variants are normally not very useful in library mode. We briefly list them here for completeness, see the documentation of `qflll` and `qflllgram` for details:

- GEN `qflll0`(GEN `x`, long `flag`)

GEN `lll`(GEN `x`) *flag*= 0

GEN `lllint`(GEN `x`) *flag*= 1

GEN `lllkerim`(GEN `x`) *flag*= 4

GEN `lllkerimgen`(GEN `x`) *flag*= 5

GEN `lllgen`(GEN `x`) *flag*= 8

- GEN `qflllgram0`(GEN `x`, long `flag`)

GEN `lllgram`(GEN `x`) *flag*= 0

GEN `lllgramint`(GEN `x`) *flag*= 1

GEN `lllgramkerim`(GEN `x`) *flag*= 4

GEN `lllgramkerimgen`(GEN `x`) *flag*= 5

GEN `lllgramgen`(GEN `x`) *flag*= 8

The basic workhorse underlying all integral and floating point LLLs is

GEN `ZM_lll`(GEN `x`, double `D`, long `flag`), where x is a ZM; $D \in]1/4, 1[$ is the Lovász constant determining the frequency of swaps during the algorithm: a larger values means better guarantees for the basis (in principle smaller basis vectors) but longer running times (suggested value: $D = 0.99$).

Important. This function does not collect garbage and its output is not suitable for either `gerepile` or `gerepileupto`. We expect the caller to do something simple with the output (e.g. matrix multiplication), then collect garbage immediately.

`flag` is an or-ed combination of the following flags:

- **LLL_GRAM.** If set, the input matrix x is the Gram matrix ${}^t v v$ of some lattice vectors v .
- **LLL_INPLACE.** Incompatible with **LLL_GRAM**. If unset, we return the base change matrix U , otherwise the transformed matrix xU . Implies **LLL_IM** (see below).
- **LLL_KEEP_FIRST.** The first vector in the output basis is the same one as was originally input. Provided this is a shortest nonzero vector of the lattice, the output basis is still LLL-reduced. This is used to reduce maximal orders of number fields with respect to the T_2 quadratic form, to ensure that the first vector in the output basis corresponds to 1 (which is a shortest vector).
- **LLL_COMPATIBLE.** DEPRECATED. This is now a no-op.

The last three flags are mutually exclusive, either 0 or a single one must be set:

- **LLL_KER** If set, only return a kernel basis K (not LLL-reduced).
- **LLL_IM** If set, only return an LLL-reduced lattice basis T . (This is implied by **LLL_INPLACE**).
- **LLL_ALL** If set, returns a 2-component vector $[K, T]$ corresponding to both kernel and image.

`GEN lllfp(GEN x, double D, long flag)` is a variant for matrices with inexact entries: x is a matrix with real coefficients (types `t_INT`, `t_FRAC` and `t_REAL`), D and $flag$ are as in `ZM_lll`. The matrix is rescaled, rounded to nearest integers, then fed to `ZM_lll`. The flag **LLL_INPLACE** is still accepted but less useful (it returns an LLL-reduced basis attached to rounded input, instead of an exact base change matrix).

`GEN ZM_lll_norms(GEN x, double D, long flag, GEN *ptB)` slightly more general version of `ZM_lll`, setting `*ptB` to a vector containing the squared norms of the Gram-Schmidt vectors (b_i^*) attached to the output basis (b_i), $b_i^* = b_i + \sum_{j < i} \mu_{i,j} b_j^*$.

`GEN lllintpartial_inplace(GEN x)` given a `ZM` x of maximal rank, returns a partially reduced basis (b_i) for the space spanned by the columns of x : $|b_i \pm b_j| \geq |b_i|$ for any two distinct basis vectors b_i, b_j . This is faster than the LLL algorithm, but produces much larger bases.

`GEN lllintpartial(GEN x)` as `lllintpartial_inplace`, but returns the base change matrix U from the canonical basis to the b_i , i.e. xU is the output of `lllintpartial_inplace`.

`GEN RM_round_maxrank(GEN G)` given a matrix G with real floating point entries and independent columns, let G_e be the rescaled matrix $2^e G$ rounded to nearest integers, for $e \geq 0$. Finds a small e such that the rank of G_e is equal to the rank of G (its number of columns) and return G_e . This is useful as a preconditioning step to speed up LLL reductions, see `nf_get_Gtwist`. Suitable for `gerepileupto`, but does not collect garbage.

`GEN Hermite_bound(long n, long prec)` return a majoration of γ_n^n where γ_n is the Hermite constant for lattices of dimension n . The bound is sharp in dimension $n \leq 8$ and $n = 24$.

13.4.3 Linear dependencies.

The following functions underly the `lindep` GP function:

GEN `lindep`(GEN `v`) real/complex entries, guess that about only the 80% leading bits of the input are correct.

GEN `lindep_bit`(GEN `v`, long `b`) real/complex entries, explicit form of the above: multiply the input by 2^b and round to nearest integer before looking for a linear dependency. Truncating dubious bits allows to find better relations.

GEN `lindepfull_bit`(GEN `v`, long `b`) as `lindep_bit` but return a matrix M with $n = \#v$ columns and r rows, with $r = n + 1$ (if v is real) or $n + 2$ (general case) which is an LLL-reduced basis of the lattice formed by concatenating vertically an identity matrix and the floor of $2^b \text{real}(v)$ and $2^b \text{imag}(v)$ if $r = n + 2$. The first n rows of M potentially correspond to relations: whenever the last $r - n$ entries of a column are small. The function `lindep_bit` essentially returns the first column of M truncated to n components.

GEN `lindep_padic`(GEN `v`) p -adic entries.

GEN `lindep_Xadic`(GEN `v`) polynomial entries.

GEN `deplin`(GEN `v`) returns a nonzero kernel vector for a `t_MAT` input.

Deprecated routine:

GEN `lindep2`(GEN `x`, long `dig`) analogous to `lindep_bit`, with `dig` counting decimal digits.

13.4.4 Reduction modulo matrices.

GEN `ZC_hnfremdiv`(GEN `x`, GEN `y`, GEN `*Q`) assuming y is an invertible ZM in HNF and x is a ZC, returns the ZC R equal to $x \bmod y$ (whose i -th entry belongs to $[-y_{i,i}/2, y_{i,i}/2[)$. Stack clean *unless* x is already reduced (in which case, returns x itself, not a copy). If Q is not NULL, set it to the ZC such that $x = yQ + R$.

GEN `ZM_hnfdivrem`(GEN `x`, GEN `y`, GEN `*Q`) reduce each column of the ZM x using `ZC_hnfremdiv`. If Q is not NULL, set it to the ZM such that $x = yQ + R$.

GEN `ZC_hnfrem`(GEN `x`, GEN `y`) alias for `ZC_hnfremdiv(x,y,NULL)`.

GEN `ZM_hnfrem`(GEN `x`, GEN `y`) alias for `ZM_hnfremdiv(x,y,NULL)`.

GEN `ZC_reducemodmatrix`(GEN `v`, GEN `y`) Let y be a ZM, not necessarily square, which is assumed to be LLL-reduced (otherwise, very poor reduction is expected). Size-reduces the ZC v modulo the \mathbf{Z} -module Y spanned by y : if the columns of y are denoted by (y_1, \dots, y_{n-1}) , we return $y_n \equiv v$ modulo Y , such that the Gram-Schmidt coefficients $\mu_{n,j}$ are less than $1/2$ in absolute value for all $j < n$. In short, y_n is almost orthogonal to Y .

GEN `ZM_reducemodmatrix`(GEN `v`, GEN `y`) Let y be as in `ZC_reducemodmatrix`, and v be a ZM. This returns a matrix v which is congruent to v modulo the \mathbf{Z} -module spanned by y , whose columns are size-reduced. This is faster than repeatedly calling `ZC_reducemodmatrix` on the columns since most of the Gram-Schmidt coefficients can be reused.

GEN `ZC_reducemodlll`(GEN `v`, GEN `y`) Let y be an arbitrary ZM, LLL-reduce it then call `ZC_reducemodmatrix`.

GEN `ZM_reducemodlll`(GEN `v`, GEN `y`) Let y be an arbitrary ZM, LLL-reduce it then call `ZM_reducemodmatrix`.

Besides the above functions, which were specific to integral input, we also have:

GEN reducemodinvertible(GEN *x*, GEN *y*) *y* is an invertible matrix and *x* a **t_COL** or **t_MAT** of compatible dimension. Returns $x - y[y^{-1}x]$, which has small entries and differs from *x* by an integral linear combination of the columns of *y*. Suitable for **gerepileupto**, but does not collect garbage.

GEN closemodinvertible(GEN *x*, GEN *y*) returns $x - \text{reducemodinvertible}(x, y)$, i.e. an integral linear combination of the columns of *y*, which is close to *x*.

GEN reducemodlll(GEN *x*, GEN *y*) LLL-reduce the nonsingular ZM *y* and call **reducemodinvertible** to find a small representative of $x \bmod y\mathbf{Z}^n$. Suitable for **gerepileupto**, but does not collect garbage.

13.5 Finite abelian groups and characters.

13.5.1 Abstract groups.

A finite abelian group *G* in GP format is given by its Smith Normal Form as a pair $[h, d]$ or triple $[h, d, g]$. Here *h* is the cardinality of *G*, (d_i) is the vector of elementary divisors, and (g_i) is a vector of generators. In short, $G = \oplus_{i \leq n} (\mathbf{Z}/d_i\mathbf{Z})g_i$, with $d_n \mid \dots \mid d_2 \mid d_1$ and $\prod d_i = h$.

Let $e(x) := \exp(2i\pi x)$. For ease of exposition, we restrict to complex-valued characters, but everything applies to more general fields *K* where *e* denotes a morphism $(\mathbf{Q}, +) \rightarrow (K^*, \times)$ such that $e(a/b)$ denotes a *b*-th root of unity.

A *character* on the abelian group $\oplus (\mathbf{Z}/d_j\mathbf{Z})g_j$ is given by a row vector $\chi = [a_1, \dots, a_n]$ such that $\chi(\prod g_j^{n_j}) = e(\sum a_j n_j / d_j)$.

GEN cyc_normalize(GEN *d*) shallow function. Given a vector $(d_i)_{i \leq n}$ of elementary divisors for a finite group (no *d_i* vanish), returns the vector $D = [1]$ if $n = 0$ (trivial group) and $[d_1, d_1/d_2, \dots, d_1/d_n]$ otherwise. This will allow to define characters as $\chi(\prod g_j^{x_j}) = e(\sum_j x_j a_j D_j / D_1)$, see **char_normalize**.

GEN char_normalize(GEN *chi*, GEN *ncyc*) shallow function. Given a character **chi** = (a_j) and *ncyc* from **cyc_normalize** above, returns the normalized representation $[d, (n_j)]$, such that $\chi(\prod g_j^{x_j}) = \zeta_d^{\sum_j n_j x_j}$, where $\zeta_d = e(1/d)$ and *d* is *minimal*. In particular, *d* is the order of **chi**. Shallow function.

GEN char_simplify(GEN *D*, GEN *N*) given a quasi-normalized character $[D, (N_j)]$ such that $\chi(\prod g_j^{x_j}) = \zeta_D^{\sum_j N_j x_j}$, but where we only assume that *D* is a multiple of the character order, return a normalized character $[d, (n_j)]$ with *d* *minimal*. Shallow function.

GEN char_denormalize(GEN *cyc*, GEN *d*, GEN *n*) given a normalized representation $[d, n]$ (where *d* need not be minimal) of a character on the abelian group with abelian divisors **cyc**, return the attached character (where the image of each generator *g_i* is given in terms of roots of unity of different orders **cyc**[*i*]).

GEN charconj(GEN *cyc*, GEN *chi*) return the complex conjugate of **chi**.

GEN charmul(GEN *cyc*, GEN *a*, GEN *b*) return the product character $a \times b$.

GEN chardiv(GEN *cyc*, GEN *a*, GEN *b*) returns the character $a/b = a \times \bar{b}$.

`int char_check(GEN cyc, GEN chi)` return 1 if `chi` is a character compatible with cyclic factors `cyc`, and 0 otherwise.

`GEN cyc2elts(GEN d)` given a `t_VEC` $d = (d_1, \dots, d_n)$ of nonnegative integers, return the vector of all `t_VECSMALLs` of length n whose i -th entry lies in $[0, d_i[$. Assumes that the product of the d_i fits in a long.

`long zv_cyc_minimize(GEN d, GEN c, GEN coprime)` given $d = (d_1, \dots, d_n)$, $d_n \mid \dots \mid d_1 \neq 0$ a list of elementary divisors for a finite abelian group as a `t_VECSMALL`, given $c = [g_1, \dots, g_n]$ representing an element in the group, and given a mask `coprime` (as from `coprimes.zv(o)`) representing a list of forbidden congruence classes modulo o , return an integer k such that `coprime`[$k \% o$] is nonzero and $k \cdot c$ is lexicographically minimal. For instance, if c is attached to a Dirichlet character χ of order o via the usual identification $\chi(g_i) = \zeta_{g_i}^{c_i}$, then χ^k is a “canonical” representative in the Galois orbit of χ .

`long zv_cyc_minimal(GEN d, GEN c, GEN coprime)` return 1 if `zv_cyc_minimize` would return $k = 1$, i.e. c is already the canonical representative for the attached character orbit.

13.5.2 Dirichlet characters.

The functions in this section are specific to characters on $(\mathbf{Z}/N\mathbf{Z})^*$. The argument G is a special `bid` structure as returned by `znstar0(N, nf_INIT)`. In this case, there are additional ways to input character via Conrey’s representation. The character `chi` is either a `t_INT` (Conrey label), a `t_COL` (a Conrey logarithm) or a `t_VEC` (generic character on `bid.gen` as explained in the previous subsection). The following low-level functions are called by GP’s generic character functions.

`int zncharcheck(GEN G, GEN chi)` return 1 if `chi` is a valid character and 0 otherwise.

`GEN zncharconj(GEN G, GEN chi)` as `charconj`.

`GEN znchardiv(GEN G, GEN a, GEN b)` as `chardiv`.

`GEN zncharker(GEN G, GEN chi)` as `charker`.

`GEN znchareval(GEN G, GEN chi, GEN n, GEN z)` as `chareval`.

`GEN zncharmulo(GEN G, GEN a, GEN b)` as `charmulo`.

`GEN zncharpow(GEN G, GEN a, GEN n)` as `charpow`.

`GEN zncharorder(GEN G, GEN chi)` as `charorder`.

The following functions handle characters in Conrey notation (attached to Conrey generators, not `G.gen`):

`int znconrey_check(GEN cyc, GEN chi)` return 1 if `chi` is a valid Conrey logarithm and 0 otherwise.

`GEN znconrey_normalized(GEN G, GEN chi)` return normalized character attached to `chi`, as in `char_normalize` but on Conrey generators.

`GEN znconreyfromchar(GEN G, GEN chi)` return Conrey logarithm attached to the generic (`t_VEC`, on `G.gen`)

`GEN znconreyfromchar_normalized(GEN G, GEN chi)` return normalized Conrey character attached to the generic (`t_VEC`, on `G.gen`) character `chi`.

`GEN znconreylog_normalize(GEN G, GEN m)` given a Conrey logarithm m (`t_COL`), return the attached normalized Conrey character, as in `char_normalize` but on Conrey generators.

GEN `znchar_quad`(GEN `G`, GEN `D`) given a nonzero `t_INT` `D` congruent to 0, 1 mod 4, return $(D/.)$ as a character modulo N , given by a Conrey logarithm (`t_COL`). Assume that $|D|$ divides N .

GEN `Zideallog`(GEN `G`, GEN `x`) return the `znconreylog` of x expressed on `G.gen`, i.e. the ordinary discrete logarithm from `ideallog`.

GEN `ncharvecexpo`(GEN `G`, GEN `nchi`) given `nchi` = $[d, n]$ a quasi-normalized character (d may be a multiple of the character order), i.e. $\chi(g_i) = e(n[i]/d)$ for all Conrey or SNF generators g_i (as usual, we use SNF generators if n is a `t_VEC` and the Conrey generators otherwise). Return a `t_VECSMALL` v such that $v[i] = -1$ if $(i, N) > 1$ else $\chi(i) = e(v[i]/d)$, $1 \leq i \leq N$.

13.6 Hecke characters.

The functions in this section are specific to Hecke characters. The argument `gc` is a `gchar` structure as returned by `gcharinit(bnf, mod)`, and the character `chi` is a `t_COL` of components on the SNF generators of `gc`.

GEN `eulerf_gchar`(GEN `an`, GEN `p`, long `prec`) `an` being the first component of a Hecke L-function `Ldata` (as output by `lfungchar`) and p a prime number, return the Euler factor at p .

GEN `gchari_lfun`(GEN `gc`, GEN `chi`, GEN `w`) `chi` being a `t_VEC` describing a Hecke character encoded on the internal basis `gc[1]`, return the `Ldata` structure corresponding to the Hecke L-function associated to `chi`.

int `is_gchar_group`(GEN `gc`) return 1 if `gc` is a valid `gchar` structure and 0 otherwise.

GEN `lfungchar`(GEN `gc`, GEN `chi`) return the `Ldata` structure corresponding to the Hecke L-function associated to `chi`.

GEN `vecan_gchar`(GEN `an`, long `n`, long `prec`) `an` being the first component of a Hecke L-function `Ldata` (as output by `lfungchar`), return a `t_VEC` of length n containing the first n Dirichlet coefficients of this L-function, computed to absolute precision `prec`.

13.7 Central simple algebras.

13.7.1 Initialization.

Low-level routines underlying `alginit`; argument `rnf` (resp. `nf`) must be true `rnf` (resp. `nf`) structure. The meaning of `flag` is the same as in `alginit`.

GEN `alg_csa_table`(GEN `nf`, GEN `mt`, long `v`, long `flag`) central simple algebra defined by a multiplication table over `nf`.

GEN `alg_cyclic`(GEN `rnf`, GEN `aut`, GEN `b`, long `flag`) cyclic algebra $(L/K, \sigma, b)$.

GEN `alg_hasse`(GEN `nf`, long `d`, GEN `hi`, GEN `hf`, long `v`, long `flag`) algebra defined by local Hasse invariants.

GEN `alg_hilbert`(GEN `nf`, GEN `a`, GEN `b`, long `v`, long `flag`) quaternion algebra.

GEN `alg_matrix`(GEN `nf`, long `n`, long `v`, long `flag`) matrix algebra of degree `n` over `nf`.

GEN `alg_complete`(GEN `rnf`, GEN `aut`, GEN `hf`, GEN `hi`, long `flag`) cyclic algebra $(L/K, \sigma, b)$ with b computed from the Hasse invariants.

13.7.2 Type checks.

`void checkalg(GEN a)` raise an exception if a was not initialized by `alginit`.

`void checklat(GEN al, GEN lat)` raise an exception if `lat` is not a valid full lattice in the algebra `al`.

`void checkhasse(GEN nf, GEN hi, GEN hf, long n)` raise an exception if (hi, hf) do not describe valid Hasse invariants of a central simple algebra of degree n over nf .

`long alg_type(GEN al)` internal function called by `algtype`: assume `al` was created by `alginit` (thereby saving a call to `checkalg`). Return values are symbolic rather than numeric:

- `al_NULL`: not a valid algebra.
- `al_TABLE`: table algebra output by `altableinit`.
- `al_CSA`: central simple algebra output by `alginit` and represented by a multiplication table over its center.
- `al_CYCLIC`: central simple algebra output by `alginit` and represented by a cyclic algebra.

`long alg_model(GEN al, GEN x)` given an element x in algebra al , check for inconsistencies (raise a type error) and return the representation model used for x :

- `al_ALGEBRAIC`: `basistoalg` form, algebraic representation.
- `al_BASIS`: `algtobasis` form, column vector on the integral basis.
- `al_MATRIX`: matrix with coefficients in an algebra.
- `al_TRIVIAL`: trivial algebra of degree 1; can be understood as both basis or algebraic form (since $e_1 = 1$).

13.7.3 Shallow accessors.

All these routines assume their argument was initialized by `alginit` and provide minor speedups compared to the GP equivalent. The routines returning a `GEN` are shallow.

`long alg_get_absdim(GEN al)` low-level version of `algabsdim`.

`long alg_get_dim(GEN al)` low-level version of `algdim`.

`long alg_get_degree(GEN al)` low-level version of `algdegree`.

`GEN alg_get_aut(GEN al)` low-level version of `algaut`.

`GEN alg_get_auts(GEN al)`, given a cyclic algebra $al = (L/K, \sigma, b)$ of degree n , returns the vector of σ^i , $1 \leq i < n$.

`GEN alg_get_b(GEN al)` low-level version of `algb`.

`GEN alg_get_basis(GEN al)` low-level version of `algbasis`.

`GEN alg_get_center(GEN al)` low-level version of `algcenter`.

`GEN alg_get_char(GEN al)` low-level version of `algchar`.

`GEN alg_get_hasse_f(GEN al)` low-level version of `alghassef`.

`GEN alg_get_hasse_i(GEN al)` low-level version of `alghassei`.

GEN `alg_get_invbasis`(GEN `al`) low-level version of `alginvbasis`.
 GEN `alg_get_multable`(GEN `al`) low-level version of `algmultable`.
 GEN `alg_get_relmultable`(GEN `al`) low-level version of `algrelmultable`.
 GEN `alg_get_splittingfield`(GEN `al`) low-level version of `algsplittingfield`.
 GEN `alg_get_abssplitting`(GEN `al`) returns the absolute *nf* structure attached to the *nf* returned by `algsplittingfield`.
 GEN `alg_get_splitpol`(GEN `al`) returns the relative polynomial defining the *nf* returned by `algsplittingfield`.
 GEN `alg_get_splittingdata`(GEN `al`) low-level version of `algsplittingdata`.
 GEN `alg_get_splittingbasis`(GEN `al`) the matrix *Lbas* from `algsplittingdata`.
 GEN `alg_get_splittingbasisinv`(GEN `al`) the matrix *Lbasinv* from `algsplittingdata`.
 GEN `alg_get_tracebasis`(GEN `al`) returns the traces of the basis elements; used by `algtrace`.
 GEN `alglat_get_primbasis`(GEN `lat`) from the description of `lat` as λL with $L \subset \mathcal{O}_0$ and $\lambda \in \mathbf{Q}$, returns a basis of L .
 GEN `alglat_get_scalar`(GEN `lat`) from the description of `lat` as λL with $L \subset \mathcal{O}_0$ and $\lambda \in \mathbf{Q}$, returns λ .

13.7.4 Other low-level functions.

GEN `conjclasses_algcenter`(GEN `cc`, GEN `p`) low-level function underlying `alggroupcenter`, where `cc` is the output of `groupelts_to_conjclasses`, and `p` is either NULL or a prime number. Not stack clean.
 GEN `algsimpledec_ss`(GEN `al`, long `maps`) assuming that `al` is semisimple, returns the second component of `algsimpledec(al,maps)`.

Chapter 14:

Elliptic curves and arithmetic geometry

This chapter is quite short, but is added as a placeholder, since we expect the library to expand in that direction.

14.1 Elliptic curves.

Elliptic curves are represented in the Weierstrass model

$$(E) : y^2z + a_1xyz + a_3yz = x^3 + a_2x^2z + a_4xz^2 + a_6z^3,$$

by the 5-tuple $[a_1, a_2, a_3, a_4, a_6]$. Points in the projective plane are represented as follows: the point at infinity $(0 : 1 : 0)$ is coded as `[0]`, a finite point $(x : y : 1)$ outside the projective line at infinity $z = 0$ is coded as $[x, y]$. Note that other points at infinity than $(0 : 1 : 0)$ cannot be represented; this is harmless, since they do not belong to any of the elliptic curves E above.

Points on the curve are just projective points as described above, they are not tied to a curve in any way: the same point may be used in conjunction with different curves, provided it satisfies their equations (if it does not, the result is usually undefined). In particular, the point at infinity belongs to all elliptic curves.

As with `factor` for polynomial factorization, the 5-tuple $[a_1, a_2, a_3, a_4, a_6]$ implicitly defines a base ring over which the curve is defined. Point coordinates must be operation-compatible with this base ring (`gadd`, `gmul`, `gdiv` involving them should not give errors).

14.1.1 Types of elliptic curves.

We call a 5-tuple as above an `ell5`; most functions require an `ell` structure, as returned by `ellinit`, which contains additional data (usually dynamically computed as needed), depending on the base field.

`GEN ellinit(GEN E, GEN D, long prec)`, returns an `ell` structure, attached to the elliptic curve E : either an `ell5`, a pair $[a_4, a_6]$ or a `t_STR` in Cremona's notation, e.g. "11a1". The optional D (NULL to omit) describes the domain over which the curve is defined.

14.1.2 Type checking.

`void checkell(GEN e)` raise an error unless e is an `ell`.

`int checkell_i(GEN e)` return 1 if e is an `ell` and 0 otherwise.

`void checkell5(GEN e)` raise an error unless e is an `ell` or an `ell5`.

`void checkellpt(GEN z)` raise an error unless z is a point (either finite or at infinity).

`int checkellpt_i(GEN z)` return 1 if z is a point (either finite or at infinity) and 0 otherwise.

`long ell_get_type(GEN e)` returns the domain type over which the curve is defined, one of

`t_ELL_Q` the field of rational numbers;

`t_ELL_NF` a number field;

`t_ELL_Qp` the field of p -adic numbers, for some prime p ;

`t_ELL_Fp` a prime finite field, base field elements are represented as \mathbb{F}_p , i.e. a `t_INT` reduced modulo p ;

`t_ELL_Fq` a nonprime finite field (a prime finite field can also be represented by this subtype, but this is inefficient), base field elements are represented as `t_FFELT`;

`t_ELL_Rg` none of the above.

`void checkell_Fq(GEN e)` checks whether e is an `ell`, defined over a finite field (either prime or nonprime). Otherwise the function raises a `pari_err_TYPE` exception.

`void checkell_Q(GEN e)` checks whether e is an `ell`, defined over \mathbb{Q} . Otherwise the function raises a `pari_err_TYPE` exception.

`void checkell_Qp(GEN e)` checks whether e is an `ell`, defined over some \mathbb{Q}_p . Otherwise the function raises a `pari_err_TYPE` exception.

`void checkellisog(GEN v)` raise an error unless v is an isogeny, from `ellisogeny`.

14.1.3 Extracting info from an `ell` structure.

These functions expect an `ell` argument. If the required data is not part of the structure, it is computed then inserted, and the new value is returned.

14.1.3.1 All domains.

`GEN ell_get_a1(GEN e)`

`GEN ell_get_a2(GEN e)`

`GEN ell_get_a3(GEN e)`

`GEN ell_get_a4(GEN e)`

`GEN ell_get_a6(GEN e)`

`GEN ell_get_b2(GEN e)`

`GEN ell_get_b4(GEN e)`

`GEN ell_get_b6(GEN e)`

`GEN ell_get_b8(GEN e)`

`GEN ell_get_c4(GEN e)`

`GEN ell_get_c6(GEN e)`

`GEN ell_get_disc(GEN e)`

`GEN ell_get_j(GEN e)`

14.1.3.2 Curves over \mathbf{Q} .

`GEN ellQ_get_N(GEN e)` returns the curve conductor

`void ellQ_get_Nfa(GEN e, GEN *N, GEN *faN)` sets N to the conductor and faN to its factorization

`int ell_is_integral(GEN e)` return 1 if e is given by an integral model, and 0 otherwise.

`long ellQ_get_CM(GEN e)` if e has CM by a principal imaginary quadratic order, return its discriminant. Else return 0.

`long ellap_CM_fast(GEN e, ulong p, long CM)` assuming that p does not divide the discriminant of E (in particular, E has good reduction at p), and that CM is as given by `ellQ_get_CM`, return the trace of Frobenius for E/\mathbf{F}_p . This is meant to quickly compute lots of a_p , esp. when e has CM by a principal quadratic order.

`long ellrootno_global(GEN e)` returns the global root number $c \in \{-1, 1\}$.

`GEN ellheightoo(GEN E, GEN P, long prec)` given $P = [x, y]$ an affine point on E , return

$$\lambda_\infty(P) + \frac{1}{12} \log |\text{disc} E| = \frac{1}{2} \text{real}(z\eta(z)) - \log |\sigma(E, z)| \in \mathbf{R},$$

where $\lambda_\infty(P)$ is the canonical local height at infinity and z is `ellpointtoz`(E, P). This is computed using Mestre's (quadratically convergent) AGM algorithm.

`long ellorder_Q(GEN E, GEN P)` return the order of $P \in E(\mathbf{Q})$, using the impossible value 0 for a point of infinite order. Ultimately called by the generic `ellorder` function.

`GEN point_to_a4a6(GEN E, GEN P, GEN p, GEN *a4)` given E/\mathbf{Q} , $p \neq 2, 3$ not dividing the discriminant of E and $P \in E(\mathbf{Q})$ outside the kernel of reduction, return the image of P on the short Weierstrass model $y^2 = x^3 + a_4x + a_6$ isomorphic to the reduction E_p of E at p . Also set $\mathbf{a4}$ to the a_4 coefficient in the above model. This function allows quick computations modulo varying primes p , avoiding the overhead of `ellinit`(E, p), followed by a change of coordinates. It produces data suitable for `FpE` routines.

`GEN point_to_a4a6_Fl(GEN E, GEN P, ulong p, ulong *pa4)` as `point_to_a4a6`, returning a `Fl`.

`GEN elldatagenerators(GEN E)` returns generators for $E(\mathbf{Q})$ extracted from Cremona's table.

`GEN ellanal_globalred(GEN e, GEN *v)` takes an *ell* over \mathbf{Q} and returns a global minimal model E (in `ellinit` form, over \mathbf{Q}) for e suitable for analytic computations related to the curve L series: it contains `ellglobalred` data, as well as global and local root numbers. If \mathbf{v} is not `NULL`, set \mathbf{v} to the needed change of variable: `NULL` if e was already the standard minimal model, such that $E = \text{ellchangecurve}(e, \mathbf{v})$ otherwise. Compared to the direct use of `ellchangecurve` followed by `ellrootno`, this function avoids converting unneeded dynamic data and avoids potential memory leaks (the changed curve would have had to be deleted using `obj_free`). The original curve e is updated as well with the same information.

`GEN ellanal_globalred_all(GEN e, GEN *v, GEN *N, GEN *tam)` as `ellanal_globalred`; further set \mathbf{N} to the curve conductor and \mathbf{tam} to the product of the local Tamagawa numbers, including the factor at infinity (multiply by the number of connected components of $e(\mathbf{R})$).

`GEN ellintegralmodel(GEN e, GEN *pv)` return an integral model for e (in `ellinit` form, over \mathbf{Q}). Set $v = \text{NULL}$ (already integral, we returned e itself), else to the variable change $[u, 0, 0, 0]$ making e integral. We have $u = 1/t$, $t > 1$.

GEN `ellintegralmodel_i`(GEN `e`, GEN `*pv`) shallow version of `ellintegralmodel`.

GEN `ellQtwist_bsdperiod`(GEN `E`, long `s`) let E be a rational elliptic curve given by a minimal model, Λ_E its period lattice, and $s \in \{-1, 1\}$. Let Ω_E^\pm be the canonical periods in $\sqrt{\pm 1}\mathbf{R}^+$ generating $\Lambda_E \cap \sqrt{\pm 1}\mathbf{R}$. Return Ω_E^+ if $s = 1$ and Ω_E^- if $s = -1$.

GEN `elltors_psylo`(GEN `e`, ulong `p`) as `elltors`, but return the p -Sylow subgroup of the torsion group.

GEN `elleulerf`(GEN `E`, GEN `p`) returns the Euler factor at p of the L -function associated to the curve E defined over a number field.

Deprecated routines.

GEN `elltors0`(GEN `e`, long `flag`) this function is deprecated; use `elltors`

14.1.3.3 Curves over a number field nf .

Let K be the number field over which E is defined, given by a nf or bnf structure.

GEN `ellnf_get_nf`(GEN `E`) returns the underlying nf .

GEN `ellnf_get_bnf`(GEN `x`) returns NULL if K does not contain a bnf structure, else return the bnf .

GEN `ellnf_vecarea`(GEN `E`) returns the vector of the period lattices areas of all the complex embeddings of E in the same order as `E.nf.roots`.

GEN `ellnf_veceta`(GEN `E`) returns the vector of the quasi-periods of all the complex embeddings of E in the same order as `E.nf.roots`.

GEN `ellnf_vecomega`(GEN `E`) returns the vector of the periods of all the complex embeddings of E in the same order as `E.nf.roots`.

14.1.3.4 Curves over \mathbf{Q}_p .

GEN `ellQp_get_p`(GEN `E`) returns p

long `ellQp_get_prec`(GEN `E`) returns the default p -adic accuracy to which we must compute approximate results attached to E .

GEN `ellQp_get_zero`(GEN `x`) returns $O(p^n)$, where n is the default p -adic accuracy as above.

The following functions are only defined when E has multiplicative reduction (Tate curves):

GEN `ellQp_Tate_uniformization`(GEN `E`, long `prec`) returns a `t_VEC` containing $u^2, u, q, [a, b]$, at p -adic precision `prec`.

GEN `ellQp_u`(GEN `E`, long `prec`) returns u .

GEN `ellQp_u2`(GEN `E`, long `prec`) returns u^2 .

GEN `ellQp_q`(GEN `E`, long `prec`) returns the Tate period q .

GEN `ellQp_ab`(GEN `E`, long `prec`) returns $[a, b]$.

GEN `ellQp_AGM`(GEN `E`, long `prec`) returns $[a, b, R, v]$, where v is an integer, a, b, R are vectors describing the sequence of 2-isogenous curves $E_i : y^2 = x(x + A_i)(x + A_i - B_i)$, $i \geq 1$ converging to the singular curve $E_\infty : y^2 = x^2(x + M)$. We have $a[i] = A[i]p^v$, $b[i] = B[i]p^v$, $R[i] = A_i - B_i$. These are used in `ellpointtoz` and `ellztopoint`.

GEN `ellQp_L`(GEN `E`, long `prec`) returns the \mathcal{L} -invariant L .

GEN `ellQp_root`(GEN `E`, long `prec`) returns e_1 .

14.1.3.5 Curves over a finite field \mathbf{F}_q .

`GEN ellff_get_p(GEN E)` returns the characteristic

`GEN ellff_get_field(GEN E)` returns p if \mathbf{F}_q is a prime field, and a `t_FFELT` belonging to \mathbf{F}_q otherwise.

`GEN ellff_get_card(GEN E)` returns $\#E(\mathbf{F}_q)$

`GEN ellff_get_gens(GEN E)` returns a minimal set of generators for $E(\mathbf{F}_q)$.

`GEN ellff_get_group(GEN E)` returns `ellgroup(E)`.

`GEN ellff_get_m(GEN E)` returns the `t_INT` m as needed by the `gen_ellgroup` function (the order of the pairing required to verify a generating set).

`GEN ellff_get_o(GEN E)` returns $[d, \text{factord}]$, where d is the exponent of $E(\mathbf{F}_q)$.

`GEN ellff_get_D(GEN E)` returns the elementary divisors for $E(\mathbf{F}_q)$ in a form suitable for `gen_ellgens`: either $[d_1]$ or $[d_1, d_2]$, where d_1 is in `ellff_get_o` format.

$[d, \text{factord}]$, where d is the exponent of $E(\mathbf{F}_q)$.

`GEN ellff_get_a4a6(GEN E)` returns a canonical “short model” for E , and the corresponding change of variable $[u, r, s, t]$. For $p \neq 2, 3$, this is $[A_4, A_6, [u, r, s, t]]$, corresponding to $y^2 = x^3 + A_4x + A_6$, where $A_4 = -27c_4$, $A_6 = -54c_6$, $[u, r, s, t] = [6, 3b_2, 3a_1, 108a_3]$.

- If $p = 3$ and the curve is ordinary ($b_2 \neq 0$), this is $[[b_2], A_6, [1, v, -a_1, -a_3]]$, corresponding to

$$y^2 = x^3 + b_2x^2 + A_6,$$

where $v = b_4/b_2$, $A_6 = b_6 - v(b_4 + v^2)$.

- If $p = 3$ and the curve is supersingular ($b_2 = 0$), this is $[-b_4, b_6, [1, 0, -a_1, -a_3]]$, corresponding to

$$y^2 = x^3 + 2b_4x + b_6.$$

- If $p = 2$ and the curve is ordinary ($a_1 \neq 0$), return $[A_2, A_6, [a_1^{-1}, da_1^{-2}, 0, (a_4 + d^2)a_1^{-1}]]$, corresponding to

$$y^2 + xy = x^3 + A_2x^2 + A_6,$$

where $d = a_3/a_1$, $a_1^2A_2 = (a_2 + d)$ and

$$a_1^6A_6 = d^3 + a_2d^2 + a_4d + a_6 + (a_4^2 + d^4)a_1^{-2}.$$

- If $p = 2$ and the curve is supersingular ($a_1 = 0$, $a_3 \neq 0$), return $[[a_3, A_4, 1/a_3], A_6, [1, a_2, 0, 0]]$, corresponding to

$$y^2 + a_3y = x^3 + A_4x + A_6,$$

where $A_4 = a_2^2 + a_4$, $A_6 = a_2a_4 + a_6$. The value $1/a_3$ is included in the vector since it is frequently needed in computations.

14.1.3.6 Curves over \mathbf{C} . (This includes curves over \mathbf{Q} !)

`long ellR_get_prec(GEN E)` return the default accuracy to which we must compute approximate results attached to E .

`GEN ellR_ab(GEN E, long prec)` return $[a, b]$

`GEN ellR_omega(GEN x, long prec)` return periods $[\omega_1, \omega_2]$.

`GEN ellR_eta(GEN E, long prec)` return quasi-periods $[\eta_1, \eta_2]$.

`GEN ellR_area(GEN x, long prec)` return the area $(\Im(\omega_1 \overline{\omega_2}))$.

`GEN ellR_roots(GEN E, long prec)` return $[e_1, e_2, e_3]$. If E is defined over \mathbf{R} , then e_1 is real. If furthermore $\text{disc} E > 0$, then $e_1 > e_2 > e_3$.

`long ellR_get_sign(GEN E)` if E is defined over \mathbf{R} returns the signe of its discriminant, otherwise return 0.

14.1.4 Points.

`int ell_is_inf(GEN z)` tests whether the point z is the point at infinity.

`GEN ellinf()` returns the point at infinity $[0]$.

14.1.5 Change of variables.

`GEN ellchangeinvert(GEN w)` given a change of variables $w = [u, r, s, t]$, returns the inverse change of variables w' , such that if $E' = \text{ellchangecurve}(E, w)$, then $E = \text{ellchangecurve}(E', w')$.

14.1.6 Generic helper functions.

The naming scheme assumes an affine equation $F(x, y) = f(x) - (y^2 + h(x)y) = 0$ in standard Weierstrass form: $f = x^3 + a_2x^2 + a_4x + a_6$, $h = a_1x + a_3$. Unless mentionned otherwise, these routine assume that all arguments are compatible with generic functions of `gadd` or `gmul` type. In particular they do not handle elements in number field in `nfalgtobasis` format.

`GEN ellbasechar(GEN E)` returns the characteristic of the base ring over which E is defined.

`GEN ec_bmodel(GEN E, long v)` returns the polynomial $4x^3 + b_2x^2 + 2b_4x + b_6$ in the variable v .

`GEN ec_phi2(GEN E, long v)` returns the polynomial $x^4 - b_4x^2 - 2b_6x - b_8$ in the variable v .

`GEN ec_f_evalx(GEN E, GEN x)` returns $f(x)$.

`GEN ec_h_evalx(GEN E, GEN x)` returns $h(x)$.

`GEN ec_dFdx_evalQ(GEN E, GEN Q)` returns $3x^2 + 2a_2x + a_4 - a_1y$, where $Q = [x, y]$.

`GEN ec_dFdy_evalQ(GEN E, GEN Q)` returns $-(2y + a_1x + a_3)$, where $Q = [x, y]$.

`GEN ec_dmFdy_evalQ(GEN e, GEN Q)` returns $2y + a_1x + a_3$, where $Q = [x, y]$.

`GEN ec_2divpol_evalx(GEN E, GEN x)` returns $4x^3 + b_2x^2 + 2b_4x + b_6$. This function supports inputs in `nfalgtobasis` format.

`GEN ec_half_deriv_2divpol(GEN E, long v)` returns $6x^2 + b_2x + b_4$ as a `t_POL` in the variable v .

`GEN ec_half_deriv_2divpol_evalx(GEN E, GEN x)` returns $6x^2 + b_2x + b_4$.

`GEN ec_3divpol_evalx(GEN E, GEN x)` returns $3x^4 + b_2x^2 + 3b_4x^2 + 3b_6x + b_8$.

14.1.7 Functions to handle elliptic curves over finite fields.

14.1.7.1 Tolerant routines.

`GEN ellap(GEN E, GEN p)` given a prime number p and an elliptic curve defined over \mathbf{Q} or \mathbf{Q}_p (assumed integral and minimal at p), computes the trace of Frobenius $a_p = p + 1 - \#E(\mathbf{F}_p)$. If E is defined over a nonprime finite field \mathbf{F}_q , ignore p and return $q + 1 - \#E(\mathbf{F}_q)$. When p is implied (E defined over \mathbf{Q}_p or a finite field), p can be omitted (set to `NULL`).

14.1.7.2 Curves defined a nonprime finite field. In this subsection, we assume that `ell_get_type(E)` is `t_ELL_Fq`. (As noted above, a curve defined over $\mathbf{Z}/p\mathbf{Z}$ can be represented as a `t_ELL_Fq`.)

`GEN FF_elltwist(GEN E)` returns the coefficients $[a_1, a_2, a_3, a_4, a_6]$ of the quadratic twist of E .

`GEN FF_ellmul(GEN E, GEN P, GEN n)` returns $[n]P$ where n is an integer and P is a point on the curve E .

`GEN FF_ellrandom(GEN E)` returns a random point in $E(\mathbf{F}_q)$. This function never returns the point at infinity, unless this is the only point on the curve.

`GEN FF_ellorder(GEN E, GEN P, GEN o)` returns the order of the point P , where o is a multiple of the order of P , or its factorization.

`GEN FF_ellcard(GEN E)` returns $\#E(\mathbf{F}_q)$.

`GEN FF_ellcard_SEA(GEN E, long s)` This function returns $\#E(\mathbf{F}_q)$, using the Schoof-Elkies-Atkin algorithm. Assume $p \neq 2, 3$. The parameter s has the same meaning as in `Fp_ellcard_SEA`.

`GEN FF_ellgens(GEN E)` returns the generators of the group $E(\mathbf{F}_q)$.

`GEN FF_elllog(GEN E, GEN P, GEN G, GEN o)` Let G be a point of order o , return e such that $[e]P = G$. If e does not exists, the result is undefined.

`GEN FF_ellgroup(GEN E, GEN *pm)` returns the structure of the Abelian group $E(\mathbf{F}_q)$ and set `*pm` to m (see `gen_ellgens`).

`GEN FF_ellweilpairing(GEN E, GEN P, GEN Q, GEN m)` returns the Weil pairing of the points of m -torsion P and Q .

`GEN FF_elltatepairing(GEN E, GEN P, GEN Q, GEN m)` returns the Tate pairing of P and Q , where $[m]P = 0$.

14.2 Arithmetic on elliptic curve over a finite field in simple form.

The functions in this section no longer operate on elliptic curve structures, as seen up to now. They are used to implement those higher-level functions without using cached information and thus require suitable explicitly enumerated data.

14.2.1 Helper functions.

`GEN elltrace_extension(GEN t, long n, GEN q)` Let E some elliptic curve over \mathbf{F}_q such that the trace of the Frobenius is t , returns the trace of the Frobenius over \mathbf{F}_q^n .

14.2.2 Elliptic curves over \mathbf{F}_p , $p > 3$.

Let p a prime number and E the elliptic curve given by the equation $E: y^2 = x^3 + a_4x + a_6$, with a_4 and a_6 in \mathbf{F}_p . A **FpE** is a point of $E(\mathbf{F}_p)$. Since an affine point and a_4 determine a unique a_6 , most functions do not take a_6 as an argument. A **FpE** is either the point at infinity (**ellinf()**) or a **FpV** with two components. The parameters a_4 and a_6 are given as **t_INTs** when required.

GEN Fp_ellj(**GEN a4**, **GEN a6**, **GEN p**) returns the j -invariant of the curve E .

void Fp_ellj_to_a4a6(**GEN j**, **GEN p**, **GEN *pa4**, **GEN *pa6**) sets ***pa4** to a_4 and ***pa6** to a_6 where a_4 and a_6 define a fixed elliptic curve with j -invariant j .

int Fp_elljissupersingular(**GEN j**, **GEN p**) returns 1 if j is the j -invariant of a supersingular curve over \mathbf{F}_p , 0 otherwise.

GEN Fp_ellcard(**GEN a4**, **GEN a6**, **GEN p**) returns the cardinality of the group $E(\mathbf{F}_p)$.

GEN Fp_ellcard_SEA(**GEN a4**, **GEN a6**, **GEN p**, **long s**) This function returns $\#E(\mathbf{F}_p)$, using the Schoof-Elkies-Atkin algorithm. If the **seadata** package is installed, the function will be faster.

The extra flag **s**, if set to a nonzero value, causes the computation to return **gen_0** (an impossible cardinality) if one of the small primes ℓ divides the curve order but does not divide s . For cryptographic applications, where one is usually interested in curves of prime order, setting $s = 1$ efficiently weeds out most uninteresting curves; if curves of order a power of 2 times a prime are acceptable, set $s = 2$. If moreover **s** is negative, similar checks are performed for the twist of the curve.

GEN Fp_ffellcard(**GEN a4**, **GEN a6**, **GEN q**, **long n**, **GEN p**) returns the cardinality of the group $E(\mathbf{F}_q)$ where $q = p^n$.

GEN Fp_ellgroup(**GEN a4**, **GEN a6**, **GEN N**, **GEN p**, **GEN *pm**) returns the group structure D of the group $E(\mathbf{F}_p)$, which is assumed to be of order N and set ***pm** to m .

GEN Fp_ellgens(**GEN a4**, **GEN a6**, **GEN ch**, **GEN D**, **GEN m**, **GEN p**) returns generators of the group $E(\mathbf{F}_p)$ with the base change **ch** (see **FpE_changepoint**), where D and m are as returned by **Fp_ellgroup**.

GEN Fp_elldivpol(**GEN a4**, **GEN a6**, **long n**, **GEN p**) returns the n -division polynomial of the elliptic curve E .

void Fp_elltwist(**GEN a4**, **GEN a6**, **GEN p**, **GEN *pa4**, **GEN *pa6**) sets ***pa4** and ***pa6** to the corresponding parameters for the quadratic twist of E . Assume p is an odd prime.

14.2.3 **FpE**.

GEN FpE_add(**GEN P**, **GEN Q**, **GEN a4**, **GEN p**) returns the sum $P + Q$ in the group $E(\mathbf{F}_p)$, where E is defined by $E: y^2 = x^3 + a_4x + a_6$, for any value of a_6 compatible with the points given.

GEN FpE_sub(**GEN P**, **GEN Q**, **GEN a4**, **GEN p**) returns $P - Q$.

GEN FpE_dbl(**GEN P**, **GEN a4**, **GEN p**) returns $2.P$.

GEN FpE_neg(**GEN P**, **GEN p**) returns $-P$.

GEN FpE_mul(**GEN P**, **GEN n**, **GEN a4**, **GEN p**) return $n.P$.

GEN FpE_changepoint(**GEN P**, **GEN m**, **GEN a4**, **GEN p**) returns the image Q of the point P on the curve $E: y^2 = x^3 + a_4x + a_6$ by the coordinate change m (which is a **FpV**).

GEN FpE_changepointinv(GEN P, GEN m, GEN a4, GEN p) returns the image Q on the curve $E : y^2 = x^3 + a_4x + a_6$ of the point P by the inverse of the coordinate change m (which is a \mathbf{FpV}).

GEN random_FpE(GEN a4, GEN a6, GEN p) returns a random point on $E(\mathbf{F}_p)$, where E is defined by $E : y^2 = x^3 + a_4x + a_6$.

GEN FpE_order(GEN P, GEN o, GEN a4, GEN p) returns the order of P in the group $E(\mathbf{F}_p)$, where o is a multiple of the order of P , or its factorization.

GEN FpE_log(GEN P, GEN G, GEN o, GEN a4, GEN p) Let G be a point of order o , return e such that $e.P = G$. If e does not exists, the result is currently undefined.

GEN FpE_tatepairing(GEN P, GEN Q, GEN m, GEN a4, GEN p) returns the Tate pairing of the point of m -torsion P and the point Q .

GEN FpE_weilpairing(GEN P, GEN Q, GEN m, GEN a4, GEN p) returns the Weil pairing of the points of m -torsion P and Q .

GEN FpE_to_mod(GEN P, GEN p) returns P as a vector of $\mathbf{t_INTMODs}$.

GEN RgE_to_FpE(GEN P, GEN p) returns the \mathbf{FpE} obtained by applying $\mathbf{Rg_to_Fp}$ coefficientwise.

14.2.4 Fle. Let p be a prime `ulong`, and E the elliptic curve given by the equation $E : y^2 = x^3 + a_4x + a_6$, where a_4 and a_6 are `ulong`. A `Fle` is either the point at infinity (`ellinf()`), or a `Flv` with two components $[x, y]$.

`long Fl_elltrace(ulong a4, ulong a6, ulong p)` returns the trace t of the Frobenius of $E(\mathbf{F}_p)$. The cardinality of $E(\mathbf{F}_p)$ is thus $p + 1 - t$, which might not fit in an `ulong`.

`long Fl_elltrace_CM(long CM, ulong a4, ulong a6, ulong p)` as `Fl_elltrace`. If \mathbf{CM} is 0, use the standard algorithm; otherwise assume the curve has CM by a principal imaginary quadratic order of discriminant \mathbf{CM} and use a faster algorithm. Useful when the curve is the reduction of E/\mathbf{Q} , which has CM by a principal order, and we need the trace of Frobenius for many distinct p , see `ellQ_get_CM`.

`ulong Fl_elldisc(ulong a4, ulong a6, ulong p)` returns the discriminant of the curve E .

`ulong Fl_elldisc_pre(ulong a4, ulong a6, ulong p, ulong pi)` returns the discriminant of the curve E , assuming pi is the pseudoinverse of p .

`ulong Fl_ellj(ulong a4, ulong a6, ulong p)` returns the j -invariant of the curve E .

`ulong Fl_ellj_pre(ulong a4, ulong a6, ulong p, ulong pi)` returns the j -invariant of the curve E , assuming pi is the pseudoinverse of p .

`void Fl_ellj_to_a4a6(ulong j, ulong p, ulong *pa4, ulong *pa6)` sets $*pa4$ to a_4 and $*pa6$ to a_6 where a_4 and a_6 define a fixed elliptic curve with j -invariant j .

`void Fl_elltwist(ulong a4, ulong a6, ulong p, ulong *pA4, ulong *pA6)` set $*pA4$ to A_4 and $*pA6$ to A_6 where A_4 and A_6 define the twist of E .

`void Fl_elltwist_disc(ulong a4, ulong a6, ulong D, ulong p, ulong *pA4, ulong *pA6)` sets $*pA4$ to A_4 and $*pA6$ to A_6 where A_4 and A_6 define the twist of E by the discriminant D .

GEN Fl_ellptors(ulong l, ulong N, ulong a4, ulong a6, ulong p) return a basis of the l -torsion subgroup of E .

GEN Fle_add(GEN P, GEN Q, ulong a4, ulong p)

```

GEN Fle_dbl(GEN P, ulong a4, ulong p)
GEN Fle_sub(GEN P, GEN Q, ulong a4, ulong p)
GEN Fle_mul(GEN P, GEN n, ulong a4, ulong p)
GEN Fle_mulu(GEN P, ulong n, ulong a4, ulong p)
GEN Fle_order(GEN P, GEN o, ulong a4, ulong p)
GEN Fle_log(GEN P, GEN G, GEN o, ulong a4, ulong p)
GEN Fle_tatepairing(GEN P, GEN Q, ulong m, ulong a4, ulong p)
GEN Fle_weilpairing(GEN P, GEN Q, ulong m, ulong a4, ulong p)
GEN random_Fle(ulong a4, ulong a6, ulong p)
GEN random_Fle_pre(ulong a4, ulong a6, ulong p, ulong pi)
GEN Fle_changepoint(GEN x, GEN ch, ulong p), ch is assumed to give the change of coordinates
[ $u, r, s, t$ ] as a t_VECSMALL.
GEN Fle_changepointinv(GEN x, GEN ch, ulong p), as Fle_changepoint

```

14.2.5 FpJ.

Let $p > 3$ be a prime `t_INT`, and E the elliptic curve given by the equation $E : y^2 = x^3 + a_4 \times x + a_6$, where a_4 and a_6 are `t_INT`. A `FpJ` is a `FpV` with three components $[x, y, z]$, representing the affine point $[x/z^2, y/z^3]$ in Jacobian coordinates, the point at infinity being represented by $[1, 1, 0]$. The following must holds: $y^2 = x^3 + a_4xz^4 + a_6z^6$. For all nonzero u , the points $[u^2x, u^3y, uz]$ and $[x, y, z]$ are representing the same affine point.

```

GEN FpJ_add(GEN P, GEN Q, GEN a4, GEN p)
GEN FpJ_dbl(GEN P, GEN a4, GEN p)
GEN FpJ_mul(GEN P, GEN n, GEN a4, GEN p);
GEN FpJ_neg(GEN P, GEN p) return  $-P$ .
GEN FpJ_to_FpE(GEN P, GEN p) return the corresponding FpE.
GEN FpE_to_FpJ(GEN P) return the corresponding FpJ.

```

14.2.6 Flj.

Let $p > 3$ be a prime. Below, pi is assumed to be the pseudoinverse of p (see `get_Fl_red`).

```

GEN Fle_to_Flj(GEN P) convert a Fle to an equivalent Flj.
GEN Flj_to_Fle(GEN P, ulong p) convert a Flj to the equivalent Fle.
GEN Flj_to_Fle_pre(GEN P, ulong p, ulong pi) convert a Flj to the equivalent Fle.
GEN Flj_add_pre(GEN P, GEN Q, ulong a4, ulong p, ulong pi)
GEN Flj_dbl_pre(GEN P, ulong a4, ulong p, ulong pi)
GEN Flj_neg(GEN P, ulong p) return  $-P$ .
GEN Flj_mulu_pre(GEN P, ulong n, ulong a4, ulong p, ulong pi)

```

GEN random_Flj_pre(ulong a4, ulong a6, ulong p, ulong pi)

GEN Flj_changepointinv_pre(GEN P, GEN ch, ulong p, ulong pi) where ch is the Flv $[u, r, s, t]$.

GEN FljV_factorback_pre(GEN P, GEN L, ulong p, ulong pi)

14.2.7 Elliptic curves over \mathbf{F}_{2^n} . Let T be an irreducible F2x and E the elliptic curve given by either the equation $E : y^2 + x * y = x^3 + a_2x^2 + a_6$, where a_2, a_6 are F2x in $\mathbf{F}_2[X]/(T)$ (ordinary case) or $E : y^2 + a_3 * y = x^3 + a_4x + a_6$, where a_3, a_4, a_6 are F2x in $\mathbf{F}_2[X]/(T)$ (supersingular case).

A F2xqE is a point of $E(\mathbf{F}_2[X]/(T))$. In the supersingular case, the parameter a2 is actually the t_VEC $[a_3, a_4, a_3^{-1}]$.

GEN F2xq_ellcard(GEN a2, GEN a6, GEN T) Return the order of the group $E(\mathbf{F}_2[X]/(T))$.

GEN F2xq_ellgroup(GEN a2, GEN a6, GEN N, GEN T, GEN *pm) Return the group structure D of the group $E(\mathbf{F}_2[X]/(T))$, which is assumed to be of order N and set *pm to m .

GEN F2xq_ellgens(GEN a2, GEN a6, GEN ch, GEN D, GEN m, GEN T) Returns generators of the group $E(\mathbf{F}_2[X]/(T))$ with the base change ch (see F2xqE_changepoint), where D and m are as returned by F2xq_ellgroup.

void F2xq_elltwist(GEN a4, GEN a6, GEN T, GEN *a4t, GEN *a6t) sets *a4t and *a6t to the parameters of the quadratic twist of E .

14.2.8 F2xqE.

GEN F2xqE_changepoint(GEN P, GEN m, GEN a2, GEN T) returns the image Q of the point P on the curve $E : y^2 + x * y = x^3 + a_2x^2 + a_6$ by the coordinate change m (which is a F2xqV).

GEN F2xqE_changepointinv(GEN P, GEN m, GEN a2, GEN T) returns the image Q on the curve $E : y^2 = x^3 + a_4x + a_6$ of the point P by the inverse of the coordinate change m (which is a F2xqV).

GEN F2xqE_add(GEN P, GEN Q, GEN a2, GEN T)

GEN F2xqE_sub(GEN P, GEN Q, GEN a2, GEN T)

GEN F2xqE_dbl(GEN P, GEN a2, GEN T)

GEN F2xqE_neg(GEN P, GEN a2, GEN T)

GEN F2xqE_mul(GEN P, GEN n, GEN a2, GEN T)

GEN random_F2xqE(GEN a2, GEN a6, GEN T)

GEN F2xqE_order(GEN P, GEN o, GEN a2, GEN T) returns the order of P in the group $E(\mathbf{F}_2[X]/(T))$, where o is a multiple of the order of P , or its factorization.

GEN F2xqE_log(GEN P, GEN G, GEN o, GEN a2, GEN T) Let G be a point of order o , return e such that $e.P = G$. If e does not exists, the result is currently undefined.

GEN F2xqE_tatepairing(GEN P, GEN Q, GEN m, GEN a2, GEN T) returns the Tate pairing of the point of m -torsion P and the point Q .

GEN F2xqE_weilpairing(GEN Q, GEN Q, GEN m, GEN a2, GEN T) returns the Weil pairing of the points of m -torsion P and Q .

GEN RgE_to_F2xqE(GEN P, GEN T) returns the F2xqE obtained by applying Rg_to_F2xq coefficient-wise.

14.2.9 Elliptic curves over \mathbf{F}_q , small characteristic $p > 2$. Let $p > 2$ be a prime `ulong`, T an irreducible `Flx` mod p , and E the elliptic curve given by the equation $E : y^2 = x^3 + a_4x + a_6$, where a_4 and a_6 are `Flx` in $\mathbf{F}_p[X]/(T)$. A `FlxqE` is a point of $E(\mathbf{F}_p[X]/(T))$.

In the special case $p = 3$, ordinary elliptic curves ($j(E) \neq 0$) cannot be represented as above, but admit a model $E : y^2 = x^3 + a_2x^2 + a_6$ with a_2 and a_6 being `Flx` in $\mathbf{F}_3[X]/(T)$. In that case, the parameter `a2` is actually stored as a `t_VEC`, $[a_2]$, to avoid ambiguities.

`GEN Flxq_ellj(GEN a4, GEN a6, GEN T, ulong p)` returns the j -invariant of the curve E .

`void Flxq_ellj_to_a4a6(GEN j, GEN T, ulong p, GEN *pa4, GEN *pa6)` sets `*pa4` to a_4 and `*pa6` to a_6 where a_4 and a_6 define a fixed elliptic curve with j -invariant j .

`GEN Flxq_ellcard(GEN a4, GEN a6, GEN T, ulong p)` returns the order of $E(\mathbf{F}_p[X]/(T))$.

`GEN Flxq_ellgroup(GEN a4, GEN a6, GEN N, GEN T, ulong p, GEN *pm)` returns the group structure D of the group $E(\mathbf{F}_p[X]/(T))$, which is assumed to be of order N and sets `*pm` to m .

`GEN Flxq_ellgens(GEN a4, GEN a6, GEN ch, GEN D, GEN m, GEN T, ulong p)` returns generators of the group $E(\mathbf{F}_p[X]/(T))$ with the base change `ch` (see `FlxqE_changepoint`), where D and m are as returned by `Flxq_ellgroup`.

`void Flxq_elltwist(GEN a4, GEN a6, GEN T, ulong p, GEN *pA4, GEN *pA6)` sets `*pA4` and `*pA6` to the corresponding parameters for the quadratic twist of E .

14.2.10 `FlxqE`.

Let $p > 2$ be a prime number.

`GEN FlxqE_changepoint(GEN P, GEN m, GEN a4, GEN T, ulong p)` returns the image Q of the point P on the curve $E : y^2 = x^3 + a_4x + a_6$ by the coordinate change m (which is a `FlxqV`).

`GEN FlxqE_changepointinv(GEN P, GEN m, GEN a4, GEN T, ulong p)` returns the image Q on the curve $E : y^2 = x^3 + a_4x + a_6$ of the point P by the inverse of the coordinate change m (which is a `FlxqV`).

`GEN FlxqE_add(GEN P, GEN Q, GEN a4, GEN T, ulong p)`

`GEN FlxqE_sub(GEN P, GEN Q, GEN a4, GEN T, ulong p)`

`GEN FlxqE_dbl(GEN P, GEN a4, GEN T, ulong p)`

`GEN FlxqE_neg(GEN P, GEN T, ulong p)`

`GEN FlxqE_mul(GEN P, GEN n, GEN a4, GEN T, ulong p)`

`GEN random_FlxqE(GEN a4, GEN a6, GEN T, ulong p)`

`GEN FlxqE_order(GEN P, GEN o, GEN a4, GEN T, ulong p)` returns the order of P in the group $E(\mathbf{F}_p[X]/(T))$, where o is a multiple of the order of P , or its factorization.

`GEN FlxqE_log(GEN P, GEN G, GEN o, GEN a4, GEN T, ulong p)` Let G be a point of order o , return e such that $e.P = G$. If e does not exist, the result is currently undefined.

`GEN FlxqE_tatepairing(GEN P, GEN Q, GEN m, GEN a4, GEN T, ulong p)` returns the Tate pairing of the point of m -torsion P and the point Q .

`GEN FlxqE_weilpairing(GEN P, GEN Q, GEN m, GEN a4, GEN T, ulong p)` returns the Weil pairing of the points of m -torsion P and Q .

GEN FlxqE_weilpairing_pre(GEN P, GEN Q, GEN m, GEN a4, GEN T, ulong p, ulong pi)
, where pi is a pseudoinverse of p , or 0 in which case we assume SMALL_ULONG(p).

GEN RgE_to_FlxqE(GEN P, GEN T, ulong p) returns the FlxqE obtained by applying Rg_to_Flxq coefficientwise.

GEN Flxq_elldivpolmod(GEN a4, GEN a6, long n, GEN h, GEN T, ulong p) returns the n -division polynomial of the elliptic curve E modulo the polynomial h .

14.2.11 Elliptic curves over \mathbf{F}_q , large characteristic .

Let $p > 3$ be a prime number, T an irreducible polynomial mod p , and E the elliptic curve given by the equation $E : y^2 = x^3 + a_4x + a_6$ with a_4 and a_6 in $\mathbf{F}_p[X]/(T)$. A FpXQE is a point of $E(\mathbf{F}_p[X]/(T))$.

GEN FpXQ_ellj(GEN a4, GEN a6, GEN T, GEN p) returns the j -invariant of the curve E .

int FpXQ_elljissupersingular(GEN j, GEN T, GEN p) returns 1 if j is the j -invariant of a supersingular curve over $\mathbf{F}_p[X]/(T)$, 0 otherwise.

int Fq_elljissupersingular(GEN j, GEN T, GEN p) as FpXQ_elljissupersingular but j can be a t_INT.

GEN ellsupersingularj_FpXQ(GEN T, GEN p) T being a ZX of degree 2, return a random supersingular j -invariant in $\mathbf{F}_p[X]/T$.

GEN FpXQ_ellcard(GEN a4, GEN a6, GEN T, GEN p) returns the order of $E(\mathbf{F}_p[X]/(T))$.

GEN FpXQ_ellcard_supersingular(GEN a4, GEN a6, GEN T, GEN p) This function returns $\#E(\mathbf{F}_p[X]/(T))$, assuming the curve is supersingular, see FpXQ_elljissupersingular.

GEN Fq_ellcard_supersingular(GEN a4, GEN a6, GEN T, GEN p) This function is identical to FpXQ_ellcard_supersingular, except that it allows T to be NULL.

GEN Fq_ellcard_SEA(GEN a4, GEN a6, GEN q, GEN T, GEN p, long s) This function returns $\#E(\mathbf{F}_p[X]/(T))$, using the Schoof-Elkies-Atkin algorithm. Assume $p \neq 2, 3$, and q is the cardinality of $\mathbf{F}_p[X]/(T)$. The parameter s has the same meaning as in Fp_ellcard_SEA. If the seadata package is installed, the function will be faster.

GEN FpXQ_ellgroup(GEN a4, GEN a6, GEN N, GEN T, GEN p, GEN *pm) Return the group structure D of the group $E(\mathbf{F}_p[X]/(T))$, which is assumed to be of order N and set $*pm$ to m .

GEN FpXQ_ellgens(GEN a4, GEN a6, GEN ch, GEN D, GEN m, GEN T, GEN p) Returns generators of the group $E(\mathbf{F}_p[X]/(T))$ with the base change ch (see FpXQE_changepoint), where D and m are as returned by FpXQ_ellgroup.

GEN FpXQ_elldivpol(GEN a4, GEN a6, long n, GEN T, GEN p) returns the n -division polynomial of the elliptic curve E .

GEN Fq_elldivpolmod(GEN a4, GEN a6, long n, GEN h, GEN T, GEN p) returns the n -division polynomial of the elliptic curve E modulo the polynomial h .

void FpXQ_elltwist(GEN a4, GEN a6, GEN T, GEN p, GEN *pA4, GEN *pA6) sets $*pA4$ and $*pA6$ to the corresponding parameters for the quadratic twist of E .

14.2.12 FpXQE.

`GEN FpXQE_changepoint(GEN P, GEN m, GEN a4, GEN T, GEN p)` returns the image Q of the point P on the curve $E : y^2 = x^3 + a_4x + a_6$ by the coordinate change m (which is a `FpXQV`).

`GEN FpXQE_changepointinv(GEN P, GEN m, GEN a4, GEN T, GEN p)` returns the image Q on the curve $E : y^2 = x^3 + a_4x + a_6$ of the point P by the inverse of the coordinate change m (which is a `FpXQV`).

`GEN FpXQE_add(GEN P, GEN Q, GEN a4, GEN T, GEN p)`

`GEN FpXQE_sub(GEN P, GEN Q, GEN a4, GEN T, GEN p)`

`GEN FpXQE_dbl(GEN P, GEN a4, GEN T, GEN p)`

`GEN FpXQE_neg(GEN P, GEN T, GEN p)`

`GEN FpXQE_mul(GEN P, GEN n, GEN a4, GEN T, GEN p)`

`GEN random_FpXQE(GEN a4, GEN a6, GEN T, GEN p)`

`GEN FpXQE_log(GEN P, GEN G, GEN o, GEN a4, GEN T, GEN p)` Let G be a point of order o , return e such that $e.P = G$. If e does not exist, the result is currently undefined.

`GEN FpXQE_order(GEN P, GEN o, GEN a4, GEN T, GEN p)` returns the order of P in the group $E(\mathbb{F}_p[X]/(T))$, where o is a multiple of the order of P , or its factorization.

`GEN FpXQE_tatepairing(GEN P, GEN Q, GEN m, GEN a4, GEN T, GEN p)` returns the Tate pairing of the point of m -torsion P and the point Q .

`GEN FpXQE_weilpairing(GEN P, GEN Q, GEN m, GEN a4, GEN T, GEN p)` returns the Weil pairing of the points of m -torsion P and Q .

`GEN RgE_to_FpXQE(GEN P, GEN T, GEN p)` returns the `FpXQE` obtained by applying `RgE_to_FpXQ` coefficientwise.

14.3 Functions related to modular polynomials.

Variants of `polmodular`, returning the modular polynomial of prime level L for the invariant coded by `inv` (0: j , 1: Weber- f , see `polclass` for the full list).

`GEN polmodular_ZXX(long L, long inv, long vx, long vy)` returns a bivariate polynomial in variables vx and vy .

`GEN polmodular_ZM(long L, long inv)` returns a matrix of (integral) coefficients.

`GEN Fp_polmodular_evalx(long L, long inv, GEN J, GEN p, long v, int derivs)` returns the modular polynomial evaluated at J modulo the prime p in the variable v (if `derivs` is nonzero, returns a vector containing the modular polynomial and its first and second derivatives, all evaluated at J modulo p).

14.3.1 Functions related to modular invariants.

`void check_modinv(long inv)` report an error if `inv` is not a valid code for a modular invariant.

`int modinv_good_disc(long inv, long D)` test whether the invariant `inv` is defined for the discriminant `D`.

`int modinv_good_prime(long inv, long p)` test whether the invariant `inv` is defined for the prime `p`.

`long modinv_height_factor(long inv)` return the height factor of the modular invariant `inv` with respect to the j -invariant. This is an integer n such that the j -invariant is asymptotically of the order of the n -th power of the invariant `inv`.

`long modinv_is_Weber(long inv)` test whether the invariant `inv` is a power of Weber f .

`long modinv_is_double_eta(long inv)` test whether the invariant `inv` is a double η quotient.

`long disc_best_modinv(long D)` the integer D being a negative discriminant, return the modular invariant compatible with D with the highest height factor.

`GEN Fp_modinv_to_j(GEN x, long inv, GEN p)` Let Φ the modular equation between j and the modular invariant `inv`, return y such that $\Phi(y, x) = 0 \pmod{p}$.

14.4 Other curves.

The following functions deal with hyperelliptic curves in weighted projective space $\mathbf{P}_{(1,d,1)}$, with coordinates (x, y, z) and a model of the form $y^2 = T(x, z)$, where T is homogeneous of degree $2d$, and squarefree. Thus the curve is nonsingular of genus $d - 1$.

`long hyperell_locally_soluble(GEN T, GEN p)` assumes that $T \in \mathbf{Z}[X]$ is integral. Returns 1 if the curve is locally soluble over \mathbf{Q}_p , 0 otherwise.

`long nf_hyperell_locally_soluble(GEN nf, GEN T, GEN pr)` let K be a number field, attached to `nf`, `pr` a *prid* attached to some maximal ideal \mathfrak{p} ; assumes that $T \in \mathbf{Z}_K[X]$ is integral. Returns 1 if the curve is locally soluble over $K_{\mathfrak{p}}$. The argument `nf` is a true *nf* structure.

Chapter 15:

L-functions

15.1 Accessors.

```
long is_linit(GEN data)
GEN ldata_get_an(GEN ldata)
GEN ldata_get_dual(GEN ldata)
long ldata_isreal(GEN ldata)
GEN ldata_get_gammavec(GEN ldata)
long ldata_get_degree(GEN ldata)
GEN ldata_get_k(GEN ldata)
GEN ldata_get_k1(GEN ldata)
GEN ldata_get_conductor(GEN ldata)
GEN ldata_get_rootno(GEN ldata)
GEN ldata_get_residue(GEN ldata)
long ldata_get_type(GEN ldata)
long linit_get_type(GEN linit)
GEN linit_get_ldata(GEN linit)
GEN linit_get_tech(GEN linit)
GEN lfun_get_domain(GEN tech)
GEN lfun_get_dom(GEN tech)
long lfun_get_bitprec(GEN tech)
GEN lfun_get_factgammavec(GEN tech)
GEN lfun_get_step(GEN tech)
GEN lfun_get_pol(GEN tech)
GEN lfun_get_Residue(GEN tech)
GEN lfun_get_k2(GEN tech)
GEN lfun_get_w2(GEN tech)
GEN lfun_get_expot(GEN tech)
long lfun_get_bitprec(GEN tech)
```

```

GEN lfunprod_get_fact(GEN tech)
GEN theta_get_an(GEN tdata)
GEN theta_get_K(GEN tdata)
GEN theta_get_R(GEN tdata)
long theta_get_bitprec(GEN tdata)
long theta_get_m(GEN tdata)
GEN theta_get_tdom(GEN tdata)
GEN theta_get_isqrtN(GEN tdata)

```

15.2 Conversions and constructors.

GEN lfunmisc_to_ldata(GEN obj) converts obj to Ldata format. Exception if obj cannot be converted.

GEN lfunmisc_to_ldata_shallow(GEN obj) as lfunmisc_to_ldata, shallow result. Exception if obj cannot be converted.

GEN lfunmisc_to_ldata_shallow_i(GEN obj) as lfunmisc_to_ldata_shallow, returning NULL on failure.

GEN lfunrtopoles(GEN r) given a vector r of “polar parts” $[\beta_i, P_i]$ where β_i is a complex number and P_i is a power series return the (β_i) , sorted with respect to `cmp_universal`.

```
int sdomain_isincl(double k, GEN dom, GEN dom0)
```

GEN ldata_vecan(GEN ldata, long N, long prec) return the vector of coefficients of indices 1 to N to precision `prec`. The output is allowed to be a `t_VECSMALL` when the coefficients are known to be all integral and fit into a `long`; for instance the Dirichlet L function of a real character or the L -function of a rational elliptic curve.

GEN ldata_newprec(GEN ldata, long prec) return a shallow copy of `ldata` with fields accurate to precision `prec`.

long etaquotype(GEN *peta, GEN *pN, GEN *pk, GEN *pCHI, long *pv, long *psd, long *pcusp) Let `eta` be the integer matrix factorization supposedly attached to an η -quotient $f(z) = \prod_i \eta(n_i z)^{e_i}$. Assuming `*peta` is initially set to `eta`, this function returns 0 if there is a type error or this does not define a function on some $X_0(N)$. Else it returns 1 and sets

- `*peta` to a normalized factorization (as would be returned by `factor`),
- `*pN` to the level N of f ,
- `*pk` to the modular weight k of f ,
- `*pCHI` to the Nebentypus of f (quadratic character) as an integer,
- `*pv` to the valuation at infinity $v_q(f)$,
- `*psd` to 1 if and only if f is self-dual,
- `*pcusp` to 1 if f is cuspidal, else to 0 if f holomorphic at all cusps, else to -1 .

The last three arguments `pCHI`, `pv` and `pcusp` can be set to `NULL`, in which case the relevant information is not computed, which saves time.

15.3 Variants of GP functions.

GEN lfun(GEN ldata, GEN s, long bitprec)
GEN lfuninit(GEN ldata, GEN dom, long der, long bitprec)
GEN lfuninit_make(long t, GEN ldata, GEN tech, GEN domain)
GEN lfunlambda(GEN ldata, GEN s, long bitprec)
GEN lfunquadneg(long D, long k) for $L(\chi_D, k)$, D fundamental discriminant and $k \geq 0$.
long lfunthetacost(GEN ldata, GEN tdom, long m, long bitprec): lfunthetacost0 when the first argument is known to be an Ldata.
GEN lfunthetacheckinit(GEN data, GEN tinf, long m, long bitprec)
GEN lfunrootno(GEN data, long bitprec)
GEN lfunabelianrelnit(GEN bnr, GEN subg, GEN dom, long der, long bitprec) where bnr is a true *bnr* structure and subg is a congruence subgroup. Not GC-clean.
GEN lfunzetakininit(GEN nf, GEN dom, long der, long bitprec) where nf is a true *nf* structure. Not GC-clean.
GEN lfunellmfpeters(GEN E, long bitprec)

15.4 Inverse Mellin transforms of Gamma products.

GEN gammamellininv(GEN Vga, GEN s, long m, long bitprec)
GEN gammamellininivinit(GEN Vga, long m, long bitprec)
GEN gammamellininivrt(GEN K, GEN s, long bitprec) not GC-clean, but suitable for gerepile-up to.
int Vgaeasytheta(GEN Vga) return 1 if the inverse Mellin transform is an exponential and 0 otherwise.
double dbllemma526(double a, double b, double c, long B)
double dblcoro526(double a, double c, long B)

Chapter 16: Modular symbols

`void checkms(GEN W)` raise an exception if W is not an *ms* structure from `msinit`.

`void checkmspadic(GEN W)` raise an exception if W is not an *mspadic* structure from `mspadicinit`.

`GEN mseval2_ooQ(GEN W, GEN phi, GEN c)` let W be a `msinit` structure for $k = 2$, ϕ be a modular symbol with integral values and c be a rational number. Return the integer $\phi(p)$, where p is the path $\{\infty, c\}$.

`void mspadic_parse_chi(GEN s, GEN *s1, GEN *s2)` see `mspadicL`; let χ be the cyclotomic character from $\text{Gal}(\mathbf{Q}_p(\mu_{p^\infty})/\mathbf{Q}_p)$ to \mathbf{Z}_p^* and τ be the Teichmüller character for $p > 2$ and the character of order 2 on $(\mathbf{Z}/4\mathbf{Z})^*$ if $p = 2$. Let s encode the p -adic character $\chi^s := \langle \chi \rangle^{s_1} \tau^{s_2}$; set `*s1` and `*s2` to the integers s_1 and s_2 .

`GEN mspadic_unit_eigenvalue(GEN ap, long k, GEN p, long n)` let p be a prime not dividing the trace of Frobenius `ap`, return the unit root of $x^2 - ap * x + p^{(k-1)}$ to p -adic accuracy p^n .

 Variants of `mfnumcusps` :

`ulong mfnumcuspsu(ulong n)`

`GEN mfnumcusps_fact(GEN fa)` where `fa` is `factor(n)`.

`ulong mfnumcuspsu_fact(GEN fa)` where `fa` is `factoru(n)`.

Chapter 17: Modular forms

17.1 Implementation of public data structures.

`void checkMF(GEN mf)` raise an exception if the argument is not a modular form space.

`GEN checkMF_i(GEN mf)` return the underlying modular form space if `mf` is either directly a modular form space from `mfinit` or a symbol from `mfsymbol`. Return `NULL` otherwise.

`int checkmf_i(GEN mf)` return 1 if the argument is a modular form and 0 otherwise.

`int checkfarey_i(GEN F)` return 1 if the argument is a Farey symbol (from `mspolygon` or `msfarey`) and 0 otherwise.

17.1.1 Accessors for modular form spaces.

Shallow functions; assume that their argument is a modular form space is created by `mfinit` and checked using `checkMF`.

`GEN MF_get_gN(GEN mf)` return the level N as a `t_INT`.

`long MF_get_N(GEN mf)` return the level N as a `long`.

`GEN MF_get_gk(GEN mf)` return the level k as a `t_INT`.

`long MF_get_k(GEN mf)` return the level k as a `long`.

`long MF_get_r(GEN mf)` assuming the level is a half-integer, return the integer $r = k - (1/2)$.

`GEN MF_get_CHI(GEN mf)` return the nebentypus χ , which is a special form of character structure attached to Dirichlet characters (see next section). Its values are given as algebraic numbers: either ± 1 or `t_POLMOD` in t .

`long MF_get_space(GEN mf)` returns the space type, corresponding to `mfinit`'s `space` flag. The current list is

`mf_NEW`, `mf_CUSP`, `mf_OLD`, `mf_EISEN`, `mf_FULL`

`GEN MF_get_basis(GEN mf)` return the \mathbf{Q} -basis of the space, concatenation of `MF_get_E` and `MF_get_S`, in this order; the forms have coefficients in $\mathbf{Q}(\chi)$. Low-level version of `mfbasis`.

`long MF_get_dim(GEN mf)` returns the dimension d of the space. It is the cardinality of `MF_get_basis`.

`GEN MF_get_E(GEN mf)` returns a \mathbf{Q} -basis for the subspace spanned by Eisenstein series in the space; the forms have coefficients in $\mathbf{Q}(\chi)$.

`GEN MF_get_S(GEN mf)` returns a \mathbf{Q} -basis for the cuspidal subspace in the space; the forms have coefficients in $\mathbf{Q}(\chi)$.

GEN `MF_get_fields`(GEN `mf`) returns the vector of polynomials defining each Galois orbit of newforms over $\mathbf{Q}(\chi)$. Uses memoization: a first call splits the space and may be costly; subsequent calls return the cached result.

GEN `MF_get_newforms`(GEN `mf`) returns a vector `vF` containing the coordinates of the eigenforms on `MF_get_basis` (`mftobasis` form). Low-level version of `mfeigenbasis`, whose elements are recovered as `mflinear`(`mf`, `gel`(`vF`, `i`)). Uses memoization, sharing the same data as `MF_get_fields`. Note that it is much more efficient to use `mfcoefs`(`mf`,) then multiply by this vector than to compute the coefficients of eigenforms from `mfeigenbasis` individually.

The following accessors are technical,

GEN `MF_get_M`(GEN `mf`) the $(1+m) \times d$ matrix whose j -th column contain the coefficients of the j -th entry in `MF_get_basis`, m is the optimal “Sturm bound” for the space: the maximum of the $v_\infty(f)$ over nonzero forms. It has entries in $\mathbf{Q}(\chi)$.

GEN `MF_get_Mindex`(GEN `mf`) is a `t_VECSMALL` containing d row indices, the corresponding rows of M form an invertible matrix M_0 .

GEN `MF_get_Minv`(GEN `mf`) the inverse of M_0 in a form suitable for fast multiplication.

GEN `MFcusp_get_vMjd`(GEN `mf`) valid only for a full *cuspidal* space. Then the functions in `MF_get_S` are of the form $B_d T_j Tr_M^{new}$. This returns the vector of triples (`t_VECSMALL`) $[M, j, d]$, in the same order.

GEN `MFnew_get_vj`(GEN `mf`) valid only for a *new* space. Then the functions in `MF_get_S` are of the form $T_j Tr_N^{new}$. This returns a `t_VECSMALL` of the Hecke indices j , in the same order.

17.1.2 Accessors for individual modular forms.

GEN `mf_get_gN`(GEN `F`) return the level of F , which may be a multiple of the conductor, as a `t_INT`

`long mf_get_N`(GEN `F`) return the level as a `long`.

GEN `mf_get_gk`(GEN `F`) return the weight of F as a `t_INT` or a `t_FRAC` with denominator 2 (half-integral weight).

`long mf_get_k`(GEN `F`) return the weight as a `long`; if the weight is not integral, this raises an exception.

`long mf_get_r`(GEN `F`) assuming F is a modular form of half-integral weight $k = (2r+1)/2$, return $r = k - (1/2)$.

GEN `mf_get_CHI`(GEN `F`) return the nebentypus, which is a special form of character structure attached to Dirichlet characters (see next section). Its values are given as algebraic numbers: either ± 1 or `t_POLMOD` in t .

GEN `mf_get_field`(GEN `F`) return the polynomial (in variable y) defining $\mathbf{Q}(f)$ over $\mathbf{Q}(\chi)$.

GEN `mf_get_NK`(GEN `F`) return the tag attached to F : a vector containing `gN`, `gk`, `CHI`, `field`. Never use its component directly, use individual accessors as above.

`long mf_get_type`(GEN `F`) returns a symbolic name for the constructor used to create the form, e.g. `t_MF_EISEN` for a general Eisenstein series. A form has a recursive structure represented by a tree: its definition may involve other forms, e.g. the tree attached to $T_n f$ contains f as a subtree. Such trees have *leaves*, forms which do not contain a strict subtree, e.g. `t_MF_DELTA` is a leaf, attached to Ramanujan’s Δ .

Here is the current list of types; since the names are liable to change, they are not documented at this point. Use `mfdescribe` to visualize their mathematical structure.

```
/*leaves*/
  t_MF_CONST, t_MF_EISEN, t_MF_Ek, t_MF_DELTA, t_MF_ETAQUO, t_MF_ELL,
  t_MF_DIHEDRAL, t_MF_THETA, t_MF_TRACE, t_MF_NEWTRACE,
/*recursive*/
  t_MF_MUL, t_MF_POW, t_MF_DIV, t_MF_BRACKET, t_MF_LINEAR, t_MF_LINEAR_BHN,
  t_MF_SHIFT, t_MF_DERIV, t_MF_DERIVE2, t_MF_TWIST, t_MF_HECKE,
  t_MF_BD,
```

17.1.3 Nebentypus. The characters stored in modular forms and modular form spaces have a special structure. One can recover the parameters of an ordinary Dirichlet character by `G = gel(CHI,1)` (the underlying `znstar`) and `chi = gel(CHI,2)` (the underlying character in `znconreylog` form).

`long mfcharmodulus(GEN CHI)` the modulus of χ .

`long mfcharorder(GEN CHI)` the order of χ .

`GEN mfcharpol(GEN CHI)` the cyclotomic polynomial Φ_n defining $\mathbf{Q}(\chi)$, always normalized so that n is not 2 mod 4.

17.1.4 Miscellaneous functions.

`long mfnewdim(long N, long k, GEN CHI)` dimension of the new part of the cuspidal space.

`long mfcuspdim(long N, long k, GEN CHI)` dimension of the cuspidal space.

`long mfoldddim(long N, long k, GEN CHI)` dimension of the old part of the cuspidal space.

`long mfeisensteindim(long N, long k, GEN CHI)` dimension of the Eisenstein subspace.

`long mffulldim(long N, long k, GEN CHI)` dimension of the full space.

`GEN mfeisensteinspaceinit(GEN NK)`

`GEN mfddiv_val(GEN F, GEN G, long vG)`

`GEN mfembed(GEN E, GEN v)`

`GEN mfmatembed(GEN E, GEN v)`

`GEN mfvecembed(GEN E, GEN v)`

`long mfsturmNgk(long N, GEN k)`

`long mfsturmNk(long N, long k)`

`long mfsturm_mf(GEN mf)`

`long mfishcuspidal(GEN mf, GEN F)`

`GEN mftobasisES(GEN mf, GEN F)`

`GEN mftocol(GEN F, long lim, long d)`

`GEN mfvectomat(GEN vF, long lim, long d)`

Chapter 18:

Plots

A `PARI_plot` canvas is a record of dimensions, with the following fields:

```
long width; /* window width */
long height; /* window height */
long hunit; /* length of horizontal 'ticks' */
long vunit; /* length of vertical 'ticks' */
long fwidth; /* font width */
long fheight; /* font height */
void (*draw)(PARI_plot *T, GEN w, GEN x, GEN y);
```

The `draw` method performs the actual drawing of a `t_VECSMALL` `w` (rectwindow indices); x and y are `t_VECSMALL`s of the same length and rectwindow $w[i]$ is drawn with its upper left corner at offset $(x[i], y[i])$. No plot engine is available in `libpari` by default, since this would introduce a dependency on extra graphical libraries. See the files `src/graph/plot*` for basic implementations of various plot engines: `plotsvg` is particularly simple (`draw` is a 1-liner).

`void pari_set_plot_engine(void (*T)(PARI_plot *))` installs the graphical engine T and initializes the graphical subsystem. No routine in this chapter will work without this initialization.

`void pari_kill_plot_engine(void)` closes the graphical subsystem and frees the resources it occupies.

18.1 Highlevel functions.

Those functions plot $f(E, x)$ for $x \in [a, b]$, using n regularly spaced points (by default).

`GEN ploth(void *E, GEN(*f)(void*, GEN), GEN a, GEN b, long flags, long n, long prec)`
draw physically.

`GEN plotrecth(void *E, GEN(*f)(void*, GEN), long w, GEN a, GEN b, ulong flags, long n, long prec)` draw in rectwindow w .

18.2 Function.

```
void plotbox(long ne, GEN gx2, GEN gy2)
void plotclip(long rect)
void plotcolor(long ne, long color)
void plotcopy(long source, long dest, GEN xoff, GEN yoff, long flag)
GEN plotcursor(long ne)
void plotdraw(GEN list, long flag)
GEN plothrow(GEN listx, GEN listy, long flag)
GEN plotsizes(long flag)
void plotinit(long ne, GEN x, GEN y, long flag)
void plotkill(long ne)
void plotline(long ne, GEN x2, GEN y2)
void plotlines(long ne, GEN listx, GEN listy, long flag)
void plotlinetype(long ne, long t)
void plotmove(long ne, GEN x, GEN y)
void plotpoints(long ne, GEN listx, GEN listy)
void plotpointsize(long ne, GEN size)
void plotpointtype(long ne, long t)
void plotrbox(long ne, GEN x2, GEN y2)
GEN plotrecthrow(long ne, GEN data, long flags)
void plotrline(long ne, GEN x2, GEN y2)
void plotrmove(long ne, GEN x, GEN y)
void plotrpoint(long ne, GEN x, GEN y)
void plotscale(long ne, GEN x1, GEN x2, GEN y1, GEN y2)
void plotstring(long ne, char*x, long dir)
```

18.2.1 Obsolete functions. These draw directly to a PostScript file specified by a global variable and should no longer be used. Use `plotexport` and friends instead.

```
void psdraw(GEN list, long flag)
GEN psplothrow(GEN listx, GEN listy, long flag)
GEN psplotth(void *E, GEN(*f)(void*, GEN), GEN a, GEN b, long flags, long n, long
prec) draw to a PostScript file.
```


18.3 Dump rectwindows to a PostScript or SVG file.

w, x, y are three `t_VECSMALL`s indicating the rectwindows to dump, at which offsets. If T is `NULL`, rescale with respect to the installed graphic engine dimensions; else with respect to T .

```
char* rect2ps(GEN w, GEN x, GEN y, PARI_plot *T)
```

`char* rect2ps_i(GEN w, GEN x, GEN y, PARI_plot *T, int plotps)` if `plotps` is 0, as above; else private version used to implement the `plotps` graphic engine (do not rescale, rotate to portrait orientation).

```
char* rect2svg(GEN w, GEN x, GEN y, PARI_plot *T)
```

18.4 Technical functions exported for convenience.

`void pari_plot_by_file(const char *env, const char *suf, const char *img)` backend used by the `plotps` and `plotsvg` graphic engines.

`void colorname_to_rgb(const char *s, int *r, int *g, int *b)` convert an X11 colorname to RGB values.

`void color_to_rgb(GEN c, int *r, int *g, int *b)` convert a pari color (`t_VECSMALL` RGB triple or `t_STR` name) to RGB values.

`void long_to_rgb(long c, int *r, int *g, int *b)` split a standard hexadecimal color value `0xfdf5e6` to its rgb components (`0xfd`, `0xf5`, `0xe6`).

Appendix A:

A Sample program and Makefile

We assume that you have installed the PARI library and include files as explained in Appendix A or in the installation guide. If you chose differently any of the directory names, change them accordingly in the Makefiles.

If the program example that we have given is in the file `extgcd.c`, then a sample Makefile might look as follows. Note that the actual file `examples/Makefile` is more elaborate and you should have a look at it if you intend to use `install()` on custom made functions.

```
CC = cc
INCDIR = /usr/include/x86_64-linux-gnu
LIBDIR = /usr/lib/x86_64-linux-gnu
CFLAGS = -O -I$(INCDIR) -L$(LIBDIR)

all: extgcd

extgcd: extgcd.c
    $(CC) $(CFLAGS) -o extgcd extgcd.c -lpari -lm
```

We then give the listing of the program `examples/extgcd.c` seen in detail in Section 4.10.

```
#include <pari/pari.h>
/*
GP;install("extgcd", "GG&&", "gcdex", "./libextgcd.so");
*/

/* return d = gcd(a,b), sets u, v such that au + bv = gcd(a,b) */
GEN
extgcd(GEN A, GEN B, GEN *U, GEN *V)
{
    pari_sp av = avma;
    GEN ux = gen_1, vx = gen_0, a = A, b = B;
    if (typ(a) != t_INT) pari_err_TYPE("extgcd",a);
    if (typ(b) != t_INT) pari_err_TYPE("extgcd",b);
    if (signe(a) < 0) { a = negi(a); ux = negi(ux); }
    while (!gequal0(b))
    {
        GEN r, q = dvmdii(a, b, &r), v = vx;
        vx = subii(ux, mulii(q, vx));
        ux = v; a = b; b = r;
    }
    *U = ux;
    *V = diviixact( subii(a, mulii(A,ux)), B );
    gerepileall(av, 3, &a, U, V); return a;
}

int
```

```

main()
{
    GEN x, y, d, u, v;
    pari_init(1000000,2);
    printf("x = "); x = gp_read_stream(stdin);
    printf("y = "); y = gp_read_stream(stdin);
    d = extgcd(x, y, &u, &v);
    pari_printf("gcd = %Ps\nu = %Ps\nv = %Ps\n", d, u, v);
    pari_close();
    return 0;
}

```

Appendix B:

PARI and threads

To use PARI in multi-threaded programs, you must configure it using `Configure --enable-tls`. Your system must implement the `_thread` storage class. As a major side effect, this breaks the `libpari` ABI: the resulting library is not compatible with the old one, and `-tls` is appended to the PARI library `soname`. On the other hand, this library is now thread-safe.

PARI provides some functions to set up PARI subthreads. In our model, each concurrent thread needs its own PARI stack. The following scheme is used:

Child thread:

```
void *child_thread(void *arg)
{
    GEN data = pari_thread_start((struct pari_thread*)arg);
    GEN result = ...; /* Compute result from data */
    pari_thread_close();
    return (void*)result;
}
```

Parent thread:

```
pthread_t th;
struct pari_thread pth;
GEN data, result;

pari_thread_alloc(&pth, s, data);
pthread_create(&th, NULL, &child_thread, (void*)&pth); /* start child */
... /* do stuff in parent */
pthread_join(th, (void*)&result); /* wait until child terminates */
result = gcopy(result); /* copy result from thread stack to main stack */
pari_thread_free(&pth); /* ... and clean up */
```

`void pari_thread_valloc(struct pari_thread *pth, size_t s, size_t v, GEN arg)` Allocate a PARI stack of size `s` which can grow to at most `v` (as with `parisize` and `parisizemax`) and associate it, together with the argument `arg`, with the PARI thread data `pth`.

`void pari_thread_alloc(struct pari_thread *pth, size_t s, GEN arg)` As above but the stack cannot grow beyond `s`.

`void pari_thread_free(struct pari_thread *pth)` Free the PARI stack attached to the PARI thread data `pth`. This is called after the child thread terminates, i.e. after `pthread_join` in the parent. Any GEN objects returned by the child in the thread stack need to be saved before running this command.

`void pari_thread_init(void)` Initialize the thread-local PARI data structures. This function is called by `pari_thread_start`.

`GEN pari_thread_start(struct pari_thread *t)` Initialize the thread-local PARI data structures and set up the thread stack using the PARI thread data `pth`. This function returns the thread argument `arg` that was given to `pari_thread_alloc`.

`void pari_thread_close(void)` Free the thread-local PARI data structures, but keeping the thread stack, so that a `GEN` returned by the thread remains valid.

Under this model, some PARI states are reset in new threads. In particular

- the random number generator is reset to the starting seed;
- the system stack exhaustion checking code, meant to catch infinite recursions, is disabled (use `pari_stackcheck_init()` to reenale it);
- cached real constants (returned by `mppi`, `mpeuler` and `mplog2`) are not shared between threads and will be recomputed as needed;

The following sample program can be compiled using

```
cc thread.c -o thread.o -lpari -lpthread
```

(Add `-I/-L` paths as necessary.)

```
#include <pari/pari.h> /* Include PARI headers */
#include <pthread.h>    /* Include POSIX threads headers */

void *
mydet(void *arg)
{
    GEN F, M;
    /* Set up thread stack and get thread parameter */
    M = pari_thread_start((struct pari_thread*) arg);
    F = QM_det(M);
    /* Free memory used by the thread */
    pari_thread_close();
    return (void*)F;
}

void *
myfactor(void *arg) /* same principle */
{
    GEN F, N;
    N = pari_thread_start((struct pari_thread*) arg);
    F = factor(N);
    pari_thread_close();
    return (void*)F;
}

int
main(void)
{
    long prec = DEFAULTPREC;
    GEN M1,M2, N1,N2, F1,F2, D1,D2;
    pthread_t th1, th2, th3, th4; /* POSIX-thread variables */
    struct pari_thread pth1, pth2, pth3, pth4; /* pari thread variables */
```

```

/* Initialise the main PARI stack and global objects (gen_0, etc.) */
pari_init(32000000,500000);
/* Compute in the main PARI stack */
N1 = addis(int2n(256), 1); /*  $2^{256} + 1$  */
N2 = subis(int2n(193), 1); /*  $2^{193} - 1$  */
M1 = mathilbert(149);
M2 = mathilbert(150);
/* Allocate pari thread structures */
pari_thread_alloc(&pth1,8000000,N1);
pari_thread_alloc(&pth2,8000000,N2);
pari_thread_alloc(&pth3,32000000,M1);
pari_thread_alloc(&pth4,32000000,M2);
/* pthread_create() and pthread_join() are standard POSIX-thread
   * functions to start and get the result of threads. */
pthread_create(&th1,NULL, &myfactor, (void*)&pth1);
pthread_create(&th2,NULL, &myfactor, (void*)&pth2);
pthread_create(&th3,NULL, &mydet, (void*)&pth3);
pthread_create(&th4,NULL, &mydet, (void*)&pth4); /* Start 4 threads */
pthread_join(th1,(void*)&F1);
pthread_join(th2,(void*)&F2);
pthread_join(th3,(void*)&D1);
pthread_join(th4,(void*)&D2); /* Wait for termination, get the results */
pari_printf("F1=%Ps\nF2=%Ps\nlog(D1)=%Ps\nlog(D2)=%Ps\n",
            F1,F2, glog(D1,prec),glog(D2,prec));
pari_thread_free(&pth1);
pari_thread_free(&pth2);
pari_thread_free(&pth3);
pari_thread_free(&pth4); /* clean up */
return 0;
}

```

Index

SomeWord refers to PARI-GP concepts.
SomeWord is a PARI-GP keyword.
SomeWord is a generic index entry.

.	
_evalexpo	61
_evallg	61
_evalprec	61
_evalvalp	61
_evalvalser	61

A

ABC_to_bnr	320
abelian_group	259
abgrp_get_cyc	292
abgrp_get_gen	292
abgrp_get_no	292
abmap_kernel	320
abmap_subgroup_image	320
abscmpii	93
abscmpiu	93
abscmprr	94
abscmpui	93
absdiviu_rem	98
absequalii	94
absequaliu	93
absequalui	93
absfrac	245
absfrac_shallow	245
absi	92
absi_shallow	92
absr	92
absrnz_equal1	94
absrnz_equal2n	94
abstorel	321
absZ_factor	174
absZ_factor_limit	174
absZ_factor_limit_strict	174
addhelp	77
addii	15
addii_sign	96
addir	15
addir_sign	97
addis	15
addiu	95
addll	81
addllx	81
addmul	81

addmulii	96
addmulii_inplace	96
addmuliu	96
addmuliu_inplace	96
addri	15
addr	15
addr_sign	97
addsi_sign	97
addui	95
addui_sign	97
addumului	96
adduu	95
affc_fixlg	255
affects_sign	62
affects_sign_safe	62
affgr	87
affii	87
affir	87
affiz	87
affrr	87
affrr_fixlg	87, 255
affsi	87
affsr	87
affsz	87
affui	87
affur	87
alarm	271
alg_complete	338
alg_csa_table	338
alg_cyclic	338
alg_get_absdim	339
alg_get_abssplitting	340
alg_get_aut	339
alg_get_auts	339
alg_get_b	339
alg_get_basis	339
alg_get_center	339
alg_get_char	339
alg_get_degree	339
alg_get_dim	339
alg_get_hasse_f	339
alg_get_hasse_i	339
alg_get_invbasis	339
alg_get_multable	339
alg_get_relmultable	339
alg_get_splitpol	340
alg_get_splittingbasis	340
alg_get_splittingbasisinv	340
alg_get_splittingdata	340

check_quaddisc	324	clean_Z_factor	177
check_quaddisc_imag	324	cleanroots	200, 247
check_quaddisc_real	324	clone	71
check_ZKmodule	292	clone	14, 27
check_ZKmodule_i	292	CLONEBIT	64
checkabgrp	292	closemodinvertible	336
checkalg	338	closure	75
checkbid	291	closure	33
checkbid_i	291	closure_arity	34
checkbnf	291	closure_callgen0	283
checkbnf_i	291	closure_callgen0prec	283
checkbnr	291	closure_callgen1	75, 283
checkbnr_i	291	closure_callgen1prec	283
checkell	341	closure_callgen2	283
checkell5	341	closure_callgenall	283
checkell_Fq	342	closure_callgenvec	283
checkell_i	341	closure_callgenvecdef	283
checkell_Q	342	closure_callgenvecdefprec	283
checkell_Qp	342	closure_callgenvecprec	283
checkellisog	342	closure_callvoid1	283
checkellpt	341	closure_context	285
checkellpt_i	341	closure_deriv	284
checkfarey_i	363	closure_derivn	284
checkgal	291	closure_disassemble	283
checkgroup	259	closure_err	285
checkgroupelts	259	closure_evalbrk	284
checkhasse	339	closure_evalgen	75, 283
checklat	338	closure_evalnobrk	283
checkMF	363	closure_evalres	284
checkMF_i	363	closure_evalvoid	75, 284
checkmf_i	363	closure_func_err	55
checkmodpr	292	closure_is_variadic	34
checkms	361	closure_trapgen	284
checkmspadic	361	cmp_Flx	235
checknf	291	cmp_nodata	234
checknf_i	291	cmp_padic	235
checknfelt_mod	292	cmp_prime_ideal	235
checkprid	292	cmp_prime_over_p	235
checkprid_i	292	cmp_RgX	235
checkrnf	291	cmp_universal	192, 230, 234
checkrnf_i	291	cmpii	92
checksqmat	291	cmpir	93
checkznstar_i	291	cmpis	93
chinese1	161	cmpiu	93
chinese1_coprime_Z	161	cmpri	93
chk_gerepileupto	70	cmprr	93
classno	325	cmprrs	93
classno2	325	cmpsi	93
clcm	101	cmpsr	93

deg2pol_shallow	229	e_ALARM	57
degpol	32, 60, 247	e_DOMAIN	177
degree	32, 246	e_MISC	39
delete_var	36, 73	e_TYPE	177
denom_i	237	ec_2divpol_evalx	346
deplin	335	ec_3divpol_evalx	346
derivser	248	ec_bmodel	346
destruction	17	ec_dFdx_evalQ	346
detint	184	ec_dFdy_evalQ	346
diagonal_shallow	229	ec_dmFdy_evalQ	346
dicyclicgroup	259	ec_f_evalx	346
disc_best_modinv	355	ec_h_evalx	346
discrayabslist	323	ec_half_deriv_2divpol	346
discrayabslistarch	323	ec_half_deriv_2divpol_evalx	346
div_content	238	ec_phi2	346
diviexact	97	echo	57
diviiround	89	ecpp	180
divis_rem	98	ecpp0	180
divisors	42	ecppexport	180
divisorsu	106	ecppisvalid	180
divisorsu_fact	106	effective length	29
divisorsu_fact_factored	106	ei_multable	301
divisorsu_moebius	106	ellff_get_o	345
diviuexact	97	ell	341
diviuuexact	97	ell_get_a1	342
divll	81	ell_get_a2	342
divll_pre	83	ell_get_a3	342
divrunextu	235	ell_get_a4	342
divsBIL	64	ell_get_a6	342
divsi_rem	98	ell_get_b2	342
divss_rem	98	ell_get_b4	342
dvdii	97	ell_get_b6	342
dvdiiiz	97	ell_get_b8	342
dvdis	97	ell_get_c4	342
dvdisz	97	ell_get_c6	342
dvdiu	97	ell_get_disc	342
dvdiuz	97	ell_get_j	342
dvdsi	97	ell_get_type	341, 347
dvdui	97	ell_is_inf	346
dvmdii	97	ell_is_integral	342
dvmdiiiz	98	ellanal_globalred	343
dvmdis	98	ellanal_globalred_all	343
dvmdsBIL	64	ellap	346
dvmdsi	98	ellap_CM_fast	342
dvmdss	98	ellbasechar	346
dvmduBIL	64	ellchangeinvert	346
dynamic array	275	elldatagridgenerators	343
		elleulerf	344
		ellff_get_a4a6	345

E

ellff_get_card	345	elltrace_extension	347
ellff_get_D	345	eltabstorel	321
ellff_get_field	345	eltabstorel_lift	321
ellff_get_gens	345	eltreltoabs	321
ellff_get_group	345	embed_disc	316
ellff_get_m	345	embed_norm	316
ellff_get_o	345	embed_roots	316
ellff_get_p	344	embed_T2	316
ellheightoo	343	embednorm_T2	316
ellinf	346	equali1	231
ellinit	341	equalii	93
ellintegralmodel	343	equalim1	232
ellintegralmodel_i	343	equalis	93
ellisogeny	342	equaliu	93
ellnf_get_bnf	344	equalrr	93
ellnf_get_nf	344	equalsi	93
ellnf_vecarea	344	equalui	93
ellnf_veceta	344	err_flush	74
ellnf_vecomega	344	err_get_compo	47
ellorder	343	err_get_num	47
ellorder_Q	343	err_printf	74
ellQ_get_CM	342, 349	error context	33
ellQ_get_N	342	error	39
ellQ_get_Nfa	342	error	271
ellQp_ab	344	eta_product_ZXn	199
ellQp_AGM	344	eta_ZXn	199
ellQp_Ei	256	etaquotype	358
ellQp_get_p	344	eulerf_gchar	338
ellQp_get_prec	344	eulerphiu	106
ellQp_get_zero	344	eulerphiu_fact	106
ellQp_L	344	evalexp	61
ellQp_q	344	evallg	61
ellQp_root	344	evallgfint	61
ellQp_Tate_uniformization	344	evalprecp	61
ellQp_u	344	evalsigne	61
ellQp_u2	344	evaltyp	61
ellQtwist_bsdperiod	343	evalvalp	61
ellR_ab	345	evalvalser	61
ellR_area	345	evalvarn	61
ellR_eta	345	exp1r_abs	254
ellR_get_prec	345	expi	60
ellR_get_sign	346	expIPiC	255
ellR_omega	345	expIPiR	255
ellR_roots	345	exp1r	255
ellrootno_global	343	exp1xy	255
ellsupersingularj_FpXQ	353	expo	30, 33, 60
elltors	344	EXPOBITS	64
elltors0	344	EXPOnumBITS	64
elltors_psylog	344	expu	95

extract0 278

F

F2c_to_mod 159
F2c_to_ZC 120
F2m_clear 119
F2m_coeff 119
F2m_copy 119
F2m_deplin 120
F2m_det 120
F2m_det_sp 120
F2m_F2c_gauss 119
F2m_F2c_invimage 119
F2m_F2c_mul 119
F2m_flip 119
F2m_gauss 119
F2m_image 119
F2m_indexrank 119
F2m_inv 120
F2m_invimage 119
F2m_ker 120
F2m_ker_sp 120
F2m_mul 119
F2m_powu 119
F2m_rank 119
F2m_row 119
F2m_rowslice 119
F2m_set 119
F2m_suppl 119
F2m_to_F2Ms 193
F2m_to_Flm 120
F2m_to_mod 159
F2m_to_ZM 120
F2m_transpose 119
F2Ms_colelim 194
F2Ms_ker 194
F2Ms_to_F2m 193
F2v_add_inplace 120
F2v_and_inplace 120
F2v_clear 118
F2v_coeff 118
F2v_copy 118
F2v_dotproduct 120
F2v_ei 119
F2v_equal0 118
F2v_flip 118
F2v_hamming 120
F2v_negimply_inplace 120

F2v_or_inplace 120
F2v_set 118
F2v_slice 118
F2v_subset 120
F2v_to_F2x 153
F2v_to_Flv 120
F2x_1_add 154
F2x_add 154
F2x_clear 153
F2x_coeff 153
F2x_copy 153
F2x_ddf 155
F2x_deflate 154
F2x_degfact 154
F2x_degree 154
F2x_deriv 154
F2x_div 154
F2x_divrem 154
F2x_equal 154
F2x_equal1 154
F2x_eval 154
F2x_even_odd 154
F2x_extgcd 154
F2x_F2xq_eval 155
F2x_F2xqV_eval 155
F2x_factor 154
F2x_factor_squarefree 154
F2x_flip 153
F2x_Frobenius 154
F2x_gcd 154
F2x_get_red 153
F2x_halfgcd 154
F2x_is_irred 154
F2x_issquare 154
F2x_matFrobenius 154
F2x_mul 154
F2x_recip 154
F2x_rem 154
F2x_renormalize 154
F2x_set 153
F2x_shift 154
F2x_sqr 154
F2x_sqrt 154
F2x_Teichmuller 155
F2x_to_F2v 173
F2x_to_F2xX 153
F2x_to_Flx 153
F2x_to_ZX 153
F2x_valrem 154

F2xC_to_FlxC	173	F2xqM_invimage	156
F2xC_to_ZXC	173	F2xqM_ker	156
F2xn_div	156	F2xqM_mul	156
F2xn_inv	156	F2xqM_rank	156
F2xn_red	155	F2xqM_suppl	156
F2xq_Artin_Schreier	155	F2xqV_roots_to_pol	155
F2xq_autpow	155	F2xqX_ddf	158
F2xq_conjvec	155	F2xqX_degfact	158
F2xq_div	155	F2xqX_disc	158
F2xq_ellcard	351	F2xqX_div	157
F2xq_ellgens	351	F2xqX_divrem	157
F2xq_ellgroup	351	F2xqX_extgcd	157
F2xq_elltwist	351	F2xqX_F2xq_mul	157
F2xq_inv	155	F2xqX_F2xq_mul_to_mon	157
F2xq_invsafe	155	F2xqX_F2xqXQ_eval	158
F2xq_log	155	F2xqX_F2xqXQV_eval	158
F2xq_matrix_pow	155	F2xqX_factor	158
F2xq_mul	155	F2xqX_factor_squarefree	158
F2xq_order	155	F2xqX_gcd	158
F2xq_pow	155	F2xqX_get_red	157
F2xq_pow_init	155	F2xqX_halfgcd	158
F2xq_pow_table	155	F2xqX_halfgcd_all	158
F2xq_powers	155	F2xqX_invBarrett	157
F2xq_powu	155	F2xqX_ispower	158
F2xq_sqr	155	F2xqX_mul	157
F2xq_sqrt	155	F2xqX_normalize	157
F2xq_sqrt_fast	155	F2xqX_powu	157
F2xq_sqrtn	155	F2xqX_red	157
F2xq_trace	155	F2xqX_rem	157
F2xqE_add	351	F2xqX_resultant	158
F2xqE_changepoint	351	F2xqX_roots	158
F2xqE_changepointinv	351	F2xqX_sqr	157
F2xqE_dbl	351	F2xqXQ_autpow	158
F2xqE_log	351	F2xqXQ_auttrace	158
F2xqE_mul	351	F2xqXQ_inv	157
F2xqE_neg	351	F2xqXQ_invsafe	157
F2xqE_order	351	F2xqXQ_mul	158
F2xqE_sub	351	F2xqXQ_pow	158
F2xqE_tatepairing	351	F2xqXQ_powers	158
F2xqE_weilpairing	351	F2xqXQ_sqr	158
F2xqM_deplin	156	F2xqXQV_red	158
F2xqM_det	156	F2xqXV_prod	158
F2xqM_F2xqC_gauss	156	F2xV_to_F2m	173
F2xqM_F2xqC_invimage	156	F2xV_to_FlxV_inplace	171
F2xqM_F2xqC_mul	156	F2xV_to_ZXV_inplace	171
F2xqM_gauss	156	F2xX_add	156
F2xqM_image	156	F2xX_deriv	156
F2xqM_indexrank	156	F2xX_F2x_add	156
F2xqM_inv	156	F2xX_F2x_mul	156

F2xX_renormalize	156	famat_div_shallow	303
F2xX_shift	156	famat_idealfactor	304
F2xX_to_F2xC	156	famat_inv	303
F2xX_to_FlxX	156	famat_inv_shallow	303
F2xX_to_Kronecker	157	famat_makecoprime	318
F2xX_to_ZXX	156	famat_mul	303
F2xXC_to_ZXXC	157	famat_mul_shallow	303
F2xXV_to_F2xM	156	famat_mulpow	303
F2xY_degrees	156	famat_mulpow_shallow	303
F2xY_F2xq_evalx	157	famat_mulpows_shallow	303
F2xY_F2xqV_evalx	157	famat_nfvalrem	304
F3c_to_mod	159	famat_pow	303
F3c_to_ZC	121	famat_pow_shallow	303
F3m_coeff	121	famat_pows_shallow	303
F3m_copy	121	famat_reduce	302, 304
F3m_ker	121	famat_remove_trivial	304
F3m_ker_sp	121	famat_sqr	303
F3m_mul	121	famat_to_nf	304
F3m_row	121	famat_to_nf_moddivisor	317
F3m_set	121	famat_to_nf_modideal_coprime	318
F3m_to_Flm	121	famat_Z_gcd	303
F3m_to_mod	159	famat_small_reduce	304
F3m_to_ZM	121	famatV_factorback	304
F3m_transpose	121	famatV_zv_factorback	304
F3v_clear	121	fetch_user_var	35, 73
F3v_coeff	121	fetch_var	36, 73
F3v_set	121	fetch_var_higher	36
F3v_to_Flv	121	fetch_var_value	36, 73
f_PRETTYMAT	263	FF_1	249
f_RAW	263, 264	FF_add	249
f_TEX	263, 264	FF_charpoly	250
factmod	160	FF_conjvec	250
factor	341	FF_div	250
factor_Aurifeuille	175	FF_ellcard	347
factor_Aurifeuille_prime	175	FF_ellcard_SEA	347
factor_pn_1	175	FF_ellgens	347
factor_pn_1_limit	175	FF_ellgroup	347
factor_proven	178	FF_elllog	347
factorback	241	FF_ellmul	347
factoredpolred	323	FF_ellorder	347
factoredpolred2	323	FF_ellrandom	347
factorial_Fl	83	FF_elltatepairing	347
factorial_Fp	104	FF_elltwist	347
factorial_lval	91	FF_ellweilpairing	347
factorint	177	FF_equal	249
factoru	175	FF_equal0	249
factoru_pow	175	FF_equal1	249
famat	302	FF_equalm1	249
famat_div	303	FF_f	248

FF_Frobenius	250	FFM_invimage	252
FF_gen	248	FFM_ker	252
FF_inv	250	FFM_mul	252
FF_ispower	250	FFM_rank	253
FF_issquare	250	FFM_suppl	253
FF_issquareall	250	FFV_roots_to_pol	252
FF_log	250	FFX_add	251
FF_map	251	FFX_ddf	251
FF_minpoly	250	FFX_degfact	252
FF_mod	248	FFX_disc	251
FF_mul	249	FFX_extgcd	251
FF_mul2n	250	FFX_factor	251
FF_neg	250	FFX_factor_squarefree	251
FF_neg_i	250	FFX_gcd	251
FF_norm	250	FFX_halfgcd	251
FF_order	250	FFX_halfgcd_all	251
FF_p	248	FFX_ispower	251
FF_p_i	248	FFX_mul	251
ff_parse_Tp	128	FFX_preimage	252
FF_pow	250	FFX_preimagerel	252
FF_primroot	250	FFX_rem	251
FF_q	248	FFX_resultant	251
FF_Q_add	249	FFX_roots	252
FF_samefield	249	FFX_sqr	251
FF_sqr	250	FFXQ_inv	253
FF_sqrt	250	FFXQ_minpoly	253
FF_sqrtn	250	FFXQ_mul	253
FF_sub	249	FFXQ_sqr	253
FF_to_F2xq	248	file_is_binary	266
FF_to_F2xq_i	248	finite field element	31
FF_to_Flxq	248	fixlg	70, 87
FF_to_Flxq_i	248	Fl_2gener_pre	84
FF_to_FpXQ	248	Fl_2gener_pre_i	84
FF_to_FpXQ_i	248	Fl_add	82
FF_trace	250	Fl_addmul_pre	84
FF_var	248	Fl_addmulmul_pre	84
FF_Z_add	249	Fl_center	82
FF_Z_mul	249	Fl_div	83
FF_Z_Z_muldiv	250	Fl_double	82
FF_zero	249	Fl_elldisc	349
FFM_deplin	252	Fl_elldisc_pre	349
FFM_det	252	Fl_ellj	349
FFM_FFC_gauss	252	Fl_ellj_pre	349
FFM_FFC_invimage	252	Fl_ellj_to_a4a6	349
FFM_FFC_mul	252	Fl_ellptors	349
FFM_gauss	252	Fl_elltrace	349
FFM_image	252	Fl_elltrace_CM	349
FFM_indexrank	252	Fl_elltwist	349
FFM_inv	252	Fl_elltwist_disc	349

Fl_half	82	Flj_to_Fle	350
Fl_inv	82	Flj_to_Fle_pre	350
Fl_invgen	82	FljV_factorback_pre	350
Fl_invsafe	82	Flm_add	117
Fl_log	83	Flm_adjoint	118
Fl_log_pre	84	Flm_center	116
Fl_mul	82	Flm_charpoly	117
Fl_mul_pre	84	Flm_copy	116
Fl_neg	82	Flm_deplin	118
Fl_order	83	Flm_det	118
Fl_powers	83	Flm_det_sp	118
Fl_powers_pre	84	Flm_Fl_add	116
Fl_powu	83	Flm_Fl_mul	116
Fl_powu_pre	84	Flm_Fl_mul_inplace	116
Fl_sqr	82	Flm_Fl_mul_pre	116
Fl_sqr_pre	84	Flm_Fl_sub	116
Fl_sqrt	83	Flm_Flc_gauss	118
Fl_sqrt_pre	84	Flm_Flc_invimage	118
Fl_sqrt_pre_i	84	Flm_Flc_mul	116
Fl_sqrtl	83	Flm_Flc_mul_pre	116
Fl_sqrtl_pre	84	Flm_Flc_mul_pre_Flx	116
Fl_sqrtn	83	Flm_gauss	118
Fl_sqrtn_pre	84	Flm_hess	118
Fl_sub	82	Flm_image	118
Fl_to_Flx	172	Flm_indexrank	118
Fl_triple	82	Flm_intersect	118
Flc_Flv_mul	116	Flm_intersect_i	118
Flc_FpV_mul	117	Flm_inv	118
Flc_lincomb1_inplace	116	Flm_invimage	118
Flc_to_mod	159	Flm_ker	118
Flc_to_ZC	171	Flm_ker_sp	118
Flc_to_ZC_inplace	171	Flm_mul	117
Fle_add	349	Flm_mul_pre	117
Fle_changepoint	350	Flm_neg	116
Fle_changepointinv	350	Flm_powers	117
Fle_dbl	349	Flm_powu	117
Fle_log	350	Flm_rank	118
Fle_mul	349	Flm_row	117
Fle_mulu	350	Flm_sqr	117
Fle_order	350	Flm_sub	117
Fle_sub	349	Flm_suppl	118
Fle_tatepairing	350	Flm_to_F2m	120
Fle_to_Flj	350	Flm_to_F3m	121
Fle_weilpairing	350	Flm_to_FlxV	172
Flj_add_pre	350	Flm_to_FlxX	172
Flj_changepointinv_pre	350	Flm_to_mod	159
Flj_dbl_pre	350	Flm_to_ZM	171
Flj_mulu_pre	350	Flm_to_ZM_inplace	171
Flj_neg	350	Flm_transpose	118

floor_safe	89	Flx_div_by_X_x	142
floorr	88	Flx_div_pre	140
flush	265	Flx_divrem	140
Flv_add	116	Flx_divrem_pre	140
Flv_add_inplace	116, 311	Flx_dotproduct	143
Flv_center	116	Flx_dotproduct_pre	143
Flv_copy	116	Flx_double	139
Flv_dotproduct	117	Flx_equal	139
Flv_dotproduct_pre	117	Flx_equal1	139
Flv_factorback	117	Flx_eval	142
Flv_Fl_div	116	Flx_eval_powers_pre	142
Flv_Fl_div_inplace	116	Flx_eval_pre	142
Flv_Fl_mul	116	Flx_extgcd	141
Flv_Fl_mul_inplace	116	Flx_extgcd_pre	141
Flv_Fl_mul_part_inplace	116	Flx_extresultant	142
Flv_Flm_polint	144	Flx_extresultant_pre	142
Flv_inv	117	Flx_factcyclo	141
Flv_inv_inplace	117	Flx_factor	141
Flv_inv_pre	117	Flx_factor_squarefree	141
Flv_inv_pre_inplace	117	Flx_factor_squarefree_pre	141
Flv_invVandermonde	144	Flx_factorff_irred	141
Flv_neg	116	Flx_ffintersect	143
Flv_neg_inplace	116	Flx_ffisom	141
Flv_polint	143	Flx_Fl_add	139
Flv_prod	117	Flx_Fl_mul	139
Flv_prod_pre	117	Flx_Fl_mul_pre	139
Flv_roots_to_pol	144	Flx_Fl_mul_to_monic	139
Flv_sub	117	Flx_Fl_sub	139
Flv_sub_inplace	117	Flx_Flv_multieval	142
Flv_sum	117	Flx_Flxq_eval	146
Flv_to_F2v	120	Flx_Flxq_eval_pre	146
Flv_to_F3v	121	Flx_FlxqV_eval	146
Flv_to_Flx	172	Flx_FlxqV_eval_pre	146
Flv_to_ZV	171	Flx_FlxY_resultant	148
Flx_add	139	Flx_Frobenius	140
Flx_blocks	143	Flx_Frobenius_pre	140
Flx_composedprod	142	Flx_fromNewton	143
Flx_composedsum	142	Flx_gcd	140
Flx_constant	139	Flx_gcd_pre	140
Flx_conv	140	Flx_get_red	138
Flx_copy	139	Flx_get_red_pre	138
Flx_ddf	141	Flx_halfgcd	140
Flx_ddf_pre	141	Flx_halfgcd_all	141
Flx_deflate	143	Flx_halfgcd_all_pre	141
Flx_degfact	141, 143	Flx_halfgcd_pre	140
Flx_deriv	140	Flx_halve	139
Flx_diff1	140	Flx_inflate	143
Flx_digits	140	Flx_integ	140
Flx_div	140	Flx_invBarrett	142

Flx_invLaplace	143	Flx_to_F2x	153
Flx_is_irred	143	Flx_to_Flv	172
Flx_is_smooth	143	Flx_to_FlxX	171
Flx_is_smooth_pre	143	Flx_to_ZX	171
Flx_is_squarefree	143	Flx_to_ZX_inplace	171
Flx_is_totally_split	143	Flx_translate1	140
Flx_ispower	141	Flx_translate1_basecase	140
Flx_Laplace	143	Flx_triple	139
Flx_lead	139	Flx_val	142
Flx_matFrobenius	140	Flx_valrem	142
Flx_matFrobenius_pre	140	FlxC_eval_powers_pre	144
Flx_mod_Xn1	141	FlxC_Flxq_eval	146
Flx_mod_Xnm1	141	FlxC_Flxq_eval_pre	146
Flx_mul	139	FlxC_FlxqV_eval	146
Flx_mul_pre	139	FlxC_FlxqV_eval_pre	146
Flx_mulu	139	FlxC_neg	144
Flx_nbfact	143	FlxC_sub	144
Flx_nbfact_by_degree	143	FlxC_to_F2xC	173
Flx_nbfact_Frobenius	143	FlxC_to_ZXC	171
Flx_nbfact_Frobenius_pre	143	FlxM_eval_powers_pre	144
Flx_nbfact_pre	143	FlxM_Flx_add_shallow	121
Flx_nbroots	143	FlxM_neg	144
Flx_neg	139	FlxM_sub	144
Flx_neg_inplace	139	FlxM_to_FlxXV	172
Flx_Newton	143	FlxM_to_ZXM	171
Flx_normalize	142	Flxn_div	145
Flx_oneroot	141	Flxn_div_pre	145
Flx_oneroot_pre	141	Flxn_exp	145
Flx_oneroot_split	141	Flxn_expint	145
Flx_oneroot_split_pre	141	Flxn_inv	145
Flx_powu	140	Flxn_mul	144
Flx_powu_pre	140	Flxn_mul_pre	144
Flx_recip	142	Flxn_red	145
Flx_red	139	Flxn_sqr	144
Flx_rem	140	Flxn_sqr_pre	144
Flx_rem_pre	140	Flxq_add	145
Flx_renormalize	142	Flxq_autpow	146
Flx_rescale	142	Flxq_autpow_pre	146
Flx_resultant	142	Flxq_autpowers	146
Flx_resultant_pre	142	Flxq_autsum	146
Flx_roots	141	Flxq_auttrace	146
Flx_roots_pre	141	Flxq_auttrace_pre	146
Flx_rootsff	141	Flxq_charpoly	147
Flx_shift	142	Flxq_conjvec	147
Flx_splitting	143	Flxq_div	145
Flx_sqr	140	Flxq_div_pre	145
Flx_sqr_pre	140	Flxq_ellcard	352
Flx_sub	139	Flxq_elldivpolmod	353
Flx_Teichmuller	143	Flxq_ellgens	352

Flxq_ellgroup	352	FlxqE_order	352
Flxq_ellj	352	FlxqE_sub	352
Flxq_ellj_to_a4a6	352	FlxqE_tatepairing	352
Flxq_elltwist	352	FlxqE_weilpairing	352
Flxq_ffisom_inv	146	FlxqE_weilpairing_pre	352
Flxq_inv	145	FlxqM_deplin	121
Flxq_inv_pre	145	FlxqM_det	122
Flxq_invsafe	145	FlxqM_Flxq_mul	121
Flxq_invsafe_pre	145	FlxqM_FlxqC_gauss	121
Flxq_is2npower	146	FlxqM_FlxqC_invimage	121
Flxq_issquare	146	FlxqM_FlxqC_mul	121
Flxq_log	146	FlxqM_gauss	122
Flxq_lroot	146	FlxqM_image	122
Flxq_lroot_fast	146	FlxqM_indexrank	122
Flxq_lroot_fast_pre	147	FlxqM_inv	122
Flxq_lroot_pre	146	FlxqM_invimage	122
Flxq_matrix_pow	146	FlxqM_ker	122
Flxq_matrix_pow_pre	146	FlxqM_mul	122
Flxq_minpoly	147	FlxqM_rank	122
Flxq_minpoly_pre	147	FlxqM_suppl	122
Flxq_mul	145	FlxqV_dotproduct	121
Flxq_mul_pre	145	FlxqV_dotproduct_pre	121
Flxq_norm	147	FlxqV_factorback	145
Flxq_order	146	FlxqV_roots_to_pol	146
Flxq_pow	145	FlxqX_composedsum	150
Flxq_pow_init	145	FlxqX_ddf	151
Flxq_pow_init_pre	145	FlxqX_ddf_degree	151
Flxq_pow_pre	145	FlxqX_degfact	151
Flxq_pow_table	145	FlxqX_disc	150
Flxq_pow_table_pre	145	FlxqX_div	150
Flxq_powers	145	FlxqX_div_by_X_x	150
Flxq_powers_pre	146	FlxqX_div_by_X_x_pre	150
Flxq_powu	145	FlxqX_div_pre	150
Flxq_powu_pre	145	FlxqX_divrem	149
Flxq_sqr	145	FlxqX_divrem_pre	150
Flxq_sqr_pre	145	FlxqX_dotproduct	150
Flxq_sqrt	146	FlxqX_eval	150
Flxq_sqrt_pre	146	FlxqX_extgcd	150
Flxq_sqrtn	146	FlxqX_extgcd_pre	150
Flxq_sub	145	FlxqX_factor	151
Flxq_trace	147	FlxqX_factor_squarefree	151
FlxqC_Flxq_mul	121	FlxqX_factor_squarefree_pre	151
FlxqE_add	352	FlxqX_Flxq_mul	149
FlxqE_changepoint	352	FlxqX_Flxq_mul_pre	149
FlxqE_changepointinv	352	FlxqX_Flxq_mul_to_mononic	149
FlxqE_dbl	352	FlxqX_Flxq_mul_to_mononic_pre	149
FlxqE_log	352	FlxqX_FlxqXQ_eval	151
FlxqE_mul	352	FlxqX_FlxqXQ_eval_pre	151
FlxqE_neg	352	FlxqX_FlxqXQV_eval	151

FlxqX_FlxqXQV_eval_pre	151	FlxqXn_mul_pre	152
FlxqX_Frobenius	151	FlxqXn_sqr	152
FlxqX_Frobenius_pre	151	FlxqXn_sqr_pre	153
FlxqX_fromNewton	151	FlxqXQ_autpow	152
FlxqX_fromNewton_pre	151	FlxqXQ_autpow_pre	152
FlxqX_gcd	150	FlxqXQ_autsum	152
FlxqX_gcd_pre	150	FlxqXQ_autsum_pre	152
FlxqX_get_red	148	FlxqXQ_auttrace	152
FlxqX_get_red_pre	148	FlxqXQ_auttrace_pre	152
FlxqX_halfgcd	150	FlxqXQ_div	152
FlxqX_halfgcd_all	150	FlxqXQ_div_pre	152
FlxqX_halfgcd_all_pre	150	FlxqXQ_halfFrobenius	152
FlxqX_halfgcd_pre	150	FlxqXQ_inv	152, 158
FlxqX_invBarrett	150	FlxqXQ_inv_pre	152
FlxqX_invBarrett_pre	150	FlxqXQ_invsafe	152, 158
FlxqX_is_squarefree	151	FlxqXQ_invsafe_pre	152
FlxqX_isplayer	151	FlxqXQ_matrix_pow	152
FlxqX_mul	149	FlxqXQ_minpoly	152
FlxqX_mul_pre	149	FlxqXQ_minpoly_pre	152
FlxqX_nbfact	151	FlxqXQ_mul	152
FlxqX_nbfact_by_degree	151	FlxqXQ_mul_pre	152
FlxqX_nbfact_Frobenius	151	FlxqXQ_pow	152
FlxqX_nbroots	151	FlxqXQ_pow_pre	152
FlxqX_Newton	151	FlxqXQ_powers	152
FlxqX_Newton_pre	151	FlxqXQ_powers_pre	152
FlxqX_normalize	149	FlxqXQ_powu	152
FlxqX_normalize_pre	149	FlxqXQ_powu_pre	152
FlxqX_powu	149	FlxqXQ_sqr	152
FlxqX_powu_pre	149	FlxqXQ_sqr_pre	152
FlxqX_red	149	FlxqXV_prod	150
FlxqX_red_pre	149	FlxT_red	144
FlxqX_rem	150	FlxV_composedsum	144
FlxqX_rem_pre	150	FlxV_Flc_mul	144
FlxqX_resultant	150	FlxV_Flv_multieval	144
FlxqX_resultant_pre	150	FlxV_Flx_fromdigits	140
FlxqX_roots	151	FlxV_prod	144
FlxqX_safegcd	150	FlxV_red	144
FlxqX_saferesultant	150	FlxV_to_Flm	172
FlxqX_sqr	149	FlxV_to_FlxX	173
FlxqX_sqr_pre	149	FlxV_to_ZXV	171
FlxqXC_FlxqXQ_eval	151	FlxV_to_ZXV_inplace	171
FlxqXC_FlxqXQ_eval_pre	151	FlxX_add	147
FlxqXC_FlxqXQV_eval	151	FlxX_blocks	148
FlxqXC_FlxqXQV_eval_pre	151	FlxX_deriv	147
FlxqXn_expint	153	FlxX_double	147
FlxqXn_expint_pre	153	FlxX_Fl_mul	147
FlxqXn_inv	153	FlxX_Flx_add	147
FlxqXn_inv_pre	153	FlxX_Flx_mul	147
FlxqXn_mul	152	FlxX_Flx_sub	147

FlxX_invLaplace	147	forperm_init	43
FlxX_Laplace	147	forperm_next	43
FlxX_neg	147	forprime	42
FlxX_renormalize	148	forprime_init	44, 180
FlxX_resultant	148	forprime_next	44, 180
FlxX_shift	148	forprime_t	43, 44
FlxX_sub	147	forprimestep	42
FlxX_swap	148	forprimestep_init	44, 180
FlxX_to_F2xX	156	forqfvec	42
FlxX_to_Flm	172	forqfvec1	42
FlxX_to_Flx	172	forsubgroup	42
FlxX_to_FlxC	172	forsubgroup(H = G, B,)	42
FlxX_to_ZXX	171	forsubset	43
FlxX_translate1	147	forsubset_init	43
FlxX_triple	147	forsubset_next	43
FlxXC_sub	148	forvec	42
FlxXC_to_F2xXC	157	forvec_init	42
FlxXC_to_ZXXC	171	forvec_next	42
FlxXM_to_ZXXM	171	Fp_2gener	104
FlxXn_red	152	Fp_2gener_i	104
FlxXV_to_FlxM	173	Fp_add	15, 102
FlxY_degreeex	147	Fp_addmul	102
FlxY_eval_powers_pre	148	Fp_center	102
FlxY_evalx	147	Fp_center_i	102
FlxY_evalx_powers_pre	148	Fp_div	103
FlxY_evalx_pre	147	Fp_divu	103
FlxY_Flx_div	147	Fp_double	102
FlxY_Flx_translate	148	Fp_ellcard	348
FlxY_Flxq_evalx	148	Fp_ellcard_SEA	348
FlxY_Flxq_evalx_pre	148	Fp_elldivpol	348
FlxY_FlxqV_evalx	148	Fp_ellgens	348
FlxY_FlxqV_evalx_pre	148	Fp_ellgroup	348
FlxYqq_pow	148	Fp_ellj	347
Fly_to_FlxY	173	Fp_ellj_to_a4a6	347
forallsubset_init	43	Fp_elljissupersingular	348
forcomposite	42	Fp_elltwist	348
forcomposite_init	42	Fp_factored_order	103
forcomposite_next	42	Fp_ffellcard	348
fordiv	42	Fp_FpX_sub	124
forell	42	Fp_FpXQ_log	129
forell(ell,a,b,,flag)	42	Fp_half	102
forksubset_init	43	Fp_inv	103
format	40	Fp_invgen	103
forpart	43	Fp_invsafe	103
forpart_init	43	Fp_isspower	103
forpart_next	43	Fp_issquare	103
forpart_prev	43	Fp_log	103, 130
forpart_t	43	Fp_modinv_to_j	355
forperm	43	Fp_mul	102

Fp_muls	102	FpM_charpoly	115
Fp_mulu	102	FpM_deplin	114
Fp_neg	102	FpM_det	114
Fp_order	103	FpM_Fp_mul	114
Fp_polmodular_evalx	354	FpM_FpC_gauss	114
Fp_pow	103	FpM_FpC_invimage	115
Fp_pow_init	103	FpM_FpC_mul	114
Fp_pow_table	103	FpM_FpC_mul_FpX	114
Fp_powers	103	FpM_gauss	114
Fp_pows	103	FpM_hess	115
Fp_powu	102	FpM_image	114
Fp_ratlift	164	FpM_indexrank	115
Fp_red	102	FpM_intersect	114
Fp_sqr	102	FpM_intersect_i	114
Fp_sqrt	103	FpM_inv	114
Fp_sqrt_i	104	FpM_invimage	115
Fp_sqrtn	104	FpM_ker	115
Fp_sub	102	FpM_mul	114
Fp_to_mod	158	FpM_powu	114
FpC_add	113	FpM_rank	115
FpC_center	113	FpM_ratlift	164
FpC_center_inplace	113	FpM_red	113
FpC_Fp_mul	114	FpM_sub	114
FpC_FpV_mul	114	FpM_suppl	115
FpC_ratlift	164	FpM_to_mod	159
FpC_red	113	FpMs_FpC_mul	193
FpC_sub	113	FpMs_FpCs_solve	194
FpC_to_mod	159	FpMs_FpCs_solve_safe	194
FpE_add	348	FpMs_leftkernel_elt	194
FpE_changepoint	348	FpV_add	113
FpE_changepointinv	348	FpV_dotproduct	114
FpE_dbl	348	FpV_dotsquare	114
FpE_log	349	FpV_factorback	114
FpE_mul	348	FpV_FpC_mul	114
FpE_neg	348	FpV_FpM_polint	125
FpE_order	349	FpV_FpMs_mul	194
FpE_sub	348	FpV_inv	103
FpE_tatepairing	349	FpV_invVandermonde	125
FpE_to_FpJ	350	FpV_polint	125
FpE_to_mod	349	FpV_prod	103
FpE_weilpairing	349	FpV_red	113
FpJ_add	350	FpV_roots_to_pol	125
FpJ_dbl	350	FpV_sub	114
FpJ_mul	350	FpV_to_mod	159
FpJ_neg	350	FpVV_to_mod	159
FpJ_to_FpE	350	FpX_add	123
FpM_add	113	FpX_center	124
FpM_center	113	FpX_center_i	124
FpM_center_inplace	113	FpX_chinese_coprime	125

FpX_composedprod	127	FpX_invLaplace	127
FpX_composedsum	127	FpX_is_irred	125, 154
FpX_conv	123	FpX_is_squarefree	125
FpX_ddf	126	FpX_is_totally_split	126
FpX_ddf_degree	126	FpX_ispower	126
FpX_degfact	126, 141, 154	FpX_Laplace	127
FpX_deriv	123	FpX_matFrobenius	124
FpX_digits	123	FpX_mul	123
FpX_disc	127	FpX_mulspec	123
FpX_div	123	FpX_mulu	124
FpX_div_by_X_x	123	FpX_nbfact	126
FpX_divrem	123	FpX_nbfact_Frobenius	126
FpX_divu	124	FpX_nbroots	126
FpX_dotproduct	124	FpX_neg	123
FpX_eval	124	FpX_Newton	127
FpX_extgcd	123	FpX_normalize	124
FpX_extresultant	127	FpX_oneroot	126
FpX_factcyclo	126	FpX_oneroot_split	126
FpX_factor	126	FpX_powu	123
FpX_factor_squarefree	126	FpX_ratlift	164
FpX_factorfff	137	FpX_red	122
FpX_factorfff_irred	137, 141	FpX_rem	123
FpX_ffintersect	138	FpX_renormalize	123
FpX_ffisom	138, 141	FpX_rescale	124
FpX_Fp_add	124	FpX_resultant	126
FpX_Fp_add_shallow	124	FpX_roots	126
FpX_Fp_div	124	FpX_roots_mult	126
FpX_Fp_mul	124	FpX_rootsfff	137, 141
FpX_Fp_mul_to_monic	124	FpX_split_part	126
FpX_Fp_mulspec	124	FpX_sqr	123
FpX_Fp_sub	124	FpX_sub	123
FpX_Fp_sub_shallow	124	FpX_to_mod	159
FpX_FpC_nfpoval	299	FpX_translate	123
FpX_FpV_multieval	124	FpX_valrem	123
FpX_FpXQ_eval	131	FpXC_center	131
FpX_FpXQV_eval	131	FpXC_FpXQ_eval	131
FpX_FpXV_multirem	125	FpXC_FpXQV_eval	131
FpX_FpXY_resultant	127	FpXC_to_mod	159
FpX_Frobenius	124	FpXM_center	131
FpX_fromNewton	127	FpXM_FpXQV_eval	131
FpX_gcd	123	FpXM_to_mod	159
FpX_gcd_check	314	FpXn_div	131
FpX_get_red	127	FpXn_exp	131
FpX_halfgcd	123	FpXn_expint	131
FpX_halfgcd_all	123	FpXn_inv	131
FpX_halfve	123	FpXn_mul	131
FpX_integ	123	FpXn_sqr	131
FpX_invBarret	127	FpXQ_add	128
FpX_invBarrett	124	FpXQ_autpow	130

FpXQ_autpowers	131	FpXQX_digits	134
FpXQ_autsum	130	FpXQX_disc	135
FpXQ_auttrace	131	FpXQX_div	134
FpXQ_charpoly	130	FpXQX_div_by_X_x	134
FpXQ_conjvec	130	FpXQX_divrem	134
FpXQ_div	128	FpXQX_dotproduct	134
FpXQ_ellcard	353	FpXQX_extgcd	134
FpXQ_ellcard_supersingular	353	FpXQX_factor	137
FpXQ_elldivpol	353	FpXQX_factor_squarefree	137
FpXQ_ellgens	353	FpXQX_FpXQ_mul	134
FpXQ_ellgroup	353	FpXQX_FpXQXQ_eval	135
FpXQ_ellj	353	FpXQX_FpXQXQV_eval	135
FpXQ_elljissupersingular	353	FpXQX_Frobenius	138
FpXQ_elltwist	353	FpXQX_gcd	134
FpXQ_ffisom_inv	138	FpXQX_get_red	135
FpXQ_inv	129	FpXQX_halfgcd	134
FpXQ_invsafe	129	FpXQX_halfgcd_all	134
FpXQ_issquare	129	FpXQX_invBarrett	134
FpXQ_log	129, 130, 146	FpXQX_isplayer	137
FpXQ_matrix_pow	130	FpXQX_mul	134
FpXQ_minpoly	130	FpXQX_nbfact	138
FpXQ_mul	128	FpXQX_nbfact_Frobenius	138
FpXQ_norm	130	FpXQX_nbroots	138
FpXQ_order	129, 146	FpXQX_normalize	133
FpXQ_pow	129	FpXQX_powu	134
FpXQ_powers	130	FpXQX_red	134
FpXQ_powu	129	FpXQX_rem	134
FpXQ_red	128	FpXQX_renormalize	134
FpXQ_sqr	128	FpXQX_resultant	134
FpXQ_sqrt	129	FpXQX_roots	137
FpXQ_sqrtn	129, 130, 146	FpXQX_roots_mult	137
FpXQ_sub	128	FpXQX_split_part	137
FpXQ_trace	130	FpXQX_sqr	134
FpXQC_to_mod	159	FpXQX_to_mod	159
FpXQE_add	354	FpXQXn_div	135
FpXQE_changepoint	353	FpXQXn_exp	135
FpXQE_changepointinv	353	FpXQXn_expint	135
FpXQE_dbl	354	FpXQXn_inv	135
FpXQE_log	354	FpXQXn_mul	135
FpXQE_mul	354	FpXQXn_sqr	135
FpXQE_neg	354	FpXQXQ_autpow	136
FpXQE_order	354	FpXQXQ_autsum	136
FpXQE_sub	354	FpXQXQ_auttrace	136
FpXQE_tatepairing	354	FpXQXQ_div	136
FpXQE_weilpairing	354	FpXQXQ_halfFrobenius	136
FpXQM_autsum	131	FpXQXQ_inv	136
FpXQX_ddf	137	FpXQXQ_invsafe	136
FpXQX_ddf_degree	137	FpXQXQ_matrix_pow	136
FpXQX_degfact	137	FpXQXQ_minpoly	136

FpXQXQ_mul	136	Fq_mulu	129
FpXQXQ_pow	136	Fq_neg	129
FpXQXQ_powers	136	Fq_neg_inv	129
FpXQXQ_sqr	136	Fq_pow	130
FpXQXT_red	134	Fq_powu	130
FpXQXV_FpXQX_fromdigits	134	Fq_red	128
FpXQXV_prod	134	Fq_sqr	129
FpXQXV_red	134	Fq_sqrt	130
FpXT_red	122	Fq_sqrtn	130
FpXV_chinese	125	Fq_sub	129
FpXV_composedsum	125	Fq_to_FF	249
FpXV_factorback	125	Fq_to_FpXQ	128
FpXV_FpC_mul	125	Fq_to_nf	310
FpXV_FpX_fromdigits	123	FqC_add	115
FpXV_prod	125	FqC_Fq_mul	115
FpXV_red	122	FqC_FqV_mul	115
FpXX_add	132	FqC_sub	115
FpXX_deriv	132	FqC_to_mod	159
FpXX_Fp_mul	132	FqM_deplin	115
FpXX_FpX_mul	132	FqM_det	115
FpXX_halve	132	FqM_FqC_gauss	115
FpXX_integ	132	FqM_FqC_invimage	115
FpXX_mulu	132	FqM_FqC_mul	115
FpXX_neg	132	FqM_gauss	115
FpXX_red	131	FqM_image	115
FpXX_renormalize	131	FqM_indexrank	115
FpXX_sub	132	FqM_inv	115
FpXY_eval	132	FqM_invimage	115
FpXY_evalx	132	FqM_ker	115
FpXY_evaly	132	FqM_mul	115
FpXY_FpXQ_evalx	132	FqM_rank	115
FpXY_FpXQ_evaly	132	FqM_suppl	115
FpXY_FpXQV_evalx	132	FqM_to_mod	159
FpXY_Fq_evaly	132	FqM_to_nfM	310
FpXYQQ_pow	132	FqV_factorback	130
Fq_add	129	FqV_inv	130
Fq_div	130	FqV_red	128
Fq_ellcard_SEA	353	FqV_roots_to_pol	137
Fq_ellcard_supersingular	353	FqV_to_nfV	310
Fq_elldivpolmod	353	FqX_add	132
Fq_elljissupersingular	353	FqX_ddf	137
Fq_Fp_mul	129	FqX_degfact	137
Fq_halve	129	FqX_deriv	133
Fq_inv	129	FqX_div	133
Fq_invsafe	129	FqX_div_by_X_x	133
Fq_ispower	130	FqX_divrem	133
Fq_issquare	130	FqX_eval	133
Fq_log	130	FqX_extgcd	133
Fq_mul	129	FqX_factor	137

gc_const	68	gen_cmp_RgX	235
gc_double	67	gen_det	215
gc_int	67	gen_digits	217
gc_long	67	gen_ellgens	213, 345
gc_needed	23	gen_ellgroup	213
gc_NULL	67	gen_factorback	241
gc_stoi	68	gen_factored_order	213
gc_ulong	67	gen_FpM_Wiedemann	194
gc_utoi	68	gen_fromdigits	217
gc_utoipos	68	gen_Gauss	215
gcdext	48	gen_Gauss_pivot	215
gcdii	101	gen_gener	213
gceil	229	gen_indexsort	234
gchari_lfun	338	gen_indexsort_uniq	234
gclone	27, 70, 71	gen_ker	215
gclone_refc	72	gen_m1	13
gcloneref	71	gen_m2	13
gcmp	230	gen_matcolinvimage	215
gcmpgs	232	gen_matcolmul	215
gcmpsg	232	gen_matid	215
gcoeff	15, 63, 277	gen_matinvimage	215
gconj	245	gen_matmul	215
gcopy	26, 71	gen_order	212, 213
gcopy_avma	70	gen_PH_log	213
gcopy_lg	71	gen_plog	212, 213
gcvtoi	230	gen_Pollard_log	212
gcvtop	220	gen_pow	240, 241
gdeuc	236	gen_pow_fold	241
gdiv	239	gen_pow_fold_i	241
gdivent[z]	235	gen_pow_i	240
gdiventgs[z]	235	gen_pow_init	241
gdiventres	235	gen_pow_table	241
gdiventsg	235	gen_powers	216, 241
gdivexact	235	gen_powu	240, 241
gdivgs	239	gen_powu_fold	241
gdivgu	235, 239	gen_powu_fold_i	241
gdivgunextu	235	gen_powu_i	241
gdivmod	236	gen_product	240
gdivround	236	gen_RgX_bkeval	216
gdivsg	239	gen_search	234
gdivz	240	gen_select_order	213
gdvd	235	gen_setminus	234
gel	14, 15, 63, 277	gen_Shanks	212
GEN	13	gen_Shanks_init	212
gen_0	13, 32	gen_Shanks_log	212
gen_1	13	gen_Shanks_sqrtm	213
gen_2	13	gen_sort	233
gen_bkeval	216	gen_sort_inplace	234
gen_bkeval_powers	216	gen_sort_shallow	234

gen_sort_uniq	234	get_F2xqX_mod	157
gen_ZpM_Dixon_Wiedemann	194	get_F2xqX_var	157
gen_ZpM_Newton	218	get_Fl_red	83
gen_ZpX_Dixon	217	get_Flx_degree	139
gen_ZpX_Newton	217	get_Flx_mod	138
GENbinbase	67	get_Flx_var	139
gener_F2xq	155	get_Flxq_field	215
gener_Flxq	147	get_Flxq_star	214
gener_FpXQ	130	get_FlxqE_group	214
gener_FpXQ_local	130	get_FlxqX_degree	149
gener_Fq_local	130	get_FlxqX_mod	149
GENtoGENstr	263	get_FlxqX_var	149
GENtoGENstr_nospace	263	get_FlxqXQ_algebra	216
GENtostr	39, 263	get_Fp_field	215
GENtostr_raw	263	get_FpE_group	214
GENtostr_unquoted	263	get_FpX_algebra	216
GENtoTeXstr	39, 263	get_FpX_degree	127
geq	233	get_FpX_mod	127
gequal	203, 231	get_FpX_var	127
gequal0	232	get_FpXQ_algebra	216
gequal1	232	get_FpXQ_star	214
gequalgs	232	get_FpXQE_group	214
gequalm1	232	get_FpXQX_algebra	216
gequalsg	232	get_FpXQX_degree	135
gequalX	230	get_FpXQX_mod	135
gerepile	18, 19, 25, 27, 68, 96	get_FpXQX_var	135
gerepileall	22	get_FpXQXQ_algebra	216
gerepileall	19, 23, 68	get_Fq_field	215
gerepileallsp	19, 68	get_lex	284
gerepilecoeffs	68	get_modpr	292
gerepilecoeffssp	69	get_nf	291
gerepilecopy	19, 23, 68	get_nf_field	215
gerepilemany	68	get_nfpol	291
gerepilemanysp	68	get_prid	292
gerepileupto	19, 25, 26, 69, 96, 175, 226, 227, 277, 306	get_Rg_algebra	216
gerepileuptoint	69	getheap	72
gerepileuptoleaf	69	getrand	101
get_arith_Z	213	getrealprecision	253
get_arith_ZZM	213	gettime	42
get_avma	67	gexpo	30, 60
get_bnf	291	gexpo_safe	60
get_bnfpol	291	gfloor	229
get_F2x_degree	153	gfrac	229
get_F2x_mod	153	ggamma1m1	254
get_F2x_var	153	ggcd	237
get_F2xq_field	215	gge	233
get_F2xqE_group	214	ggt	233
get_F2xqX_degree	157	ghalf	13
		gidentical	192, 231

gimag	245	gp_callprec	285
ginv	239	gp_callvoid	286
ginvmod	236	gp_context_restore	57
gisdouble	219	gp_context_save	57
gisexactzero	231	gp_display_hist	57
glcm	237	gp_echo_and_log	57
gle	232	gp_eval	285
glt	232	gp_evalbool	285
gmael	15, 63	gp_evalprec	285
gmael1	15	gp_evalupto	285
gmael2	63	gp_evalvoid	285
gmael3	63	gp_filter	56
gmael4	63	gp_format_prompt	56
gmael5	63	gp_format_time	56
gmax	231	gp_handle_exception	55
gmax_shallow	231	gp_help	57
gmaxgs	232	gp_load_gprc	56
gmaxsg	232	gp_meta	56
gmin	231	gp_read_file	38, 56
gmin_shallow	231	gp_read_str	35, 37, 56, 77
gmings	232	gp_read_str_bitprec	37
gminsg	232	gp_read_str_multiline	37
gmod[z]	236	gp_read_str_prec	37
gmodgs	236	gp_read_stream	37
gmodsg	236	gp_sigint_fun	55
gmodulgs	221	gphelp_keyword_list	57
gmodulo	221	gpinstall	56
gmodulsg	221	gpow	239
gmodulss	221	gpowers	240
gmul	239	gpowgs	239
gmul2n[z]	230	gprec	220
gmulgs	239	gprec_w	220
gmulgu	239	gprec_wensure	220
gmulsg	239	gprec_wtrunc	220
gmulug	239	gprecision	61
gmulz	240	gprimepi_lower_bound	179
gne	233	gprimepi_upper_bound	179
gneg[z]	238	Gram matrix	189
gneg_i	238	gram_matrix	189
gnorml1	242	greal	245
gnorml1_fake	242	gred_rfac2	33
gnorml2	241	grem	236
gnot	233	grndtoi	229
gor	233	grootsof1	240
GP prototype	74	ground	229
gp_alarm_handler	57	group_abelianHNF	260
gp_call	285	group_abelianSNF	260
gp_call2	285	group_domain	259
gp_callbool	286	group_elts	259

hash_select	275	idealaddmultoone	307
hash_str	274, 275	idealaddtoone	306, 307
hash_str_len	275	idealaddtoone_i	306
hash_values	275	idealaddtoone_raw	306
hash_zv	275	idealappr	307, 323
hashtentry	273	idealappr0	323
hashtable	273	idealapprfact	307
hclassno	325	idealchinese	307
hclassno6	326	idealchineseinit	307
hclassno6u	326	idealcoprime	307
hclassno6u_no_cache	326	idealcoprimefact	307
hclassnoF_fact	326	idealdiv	305
heap	14	idealdivexact	305
Hermite_bound	334	idealdivpowprime	306
hexadecimal tree	40	idealfactor	304, 307, 308
HIGHBIT	64	idealfactor_limit	308
HIGHEXPOBIT	64	idealfactor_partial	308
HIGHMASK	64	idealfrobenius_aut	309
HIGHVALPBIT	64	idealhnf	304, 305
HIGHWORD	64	idealhnf0	305
hilbertii	107	idealHNF_inv	306
hnf	332	idealHNF_inv_Z	306
hnf_CENTER	329	idealHNF_mul	306
hnf_divscale	330	idealhnf_principal	305
hnf_invimage	330	idealhnf_shallow	305
hnf_invscale	330	idealhnf_two	305
hnf_MODID	329	idealHNF_Z_factor	308
hnf_PART	329	idealHNF_Z_factor_i	308
hnf_solve	330	idealinv	305
hnfall	332	ideallog	304
hnfddivide	330	ideallog_units	319
hnflll	332	ideallog_units0	319
hnfmerge_get_1	306	idealmoddivisor	317
hnfmod	332	idealmul	305
hnfmodid	332	idealmulpowprime	306
hnfperm	332	idealmulred	305, 314
hqfeval	243	idealpow	305
hyperell_locally_soluble	355	idealpowred	305
		idealpows	305
		idealprimedec	304, 307, 308
		idealprimedec_degrees	308
		idealprimedec_galois	308
		idealprimedec_kummer	308
		idealprimedec_limit_f	308
		idealprimedec_limit_norm	308
		idealprincipalunits	312
		idealprod	306
		idealprodprime	306
		idealprodval	306

I	
icopy	87
icopy_avma	70
icopyifstack	71
icopyspec	87
id_MAT	292
id_PRIME	292
id_PRINCIPAL	292
idealadd	305

idealpseudomin	317	int_W_lg	29
idealpseudomin_nonscalar	317	integer	28
idealpseudominv	317	integser	248
idealpseudored	317	inv_content	238
idealramfrobenius	309	invmod	103
idealramfrobenius_aut	309	invmod2BIL	82
idealramgroups_aut	309	invr	96
idealred	317	is_357_power	106, 173, 174
idealred0	317	is_bigint	88
idealred_elt	317	is_const_t	63
ideals_by_norm	306	is_entry	73
idealsqr	305	is_extscalar_t	63
idealstar	312	is_gchar_group	338
idealstar0	323	is_intreal_t	62
Idealstarmod	296	is_linit	357
Idealstarprk	318	is_matvec_t	63
idealtyp	292	is_nf_extfactor	292
identity_perm	257	is_nf_factor	292
identity_ZV	181	is_noncalc_t	63
identity_zv	186	is_pm1	232
ifac_isprime	178	is_pth_power	174
ifac_next	178	is_qfb_t	62
ifac_read	178	is_rational_t	62
ifac_skip	178	is_real_t	62
ifac_start	178	is_recursive_t	62
imag_i	245	is_scalar_t	63
image	195	is_universal_constant	219
image2	194	is_vec_t	62
indexlexsort	233	is_Z_factor	177
indexpartial	314	is_Z_factornon0	177
indexsort	233	is_Z_factorpos	177
indexvecsort	233	isclone	28
indices_to_vec01	311	iscomplex	232
inf_get_sign	34	isexactzero	231
infinity	34	isinexact	232
init_Flxq	142	isinexactreal	232
init_Fq	137	isint	232
initprimetable	65	isint1	231
input	37	isintm1	231
install	35, 40, 76, 78	isintzero	231
int2n	86	ismpzero	231
int2u	86	isonstack	71
int2um1	86	isprime	179
int_LSW	29	isprimeAPRCL	179
int_MSW	29	isprimeECPP	179
int_nextW	29	isprimepower	107
int_normalize	29	isprincipal	315
int_precW	29	isprincipalfact	315
int_W	29	isprincipalfact_or_fail	315

isprincipalforce	323	leading_coeff	32, 63
isprincipalgen	323	leafcopy	87, 277
isprincipalgenforce	323	leafcopy_avma	87
isprincipalraygen	323	Legendre symbol	104
isrationalzero	231	lexcmp	230
isrationalzeroscalar	232	lexsort	233
isrealappr	232	lfun	358
issmall	232	lfun_get_bitprec	357
itor	87	lfun_get_dom	357
itos	27, 88, 219	lfun_get_domain	357
itos_or_0	88	lfun_get_expot	357
itostr	263	lfun_get_factgammavec	357
itou	88, 219	lfun_get_k2	357
itou_or_0	88	lfun_get_pol	357
K			
killblock	71	lfun_get_Residue	357
krois	104	lfun_get_step	357
kroi	104	lfun_get_w2	357
Kronecker symbol	104	lfunabelianreinit	359
kronecker	104	lfunellmfpeters	359
Kronecker_to_F2xqX	157	lfungchar	338
Kronecker_to_FlxqX	149	lfuninit	359
Kronecker_to_FlxqX_pre	149	lfuninit_make	359
Kronecker_to_FpXQX	134	lfunlambda	359
Kronecker_to_mod	211	lfunmisc_to_ldata	358
Kronecker_to_ZXQX	200	lfunmisc_to_ldata_shallow	358
Kronecker_to_ZXX	200	lfunmisc_to_ldata_shallow_i	358
krosi	104	lfunprod_get_fact	357
kross	104	lfunquadneg	359
kroui	104	lfunrootno	359
krouu	104	lfunrttopoles	358
L			
lcmii	101	lfunthetacheckinit	359
ldata_get_an	357	lfunthetacost	359
ldata_get_conductor	357	lfunzetakinit	359
ldata_get_degree	357	lg	28, 59
ldata_get_dual	357	lg2prec	59
ldata_get_gammavec	357	lg_increase	28
ldata_get_k	357	LGBITS	64
ldata_get_k1	357	lgcols	60
ldata_get_residue	357	lgefint	29, 59
ldata_get_rootno	357	LGnumBITS	64
ldata_get_type	357	lgpol	60
ldata_isreal	357	library mode	13
ldata_newprec	358	lift	221
ldata_vecan	358	lift0	221
		lift_shallow	221
		liftall	221
		liftall_shallow	221
		liftint	221
		liftint_shallow	221

liftpol	221	malloc	268
liftpol_shallow	221	mantissa2nr	90
lincombii	96	mantissa_real	30, 90
lindep	334	map_proto_G	105
lindep2	335	map_proto_GL	105
lindep_bit	334	map_proto_lG	105
lindep_padic	335	map_proto_lGL	105
lindep_Xadic	335	matbrute	266
lindepfull_bit	335	matdet	184
linit_get_ldata	357	mathnf	305
linit_get_tech	357	matid	224
linit_get_type	357	matid_F2m	119
list	34	matid_F2xqM	156
LLL	330, 333	matid_Flm	116
l1l	333	matid_FlxqM	122
LLL_ALL	334	matpermanent	184
LLL_COMPATIBLE	334	matrix	33
LLL_GRAM	333	matrixqz	332
LLL_IM	333, 334	matslice	278
LLL_INPLACE	333, 334	maxdd	92
LLL_KEEP_FIRST	334	maxomegaoddu	106
LLL_KER	334	maxomegau	106
l1lfp	334	maxprime	13, 65
l1lgen	333	maxprime_check	65
l1lgram	333	maxprimelim	65
l1lgramgen	333	maxprimeN	65
l1lgramint	333	maxss	92
l1lgramkerim	333	maxuu	92
l1lgramkeringen	333	MAXVARN	64
l1lint	333	MEDDEFAULTPREC	16, 63
l1lintpartial	334	merge_factor	234
l1lintpartial_inplace	334	merge_sort_uniq	234
l1lkerim	333	MF_get_basis	363, 364
l1lkeringen	333	MF_get_CHI	363
LOG10_2	65	mf_get_CHI	364
LOG2_10	65	MF_get_dim	363
logint	100	MF_get_E	363
logintall	100	mf_get_field	364
logr_abs	254	MF_get_fields	363
LONG_MAX	63	MF_get_gk	363
long_to_rgb	369	mf_get_gk	364
loop_break	284	MF_get_gN	363
LOWMASK	64	mf_get_gN	364
LOWWORD	64	MF_get_k	363
		mf_get_k	364
		MF_get_M	364
		MF_get_Mindex	364
		MF_get_Minv	364
		MF_get_N	363
M			
M_LN2	65		
M_PI	65		

mf_get_N	364	mkcomplex	226
MF_get_newforms	363	mkerr	227
mf_get_NK	364	mkfrac	226
MF_get_r	363	mkfraccopy	225
mf_get_r	364	mkfracss	225
MF_get_S	363, 364	mkintmod	226
MF_get_space	363	mkintmodu	224
mf_get_type	364	mkintn	24, 25, 88, 228
mfcharmodulus	365	mkmat	227
mfcharorder	365	mkmat2	227
mfcharpol	365	mkmat22	227
MFcusp_get_vMjd	364	mkmat22s	225
mfcuspdim	365	mkmat3	227
mfddiv_val	365	mkmat4	227
mfeisensteindim	365	mkmat5	227
mfeisensteinspaceinit	365	mkmatcopy	225
mfembed	365	mkmoo	34
mffulldim	365	mkoo	34
mfiscuspidal	365	mkpolmod	226
mfmaterembed	365	mkpoln	24, 228
MFnew_get_vj	364	mkqfb	227
mfnewdim	365	mkquad	226
mfnumcusps_fact	361	mkfrac	226
mfnumcuspsu	361	mkfraccopy	225
mfnumcuspsu_fact	361	mkvec	227
mfolddim	365	mkvec2	227
mfsturm_mf	365	mkvec2copy	225
mfsturmNgk	365	mkvec2s	225
mfsturmNk	365	mkvec3	227
mftobasisES	365	mkvec3s	225
mftocol	365	mkvec4	227
mfvecembed	365	mkvec4s	225
mfvectomat	365	mkvec5	227
millerrabin	180	mkveccopy	225
mindd	92	mkvecn	25, 229
minss	92	mkvecs	225
minuu	92	mkvecsmall	225
mkcol	226	mkvecsmall2	225
mkcol2	226	mkvecsmall3	225
mkcol2s	225	mkvecsmall4	226
mkcol3	226	mkvecsmall5	226
mkcol3s	225	mkvecsmalln	226
mkcol4	226	Mod16	99
mkcol4s	225	mod16	99
mkcol5	226	Mod2	99
mkcol6	226	mod2	99
mkcolcopy	225	mod2BIL	99
mkcoln	25, 229	Mod32	99
mkcols	225	mod32	99

newblock	71	nfchecksigns	311
nf_cxlog	312	nfcyclotomicunits	322
nf_cxlog_normalize	312	nfdiv	299
nf_deg1_prime	308	nfdiveuc	299
nf_FORCE	315	nfdivrem	299
nf_GEN	314	nfeltembed_i	312
nf_GEN_IF_PRINCIPAL	315	nfeltup	321
nf_GENMAT	314, 315	nfembed	312
nf_get_allroots	293	nffactorback	304
nf_get_degree	293	nfgaloisconj	322
nf_get_diff	293	nfgaloismatrix	324
nf_get_disc	293	nfgaloismatrixapply	324
nf_get_G	293	nfgaloispermtobasis	324
nf_get_Gtwist	316, 317, 334	nfgcd	202
nf_get_Gtwist1	316	nfgcd_all	202
nf_get_index	293	nfgwkummer	320
nf_get_invzk	293	nfinit_basic	313
nf_get_M	293, 315	nfinit_complete	314
nf_get_pol	293	nfinv	299
nf_get_prec	293	nfinvmodideal	300
nf_get_r1	293	nfissquarefree	320
nf_get_r2	293	nflogembed	313
nf_get_ramified_primes	293	nfM_det	301
nf_get_roots	293	nfM_inv	301
nf_get_roundG	293, 316, 317	nfM_ker	301
nf_get_sign	293	nfM_mul	301
nf_get_Tr	293	nfM_nfC_mul	301
nf_get_varn	293	nfM_to_FqM	310
nf_get_zk	293	nfmaxord	313
nf_get_zkden	293	nfmaxord_t	313, 314
nf_get_zkprimpart	293	nfmaxord_to_nf	313, 314
nf_hyperell_locally_soluble	355	nfmod	299
nf_nfzk	321	nfmodprinit	309, 310
nf_PARTIALFACT	313	nfmul	299
nf_pV_to_prV	308	nfmul_i	300
nf_rnfeq	320, 321	nfnewprec	298
nf_rnfeqsimple	321	nfnewprec_shallow	298
nf_ROUND2	313	nfnorm	299
nf_to_Fp_coprime	318	nfpoleval	299
nf_to_Fq	309, 310	nfpow	299
nf_to_Fq_init	309	nfpow_u	299
nf_to_scalar_or_alg	300	nfpowmodideal	300
nf_to_scalar_or_basis	299	nfroofs_if_split	322
nfadd	299	nfrootsof1	322
nfalgtobasis	300	nfsign	304, 311
nfarchstar	312	nfsign_arch	304, 311
nfbasistoalg	300	nfsign_from_logarch	312
nfC_multable_mul	301	nfsign_fu	311
nfC_nf_mul	300, 301	nfsign_tu	312

<code>nfsign_units</code>	311
<code>nfsqr</code>	299
<code>nfsqri</code>	300
<code>nfsqsub</code>	299
<code>nftrace</code>	299
<code>nftyp</code>	291
<code>nfV_cxlog</code>	313
<code>nfV_to_FqV</code>	310
<code>nfV_to_scalar_or_alg</code>	300
<code>nfval</code>	299, 310
<code>nfX_disc</code>	300
<code>nfX_resultant</code>	300
<code>nfX_to_FqX</code>	310
<code>nfX_to_monice</code>	300
<code>nm_Z_mul</code>	172
<code>nmV_chinese_center</code>	163
<code>nmV_chinese_center_tree</code>	163
<code>NO_VARIABLE</code>	32, 34, 60, 64
<code>nonsquare_Fl</code>	83
<code>normalize_frac</code>	62
<code>normalizapol</code>	32, 221
<code>normalizapol_approx</code>	221
<code>normalizapol_lg</code>	221
<code>normalizeser</code>	223
<code>numberofconjugates</code>	322
<code>numdivu</code>	106
<code>numdivu_fact</code>	106
<code>numer_i</code>	237
<code>numerr_name</code>	273
<code>nv_fromdigits_2k</code>	90
<code>nxCV_chinese_center</code>	163
<code>nxCV_chinese_center_tree</code>	164
<code>nxMV_chinese_center</code>	163
<code>nxV_chinese_center</code>	163
<code>nxV_chinese_center_tree</code>	164

O

<code>obj</code>	289
<code>obj_check</code>	289
<code>obj_checkbuild</code>	290
<code>obj_checkbuild_padicprec</code>	290
<code>obj_checkbuild_prec</code>	290
<code>obj_checkbuild_realprec</code>	290
<code>obj_free</code>	290, 343
<code>obj_init</code>	289
<code>obj_insert</code>	289, 290
<code>obj_insert_shallow</code>	290
<code>obj_reinit</code>	289

<code>odd</code>	82
<code>odd_prime_divisors</code>	175
<code>omega</code>	177
<code>omegau</code>	106
<code>ONLY_DIVIDES</code>	110, 206
<code>ONLY_REM</code>	110, 206
<code>out_printf</code>	265
<code>out_putc</code>	265
<code>out_puts</code>	265
<code>out_term_color</code>	266
<code>out_vprintf</code>	265
<code>outmat</code>	38
<code>output</code>	38
<code>output</code>	38, 40, 266

P

<code>p-adic number</code>	31
<code>p_to_FF</code>	249
<code>p_to_FF(p,0)</code>	249
<code>padic_to_Fl</code>	169
<code>padic_to_Fp</code>	112
<code>padic_to_Q</code>	168
<code>padic_to_Q_shallow</code>	168
<code>padicprec</code>	168
<code>padicprec_relative</code>	168
<code>parfor</code>	44
<code>parfor_init</code>	44
<code>parfor_next</code>	44
<code>parfor_stop</code>	45
<code>parforeach</code>	45
<code>parforeach_init</code>	45
<code>parforeach_next</code>	45
<code>parforeach_stop</code>	45
<code>parforprime</code>	46
<code>parforprime_init</code>	46
<code>parforprime_next</code>	46
<code>parforprime_stop</code>	46
<code>parforprimestep</code>	46
<code>parforprimestep_init</code>	46
<code>parforstep</code>	45
<code>parforstep_init</code>	45
<code>parforstep_next</code>	45
<code>parforstep_stop</code>	46
<code>parforvec</code>	46
<code>parforvec_init</code>	46
<code>parforvec_next</code>	46
<code>parforvec_stop</code>	46
<code>pari_add_defaults_module</code>	54

pari_add_function	54	pari_malloc	16, 66, 271
pari_add_hist	57	pari_mt_close	53
pari_add_module	54	pari_mt_init	52
pari_alarm	56	pari_nb_hist	57
pari_ask_confirm	56	PARI_OLD_NAMES	14
pari_base64	264	pari_outfile	38, 265
pari_calloc	16	PARI_plot	367
pari_CATCH	47	pari_plot_by_file	369
pari_CATCH_reset	47	pari_PRIMES	14
pari_center	56	pari_print_version	56
pari_close	51	pari_printf	38, 39, 40, 74, 265, 266
pari_close_opts	53	pari_putc	38, 74, 265
pari_community	56	pari_puts	38, 74, 265, 266
pari_compile_str	56	pari_rand	101
pari_daemon	53	pari_realloc	16, 271
pari_ENDCATCH	47	pari_realloc_ip	16
pari_err	33, 39, 47, 268, 288	pari_RETRY	47
pari_err2str	273	pari_safefopen	267
pari_err_display	273	pari_set_last_newline	265
pari_err_last	47	pari_set_plot_engine	367
pari_err_TYPE	342	pari_sig_init	53
pari_errfile	265	pari_sighandler	53
pari_fclose	267	pari_sp	17
pari_flush	38, 265	pari_sprintf	39, 263
pari_fopen	267	pari_stack_alloc	276
pari_fopen_or_fail	267	pari_stack_base	277
pari_fopengz	267	pari_stack_delete	277
pari_fprintf	39	pari_stack_init	276
pari_fread_chars	266	pari_stack_new	276
pari_free	16, 66	pari_stack_pushp	277
pari_get_hist	57	pari_stackcheck_init	53
pari_get_histrttime	57	pari_stdin_isatty	267
pari_get_histtime	57	pari_str	264
pari_get_homedir	267	pari_strdup	263
pari_histtime	57	pari_strndup	263
pari_hit_return	56	pari_thread_alloc	373
pari_infile	56	pari_thread_close	373
pari_init	13, 14, 51	pari_thread_free	373
pari_init_opts	51	pari_thread_init	373
pari_init_primes	52, 53	pari_thread_start	373
pari_is_default	286	pari_thread_valloc	373
pari_is_dir	266	pari_timer	41
pari_is_file	266	pari_TRY	47
pari_kernel_close	52	pari_unique_dir	268
pari_kernel_init	52	pari_unique_filename	268
pari_kernel_version	79	pari_unique_filename_suffix	268
pari_kill_plot_engine	367	pari_unlink	266
pari_last_was_newline	265	pari_var_close	72
pari_library_path	56	pari_var_create	72

pari_var_init	72	PiI2n	257
pari_var_next	72	plotbox	367
pari_var_next_temp	72	plotclip	367
PARI_VERSION	79	plotcolor	367
pari_version	79	plotcopy	367
PARI_VERSION_SHIFT	79	plotcursor	367
pari_vfprintf	39	plotdraw	367
pari_vprintf	39	ploth	367
pari_vsprintf	39	plothraw	367
pari_warn	40	plothsizes	367
paricfg_buildinfo	79	plotinit	367
paricfg_compileddate	79	plotkill	367
paricfg_datadir	79	plotline	367
paricfg_gphelp	79	plotlines	367
paricfg_mt_engine	79	plotlinetype	368
paricfg_vcsversion	79	plotmove	368
paricfg_version	79	plotpoints	368
paricfg_version_code	79	plotpointsize	368
pariErr	265	plotpointtype	368
PariOUT	264	plotrbox	368
pariOut	265	plotrecth	367
paristack_newsize	54	plotrecthraw	368
paristack_resize	53	plotrline	368
paristack_setsize	53	plotrmove	368
parivstack_reset	53	plotrpoint	368
parivstack_resize	54	plotscale	368
parser code	77	plotstring	368
path_expand	267	point_to_a4a6	343
perm_commute	258	point_to_a4a6_Fl	343
perm_conj	258	pol0_F2x	153
perm_cycles	258	pol0_Flx	141
perm_inv	258	pol1_F2x	153
perm_mul	258	pol1_F2xX	156
perm_order	258	pol1_Flx	141
perm_orderu	258	pol1_FlxX	147
perm_pow	258	pol_0	223
perm_powu	258	pol_1	223
perm_sign	258	pol_x	223
perm_sqr	258	pol_x_powers	224
perm_to_GAP	258	pol_xn	224
perm_to_Z	258	pol_xnall	224
pgener_Fl	83	polclass	354
pgener_Fl_local	83	polcoef_i	246
pgener_Fp	104	poldivrem	236
pgener_Fp_local	105	poleval	205, 242
pgener_Zl	83	polgalois	261
pgener_Zp	104	polhensellift	165, 167
Pi2n	257	polint_i	189
PiI2	257	polintspec	189

pollegendre_reduced	247	pr_get_tau	307
polmod	31	pr_hnf	307
polmod_nffix	322	pr_inv	307
polmod_nffix2	322	pr_inv_p	307
polmod_to_embed	247	pr_is_inert	307
polmodular	354	pr_norm	307
polmodular_ZM	354	pr_uniformizer	309
polmodular_ZXX	354	prec2lg	59
Polred	323	prec2nbits	59
polred0	323	prec2nbits_mul	59
polredabs	323	prec2ndec	59
polredabs2	323	precdbl	59
polredabsall	323	precision	60
Polrev	223	precision0	221
polx_F2x	154	precp	31, 60
polx_F2xX	156	PRECPBITS	64
polx_Flx	142	PRECPSHIFT	64
polx_FlxX	147	preferences file	77
polx_zx	202	<i>prid</i>	307
polxn_Flx	142	prime	179
polynomial	32	prime_fact	224
pop_lex	76, 284	primeform	327
pow2Pis	255	primeform_u	327
powcx	255	primepi_lower_bound	179
powcx_prec	255	primepi_upper_bound	178, 179
power series	33	primes	179
powersr	100	primes_interval	179
powgi	240	primes_interval_zv	179
powii	99	PRIMES_search	65
powis	99	primes_upto_zv	179
powIs	100	primes_zv	179
powiu	99	primitive root	83
powPis	255	primitive_part	237
powrfrac	100	primpart	237
powrs	99	print_fun_list	57
powrshalf	100	printf	38, 39, 74
powru	100	prodprimes	65
powruhalf	100	prV_lcm_capZ	308
powuu	99	prV_primes	309
ppg	176	psdraw	368
ppi	176	psi1series	248
pple	176	psploth	368
ppo	176	psplothraw	368
pr_basis_perm	310	pthread_join	373
pr_equal	311	push_lex	76, 284
pr_get_e	307	putch	265
pr_get_f	307	puts	265
pr_get_gen	307		
pr_get_p	307		

Q

Q_abs	237	qfbsolve	327
Q_abs_shallow	237	qfbsqr	326
Q_content	238	qfbsqr_i	326
Q_content_safe	238	qfeval	243
Q_denom	238	qfevalb	243
Q_denom_safe	238	qfi_log	327
Q_div_to_int	238	qfi_order	327
Q_factor	176	qfi_Shanks	327
Q_factor_limit	176	qfiseven	190
Q_gcd	237	qfisolvep	327
Q_lval	237	qflll0	333
Q_lvalrem	237	qflllgram0	333
Q_mul_to_int	238	qfr3	328
Q_muli_to_int	238	qfr3_comp	328
Q_primitive_part	238	qfr3_compraw	328
Q_primpart	238	qfr3_pow	328
Q_pval	237	qfr3_red	328
Q_pvalrem	237	qfr3_rho	328
Q_remove_denom	238, 299	qfr3_to_qfr	328
Q_to_famat	303	qfr5	328
Qab_trace_init	302	qfr5_comp	328
Qab_tracerel	302	qfr5_compraw	329
QabM_tracerel	302	qfr5_dist	329
QabV_tracerel	302	qfr5_pow	329
Qdivii	237	qfr5_red	329
Qdivis	237	qfr5_rho	329
Qdiviu	237	qfr5_to_qfr	329
Qevproj_apply	185	qfr_data_init	328
Qevproj_apply_vecei	185	qfr_to_qfr5	329
Qevproj_down	185	qfrsolvep	327
Qevproj_init	185	QM_charpoly_ZX	185
qf_RgM_apply	243	QM_charpoly_ZX_bound	185
qf_ZM_apply	243	QM_det	187
qfb_1	326	QM_gauss	185
qfb_disc	246	QM_gauss_i	185
qfb_disc3	246	QM_image	185
qfb_equal1	326	QM_image_shallow	185
qfb_ZM_apply	246	QM_ImQ	332
qfbcomp	326	QM_ImQ_all	332
qfbcomp_i	326	QM_ImQ_hnf	332
qfbcompraw	326	QM_ImQ_hnfall	332
qfbcompraw_i	326	QM_ImZ	332
qfbforms	246	QM_ImZ_all	332
qfbpow	327	QM_ImZ_hnf	332
qfbpow_i	327	QM_ImZ_hnfall	332
qfbpowraw	327	QM_indexrank	185
qfbpows	327	QM_inv	185
qfbred	326	QM_ker	187
qfbred_i	326	QM_minors_coprime	332

QM_mul	187	QXQ_mul(A,QXQ_inv(B,T),T)	201
QM_QC_mul	187	QXQ_norm	200, 201
QM_rank	185	QXQ_powers	201
QM_sqr	187	QXQ_reverse	201
Qp_agm2_sequence	256	QXQ_sqr	201
Qp_ascending_Landen	256	QXQ_to_mod_shallow	159
Qp_descending_Landen	256	QXQC_to_mod_shallow	160
Qp_exp	256	QXQM_mul	202
Qp_exp_prec	256	QXQM_sqr	202
Qp_gamma	256	QXQM_to_mod_shallow	160
Qp_log	256	QXQV_to_FpM	310
Qp_psi	256	QXQV_to_mod	159
Qp_sqrt	256	QXQX_gcd	202
Qp_sqrtn	256	QXQX_homogenous_evalpow	202
Qp_zeta	256	QXQX_mul	201
Qp_zetahurwitz	256	QXQX_powers	201
QpV_to_QV	168	QXQX_QXQ_mul	201
QR_init	192	QXQX_sqr	201
Qtoss	225	QXQX_to_mod_shallow	159
quad_disc	246	QXQXV_to_mod	160
quadclassno	325	QXV_QXQ_eval	201
quadclassnoF	325	QXY_QXQ_evalx	201
quadclassnoF_fact	325		
quadclassnos	325		
quadnorm	246		
quadpoly	31		
quadpoly_i	226		
quadratic number	31		
quadratic_prec_mask	168		
quadtofp	219		
quotient_group	260		
quotient_groupeelts	260		
quotient_perm	260		
quotient_subgroup_lift	261		
QV_isscalar	190		
QX_complex_roots	200, 247		
QX_disc	200		
QX_factor	200		
QX_gcd	200		
QX_mul	200		
QX_resultant	200		
QX_sqr	200		
QX_ZX_rem	200		
QX_ZXQV_eval	201		
QXQ_charpoly	201		
QXQ_div	201		
QXQ_intnorm	201		
QXQ_inv	201		
QXQ_mul	201		
		R	
		R_abs	245
		R_abs_shallow	245
		R_from_QR	192
		radicalu	106
		random	101
		random_bits	101
		random_F2x	154
		random_F2xqE	351
		random_F2xqX	157
		random_Fl	83, 102
		random_Fle	350
		random_Fle_pre	350
		random_Flj_pre	350
		random_Flv	116
		random_Flx	142
		random_FlxqE	352
		random_FlxqX	149
		random_FpC	113
		random_FpE	348
		random_FpV	113
		random_FpX	126
		random_FpXQE	354
		random_FpXQX	134
		random_Fq	129

random_zv	186	retmkmat2	228
randomi	102	retmkmat22	228
randomr	102	retmkmat3	228
rational function	33	retmkmat4	228
rational number	31	retmkmat5	228
raw	263	retmkpolmod	228
rcopy	87	retmkquad	228
rdivii	97	retmkfrac	228
rdiviiz	97	retmkvec	227
rdivis	97	retmkvec2	227
rdivsi	97	retmkvec3	227
rdivss	97	retmkvec4	227
read	37, 38	retmkvec5	227
readseq	37	rfrac_deflate	204
real number	30	rfrac_deflate_max	204
real2n	86	rfrac_deflate_order	204
real_0	86	rfrac_to_ser	222
real_0_bit	86	rfrac_to_ser_i	223
real_1	86	rfracrecip	203
real_1_bit	86	rfracrecip_to_ser_absolute	223
real_i	245	Rg_col_ei	224
real_m1	86	Rg_get_0	33, 111
real_m2n	86	Rg_get_1	111
realprec	59	Rg_is_FF	249
rect2ps	368	Rg_is_Fp	112
rect2ps_i	368	Rg_is_FpXQ	128
rect2svg	369	Rg_nffix	321, 322
reducemodinvertible	335	Rg_RgC_sub	188
reducemodlll	336	Rg_RgX_sub	205
remi2n	96, 195	Rg_to_F2	169
remll_pre	84	Rg_to_F2xq	170
remlll_pre	84	Rg_to_Fl	169
remsBIL	64	Rg_to_Flxq	170
residual_characteristic	247	Rg_to_Fp	112, 113
resultant (reduced)	166	Rg_to_FpXQ	128
resultant	236, 247	Rg_to_Fq	128
resultant2	247	Rg_to_RgC	222
retconst_col	228	Rg_type	110
retconst_vec	227	RgC_add	187
retmkcol	228	RgC_fpnorml2	191
retmkcol2	228	RgC_gtofp	190
retmkcol3	228	RgC_gtomp	190
retmkcol4	228	RgC_is_ei	190
retmkcol5	228	RgC_is_FFC	249
retmkcol6	228	RgC_neg	187
retmkcomplex	228	RgC_Rg_add	188
retmkfrac	228	RgC_Rg_div	188
retmkintmod	228	RgC_Rg_mul	188
retmkmat	228	RgC_Rg_sub	188

RgC_RgM_mul	189	RgM_Rg_sub	188
RgC_RgV_mul	188	RgM_Rg_sub_shallow	188
RgC_RgV_mulrealsym	189	RgM_RgC_invimage	191
RgC_sub	187	RgM_RgC_mul	188
RgC_to_FpC	112	RgM_RgC_type	112
RgC_to_FqC	115	RgM_RgV_mul	189
RgC_to_nfC	300	RgM_RgX_mul	188
RgE_to_F2xqE	351	RgM_shallowcopy	277
RgE_to_FlxqE	352	RgM_solve	191
RgE_to_FpE	349	RgM_solve_realimag	191
RgE_to_FpXQE	354	RgM_sqr	188
RgM_add	187	RgM_sub	187
RgM_Babai	192	RgM_sumcol	189
RgM_check_ZM	183	RgM_to_F2m	120
RgM_Cholesky	192	RgM_to_F3m	121
RgM_det_triangular	191	RgM_to_Flm	170
RgM_diagonal	190	RgM_to_FpM	113
RgM_diagonal_shallow	190	RgM_to_FqM	115
RgM_dimensions	187	RgM_to_nfM	300
RgM_div	188	RgM_to_RgXV	222
RgM_Fp_init	113	RgM_to_RgXV_reverse	222
RgM_fpnorml2	191, 241	RgM_to_RgXX	222
RgM_gram_schmidt	192	RgM_transmul	188
RgM_gtofp	191	RgM_transmultosym	188
RgM_gtomp	191, 192	RgM_type	112
RgM_Hadamard	191	RgM_type2	112
RgM_hnfall	333	RgM_zc_mul	172
RgM_inv	191	RgM_zm_mul	172
RgM_inv_upper	191	RgM_ZM_mul	188
RgM_invimage	191	RgMrow_RgC_mul	188
RgM_is_FFM	249	RgMrow_zc_mul	172
RgM_is_FpM	112	RgMs_structelim	194
RgM_is_QM	190	RgV_add	187
RgM_is_ZM	190	RgV_check_ZV	181
RgM_isdiagonal	190	RgV_dotproduct	189
RgM_isidentity	190	RgV_dotsquare	189
RgM_isscalar	190	RgV_F2v_extract_shallow	278
RgM_minor	278	RgV_gtofp	190
RgM_mul	188	RgV_is_arithprog	181
RgM_mulreal	188	RgV_is_FpV	112
RgM_multosym	188	RgV_is_prV	292
RgM_neg	187	RgV_is_QV	181
RgM_powers	189	RgV_is_ZMV	187
RgM_QR_init	192	RgV_is_ZV	181
RgM_rescale_to_int	183	RgV_is_ZVnon0	181
RgM_Rg_add	187	RgV_is_ZVpos	181
RgM_Rg_add_shallow	188	RgV_isin	190
RgM_Rg_div	188	RgV_isin_i	190
RgM_Rg_mul	188	RgV_isscalar	190

RgV_kill0	189	RgX_div_by_X_x	206
RgV_neg	187	RgX_divrem	206
RgV_nffix	321	RgX_divs	205
RgV_polint	189	RgX_equal	203
RgV_prod	189	RgX_equal_var	203
RgV_Rg_mul	188	RgX_even_odd	154, 203
RgV_RgC_mul	188	RgX_extgcd	207
RgV_RgM_mul	188	RgX_extgcd_simple	207
RgV_sub	187	RgX_fpnorml2	207
RgV_sum	189	RgX_gcd	207
RgV_sumpart	189	RgX_gcd_simple	207
RgV_sumpart2	189	RgX_gtofp	207
RgV_to_F2v	120	RgX_halfgcd	207
RgV_to_F3v	121	RgX_halfgcd_all	207
RgV_to_Flv	170	RgX_homogenize	204
RgV_to_FpV	112	RgX_homogenous_evalpow	204
RgV_to_RgM	222	RgX_inflate	204
RgV_to_RgX	221	RgX_integ	207
RgV_to_RgX_reverse	222	RgX_is_FpX	122
RgV_to_ser	222	RgX_is_FpXQX	128
RgV_to_str	263, 264	RgX_is_monomial	202
RgV_type	112	RgX_is_QX	202
RgV_type2	112	RgX_is_rational	202
RgV_zc_mul	172	RgX_is_ZX	202
RgV_zm_mul	172	RgX_isscalar	202
RgX_act_G12Q	208	RgX_mul	205
RgX_act_ZG12Q	208	RgX_mul2n	205
RgX_add	205	RgX_mul_i	205
RgX_addmulXn	206	RgX_mul_normalized	206
RgX_addmulXn_shallow	206	RgX_mulhigh_i	208
RgX_addspec	207	RgX_muls	205
RgX_addspec_shallow	207	RgX_mulspec	207
RgX_affine	208	RgX_mulXn	206
RgX_blocks	143, 148, 203	RgX_neg	205
RgX_check_QX	200	RgX_nffix	321
RgX_check_ZX	195	RgX_normalize	205
RgX_check_ZXX	199	RgX_pseudodivrem	206
RgX_chinese_coprime	207	RgX_pseudorem	206
RgX_coeff	203	RgX_recip	203
RgX_copy	203	RgX_recip_i	203
RgX_cxeval	242	RgX_recip_shallow	203
RgX_deflate	203	RgX_rem	206
RgX_deflate_max	204	RgX_renormalize	203
RgX_deflate_order	203	RgX_renormalize_lg	203
RgX_degree	202	RgX_rescale	207
RgX_deriv	207	RgX_rescale_to_int	204
RgX_digits	206	RgX_resultant_all	207
RgX_disc	207	RgX_Rg_add	205
RgX_div	206	RgX_Rg_add_shallow	205

RgX_Rg_div	205	RgXn_exp	209
RgX_Rg_divexact	205	RgXn_expint	209
RgX_Rg_eval_bk	205	RgXn_inv	208
RgX_Rg_mul	205	RgXn_inv_i	208
RgX_Rg_sub	205	RgXn_mul	208
RgX_Rg_type	111	RgXn_powers	209
RgX_RgM_eval	242	RgXn_powu	209
RgX_RgMV_eval	243	RgXn_powu_i	209
RgX_RgV_eval	205	RgXn_recip_shallow	208
RgX_RgXn_eval	209	RgXn_red_shallow	208
RgX_RgXnV_eval	209	RgXn_reverse	209
RgX_RgXQ_eval	209, 210	RgXn_sqr	208
RgX_RgXQV_eval	210	RgXn_sqrt	209
RgX_rotate_shallow	204	RgXnV_red_shallow	209
RgX_shift	154, 204	RgXQ_charpoly	209
RgX_shift_inplace	204	RgXQ_inv	209
RgX_shift_inplace_init	204	RgXQ_matrix_pow	209
RgX_shift_shallow	204	RgXQ_minpoly	210
RgX_splitting	143, 203	RgXQ_mul	209
RgX_sqr	206	RgXQ_norm	209
RgX_sqr_i	206	RgXQ_pow	209
RgX_sqrhigh_i	208	RgXQ_powers	209
RgX_sqrspec	207	RgXQ_powu	209
RgX_sub	205	RgXQ_ratlift	210
RgX_sylvestermatrix	229	RgXQ_reverse	210
RgX_to_F2x	169	RgXQ_sqr	209
RgX_to_Flx	170	RgXQ_trace	209
RgX_to_FlxqX	170	RgXQC_red	210
RgX_to_FpX	122	RgXQM_mul	210
RgX_to_FpXQX	128	RgXQM_red	210
RgX_to_FqX	128	RgXQV_factorback	210
RgX_to_nfX	300	RgXQV_red	210
RgX_to_RgC	222	RgXQV_RgXQ_mul	210
RgX_to_RgV	222	RgXQX_div	211
RgX_to_ser	222	RgXQX_divrem	211
RgX_to_ser_inexact	222	RgXQX_mul	210
RgX_translate	208	RgXQX_powers	210
RgX_type	111	RgXQX_pseudodivrem	206
RgX_type2	112	RgXQX_pseudorem	206
RgX_type3	112	RgXQX_red	210
RgX_type_decode	111	RgXQX_rem	211
RgX_type_is_composite	111	RgXQX_RgXQ_mul	210
RgX_unscale	208	RgXQX_sqr	210
RgX_val	205	RgXQX_translate	211
RgX_valrem	205	RgXV_maxdegree	205
RgX_valrem_inexact	205	RgXV_prod	206
RgXn_div	209	RgXV_rescale	208
RgXn_div_i	209	RgXV_RgV_eval	205
RgXn_eval	209	RgXV_to_FlxV	170

sd_help	287	set_avma	67
sd_histfile	287	set_lex	284
sd_histsize	287	set_sign_mod_divisor	312
sd_intarray	288	setabssign	62
sd_lines	287	setalldebug	41
sd_linewrap	287	setdefault	54, 286
sd_log	287	setexpo	30, 33, 62
sd_logfile	287	setisclone	28
sd_nbthreads	287	setlg	28, 62
sd_new_galois_format	287	setlgfint	29, 62
sd_output	287	setprec	31, 62
sd_parisize	287	setrand	101
sd_parisizemax	287	setrealprecision	253
sd_path	287	setsigne	29, 32, 33, 62
sd_plothsizes	287	settyp	28, 62
sd_prettyprinter	287	setunion_i	234
sd_primelimit	287	setvalp	31, 62
sd_prompt	287	setvalser	33, 62
sd_prompt_cont	287	setvarn	25, 32, 33, 62, 228
sd_psfile	287	<i>shallow</i>	51
sd_readline	287	shallowconcat	277, 278
sd_realbitprecision	287	shallowconcat1	277
sd_realprecision	287	shallowcopy	26, 277
sd_recover	287	shallowextract	278
sd_secure	287	shallowmatconcat	278
sd_seriesprecision	287	shallowmatextract	278
sd_simplify	287	shallowtrans	277
sd_sopath	287	shift_left	90
sd_strictargs	287	shift_right	90
sd_strictmatch	287	shiftaddress	67
sd_string	289	shiftaddress_canon	67
sd_TeXstyle	286	shifti	89
sd_threadsize	287	shiftl	82
sd_threadsizemax	287	shiftlr	82
sd_timer	287	shiftr	89
sd_toggle	288	shiftr_inplace	89
sd_ulong	288	SIGNBITS	64
sdivsi	98	signe	29, 32, 33, 59
sdivsi_rem	98	SIGNumBITS	64
sdivss_rem	98	SIGNSHIFT	64
sdomain_isincl	358	simplefactmod	160
secure	55	simplify	71
ser_inv	248	simplify_shallow	71
ser_isexactzero	248	sisfundamental	106
ser_normalize	248	sizedigit	61
ser_unscale	248	SL2_inv_shallow	184
serchop0	223	SMALL_ULONG	85
serchop_i	223	smallpolred	323
sertoser	248	smallpolred2	323

uissquare	173	VALPBITS	64
uissquareall	173	VALPnumBITS	64
uissquarefree	106	vals	89
uissquarefree_fact	106	valser	33, 60
ulcm	101	vandermondeinverse	189
ulogint	100	vandermondeinverseinit	190
ulogintall	100	varargs	24
ulong	51	varhigher	35
ULONG_MAX	63	variable (priority)	34
umodi2n	99	variable (temporary)	36
umodiu	99	variable (user)	35
umodsu	99	variable number	32, 34, 75
umodui	99	varlower	35
umuluu_le	96	varn	32, 33, 34, 60
umuluu_or_0	96	VARNBITS	64
unegisfundamental	106	varncmp	34
unegquadclassnoF	325	varnmax	37
unextprime	179	varnmin	37
unsetisclone	28	VARNnumBITS	64
uordinal	263	VARNSHIFT	64
uposisfundamental	106	vars_sort_inplace	72
uposquadclassnoF	325	vars_to_RgXV	73
upowers	100	vconcat	278
upowuu	100	vec01_to_indices	311
upper_to_cx	219	vec_append	279
upr_norm	307	vec_ei	224
uprecprime	179	vec_equiv	280
uprime	179	vec_insert	280
uprimepi	178	vec_is1to1	279
uquadclassnoF_fact	325	vec_isconst	279
usqrt	173	vec_lengthen	280
usqrtn	173	vec_prepend	279
usumdiv_fact	107	vec_Q_primpart	238
usumdivk_fact	107	vec_reduce	280
utoi	88	vec_setconst	279
utoineg	88	vec_shorten	280
utoipos	88	vec_to_vecsmall	280
utor	88	vecan_gchar	338
uu32toi	25, 88	vecbinomial	245
uu32toineg	88	vecdiv	279
uutoi	88	vecextract	278
uutoineg	88	vecfactoroddu	175
uutoQ	225	vecfactoroddu_i	175
		vecfactorsquarefreeu	175
		vecfactorsquarefreeu_coprime	176
		vecfactoru	175
		vecfactoru_i	175
		vecindexmax	233
		vecindexmin	233
V			
va_list	39		
vali	89		
valp	31, 60		

Z_isfundamental	178	ZC_neg	181
Z_ispow2	173	ZC_nfval	310
Z_ispower	173	ZC_nfvalrem	310
Z_ispowerall	173	ZC_prdvd	311
Z_issmooth	174	ZC_Q_mul	184
Z_issmooth_fact	174	ZC_reducemodlll	335
Z_issquare	173	ZC_reducemodmatrix	335
Z_issquareall	173	ZC_sub	181
Z_issquarefree	178	zc_to_ZC	171
Z_issquarefree_fact	178	ZC_union_shallow	182
Z_lsmoothen	175	ZC_Z_add	181
Z_lval	91	ZC_Z_div	182
z_lval	91	ZC_Z_divexact	181
Z_lvalrem	91	ZC_z_mul	172
z_lvalrem	91	ZC_Z_mul	181
Z_lvalrem_stop	91	ZC_Z_sub	181
Z_nv_mod	161	ZC_ZV_mul	182
Z_pollardbrent	176	zCs_to_ZC	193
Z_ppgle	176	zero_F2m	119
Z_ppio	176	zero_F2m_copy	120
Z_ppo	176	zero_F2v	119
Z_pval	91	zero_F2x	153
z_pval	91	zero_F3m_copy	121
Z_pvalrem	91	zero_F3v	121
z_pvalrem	91	zero_Flm	117
Z_smoothen	175	zero_Flm_copy	117
Z_to_F2x	153	zero_Flv	117
Z_to_famat	303	zero_Flx	141
Z_to_Flx	172	zero_FlxC	144
Z_to_FpX	124	zero_FlxM	144
Z_to_perm	258	zero_zm	186
Z_ZC_sub	181	zero_zv	186
Z_ZV_mod	161	zero_zx	202
Z_ZV_mod_tree	162	zerocol	224
Z_ZX_sub	195	zeromat	224
ZabM_indexrank	302	zeromatcopy	224
ZabM_inv	302	zeropadic	223
ZabM_inv_ratlift	302	zeropadic_shallow	229
ZabM_ker	302	zeropol	224
ZabM_pseudoinv	302	zeroser	223
ZC_add	181	zerovec	224
ZC_copy	181	zerovec_block	224
ZC_divexactu	181	ZG_add	193
ZC_hnfrem	335	ZG_G_mul	193
ZC_hnfremdiv	335	ZG_mul	193
ZC_is_ei	185	ZG_neg	193
ZC_lincomb	182	ZG_normalize	192
ZC_lincomb1_inplace	182	ZG_sub	193
ZC_lincomb1_inplace_i	182	ZG_Z_mul	193

ZGC_G_mul	193	ZM_hnfmodid	329, 332
ZGC_G_mul_inplace	193	ZM_hnfmodprime	329
ZGC_Z_mul	193	ZM_hnfperm	330
ZGCs_add	193	ZM_hnfrem	335
Zideallog	337	ZM_imagecompl	184
zidealstar	322	ZM_incremental_CRT	161
zidealstarinit	322	ZM_indeximage	184
zidealstarinitgen	322	ZM_indexrank	184
zk_inv	301	ZM_init_CRT	161
zk_multable	301, 305	ZM_inv	184
zk_scalar_or_multable	301, 307	ZM_inv_ratlift	184
zk_to_Fq	310	ZM_isdiagonal	185
zk_to_Fq_init	310	ZM_ishnf	185
zkC_multable_mul	301	ZM_isidentity	185
zkchinese	306	ZM_isscalar	185
zkchinese1	306	ZM_ker	184
zkchineseinit	306	ZM_lll	333, 334
zkmodprinit	310	ZM_lll_norms	334
zkmultable_capZ	301	ZM_max_expi	184
zkmultable_inv	301	ZM_max_lg	184
zlm_echelon	168	ZM_merge_factor	234
ZlM_gauss	168	ZM_mul	183
zlx_translate1	140	zm_mul	186
zlxX_translate1	148	ZM_mul_diag	183
ZM2_mul	183	ZM_multosym	183
ZM2_sqr	183	ZM_neg	183
ZM_add	183	ZM_nm_mul	172
ZM_charpoly	184	ZM_nv_mod_tree	162
ZM_copy	183	ZM_permanent	184
zm_copy	186	zm_permanent	187
ZM_det	184	ZM_pow	184
ZM_det_triangular	185	ZM_powu	184
ZM_detmult	184	ZM_pseudoinv	184
ZM_diag_mul	183	ZM_Q_mul	184
ZM_divexactu	183	ZM_rank	184
ZM_equal	183	ZM_reducemodlll	335
ZM_equal0	183	ZM_reducemodmatrix	335
ZM_famat_limit	304	zm_row	187
ZM_gauss	185	ZM_snf	330
ZM_hnf	329, 332	ZM_snf_group	331
ZM_hnf_knapsack	330	ZM_snfall	331
ZM_hnfall	329, 330, 332, 333	ZM_snfall_i	331
ZM_hnfall_i	330	ZM_snfclean	331
ZM_hnfcenter	330	ZM_sqr	183
ZM_hnfdivrem	335	ZM_sub	183
ZM_hnflll	330	ZM_supnorm	184, 241
ZM_hnfmod	329, 332	ZM_to_F2m	120
ZM_hnfmodall	329	ZM_to_F3m	121
ZM_hnfmodall_i	329	ZM_to_Flm	170

zm_to_Flm	171	znstar_get_pe	297
ZM_to_zm	171	znstar_get_U	297
zm_to_ZM	171	znstar_get_Ui	297
zm_to_zxV	172	Zp_div	164
ZM_togglesign	183	Zp_exp	165
ZM_transmul	183	Zp_inv	164
ZM_transmultosym	183	Zp_invlift	164
zm_transpose	186	Zp_issquare	104
ZM_Z_div	184	Zp_log	165
ZM_Z_divexact	183	Zp_sqrt	164
ZM_Z_mul	183	Zp_sqrtlift	165
ZM_zc_mul	172	Zp_sqrtnlift	165
ZM_ZC_mul	183	Zp_teichmuller	165
zm_zc_mul	186	ZpM_echelon	168
ZM_zm_mul	172	ZpM_invlift	165
ZM_ZV_mod	184	ZpMs_ZpCs_solve	194
ZM_ZX_mul	183	ZpX_disc_val	166
ZMrow_equal0	183	ZpX_Frobenius	166
ZMrow_ZC_mul	183	ZpX_gcd	166
zMs_to_ZM	193	ZpX_liftfact	165
zMs_ZC_mul	194	ZpX_liftroot	165, 167
ZMV_to_FlmV	187	ZpX_liftroots	165
ZMV_to_zmV	187	ZpX_monic_factor	166
zmV_to_ZMV	187	ZpX_primedec	166
Zn_ispower	104	ZpX_reduced_resultant	166
Zn_issquare	104	ZpX_reduced_resultant_fast	166
Zn_quad_roots	104	ZpX_resultant_val	166
Zn_sqrt	104	ZpX_roots	165
znchar_quad	337	ZpX_ZpXQ_liftroot	167
zncharcheck	337	ZpX_ZpXQ_liftroot_ea	167
zncharconj	337	ZpXQ_div	166
znchardiv	337	ZpXQ_inv	166
znchareval	337	ZpXQ_invlift	166
zncharker	337	ZpXQ_log	167
zncharmul	337	ZpXQ_sqrt	167
zncharorder	337	ZpXQ_sqrtnlift	166
zncharpow	337	ZpXQM_prodFrobenius	167
znconrey_check	337	ZpXQX_digits	168
znconrey_normalized	337	ZpXQX_divrem	168
znconreyfromchar	337	ZpXQX_liftfact	167
znconreyfromchar_normalized	337	ZpXQX_liftroot	167, 168
znconreylog_normalize	337	ZpXQX_liftroot_vald	167
znstar_get_conreycyc	297	ZpXQX_liftroots	167
znstar_get_conreygen	297	ZpXQX_roots	167
znstar_get_cyc	297	ZpXQX_ZpXQXQ_liftroot	168
znstar_get_faN	297	Zq_sqrtnlift	167
znstar_get_gen	297	ZqX_liftfact	168
znstar_get_N	297	ZqX_liftroot	168
znstar_get_no	297	ZqX_roots	168

ZqX_ZqXQ_liftroot	168	zv_snf_rank	332
zv_abs	186	ZV_snf_rank_u	332
ZV_abscmp	181	ZV_snf_trunc	331
ZV_allpnqn	101	ZV_snfall	331
ZV_cba	177	ZV_snfclean	331
ZV_cba_extend	176	ZV_sort	182
ZV_chinese	162	ZV_sort_inplace	182
ZV_chinese_center	162	ZV_sort_shallow	182
ZV_chinese_tree	163	ZV_sort_uniq	182
ZV_chinesetree	163	ZV_sort_uniq_shallow	182
ZV_cmp	181, 235	ZV_sum	182
zv_cmp0	186	zv_sum	186
ZV_content	182	zv_sumpart	186
zv_content	186	ZV_to_F2v	120
zv_copy	186	ZV_to_F3v	121
zv_cyc_minimal	337	ZV_to_Flv	170
zv_cyc_minimize	337	zv_to_Flv	171
zv_diagonal	187	ZV_to_nv	171
ZV_dotproduct	182	ZV_to_zv	171
zv_dotproduct	186	zv_to_ZV	171
ZV_dotsquare	182	zv_to_zx	172
ZV_dvd	182	ZV_togglesign	181
ZV_equal	181	ZV_union_shallow	182
zv_equal	186	ZV_Z_dvd	91
ZV_equal0	181	zv_z_mul	186
zv_equal0	186	ZV_zc_mul	172
ZV_extgcd	101, 182	zv_ZM_mul	172
ZV_indexsort	182	ZV_ZM_mul	183
ZV_isscalar	190	ZV_zMs_mul	194
ZV_lcm	101	ZV_ZV_mod	182
ZV_lval	91	zvV_equal	187
ZV_lvalrem	91	ZX_add	195
ZV_max_expi	182	ZX_affine	197
ZV_max_lg	182	ZX_composedsum	198
zv_neg	186	ZX_compositum	198
ZV_neg_inplace	181	ZX_content	196
zv_neg_inplace	186	ZX_copy	195
ZV_nv_mod_tree	162	ZX_deflate_max	196
ZV_prod	182	ZX_deflate_order	196
zv_prod	186	ZX_deriv	197
zv_prod_Z	186	ZX_digits	196
ZV_producttree	161, 163	ZX_disc	197
ZV_pval	91	ZX_div_by_X_1	196
ZV_pvalrem	91	ZX_divuexact	195
ZV_search	182	ZX_equal	195, 198
zv_search	186	ZX_equal1	195
ZV_snf_gcd	101, 331	ZX_eval1	197
ZV_snf_group	331	ZX_factor	197
ZV_snf_rank	332	ZX_gcd	196

ZX_gcd_all	196	ZX_unscale2n	197
ZX_graeffe	197	ZX_unscale_div	197
ZX_incremental_CRT	161	ZX_unscale_divpow	197
ZX_init_CRT	161	ZX_Uspensky	197
ZX_is_irred	197	ZX_val	196
ZX_is_monic	195	ZX_valrem	196
ZX_is_squarefree	197	ZX_Z_add	195
ZX_lval	92	ZX_Z_add_shallow	195
zx_lval	202	ZX_Z_divexact	195
ZX_lvalrem	91	zx_z_divexact	202
ZX_max_lg	195	ZX_Z_eval	197
ZX_mod_Xnm1	196	ZX_Z_mul	195
ZX_mul	195, 200	ZX_Z_normalize	196
ZX_mulspec	195	ZX_Z_sub	195
ZX_mulu	195	ZX_z_unscale	197
ZX_neg	195	ZX_Zp_root	165
ZX_nv_mod_tree	162	ZX_ZXY_resultant	198
ZX_primitive_to_monic	196	ZX_ZXY_rnfequation	198
ZX_pval	91	ZXC_nv_mod_tree	162
ZX_pvalrem	91	ZXC_to_FlxC	170
ZX_Q_mul	196	ZXM_incremental_CRT	161
ZX_Q_normalize	196, 313	ZXM_init_CRT	161
ZX_radical	196	ZXM_nv_mod_tree	162
ZX_realroots_irred	198	ZXM_to_FlxM	171
ZX_rem	196	ZXn_mul	199
ZX_remi2n	195	ZXn_sqr	199
ZX_renormalize	195	ZXQ_charpoly	199
zx_renormalize	202	ZXQ_minpoly	199
ZX_rescale	196	ZXQ_mul	198
ZX_rescale2n	197	ZXQ_powers	199
ZX_rescale_lt	197	ZXQ_powu	199
ZX_resultant	197	ZXQ_sqr	198
zx_shift	202	ZXQM_mul	199
ZX_shifti	195	ZXQM_sqr	199
ZX_sqr	195, 200	ZXQX_dvd	206
ZX_sqrspec	195	ZXQX_gcd	199
ZX_squff	197	ZXQX_mul	199
ZX_sturm	198	ZXQX_sqr	199
ZX_sturm_irred	198	ZXQX_ZXQ_mul	199
ZX_sturmpart	198	ZXT_remi2n	198
ZX_sub	195	ZXT_to_FlxT	170
ZX_to_F2x	153	ZXV_dotproduct	198
ZX_to_Flx	170	ZXV_equal	198
zx_to_Flx	171	ZXV_pvalrem	92
ZX_to_monic	196	ZXV_remi2n	198
zx_to_zv	172	ZXV_to_FlxV	170
zx_to_ZX	171	ZXV_Z_mul	198
ZX_translate	197	ZXV_ZX_fromdigits	196
ZX_unscale	197	ZXX_evalx0	200

ZXX_max_lg	200
ZXX_mul_Kronecker	200
ZXX_nv_mod_tree	162
ZXX_pvalrem	91
ZXX_Q_mul	200
ZXX_renormalize	199
ZXX_sqr_Kronecker	200
ZXX_to_F2xX	156
ZXX_to_FlxX	170
zxX_to_FlxX	170
zxX_to_Kronecker	149
ZXX_Z_add_shallow	200
ZXX_Z_divexact	200
ZXX_Z_mul	200
ZXXT_to_FlxXT	170
ZXXV_to_FlxXV	170